



Entity Reference

/Amster 6

Latest update: 6.0.0

ForgeRock AS
201 Mission St., Suite 2900
San Francisco, CA 94105, USA
+1 415-599-1100 (US)
www.forgerock.com

Copyright © 2017-2018 ForgeRock AS.

Abstract

Reference of the ForgeRock® Access Management command-line interface entities.



This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License.

To view a copy of this license, visit <https://creativecommons.org/licenses/by-nc-nd/3.0/> or send a letter to Creative Commons, 444 Castro Street, Suite 900, Mountain View, California, 94041, USA.

ForgeRock® and ForgeRock Identity Platform™ are trademarks of ForgeRock Inc. or its subsidiaries in the U.S. and in other countries. Trademarks are the property of their respective owners.

UNLESS OTHERWISE MUTUALLY AGREED BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

DejaVu Fonts

Bitstream Vera Fonts Copyright

Copyright (c) 2003 by Bitstream, Inc. All Rights Reserved. Bitstream Vera is a trademark of Bitstream, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Bitstream" or the word "Vera".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Bitstream Vera" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL BITSTREAM OR THE GNOME FOUNDATION BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the names of Gnome, the Gnome Foundation, and Bitstream Inc., shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from the Gnome Foundation or Bitstream Inc., respectively. For further information, contact: fonts at gnome dot org.

Arev Fonts Copyright

Copyright (c) 2006 by Tavmjong Bah. All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the modifications to the Bitstream Vera Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Tavmjong Bah" or the word "Arev".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Tavmjong Bah Arev" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL TAVMJONG BAH BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the name of Tavmjong Bah shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from Tavmjong Bah. For further information, contact: tavmjong @ free . fr.

FontAwesome Copyright

Copyright (c) 2017 by Dave Gandy, <http://fontawesome.io>.

This Font Software is licensed under the SIL Open Font License, Version 1.1. See <https://opensource.org/licenses/OFL-1.1>.

Table of Contents

Preface	viii
1. Amster Entity Reference	1
1.1. AccountLockout	1
1.2. ActiveDirectory	4
1.3. ActiveDirectoryApplicationModeADAM	21
1.4. ActiveDirectoryModule	38
1.5. AdaptiveRiskModule	52
1.6. AdvancedProperties	82
1.7. AgentGroups	83
1.8. AgentService	84
1.9. Agents	85
1.10. AmsterModule	86
1.11. AnonymousModule	91
1.12. AnonymousUserMapping	97
1.13. ApplicationTypes	100
1.14. Applications	101
1.15. AuditEvent	107
1.16. AuditLogging	118
1.17. AuthLevelDecision	123
1.18. AuthTree	126
1.19. Authentication	133
1.20. AuthenticationChains	161
1.21. AuthenticationModules	167
1.22. AuthenticationNodes	169
1.23. AuthenticationTreesConfiguration	169
1.24. AuthenticatorOath	171
1.25. AuthenticatorOathModule	178
1.26. AuthenticatorPush	188
1.27. AuthenticatorPushModule	195
1.28. AuthenticatorPushRegistrationModule	200
1.29. BaseUrlSource	207
1.30. CRESTReporter	212
1.31. CertificateModule	215
1.32. ChoiceCollector	231
1.33. CircleOfTrust	235
1.34. CommonFederationConfiguration	238
1.35. ConditionTypes	243
1.36. CreatePassword	244
1.37. Csv	247
1.38. CtsDataStoreProperties	267
1.39. Dashboard	270
1.40. DashboardInstance	274
1.41. DashboardUserService	278
1.42. Dashboards	281

1.43. DataStoreDecision	282
1.44. DataStoreModule	284
1.45. DecisionCombiners	288
1.46. DefaultAdvancedProperties	289
1.47. DefaultCtsDataStoreProperties	290
1.48. DefaultDirectoryConfiguration	292
1.49. DefaultGeneralProperties	294
1.50. DefaultSdkProperties	297
1.51. DefaultSecurityProperties	300
1.52. DefaultSessionProperties	305
1.53. DefaultUmaDataStoreProperties	307
1.54. DeviceIDService	313
1.55. DeviceIdMatchModule	320
1.56. DeviceIdSaveModule	325
1.57. DirectoryConfiguration	330
1.58. ElasticSearch	332
1.59. EmailService	347
1.60. FailureURL	354
1.61. FederationModule	357
1.62. ForgottenPassword	361
1.63. ForgottenUsername	363
1.64. GeneralProperties	364
1.65. GenericLDAPv3	368
1.66. GetSessionData	386
1.67. GlobalScripts	389
1.68. Globalization	394
1.69. GraphiteReporter	398
1.70. HOTPGenerator	401
1.71. HotpModule	404
1.72. HttpBasicModule	415
1.73. IDMProvisioning	420
1.74. IdRepository	425
1.75. IdRepositoryUser	430
1.76. IdffEntity	436
1.77. InnerTreeEvaluator	439
1.78. J2EEAgentGroups	442
1.79. J2eeAgents	503
1.80. Jdbc	609
1.81. JdbcModule	626
1.82. Jms	635
1.83. Json	651
1.84. JwtProofOfPossessionModule	669
1.85. KbaQuestions	675
1.86. LDAPDecision	676
1.87. LdapModule	685
1.88. LegacyUserSelfService	700
1.89. Logging	707

1.90. MembershipModule	714
1.91. Meter	720
1.92. ModifyAuthLevel	723
1.93. Monitoring	726
1.94. MsisdnModule	728
1.95. MultiFederationProtocol	739
1.96. Naming	740
1.97. OAuth20	744
1.98. OAuth2ClientAgentGroups	753
1.99. OAuth2Clients	774
1.100. OAuth2Module	810
1.101. OAuth2Provider	831
1.102. OAuth2RemoteConsentAgentGroups	880
1.103. OAuth2SoftwarePublisherAgentGroups	886
1.104. OAuth2UserApplications	891
1.105. OTPCollectorDecision	892
1.106. OTPEmailSender	895
1.107. OTPSMSSender	900
1.108. OathModule	905
1.109. OathUserDevices	917
1.110. OpenDJ	919
1.111. OpenIdConnectModule	938
1.112. PageNode	947
1.113. PasswordCollector	951
1.114. PendingUmaRequests	953
1.115. PersistentCookieDecision	956
1.116. PersistentCookieModule	960
1.117. Platform	967
1.118. Policies	969
1.119. PolicyAgents	979
1.120. PolicyConfiguration	984
1.121. PollingWaitNode	995
1.122. PrometheusReporter	1000
1.123. ProvisionDynamicAccount	1003
1.124. ProvisionIDMAccount	1006
1.125. PushNotification	1009
1.126. PushNotificationResponse	1017
1.127. PushResultVerifierNode	1018
1.128. PushSender	1021
1.129. PushUserDevices	1025
1.130. RESTSecurityTokenServices	1027
1.131. RadiusClient	1050
1.132. RadiusModule	1054
1.133. RadiusServer	1062
1.134. Realms	1064
1.135. Records	1067
1.136. RecoveryCodeCollectorDecision	1070

1.137. RegisterLogoutWebhook	1073
1.138. RemoteConsentAgent	1076
1.139. RemoteConsentService	1087
1.140. RemoveSessionProperties	1093
1.141. ResourceSets	1096
1.142. ResourceTypes	1099
1.143. RestApis	1103
1.144. RetryLimitDecision	1105
1.145. SOAPSecurityTokenServices	1108
1.146. SaeModule	1132
1.147. Saml2Entity	1136
1.148. Saml2Module	1139
1.149. SamlV2ServiceConfiguration	1150
1.150. SamlV2SoapBinding	1156
1.151. ScriptStore	1157
1.152. ScriptTypes	1162
1.153. ScriptedDecision	1164
1.154. ScriptedModule	1168
1.155. Scripting	1173
1.156. ScriptingEngineConfiguration	1174
1.157. Scripts	1179
1.158. SdkProperties	1184
1.159. SecurID	1190
1.160. SecurityProperties	1194
1.161. SecurityTokenServices	1203
1.162. ServerInformation	1203
1.163. ServerVersion	1204
1.164. Servers	1204
1.165. Services	1207
1.166. Session	1209
1.167. SessionProperties	1219
1.168. SessionPropertyWhiteList	1223
1.169. SessionUserService	1227
1.170. Sessions	1231
1.171. SetPersistentCookie	1235
1.172. SetSessionProperties	1240
1.173. SharedAgents	1243
1.174. Sites	1248
1.175. SoapSTSAgentGroups	1251
1.176. SoapStsAgents	1254
1.177. SocialAuthInstagramModule	1258
1.178. SocialAuthOAuth2Module	1276
1.179. SocialAuthOpenIDModule	1300
1.180. SocialAuthTwitterModule	1326
1.181. SocialAuthVKontakteModule	1343
1.182. SocialAuthWeChatMobileModule	1364
1.183. SocialAuthWeChatModule	1383

1.184. SocialAuthentication	1404
1.185. SocialFacebook	1410
1.186. SocialGoogle	1419
1.187. SocialIgnoreProfile	1428
1.188. SoftwarePublisher	1431
1.189. Splunk	1438
1.190. SubjectAttributes	1450
1.191. SubjectTypes	1451
1.192. SuccessURL	1452
1.193. SunDSWithOpenAMSchema	1454
1.194. SupportedIds	1476
1.195. Syslog	1478
1.196. TimerStart	1490
1.197. TimerStop	1493
1.198. TivoliDirectoryServer	1496
1.199. TransactionAuthentication	1514
1.200. TrustedUserDevices	1518
1.201. UmaDataStoreProperties	1519
1.202. UmaPolicies	1530
1.203. UmaProvider	1533
1.204. UmaResourceSetLabels	1541
1.205. UmaUserAuditHistory	1543
1.206. User	1544
1.207. UserGroups	1548
1.208. UserPolicies	1549
1.209. UserRegistration	1556
1.210. UserSelfService	1557
1.211. UserServices	1583
1.212. UsernameCollector	1585
1.213. ValidationService	1588
1.214. WebAgentGroups	1592
1.215. WebAgents	1631
1.216. WebhookService	1701
1.217. WindowsDesktopSsoModule	1706
1.218. WindowsNtModule	1713
1.219. WsEntity	1719
1.220. ZeroPageLoginCollector	1721
A. Getting Support	1726
A.1. Accessing Documentation Online	1726
A.2. Using the ForgeRock.org Site	1726
A.3. Getting Support and Contacting ForgeRock	1727

Preface

This reference contains:

- Entities supported in Amster commands
- Actions you can perform with Amster commands.

This guide is written for anyone using Amster to configure and manage ForgeRock Access Management deployments.

About ForgeRock Identity Platform™ Software

ForgeRock Identity Platform™ serves as the basis for our simple and comprehensive Identity and Access Management solution. We help our customers deepen their relationships with their customers, and improve the productivity and connectivity of their employees and partners. For more information about ForgeRock and about the platform, see <https://www.forgerock.com>.

Chapter 1

Amster Entity Reference

This chapter contains details of the entities available to Amster in AM 6.

1.1. AccountLockout

1.1.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/AccountLockoutNode`

Resource version: `1.0`

1.1.1.1. create

Usage:

```
am> create AccountLockout --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "lockAction" : {
      "title" : "Lock Action",
      "description" : "If the action is set to LOCK, the node will lock the account.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "lockAction" ]
}
```

1.1.1.2. delete

Usage:

```
am> delete AccountLockout --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.1.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AccountLockout --realm Realm --actionName getAllTypes
```

1.1.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AccountLockout --realm Realm --actionName getCreatableTypes
```

1.1.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action AccountLockout --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.1.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AccountLockout --realm Realm --actionName nextdescendents
```

1.1.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query AccountLockout --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.1.1.8. read

Usage:

```
am> read AccountLockout --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.1.1.9. update

Usage:

```
am> update AccountLockout --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "lockAction" : {
      "title" : "Lock Action",
      "description" : "If the action is set to LOCK, the node will lock the account.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "lockAction" ]
}
```

1.2. ActiveDirectory

1.2.1. Realm Operations

Resource path: `/realm-config/services/id-repositories/LDAPv3ForAD`

Resource version: `1.0`

1.2.1.1. create

Usage:

```
am> create ActiveDirectory --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userconfig" : {
      "type" : "object",
      "title" : "User Configuration",
      "propertyOrder" : 3,
      "properties" : {
        "sun-idrepo-ldapv3-config-users-search-filter" : {
          "title" : "LDAP Users Search Filter",
          "description" : "",
          "propertyOrder" : 2200,
          "required" : false,

```



```
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-people-container-value" : {
  "title" : "LDAP People Container Value",
  "description" : "",
  "propertyOrder" : 5100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-attempts-attr" : {
  "title" : "Knowledge Based Authentication Attempts Attribute Name",
  "description" : "",
  "propertyOrder" : 5410,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-users-search-attribute" : {
  "title" : "LDAP Users Search Attribute",
  "description" : "",
  "propertyOrder" : 2100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-people-container-name" : {
  "title" : "LDAP People Container Naming Attribute",
  "description" : "",
  "propertyOrder" : 5000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-user-attributes" : {
  "title" : "LDAP User Attributes",
  "description" : "",
  "propertyOrder" : 2400,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-index-attr" : {
  "title" : "Knowledge Based Authentication Active Index",
  "description" : "",
  "propertyOrder" : 5400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-attr" : {
  "title" : "Knowledge Based Authentication Attribute Name",
```

```
"description" : "",
"propertyOrder" : 5300,
"required" : false,
"items" : {
  "type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-inactive" : {
  "title" : "User Status Inactive Value",
  "description" : "",
  "propertyOrder" : 2800,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-user-objectclass" : {
  "title" : "LDAP User Object Class",
  "description" : "",
  "propertyOrder" : 2300,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-active" : {
  "title" : "User Status Active Value",
  "description" : "",
  "propertyOrder" : 2700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-isactive" : {
  "title" : "Attribute Name of User Status",
  "description" : "",
  "propertyOrder" : 2600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
  "title" : "Create User Attribute Mapping",
  "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
  "propertyOrder" : 2500,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
}
},
"groupconfig" : {
  "type" : "object",
```

```
"title" : "Group Configuration",
"propertyOrder" : 5,
"properties" : {
  "sun-idrepo-ldapv3-config-groups-search-filter" : {
    "title" : "LDAP Groups Search Filter",
    "description" : "",
    "propertyOrder" : 3000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-container-value" : {
    "title" : "LDAP Groups Container Value",
    "description" : "",
    "propertyOrder" : 3200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-groups-search-attribute" : {
    "title" : "LDAP Groups Search Attribute",
    "description" : "",
    "propertyOrder" : 2900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-memberof" : {
    "title" : "Attribute Name for Group Membership",
    "description" : "",
    "propertyOrder" : 3500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-attributes" : {
    "title" : "LDAP Groups Attributes",
    "description" : "",
    "propertyOrder" : 3400,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-container-name" : {
    "title" : "LDAP Groups Container Naming Attribute",
    "description" : "",
    "propertyOrder" : 3100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-objectclass" : {
    "title" : "LDAP Groups Object Class",
    "description" : "",
    "propertyOrder" : 3300,
    "required" : false,
```

```

    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-uniquemember" : {
    "title" : "Attribute Name of Unique Member",
    "description" : "",
    "propertyOrder" : 3600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"ldapsettings" : {
  "type" : "object",
  "title" : "Server Settings",
  "propertyOrder" : 0,
  "properties" : {
    "openam-idrepo-ldapv3-heartbeat-interval" : {
      "title" : "LDAP Connection Heartbeat Interval",
      "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
error) then it may take up to the interval period before the problem is detected. Use along with the
Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
disabling heartbeat requests.",
      "propertyOrder" : 1300,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-connection-mode" : {
      "title" : "LDAP Connection Mode",
      "description" : "Defines which protocol/operation is used to establish the connection to
the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
      "propertyOrder" : 1000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-timeunit" : {
      "title" : "LDAP Connection Heartbeat Time Unit",
      "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
it may take up to the interval period before the problem is detected. Use along with the Heartbeat
Interval parameter to define the exact interval.",
      "propertyOrder" : 1400,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "sun-idrepo-ldapv3-config-authid" : {

```

```

    "title" : "LDAP Bind DN",
    "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
    "propertyOrder" : 700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-max-result" : {
    "title" : "Maximum Results Returned from Search",
    "description" : "",
    "propertyOrder" : 1500,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-organization_name" : {
    "title" : "LDAP Organization DN",
    "description" : "",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-search-scope" : {
    "title" : "LDAPv3 Plug-in Search Scope",
    "description" : "",
    "propertyOrder" : 2000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-time-limit" : {
    "title" : "Search Timeout",
    "description" : "In seconds.",
    "propertyOrder" : 1600,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-ldap-server" : {
    "title" : "LDAP Server",
    "description" : "Format: LDAP server host name:port | server_ID | site_ID",
    "propertyOrder" : 600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-authpw" : {
    "title" : "LDAP Bind Password",
    "description" : "",
    "propertyOrder" : 800,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }

```

```

    },
    "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
      "title" : "LDAP Connection Pool Maximum Size",
      "description" : "",
      "propertyOrder" : 1200,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
},
"pluginconfig" : {
  "type" : "object",
  "title" : "Plug-in Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "sunIdRepoSupportedOperations" : {
      "title" : "LDAPv3 Plug-in Supported Types and Operations",
      "description" : "",
      "propertyOrder" : 1900,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sunIdRepoAttributeMapping" : {
      "title" : "Attribute Name Mapping",
      "description" : "",
      "propertyOrder" : 1800,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sunIdRepoClass" : {
      "title" : "LDAPv3 Repository Plug-in Class Name",
      "description" : "",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"persistentsearch" : {
  "type" : "object",
  "title" : "Persistent Search Controls",
  "propertyOrder" : 7,
  "properties" : {
    "sun-idrepo-ldapv3-config-psearch-scope" : {
      "title" : "Persistent Search Scope",
      "description" : "",
      "propertyOrder" : 5700,
      "required" : false,
      "type" : "string",

```

```

    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-psearchbase" : {
    "title" : "Persistent Search Base DN",
    "description" : "",
    "propertyOrder" : 5500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
},
"cachecontrol" : {
  "type" : "object",
  "title" : "Cache Control",
  "propertyOrder" : 9,
  "properties" : {
    "sun-idrepo-ldapv3-dncache-enabled" : {
      "title" : "DN Cache",
      "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
      "propertyOrder" : 5900,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-dncache-size" : {
      "title" : "DN Cache Size",
      "description" : "In DN items, only used when DN Cache is enabled.",
      "propertyOrder" : 6000,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
},
"authentication" : {
  "type" : "object",
  "title" : "Authentication Configuration",
  "propertyOrder" : 4,
  "properties" : {
    "sun-idrepo-ldapv3-config-auth-naming-attr" : {
      "title" : "Authentication Naming Attribute",
      "description" : "",
      "propertyOrder" : 5200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"errorhandling" : {
  "type" : "object",
  "title" : "Error Handling Configuration",
  "propertyOrder" : 8,
  "properties" : {

```

```
"com.ipplanet.am.ldap.connection.delay.between.retries" : {  
  "title" : "The Delay Time Between Retries",  
  "description" : "In milliseconds.",  
  "propertyOrder" : 5800,  
  "required" : false,  
  "type" : "integer",  
  "exampleValue" : ""  
}  
}  
}  
}
```

1.2.1.2. delete

Usage:

```
am> delete ActiveDirectory --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.2.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ActiveDirectory --realm Realm --actionName getAllTypes
```

1.2.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ActiveDirectory --realm Realm --actionName getCreatableTypes
```

1.2.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ActiveDirectory --realm Realm --actionName nextdescendents
```


1.2.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ActiveDirectory --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.2.1.7. read

Usage:

```
am> read ActiveDirectory --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.2.1.8. update

Usage:

```
am> update ActiveDirectory --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userconfig" : {
      "type" : "object",
      "title" : "User Configuration",
      "propertyOrder" : 3,
      "properties" : {
        "sun-idrepo-ldapv3-config-users-search-filter" : {
          "title" : "LDAP Users Search Filter",
          "description" : "",
          "propertyOrder" : 2200,

```

```
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-people-container-value" : {
"title" : "LDAP People Container Value",
"description" : "",
"propertyOrder" : 5100,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-attempts-attr" : {
"title" : "Knowledge Based Authentication Attempts Attribute Name",
"description" : "",
"propertyOrder" : 5410,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-users-search-attribute" : {
"title" : "LDAP Users Search Attribute",
"description" : "",
"propertyOrder" : 2100,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-people-container-name" : {
"title" : "LDAP People Container Naming Attribute",
"description" : "",
"propertyOrder" : 5000,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-user-attributes" : {
"title" : "LDAP User Attributes",
"description" : "",
"propertyOrder" : 2400,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-index-attr" : {
"title" : "Knowledge Based Authentication Active Index",
"description" : "",
"propertyOrder" : 5400,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-attr" : {
```

```

        "title" : "Knowledge Based Authentication Attribute Name",
        "description" : "",
        "propertyOrder" : 5300,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-inactive" : {
        "title" : "User Status Inactive Value",
        "description" : "",
        "propertyOrder" : 2800,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-user-objectclass" : {
        "title" : "LDAP User Object Class",
        "description" : "",
        "propertyOrder" : 2300,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-active" : {
        "title" : "User Status Active Value",
        "description" : "",
        "propertyOrder" : 2700,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-isactive" : {
        "title" : "Attribute Name of User Status",
        "description" : "",
        "propertyOrder" : 2600,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
        "title" : "Create User Attribute Mapping",
        "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
        "propertyOrder" : 2500,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"groupconfig" : {

```

```
"type" : "object",
"title" : "Group Configuration",
"propertyOrder" : 5,
"properties" : {
  "sun-idrepo-ldapv3-config-groups-search-filter" : {
    "title" : "LDAP Groups Search Filter",
    "description" : "",
    "propertyOrder" : 3000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-container-value" : {
    "title" : "LDAP Groups Container Value",
    "description" : "",
    "propertyOrder" : 3200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-groups-search-attribute" : {
    "title" : "LDAP Groups Search Attribute",
    "description" : "",
    "propertyOrder" : 2900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-memberof" : {
    "title" : "Attribute Name for Group Membership",
    "description" : "",
    "propertyOrder" : 3500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-attributes" : {
    "title" : "LDAP Groups Attributes",
    "description" : "",
    "propertyOrder" : 3400,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-container-name" : {
    "title" : "LDAP Groups Container Naming Attribute",
    "description" : "",
    "propertyOrder" : 3100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-objectclass" : {
    "title" : "LDAP Groups Object Class",
    "description" : "",
    "propertyOrder" : 3300,
```

```

    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-uniquemember" : {
    "title" : "Attribute Name of Unique Member",
    "description" : "",
    "propertyOrder" : 3600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
},
"ldapsettings" : {
  "type" : "object",
  "title" : "Server Settings",
  "propertyOrder" : 0,
  "properties" : {
    "openam-idrepo-ldapv3-heartbeat-interval" : {
      "title" : "LDAP Connection Heartbeat Interval",
      "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
error) then it may take up to the interval period before the problem is detected. Use along with the
Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
disabling heartbeat requests.",
      "propertyOrder" : 1300,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-connection-mode" : {
      "title" : "LDAP Connection Mode",
      "description" : "Defines which protocol/operation is used to establish the connection to
the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
      "propertyOrder" : 1000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-timeunit" : {
      "title" : "LDAP Connection Heartbeat Time Unit",
      "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
it may take up to the interval period before the problem is detected. Use along with the Heartbeat
Interval parameter to define the exact interval.",
      "propertyOrder" : 1400,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},

```

```
"sun-idrepo-ldapv3-config-authid" : {
  "title" : "LDAP Bind DN",
  "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
  "propertyOrder" : 700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-max-result" : {
  "title" : "Maximum Results Returned from Search",
  "description" : "",
  "propertyOrder" : 1500,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-organization_name" : {
  "title" : "LDAP Organization DN",
  "description" : "",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-search-scope" : {
  "title" : "LDAPv3 Plug-in Search Scope",
  "description" : "",
  "propertyOrder" : 2000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-time-limit" : {
  "title" : "Search Timeout",
  "description" : "In seconds.",
  "propertyOrder" : 1600,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-ldap-server" : {
  "title" : "LDAP Server",
  "description" : "Format: LDAP server host name:port | server_ID | site_ID",
  "propertyOrder" : 600,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-authpw" : {
  "title" : "LDAP Bind Password",
  "description" : "",
  "propertyOrder" : 800,
  "required" : false,
  "type" : "string",
  "format" : "password",
```

```

    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
    "title" : "LDAP Connection Pool Maximum Size",
    "description" : "",
    "propertyOrder" : 1200,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"pluginconfig" : {
  "type" : "object",
  "title" : "Plug-in Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "sunIdRepoSupportedOperations" : {
      "title" : "LDAPv3 Plug-in Supported Types and Operations",
      "description" : "",
      "propertyOrder" : 1900,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sunIdRepoAttributeMapping" : {
      "title" : "Attribute Name Mapping",
      "description" : "",
      "propertyOrder" : 1800,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sunIdRepoClass" : {
      "title" : "LDAPv3 Repository Plug-in Class Name",
      "description" : "",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"persistentsearch" : {
  "type" : "object",
  "title" : "Persistent Search Controls",
  "propertyOrder" : 7,
  "properties" : {
    "sun-idrepo-ldapv3-config-psearch-scope" : {
      "title" : "Persistent Search Scope",
      "description" : "",
      "propertyOrder" : 5700,
      "required" : false,

```

```

        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-psearchbase" : {
        "title" : "Persistent Search Base DN",
        "description" : "",
        "propertyOrder" : 5500,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"cachecontrol" : {
    "type" : "object",
    "title" : "Cache Control",
    "propertyOrder" : 9,
    "properties" : {
        "sun-idrepo-ldapv3-dncache-enabled" : {
            "title" : "DN Cache",
            "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
            "propertyOrder" : 5900,
            "required" : false,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-dncache-size" : {
            "title" : "DN Cache Size",
            "description" : "In DN items, only used when DN Cache is enabled.",
            "propertyOrder" : 6000,
            "required" : false,
            "type" : "integer",
            "exampleValue" : ""
        }
    }
}
},
"authentication" : {
    "type" : "object",
    "title" : "Authentication Configuration",
    "propertyOrder" : 4,
    "properties" : {
        "sun-idrepo-ldapv3-config-auth-naming-attr" : {
            "title" : "Authentication Naming Attribute",
            "description" : "",
            "propertyOrder" : 5200,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}
},
"errorhandling" : {
    "type" : "object",
    "title" : "Error Handling Configuration",
    "propertyOrder" : 8,

```



```
    "properties" : {
      "com.ipianet.am.ldap.connection.delay.between.retries" : {
        "title" : "The Delay Time Between Retries",
        "description" : "In milliseconds.",
        "propertyOrder" : 5800,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
      }
    }
  }
}
```

1.3. ActiveDirectoryApplicationModeADAM

1.3.1. Realm Operations

Resource path: `/realm-config/services/id-repositories/LDAPv3ForADAM`

Resource version: `1.0`

1.3.1.1. create

Usage:

```
am> create ActiveDirectoryApplicationModeADAM --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "errorhandling" : {
      "type" : "object",
      "title" : "Error Handling Configuration",
      "propertyOrder" : 8,
      "properties" : {
        "com.ipianet.am.ldap.connection.delay.between.retries" : {
          "title" : "The Delay Time Between Retries",
          "description" : "In milliseconds.",
          "propertyOrder" : 5800,
          "required" : false,

```

```

    "type" : "integer",
    "exampleValue" : ""
  }
}
},
"ldapsettings" : {
  "type" : "object",
  "title" : "Server Settings",
  "propertyOrder" : 0,
  "properties" : {
    "sun-idrepo-ldapv3-config-search-scope" : {
      "title" : "LDAPv3 Plug-in Search Scope",
      "description" : "",
      "propertyOrder" : 2000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-interval" : {
      "title" : "LDAP Connection Heartbeat Interval",
      "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
error) then it may take up to the interval period before the problem is detected. Use along with the
Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
disabling heartbeat requests.",
      "propertyOrder" : 1300,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
      "title" : "LDAP Connection Pool Maximum Size",
      "description" : "",
      "propertyOrder" : 1200,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-authid" : {
      "title" : "LDAP Bind DN",
      "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
      "propertyOrder" : 700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-max-result" : {
      "title" : "Maximum Results Returned from Search",
      "description" : "",
      "propertyOrder" : 1500,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-timeunit" : {
      "title" : "LDAP Connection Heartbeat Time Unit",

```

```

    "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
it may take up to the interval period before the problem is detected. Use along with the Heartbeat
Interval parameter to define the exact interval.",
    "propertyOrder" : 1400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-organization_name" : {
    "title" : "LDAP Organization DN",
    "description" : "",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-ldap-server" : {
    "title" : "LDAP Server",
    "description" : "Format: LDAP server host name:port | server_ID | site_ID",
    "propertyOrder" : 600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-time-limit" : {
    "title" : "Search Timeout",
    "description" : "In seconds.",
    "propertyOrder" : 1600,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-authpw" : {
    "title" : "LDAP Bind Password",
    "description" : "",
    "propertyOrder" : 800,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection-mode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Defines which protocol/operation is used to establish the connection to
the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
    "propertyOrder" : 1000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}

```

```
},
"userconfig" : {
  "type" : "object",
  "title" : "User Configuration",
  "propertyOrder" : 3,
  "properties" : {
    "sun-idrepo-ldapv3-config-people-container-value" : {
      "title" : "LDAP People Container Value",
      "description" : "",
      "propertyOrder" : 5100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-isactive" : {
      "title" : "Attribute Name of User Status",
      "description" : "",
      "propertyOrder" : 2600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-users-search-attribute" : {
      "title" : "LDAP Users Search Attribute",
      "description" : "",
      "propertyOrder" : 2100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-user-objectclass" : {
      "title" : "LDAP User Object Class",
      "description" : "",
      "propertyOrder" : 2300,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-user-attributes" : {
      "title" : "LDAP User Attributes",
      "description" : "",
      "propertyOrder" : 2400,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-people-container-name" : {
      "title" : "LDAP People Container Naming Attribute",
      "description" : "",
      "propertyOrder" : 5000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```

    },
    "sun-idrepo-ldapv3-config-auth-kba-attr" : {
      "title" : "Knowledge Based Authentication Attribute Name",
      "description" : "",
      "propertyOrder" : 5300,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
      "title" : "Create User Attribute Mapping",
      "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
      "propertyOrder" : 2500,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-auth-kba-attempts-attr" : {
      "title" : "Knowledge Based Authentication Attempts Attribute Name",
      "description" : "",
      "propertyOrder" : 5410,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-inactive" : {
      "title" : "User Status Inactive Value",
      "description" : "",
      "propertyOrder" : 2800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-users-search-filter" : {
      "title" : "LDAP Users Search Filter",
      "description" : "",
      "propertyOrder" : 2200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-auth-kba-index-attr" : {
      "title" : "Knowledge Based Authentication Active Index",
      "description" : "",
      "propertyOrder" : 5400,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-active" : {

```

```

    "title" : "User Status Active Value",
    "description" : "",
    "propertyOrder" : 2700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
},
"cachecontrol" : {
  "type" : "object",
  "title" : "Cache Control",
  "propertyOrder" : 9,
  "properties" : {
    "sun-idrepo-ldapv3-dncache-size" : {
      "title" : "DN Cache Size",
      "description" : "In DN items, only used when DN Cache is enabled.",
      "propertyOrder" : 6000,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-dncache-enabled" : {
      "title" : "DN Cache",
      "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
      "propertyOrder" : 5900,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
},
"groupconfig" : {
  "type" : "object",
  "title" : "Group Configuration",
  "propertyOrder" : 5,
  "properties" : {
    "sun-idrepo-ldapv3-config-groups-search-attribute" : {
      "title" : "LDAP Groups Search Attribute",
      "description" : "",
      "propertyOrder" : 2900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-objectclass" : {
      "title" : "LDAP Groups Object Class",
      "description" : "",
      "propertyOrder" : 3300,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}

```

```
},
"sun-idrepo-ldapv3-config-memberof" : {
  "title" : "Attribute Name for Group Membership",
  "description" : "",
  "propertyOrder" : 3500,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-container-value" : {
  "title" : "LDAP Groups Container Value",
  "description" : "",
  "propertyOrder" : 3200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-container-name" : {
  "title" : "LDAP Groups Container Naming Attribute",
  "description" : "",
  "propertyOrder" : 3100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-attributes" : {
  "title" : "LDAP Groups Attributes",
  "description" : "",
  "propertyOrder" : 3400,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-unique-member" : {
  "title" : "Attribute Name of Unique Member",
  "description" : "",
  "propertyOrder" : 3600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-groups-search-filter" : {
  "title" : "LDAP Groups Search Filter",
  "description" : "",
  "propertyOrder" : 3000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"authentication" : {
  "type" : "object",
  "title" : "Authentication Configuration",
  "propertyOrder" : 4,
  "properties" : {
```

```
"sun-idrepo-ldapv3-config-auth-naming-attr" : {
  "title" : "Authentication Naming Attribute",
  "description" : "",
  "propertyOrder" : 5200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
},
"persistentsearch" : {
  "type" : "object",
  "title" : "Persistent Search Controls",
  "propertyOrder" : 7,
  "properties" : {
    "sun-idrepo-ldapv3-config-psearchbase" : {
      "title" : "Persistent Search Base DN",
      "description" : "",
      "propertyOrder" : 5500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-psearch-scope" : {
      "title" : "Persistent Search Scope",
      "description" : "",
      "propertyOrder" : 5700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"pluginconfig" : {
  "type" : "object",
  "title" : "Plug-in Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "sunIdRepoAttributeMapping" : {
      "title" : "Attribute Name Mapping",
      "description" : "",
      "propertyOrder" : 1800,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sunIdRepoSupportedOperations" : {
      "title" : "LDAPv3 Plug-in Supported Types and Operations",
      "description" : "",
      "propertyOrder" : 1900,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```



```
    },  
    "sunIdRepoClass" : {  
      "title" : "LDAPv3 Repository Plug-in Class Name",  
      "description" : "",  
      "propertyOrder" : 1700,  
      "required" : true,  
      "type" : "string",  
      "exampleValue" : ""  
    }  
  }  
}  
}
```

1.3.1.2. delete

Usage:

```
am> delete ActiveDirectoryApplicationModeADAM --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.3.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ActiveDirectoryApplicationModeADAM --realm Realm --actionName getAllTypes
```

1.3.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ActiveDirectoryApplicationModeADAM --realm Realm --actionName getCreatableTypes
```

1.3.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ActiveDirectoryApplicationModeADAM --realm Realm --actionName nextdescendents
```

1.3.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ActiveDirectoryApplicationModeADAM --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.3.1.7. read

Usage:

```
am> read ActiveDirectoryApplicationModeADAM --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.3.1.8. update

Usage:

```
am> update ActiveDirectoryApplicationModeADAM --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "errorhandling" : {
      "type" : "object",
      "title" : "Error Handling Configuration",
      "propertyOrder" : 8,
      "properties" : {
        "com.iplanet.am.ldap.connection.delay.between.retries" : {
          "title" : "The Delay Time Between Retries",
          "description" : "In milliseconds.",
          "propertyOrder" : 5800,

```

```

    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"ldapsettings" : {
  "type" : "object",
  "title" : "Server Settings",
  "propertyOrder" : 0,
  "properties" : {
    "sun-idrepo-ldapv3-config-search-scope" : {
      "title" : "LDAPv3 Plug-in Search Scope",
      "description" : "",
      "propertyOrder" : 2000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-interval" : {
      "title" : "LDAP Connection Heartbeat Interval",
      "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
error) then it may take up to the interval period before the problem is detected. Use along with the
Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
disabling heartbeat requests.",
      "propertyOrder" : 1300,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
      "title" : "LDAP Connection Pool Maximum Size",
      "description" : "",
      "propertyOrder" : 1200,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-authid" : {
      "title" : "LDAP Bind DN",
      "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
      "propertyOrder" : 700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-max-result" : {
      "title" : "Maximum Results Returned from Search",
      "description" : "",
      "propertyOrder" : 1500,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-timeunit" : {
      "title" : "LDAP Connection Heartbeat Time Unit",

```

```

    "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
it may take up to the interval period before the problem is detected. Use along with the Heartbeat
Interval parameter to define the exact interval.",
    "propertyOrder" : 1400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-organization_name" : {
    "title" : "LDAP Organization DN",
    "description" : "",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-ldap-server" : {
    "title" : "LDAP Server",
    "description" : "Format: LDAP server host name:port | server_ID | site_ID",
    "propertyOrder" : 600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-time-limit" : {
    "title" : "Search Timeout",
    "description" : "In seconds.",
    "propertyOrder" : 1600,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-authpw" : {
    "title" : "LDAP Bind Password",
    "description" : "",
    "propertyOrder" : 800,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection-mode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Defines which protocol/operation is used to establish the connection to
the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
    "propertyOrder" : 1000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}

```

```
},
"userconfig" : {
  "type" : "object",
  "title" : "User Configuration",
  "propertyOrder" : 3,
  "properties" : {
    "sun-idrepo-ldapv3-config-people-container-value" : {
      "title" : "LDAP People Container Value",
      "description" : "",
      "propertyOrder" : 5100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-isactive" : {
      "title" : "Attribute Name of User Status",
      "description" : "",
      "propertyOrder" : 2600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-users-search-attribute" : {
      "title" : "LDAP Users Search Attribute",
      "description" : "",
      "propertyOrder" : 2100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-user-objectclass" : {
      "title" : "LDAP User Object Class",
      "description" : "",
      "propertyOrder" : 2300,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-user-attributes" : {
      "title" : "LDAP User Attributes",
      "description" : "",
      "propertyOrder" : 2400,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-people-container-name" : {
      "title" : "LDAP People Container Naming Attribute",
      "description" : "",
      "propertyOrder" : 5000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```
},
"sun-idrepo-ldapv3-config-auth-kba-attr" : {
  "title" : "Knowledge Based Authentication Attribute Name",
  "description" : "",
  "propertyOrder" : 5300,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
  "title" : "Create User Attribute Mapping",
  "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
  "propertyOrder" : 2500,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-attempts-attr" : {
  "title" : "Knowledge Based Authentication Attempts Attribute Name",
  "description" : "",
  "propertyOrder" : 5410,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-inactive" : {
  "title" : "User Status Inactive Value",
  "description" : "",
  "propertyOrder" : 2800,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-users-search-filter" : {
  "title" : "LDAP Users Search Filter",
  "description" : "",
  "propertyOrder" : 2200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-index-attr" : {
  "title" : "Knowledge Based Authentication Active Index",
  "description" : "",
  "propertyOrder" : 5400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-active" : {
```

```

    "title" : "User Status Active Value",
    "description" : "",
    "propertyOrder" : 2700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
},
"cachecontrol" : {
  "type" : "object",
  "title" : "Cache Control",
  "propertyOrder" : 9,
  "properties" : {
    "sun-idrepo-ldapv3-dncache-size" : {
      "title" : "DN Cache Size",
      "description" : "In DN items, only used when DN Cache is enabled.",
      "propertyOrder" : 6000,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-dncache-enabled" : {
      "title" : "DN Cache",
      "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
      "propertyOrder" : 5900,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
},
"groupconfig" : {
  "type" : "object",
  "title" : "Group Configuration",
  "propertyOrder" : 5,
  "properties" : {
    "sun-idrepo-ldapv3-config-groups-search-attribute" : {
      "title" : "LDAP Groups Search Attribute",
      "description" : "",
      "propertyOrder" : 2900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-objectclass" : {
      "title" : "LDAP Groups Object Class",
      "description" : "",
      "propertyOrder" : 3300,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}

```

```
},
"sun-idrepo-ldapv3-config-memberof" : {
  "title" : "Attribute Name for Group Membership",
  "description" : "",
  "propertyOrder" : 3500,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-container-value" : {
  "title" : "LDAP Groups Container Value",
  "description" : "",
  "propertyOrder" : 3200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-container-name" : {
  "title" : "LDAP Groups Container Naming Attribute",
  "description" : "",
  "propertyOrder" : 3100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-attributes" : {
  "title" : "LDAP Groups Attributes",
  "description" : "",
  "propertyOrder" : 3400,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-unique-member" : {
  "title" : "Attribute Name of Unique Member",
  "description" : "",
  "propertyOrder" : 3600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-groups-search-filter" : {
  "title" : "LDAP Groups Search Filter",
  "description" : "",
  "propertyOrder" : 3000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"authentication" : {
  "type" : "object",
  "title" : "Authentication Configuration",
  "propertyOrder" : 4,
  "properties" : {
```



```
"sun-idrepo-ldapv3-config-auth-naming-attr" : {
  "title" : "Authentication Naming Attribute",
  "description" : "",
  "propertyOrder" : 5200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
},
"persistentsearch" : {
  "type" : "object",
  "title" : "Persistent Search Controls",
  "propertyOrder" : 7,
  "properties" : {
    "sun-idrepo-ldapv3-config-psearchbase" : {
      "title" : "Persistent Search Base DN",
      "description" : "",
      "propertyOrder" : 5500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-psearch-scope" : {
      "title" : "Persistent Search Scope",
      "description" : "",
      "propertyOrder" : 5700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"pluginconfig" : {
  "type" : "object",
  "title" : "Plug-in Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "sunIdRepoAttributeMapping" : {
      "title" : "Attribute Name Mapping",
      "description" : "",
      "propertyOrder" : 1800,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sunIdRepoSupportedOperations" : {
      "title" : "LDAPv3 Plug-in Supported Types and Operations",
      "description" : "",
      "propertyOrder" : 1900,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

```

    },
    "sunIdRepoClass" : {
      "title" : "LDAPv3 Repository Plug-in Class Name",
      "description" : "",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
}
}

```

1.4. ActiveDirectoryModule

1.4.1. Realm Operations

Resource path: `/realm-config/authentication/modules/activedirectory`

Resource version: `1.0`

1.4.1.1. create

Usage:

```
am> create ActiveDirectoryModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "primaryLdapServer" : {
      "title" : "Primary Active Directory Server ",
      "description" : "Use this list to set the primary Active Directory server used for authentication. <br><br>The Active Directory authentication module will use this list as the primary server for authentication. A single entry must be in the format:<br><br><code>server:port/</code><br><br>Multiple entries allow associations between OpenAM servers and an Active Directory server. The format is:<br><br><code>local server name | server:port</code><br><br>The local server name is the full name of the server from the list of servers and sites.",
      "propertyOrder" : 100,
      "required" : true,
    }
  }
}

```

```

        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "connectionHeartbeatInterval" : {
        "title" : "LDAP Connection Heartbeat Interval",
        "description" : "Specifies how often should OpenAM send a heartbeat request to the
        directory.<br><br>Use this option in case a firewall/loadbalancer can close idle connections,
        since the heartbeat requests will ensure that the connections won't become idle. Use along with the
        Heartbeat Time Unit parameter to define the correct interval. Zero or negative value will result in
        disabling heartbeat requests.",
        "propertyOrder" : 1500,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "userSearchStartDN" : {
        "title" : "DN to Start User Search",
        "description" : "The search for accounts to be authenticated start from this base DN <br><br>For
        a single server just enter the Base DN to be searched. Multiple OpenAM servers can have different
        base DN's for the search The format is as follows:<br><br><code>local server name | search DN</
        code><br><br><i>NB </i>The local server name is the full name of the server from the list of servers
        and sites.",
        "propertyOrder" : 300,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "trustAllServerCertificates" : {
        "title" : "Trust All Server Certificates",
        "description" : "Enables a <code>X509TrustManager</code> that trusts all
        certificates.<br><br>This feature will allow the LDAP authentication module to connect to LDAP
        servers protected by self signed or invalid certificates (such as invalid hostname).<br><br><i>NB
        </i>Use this feature with care as it bypasses the normal certificate verification process",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "userBindDN" : {
        "title" : "Bind User DN",
        "description" : "The DN of an admin user used by the module to authentication to the LDAP
        server<br><br>The LDAP module requires an administration account in order to perform functionality
        such as password reset.<br><br><i>NB </i><code>cn=Directory Manager</code> should not be used in
        production systems.",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "searchScope" : {
        "title" : "Search Scope",
        "description" : "The level in the Directory Server that will be searched for a matching
        user profile.<br><br>This attribute controls how the directory is searched.<br><br>
    
```

```

<<ul><li><code>OBJECT</code>: Only the Base DN is searched.</li><li><code>ONELEVEL</code>: Only the
single level below (and not the Base DN) is searched</li><li><code>SUBTREE</code>: The Base DN and
all levels below are searched</li></ul>",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default). ",
    "propertyOrder" : 1800,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "userSearchFilter" : {
    "title" : "User Search Filter",
    "description" : "This search filter will be appended to the standard user search
filter.<br><br>This attribute can be used to append a custom search filter to the standard filter.
For example: <code>(objectClass=person)</code>would result in the following user search filter:<br>
<br><code>(&(uid=<i>user</i>)(objectClass=person))</code>",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "connectionHeartbeatTimeUnit" : {
    "title" : "LDAP Connection Heartbeat Time Unit",
    "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>Use this option in case a firewall/loadbalancer can close idle connections, since the
heartbeat requests will ensure that the connections won't become idle.",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "openam-auth-ldap-connection-mode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Defines which protocol/operation is used to establish the connection to the
LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "profileAttributeMappings" : {
    "title" : "User Creation Attributes",
    "description" : "Controls the mapping of local attribute to external attribute for dynamic
profile creation.<br><br>If dynamic profile creation is enabled; this feature allows for a mapping
between the attribute/values retrieved from the users authenticated profile and the attribute/values
that will be provisioned into their matching account in the data store.<br><br>The format of this
property is: <br><br><code> local attr1|external attr1</code>",
    "propertyOrder" : 1300,

```

```

        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "secondaryLdapServer" : {
        "title" : "Secondary Active Directory Server",
        "description" : "Use this list to set the secondary (failover) Active Directory server used
for authentication.<br><br>If the primary Active Directory server fails, the Active Directory
authentication module will failover to the secondary server. A single entry must be in the
format:<br><br><code>server:port</code><br><br>Multiple entries allow associations between
OpenAM servers and an Active Directory server. The format is:<br><br><code>local server name |
server:port</code><br><br><i>NB </i>The local server name is the full name of the server from the
list of servers and sites.",
        "propertyOrder" : 200,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "userBindPassword" : {
        "title" : "Bind User Password",
        "description" : "The password of the administration account.",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "userSearchAttributes" : {
        "title" : "Attributes Used to Search for a User to be Authenticated",
        "description" : "The attributes specified in this list form the LDAP search filter.<br><br>The
default value of uid will form the following search filter of <code>uid=<i>user</i></code>, if there
are multiple values such as uid and cn, the module will create a search filter as follows <code>(|
uid=<i>user</i>)(cn=<i>user</i>)</code>",
        "propertyOrder" : 700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "userProfileRetrievalAttribute" : {
        "title" : "Attribute Used to Retrieve User Profile",
        "description" : "The LDAP module will use this attribute to search of the profile of an
authenticated user.<br><br>This is the attribute used to find the profile of the authenticated user.
Normally this will be the same attribute used to find the user account. The value will be the name of
the user used for authentication.",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "returnUserDN" : {

```

```
    "title" : "Return User DN to DataStore",
    "description" : "Controls whether the DN or the username is returned as the authentication
principal.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "operationTimeout" : {
    "title" : "LDAP operations timeout",
    "description" : "Defines the timeout in seconds OpenAM should wait for a response of the
Directory Server - <code>0</code> means no timeout.<br><br>If the Directory Server's host is down
completely or the TCP connection became stale OpenAM waits until operation timeouts from the OS
or the JVM are applied. However this setting allows more granular control within OpenAM itself. A value
of <code>0</code> means NO timeout is applied on OpenAM level and the timeouts from the JVM or OS
will apply.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
```

1.4.1.2. delete

Usage:

```
am> delete ActiveDirectoryModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.4.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ActiveDirectoryModule --realm Realm --actionName getAllTypes
```

1.4.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ActiveDirectoryModule --realm Realm --actionName getCreatableTypes
```

1.4.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ActiveDirectoryModule --realm Realm --actionName nextdescendents
```

1.4.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ActiveDirectoryModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.4.1.7. read

Usage:

```
am> read ActiveDirectoryModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.4.1.8. update

Usage:

```
am> update ActiveDirectoryModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "primaryLdapServer" : {
      "title" : "Primary Active Directory Server ",
      "description" : "Use this list to set the primary Active Directory server used for authentication. <br><br>The Active Directory authentication module will use this list as the primary server for authentication. A single entry must be in the format:<br><br><code>server:port</code><br><br>Multiple entries allow associations between OpenAM servers and an Active Directory server. The format is:<br><br><code>local server name | server:port</code><br><br>The local server name is the full name of the server from the list of servers and sites.",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "connectionHeartbeatInterval" : {
      "title" : "LDAP Connection Heartbeat Interval",
      "description" : "Specifies how often should OpenAM send a heartbeat request to the directory.<br><br>Use this option in case a firewall/loadbalancer can close idle connections, since the heartbeat requests will ensure that the connections won't become idle. Use along with the Heartbeat Time Unit parameter to define the correct interval. Zero or negative value will result in disabling heartbeat requests.",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "userSearchStartDN" : {
      "title" : "DN to Start User Search",
      "description" : "The search for accounts to be authenticated start from this base DN <br><br>For a single server just enter the Base DN to be searched. Multiple OpenAM servers can have different base DN's for the search The format is as follows:<br><br><code>local server name | search DN</code><br><br><i>NB </i>The local server name is the full name of the server from the list of servers and sites.",
      "propertyOrder" : 300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "trustAllServerCertificates" : {
      "title" : "Trust All Server Certificates",
      "description" : "Enables a <code>X509TrustManager</code> that trusts all certificates.<br><br>This feature will allow the LDAP authentication module to connect to LDAP servers protected by self signed or invalid certificates (such as invalid hostname).<br><br><i>NB </i>Use this feature with care as it bypasses the normal certificate verification process",
      "propertyOrder" : 1400,
      "required" : true,
      "type" : "boolean",

```



```

    "exampleValue" : ""
  },
  "userBindDN" : {
    "title" : "Bind User DN",
    "description" : "The DN of an admin user used by the module to authentication to the LDAP
server<br><br>The LDAP module requires an administration account in order to perform functionality
such as password reset.<br><br><i>NB </i><code>cn=Directory Manager</code> should not be used in
production systems.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "searchScope" : {
    "title" : "Search Scope",
    "description" : "The level in the Directory Server that will be searched for a matching
user profile.<br><br>This attribute controls how the directory is searched.<br><br>
<ul><li><code>OBJECT</code>: Only the Base DN is searched.</li><li><code>ONELEVEL</code>: Only the
single level below (and not the Base DN) is searched</li><li><code>SUBTREE</code>: The Base DN and
all levels below are searched</li></ul>",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default). ",
    "propertyOrder" : 1800,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "userSearchFilter" : {
    "title" : "User Search Filter",
    "description" : "This search filter will be appended to the standard user search
filter.<br><br>This attribute can be used to append a custom search filter to the standard filter.
For example: <code>(objectClass=person)</code>would result in the following user search filter:<br>
<br><code>(&(uid=<i>user</i>)(objectClass=person))</code>",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "connectionHeartbeatTimeUnit" : {
    "title" : "LDAP Connection Heartbeat Time Unit",
    "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>Use this option in case a firewall/loadbalancer can close idle connections, since the
heartbeat requests will ensure that the connections won't become idle.",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "openam-auth-ldap-connection-mode" : {
    "title" : "LDAP Connection Mode",

```

```

        "description" : "Defines which protocol/operation is used to establish the connection to the
LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
        "propertyOrder" : 1000,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "profileAttributeMappings" : {
        "title" : "User Creation Attributes",
        "description" : "Controls the mapping of local attribute to external attribute for dynamic
profile creation.<br><br>If dynamic profile creation is enabled; this feature allows for a mapping
between the attribute/values retrieved from the users authenticated profile and the attribute/values
that will be provisioned into their matching account in the data store.<br><br>The format of this
property is: <br><br><code> local attr|external attr</code>",
        "propertyOrder" : 1300,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "secondaryLdapServer" : {
        "title" : "Secondary Active Directory Server",
        "description" : "Use this list to set the secondary (failover) Active Directory server used
for authentication.<br><br>If the primary Active Directory server fails, the Active Directory
authentication module will failover to the secondary server. A single entry must be in the
format:<br><br><code>server:port</code><br><br>Multiple entries allow associations between
OpenAM servers and an Active Directory server. The format is:<br><br><code>local server name |
server:port</code><br><br><i>NB </i></code>The local server name is the full name of the server from the
list of servers and sites.",
        "propertyOrder" : 200,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "userBindPassword" : {
        "title" : "Bind User Password",
        "description" : "The password of the administration account.",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "userSearchAttributes" : {
        "title" : "Attributes Used to Search for a User to be Authenticated",
        "description" : "The attributes specified in this list form the LDAP search filter.<br><br>The
default value of uid will form the following search filter of <code>uid=<i>user</i></code>, if there
are multiple values such as uid and cn, the module will create a search filter as follows <code>(|
(uid=<i>user</i>)(cn=<i>user</i>))</code>",
        "propertyOrder" : 700,
        "required" : true,
    }

```

```

        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      },
      "userProfileRetrievalAttribute" : {
        "title" : "Attribute Used to Retrieve User Profile",
        "description" : "The LDAP module will use this attribute to search of the profile of an authenticated user.<br><br>This is the attribute used to find the profile of the authenticated user. Normally this will be the same attribute used to find the user account. The value will be the name of the user used for authentication.",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "returnUserDN" : {
        "title" : "Return User DN to DataStore",
        "description" : "Controls whether the DN or the username is returned as the authentication principal.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "operationTimeout" : {
        "title" : "LDAP operations timeout",
        "description" : "Defines the timeout in seconds OpenAM should wait for a response of the Directory Server - <code>0</code> means no timeout.<br><br>If the Directory Server's host is down completely or the TCP connection became stale OpenAM waits until operation timeouts from the OS or the JVM are applied. However this setting allows more granular control within OpenAM itself. A value of <code>0</code> means NO timeout is applied on OpenAM level and the timeouts from the JVM or OS will apply.",
        "propertyOrder" : 1700,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      }
    }
  }
}

```

1.4.2. Global Operations

Resource path: </global-config/authentication/modules/activedirectory>

Resource version: [1.0](#)

1.4.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ActiveDirectoryModule --global --actionName getAllTypes
```

1.4.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ActiveDirectoryModule --global --actionName getCreatableTypes
```

1.4.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ActiveDirectoryModule --global --actionName nextdescendents
```

1.4.2.4. read

Usage:

```
am> read ActiveDirectoryModule --global
```

1.4.2.5. update

Usage:

```
am> update ActiveDirectoryModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "trustAllServerCertificates" : {
          "title" : "Trust All Server Certificates",
          "description" : "Enables a <code>X509TrustManager</code> that trusts all
certificates.<br><br>This feature will allow the LDAP authentication module to connect to LDAP
servers protected by self signed or invalid certificates (such as invalid hostname).<br><br><i>NB
</i>Use this feature with care as it bypasses the normal certificate verification process",
          "propertyOrder" : 1400,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        }
      }
    }
  }
}
```

```

    },
    "returnUserDN" : {
      "title" : "Return User DN to DataStore",
      "description" : "Controls whether the DN or the username is returned as the authentication
principal.",
      "propertyOrder" : 1200,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "operationTimeout" : {
      "title" : "LDAP operations timeout",
      "description" : "Defines the timeout in seconds OpenAM should wait for a response of the
Directory Server - <code>0</code> means no timeout.<br><br>If the Directory Server's host is down
completely or the TCP connection became stale OpenAM waits until operation timeouts from the OS or
the JVM are applied. However this setting allows more granular control within OpenAM itself. A value
of <code>0</code> means NO timeout is applied on OpenAM level and the timeouts from the JVM or OS
will apply.",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default). ",
      "propertyOrder" : 1800,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "searchScope" : {
      "title" : "Search Scope",
      "description" : "The level in the Directory Server that will be searched for a
matching user profile.<br><br>This attribute controls how the directory is searched.<br><br>
<ul><li><code>OBJECT</code>: Only the Base DN is searched.</li><li><code>ONELEVEL</code>: Only the
single level below (and not the Base DN) is searched</li><li><code>SUBTREE</code>: The Base DN and
all levels below are searched</li></ul>",
      "propertyOrder" : 900,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "userBindDN" : {
      "title" : "Bind User DN",
      "description" : "The DN of an admin user used by the module to authentication to the LDAP
server<br><br>The LDAP module requires an administration account in order to perform functionality
such as password reset.<br><br><i>NB </i><code>cn=Directory Manager</code> should not be used in
production systems.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "userSearchAttributes" : {
      "title" : "Attributes Used to Search for a User to be Authenticated",

```

```

    "description" : "The attributes specified in this list form the LDAP search
filter.<br><br>The default value of uid will form the following search filter of <code>uid=<i>user</i></code>,
if there are multiple values such as uid and cn, the module will create a search filter as
follows <code>(|(uid=<i>user</i>)(cn=<i>user</i>))</code>",
    "propertyOrder" : 700,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"UserProfileRetrievalAttribute" : {
    "title" : "Attribute Used to Retrieve User Profile",
    "description" : "The LDAP module will use this attribute to search of the profile of an
authenticated user.<br><br>This is the attribute used to find the profile of the authenticated user.
Normally this will be the same attribute used to find the user account. The value will be the name of
the user used for authentication.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"SecondaryLdapServer" : {
    "title" : "Secondary Active Directory Server",
    "description" : "Use this list to set the secondary (failover) Active Directory server
used for authentication.<br><br>If the primary Active Directory server fails, the Active Directory
authentication module will failover to the secondary server. A single entry must be in the
format:<br><br><code>server:port</code><br><br>Multiple entries allow associations between
OpenAM servers and an Active Directory server. The format is:<br><br><code>local server name |
server:port</code><br><br><i>NB </i>The local server name is the full name of the server from the
list of servers and sites.",
    "propertyOrder" : 200,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"profileAttributeMappings" : {
    "title" : "User Creation Attributes",
    "description" : "Controls the mapping of local attribute to external attribute for dynamic
profile creation.<br><br>If dynamic profile creation is enabled; this feature allows for a mapping
between the attribute/values retrieved from the users authenticated profile and the attribute/values
that will be provisioned into their matching account in the data store.<br><br>The format of this
property is: <br><br><code> local attr|external attr</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"connectionHeartbeatInterval" : {
    "title" : "LDAP Connection Heartbeat Interval",
    "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>Use this option in case a firewall/loadbalancer can close idle connections,

```

since the heartbeat requests will ensure that the connections won't become idle. Use along with the Heartbeat Time Unit parameter to define the correct interval. Zero or negative value will result in disabling heartbeat requests.",

```

    "propertyOrder" : 1500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "userBindPassword" : {
    "title" : "Bind User Password",
    "description" : "The password of the administration account.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "primaryLdapServer" : {
    "title" : "Primary Active Directory Server ",
    "description" : "Use this list to set the primary Active Directory server used for authentication. <br><br>The Active Directory authentication module will use this list as the primary server for authentication. A single entry must be in the format:<br><br><code>server:port/</code><br><br>Multiple entries allow associations between OpenAM servers and an Active Directory server. The format is:<br><br><code>local server name | server:port</code><br><br>The local server name is the full name of the server from the list of servers and sites.",
    "propertyOrder" : 100,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "connectionHeartbeatTimeUnit" : {
    "title" : "LDAP Connection Heartbeat Time Unit",
    "description" : "Defines the time unit corresponding to the Heartbeat Interval setting.<br><br>Use this option in case a firewall/loadbalancer can close idle connections, since the heartbeat requests will ensure that the connections won't become idle.",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userSearchFilter" : {
    "title" : "User Search Filter",
    "description" : "This search filter will be appended to the standard user search filter.<br><br>This attribute can be used to append a custom search filter to the standard filter. For example: <code>(objectClass=person)</code>would result in the following user search filter:<br><br><code>(&(uid=<i>user</i>)(objectClass=person))</code>",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "openam-auth-ldap-connection-mode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Defines which protocol/operation is used to establish the connection to the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the

```

```

connection is secured via SSL or TLS. <br/> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"userSearchStartDN" : {
  "title" : "DN to Start User Search",
  "description" : "The search for accounts to be authenticated start from this base DN
<br><br>For a single server just enter the Base DN to be searched. Multiple OpenAM servers can have
different base DNS for the search The format is as follows:<br/><br/><code>local server name | search
DN</code><br/><br/><i>NB </i>The local server name is the full name of the server from the list of
servers and sites.",
  "propertyOrder" : 300,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}
}

```

1.5. AdaptiveRiskModule

1.5.1. Realm Operations

Resource path: `/realm-config/authentication/modules/adaptiverisk`

Resource version: `1.0`

1.5.1.1. create

Usage:

```
am> create AdaptiveRiskModule --realm Realm --id id --body body
```

Parameters:

`--id`

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "attributecheck" : {
      "type" : "object",
      "title" : "Profile Attribute",
      "propertyOrder" : 7,
      "properties" : {
        "profileRiskAttributeScore" : {
          "title" : "Score",
          "description" : "The amount to increment the score if this check fails.",
          "propertyOrder" : 3100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "profileRiskAttributeCheckEnabled" : {
          "title" : "Profile Risk Attribute check",
          "description" : "Enables the checking of the user profile for a matching attribute and value.<br><br>If this check is enabled, the check will pass if the users profile contains the required risk attribute and value.",
          "propertyOrder" : 2800,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "profileRiskAttributeName" : {
          "title" : "Attribute Name",
          "description" : "The name of the attribute to retrieve from the user profile in the data store.",
          "propertyOrder" : 2900,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "invertProfileRiskAttributeScore" : {
          "title" : "Invert Result",
          "description" : "If the check succeeds the score will be included in the total, for failure the score will not be incremented.",
          "propertyOrder" : 3200,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "profileRiskAttributeValue" : {
          "title" : "Attribute Value",
          "description" : "The required value of the named attribute.",
          "propertyOrder" : 3000,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    }
  },
  "lastlogin" : {
```

```
"type" : "object",
"title" : "Time Since Last Login",
"propertyOrder" : 6,
"properties" : {
  "timeSinceLastLoginCheckEnabled" : {
    "title" : "Time since Last login Check",
    "description" : "Enables the checking of the last time the user successfully
authenticated.<br><br>If this check is enabled, the check ensures the user has successfully
authenticated within a given interval. If the interval has been exceeded the check will fail. The
last authentication for the user is stored in a client cookie.",
    "propertyOrder" : 2200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "maxTimeSinceLastLogin" : {
    "title" : "Max Time since Last login",
    "description" : "The maximum number of days that can elapse before this test.",
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "timeSinceLastLoginCookieName" : {
    "title" : "Cookie Name",
    "description" : "The name of the cookie used to store the time of the last successful
authentication.",
    "propertyOrder" : 2300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saveLastLoginTimeOnSuccessfulLogin" : {
    "title" : "Save time of Successful Login",
    "description" : "The last login time will be saved in a client cookie<br><br>The Adaptive
Risk Post Authentication Plug-in will update the last login time",
    "propertyOrder" : 2500,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "invertTimeSinceLastLoginScore" : {
    "title" : "Invert Result",
    "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
    "propertyOrder" : 2700,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "timeSinceLastLoginScore" : {
    "title" : "Score",
    "description" : "The amount to increment the score if this check fails.",
    "propertyOrder" : 2600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
```

```

},
"devicecookie" : {
  "type" : "object",
  "title" : "Device Cookie",
  "propertyOrder" : 5,
  "properties" : {
    "deviceCookieScore" : {
      "title" : "Score",
      "description" : "The amount to increment the score if this check fails.",
      "propertyOrder" : 3600,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "saveDeviceCookieValueOnSuccessfulLogin" : {
      "title" : "Save Device Registration on Successful Login",
      "description" : "Set the device cookie on the client response<br><br>The Adaptive Risk Post
Authentication Plug-in will set the device cookie on the client response",
      "propertyOrder" : 3500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "deviceCookieName" : {
      "title" : "Cookie Name",
      "description" : "The name of the cookie to be checked for (and optionally set) on the client
request",
      "propertyOrder" : 3400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "deviceCookieCheckEnabled" : {
      "title" : "Device Registration Cookie Check",
      "description" : "Enables the checking of the client request for a known cookie.<br><br>If
this check is enabled, the check will pass if the client request contains the named cookie.",
      "propertyOrder" : 3300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "invertDeviceCookieScore" : {
      "title" : "Invert Result",
      "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
      "propertyOrder" : 3700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
},
"knowncookie" : {
  "type" : "object",
  "title" : "Known Cookie",
  "propertyOrder" : 4,
  "properties" : {
    "knownCookieCheckEnabled" : {
      "title" : "Cookie Value Check",

```

```

        "description" : "Enables the checking of a known cookie value in the client
request<br><br>If this check is enabled, the check looks for a known cookie in the client request. If
the cookie exists and has the correct value then the check will pass. ",
        "propertyOrder" : 1600,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "createKnownCookieOnSuccessfulLogin" : {
        "title" : "Save Cookie Value on Successful Login",
        "description" : "The cookie will be created on the client after successful login<br><br>The
Adaptive Risk Post Authentication Plug-in will set the cookie on the client response",
        "propertyOrder" : 1900,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "knownCookieScore" : {
        "title" : "Score",
        "description" : "The amount to increment the score if this check fails.",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "invertKnownCookieScore" : {
        "title" : "Invert Result",
        "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "knownCookieValue" : {
        "title" : "Cookie Value",
        "description" : "The value to be set on the cookie.",
        "propertyOrder" : 1800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "knownCookieName" : {
        "title" : "Cookie Name",
        "description" : "The name of the cookie to set on the client.",
        "propertyOrder" : 1700,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"requestheader" : {
    "type" : "object",
    "title" : "Request Header",
    "propertyOrder" : 9,
    "properties" : {
        "requestHeaderScore" : {
            "title" : "Score",

```

```

    "description" : "The amount to increment the score if this check fails.",
    "propertyOrder" : 4600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "requestHeaderCheckEnabled" : {
    "title" : "Request Header Check",
    "description" : "Enables the checking of the client request for a known header name and
value.<br><br>The request header check will pass if the client request contains the required named
header and value.",
    "propertyOrder" : 4300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "invertRequestHeaderScore" : {
    "title" : "Invert Result",
    "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
    "propertyOrder" : 4700,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "requestHeaderName" : {
    "title" : "Request Header Name",
    "description" : "The name of the required HTTP header ",
    "propertyOrder" : 4400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "requestHeaderValue" : {
    "title" : "Request Header Value",
    "description" : "The required value of the named HTTP header.",
    "propertyOrder" : 4500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"iprange" : {
  "type" : "object",
  "title" : "IP Address Range",
  "propertyOrder" : 2,
  "properties" : {
    "ipRange" : {
      "title" : "IP Range",
      "description" : "The list of IP address to compare against the client IP address.<br><br>The
format of the IP address is as follows:<br><br><ul><li>Single IP address: <code>172.16.90.1</
code></li><li>CIDR notation: <code>172.16.90.0/24</code></li><li>IP net-block with netmask:
<code>172.16.90.0:255.255.255.0</code></li></ul>",
      "propertyOrder" : 700,
      "required" : true,
      "items" : {
        "type" : "string"
      }
    }
  }
},

```

```

    "type" : "array",
    "exampleValue" : ""
  },
  "ipRangeScore" : {
    "title" : "Score",
    "description" : "The amount to increment the score if this check fails.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "ipRangeCheckEnabled" : {
    "title" : "IP Range Check",
    "description" : "Enables the checking of the client IP address against a list of IP
addresses.<br><br>The IP range check compares the IP of the client against a list of IP addresses, if
the client IP is found within said list the check is successful.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "invertIPRangeScoreEnabled" : {
    "title" : "Invert Result",
    "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"authfailed" : {
  "type" : "object",
  "title" : "Failed Authentications",
  "propertyOrder" : 1,
  "properties" : {
    "failureScore" : {
      "title" : "Score",
      "description" : "The amount to increment the score if this check fails.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "failedAuthenticationCheckEnabled" : {
      "title" : "Failed Authentication Check",
      "description" : "Checks if the user has past authentication failures.<br><br>Check if the
OpenAM account lockout mechanism has recorded past authentication failures for the user.<br/><br/>
><i>NB </i>For this check to function, Account Lockout must be enabled.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "invertFailureScore" : {
      "title" : "Invert Result",
      "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",

```

```

        "propertyOrder" : 500,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"geolocation" : {
    "type" : "object",
    "title" : "Geo Location",
    "propertyOrder" : 8,
    "properties" : {
        "invertGeolocationScore" : {
            "title" : "Invert Result",
            "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
            "propertyOrder" : 4200,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "geolocationCheckEnabled" : {
            "title" : "Geolocation Country Code Check",
            "description" : "Enables the checking of the client IP address against the geolocation
database.<br><br>The geolocation database associates IP addresses against their known location. This
check passes if the country associated with the client IP address is matched against the list of
valid country codes.<br><br>The geolocation database is available in binary format at <a href=
\"http://www.maxmind.com/app/country\" target=\"_blank\">MaxMind</a>.",
            "propertyOrder" : 3800,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "geolocationValidCountryCodes" : {
            "title" : "Valid Country Codes",
            "description" : "The list of country codes that are considered as valid locations for client
IPs.<br><br>The list is made up of country codes separated by a | character; for example:<br><br>
<code>gb|us|no|fr</code>",
            "propertyOrder" : 4000,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "geolocationDatabaseLocation" : {
            "title" : "Geolocation Database location",
            "description" : "The path to the location of the GEO location database.<br><br>The
Geolocation database is not distributed with OpenAM, you can get it in binary format from <a href=
\"http://www.maxmind.com/app/country\" target=\"_blank\">MaxMind</a>.",
            "propertyOrder" : 3900,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "geolocationScore" : {
            "title" : "Score",
            "description" : "The amount to increment the score if this check fails.",
            "propertyOrder" : 4100,
            "required" : true,
            "type" : "integer",

```

```

        "exampleValue" : ""
    }
}
},
"iphistory" : {
    "type" : "object",
    "title" : "IP Address History",
    "propertyOrder" : 3,
    "properties" : {
        "invertIPHHistoryScore" : {
            "title" : "Invert Result",
            "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
            "propertyOrder" : 1500,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "saveSuccessfulIP" : {
            "title" : "Save Successful IP Address",
            "description" : "The IP History list will be updated in the data store<br><br>The Adaptive
Risk Post Authentication Plug-in will update the IP history list if the overall authentication is
successful.",
            "propertyOrder" : 1300,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "ipHistoryCount" : {
            "title" : "History size",
            "description" : "The number of client IP addresses to save in the history list.",
            "propertyOrder" : 1100,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "ipHistoryCheckEnabled" : {
            "title" : "IP History Check",
            "description" : "Enables the checking of client IP address against a list of past IP
addresses.<br><br>If this check is enabled; a set number of past IP addresses used by the client to
access OpenAM is recorded in the user profile. This check passes if the current client IP address
is present in the history list. If the IP address is not present, the check fails and the IP address
is added to list if the overall authentication is successful (causing the oldest IP address to be
removed).",
            "propertyOrder" : 1000,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "ipHistoryScore" : {
            "title" : "Score",
            "description" : "The amount to increment the score if this check fails.",
            "propertyOrder" : 1400,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "ipHistoryProfileAttribute" : {
            "title" : "Profile Attribute Name",

```



```

    "description" : "The name of the attribute used to store the IP history list in the data
store.<br><br>IP history list is stored in the Data Store meaning your Data Store should be able
to store values under the configured attribute name. If you're using a directory server as backend,
make sure your Data Store configuration contains the necessary objectclass and attribute related
settings.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"general" : {
  "type" : "object",
  "title" : "General",
  "propertyOrder" : 0,
  "properties" : {
    "riskThreshold" : {
      "title" : "Risk Threshold",
      "description" : "If the risk threshold value is not reached after executing the different
tests, the authentication is considered to be successful.<br><br>Associated with many of the adaptive
risk checks is a score; if a check does not passes then the score is added to the current running
total. The final score is then compared with the <i>Risk Threshold</i>, if the score is lesser than
said threshold the module will be successful. ",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
}
}
}
}

```

1.5.1.2. delete

Usage:

```
am> delete AdaptiveRiskModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.5.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AdaptiveRiskModule --realm Realm --actionName getAllTypes
```

1.5.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AdaptiveRiskModule --realm Realm --actionName getCreatableTypes
```

1.5.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AdaptiveRiskModule --realm Realm --actionName nextdescendents
```

1.5.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query AdaptiveRiskModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.5.1.7. read

Usage:

```
am> read AdaptiveRiskModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.5.1.8. update

Usage:

```
am> update AdaptiveRiskModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "attributecheck" : {
      "type" : "object",
      "title" : "Profile Attribute",
      "propertyOrder" : 7,
      "properties" : {
        "profileRiskAttributeScore" : {
          "title" : "Score",
          "description" : "The amount to increment the score if this check fails.",
          "propertyOrder" : 3100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "profileRiskAttributeCheckEnabled" : {
          "title" : "Profile Risk Attribute check",
          "description" : "Enables the checking of the user profile for a matching attribute and value.<br><br>If this check is enabled, the check will pass if the users profile contains the required risk attribute and value.",
          "propertyOrder" : 2800,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "profileRiskAttributeName" : {
          "title" : "Attribute Name",
          "description" : "The name of the attribute to retrieve from the user profile in the data store.",
          "propertyOrder" : 2900,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "invertProfileRiskAttributeScore" : {
          "title" : "Invert Result",
          "description" : "If the check succeeds the score will be included in the total, for failure the score will not be incremented.",
          "propertyOrder" : 3200,
          "required" : true,
          "type" : "boolean",

```

```

        "exampleValue" : ""
    },
    "profileRiskAttributeValue" : {
        "title" : "Attribute Value",
        "description" : "The required value of the named attribute.",
        "propertyOrder" : 3000,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
},
"lastlogin" : {
    "type" : "object",
    "title" : "Time Since Last Login",
    "propertyOrder" : 6,
    "properties" : {
        "timeSinceLastLoginCheckEnabled" : {
            "title" : "Time since Last login Check",
            "description" : "Enables the checking of the last time the user successfully authenticated.<br><br>If this check is enabled, the check ensures the user has successfully authenticated within a given interval. If the interval has been exceeded the check will fail. The last authentication for the user is stored in a client cookie.",
            "propertyOrder" : 2200,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "maxTimeSinceLastLogin" : {
            "title" : "Max Time since Last login",
            "description" : "The maximum number of days that can elapse before this test.",
            "propertyOrder" : 2400,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "timeSinceLastLoginCookieName" : {
            "title" : "Cookie Name",
            "description" : "The name of the cookie used to store the time of the last successful authentication.",
            "propertyOrder" : 2300,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "saveLastLoginTimeOnSuccessfulLogin" : {
            "title" : "Save time of Successful Login",
            "description" : "The last login time will be saved in a client cookie<br><br>The Adaptive Risk Post Authentication Plug-in will update the last login time",
            "propertyOrder" : 2500,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "invertTimeSinceLastLoginScore" : {
            "title" : "Invert Result",
            "description" : "If the check succeeds the score will be included in the total, for failure the score will not be incremented.",
            "propertyOrder" : 2700,

```

```

    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "timeSinceLastLoginScore" : {
    "title" : "Score",
    "description" : "The amount to increment the score if this check fails.",
    "propertyOrder" : 2600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
},
"devicecookie" : {
  "type" : "object",
  "title" : "Device Cookie",
  "propertyOrder" : 5,
  "properties" : {
    "deviceCookieScore" : {
      "title" : "Score",
      "description" : "The amount to increment the score if this check fails.",
      "propertyOrder" : 3600,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "saveDeviceCookieValueOnSuccessfulLogin" : {
      "title" : "Save Device Registration on Successful Login",
      "description" : "Set the device cookie on the client response<br><br>The Adaptive Risk Post
Authentication Plug-in will set the device cookie on the client response",
      "propertyOrder" : 3500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "deviceCookieName" : {
      "title" : "Cookie Name",
      "description" : "The name of the cookie to be checked for (and optionally set) on the client
request",
      "propertyOrder" : 3400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "deviceCookieCheckEnabled" : {
      "title" : "Device Registration Cookie Check",
      "description" : "Enables the checking of the client request for a known cookie.<br><br>If
this check is enabled, the check will pass if the client request contains the named cookie.",
      "propertyOrder" : 3300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "invertDeviceCookieScore" : {
      "title" : "Invert Result",
      "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
      "propertyOrder" : 3700,

```

```

    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"knowncookie" : {
  "type" : "object",
  "title" : "Known Cookie",
  "propertyOrder" : 4,
  "properties" : {
    "knownCookieCheckEnabled" : {
      "title" : "Cookie Value Check",
      "description" : "Enables the checking of a known cookie value in the client
request<br><br>If this check is enabled, the check looks for a known cookie in the client request. If
the cookie exists and has the correct value then the check will pass. ",
      "propertyOrder" : 1600,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "createKnownCookieOnSuccessfulLogin" : {
      "title" : "Save Cookie Value on Successful Login",
      "description" : "The cookie will be created on the client after successful login<br><br>The
Adaptive Risk Post Authentication Plug-in will set the cookie on the client response",
      "propertyOrder" : 1900,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "knownCookieScore" : {
      "title" : "Score",
      "description" : "The amount to increment the score if this check fails.",
      "propertyOrder" : 2000,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "invertKnownCookieScore" : {
      "title" : "Invert Result",
      "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
      "propertyOrder" : 2100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "knownCookieValue" : {
      "title" : "Cookie Value",
      "description" : "The value to be set on the cookie.",
      "propertyOrder" : 1800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "knownCookieName" : {
      "title" : "Cookie Name",
      "description" : "The name of the cookie to set on the client.",
      "propertyOrder" : 1700,

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"requestheader" : {
  "type" : "object",
  "title" : "Request Header",
  "propertyOrder" : 9,
  "properties" : {
    "requestHeaderScore" : {
      "title" : "Score",
      "description" : "The amount to increment the score if this check fails.",
      "propertyOrder" : 4600,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "requestHeaderCheckEnabled" : {
      "title" : "Request Header Check",
      "description" : "Enables the checking of the client request for a known header name and value.<br><br>The request header check will pass if the client request contains the required named header and value.",
      "propertyOrder" : 4300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "invertRequestHeaderScore" : {
      "title" : "Invert Result",
      "description" : "If the check succeeds the score will be included in the total, for failure the score will not be incremented.",
      "propertyOrder" : 4700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "requestHeaderName" : {
      "title" : "Request Header Name",
      "description" : "The name of the required HTTP header ",
      "propertyOrder" : 4400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "requestHeaderValue" : {
      "title" : "Request Header Value",
      "description" : "The required value of the named HTTP header.",
      "propertyOrder" : 4500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"iprange" : {
  "type" : "object",
  "title" : "IP Address Range",

```

```

    "propertyOrder" : 2,
    "properties" : {
      "ipRange" : {
        "title" : "IP Range",
        "description" : "The list of IP address to compare against the client IP address.<br><br>The
format of the IP address is as follows:<br><br><ul><li>Single IP address: <code>172.16.90.1</
code></li><li>CIDR notation: <code>172.16.90.0/24</code></li><li>IP net-block with netmask:
<code>172.16.90.0:255.255.255.0</code></li></ul>",
        "propertyOrder" : 700,
        "required" : true,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      },
      "ipRangeScore" : {
        "title" : "Score",
        "description" : "The amount to increment the score if this check fails.",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      },
      "ipRangeCheckEnabled" : {
        "title" : "IP Range Check",
        "description" : "Enables the checking of the client IP address against a list of IP
addresses.<br><br>The IP range check compares the IP of the client against a list of IP addresses, if
the client IP is found within said list the check is successful.",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "invertIPRangeScoreEnabled" : {
        "title" : "Invert Result",
        "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
        "propertyOrder" : 900,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      }
    }
  },
  "authfailed" : {
    "type" : "object",
    "title" : "Failed Authentications",
    "propertyOrder" : 1,
    "properties" : {
      "failureScore" : {
        "title" : "Score",
        "description" : "The amount to increment the score if this check fails.",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      }
    },
    "failedAuthenticationCheckEnabled" : {

```



```

    "title" : "Failed Authentication Check",
    "description" : "Checks if the user has past authentication failures.<br><br>Check if the
OpenAM account lockout mechanism has recorded past authentication failures for the user.<br><br/>
<i>NB </i>For this check to function, Account Lockout must be enabled.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "invertFailureScore" : {
    "title" : "Invert Result",
    "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"geolocation" : {
  "type" : "object",
  "title" : "Geo Location",
  "propertyOrder" : 8,
  "properties" : {
    "invertGeolocationScore" : {
      "title" : "Invert Result",
      "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
      "propertyOrder" : 4200,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "geolocationCheckEnabled" : {
      "title" : "Geolocation Country Code Check",
      "description" : "Enables the checking of the client IP address against the geolocation
database.<br><br>The geolocation database associates IP addresses against their known location. This
check passes if the country associated with the client IP address is matched against the list of
valid country codes.<br><br>The geolocation database is available in binary format at <a href=
'http://www.maxmind.com/app/country' target='_blank'>MaxMind</a>.",
      "propertyOrder" : 3800,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "geolocationValidCountryCodes" : {
      "title" : "Valid Country Codes",
      "description" : "The list of country codes that are considered as valid locations for client
IPs.<br><br>The list is made up of country codes separated by a | character; for example:<br><br/>
<code>gb|us|no|fr</code>",
      "propertyOrder" : 4000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "geolocationDatabaseLocation" : {
      "title" : "Geolocation Database location",

```

```

    "description" : "The path to the location of the GEO location database.<br><br>The
    Geolocation database is not distributed with OpenAM, you can get it in binary format from <a href=
    \"http://www.maxmind.com/app/country\" target=\"_blank\">MaxMind</a>.",
    "propertyOrder" : 3900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "geolocationScore" : {
    "title" : "Score",
    "description" : "The amount to increment the score if this check fails.",
    "propertyOrder" : 4100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
},
"iphistory" : {
  "type" : "object",
  "title" : "IP Address History",
  "propertyOrder" : 3,
  "properties" : {
    "invertIPHHistoryScore" : {
      "title" : "Invert Result",
      "description" : "If the check succeeds the score will be included in the total, for failure
the score will not be incremented.",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "saveSuccessfulIP" : {
      "title" : "Save Successful IP Address",
      "description" : "The IP History list will be updated in the data store<br><br>The Adaptive
Risk Post Authentication Plug-in will update the IP history list if the overall authentication is
successful.",
      "propertyOrder" : 1300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "ipHistoryCount" : {
      "title" : "History size",
      "description" : "The number of client IP addresses to save in the history list.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "ipHistoryCheckEnabled" : {
      "title" : "IP History Check",
      "description" : "Enables the checking of client IP address against a list of past IP
addresses.<br><br>If this check is enabled; a set number of past IP addresses used by the client to
access OpenAM is recorded in the user profile. This check passes if the current client IP address
is present in the history list. If the IP address is not present, the check fails and the IP address
is added to list if the overall authentication is successful (causing the oldest IP address to be
removed).",
      "propertyOrder" : 1000,

```

```

    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ipHistoryScore" : {
    "title" : "Score",
    "description" : "The amount to increment the score if this check fails.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "ipHistoryProfileAttribute" : {
    "title" : "Profile Attribute Name",
    "description" : "The name of the attribute used to store the IP history list in the data
store.<br><br>IP history list is stored in the Data Store meaning your Data Store should be able
to store values under the configured attribute name. If you're using a directory server as backend,
make sure your Data Store configuration contains the necessary objectclass and attribute related
settings.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"general" : {
  "type" : "object",
  "title" : "General",
  "propertyOrder" : 0,
  "properties" : {
    "riskThreshold" : {
      "title" : "Risk Threshold",
      "description" : "If the risk threshold value is not reached after executing the different
tests, the authentication is considered to be successful.<br><br>Associated with many of the adaptive
risk checks is a score; if a check does not passes then the score is added to the current running
total. The final score is then compared with the <i>Risk Threshold</i>, if the score is lesser than
said threshold the module will be successful. ",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
}
}
}

```

1.5.2. Global Operations

Resource path: `/global-config/authentication/modules/adaptiverisk`

Resource version: `1.0`

1.5.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AdaptiveRiskModule --global --actionName getAllTypes
```

1.5.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AdaptiveRiskModule --global --actionName getCreatableTypes
```

1.5.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AdaptiveRiskModule --global --actionName nextdescendents
```

1.5.2.4. read

Usage:

```
am> read AdaptiveRiskModule --global
```

1.5.2.5. update

Usage:

```
am> update AdaptiveRiskModule --global --body body
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "general" : {
          "type" : "object",
          "title" : "General",
          "propertyOrder" : 0,
          "properties" : {
            "riskThreshold" : {
              "title" : "Risk Threshold",
              "description" : "If the risk threshold value is not reached after executing the
different tests, the authentication is considered to be successful.<br><br>Associated with many
of the adaptive risk checks is a score; if a check does not passes then the score is added to the
current running total. The final score is then compared with the <i>Risk Threshold</i>, if the score
is lesser than said threshold the module will be successful. ",
              "propertyOrder" : 200,
              "required" : true,
              "type" : "integer",
              "exampleValue" : ""
            },
            "authenticationLevel" : {
              "title" : "Authentication Level",
              "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
              "propertyOrder" : 100,
              "required" : true,
              "type" : "integer",
              "exampleValue" : ""
            }
          }
        },
        "knowncookie" : {
          "type" : "object",
          "title" : "Known Cookie",
          "propertyOrder" : 4,
          "properties" : {
            "knownCookieValue" : {
              "title" : "Cookie Value",
              "description" : "The value to be set on the cookie.",
              "propertyOrder" : 1800,
              "required" : true,
              "type" : "string",
              "exampleValue" : ""
            }
          },
          "createKnownCookieOnSuccessfulLogin" : {
            "title" : "Save Cookie Value on Successful Login",
            "description" : "The cookie will be created on the client after successful
login<br><br>The Adaptive Risk Post Authentication Plug-in will set the cookie on the client
response",
            "propertyOrder" : 1900,
            "required" : true,
            "type" : "boolean",

```

```

    "exampleValue" : ""
  },
  "knownCookieName" : {
    "title" : "Cookie Name",
    "description" : "The name of the cookie to set on the client.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "knownCookieScore" : {
    "title" : "Score",
    "description" : "The amount to increment the score if this check fails.",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "knownCookieCheckEnabled" : {
    "title" : "Cookie Value Check",
    "description" : "Enables the checking of a known cookie value in the client
request<br><br>If this check is enabled, the check looks for a known cookie in the client request. If
the cookie exists and has the correct value then the check will pass. ",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "invertKnownCookieScore" : {
    "title" : "Invert Result",
    "description" : "If the check succeeds the score will be included in the total, for
failure the score will not be incremented.",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"authfailed" : {
  "type" : "object",
  "title" : "Failed Authentications",
  "propertyOrder" : 1,
  "properties" : {
    "failureScore" : {
      "title" : "Score",
      "description" : "The amount to increment the score if this check fails.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "invertFailureScore" : {
      "title" : "Invert Result",
      "description" : "If the check succeeds the score will be included in the total, for
failure the score will not be incremented.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "boolean",

```

```

        "exampleValue" : ""
    },
    "failedAuthenticationCheckEnabled" : {
        "title" : "Failed Authentication Check",
        "description" : "Checks if the user has past authentication failures.<br><br>Check if
the OpenAM account lockout mechanism has recorded past authentication failures for the user.<br><br>
<i></i>For this check to function, Account Lockout must be enabled.",
        "propertyOrder" : 300,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"lastlogin" : {
    "type" : "object",
    "title" : "Time Since Last Login",
    "propertyOrder" : 6,
    "properties" : {
        "invertTimeSinceLastLoginScore" : {
            "title" : "Invert Result",
            "description" : "If the check succeeds the score will be included in the total, for
failure the score will not be incremented.",
            "propertyOrder" : 2700,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "timeSinceLastLoginScore" : {
            "title" : "Score",
            "description" : "The amount to increment the score if this check fails.",
            "propertyOrder" : 2600,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "saveLastLoginTimeOnSuccessfulLogin" : {
            "title" : "Save time of Successful Login",
            "description" : "The last login time will be saved in a client cookie<br><br>The
Adaptive Risk Post Authentication Plug-in will update the last login time",
            "propertyOrder" : 2500,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "timeSinceLastLoginCheckEnabled" : {
            "title" : "Time since Last login Check",
            "description" : "Enables the checking of the last time the user successfully
authenticated.<br><br>If this check is enabled, the check ensures the user has successfully
authenticated within a given interval. If the interval has been exceeded the check will fail. The
last authentication for the user is stored in a client cookie.",
            "propertyOrder" : 2200,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "timeSinceLastLoginCookieName" : {
            "title" : "Cookie Name",

```

```

        "description" : "The name of the cookie used to store the time of the last successful
authentication.",
        "propertyOrder" : 2300,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "maxTimeSinceLastLogin" : {
        "title" : "Max Time since Last login",
        "description" : "The maximum number of days that can elapse before this test.",
        "propertyOrder" : 2400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"iphistory" : {
    "type" : "object",
    "title" : "IP Address History",
    "propertyOrder" : 3,
    "properties" : {
        "ipHistoryCount" : {
            "title" : "History size",
            "description" : "The number of client IP addresses to save in the history list.",
            "propertyOrder" : 1100,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "invertIPHHistoryScore" : {
            "title" : "Invert Result",
            "description" : "If the check succeeds the score will be included in the total, for
failure the score will not be incremented.",
            "propertyOrder" : 1500,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "saveSuccessfulIP" : {
            "title" : "Save Successful IP Address",
            "description" : "The IP History list will be updated in the data store<br><br>The
Adaptive Risk Post Authentication Plug-in will update the IP history list if the overall
authentication is successful.",
            "propertyOrder" : 1300,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "ipHistoryProfileAttribute" : {
            "title" : "Profile Attribute Name",
            "description" : "The name of the attribute used to store the IP history list in the data
store.<br><br>IP history list is stored in the Data Store meaning your Data Store should be able
to store values under the configured attribute name. If you're using a directory server as backend,
make sure your Data Store configuration contains the necessary objectclass and attribute related
settings.",
            "propertyOrder" : 1200,
            "required" : true,
            "type" : "string",

```



```

    "exampleValue" : ""
  },
  "ipHistoryScore" : {
    "title" : "Score",
    "description" : "The amount to increment the score if this check fails.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "ipHistoryCheckEnabled" : {
    "title" : "IP History Check",
    "description" : "Enables the checking of client IP address against a list of past IP
addresses.<br><br>If this check is enabled; a set number of past IP addresses used by the client to
access OpenAM is recorded in the user profile. This check passes if the current client IP address
is present in the history list. If the IP address is not present, the check fails and the IP address
is added to list if the overall authentication is successful (causing the oldest IP address to be
removed).",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"devicecookie" : {
  "type" : "object",
  "title" : "Device Cookie",
  "propertyOrder" : 5,
  "properties" : {
    "invertDeviceCookieScore" : {
      "title" : "Invert Result",
      "description" : "If the check succeeds the score will be included in the total, for
failure the score will not be incremented.",
      "propertyOrder" : 3700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "deviceCookieScore" : {
      "title" : "Score",
      "description" : "The amount to increment the score if this check fails.",
      "propertyOrder" : 3600,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "saveDeviceCookieValueOnSuccessfulLogin" : {
      "title" : "Save Device Registration on Successful Login",
      "description" : "Set the device cookie on the client response<br><br>The Adaptive Risk
Post Authentication Plug-in will set the device cookie on the client response",
      "propertyOrder" : 3500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  },
  "deviceCookieName" : {
    "title" : "Cookie Name",

```

```

        "description" : "The name of the cookie to be checked for (and optionally set) on the
client request",
        "propertyOrder" : 3400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "deviceCookieCheckEnabled" : {
        "title" : "Device Registration Cookie Check",
        "description" : "Enables the checking of the client request for a known
cookie.<br><br>If this check is enabled, the check will pass if the client request contains the named
cookie.",
        "propertyOrder" : 3300,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
},
"attributecheck" : {
    "type" : "object",
    "title" : "Profile Attribute",
    "propertyOrder" : 7,
    "properties" : {
        "invertProfileRiskAttributeScore" : {
            "title" : "Invert Result",
            "description" : "If the check succeeds the score will be included in the total, for
failure the score will not be incremented.",
            "propertyOrder" : 3200,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "profileRiskAttributeCheckEnabled" : {
            "title" : "Profile Risk Attribute check",
            "description" : "Enables the checking of the user profile for a matching attribute
and value.<br><br>If this check is enabled, the check will pass if the users profile contains the
required risk attribute and value.",
            "propertyOrder" : 2800,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "profileRiskAttributeValue" : {
            "title" : "Attribute Value",
            "description" : "The required value of the named attribute.",
            "propertyOrder" : 3000,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "profileRiskAttributeScore" : {
            "title" : "Score",
            "description" : "The amount to increment the score if this check fails.",
            "propertyOrder" : 3100,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        }
    }
},

```

```

        "profileRiskAttributeName" : {
            "title" : "Attribute Name",
            "description" : "The name of the attribute to retrieve from the user profile in the data
store.",
            "propertyOrder" : 2900,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    },
    "geolocation" : {
        "type" : "object",
        "title" : "Geo Location",
        "propertyOrder" : 8,
        "properties" : {
            "invertGeolocationScore" : {
                "title" : "Invert Result",
                "description" : "If the check succeeds the score will be included in the total, for
failure the score will not be incremented.",
                "propertyOrder" : 4200,
                "required" : true,
                "type" : "boolean",
                "exampleValue" : ""
            },
            "geolocationScore" : {
                "title" : "Score",
                "description" : "The amount to increment the score if this check fails.",
                "propertyOrder" : 4100,
                "required" : true,
                "type" : "integer",
                "exampleValue" : ""
            },
            "geolocationCheckEnabled" : {
                "title" : "Geolocation Country Code Check",
                "description" : "Enables the checking of the client IP address against the geolocation
database.<br><br>The geolocation database associates IP addresses against their known location. This
check passes if the country associated with the client IP address is matched against the list of
valid country codes.<br><br>The geolocation database is available in binary format at <a href=
'http://www.maxmind.com/app/country' target='_blank'>MaxMind</a>.",
                "propertyOrder" : 3800,
                "required" : true,
                "type" : "boolean",
                "exampleValue" : ""
            },
            "geolocationValidCountryCodes" : {
                "title" : "Valid Country Codes",
                "description" : "The list of country codes that are considered as valid locations for
client IPs.<br><br>The list is made up of country codes separated by a | character; for example:<br>
<code>gb|us|no|fr</code>",
                "propertyOrder" : 4000,
                "required" : true,
                "type" : "string",
                "exampleValue" : ""
            },
            "geolocationDatabaseLocation" : {
                "title" : "Geolocation Database location",

```

```

        "description" : "The path to the location of the GEO location database.<br><br>The
        Geolocation database is not distributed with OpenAM, you can get it in binary format from <a href=
        \"http://www.maxmind.com/app/country\" target=\"_blank\">MaxMind</a>.",
        "propertyOrder" : 3900,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"requestheader" : {
    "type" : "object",
    "title" : "Request Header",
    "propertyOrder" : 9,
    "properties" : {
        "invertRequestHeaderScore" : {
            "title" : "Invert Result",
            "description" : "If the check succeeds the score will be included in the total, for
failure the score will not be incremented.",
            "propertyOrder" : 4700,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "requestHeaderValue" : {
            "title" : "Request Header Value",
            "description" : "The required value of the named HTTP header.",
            "propertyOrder" : 4500,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "requestHeaderCheckEnabled" : {
            "title" : "Request Header Check",
            "description" : "Enables the checking of the client request for a known header name and
value.<br><br>The request header check will pass if the client request contains the required named
header and value.",
            "propertyOrder" : 4300,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "requestHeaderName" : {
            "title" : "Request Header Name",
            "description" : "The name of the required HTTP header ",
            "propertyOrder" : 4400,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "requestHeaderScore" : {
            "title" : "Score",
            "description" : "The amount to increment the score if this check fails.",
            "propertyOrder" : 4600,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        }
    }
}
}

```

```

    },
    "iprange" : {
      "type" : "object",
      "title" : "IP Address Range",
      "propertyOrder" : 2,
      "properties" : {
        "ipRangeCheckEnabled" : {
          "title" : "IP Range Check",
          "description" : "Enables the checking of the client IP address against a list of IP
addresses.<br><br>The IP range check compares the IP of the client against a list of IP addresses, if
the client IP is found within said list the check is successful.",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "ipRangeScore" : {
          "title" : "Score",
          "description" : "The amount to increment the score if this check fails.",
          "propertyOrder" : 800,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "ipRange" : {
          "title" : "IP Range",
          "description" : "The list of IP address to compare against the client IP
address.<br><br>The format of the IP address is as follows:<br><br><ul><li>Single IP address:
<code>172.16.90.1</code></li><li>CIDR notation: <code>172.16.90.0/24</code></li><li>IP net-block with
netmask: <code>172.16.90.0:255.255.255.0</code></li></ul>",
          "propertyOrder" : 700,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "invertIPRangeScoreEnabled" : {
          "title" : "Invert Result",
          "description" : "If the check succeeds the score will be included in the total, for
failure the score will not be incremented.",
          "propertyOrder" : 900,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        }
      }
    },
    "type" : "object",
    "title" : "Realm Defaults"
  }
}

```

1.6. AdvancedProperties

1.6.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/{serverName}/properties/advanced`

Resource version: `1.0`

1.6.1.1. read

Usage:

```
am> read AdvancedProperties --global --serverName serverName
```

Parameters:

--serverName

An object of property key-value pairs

1.6.1.2. update

Usage:

```
am> update AdvancedProperties --global --serverName serverName --body body
```

Parameters:

--serverName

An object of property key-value pairs

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "patternProperties" : {
    ".+" : {
      "type" : "string",
      "title" : "Value",
      "description" : "Any string value"
    }
  },
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "An object of property key-value pairs",
  "type" : "object",
  "title" : "Advanced Properties"
}
```

1.7. AgentGroups

1.7.1. Realm Operations

Aggregating Agent Groups handler that is responsible for querying the aggregating agent groups

Resource path: `/realm-config/agents/groups`

Resource version: `1.0`

1.7.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AgentGroups --realm Realm --actionName getAllTypes
```

1.7.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AgentGroups --realm Realm --actionName getCreatableTypes
```

1.7.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AgentGroups --realm Realm --actionName nextdescendents
```

1.7.1.4. query

Querying the aggregating agent groups

Usage:

```
am> query AgentGroups --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.8. AgentService

1.8.1. Global Operations

Resource path: `/global-config/agents/AgentService`

Resource version: `1.0`

1.8.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AgentService --global --actionName getAllTypes
```

1.8.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AgentService --global --actionName getCreatableTypes
```

1.8.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AgentService --global --actionName nextdescendents
```

1.8.1.4. read

Usage:

```
am> read AgentService --global
```

1.8.1.5. update

Usage:

```
am> update AgentService --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object"
}
```

1.9. Agents

1.9.1. Realm Operations

Aggregating Agents handler that is responsible for querying the aggregating agents

Resource path: `/realm-config/agents`

Resource version: `1.0`

1.9.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Agents --realm Realm --actionName getAllTypes
```

1.9.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Agents --realm Realm --actionName getCreatableTypes
```

1.9.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Agents --realm Realm --actionName nextdescendents
```

1.9.1.4. query

Querying the aggregating agents

Usage:

```
am> query Agents --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.9.2. Global Operations

Global and default configuration for agents

Resource path: `/global-config/agents`

Resource version: `1.0`

1.9.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Agents --global --actionName getAllTypes
```

1.9.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Agents --global --actionName getCreatableTypes
```

1.9.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Agents --global --actionName nextdescendents
```

1.10. AmsterModule

1.10.1. Realm Operations

Resource path: `/realm-config/authentication/modules/amster`

Resource version: 1.0

1.10.1.1. create

Usage:

```
am> create AmsterModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "enabled" : {
      "title" : "Enabled",
      "description" : "If not enabled, prevents PKI login using the Amster module.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "authorizedKeys" : {
      "title" : "Authorized Keys",
      "description" : "The location of the authorized_keys file (which has the same format as an
OpenSSH authorized_keys file) to use to validate remote Amster connections.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.10.1.2. delete

Usage:

```
am> delete AmsterModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.10.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AmsterModule --realm Realm --actionName getAllTypes
```

1.10.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AmsterModule --realm Realm --actionName getCreatableTypes
```

1.10.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AmsterModule --realm Realm --actionName nextdescendents
```

1.10.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query AmsterModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.10.1.7. read

Usage:

```
am> read AmsterModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.10.1.8. update

Usage:

```
am> update AmsterModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "enabled" : {
      "title" : "Enabled",
      "description" : "If not enabled, prevents PKI login using the Amster module.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "authorizedKeys" : {
      "title" : "Authorized Keys",
      "description" : "The location of the authorized_keys file (which has the same format as an
OpenSSH authorized_keys file) to use to validate remote Amster connections.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.10.2. Global Operations

Resource path: `/global-config/authentication/modules/amster`

Resource version: `1.0`

1.10.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AmsterModule --global --actionName getAllTypes
```

1.10.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AmsterModule --global --actionName getCreatableTypes
```

1.10.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AmsterModule --global --actionName nextdescendents
```

1.10.2.4. read

Usage:

```
am> read AmsterModule --global
```

1.10.2.5. update

Usage:

```
am> update AmsterModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "If not enabled, prevents PKI login using the Amster module.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "authorizedKeys" : {
          "title" : "Authorized Keys",
          "description" : "The location of the authorized_keys file (which has the same format as an
OpenSSH authorized_keys file) to use to validate remote Amster connections.",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        }
      }
    },
    "type" : "object",
    "title" : "Realm Defaults"
  }
}
```

1.11. AnonymousModule

1.11.1. Realm Operations

Resource path: [/realm-config/authentication/modules/anonymous](#)

Resource version: [1.0](#)

1.11.1.1. create

Usage:

```
am> create AnonymousModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "validAnonymousUsers" : {
      "title" : "Valid Anonymous Users",
      "description" : "List of accounts that are allowed to login without providing
credentials.<br><br>Any username on this list will be allows anonymous access to OpenAM. Usernames
listed here must have matching profiles in the data store or the user profile requirement must be
disabled. The username can be specified during anonymous authentication as follows:<br><br><code>/
openam/UI/Login?module=anonymous&IDToken1=<i>username</i></code>",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "caseSensitiveUsernameMatchingEnabled" : {
      "title" : "Case Sensitive User IDs",
      "description" : "If enabled, username matching will be case sensitive.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "defaultAnonymousUsername" : {
      "title" : "Default Anonymous User Name",
      "description" : "The default username to use if no username is supplied during authentication.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```



```
}  
}
```

1.11.1.2. delete

Usage:

```
am> delete AnonymousModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.11.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AnonymousModule --realm Realm --actionName getAllTypes
```

1.11.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AnonymousModule --realm Realm --actionName getCreatableTypes
```

1.11.1.5. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AnonymousModule --realm Realm --actionName nextdescendants
```

1.11.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query AnonymousModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.11.1.7. read

Usage:

```
am> read AnonymousModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.11.1.8. update

Usage:

```
am> update AnonymousModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "validAnonymousUsers" : {
      "title" : "Valid Anonymous Users",
      "description" : "List of accounts that are allowed to login without providing
credentials.<br><br>Any username on this list will be allows anonymous access to OpenAM. Usernames
listed here must have matching profiles in the data store or the user profile requirement must be
disabled. The username can be specified during anonymous authentication as follows:<br><br><code>/
openam/UI/Login?module=anonymous&IDToken1=<i>username</i></code>",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      }
    },
  },
}
```

```

    "type" : "array",
    "exampleValue" : ""
  },
  "caseSensitiveUsernameMatchingEnabled" : {
    "title" : "Case Sensitive User IDs",
    "description" : "If enabled, username matching will be case sensitive.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "defaultAnonymousUsername" : {
    "title" : "Default Anonymous User Name",
    "description" : "The default username to use if no username is supplied during authentication.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}

```

1.11.2. Global Operations

Resource path: `/global-config/authentication/modules/anonymous`

Resource version: `1.0`

1.11.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AnonymousModule --global --actionName getAllTypes
```

1.11.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AnonymousModule --global --actionName getCreatableTypes
```

1.11.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AnonymousModule --global --actionName nextdescendents
```

1.11.2.4. read

Usage:

```
am> read AnonymousModule --global
```

1.11.2.5. update

Usage:

```
am> update AnonymousModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "defaultAnonymousUsername" : {
          "title" : "Default Anonymous User Name",
          "description" : "The default username to use if no username is supplied during authentication.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    }
  }
}
```

```

    },
    "validAnonymousUsers" : {
      "title" : "Valid Anonymous Users",
      "description" : "List of accounts that are allowed to login without providing
credentials.<br><br>Any username on this list will be allows anonymous access to OpenAM. Usernames
listed here must have matching profiles in the data store or the user profile requirement must be
disabled. The username can be specified during anonymous authentication as follows:<br/><br/><code>/
openam/UI/Login?module=anonymous&IDToken1=<i>username</i></code>",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "caseSensitiveUsernameMatchingEnabled" : {
      "title" : "Case Sensitive User IDs",
      "description" : "If enabled, username matching will be case sensitive.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  },
  "type" : "object",
  "title" : "Realm Defaults"
}
}
}

```

1.12. AnonymousUserMapping

1.12.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/AnonymousUserNode`

Resource version: `1.0`

1.12.1.1. create

Usage:

```
am> create AnonymousUserMapping --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "anonymousUserName" : {
      "title" : "Anonymous User Name",
      "description" : "The username of the user that will represent the anonymous user. This user
account must already exist in the realm.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "anonymousUserName" ]
}
```

1.12.1.2. delete

Usage:

```
am> delete AnonymousUserMapping --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.12.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AnonymousUserMapping --realm Realm --actionName getAllTypes
```

1.12.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AnonymousUserMapping --realm Realm --actionName getCreatableTypes
```

1.12.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action AnonymousUserMapping --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.12.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AnonymousUserMapping --realm Realm --actionName nextdescendents
```

1.12.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query AnonymousUserMapping --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.12.1.8. read

Usage:

```
am> read AnonymousUserMapping --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.12.1.9. update

Usage:

```
am> update AnonymousUserMapping --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "anonymousUserName" : {
      "title" : "Anonymous User Name",
      "description" : "The username of the user that will represent the anonymous user. This user
account must already exist in the realm.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "anonymousUserName" ]
}
```

1.13. ApplicationTypes

1.13.1. Realm Operations

Service for reading and listing the available application types. Application types act as templates for policy sets, and define how to compare resources and index policies. OpenAM provides a default application type that represents web resources called iPlanetAMWebAgentService

Resource path: [/applicationtypes](#)

Resource version: [1.0](#)

1.13.1.1. query

Lists the application types using a query filter

Usage:


```
am> query ApplicationTypes --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.13.1.2. read

Reads an individual application type by the provided application type name

Usage:

```
am> read ApplicationTypes --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.14. Applications

1.14.1. Realm Operations

Service for manipulating Applications. It supports the CRUDQ operations.

Resource path: [/applications](#)

Resource version: [2.1](#)

1.14.1.1. create

Creates a new Application in a realm

Usage:

```
am> create Applications --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Application schema",
  "type" : "object",
  "title" : "Application",
  "properties" : {
    "name" : {
      "type" : "string",
      "title" : "Name",
      "description" : "Unique application identifier."
    },
    "displayName" : {
      "type" : "string",
      "title" : "Display name",
      "description" : "When defined, it is displayed in the UI instead of application name."
    },
    "description" : {
      "type" : "string",
      "title" : "Description",
      "description" : "String describing the application."
    },
    "applicationType" : {
      "type" : "string",
      "title" : "Application type",
      "description" : "Name of the application type used as a template for the policy set."
    },
    "conditions" : {
      "type" : "array",
      "items" : {
        "type" : "string",
        "title" : "Conditions",
        "description" : "Condition types allowed in the context of the policy set."
      }
    },
    "subjects" : {
      "type" : "array",
      "items" : {
        "type" : "string",
        "title" : "Subjects",
        "description" : "Subject types allowed in the context of the policy set."
      }
    },
    "resourceTypeUuids" : {
      "type" : "array",
      "items" : {
        "type" : "string",
        "title" : "Resource type uuids",
        "description" : "A list of the UUIDs of the resource types associated with the policy set."
      }
    },
    "entitlementCombiner" : {
      "type" : "string",
      "title" : "Entitlement combiner",
      "description" : "Name of the decision combiner, such as \"DenyOverride\"."
    }
  }
}
```

```

"searchIndex" : {
  "type" : "string",
  "title" : "Search index",
  "description" : "Class name of the implementation for searching indexes for resource names, such
as \com.sun.identity.entitlement.util.ResourceNameSplitter\" for URL resource names."
},
"saveIndex" : {
  "type" : "string",
  "title" : "Save index",
  "description" : "Class name of the implementation for creating indexes for resource names, such
as \com.sun.identity.entitlement.util.ResourceNameIndexGenerator\" for URL resource names."
},
"resourceComparator" : {
  "type" : "string",
  "title" : "Resource comparator",
  "description" : "Class name of the resource comparator implementation
used in the context of the policy set. The following implementations
are available: \com.sun.identity.entitlement.ExactMatchResourceName\",
\com.sun.identity.entitlement.PrefixResourceName\", \com.sun.identity.entitlement.RegExResourceName
\", \com.sun.identity.entitlement.URLResourceName\"."
},
"attributeNames" : {
  "type" : "array",
  "items" : {
    "type" : "string",
    "title" : "Attribute names",
    "description" : "A list of attribute names such as cn. The list is used to aid policy indexing
and lookup."
  }
},
"createdBy" : {
  "type" : "string",
  "title" : "Created by",
  "description" : "A string containing the universal identifier DN of the subject that created the
application."
},
"lastModifiedBy" : {
  "type" : "string",
  "title" : "Last modified by",
  "description" : "A string containing the universal identifier DN of the subject that most
recently updated the application. If the application has not been modified since it was created, this
will be the same value as createdBy."
},
"creationDate" : {
  "type" : "integer",
  "title" : "Creation date",
  "description" : "An integer containing the creation date and time, in number of seconds since
the Unix Epoch."
},
"lastModifiedDate" : {
  "type" : "integer",
  "title" : "Last modified date",
  "description" : "An integer containing the last modified date and time, in number of seconds
since the Unix Epoch. If the application has not been modified since it was created, this will be the
same value as creationDate."
},
"editable" : {
  "type" : "boolean",
  "title" : "Editable",

```

```
    "description" : "It indicates if application is editable."  
  },  
  "required" : [ "name", "applicationType" ]  
}
```

1.14.1.2. delete

Deletes an individual Application in a realm specified by its name

Usage:

```
am> delete Applications --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.14.1.3. query

Lists all the Applications in a realm

Usage:

```
am> query Applications --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.14.1.4. read

Reads an individual Application in a realm specified by its name

Usage:

```
am> read Applications --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.14.1.5. update

Updates an individual Application in a realm specified by its name

Usage:

```
am> update Applications --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Application schema",
  "type" : "object",
  "title" : "Application",
  "properties" : {
    "name" : {
      "type" : "string",
      "title" : "Name",
      "description" : "Unique application identifier."
    },
    "displayName" : {
      "type" : "string",
      "title" : "Display name",
      "description" : "When defined, it is displayed in the UI instead of application name."
    },
    "description" : {
      "type" : "string",
      "title" : "Description",
      "description" : "String describing the application."
    },
    "applicationType" : {
      "type" : "string",
      "title" : "Application type",
      "description" : "Name of the application type used as a template for the policy set."
    },
    "conditions" : {
      "type" : "array",
      "items" : {
        "type" : "string",
        "title" : "Conditions",
        "description" : "Condition types allowed in the context of the policy set."
      }
    },
    "subjects" : {
      "type" : "array",
      "items" : {
        "type" : "string",
        "title" : "Subjects",
        "description" : "Subject types allowed in the context of the policy set."
      }
    },
    "resourceTypeUuids" : {
      "type" : "array",
      "items" : {
```

```

        "type" : "string",
        "title" : "Resource type uuids",
        "description" : "A list of the UUIDs of the resource types associated with the policy set."
    }
},
"entitlementCombiner" : {
    "type" : "string",
    "title" : "Entitlement combiner",
    "description" : "Name of the decision combiner, such as \"DenyOverride\"."
},
"searchIndex" : {
    "type" : "string",
    "title" : "Search index",
    "description" : "Class name of the implementation for searching indexes for resource names, such
as \"com.sun.identity.entitlement.util.ResourceNameSplitter\" for URL resource names."
},
"saveIndex" : {
    "type" : "string",
    "title" : "Save index",
    "description" : "Class name of the implementation for creating indexes for resource names, such
as \"com.sun.identity.entitlement.util.ResourceNameIndexGenerator\" for URL resource names."
},
"resourceComparator" : {
    "type" : "string",
    "title" : "Resource comparator",
    "description" : "Class name of the resource comparator implementation
used in the context of the policy set. The following implementations
are available: \"com.sun.identity.entitlement.ExactMatchResourceName\",
\"com.sun.identity.entitlement.PrefixResourceName\", \"com.sun.identity.entitlement.RegExResourceName
\", \"com.sun.identity.entitlement.URLResourceName\"."
},
"attributeNames" : {
    "type" : "array",
    "items" : {
        "type" : "string",
        "title" : "Attribute names",
        "description" : "A list of attribute names such as cn. The list is used to aid policy indexing
and lookup."
    }
},
"createdBy" : {
    "type" : "string",
    "title" : "Created by",
    "description" : "A string containing the universal identifier DN of the subject that created the
application."
},
"lastModifiedBy" : {
    "type" : "string",
    "title" : "Last modified by",
    "description" : "A string containing the universal identifier DN of the subject that most
recently updated the application. If the application has not been modified since it was created, this
will be the same value as createdBy."
},
"creationDate" : {
    "type" : "integer",
    "title" : "Creation date",
    "description" : "An integer containing the creation date and time, in number of seconds since
the Unix Epoch."
},
}

```

```
"lastModifiedDate" : {
  "type" : "integer",
  "title" : "Last modified date",
  "description" : "An integer containing the last modified date and time, in number of seconds
since the Unix Epoch. If the application has not been modified since it was created, this will be the
same value as creationDate."
},
"editable" : {
  "type" : "boolean",
  "title" : "Editable",
  "description" : "It indicates if application is editable."
}
},
"required" : [ "name", "applicationType" ]
}
```

1.15. AuditEvent

1.15.1. Realm Operations

Audit events are logged through a realm audit service.

Resource path: `/realm-audit/{topic}`

Resource version: `1.0`

1.15.1.1. create

Create a new audit event, which will be handled and logged by the configured audit service.

Usage:

```
am> create AuditEvent --realm Realm --topic topic --body body
```

Parameters:

--topic

Audit events are logged through a realm audit service.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "The schema contains properties that are common to all topics and some that are
unique to a specific topic. The description of each property indicates which topic the property
applies to.",
  "title" : "Audit event schema",
  "type" : "object",
  "properties" : {
    "_id" : {
```

```
    "title" : "ID",
    "description" : "The ID of the event, used by all topics",
    "type" : "string"
  },
  "timestamp" : {
    "title" : "Timestamp",
    "description" : "The time at which the event occurred, used by all topics",
    "type" : "string"
  },
  "eventName" : {
    "title" : "Event name",
    "description" : "The name of the event, used by all topics",
    "type" : "string"
  },
  "transactionId" : {
    "title" : "Transaction ID",
    "description" : "The transaction ID of the event, used by all topics",
    "type" : "string"
  },
  "userId" : {
    "title" : "User ID",
    "description" : "The ID of the user responsible for the event, used by all topics",
    "type" : "string"
  },
  "trackingIds" : {
    "title" : "Tracking IDs",
    "description" : "The tracking IDs of the event, used by all topics",
    "type" : "array",
    "items" : {
      "id" : "0",
      "type" : "string"
    }
  },
  "component" : {
    "title" : "Component",
    "description" : "The component responsible for the event, used by all topics",
    "type" : "string"
  },
  "realm" : {
    "title" : "Realm",
    "description" : "The realm in which the event occurred, used by all topics",
    "type" : "string"
  },
  "server" : {
    "title" : "Server",
    "description" : "The server details for an access event",
    "type" : "object",
    "properties" : {
      "ip" : {
        "title" : "Server IP address",
        "description" : "The server ip address for an access event",
        "type" : "string"
      },
      "port" : {
        "title" : "Server port",
        "description" : "The server port for an access event",
        "type" : "integer"
      }
    }
  }
}
```



```
},
"client" : {
  "title" : "Client",
  "description" : "The client details for an access event",
  "type" : "object",
  "properties" : {
    "ip" : {
      "title" : "Client IP address",
      "description" : "The client IP address for an access event",
      "type" : "string"
    },
    "port" : {
      "title" : "Client port",
      "description" : "The client port for an access event",
      "type" : "integer"
    }
  }
},
"request" : {
  "title" : "Request",
  "description" : "The request details for an access event",
  "type" : "object",
  "properties" : {
    "protocol" : {
      "title" : "Request protocol",
      "description" : "The request protocol for an access event",
      "type" : "string"
    },
    "operation" : {
      "title" : "Request operation",
      "description" : "The request operation for an access event",
      "type" : "string"
    },
    "detail" : {
      "title" : "Request detail",
      "description" : "The request detail for an access event",
      "type" : "object"
    }
  }
},
"http" : {
  "title" : "Http details",
  "description" : "The Http details for an access event",
  "type" : "object",
  "properties" : {
    "request" : {
      "title" : "Http request",
      "description" : "The http request for an access event",
      "type" : "object",
      "properties" : {
        "secure" : {
          "title" : "Http secure",
          "description" : "The http secure property for an access event",
          "type" : "boolean"
        }
      }
    },
    "method" : {
      "title" : "Http method",
      "description" : "The http method for an access event",
      "type" : "string"
    }
  }
}
```

```
    },
    "path" : {
      "title" : "Http path",
      "description" : "The http path for an access event",
      "type" : "string"
    },
  },
  "queryParameters" : {
    "title" : "Http query parameters",
    "description" : "The http query parameters for an access event",
    "type" : "object",
    "additionalProperties" : {
      "type" : "array",
      "items" : {
        "type" : "string"
      }
    }
  },
  "headers" : {
    "title" : "Http headers",
    "description" : "The http headers for an access event",
    "type" : "object",
    "additionalProperties" : {
      "type" : "array",
      "items" : {
        "type" : "string"
      }
    }
  },
  "cookies" : {
    "title" : "Http cookies",
    "description" : "The http cookies for an access event",
    "type" : "object",
    "additionalProperties" : {
      "type" : "string"
    }
  }
},
"response" : {
  "title" : "Http response",
  "description" : "The http response for an access event",
  "type" : "object",
  "properties" : {
    "headers" : {
      "title" : "Http request headers",
      "description" : "The http request headers for an access event",
      "type" : "object",
      "additionalProperties" : {
        "type" : "array",
        "items" : {
          "type" : "string"
        }
      }
    }
  }
}
},
"response" : {
```

```
"title" : "Response",
"description" : "The response details for an access event",
"type" : "object",
"properties" : {
  "status" : {
    "title" : "Response status",
    "description" : "The response status for an access event",
    "type" : "string"
  },
  "statusCode" : {
    "title" : "Response status code",
    "description" : "The response status code for an access event",
    "type" : "string"
  },
  "detail" : {
    "title" : "Response detail",
    "description" : "The response detail for an access event",
    "type" : "object"
  },
  "elapsedTime" : {
    "title" : "Response elapsed time",
    "description" : "The response elapsedTime for an access event",
    "type" : "integer"
  },
  "elapsedTimeUnits" : {
    "title" : "Response elapsed time units",
    "description" : "The response elapsed time units for an access event",
    "type" : "string"
  }
}
},
"runAs" : {
  "title" : "Run as",
  "description" : "What the change that triggered an activity or config event was run as",
  "type" : "string"
},
"objectId" : {
  "title" : "Object ID",
  "description" : "The object ID of the change that triggered an activity or config event",
  "type" : "string"
},
"operation" : {
  "title" : "Operation",
  "description" : "The operation that triggered an activity or config event",
  "type" : "string"
},
"before" : {
  "title" : "Before state",
  "description" : "The state before an activity or config event occurred",
  "type" : "object"
},
"after" : {
  "title" : "After state",
  "description" : "The state after an activity or config event occurred",
  "type" : "object"
},
"changedFields" : {
  "title" : "Changed fields",
  "description" : "The changed fields after an activity or config event occurred",
```

```

        "type" : "array",
        "items" : {
            "id" : "1",
            "type" : "string"
        }
    },
    "revision" : {
        "title" : "Revision",
        "description" : "The revision for an activity or config event",
        "type" : "string"
    },
    "result" : {
        "title" : "Result",
        "description" : "The result of the authentication event",
        "type" : "string"
    },
    "principal" : {
        "title" : "Principal",
        "description" : "The principal responsible for the authentication event",
        "type" : "array",
        "items" : {
            "type" : "string"
        }
    },
    "context" : {
        "title" : "Context",
        "description" : "The context of an authentication event",
        "type" : "object",
        "properties" : { }
    },
    "entries" : {
        "title" : "Entries",
        "description" : "The entries for an authentication event",
        "type" : "array",
        "items" : {
            "type" : "object",
            "properties" : {
                "moduleId" : {
                    "title" : "Module ID",
                    "description" : "The module ID for the authentication event",
                    "type" : "string"
                },
                "result" : {
                    "title" : "Module result",
                    "description" : "The result of the module authentication event",
                    "type" : "string"
                },
                "info" : {
                    "title" : "Entries information",
                    "description" : "The entries information for an authentication event",
                    "type" : "object",
                    "properties" : { }
                }
            }
        }
    },
    "required" : [ "transactionId", "timestamp" ]

```

```
}
```

1.15.2. Global Operations

Audit events are logged through the global audit service.

Resource path: `/global-audit/{topic}`

Resource version: `1.0`

1.15.2.1. create

Create a new audit event, which will be handled and logged by the configured audit service.

Usage:

```
am> create AuditEvent --global --topic topic --body body
```

Parameters:

--topic

Audit events are logged through the global audit service.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "The schema contains properties that are common to all topics and some that are
  unique to a specific topic. The description of each property indicates which topic the property
  applies to.",
  "title" : "Audit event schema",
  "type" : "object",
  "properties" : {
    "_id" : {
      "title" : "ID",
      "description" : "The ID of the event, used by all topics",
      "type" : "string"
    },
    "timestamp" : {
      "title" : "Timestamp",
      "description" : "The time at which the event occurred, used by all topics",
      "type" : "string"
    },
    "eventName" : {
      "title" : "Event name",
      "description" : "The name of the event, used by all topics",
      "type" : "string"
    },
    "transactionId" : {
      "title" : "Transaction ID",
      "description" : "The transaction ID of the event, used by all topics",
      "type" : "string"
    }
  }
}
```

```
},
"userId" : {
  "title" : "User ID",
  "description" : "The ID of the user responsible for the event, used by all topics",
  "type" : "string"
},
"trackingIds" : {
  "title" : "Tracking IDs",
  "description" : "The tracking IDs of the event, used by all topics",
  "type" : "array",
  "items" : {
    "id" : "0",
    "type" : "string"
  }
},
"component" : {
  "title" : "Component",
  "description" : "The component responsible for the event, used by all topics",
  "type" : "string"
},
"realm" : {
  "title" : "Realm",
  "description" : "The realm in which the event occurred, used by all topics",
  "type" : "string"
},
"server" : {
  "title" : "Server",
  "description" : "The server details for an access event",
  "type" : "object",
  "properties" : {
    "ip" : {
      "title" : "Server IP address",
      "description" : "The server ip address for an access event",
      "type" : "string"
    },
    "port" : {
      "title" : "Server port",
      "description" : "The server port for an access event",
      "type" : "integer"
    }
  }
},
"client" : {
  "title" : "Client",
  "description" : "The client details for an access event",
  "type" : "object",
  "properties" : {
    "ip" : {
      "title" : "Client IP address",
      "description" : "The client IP address for an access event",
      "type" : "string"
    },
    "port" : {
      "title" : "Client port",
      "description" : "The client port for an access event",
      "type" : "integer"
    }
  }
},
}
```

```
"request" : {
  "title" : "Request",
  "description" : "The request details for an access event",
  "type" : "object",
  "properties" : {
    "protocol" : {
      "title" : "Request protocol",
      "description" : "The request protocol for an access event",
      "type" : "string"
    },
    "operation" : {
      "title" : "Request operation",
      "description" : "The request operation for an access event",
      "type" : "string"
    },
    "detail" : {
      "title" : "Request detail",
      "description" : "The request detail for an access event",
      "type" : "object"
    }
  }
},
"http" : {
  "title" : "Http details",
  "description" : "The Http details for an access event",
  "type" : "object",
  "properties" : {
    "request" : {
      "title" : "Http request",
      "description" : "The http request for an access event",
      "type" : "object",
      "properties" : {
        "secure" : {
          "title" : "Http secure",
          "description" : "The http secure property for an access event",
          "type" : "boolean"
        },
        "method" : {
          "title" : "Http method",
          "description" : "The http method for an access event",
          "type" : "string"
        },
        "path" : {
          "title" : "Http path",
          "description" : "The http path for an access event",
          "type" : "string"
        },
        "queryParameters" : {
          "title" : "Http query parameters",
          "description" : "The http query parameters for an access event",
          "type" : "object",
          "additionalProperties" : {
            "type" : "array",
            "items" : {
              "type" : "string"
            }
          }
        }
      }
    },
    "headers" : {
```

```

        "title" : "Http headers",
        "description" : "The http headers for an access event",
        "type" : "object",
        "additionalProperties" : {
            "type" : "array",
            "items" : {
                "type" : "string"
            }
        }
    },
    "cookies" : {
        "title" : "Http cookies",
        "description" : "The http cookies for an access event",
        "type" : "object",
        "additionalProperties" : {
            "type" : "string"
        }
    }
},
"response" : {
    "title" : "Http response",
    "description" : "The http response for an access event",
    "type" : "object",
    "properties" : {
        "headers" : {
            "title" : "Http request headers",
            "description" : "The http request headers for an access event",
            "type" : "object",
            "additionalProperties" : {
                "type" : "array",
                "items" : {
                    "type" : "string"
                }
            }
        }
    }
},
"response" : {
    "title" : "Response",
    "description" : "The response details for an access event",
    "type" : "object",
    "properties" : {
        "status" : {
            "title" : "Response status",
            "description" : "The response status for an access event",
            "type" : "string"
        },
        "statusCode" : {
            "title" : "Response status code",
            "description" : "The response status code for an access event",
            "type" : "string"
        }
    },
    "detail" : {
        "title" : "Response detail",
        "description" : "The response detail for an access event",
        "type" : "object"
    }
}

```



```
    },
    "elapsedTime" : {
      "title" : "Response elapsed time",
      "description" : "The response elapsedTime for an access event",
      "type" : "integer"
    },
    "elapsedTimeUnits" : {
      "title" : "Response elapsed time units",
      "description" : "The response elapsed time units for an access event",
      "type" : "string"
    }
  }
},
"runAs" : {
  "title" : "Run as",
  "description" : "What the change that triggered an activity or config event was run as",
  "type" : "string"
},
"objectId" : {
  "title" : "Object ID",
  "description" : "The object ID of the change that triggered an activity or config event",
  "type" : "string"
},
"operation" : {
  "title" : "Operation",
  "description" : "The operation that triggered an activity or config event",
  "type" : "string"
},
"before" : {
  "title" : "Before state",
  "description" : "The state before an activity or config event occurred",
  "type" : "object"
},
"after" : {
  "title" : "After state",
  "description" : "The state after an activity or config event occurred",
  "type" : "object"
},
"changedFields" : {
  "title" : "Changed fields",
  "description" : "The changed fields after an activity or config event occurred",
  "type" : "array",
  "items" : {
    "id" : "1",
    "type" : "string"
  }
},
"revision" : {
  "title" : "Revision",
  "description" : "The revision for an activity or config event",
  "type" : "string"
},
"result" : {
  "title" : "Result",
  "description" : "The result of the authentication event",
  "type" : "string"
},
"principal" : {
  "title" : "Principal",
```

```
    "description" : "The principal responsible for the authentication event",
    "type" : "array",
    "items" : {
      "type" : "string"
    }
  },
  "context" : {
    "title" : "Context",
    "description" : "The context of an authentication event",
    "type" : "object",
    "properties" : { }
  },
  "entries" : {
    "title" : "Entries",
    "description" : "The entries for an authentication event",
    "type" : "array",
    "items" : {
      "type" : "object",
      "properties" : {
        "moduleId" : {
          "title" : "Module ID",
          "description" : "The module ID for the authentication event",
          "type" : "string"
        },
        "result" : {
          "title" : "Module result",
          "description" : "The result of the module authentication event",
          "type" : "string"
        },
        "info" : {
          "title" : "Entries information",
          "description" : "The entries information for an authentication event",
          "type" : "object",
          "properties" : { }
        }
      }
    }
  },
  "required" : [ "transactionId", "timestamp" ]
}
```

1.16. AuditLogging

1.16.1. Realm Operations

Resource path: `/realm-config/services/audit`

Resource version: `1.0`

1.16.1.1. create

Usage:

```
am> create AuditLogging --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "auditEnabled" : {
      "title" : "Audit logging",
      "description" : "Enable audit logging in OpenAM.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "fieldFilterPolicy" : {
      "title" : "Field exclusion policies",
      "description" : "A list of fields or values (JSON pointers) to exclude from the audit
event.<br><br>To specify a field or value within a field to be filtered out of the event, start
the pointer with the event topic, for example access, activity, authentication, or config, followed
by the field name or the path to the value in the field.<p><p>For example, to filter out the
<code>userId</code> field in an access event the pointer will be <code>/access/userId</code>.<p>To
filter out the <code>content-type</code> value in the <code>http.request.headers</code> field the
pointer will be <code>/access/http/request/headers/content-type</code>.<p>Only values that are made
up of JSON strings can be manipulated in this way.",
      "propertyOrder" : 200,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.16.1.2. delete

Usage:

```
am> delete AuditLogging --realm Realm
```

1.16.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuditLogging --realm Realm --actionName getAllTypes
```

1.16.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuditLogging --realm Realm --actionName getCreatableTypes
```

1.16.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuditLogging --realm Realm --actionName nextdescendents
```

1.16.1.6. read

Usage:

```
am> read AuditLogging --realm Realm
```

1.16.1.7. update

Usage:

```
am> update AuditLogging --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "auditEnabled" : {
      "title" : "Audit logging",
      "description" : "Enable audit logging in OpenAM.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "fieldFilterPolicy" : {
      "title" : "Field exclusion policies",
      "description" : "A list of fields or values (JSON pointers) to exclude from the audit event.<br><br>To specify a field or value within a field to be filtered out of the event, start the pointer with the event topic, for example access, activity, authentication, or config, followed by the field name or the path to the value in the field.<p><p>For example, to filter out the <code>userId</code> field in an access event the pointer will be <code>/access/userId</code>.<p>To filter out the <code>content-type</code> value in the <code>http.request.headers</code> field the pointer will be <code>/access/http/request/headers/content-type</code>.<p>Only values that are made up of JSON strings can be manipulated in this way.",
      "propertyOrder" : 200,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}

```

1.16.2. Global Operations

Resource path: `/global-config/services/audit`

Resource version: `1.0`

1.16.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuditLogging --global --actionName getAllTypes
```

1.16.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuditLogging --global --actionName getCreatableTypes
```

1.16.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuditLogging --global --actionName nextdescendents
```

1.16.2.4. read

Usage:

```
am> read AuditLogging --global
```

1.16.2.5. update

Usage:

```
am> update AuditLogging --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "auditEnabled" : {
      "title" : "Audit logging",
      "description" : "Enable audit logging in OpenAM.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "fieldFilterPolicy" : {
      "title" : "Field exclusion policies",
      "description" : "A list of fields or values (JSON pointers) to exclude from the audit
event.<br><br>To specify a field or value within a field to be filtered out of the event, start
the pointer with the event topic, for example access, activity, authentication, or config, followed
by the field name or the path to the value in the field.<p><p>For example, to filter out the
<code>userId</code> field in an access event the pointer will be <code>/access/userId</code>.<p>To
filter out the <code>content-type</code> value in the <code>http.request.headers</code> field the
pointer will be <code>/access/http/request/headers/content-type</code>.<p>Only values that are made
up of JSON strings can be manipulated in this way.",
      "propertyOrder" : 200,
      "required" : false,
```

```

    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "defaults" : {
    "properties" : {
      "fieldFilterPolicy" : {
        "title" : "Field exclusion policies",
        "description" : "A list of fields or values (JSON pointers) to exclude from the audit event.<br><br>To specify a field or value within a field to be filtered out of the event, start the pointer with the event topic, for example access, activity, authentication, or config, followed by the field name or the path to the value in the field.<p><p>For example, to filter out the <code>userId</code> field in an access event the pointer will be <code>/access/userId</code>.<p>To filter out the <code>content-type</code> value in the <code>http.request.headers</code> field the pointer will be <code>/access/http/request/headers/content-type</code>.<p>Only values that are made up of JSON strings can be manipulated in this way.",
        "propertyOrder" : 200,
        "required" : false,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      },
      "auditEnabled" : {
        "title" : "Audit logging",
        "description" : "Enable audit logging in OpenAM.",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      }
    }
  },
  "type" : "object",
  "title" : "Realm Defaults"
}
}
}

```

1.17. AuthLevelDecision

1.17.1. Realm Operations

Resource path: </realm-config/authentication/authenticationtrees/nodes/AuthLevelDecisionNode>

Resource version: [1.0](#)

1.17.1.1. create

Usage:

```
am> create AuthLevelDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authLevelRequirement" : {
      "title" : "Sufficient Authentication Level",
      "description" : "The current authentication level must be greater than or equal to this value
for the decision to return true.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "authLevelRequirement" ]
}
```

1.17.1.2. delete

Usage:

```
am> delete AuthLevelDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.17.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthLevelDecision --realm Realm --actionName getAllTypes
```

1.17.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthLevelDecision --realm Realm --actionName getCreatableTypes
```

1.17.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action AuthLevelDecision --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.17.1.6. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthLevelDecision --realm Realm --actionName nextdescendants
```

1.17.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query AuthLevelDecision --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.17.1.8. read

Usage:

```
am> read AuthLevelDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.17.1.9. update

Usage:

```
am> update AuthLevelDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authLevelRequirement" : {
      "title" : "Sufficient Authentication Level",
      "description" : "The current authentication level must be greater than or equal to this value
for the decision to return true.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "authLevelRequirement" ]
}
```

1.18. AuthTree

1.18.1. Realm Operations

Authentication trees.

Resource path: [/realm-config/authentication/authenticationtrees/trees](#)

Resource version: [1.0](#)

1.18.1.1. create

Usage:

```
am> create AuthTree --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description": "A tree contains a set of nodes and their connections.",
  "type": "object",
  "title": "Authentication Tree",
  "properties": {
    "nodes": {
      "type": "object",
      "title": "Nodes",
      "description": "A map of node ID to node association details.",
      "patternProperties": {
        ".*": {
          "type": "object",
          "title": "Node",
          "description": "A association of a node with a tree.",
          "properties": {
            "connections": {
              "type": "object",
              "title": "Connections",
              "description": "The node's connected outcomes.",
              "patternProperties": {
                ".*": {
                  "type": "string",
                  "title": "Node ID",
                  "description": "The ID of the node that this outcome connects to."
                }
              }
            }
          }
        },
        "_outcomes": {
          "type": "array",
          "title": "Outcomes",
          "description": "The node's complete set of outcomes.",
          "readOnly": true,
          "items": {
            "type": "object",
            "title": "Outcome",
            "description": "A possible outcome of the node.",
            "readOnly": true,
            "properties": {
              "id": {
                "type": "string",
                "title": "ID",

```

```

        "description" : "The identifier of the outcome.",
        "readOnly" : true
    },
    "displayName" : {
        "type" : "string",
        "title" : "Display Name",
        "description" : "The display name of the outcome, in the requester's preferred
locale.",
        "readOnly" : true
    }
}
},
"nodeType" : {
    "title" : "Type",
    "description" : "The name of the SMS service for this node.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"displayName" : {
    "title" : "Display Name",
    "description" : "The name of the node to show in the tree UI.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
}
}
},
},
"entryNodeId" : {
    "title" : "Entry Node",
    "description" : "The ID of the node that the tree starts processing from.",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
}
}
}

```

1.18.1.2. delete

Usage:

```
am> delete AuthTree --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.18.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthTree --realm Realm --actionName getAllTypes
```

1.18.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthTree --realm Realm --actionName getCreatableTypes
```

1.18.1.5. getIds

Get the names of each tree configured in this realm.

Usage:

```
am> action AuthTree --realm Realm --actionName getIds
```

1.18.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthTree --realm Realm --actionName nextdescendents
```

1.18.1.7. query

Query for all authentication trees. Only a query filter of 'true' is supported.

Usage:

```
am> query AuthTree --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.18.1.8. read

Usage:

```
am> read AuthTree --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.18.1.9. update

Usage:

```
am> update AuthTree --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description": "A tree contains a set of nodes and their connections.",
  "type": "object",
  "title": "Authentication Tree",
  "properties": {
    "nodes": {
      "type": "object",
      "title": "Nodes",
      "description": "A map of node ID to node association details.",
      "patternProperties": {
        ".*": {
          "type": "object",
          "title": "Node",
          "description": "A association of a node with a tree.",
          "properties": {
            "connections": {
              "type": "object",
              "title": "Connections",
              "description": "The node's connected outcomes.",
              "patternProperties": {
                ".*": {
                  "type": "string",
                  "title": "Node ID",
                  "description": "The ID of the node that this outcome connects to."
                }
              }
            }
          }
        },
        "_outcomes": {
          "type": "array",
          "title": "Outcomes",
          "description": "The node's complete set of outcomes."
        }
      }
    }
  }
}
```

```

        "readOnly" : true,
        "items" : {
            "type" : "object",
            "title" : "Outcome",
            "description" : "A possible outcome of the node.",
            "readOnly" : true,
            "properties" : {
                "id" : {
                    "type" : "string",
                    "title" : "ID",
                    "description" : "The identifier of the outcome.",
                    "readOnly" : true
                },
                "displayName" : {
                    "type" : "string",
                    "title" : "Display Name",
                    "description" : "The display name of the outcome, in the requester's preferred
locale.",
                    "readOnly" : true
                }
            }
        },
    },
    "nodeType" : {
        "title" : "Type",
        "description" : "The name of the SMS service for this node.",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "displayName" : {
        "title" : "Display Name",
        "description" : "The name of the node to show in the tree UI.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
}
},
"entryNodeId" : {
    "title" : "Entry Node",
    "description" : "The ID of the node that the tree starts processing from.",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
}
}
}

```

1.18.1.10. validate

Validates a tree giving errors and warnings.

Usage:

```
am> action AuthTree --realm Realm --body body --actionName validate
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "A tree contains a set of nodes and their connections.",
  "type" : "object",
  "title" : "Authentication Tree",
  "properties" : {
    "nodes" : {
      "type" : "object",
      "title" : "Nodes",
      "description" : "A map of node ID to node association details.",
      "patternProperties" : {
        ".*" : {
          "type" : "object",
          "title" : "Node",
          "description" : "A association of a node with a tree.",
          "properties" : {
            "connections" : {
              "type" : "object",
              "title" : "Connections",
              "description" : "The node's connected outcomes.",
              "patternProperties" : {
                ".*" : {
                  "type" : "string",
                  "title" : "Node ID",
                  "description" : "The ID of the node that this outcome connects to."
                }
              }
            }
          }
        },
        "_outcomes" : {
          "type" : "array",
          "title" : "Outcomes",
          "description" : "The node's complete set of outcomes.",
          "readOnly" : true,
          "items" : {
            "type" : "object",
            "title" : "Outcome",
            "description" : "A possible outcome of the node.",
            "readOnly" : true,
            "properties" : {
              "id" : {
                "type" : "string",
                "title" : "ID",
                "description" : "The identifier of the outcome.",
                "readOnly" : true
              },
              "displayName" : {
                "type" : "string",
                "title" : "Display Name",
                "description" : "The display name of the outcome, in the requester's preferred
locale.",

```



```
        "readOnly" : true
      }
    }
  },
  "nodeType" : {
    "title" : "Type",
    "description" : "The name of the SMS service for this node.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "displayName" : {
    "title" : "Display Name",
    "description" : "The name of the node to show in the tree UI.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"entryNodeId" : {
  "title" : "Entry Node",
  "description" : "The ID of the node that the tree starts processing from.",
  "propertyOrder" : null,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
```

1.19. Authentication

1.19.1. Realm Operations

Resource path: `/realm-config/authentication`

Resource version: `1.0`

1.19.1.1. create

Usage:

```
am> create Authentication --realm Realm --body body
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "general" : {
      "type" : "object",
      "title" : "General",
      "propertyOrder" : 3,
      "properties" : {
        "userStatusCallbackPlugins" : {
          "title" : "Pluggable User Status Event Classes",
          "description" : "List of classes to be called when status of the user account
changes.<br><br>When the status of a users account changes, OpenAM can be configured to call into
a custom class. The custom class can then be used to perform some action as required. The built in
status change events are:<br><br><ul><li>Account locked</li><li>Password changed</li></ul><br>
>Custom code can also extend this mechanism.",
          "propertyOrder" : 2600,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "twoFactorRequired" : {
          "title" : "Two Factor Authentication Mandatory",
          "description" : "Enforces ALL 2FA (OATH and Push) authentication Modules (not nodes) only
for this authentication realm.",
          "propertyOrder" : 3900,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "identityType" : {
          "title" : "Identity Types",
          "description" : "",
          "propertyOrder" : 2500,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "locale" : {
          "title" : "Default Authentication Locale",
          "description" : "",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "statelessSessionsEnabled" : {
          "title" : "Use Client-based Sessions",
```

```

    "description" : "Enables client-based sessions.<br><br>Client-based sessions provide elastic
scalability by storing all session state as a JWT in a cookie stored on the client. It is highly
recommended to enable signing and encryption of the JWT in the global session service.",
    "propertyOrder" : 3800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "defaultAuthLevel" : {
    "title" : "Default Authentication Level",
    "description" : "The default authentication level for modules in this realm.<br><br>If
the authentication module does not set it's own auth level then the module will have the default
authentication level for the realm.",
    "propertyOrder" : 4100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
},
"security" : {
  "type" : "object",
  "title" : "Security",
  "propertyOrder" : 5,
  "properties" : {
    "keyAlias" : {
      "title" : "Persistent Cookie Encryption Certificate Alias",
      "description" : "Keystore Alias for encrypting Persistent Cookies.<br><br>This is the alias
for the private/public keys in the Keystore used in Persistent Cookie authentication requests.",
      "propertyOrder" : 3300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sharedSecret" : {
      "title" : "Organization Authentication Signing Secret",
      "description" : "HMAC shared secret for signing RESTful Authentication requests.<br><br>This
is the shared secret for signing state used in RESTful authentication requests. Should be at Base-64
encoded and at least 128-bits in length. By default a cryptographically secure random value is
generated.",
      "propertyOrder" : 4000,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "zeroPageLoginAllowedWithoutReferrer" : {
      "title" : "Zero Page Login Allowed without Referer?",
      "description" : "Whether to allow Zero Page Login if the HTTP Referer header is
missing.<br><br>The HTTP Referer header is sometimes missing from requests (e.g., if making a request
to HTTP from HTTPS). This setting controls whether such requests should be allowed or not. Setting
to 'true' will reduce the risk of Login CSRF attacks with Zero Page Login, but may potentially deny
legitimate requests.",
      "propertyOrder" : 3700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  },
  "moduleBasedAuthEnabled" : {

```

```

    "title" : "Module Based Authentication",
    "description" : "Allows a user to authenticate via module based authentication.<br><br>The
feature allow users to override the realm configuration and use a named authentication module to
authenticate.<br><br><i>NB </i>Recommended to turn this feature off in production environments.",
    "propertyOrder" : 2800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "zeroPageLoginEnabled" : {
    "title" : "Zero Page Login",
    "description" : "Allows a user to authenticate using GET request parameters without
showing the login screen.<br><br>Enable this feature if the authentication mechanism uses a single
authentication screen or the first authentication screen should always be invisible to users (since
it is auto-submitted). Use caution when enabling this feature as it can be used to authenticate using
regular GET parameters, which could be cached by browsers and logged in server and proxy access logs
exposing the values of the GET parameters.",
    "propertyOrder" : 3400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "zeroPageLoginReferrerWhiteList" : {
    "title" : "Zero Page Login Referrer Whitelist",
    "description" : "List of allowed HTTP Referer (sic) URLs from which Zero Page Login requests
are allowed.<br><br>Enter here all URLs from which you want to allow Zero Page Login. This provides
some mitigation against Login CSRF attacks. Leave empty to allow from any Referer. Applies to both
GET and POST login requests.",
    "propertyOrder" : 3600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"trees" : {
  "type" : "object",
  "title" : "Trees",
  "propertyOrder" : 4,
  "properties" : {
    "authenticationSessionsWhitelist" : {
      "title" : "Enable whitelisting",
      "description" : "Enables explicit whitelisting of valid authentication states to prevent
replay attacks.<br><br>If enabled, each time a response is sent to the user a randomly generated
state parameter is also sent back to user. This state parameter is stored accessible to AM and
must be sent in with the subsequent request. After a request has been received with a valid state
parameter, the next response contains a new state, and the server's view of the valid state parameter
is updated.",
      "propertyOrder" : 3860,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "authenticationSessionsMaxDuration" : {
      "title" : "Max duration (minutes)",

```

```

        "description" : "Specify how long an authentication session can last.<br><br>From the time
an authentication session is generated, the session will be invalid after this number of minutes.
Values from <strong>1</strong> upwards are allowed.",
        "propertyOrder" : 3860,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "authenticationSessionsStateManagement" : {
        "title" : "Authentication session state management scheme",
        "description" : "Specify how the authentication session state is managed.<br><br>CTS option
will write the state down to the underlying core token store.<br />JWT option will transmit the
state in a JWT to the client.<br />In-Memory option will maintain the state in the memory (requires
sticky loadbalancing).<br /><br /> <em>To configure JWT signing, encryption, and blacklisting use the
options in the Client-based Sessions section of the Sessions Global service.</em>",
        "propertyOrder" : 3850,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"accountlockout" : {
    "type" : "object",
    "title" : "Account Lockout",
    "propertyOrder" : 2,
    "properties" : {
        "lockoutDurationMultiplier" : {
            "title" : "Lockout Duration Multiplier",
            "description" : "Value multiplied to the Login Failure Lockout Duration for each successive
lockout.<br><br>This property is used to enable OpenAM to increase the account lockout duration for
each successive account lockout. For example: If the lockout duration is set to 10 and the duration
multiplier is set to 2; the duration of the first lockout will be 10 minutes and the duration of the
second lockout will be 20 minutes.<br><br>The default value of 1 disables this function. ",
            "propertyOrder" : 1400,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "lockoutDuration" : {
            "title" : "Login Failure Lockout Duration",
            "description" : "The duration of the users account lockout, in minutes.<br><br>OpenAM can
either lockout the users account indefinitely (until administration action) by setting the duration
to 0, (the default) or OpenAM can lock the users account for a given number of minutes. After the
lockout interval, the user will be able to successfully authenticate to OpenAM.",
            "propertyOrder" : 1300,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "invalidAttemptsDataAttributeName" : {
            "title" : "Invalid Attempts Data Attribute Name",
            "description" : "The name of the attribute used to store information about failed
authentications.<br><br>OpenAM can be configured to store information about invalid authentications
in the users profile. This allows multiple instances of OpenAM in the same site to share
information about a users invalid authentication attempts. By default the custom attribute;
<code>sunAMAuthInvalidAttemptsData</code> defined in the <code>sunAMAuthAccountLockout</code>
objectclass is used to store this data. Use this property to change the attribute used by OpenAM to
    
```

```

store this information.<br/><br/><i>NB </i>Any attribute specified must be a valid attribute in the
data store.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
    "lockoutEmailAddress" : {
        "title" : "Email Address to Send Lockout Notification",
        "description" : "An email address or set of email addresses that receive notifications
about account lockout events.<br/><br/>OpenAM can be configured to send a localisable email
message to a set of email addresses when account lockout events occur. The contents of the
email message is configured using the following properties in the <code>amAuth.properties</code>
file.<br/><ul><li><code>lockOutEmailFrom</code> : The \"From\" address of the email message</
li><li><code>lockOutEmailSub</code> : The subject of the email message</li><li><code>lockOutEmailMsg</
code> : The contents of the email message</li></ul><br/>The identity for whom the account has
been locked is included in the email message.<br/><br/>The format of this property is:<br/>
<code>emailaddress|locale|charset</code>. Multiple email addresses are space-separated.<br/>Email
addresses must include the domain name, such as <code>admin@example.com</code>.",
        "propertyOrder" : 1100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "loginFailureDuration" : {
        "title" : "Login Failure Lockout Interval",
        "description" : "The lockout interval time is in minutes.<br/><br/>OpenAM tracks the failed
authentication count for a user over the lockout interval.<br/><br/>For example: If the lockout
interval is 5 minutes and the lockout count is 5; the user will have to have failed to authenticate
5 times over the previous 5 minutes for the account to be locked. Failed authentications the occurred
outside of the 5 minute interval are ignored.",
        "propertyOrder" : 1000,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "lockoutAttributeName" : {
        "title" : "Lockout Attribute Name",
        "description" : "Name of custom lockout attribute <br/><br/>When OpenAM locks an account, the
<code>inetuserstatus</code> attribute in the locked account is set to Inactive. In addition, OpenAM
can set the value of another attribute in the users profile. ",
        "propertyOrder" : 1500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "storeInvalidAttemptsInDataStore" : {
        "title" : "Store Invalid Attempts in Data Store",
        "description" : "Enables sharing of login failure attempts across AM Instances<br/><br/>When
this setting is enabled OpenAM will store the users invalid authentication information in the data
store under the attribute configured in the <i>Invalid Attempts Data Attribute Name</i> property.",
        "propertyOrder" : 2700,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "lockoutWarnUserCount" : {
        "title" : "Warn User After N Failures",
    }

```

```

      "description" : "Warn the user when they reach this level of failed
      authentications.<br><br>The user will be given a warning when they reach this level of failed
      authentications during the lockout interval.<br>The text of the lockout warning is configured using
      the <code>lockOutWarning</code> property in the <code>amAuth.properties</code> file.",
      "propertyOrder" : 1200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "loginFailureCount" : {
      "title" : "Login Failure Lockout Count",
      "description" : "The maximum number of failed authentications for a user before their
      account is locked.<br><br>This setting controls the maximum number of failed authentications a user
      can have during the lockout interval before OpenAM locks the users account.",
      "propertyOrder" : 900,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "lockoutAttributeValue" : {
      "title" : "Lockout Attribute Value",
      "description" : "Value to set in custom lockout attribute<br><br>This is the value that will
      be set on the custom attribute in the users profile when they account is locked.",
      "propertyOrder" : 1600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "loginFailureLockoutMode" : {
      "title" : "Login Failure Lockout Mode",
      "description" : "Enables account lockout functionality for users authenticating to this
      realm.<br><br>OpenAM can track the number of failed authentications by a user over time and if a pre-
      defined limit is breached, OpenAM can lockout the users account and perform additional functions.<br>
      <br><i>NB</i> This functionality is in addition to any account lockout behaviour implemented by the
      LDAP Directory Server.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
},
"postauthprocess" : {
  "type" : "object",
  "title" : "Post Authentication Processing",
  "propertyOrder" : 6,
  "properties" : {
    "loginFailureUrl" : {
      "title" : "Default Failure Login URL ",
      "description" : "Failed logins will be forwarded to this URL<br><br>This is the URL to
      which clients will be forwarded upon failed authentication. Enter a URL or URI relative to the
      local OpenAM. URL or URI can be prefixed with ClientType|URL if client specific. URL without http(s)
      protocol will be appended to the current URI of OpenAM.",
      "propertyOrder" : 1900,
      "required" : true,
      "items" : {
        "type" : "string"
      }
    },
    "type" : "array",

```

```

        "exampleValue" : ""
    },
    "userAttributeSessionMapping" : {
        "title" : "User Attribute Mapping to Session Attribute",
        "description" : "Mapping of user profile attribute name to session attribute
name.<br><br>The setting causes OpenAM to read the named attributes from the users profile in the
data store and store their values in the users session.<br/></br>Format: User Profile Attribute|
Session Attribute name. ",
        "propertyOrder" : 3000,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "usernameGeneratorClass" : {
        "title" : "Pluggable User Name Generator Class",
        "description" : "The name of the default implementation of the user name
generator class.<br><br>The name of the class used to return a list of usernames to
the Membership auth module.<br/><br/><i>NB </i>This class must implement the interface
<code>com.sun.identity.authentication.spi.UserIDGenerator</code>",
        "propertyOrder" : 2200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "loginPostProcessClass" : {
        "title" : "Authentication Post Processing Classes",
        "description" : "A list of post authentication processing classes for all users
in this realm.<br><br>This is a list of Post Processing Classes that will be called by
OpenAM for all users that authenticate to this realm. Refer to the documentation for the
places where the list of post authentication classes can be set and their precedence.
<br/><br/>For example: org.forgerock.auth.PostProcessClass<br/><i>NB </i>OpenAM must be
able to find these classes on the <code>CLASSPATH</code> and must implement the interface
<code>com.sun.identity.authentication.spi.AMPostAuthProcessInterface</code>.",
        "propertyOrder" : 2000,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "loginSuccessUrl" : {
        "title" : "Default Success Login URL",
        "description" : "Successful logins will be forwarded to this URL<br><br>This is the URL to
which clients will be forwarded upon successful authentication. Enter a URL or URI relative to the
local OpenAM. URL or URI can be prefixed with the ClientType|URL if client specific. URL without
http(s) protocol will be appended to the current URI of OpenAM.",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "usernameGeneratorEnabled" : {

```



```

    "title" : "Generate UserID Mode",
    "description" : "Enables this mode in the Membership auth module.<br><br>When this mode is
enabled, if the Membership auth module detects that the supplied username already exists in the data
store then a list of valid usernames can be shown to the user, if requested by said user.",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"userprofile" : {
  "type" : "object",
  "title" : "User Profile",
  "propertyOrder" : 0,
  "properties" : {
    "dynamicProfileCreation" : {
      "title" : "User Profile",
      "description" : "Controls the result of the user profile success post successful
authentication.<br><br>Controls whether a user profile is required for authentication to be
successful or if the profile will be dynamically created if none already exists. Choose ignore if you
do not have a data store configured in the realm.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "aliasAttributeName" : {
      "title" : "Alias Search Attribute Name",
      "description" : "The secondary LDAP attribute retrieves the user profile if the primary
LDAP attribute specified in 'User Naming Attribute' fails.<br><br>This list of LDAP attributes
is used to extend the set of attributes searched by OpenAM to find the users profile.<br>For
example: <ul><li>cn</li><li>mail</li><li>givenname</li></ul><br>A user authenticates to OpenAM
under the id of steve, OpenAM will first search using the naming attribute (uid by default) so
uid=steve, if no match is found then cn=steve will be searched until a match is found or the list is
exhausted.<br><br><i>NB </i> Only used when User Profile searching is enabled.",
      "propertyOrder" : 400,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "defaultRole" : {
      "title" : "User Profile Dynamic Creation Default Roles",
      "description" : "List of roles of which dynamically created users will be a
member.<br><br>Enter the DN for each role that will be assigned to a new user when their profile has
been dynamically created by OpenAM.<br><br><i>NB </i> Deprecated functionality in OpenAM.",
      "propertyOrder" : 300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
},
}

```

```
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : -1,
  "properties" : {
    "orgConfig" : {
      "title" : "Organization Authentication Configuration",
      "description" : "Default Authentication Service for users<br><br>This is the authentication
service that will be used to authenticate users to this realm.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "adminAuthModule" : {
      "title" : "Administrator Authentication Configuration",
      "description" : "Default Authentication Service for administrators<br><br>This is the
authentication service that will be used to authentication administrative users to this realm.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
```

1.19.1.2. delete

Usage:

```
am> delete Authentication --realm Realm
```

1.19.1.3. read

Usage:

```
am> read Authentication --realm Realm
```

1.19.1.4. update

Usage:

```
am> update Authentication --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "general" : {
      "type" : "object",
      "title" : "General",
      "propertyOrder" : 3,
      "properties" : {
        "userStatusCallbackPlugins" : {
          "title" : "Pluggable User Status Event Classes",
          "description" : "List of classes to be called when status of the user account
changes.<br><br>When the status of a users account changes, OpenAM can be configured to call into
a custom class. The custom class can then be used to perform some action as required. The built in
status change events are:<br><br><ul><li>Account locked</li><li>Password changed</li></ul><br>
>Custom code can also extend this mechanism.",
          "propertyOrder" : 2600,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "twoFactorRequired" : {
          "title" : "Two Factor Authentication Mandatory",
          "description" : "Enforces ALL 2FA (OATH and Push) authentication Modules (not nodes) only
for this authentication realm.",
          "propertyOrder" : 3900,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "identityType" : {
          "title" : "Identity Types",
          "description" : "",
          "propertyOrder" : 2500,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "locale" : {
          "title" : "Default Authentication Locale",
          "description" : "",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "statelessSessionsEnabled" : {
          "title" : "Use Client-based Sessions",
          "description" : "Enables client-based sessions.<br><br>Client-based sessions provide elastic
scalability by storing all session state as a JWT in a cookie stored on the client. It is highly
recommended to enable signing and encryption of the JWT in the global session service.",
          "propertyOrder" : 3800,
          "required" : true,

```

```

    "type" : "boolean",
    "exampleValue" : ""
  },
  "defaultAuthLevel" : {
    "title" : "Default Authentication Level",
    "description" : "The default authentication level for modules in this realm.<br><br>If
the authentication module does not set it's own auth level then the module will have the default
authentication level for the realm.",
    "propertyOrder" : 4100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
},
"security" : {
  "type" : "object",
  "title" : "Security",
  "propertyOrder" : 5,
  "properties" : {
    "keyAlias" : {
      "title" : "Persistent Cookie Encryption Certificate Alias",
      "description" : "Keystore Alias for encrypting Persistent Cookies.<br><br>This is the alias
for the private/public keys in the Keystore used in Persistent Cookie authentication requests.",
      "propertyOrder" : 3300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sharedSecret" : {
      "title" : "Organization Authentication Signing Secret",
      "description" : "HMAC shared secret for signing RESTful Authentication requests.<br><br>This
is the shared secret for signing state used in RESTful authentication requests. Should be at Base-64
encoded and at least 128-bits in length. By default a cryptographically secure random value is
generated.",
      "propertyOrder" : 4000,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "zeroPageLoginAllowedWithoutReferrer" : {
      "title" : "Zero Page Login Allowed without Referrer?",
      "description" : "Whether to allow Zero Page Login if the HTTP Referer header is
missing.<br><br>The HTTP Referer header is sometimes missing from requests (e.g., if making a request
to HTTP from HTTPS). This setting controls whether such requests should be allowed or not. Setting
to 'true' will reduce the risk of Login CSRF attacks with Zero Page Login, but may potentially deny
legitimate requests.",
      "propertyOrder" : 3700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "moduleBasedAuthEnabled" : {
      "title" : "Module Based Authentication",
      "description" : "Allows a user to authenticate via module based authentication.<br><br>The
feature allow users to override the realm configuration and use a named authentication module to
authenticate.<br><br><i>NB </i>Recommended to turn this feature off in production environments.",
      "propertyOrder" : 2800,

```

```

    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "zeroPageLoginEnabled" : {
    "title" : "Zero Page Login",
    "description" : "Allows a user to authenticate using GET request parameters without
showing the login screen.<br><br>Enable this feature if the authentication mechanism uses a single
authentication screen or the first authentication screen should always be invisible to users (since
it is auto-submitted). Use caution when enabling this feature as it can be used to authenticate using
regular GET parameters, which could be cached by browsers and logged in server and proxy access logs
exposing the values of the GET parameters.",
    "propertyOrder" : 3400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "zeroPageLoginReferrerWhiteList" : {
    "title" : "Zero Page Login Referrer Whitelist",
    "description" : "List of allowed HTTP Referer (sic) URLs from which Zero Page Login requests
are allowed.<br><br>Enter here all URLs from which you want to allow Zero Page Login. This provides
some mitigation against Login CSRF attacks. Leave empty to allow from any Referer. Applies to both
GET and POST login requests.",
    "propertyOrder" : 3600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"trees" : {
  "type" : "object",
  "title" : "Trees",
  "propertyOrder" : 4,
  "properties" : {
    "authenticationSessionsWhitelist" : {
      "title" : "Enable whitelisting",
      "description" : "Enables explicit whitelisting of valid authentication states to prevent
replay attacks.<br><br>If enabled, each time a response is sent to the user a randomly generated
state parameter is also sent back to user. This state parameter is stored accessible to AM and
must be sent in with the subsequent request. After a request has been received with a valid state
parameter, the next response contains a new state, and the server's view of the valid state parameter
is updated.",
      "propertyOrder" : 3860,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "authenticationSessionsMaxDuration" : {
      "title" : "Max duration (minutes)",
      "description" : "Specify how long an authentication session can last.<br><br>From the time
an authentication session is generated, the session will be invalid after this number of minutes.
Values from <strong>1</strong> upwards are allowed.",
      "propertyOrder" : 3860,
      "required" : true,
      "type" : "integer",

```

```

    "exampleValue" : ""
  },
  "authenticationSessionsStateManagement" : {
    "title" : "Authentication session state management scheme",
    "description" : "Specify how the authentication session state is managed.<br><br>CTS option
will write the state down to the underlying core token store.<br />JWT option will transmit the
state in a JWT to the client.<br />In-Memory option will maintain the state in the memory (requires
sticky loadbalancing).<br /><br /> <em>To configure JWT signing, encryption, and blacklisting use the
options in the Client-based Sessions section of the Sessions global service.</em>",
    "propertyOrder" : 3850,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"accountlockout" : {
  "type" : "object",
  "title" : "Account Lockout",
  "propertyOrder" : 2,
  "properties" : {
    "lockoutDurationMultiplier" : {
      "title" : "Lockout Duration Multiplier",
      "description" : "Value multiplied to the Login Failure Lockout Duration for each successive
lockout.<br><br>This property is used to enable OpenAM to increase the account lockout duration for
each successive account lockout. For example: If the lockout duration is set to 10 and the duration
multiplier is set to 2; the duration of the first lockout will be 10 minutes and the duration of the
second lockout will be 20 minutes.<br><br>The default value of 1 disables this function. ",
      "propertyOrder" : 1400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "lockoutDuration" : {
      "title" : "Login Failure Lockout Duration",
      "description" : "The duration of the users account lockout, in minutes.<br><br>OpenAM can
either lockout the users account indefinitely (until administration action) by setting the duration
to 0, (the default) or OpenAM can lock the users account for a given number of minutes. After the
lockout interval, the user will be able to successfully authenticate to OpenAM.",
      "propertyOrder" : 1300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "invalidAttemptsDataAttributeName" : {
      "title" : "Invalid Attempts Data Attribute Name",
      "description" : "The name of the attribute used to store information about failed
authentications.<br><br>OpenAM can be configured to store information about invalid authentications
in the users profile. This allows multiple instances of OpenAM in the same site to share
information about a users invalid authentication attempts. By default the custom attribute;
<code>sunAMAuthInvalidAttemptsData</code> defined in the <code>sunAMAuthAccountLockout</code>
objectclass is used to store this data. Use this property to change the attribute used by OpenAM to
store this information.<br><br><i>NB </i>Any attribute specified must be a valid attribute in the
data store.",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},

```

```

"lockoutEmailAddress" : {
  "title" : "Email Address to Send Lockout Notification",
  "description" : "An email address or set of email addresses that receive notifications
about account lockout events.<br><br>OpenAM can be configured to send a localisable email
message to a set of email addresses when account lockout events occur. The contents of the
email message is configured using the following properties in the <code>amAuth.properties</code>
file.<br><ul><li><code>lockOutEmailFrom</code> : The \"From\" address of the email message</
li><li><code>lockOutEmailSub</code> : The subject of the email message</li><li><code>lockOutEmailMsg</
code> : The contents of the email message</li></ul><br>The identity for whom the account has
been locked is included in the email message.<br><br>The format of this property is:<br>
<code>emailaddress|locale|charset</code>. Multiple email addresses are space-separated.<br>Email
addresses must include the domain name, such as <code>admin@example.com</code>.",
  "propertyOrder" : 1100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"loginFailureDuration" : {
  "title" : "Login Failure Lockout Interval",
  "description" : "The lockout interval time is in minutes.<br><br>OpenAM tracks the failed
authentication count for a user over the lockout interval.<br><br>For example: If the lockout
interval is 5 minutes and the lockout count is 5; the user will have to have failed to authenticate
5 times over the previous 5 minutes for the account to be locked. Failed authentications the occurred
outside of the 5 minute interval are ignored.",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"lockoutAttributeName" : {
  "title" : "Lockout Attribute Name",
  "description" : "Name of custom lockout attribute <br><br>When OpenAM locks an account, the
<code>inetuserstatus</code> attribute in the locked account is set to Inactive. In addition, OpenAM
can set the value of another attribute in the users profile. ",
  "propertyOrder" : 1500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"storeInvalidAttemptsInDataStore" : {
  "title" : "Store Invalid Attempts in Data Store",
  "description" : "Enables sharing of login failure attempts across AM Instances<br><br>When
this setting is enabled OpenAM will store the users invalid authentication information in the data
store under the attribute configured in the <i>Invalid Attempts Data Attribute Name</i> property.",
  "propertyOrder" : 2700,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"lockoutWarnUserCount" : {
  "title" : "Warn User After N Failures",
  "description" : "Warn the user when they reach this level of failed
authentications.<br><br>The user will be given a warning when they reach this level of failed
authentications during the lockout interval.<br><br>The text of the lockout warning is configured using
the <code>lockOutWarning</code> property in the <code>amAuth.properties</code> file.",
  "propertyOrder" : 1200,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}

```

```

    },
    "loginFailureCount" : {
      "title" : "Login Failure Lockout Count",
      "description" : "The maximum number of failed authentications for a user before their
account is locked.<br><br>This setting controls the maximum number of failed authentications a user
can have during the lockout interval before OpenAM locks the users account.",
      "propertyOrder" : 900,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "lockoutAttributeValue" : {
      "title" : "Lockout Attribute Value",
      "description" : "Value to set in custom lockout attribute<br><br>This is the value that will
be set on the custom attribute in the users profile when they account is locked.",
      "propertyOrder" : 1600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "loginFailureLockoutMode" : {
      "title" : "Login Failure Lockout Mode",
      "description" : "Enables account lockout functionality for users authenticating to this
realm.<br><br>OpenAM can track the number of failed authentications by a user over time and if a pre-
defined limit is breached, OpenAM can lockout the users account and perform additional functions.<br>
<br><i>NB </i></i>This functionality is in addition to any account lockout behaviour implemented by the
LDAP Directory Server.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
},
"postauthprocess" : {
  "type" : "object",
  "title" : "Post Authentication Processing",
  "propertyOrder" : 6,
  "properties" : {
    "loginFailureUrl" : {
      "title" : "Default Failure Login URL ",
      "description" : "Failed logins will be forwarded to this URL<br><br>This is the URL to
which clients will be forwarded upon failed authentication. Enter a URL or URI relative to the
local OpenAM. URL or URI can be prefixed with ClientType|URL if client specific. URL without http(s)
protocol will be appended to the current URI of OpenAM.",
      "propertyOrder" : 1900,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "userAttributeSessionMapping" : {
      "title" : "User Attribute Mapping to Session Attribute",
      "description" : "Mapping of user profile attribute name to session attribute
name.<br><br>The setting causes OpenAM to read the named attributes from the users profile in the
data store and store their values in the users session.<br><br>Format: User Profile Attribute|
Session Attribute name. ",

```



```

        "propertyOrder" : 3000,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "usernameGeneratorClass" : {
        "title" : "Pluggable User Name Generator Class",
        "description" : "The name of the default implementation of the user name
generator class.<br><br>The name of the class used to return a list of usernames to
the Membership auth module.<br><br><i>NB </i>This class must implement the interface
<code>com.sun.identity.authentication.spi.UserIDGenerator</code>",
        "propertyOrder" : 2200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "loginPostProcessClass" : {
        "title" : "Authentication Post Processing Classes",
        "description" : "A list of post authentication processing classes for all users
in this realm.<br><br>This is a list of Post Processing Classes that will be called by
OpenAM for all users that authenticate to this realm. Refer to the documentation for the
places where the list of post authentication classes can be set and their precedence.
<br><br>For example: org.forgerock.auth.PostProcessClass<br><i>NB </i>OpenAM must be
able to find these classes on the <code>CLASSPATH</code> and must implement the interface
<code>com.sun.identity.authentication.spi.AMPostAuthProcessInterface</code>.",
        "propertyOrder" : 2000,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "loginSuccessUrl" : {
        "title" : "Default Success Login URL",
        "description" : "Successful logins will be forwarded to this URL<br><br>This is the URL to
which clients will be forwarded upon successful authentication. Enter a URL or URI relative to the
local OpenAM. URL or URI can be prefixed with the ClientType|URL if client specific. URL without
http(s) protocol will be appended to the current URI of OpenAM.",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "usernameGeneratorEnabled" : {
        "title" : "Generate UserID Mode",
        "description" : "Enables this mode in the Membership auth module.<br><br>When this mode is
enabled, if the Membership auth module detects that the supplied username already exists in the data
store then a list of valid usernames can be shown to the user, if requested by said user.",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }

```

```

    }
  },
  "userprofile" : {
    "type" : "object",
    "title" : "User Profile",
    "propertyOrder" : 0,
    "properties" : {
      "dynamicProfileCreation" : {
        "title" : "User Profile",
        "description" : "Controls the result of the user profile success post successful authentication.<br><br>Controls whether a user profile is required for authentication to be successful or if the profile will be dynamically created if none already exists. Choose ignore if you do not have a data store configured in the realm.",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "aliasAttributeName" : {
        "title" : "Alias Search Attribute Name",
        "description" : "The secondary LDAP attribute retrieves the user profile if the primary LDAP attribute specified in 'User Naming Attribute' fails.<br><br>This list of LDAP attributes is used to extend the set of attributes searched by OpenAM to find the users profile.<br>For example: <ul><li>cn</li><li>mail</li><li>givenname</li></ul><br>A user authenticates to OpenAM under the id of steve, OpenAM will first search using the naming attribute (uid by default) so uid=steve, if no match is found then cn=steve will be searched until a match is found or the list is exhausted.<br><br><i>NB </i> Only used when User Profile searching is enabled.",
        "propertyOrder" : 400,
        "required" : true,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      },
      "defaultRole" : {
        "title" : "User Profile Dynamic Creation Default Roles",
        "description" : "List of roles of which dynamically created users will be a member.<br><br>Enter the DN for each role that will be assigned to a new user when their profile has been dynamically created by OpenAM.<br><br><i>NB </i> Deprecated functionality in OpenAM.",
        "propertyOrder" : 300,
        "required" : true,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      }
    }
  }
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : -1,
  "properties" : {
    "orgConfig" : {
      "title" : "Organization Authentication Configuration",

```

```

    "description" : "Default Authentication Service for users<br><br>This is the authentication
service that will be used to authenticate users to this realm.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "adminAuthModule" : {
    "title" : "Administrator Authentication Configuration",
    "description" : "Default Authentication Service for administrators<br><br>This is the
authentication service that will be used to authentication administrative users to this realm.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}
}
}

```

1.19.2. Global Operations

Resource path: `/global-config/authentication`

Resource version: `1.0`

1.19.2.1. read

Usage:

```
am> read Authentication --global
```

1.19.2.2. update

Usage:

```
am> update Authentication --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "remoteAuthSecurityEnabled" : {
      "title" : "Remote Auth Security",
      "description" : "OpenAM requires authentication client to authenticate itself before
authenticating users.<br><br>When this setting is enabled, OpenAM will require the authentication

```

```

client (such as a policy agent) to authentication itself to OpenAM before the client will be allow to
use the remote authentication API to authenticate users. ",
    "propertyOrder" : 2900,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"keepPostProcessInstances" : {
    "title" : "Keep Post Process Objects for Logout Processing",
    "description" : "Store Post Processing Classes for the duration of the session.<br><br>Enabling
this setting will cause OpenAM to store instances of post processing classes into the users session.
When the user logs out the original instances of the post processing classes will be called instead
of new instances. This may be needed for special logout processing.<br><br><i>NB </i>Enabling this
setting will increase the memory usage of OpenAM.",
    "propertyOrder" : 3100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"ldapConnectionPoolDefaultSize" : {
    "title" : "Default LDAP Connection Pool Size",
    "description" : "The default connection pool size; format is: minimum:maximum",
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"authenticators" : {
    "title" : "Pluggable Authentication Module Classes",
    "description" : "List of configured authentication modules<br><br>The list of
configured authentication modules available to OpenAM. All modules must extend from the
<code>com.sun.identity.authentication.spi.AMLoginModule</code> class.",
    "propertyOrder" : 500,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"ldapConnectionPoolSize" : {
    "title" : "LDAP Connection Pool Size",
    "description" : "Controls the size of the LDAP connection pool used for
authentication<br><br>Control the size of the connection pool to the LDAP directory server used by
any of the authentication modules that use LDAP directly such as LDAP or Active Directory.Different
OpenAM servers can be configured with different connection pool settings.<br><br>Format:
host:port:minimum:maximum",
    "propertyOrder" : 2300,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"defaults" : {
    "properties" : {
        "accountlockout" : {
            "type" : "object",

```

```

"title" : "Account Lockout",
"propertyOrder" : 2,
"properties" : {
  "invalidAttemptsDataAttributeName" : {
    "title" : "Invalid Attempts Data Attribute Name",
    "description" : "The name of the attribute used to store information about failed
    authentications.<br><br>OpenAM can be configured to store information about invalid authentications
    in the users profile. This allows multiple instances of OpenAM in the same site to share
    information about a users invalid authentication attempts. By default the custom attribute;
    <code>sunAMAuthInvalidAttemptsData</code> defined in the <code>sunAMAuthAccountLockout</code>
    objectclass is used to store this data. Use this property to change the attribute used by OpenAM to
    store this information.<br><br><i>NB </i>Any attribute specified must be a valid attribute in the
    data store.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "lockoutWarnUserCount" : {
    "title" : "Warn User After N Failures",
    "description" : "Warn the user when they reach this level of failed
    authentications.<br><br>The user will be given a warning when they reach this level of failed
    authentications during the lockout interval.<br><br>The text of the lockout warning is configured using
    the <code>lockOutWarning</code> property in the <code>amAuth.properties</code> file.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "lockoutAttributeValue" : {
    "title" : "Lockout Attribute Value",
    "description" : "Value to set in custom lockout attribute<br><br>This is the value that
    will be set on the custom attribute in the users profile when they account is locked.",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "lockoutEmailAddress" : {
    "title" : "Email Address to Send Lockout Notification",
    "description" : "An email address or set of email addresses that receive notifications
    about account lockout events.<br><br>OpenAM can be configured to send a localisable email
    message to a set of email addresses when account lockout events occur. The contents of the
    email message is configured using the following properties in the <code>amAuth.properties</code>
    file.<br><br><ul><li><code>lockOutEmailFrom</code> : The \"From\" address of the email message</
    li><li><code>lockOutEmailSub</code> : The subject of the email message</li><li><code>lockOutEmailMsg</
    code> : The contents of the email message</li></ul><br><br>The identity for whom the account has
    been locked is included in the email message.<br><br>The format of this property is:<br>
    <code>emailaddress|locale|charset</code>. Multiple email addresses are space-separated.<br>Email
    addresses must include the domain name, such as <code>admin@example.com</code>.",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "loginFailureCount" : {
    "title" : "Login Failure Lockout Count",

```

```

    "description" : "The maximum number of failed authentications for a user before their
account is locked.<br><br>This setting controls the maximum number of failed authentications a user
can have during the lockout interval before OpenAM locks the users account.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "lockoutDurationMultiplier" : {
    "title" : "Lockout Duration Multiplier",
    "description" : "Value multiplied to the Login Failure Lockout Duration for each
successive lockout.<br><br>This property is used to enable OpenAM to increase the account lockout
duration for each successive account lockout. For example: If the lockout duration is set to 10 and
the duration multiplier is set to 2; the duration of the first lockout will be 10 minutes and the
duration of the second lockout will be 20 minutes.<br><br>The default value of 1 disables this
function. ",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "loginFailureLockoutMode" : {
    "title" : "Login Failure Lockout Mode",
    "description" : "Enables account lockout functionality for users authenticating to this
realm.<br><br>OpenAM can track the number of failed authentications by a user over time and if a
pre-defined limit is breached, OpenAM can lockout the users account and perform additional functions.<br>
<br><i>NB </i></i>This functionality is in addition to any account lockout behaviour implemented by the
LDAP Directory Server.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "lockoutAttributeName" : {
    "title" : "Lockout Attribute Name",
    "description" : "Name of custom lockout attribute <br><br>When OpenAM locks an account,
the <code>inetuserstatus</code> attribute in the locked account is set to Inactive. In addition,
OpenAM can set the value of another attribute in the users profile. ",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "storeInvalidAttemptsInDataStore" : {
    "title" : "Store Invalid Attempts in Data Store",
    "description" : "Enables sharing of login failure attempts across AM
Instances<br><br>When this setting is enabled OpenAM will store the users invalid authentication
information in the data store under the attribute configured in the <i>Invalid Attempts Data
Attribute Name</i> property.",
    "propertyOrder" : 2700,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "loginFailureDuration" : {
    "title" : "Login Failure Lockout Interval",
    "description" : "The lockout interval time is in minutes.<br><br>OpenAM tracks the
failed authentication count for a user over the lockout interval.<br><br>For example: If the
lockout interval is 5 minutes and the lockout count is 5; the user will have to have failed to

```

```

authenticate 5 times over the previous 5 minutes for the account to be locked. Failed authentications
the occurred outside of the 5 minute interval are ignored.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
},
"lockoutDuration" : {
    "title" : "Login Failure Lockout Duration",
    "description" : "The duration of the users account lockout, in minutes.<br><br>OpenAM
can either lockout the users account indefinitely (until administration action) by setting the
duration to 0, (the default) or OpenAM can lock the users account for a given number of minutes.
After the lockout interval, the user will be able to successfully authenticate to OpenAM.",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
}
}
},
"postauthprocess" : {
    "type" : "object",
    "title" : "Post Authentication Processing",
    "propertyOrder" : 6,
    "properties" : {
        "loginFailureUrl" : {
            "title" : "Default Failure Login URL ",
            "description" : "Failed logins will be forwarded to this URL<br><br>This is the URL
to which clients will be forwarded upon failed authentication. Enter a URL or URI relative to the
local OpenAM. URL or URI can be prefixed with ClientType|URL if client specific. URL without http(s)
protocol will be appended to the current URI of OpenAM.",
            "propertyOrder" : 1900,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "usernameGeneratorClass" : {
            "title" : "Pluggable User Name Generator Class",
            "description" : "The name of the default implementation of the user name
generator class.<br><br>The name of the class used to return a list of usernames to
the Membership auth module.<br><br><i>NB </i>This class must implement the interface
<code>com.sun.identity.authentication.spi.UserIDGenerator</code>",
            "propertyOrder" : 2200,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "usernameGeneratorEnabled" : {
            "title" : "Generate UserID Mode",
            "description" : "Enables this mode in the Membership auth module.<br><br>When this mode
is enabled, if the Membership auth module detects that the supplied username already exists in the
data store then a list of valid usernames can be shown to the user, if requested by said user.",
            "propertyOrder" : 2100,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        }
    }
}

```

```

    },
    "loginSuccessUrl" : {
      "title" : "Default Success Login URL",
      "description" : "Successful logins will be forwarded to this URL<br><br>This is the URL
to which clients will be forwarded upon successful authentication. Enter a URL or URI relative to
the local OpenAM. URL or URI can be prefixed with the ClientType|URL if client specific. URL without
http(s) protocol will be appended to the current URI of OpenAM.",
      "propertyOrder" : 1800,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "loginPostProcessClass" : {
      "title" : "Authentication Post Processing Classes",
      "description" : "A list of post authentication processing classes for all
users in this realm.<br><br>This is a list of Post Processing Classes that will be called
by OpenAM for all users that authenticate to this realm. Refer to the documentation for
the places where the list of post authentication classes can be set and their precedence.
<br><br>For example: org.forgerock.auth.PostProcessClass<br><i>NB </i>OpenAM must be
able to find these classes on the <code>CLASSPATH</code> and must implement the interface
<code>com.sun.identity.authentication.spi.AMPostAuthProcessInterface</code>.",
      "propertyOrder" : 2000,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "userAttributeSessionMapping" : {
      "title" : "User Attribute Mapping to Session Attribute",
      "description" : "Mapping of user profile attribute name to session attribute
name.<br><br>The setting causes OpenAM to read the named attributes from the users profile in the
data store and store their values in the users session.<br><br>Format: User Profile Attribute|
Session Attribute name. ",
      "propertyOrder" : 3000,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
},
"general" : {
  "type" : "object",
  "title" : "General",
  "propertyOrder" : 3,
  "properties" : {
    "locale" : {
      "title" : "Default Authentication Locale",
      "description" : "",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",

```



```

    "exampleValue" : ""
  },
  "statelessSessionsEnabled" : {
    "title" : "Use Client-based Sessions",
    "description" : "Enables client-based sessions.<br><br>Client-based sessions provide
elastic scalability by storing all session state as a JWT in a cookie stored on the client. It is
highly recommended to enable signing and encryption of the JWT in the global session service.",
    "propertyOrder" : 3800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userStatusCallbackPlugins" : {
    "title" : "Pluggable User Status Event Classes",
    "description" : "List of classes to be called when status of the user account
changes.<br><br>When the status of a users account changes, OpenAM can be configured to call into
a custom class. The custom class can then be used to perform some action as required. The built in
status change events are:<br><br><ul><li>Account locked</li><li>Password changed</li></ul><br>
Custom code can also extend this mechanism.",
    "propertyOrder" : 2600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "identityType" : {
    "title" : "Identity Types",
    "description" : "",
    "propertyOrder" : 2500,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "twoFactorRequired" : {
    "title" : "Two Factor Authentication Mandatory",
    "description" : "Enforces ALL 2FA (OATH and Push) authentication Modules (not nodes)
only for this authentication realm.",
    "propertyOrder" : 3900,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "defaultAuthLevel" : {
    "title" : "Default Authentication Level",
    "description" : "The default authentication level for modules in this realm.<br><br>If
the authentication module does not set it's own auth level then the module will have the default
authentication level for the realm.",
    "propertyOrder" : 4100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
},

```

```

"security" : {
  "type" : "object",
  "title" : "Security",
  "propertyOrder" : 5,
  "properties" : {
    "sharedSecret" : {
      "title" : "Organization Authentication Signing Secret",
      "description" : "HMAC shared secret for signing RESTful Authentication
requests.<br><br>This is the shared secret for signing state used in RESTful authentication requests.
Should be at Base-64 encoded and at least 128-bits in length. By default a cryptographically secure
random value is generated.",
      "propertyOrder" : 4000,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "moduleBasedAuthEnabled" : {
      "title" : "Module Based Authentication",
      "description" : "Allows a user to authenticate via module based
authentication.<br><br>The feature allow users to override the realm configuration and use a named
authentication module to authenticate.<br></><br><i>NB </i>Recommended to turn this feature off in
production environments.",
      "propertyOrder" : 2800,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "zeroPageLoginAllowedWithoutReferrer" : {
      "title" : "Zero Page Login Allowed without Referer?",
      "description" : "Whether to allow Zero Page Login if the HTTP Referer header is
missing.<br><br>The HTTP Referer header is sometimes missing from requests (e.g., if making a request
to HTTP from HTTPS). This setting controls whether such requests should be allowed or not. Setting
to 'true' will reduce the risk of Login CSRF attacks with Zero Page Login, but may potentially deny
legitimate requests.",
      "propertyOrder" : 3700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "zeroPageLoginEnabled" : {
      "title" : "Zero Page Login",
      "description" : "Allows a user to authenticate using GET request parameters without
showing the login screen.<br><br>Enable this feature if the authentication mechanism uses a single
authentication screen or the first authentication screen should always be invisible to users (since
it is auto-submitted). Use caution when enabling this feature as it can be used to authenticate using
regular GET parameters, which could be cached by browsers and logged in server and proxy access logs
exposing the values of the GET parameters.",
      "propertyOrder" : 3400,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "zeroPageLoginReferrerWhiteList" : {
      "title" : "Zero Page Login Referer Whitelist",
      "description" : "List of allowed HTTP Referer (sic) URLs from which Zero Page Login
requests are allowed.<br><br>Enter here all URLs from which you want to allow Zero Page Login. This
provides some mitigation against Login CSRF attacks. Leave empty to allow from any Referer. Applies
to both GET and POST login requests.",

```

```

    "propertyOrder" : 3600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "keyAlias" : {
    "title" : "Persistent Cookie Encryption Certificate Alias",
    "description" : "Keystore Alias for encrypting Persistent Cookies.<br><br>This is
the alias for the private/public keys in the Keystore used in Persistent Cookie authentication
requests.",
    "propertyOrder" : 3300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : -1,
  "properties" : {
    "orgConfig" : {
      "title" : "Organization Authentication Configuration",
      "description" : "Default Authentication Service for users<br><br>This is the
authentication service that will be used to authenticate users to this realm.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "adminAuthModule" : {
      "title" : "Administrator Authentication Configuration",
      "description" : "Default Authentication Service for administrators<br><br>This is the
authentication service that will be used to authentication administrative users to this realm.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"trees" : {
  "type" : "object",
  "title" : "Trees",
  "propertyOrder" : 4,
  "properties" : {
    "authenticationSessionsWhitelist" : {
      "title" : "Enable whitelisting",
      "description" : "Enables explicit whitelisting of valid authentication states to prevent
replay attacks.<br><br>If enabled, each time a response is sent to the user a randomly generated
state parameter is also sent back to user. This state parameter is stored accessible to AM and
must be sent in with the subsequent request. After a request has been received with a valid state
parameter, the next response contains a new state, and the server's view of the valid state parameter
is updated.",
      "propertyOrder" : 3860,

```

```

    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "authenticationSessionsMaxDuration" : {
    "title" : "Max duration (minutes)",
    "description" : "Specify how long an authentication session can last.<br><br>From
the time an authentication session is generated, the session will be invalid after this number of
minutes. Values from <strong>1</strong> upwards are allowed.",
    "propertyOrder" : 3860,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "authenticationSessionsStateManagement" : {
    "title" : "Authentication session state management scheme",
    "description" : "Specify how the authentication session state is managed.<br><br>CTS
option will write the state down to the underlying core token store.<br />JWT option will transmit
the state in a JWT to the client.<br />In-Memory option will maintain the state in the memory
(requires sticky loadbalancing).<br /><br /> <em>To configure JWT signing, encryption, and
blacklisting use the options in the Client-based Sessions section of the Sessions global service.</
em>",
    "propertyOrder" : 3850,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"userprofile" : {
  "type" : "object",
  "title" : "User Profile",
  "propertyOrder" : 0,
  "properties" : {
    "aliasAttributeName" : {
      "title" : "Alias Search Attribute Name",
      "description" : "The secondary LDAP attribute retrieves the user profile if the primary
LDAP attribute specified in 'User Naming Attribute' fails.<br><br>This list of LDAP attributes
is used to extend the set of attributes searched by OpenAM to find the users profile.<br>For
example: <ul><li>cn</li><li>mail</li><li>givenname</li></ul><br>A user authenticates to OpenAM
under the id of steve, OpenAM will first search using the naming attribute (uid by default) so
uid=steve, if no match is found then cn=steve will be searched until a match is found or the list is
exhausted.<br><br><i>NB </i> Only used when User Profile searching is enabled.",
      "propertyOrder" : 400,
      "required" : true,
      "items" : {
        "type" : "string"
      },
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "defaultRole" : {
    "title" : "User Profile Dynamic Creation Default Roles",
    "description" : "List of roles of which dynamically created users will be a
member.<br><br>Enter the DN for each role that will be assigned to a new user when their profile has
been dynamically created by OpenAM.<br><br><i>NB </i> Deprecated functionality in OpenAM.",
    "propertyOrder" : 300,
    "required" : true,
    "items" : {

```

```
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "dynamicProfileCreation" : {
      "title" : "User Profile",
      "description" : "Controls the result of the user profile success post successful authentication.<br><br>Controls whether a user profile is required for authentication to be successful or if the profile will be dynamically created if none already exists. Choose ignore if you do not have a data store configured in the realm.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
```

1.20. AuthenticationChains

1.20.1. Realm Operations

Resource path: `/realm-config/authentication/chains`

Resource version: `1.0`

1.20.1.1. create

Usage:

```
am> create AuthenticationChains --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
```

```

"properties" : {
  "loginSuccessUrl" : {
    "title" : "Login Success URL",
    "description" : "URL or ClientType|URL if client specific. URL without http(s) protocol will be
appended to the current URI.",
    "propertyOrder" : 200,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "authChainConfiguration" : {
    "title" : "Authentication Configuration",
    "description" : "",
    "propertyOrder" : 100,
    "required" : true,
    "exampleValue" : "",
    "type" : "array",
    "items" : {
      "type" : "object",
      "properties" : {
        "module" : {
          "type" : "string"
        },
        "criteria" : {
          "type" : "string"
        },
        "options" : {
          "type" : "object",
          "patternProperties" : {
            ".*" : {
              "type" : "string"
            }
          }
        }
      }
    }
  }
},
"loginPostProcessClass" : {
  "title" : "Authentication Post Processing Classes",
  "description" : "Example: com.abc.authentication.PostProcessClass",
  "propertyOrder" : 400,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"loginFailureUrl" : {
  "title" : "Login Failed URL",
  "description" : "URL or ClientType|URL if client specific. URL without http(s) protocol will be
appended to the current URI.",
  "propertyOrder" : 300,
  "required" : true,
  "items" : {
    "type" : "string"
  }
}

```

```
    },  
    "type" : "array",  
    "exampleValue" : ""  
  }  
}
```

1.20.1.2. delete

Usage:

```
am> delete AuthenticationChains --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.20.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticationChains --realm Realm --actionName getAllTypes
```

1.20.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticationChains --realm Realm --actionName getCreatableTypes
```

1.20.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticationChains --realm Realm --actionName nextdescendents
```

1.20.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query AuthenticationChains --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.20.1.7. read

Usage:

```
am> read AuthenticationChains --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.20.1.8. update

Usage:

```
am> update AuthenticationChains --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "loginSuccessUrl" : {
      "title" : "Login Success URL",
      "description" : "URL or ClientType|URL if client specific. URL without http(s) protocol will be
appended to the current URI.",
      "propertyOrder" : 200,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",

```



```

    "exampleValue" : ""
  },
  "authChainConfiguration" : {
    "title" : "Authentication Configuration",
    "description" : "",
    "propertyOrder" : 100,
    "required" : true,
    "exampleValue" : "",
    "type" : "array",
    "items" : {
      "type" : "object",
      "properties" : {
        "module" : {
          "type" : "string"
        },
        "criteria" : {
          "type" : "string"
        },
        "options" : {
          "type" : "object",
          "patternProperties" : {
            ".*" : {
              "type" : "string"
            }
          }
        }
      }
    }
  },
  "loginPostProcessClass" : {
    "title" : "Authentication Post Processing Classes",
    "description" : "Example: com.abc.authentication.PostProcessClass",
    "propertyOrder" : 400,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "loginFailureUrl" : {
    "title" : "Login Failed URL",
    "description" : "URL or ClientType|URL if client specific. URL without http(s) protocol will be
appended to the current URI.",
    "propertyOrder" : 300,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
}
}

```

1.20.2. Global Operations

Resource path: `/global-config/authentication/chains`

Resource version: `1.0`

1.20.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticationChains --global --actionName getAllTypes
```

1.20.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticationChains --global --actionName getCreatableTypes
```

1.20.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticationChains --global --actionName nextdescendents
```

1.20.2.4. read

Usage:

```
am> read AuthenticationChains --global
```

1.20.2.5. update

Usage:

```
am> update AuthenticationChains --global --body body
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "dynamic" : {
      "properties" : {
        "authChainConfiguration" : {
          "title" : "Authentication Configuration",
          "description" : "",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      },
      "type" : "object",
      "title" : "Dynamic Attributes"
    }
  }
}
```

1.21. AuthenticationModules

1.21.1. Realm Operations

The collection of all authentication modules in a realm allows querying for all module instances.

Resource path: [/realm-config/authentication/modules](#)

Resource version: [1.0](#)

1.21.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticationModules --realm Realm --actionName getAllTypes
```

1.21.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticationModules --realm Realm --actionName getCreatableTypes
```

1.21.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticationModules --realm Realm --actionName nextdescendents
```

1.21.1.4. query

Query for authentication module instances

Usage:

```
am> query AuthenticationModules --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [_id]

1.21.2. Global Operations

Global and default configuration for authentication modules

Resource path: [/global-config/authentication/modules](#)

Resource version: [1.0](#)

1.21.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticationModules --global --actionName getAllTypes
```

1.21.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticationModules --global --actionName getCreatableTypes
```

1.21.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticationModules --global --actionName nextdescendents
```

1.22. AuthenticationNodes

1.22.1. Realm Operations

Auth Tree Nodes

Resource path: `/realm-config/authentication/authenticationtrees/nodes`

Resource version: `1.0`

1.22.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticationNodes --realm Realm --actionName getAllTypes
```

1.22.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticationNodes --realm Realm --actionName getCreatableTypes
```

1.22.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticationNodes --realm Realm --actionName nextdescendents
```

1.23. AuthenticationTreesConfiguration

1.23.1. Realm Operations

Sub-path parent for all authentication tree configuration.

Resource path: `/realm-config/authentication/authenticationtrees`

Resource version: 1.0

1.23.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticationTreesConfiguration --realm Realm --actionName getAllTypes
```

1.23.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticationTreesConfiguration --realm Realm --actionName getCreatableTypes
```

1.23.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticationTreesConfiguration --realm Realm --actionName nextdescendents
```

1.23.2. Global Operations

Resource path: [/global-config/authentication/authenticationtrees](#)

Resource version: 1.0

1.23.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticationTreesConfiguration --global --actionName getAllTypes
```

1.23.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticationTreesConfiguration --global --actionName getCreatableTypes
```

1.23.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticationTreesConfiguration --global --actionName nextdescendents
```

1.23.2.4. read

Usage:

```
am> read AuthenticationTreesConfiguration --global
```

1.23.2.5. update

Usage:

```
am> update AuthenticationTreesConfiguration --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object"
}
```

1.24. AuthenticatorOath

1.24.1. Realm Operations

Resource path: [/realm-config/services/authenticatorOathService](#)

Resource version: [1.0](#)

1.24.1.1. create

Usage:

```
am> create AuthenticatorOath --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticatorOATHSkippableName" : {
      "title" : "ForgeRock Authenticator (OATH) Device Skippable Attribute Name",
      "description" : "The data store attribute that holds the user's decision to enable or disable obtaining and providing a password obtained from the ForgeRock Authenticator app. This attribute must be writeable.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticatorOATHDeviceSettingsEncryptionKeystorePrivateKeyPassword" : {
      "title" : "Private Key Password",
      "description" : "Password to unlock the private key.",
      "propertyOrder" : 700,
      "required" : false,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "oathAttrName" : {
      "title" : "Profile Storage Attribute",
      "description" : "Attribute for storing ForgeRock Authenticator OATH profiles.<br><br>The default attribute is added to the user store during OpenAM installation. If you want to use a different attribute, you must make sure to add it to your user store schema prior to deploying two-step verification with a ForgeRock OATH authenticator app in OpenAM. OpenAM must be able to write to the attribute.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticatorOATHDeviceSettingsEncryptionScheme" : {
      "title" : "Device Profile Encryption Scheme",
      "description" : "Encryption scheme for securing device profiles stored on the server.<br><br>If enabled, each device profile is encrypted using a unique random secret key using the given strength of AES encryption in CBC mode with PKCS#5 padding. An HMAC-SHA of the given strength (truncated to half-size) is used to ensure integrity protection and authenticated encryption. The unique random key is encrypted with the given RSA key pair and stored with the device profile.<p><p><i>Note:</i> AES-256 may require installation of the JCE Unlimited Strength policy files.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticatorOATHDeviceSettingsEncryptionKeystore" : {
      "title" : "Encryption Key Store",
      "description" : "Path to the key store from which to load encryption keys.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```



```

"authenticatorOATHDeviceSettingsEncryptionKeystoreKeyPairAlias" : {
  "title" : "Key-Pair Alias",
  "description" : "Alias of the certificate and private key in the key store. The private key is
used to encrypt and decrypt device profiles.",
  "propertyOrder" : 600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"authenticatorOATHDeviceSettingsEncryptionKeystorePassword" : {
  "title" : "Key Store Password",
  "description" : "Password to unlock the key store. This password will be encrypted.",
  "propertyOrder" : 500,
  "required" : false,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"authenticatorOATHDeviceSettingsEncryptionKeystoreType" : {
  "title" : "Key Store Type",
  "description" : "Type of encryption key store.<br><br><i>Note:</i> PKCS#11 keys tores require
hardware support such as a security device or smart card and is not available by default in most
JVM installations.<p><p>See the <a href=\"https://docs.oracle.com/javase/8/docs/technotes/guides/
security/p11guide.html\" target=\"_blank\">JDK 8 PKCS#11 Reference Guide</a> for more details.",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
}

```

1.24.1.2. delete

Usage:

```
am> delete AuthenticatorOath --realm Realm
```

1.24.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticatorOath --realm Realm --actionName getAllTypes
```

1.24.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticatorOath --realm Realm --actionName getCreatableTypes
```

1.24.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticatorOath --realm Realm --actionName nextdescendents
```

1.24.1.6. read

Usage:

```
am> read AuthenticatorOath --realm Realm
```

1.24.1.7. update

Usage:

```
am> update AuthenticatorOath --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticatorOATHSkippableName" : {
      "title" : "ForgeRock Authenticator (OATH) Device Skippable Attribute Name",
      "description" : "The data store attribute that holds the user's decision to enable or disable obtaining and providing a password obtained from the ForgeRock Authenticator app. This attribute must be writeable.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticatorOATHDeviceSettingsEncryptionKeystorePrivateKeyPassword" : {
      "title" : "Private Key Password",
      "description" : "Password to unlock the private key.",
      "propertyOrder" : 700,
      "required" : false,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "oathAttrName" : {
      "title" : "Profile Storage Attribute",
      "description" : "Attribute for storing ForgeRock Authenticator OATH profiles.<br><br>The default attribute is added to the user store during OpenAM installation. If you want to use a different attribute, you must make sure to add it to your user store schema prior to deploying two-step
```

```

verification with a ForgeRock OATH authenticator app in OpenAM. OpenAM must be able to write to the
attribute.",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authenticatorOATHDeviceSettingsEncryptionScheme" : {
  "title" : "Device Profile Encryption Scheme",
  "description" : "Encryption scheme for securing device profiles stored on the server.<br><br>If
enabled, each device profile is encrypted using a unique random secret key using the given strength
of AES encryption in CBC mode with PKCS#5 padding. An HMAC-SHA of the given strength (truncated to
half-size) is used to ensure integrity protection and authenticated encryption. The unique random
key is encrypted with the given RSA key pair and stored with the device profile.<p><p><i>Note:</i>
AES-256 may require installation of the JCE Unlimited Strength policy files.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authenticatorOATHDeviceSettingsEncryptionKeystore" : {
  "title" : "Encryption Key Store",
  "description" : "Path to the key store from which to load encryption keys.",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authenticatorOATHDeviceSettingsEncryptionKeystoreKeyPairAlias" : {
  "title" : "Key-Pair Alias",
  "description" : "Alias of the certificate and private key in the key store. The private key is
used to encrypt and decrypt device profiles.",
  "propertyOrder" : 600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"authenticatorOATHDeviceSettingsEncryptionKeystorePassword" : {
  "title" : "Key Store Password",
  "description" : "Password to unlock the key store. This password will be encrypted.",
  "propertyOrder" : 500,
  "required" : false,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"authenticatorOATHDeviceSettingsEncryptionKeystoreType" : {
  "title" : "Key Store Type",
  "description" : "Type of encryption key store.<br><br><i>Note:</i> PKCS#11 keys tores require
hardware support such as a security device or smart card and is not available by default in most
JVM installations.<p><p>See the <a href=\"https://docs.oracle.com/javase/8/docs/technotes/guides/
security/pllguide.html\" target=\"_blank\">JDK 8 PKCS#11 Reference Guide</a> for more details.",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
}

```

```
}
```

1.24.2. Global Operations

Resource path: `/global-config/services/authenticatorOathService`

Resource version: `1.0`

1.24.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticatorOath --global --actionName getAllTypes
```

1.24.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticatorOath --global --actionName getCreatableTypes
```

1.24.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticatorOath --global --actionName nextdescendents
```

1.24.2.4. read

Usage:

```
am> read AuthenticatorOath --global
```

1.24.2.5. update

Usage:

```
am> update AuthenticatorOath --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "authenticatorOATHDeviceSettingsEncryptionScheme" : {
          "title" : "Device Profile Encryption Scheme",
          "description" : "Encryption scheme for securing device profiles stored on the
server.<br><br>If enabled, each device profile is encrypted using a unique random secret key
using the given strength of AES encryption in CBC mode with PKCS#5 padding. An HMAC-SHA of the
given strength (truncated to half-size) is used to ensure integrity protection and authenticated
encryption. The unique random key is encrypted with the given RSA key pair and stored with the device
profile.<p><p><i>Note:</i> AES-256 may require installation of the JCE Unlimited Strength policy
files.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "oathAttrName" : {
          "title" : "Profile Storage Attribute",
          "description" : "Attribute for storing ForgeRock Authenticator OATH profiles.<br><br>The
default attribute is added to the user store during OpenAM installation. If you want to use a
different attribute, you must make sure to add it to your user store schema prior to deploying two-
step verification with a ForgeRock OATH authenticator app in OpenAM. OpenAM must be able to write to
the attribute.",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticatorOATHSkippableName" : {
          "title" : "ForgeRock Authenticator (OATH) Device Skippable Attribute Name",
          "description" : "The data store attribute that holds the user's decision to enable or
disable obtaining and providing a password obtained from the ForgeRock Authenticator app. This
attribute must be writeable.",
          "propertyOrder" : 800,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticatorOATHDeviceSettingsEncryptionKeystorePassword" : {
          "title" : "Key Store Password",
          "description" : "Password to unlock the key store. This password will be encrypted.",
          "propertyOrder" : 500,
          "required" : false,
          "type" : "string",
          "format" : "password",
          "exampleValue" : ""
        },
        "authenticatorOATHDeviceSettingsEncryptionKeystoreKeyPairAlias" : {
          "title" : "Key-Pair Alias",
          "description" : "Alias of the certificate and private key in the key store. The private key
is used to encrypt and decrypt device profiles.",
          "propertyOrder" : 600,

```

```

    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorOATHDeviceSettingsEncryptionKeystore" : {
    "title" : "Encryption Key Store",
    "description" : "Path to the key store from which to load encryption keys.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorOATHDeviceSettingsEncryptionKeystorePrivateKeyPassword" : {
    "title" : "Private Key Password",
    "description" : "Password to unlock the private key.",
    "propertyOrder" : 700,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "authenticatorOATHDeviceSettingsEncryptionKeystoreType" : {
    "title" : "Key Store Type",
    "description" : "Type of encryption key store.<br><br><i>Note:</i> PKCS#11 keys tores
require hardware support such as a security device or smart card and is not available by default
in most JVM installations.<p><p>See the <a href=\"https://docs.oracle.com/javase/8/docs/technotes/
guides/security/p11guide.html\" target=\"_blank\">JDK 8 PKCS#11 Reference Guide</a> for more
details.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}

```

1.25. AuthenticatorOathModule

1.25.1. Realm Operations

Resource path: `/realm-config/authentication/modules/authenticatoroath`

Resource version: `1.0`

1.25.1.1. create

Usage:

```
am> create AuthenticatorOathModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "addChecksumToOtpEnabled" : {
      "title" : "Add Checksum Digit",
      "description" : "This adds a checksum digit to the OTP.<br><br>This adds a digit to the end
of the OTP generated to be used as a checksum to verify the OTP was generated correctly. This is in
addition to the actual password length. You should only set this if your device supports it.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "oathAlgorithm" : {
      "title" : "OATH Algorithm to Use",
      "description" : "Choose the algorithm your device uses to generate the OTP.<br><br>HOTP uses a
counter value that is incremented every time a new OTP is generated. TOTP generates a new OTP every
few seconds as specified by the time step interval.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "totpTimeStepInterval" : {
      "title" : "TOTP Time Step Interval",
      "description" : "The TOTP time step in seconds that the OTP device uses to generate the
OTP.<br><br>This is the time interval that one OTP is valid for. For example, if the time step is 30
seconds, then a new OTP will be generated every 30 seconds. This makes a single OTP valid for only 30
seconds.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "totpMaximumClockDrift" : {
      "title" : "Maximum Allowed Clock Drift",
      "description" : "Number of time steps a client is allowed to get out of sync with the server
before manual resynchronisation is required. For example, with 3 allowed drifts and a time step
interval of 30 seconds the server will allow codes from up to 90 seconds from the current time to be
treated as the current time step. The drift for a user's device is calculated each time they enter a
new code. If the drift exceeds this value, the user's authentication code will be rejected.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
}
```

```

"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"minimumSecretKeyLength" : {
  "title" : "Minimum Secret Key Length",
  "description" : "Number of hexadecimal characters allowed for the Secret Key.",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"totpTimeStepsInWindow" : {
  "title" : "TOTP Time Steps",
  "description" : "The number of time steps to check before and after receiving a OTP.<br><br>This is the number of time step intervals to check the received OTP against both forward in time and back in time. For example, with 1 time steps and a time step interval of 30 seconds the server will allow a code between the previous code, the current code and the next code.",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"oathIssuerName" : {
  "title" : "Name of the Issuer",
  "description" : "Name to identify the OTP issuer.",
  "propertyOrder" : 1100,
  "required" : true,
  "type" : "string",
  "exampleValue" : "ForgeRock"
},
"passwordLength" : {
  "title" : "One Time Password Length ",
  "description" : "The length of the generated OTP in digits, must be at least 6 and compatible with the hardware/software OTP generators you expect your end-users to use. For example, Google and ForgeRock authenticators support values of 6 and 8.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"frOathOtpMaxRetry" : {
  "title" : "One Time Password Max Retry",
  "description" : "The number of times entry of the OTP may be attempted. Minimum is 1 maximum is 10 and default is 3.",
  "propertyOrder" : null,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"truncationOffset" : {
  "title" : "Truncation Offset",

```



```
"description" : "This adds an offset to the generation of the OTP.<br><br>This is an option used by the HOTP algorithm that not all devices support. This should be left default unless you know your device uses a offset.",
"propertyOrder" : 700,
"required" : true,
"type" : "integer",
"exampleValue" : ""
},
"hotpWindowSize" : {
  "title" : "HOTP Window Size",
  "description" : "The size of the window to resynchronize with the client.<br><br>This sets the window that the OTP device and the server counter can be out of sync. For example, if the window size is 100 and the servers last successful login was at counter value 2, then the server will accept a OTP from the OTP device that is from device counter 3 to 102.",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}
}
```

1.25.1.2. delete

Usage:

```
am> delete AuthenticatorOathModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.25.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticatorOathModule --realm Realm --actionName getAllTypes
```

1.25.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticatorOathModule --realm Realm --actionName getCreatableTypes
```

1.25.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticatorOathModule --realm Realm --actionName nextdescendents
```

1.25.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query AuthenticatorOathModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.25.1.7. read

Usage:

```
am> read AuthenticatorOathModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.25.1.8. update

Usage:

```
am> update AuthenticatorOathModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "addChecksumToOtpEnabled" : {
      "title" : "Add Checksum Digit",
      "description" : "This adds a checksum digit to the OTP.<br><br>This adds a digit to the end of the OTP generated to be used as a checksum to verify the OTP was generated correctly. This is in addition to the actual password length. You should only set this if your device supports it.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "oathAlgorithm" : {
      "title" : "OATH Algorithm to Use",
      "description" : "Choose the algorithm your device uses to generate the OTP.<br><br>HOTP uses a counter value that is incremented every time a new OTP is generated. TOTP generates a new OTP every few seconds as specified by the time step interval.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "totpTimeStepInterval" : {
      "title" : "TOTP Time Step Interval",
      "description" : "The TOTP time step in seconds that the OTP device uses to generate the OTP.<br><br>This is the time interval that one OTP is valid for. For example, if the time step is 30 seconds, then a new OTP will be generated every 30 seconds. This makes a single OTP valid for only 30 seconds.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "totpMaximumClockDrift" : {
      "title" : "Maximum Allowed Clock Drift",
      "description" : "Number of time steps a client is allowed to get out of sync with the server before manual resynchronisation is required. For example, with 3 allowed drifts and a time step interval of 30 seconds the server will allow codes from up to 90 seconds from the current time to be treated as the current time step. The drift for a user's device is calculated each time they enter a new code. If the drift exceeds this value, the user's authentication code will be rejected.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

```

},
"minimumSecretKeyLength" : {
  "title" : "Minimum Secret Key Length",
  "description" : "Number of hexadecimal characters allowed for the Secret Key.",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"totpTimeStepsInWindow" : {
  "title" : "TOTP Time Steps",
  "description" : "The number of time steps to check before and after receiving a OTP.<br><br>This is the number of time step intervals to check the received OTP against both forward in time and back in time. For example, with 1 time steps and a time step interval of 30 seconds the server will allow a code between the previous code, the current code and the next code.",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"oathIssuerName" : {
  "title" : "Name of the Issuer",
  "description" : "Name to identify the OTP issuer.",
  "propertyOrder" : 1100,
  "required" : true,
  "type" : "string",
  "exampleValue" : "ForgeRock"
},
"passwordLength" : {
  "title" : "One Time Password Length ",
  "description" : "The length of the generated OTP in digits, must be at least 6 and compatible with the hardware/software OTP generators you expect your end-users to use. For example, Google and ForgeRock authenticators support values of 6 and 8.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"frOathOtpMaxRetry" : {
  "title" : "One Time Password Max Retry",
  "description" : "The number of times entry of the OTP may be attempted. Minimum is 1 maximum is 10 and default is 3.",
  "propertyOrder" : null,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"truncationOffset" : {
  "title" : "Truncation Offset",
  "description" : "This adds an offset to the generation of the OTP.<br><br>This is an option used by the HOTP algorithm that not all devices support. This should be left default unless you know your device uses a offset.",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"hotpWindowSize" : {
  "title" : "HOTP Window Size",

```

```
"description" : "The size of the window to resynchronize with the client.<br><br>This sets the window that the OTP device and the server counter can be out of sync. For example, if the window size is 100 and the servers last successful login was at counter value 2, then the server will accept a OTP from the OTP device that is from device counter 3 to 102.",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}
}
```

1.25.2. Global Operations

Resource path: `/global-config/authentication/modules/authenticatorOath`

Resource version: `1.0`

1.25.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticatorOathModule --global --actionName getAllTypes
```

1.25.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticatorOathModule --global --actionName getCreatableTypes
```

1.25.2.3. nextDescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticatorOathModule --global --actionName nextDescendants
```

1.25.2.4. read

Usage:

```
am> read AuthenticatorOathModule --global
```

1.25.2.5. update

Usage:

```
am> update AuthenticatorOathModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "addChecksumToOtpEnabled" : {
          "title" : "Add Checksum Digit",
          "description" : "This adds a checksum digit to the OTP.<br><br>This adds a digit to the end of the OTP generated to be used as a checksum to verify the OTP was generated correctly. This is in addition to the actual password length. You should only set this if your device supports it.",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "totpMaximumClockDrift" : {
          "title" : "Maximum Allowed Clock Drift",
          "description" : "Number of time steps a client is allowed to get out of sync with the server before manual resynchronisation is required. For example, with 3 allowed drifts and a time step interval of 30 seconds the server will allow codes from up to 90 seconds from the current time to be treated as the current time step. The drift for a user's device is calculated each time they enter a new code. If the drift exceeds this value, the user's authentication code will be rejected.",
          "propertyOrder" : 1000,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "oathIssuerName" : {
          "title" : "Name of the Issuer",
          "description" : "Name to identify the OTP issuer.",
          "propertyOrder" : 1100,
          "required" : true,
          "type" : "string",
          "exampleValue" : "ForgeRock"
        },
        "frOathOtpMaxRetry" : {
```

```

    "title" : "One Time Password Max Retry",
    "description" : "The number of times entry of the OTP may be attempted. Minimum is 1 maximum
is 10 and default is 3.",
    "propertyOrder" : null,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "totpTimeStepsInWindow" : {
    "title" : "TOTP Time Steps",
    "description" : "The number of time steps to check before and after receiving a
OTP.<br><br>This is the number of time step intervals to check the received OTP against both forward
in time and back in time. For example, with 1 time steps and a time step interval of 30 seconds the
server will allow a code between the previous code, the current code and the next code.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "oathAlgorithm" : {
    "title" : "OATH Algorithm to Use",
    "description" : "Choose the algorithm your device uses to generate the OTP.<br><br>HOTP uses
a counter value that is incremented every time a new OTP is generated. TOTP generates a new OTP every
few seconds as specified by the time step interval.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "minimumSecretKeyLength" : {
    "title" : "Minimum Secret Key Length",
    "description" : "Number of hexadecimal characters allowed for the Secret Key.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "totpTimeStepInterval" : {
    "title" : "TOTP Time Step Interval",
    "description" : "The TOTP time step in seconds that the OTP device uses to generate the
OTP.<br><br>This is the time interval that one OTP is valid for. For example, if the time step is 30
seconds, then a new OTP will be generated every 30 seconds. This makes a single OTP valid for only 30
seconds.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "truncationOffset" : {
    "title" : "Truncation Offset",
    "description" : "This adds an offset to the generation of the OTP.<br><br>This is an option
used by the HOTP algorithm that not all devices support. This should be left default unless you know
your device uses a offset.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "hotpWindowSize" : {

```

```

    "title" : "HOTP Window Size",
    "description" : "The size of the window to resynchronize with the client.<br><br>This sets
the window that the OTP device and the server counter can be out of sync. For example, if the window
size is 100 and the servers last successful login was at counter value 2, then the server will accept
a OTP from the OTP device that is from device counter 3 to 102.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "passwordLength" : {
    "title" : "One Time Password Length ",
    "description" : "The length of the generated OTP in digits, must be at least 6 and
compatible with the hardware/software OTP generators you expect your end-users to use. For example,
Google and ForgeRock authenticators support values of 6 and 8.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}

```

1.26. AuthenticatorPush

1.26.1. Realm Operations

Resource path: [/realm-config/services/authenticatorPushService](#)

Resource version: [1.0](#)

1.26.1.1. create

Usage:

```
am> create AuthenticatorPush --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "authenticatorPushDeviceSettingsEncryptionKeystorePrivateKeyPassword" : {

```



```

    "title" : "Private Key Password",
    "description" : "Password to unlock the private key.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionKeystorePassword" : {
    "title" : "Key Store Password",
    "description" : "Password to unlock the key store. This password is encrypted when it is saved
in the OpenAM configuration. You should modify the default value.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionKeystoreKeyPairAlias" : {
    "title" : "Key-Pair Alias",
    "description" : "Alias of the certificate and private key in the key store. The private key is
used to encrypt and decrypt device profiles.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionKeystore" : {
    "title" : "Encryption Key Store",
    "description" : "Path to the key store from which to load encryption keys.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "pushAttrName" : {
    "title" : "Profile Storage Attribute",
    "description" : "The user's attribute in which to store Push Notification profiles.<br><br>The
default attribute is added to the schema when you prepare a user store for use with OpenAM. If you
want to use a different attribute, you must make sure to add it to your user store schema prior to
deploying push notifications with the ForgeRock Authenticator app in OpenAM. OpenAM must be able to
write to the attribute.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionScheme" : {
    "title" : "Device Profile Encryption Scheme",
    "description" : "Encryption scheme to use to secure device profiles stored on the
server.<br><br>If enabled, each device profile is encrypted using a unique random secret key
using the given strength of AES encryption in CBC mode with PKCS#5 padding. An HMAC-SHA of the
given strength (truncated to half-size) is used to ensure integrity protection and authenticated
encryption. The unique random key is encrypted with the given RSA key pair and stored with the device
profile.<p><p><i>Note:</i> AES-256 may require installation of the JCE Unlimited Strength policy
files.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",

```

```
    "exampleValue" : ""
  },
  "authenticatorPushSkippableName" : {
    "title" : "ForgeRock Authenticator (Push) Device Skippable Attribute Name",
    "description" : "Name of the attribute on a user's profile used to store their selection of
whether to skip ForgeRock Authenticator (Push) 2FA modules.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionKeystoreType" : {
    "title" : "Key Store Type",
    "description" : "Type of key store to load.<br><br><i>Note:</i> PKCS#11 key stores require
hardware support such as a security device or smart card and is not available by default in most
JVM installations.<p><p>See the <a href="https://docs.oracle.com/javase/8/docs/technotes/guides/
security/p11guide.html\" target="_blank\">JDK 8 PKCS#11 Reference Guide</a> for more details.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.26.1.2. delete

Usage:

```
am> delete AuthenticatorPush --realm Realm
```

1.26.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticatorPush --realm Realm --actionName getAllTypes
```

1.26.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticatorPush --realm Realm --actionName getCreatableTypes
```

1.26.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticatorPush --realm Realm --actionName nextdescendents
```

1.26.1.6. read

Usage:

```
am> read AuthenticatorPush --realm Realm
```

1.26.1.7. update

Usage:

```
am> update AuthenticatorPush --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticatorPushDeviceSettingsEncryptionKeystorePrivateKeyPassword" : {
      "title" : "Private Key Password",
      "description" : "Password to unlock the private key.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "authenticatorPushDeviceSettingsEncryptionKeystorePassword" : {
      "title" : "Key Store Password",
      "description" : "Password to unlock the key store. This password is encrypted when it is saved
in the OpenAM configuration. You should modify the default value.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "authenticatorPushDeviceSettingsEncryptionKeystoreKeyPairAlias" : {
      "title" : "Key-Pair Alias",
      "description" : "Alias of the certificate and private key in the key store. The private key is
used to encrypt and decrypt device profiles.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticatorPushDeviceSettingsEncryptionKeystore" : {
      "title" : "Encryption Key Store",
```

```

    "description" : "Path to the key store from which to load encryption keys.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "pushAttrName" : {
    "title" : "Profile Storage Attribute",
    "description" : "The user's attribute in which to store Push Notification profiles.<br><br>The default attribute is added to the schema when you prepare a user store for use with OpenAM. If you want to use a different attribute, you must make sure to add it to your user store schema prior to deploying push notifications with the ForgeRock Authenticator app in OpenAM. OpenAM must be able to write to the attribute.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionScheme" : {
    "title" : "Device Profile Encryption Scheme",
    "description" : "Encryption scheme to use to secure device profiles stored on the server.<br><br>If enabled, each device profile is encrypted using a unique random secret key using the given strength of AES encryption in CBC mode with PKCS#5 padding. An HMAC-SHA of the given strength (truncated to half-size) is used to ensure integrity protection and authenticated encryption. The unique random key is encrypted with the given RSA key pair and stored with the device profile.<p><p><i>Note:</i> AES-256 may require installation of the JCE Unlimited Strength policy files.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushSkippableName" : {
    "title" : "ForgeRock Authenticator (Push) Device Skippable Attribute Name",
    "description" : "Name of the attribute on a user's profile used to store their selection of whether to skip ForgeRock Authenticator (Push) 2FA modules.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionKeystoreType" : {
    "title" : "Key Store Type",
    "description" : "Type of key store to load.<br><br><i>Note:</i> PKCS#11 key stores require hardware support such as a security device or smart card and is not available by default in most JVM installations.<p><p>See the <a href=\"https://docs.oracle.com/javase/8/docs/technotes/guides/security/pllguide.html\" target=\"_blank\">JDK 8 PKCS#11 Reference Guide</a> for more details.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}

```

1.26.2. Global Operations

Resource path: `/global-config/services/authenticatorPushService`

Resource version: `1.0`

1.26.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticatorPush --global --actionName getAllTypes
```

1.26.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticatorPush --global --actionName getCreatableTypes
```

1.26.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticatorPush --global --actionName nextdescendents
```

1.26.2.4. read

Usage:

```
am> read AuthenticatorPush --global
```

1.26.2.5. update

Usage:

```
am> update AuthenticatorPush --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
```

```

"properties" : {
  "pushAttrName" : {
    "title" : "Profile Storage Attribute",
    "description" : "The user's attribute in which to store Push Notification
profiles.<br><br>The default attribute is added to the schema when you prepare a user store for use
with OpenAM. If you want to use a different attribute, you must make sure to add it to your user
store schema prior to deploying push notifications with the ForgeRock Authenticator app in OpenAM.
OpenAM must be able to write to the attribute.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionKeystoreKeyPairAlias" : {
    "title" : "Key-Pair Alias",
    "description" : "Alias of the certificate and private key in the key store. The private key
is used to encrypt and decrypt device profiles.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionKeystorePassword" : {
    "title" : "Key Store Password",
    "description" : "Password to unlock the key store. This password is encrypted when it is
saved in the OpenAM configuration. You should modify the default value.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionKeystorePrivateKeyPassword" : {
    "title" : "Private Key Password",
    "description" : "Password to unlock the private key.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionScheme" : {
    "title" : "Device Profile Encryption Scheme",
    "description" : "Encryption scheme to use to secure device profiles stored on the
server.<br><br>If enabled, each device profile is encrypted using a unique random secret key
using the given strength of AES encryption in CBC mode with PKCS#5 padding. An HMAC-SHA of the
given strength (truncated to half-size) is used to ensure integrity protection and authenticated
encryption. The unique random key is encrypted with the given RSA key pair and stored with the device
profile.<p><p><i>Note:</i> AES-256 may require installation of the JCE Unlimited Strength policy
files.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionKeystore" : {
    "title" : "Encryption Key Store",
    "description" : "Path to the key store from which to load encryption keys.",
    "propertyOrder" : 300,

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushDeviceSettingsEncryptionKeystoreType" : {
    "title" : "Key Store Type",
    "description" : "Type of key store to load.<br><br><i>Note:</i> PKCS#11 key stores require
hardware support such as a security device or smart card and is not available by default in most
JVM installations.<p><p>See the <a href=\"https://docs.oracle.com/javase/8/docs/technotes/guides/
security/p11guide.html\" target=\"_blank\">JDK 8 PKCS#11 Reference Guide</a> for more details.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticatorPushSkippableName" : {
    "title" : "ForgeRock Authenticator (Push) Device Skippable Attribute Name",
    "description" : "Name of the attribute on a user's profile used to store their selection of
whether to skip ForgeRock Authenticator (Push) 2FA modules.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}
}

```

1.27. AuthenticatorPushModule

1.27.1. Realm Operations

Resource path: `/realm-config/authentication/modules/authPush`

Resource version: `1.0`

1.27.1.1. create

Usage:

```
am> create AuthenticatorPushModule --realm Realm --id id --body body
```

Parameters:

`--id`

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "pushMessage" : {
      "title" : "Login Message",
      "description" : "Message transmitted over Push. Use the label {{user}} to replace with the registered login's username, and {{issuer}} to replace with the name of the issuer stored at registration.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "timeoutInMilliseconds" : {
      "title" : "Return Message Timeout (ms)",
      "description" : "The period of time (in milliseconds) within which a push notification should be replied to.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.27.1.2. delete

Usage:

```
am> delete AuthenticatorPushModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.27.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticatorPushModule --realm Realm --actionName getAllTypes
```

1.27.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticatorPushModule --realm Realm --actionName getCreatableTypes
```

1.27.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticatorPushModule --realm Realm --actionName nextdescendents
```

1.27.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query AuthenticatorPushModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.27.1.7. read

Usage:

```
am> read AuthenticatorPushModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.27.1.8. update

Usage:

```
am> update AuthenticatorPushModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "pushMessage" : {
      "title" : "Login Message",
      "description" : "Message transmitted over Push. Use the label {{user}} to replace with the
registered login's username, and {{issuer}} to replace with the name of the issuer stored at
registration.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "timeoutInMilliSeconds" : {
      "title" : "Return Message Timeout (ms)",
      "description" : "The period of time (in milliseconds) within which a push notification should be
replied to.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.27.2. Global Operations

Resource path: `/global-config/authentication/modules/authPush`

Resource version: `1.0`

1.27.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticatorPushModule --global --actionName getAllTypes
```

1.27.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticatorPushModule --global --actionName getCreatableTypes
```

1.27.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticatorPushModule --global --actionName nextdescendents
```

1.27.2.4. read

Usage:

```
am> read AuthenticatorPushModule --global
```

1.27.2.5. update

Usage:

```
am> update AuthenticatorPushModule --global --body body
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "pushMessage" : {
          "title" : "Login Message",
          "description" : "Message transmitted over Push. Use the label {{user}} to replace with
the registered login's username, and {{issuer}} to replace with the name of the issuer stored at
registration.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "timeoutInMilliseconds" : {
          "title" : "Return Message Timeout (ms)",
          "description" : "The period of time (in milliseconds) within which a push notification
should be replied to.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        }
      }
    },
    "type" : "object",
    "title" : "Realm Defaults"
  }
}
```

1.28. AuthenticatorPushRegistrationModule

1.28.1. Realm Operations

Resource path: [/realm-config/authentication/modules/authPushReg](#)

Resource version: 1.0

1.28.1.1. create

Usage:

```
am> create AuthenticatorPushRegistrationModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "bgcolour" : {
      "title" : "Background Colour",
      "description" : "The background colour of the image to display behind your identity issuer's
      logo within the mobile app.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "appleLink" : {
      "title" : "App Store App URL",
      "description" : "URL of the app to download on the App Store.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
      authentication module has an authentication level that can be used to indicate the level of security
      associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "timeoutInMilliSeconds" : {
      "title" : "Registration Response Timeout (ms)",
      "description" : "The period of time (in milliseconds) within which the registration QR code
      should be replied to.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "imgUrl" : {
      "title" : "Image URL",
      "description" : "The location of the image to download and display as your identity issuer's
      logo within the mobile app.",
      "propertyOrder" : 500,

```

```
    "required" : true,
    "type" : "string",
    "exampleValue" : "http://example.com/image.png"
  },
  "googleLink" : {
    "title" : "Google Play URL",
    "description" : "URL of the app to download on Google Play.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "issuer" : {
    "title" : "Issuer Name",
    "description" : "The Name of the service as it will appear on the registered device.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.28.1.2. delete

Usage:

```
am> delete AuthenticatorPushRegistrationModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.28.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticatorPushRegistrationModule --realm Realm --actionName getAllTypes
```

1.28.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticatorPushRegistrationModule --realm Realm --actionName getCreatableTypes
```

1.28.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticatorPushRegistrationModule --realm Realm --actionName nextdescendents
```

1.28.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query AuthenticatorPushRegistrationModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.28.1.7. read

Usage:

```
am> read AuthenticatorPushRegistrationModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.28.1.8. update

Usage:

```
am> update AuthenticatorPushRegistrationModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "bgcolour" : {
      "title" : "Background Colour",
      "description" : "The background colour of the image to display behind your identity issuer's logo within the mobile app.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "appleLink" : {
      "title" : "App Store App URL",
      "description" : "URL of the app to download on the App Store.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "timeoutInMilliSeconds" : {
      "title" : "Registration Response Timeout (ms)",
      "description" : "The period of time (in milliseconds) within which the registration QR code should be replied to.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "imgUrl" : {
      "title" : "Image URL",
      "description" : "The location of the image to download and display as your identity issuer's logo within the mobile app.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "exampleValue" : "http://example.com/image.png"
    },
    "googleLink" : {
      "title" : "Google Play URL",
      "description" : "URL of the app to download on Google Play.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```



```
    },
    "issuer" : {
      "title" : "Issuer Name",
      "description" : "The Name of the service as it will appear on the registered device.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.28.2. Global Operations

Resource path: `/global-config/authentication/modules/authPushReg`

Resource version: `1.0`

1.28.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action AuthenticatorPushRegistrationModule --global --actionName getAllTypes
```

1.28.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action AuthenticatorPushRegistrationModule --global --actionName getCreatableTypes
```

1.28.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action AuthenticatorPushRegistrationModule --global --actionName nextdescendents
```

1.28.2.4. read

Usage:

```
am> read AuthenticatorPushRegistrationModule --global
```

1.28.2.5. update

Usage:

```
am> update AuthenticatorPushRegistrationModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "appleLink" : {
          "title" : "App Store App URL",
          "description" : "URL of the app to download on the App Store.",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "imgUrl" : {
          "title" : "Image URL",
          "description" : "The location of the image to download and display as your identity issuer's
logo within the mobile app.",
          "propertyOrder" : 500,
          "required" : true,
          "type" : "string",
          "exampleValue" : "http://example.com/image.png"
        },
        "timeoutInMilliseconds" : {
          "title" : "Registration Response Timeout (ms)",
          "description" : "The period of time (in milliseconds) within which the registration QR code
should be replied to.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "bgcolour" : {
          "title" : "Background Colour",
          "description" : "The background colour of the image to display behind your identity issuer's
logo within the mobile app.",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",

```

```
    "propertyOrder" : 100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "googleLink" : {
    "title" : "Google Play URL",
    "description" : "URL of the app to download on Google Play.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "issuer" : {
    "title" : "Issuer Name",
    "description" : "The Name of the service as it will appear on the registered device.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
```

1.29. BaseUrlSource

1.29.1. Realm Operations

Resource path: [/realm-config/services/baseurl](#)

Resource version: **1.0**

1.29.1.1. create

Usage:

```
am> create BaseUrlSource --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
```

```

"source" : {
  "title" : "Base URL Source",
  "description" : "Specifies the source of the base URL. Choose from the
following:<ul> <li>Extension class. Specifies that the extension class returns a
base URL from a provided HttpServletRequest. In the Extension class name field, enter
<code>org.forgerock.openam.services.baseurl.BaseURLProvider</code>.</li><li>Fixed value. Specifies
that the base URL is retrieved from a specific base URL value. In the Fixed value base URL field,
enter the base URL value.</li><li>Forwarded header. Specifies that the base URL is retrieved from
a forwarded header field in the HTTP request. The Forwarded HTTP header field is standardized and
specified in <a href=\"https://tools.ietf.org/html/rfc7239\">RFC7239</a>.</li><li>Host/protocol
from incoming request. Specifies that the hostname, server name, and port are retrieved from the
incoming HTTP request.</li><li>X-Forwarded-* headers. Specifies that the base URL is retrieved from
non-standard header fields, such as <code>X-Forwarded-For</code>, <code>X-Forwarded-By</code>, and
<code>X-Forwarded-Proto</code>.</li></ul>",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"extensionClassName" : {
  "title" : "Extension class name",
  "description" : "If Extension class is selected as the Base URL source, enter
<code>org.forgerock.openam.services.baseurl.BaseURLProvider</code> in the Extension class name
field.",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"contextPath" : {
  "title" : "Context path",
  "description" : "Specifies the context path for the base URL.<p><p>If provided, the base URL
includes the deployment context path appended to the calculated URL.<p>For example, <code>/openam/</
code>.",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"fixedValue" : {
  "title" : "Fixed value base URL",
  "description" : "If Fixed value is selected as the Base URL source, enter the base URL in the
Fixed value base URL field.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
}
}

```

1.29.1.2. delete

Usage:

```
am> delete BaseUrlSource --realm Realm
```

1.29.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action BaseUrlSource --realm Realm --actionName getAllTypes
```

1.29.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action BaseUrlSource --realm Realm --actionName getCreatableTypes
```

1.29.1.5. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action BaseUrlSource --realm Realm --actionName nextdescendants
```

1.29.1.6. read

Usage:

```
am> read BaseUrlSource --realm Realm
```

1.29.1.7. update

Usage:

```
am> update BaseUrlSource --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "source" : {
      "title" : "Base URL Source",
      "description" : "Specifies the source of the base URL. Choose from the
following:<ul> <li>Extension class. Specifies that the extension class returns a
base URL from a provided HttpServletRequest. In the Extension class name field, enter
<code>org.forgerock.openam.services.baseurl.BaseURLProvider</code>.</li><li>Fixed value. Specifies
```

that the base URL is retrieved from a specific base URL value. In the Fixed value base URL field, enter the base URL value.

- Forwarded header. Specifies that the base URL is retrieved from a forwarded header field in the HTTP request. The Forwarded HTTP header field is standardized and specified in [RFC7239](https://tools.ietf.org/html/rfc7239).
- Host/protocol from incoming request. Specifies that the hostname, server name, and port are retrieved from the incoming HTTP request.
- X-Forwarded-* headers. Specifies that the base URL is retrieved from non-standard header fields, such as `X-Forwarded-For`, `X-Forwarded-By`, and `X-Forwarded-Proto`.

```

    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "extensionClassName" : {
    "title" : "Extension class name",
    "description" : "If Extension class is selected as the Base URL source, enter
<code>org.forgerock.openam.services.baseurl.BaseURLProvider</code> in the Extension class name
field.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "contextPath" : {
    "title" : "Context path",
    "description" : "Specifies the context path for the base URL.<p><p>If provided, the base URL
includes the deployment context path appended to the calculated URL.<p>For example, <code>/openam/</code>.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "fixedValue" : {
    "title" : "Fixed value base URL",
    "description" : "If Fixed value is selected as the Base URL source, enter the base URL in the
Fixed value base URL field.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}

```

1.29.2. Global Operations

Resource path: `/global-config/services/baseurl`

Resource version: `1.0`

1.29.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action BaseUrlSource --global --actionName getAllTypes
```

1.29.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action BaseUrlSource --global --actionName getCreatableTypes
```

1.29.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action BaseUrlSource --global --actionName nextdescendents
```

1.29.2.4. read

Usage:

```
am> read BaseUrlSource --global
```

1.29.2.5. update

Usage:

```
am> update BaseUrlSource --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "extensionClassName" : {
          "title" : "Extension class name",
          "description" : "If Extension class is selected as the Base URL source, enter
<code>org.forgerock.openam.services.baseurl.BaseURLProvider</code> in the Extension class name
field.",
          "propertyOrder" : 300,
          "required" : true,
```

```

        "type" : "string",
        "exampleValue" : ""
    },
    "contextPath" : {
        "title" : "Context path",
        "description" : "Specifies the context path for the base URL.<p><p>If provided, the base URL includes the deployment context path appended to the calculated URL.<p>For example, <code>/openam/</code>.",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "source" : {
        "title" : "Base URL Source",
        "description" : "Specifies the source of the base URL. Choose from the following:<ul> <li>Extension class. Specifies that the extension class returns a base URL from a provided HttpServletRequest. In the Extension class name field, enter <code>org.forgerock.openam.services.baseurl.BaseURLProvider</code>.</li><li>Fixed value. Specifies that the base URL is retrieved from a specific base URL value. In the Fixed value base URL field, enter the base URL value.</li><li>Forwarded header. Specifies that the base URL is retrieved from a forwarded header field in the HTTP request. The Forwarded HTTP header field is standardized and specified in <a href=\"https://tools.ietf.org/html/rfc7239\">RFC7239</a>.</li><li>Host/protocol from incoming request. Specifies that the hostname, server name, and port are retrieved from the incoming HTTP request.</li><li>X-Forwarded-* headers. Specifies that the base URL is retrieved from non-standard header fields, such as <code>X-Forwarded-For</code>, <code>X-Forwarded-By</code>, and <code>X-Forwarded-Proto</code>.</li></ul>",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "fixedValue" : {
        "title" : "Fixed value base URL",
        "description" : "If Fixed value is selected as the Base URL source, enter the base URL in the Fixed value base URL field.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
}
}
}

```

1.30. CRESTReporter

1.30.1. Global Operations

Resource path: </global-config/services/monitoring/crest>

Resource version: 1.0

1.30.1.1. create

Usage:

```
am> create CRESTReporter --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "enabled" : {
      "title" : "Enabled",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
```

1.30.1.2. delete

Usage:

```
am> delete CRESTReporter --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.30.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action CRESTReporter --global --actionName getAllTypes
```

1.30.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action CRESTReporter --global --actionName getCreatableTypes
```

1.30.1.5. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action CRESTReporter --global --actionName nextdescendants
```

1.30.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query CRESTReporter --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.30.1.7. read

Usage:

```
am> read CRESTReporter --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.30.1.8. update

Usage:

```
am> update CRESTReporter --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "enabled" : {
      "title" : "Enabled",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
```

1.31. CertificateModule

1.31.1. Realm Operations

Resource path: `/realm-config/authentication/modules/certificate`

Resource version: `1.0`

1.31.1.1. create

Usage:

```
am> create CertificateModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "matchCertificateInLdap" : {
      "title" : "Match Certificate in LDAP",
      "description" : "The client certificate must exist in the directory for the authentication to be successful.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "otherCertificateAttributeToProfileMapping" : {
      "title" : "Other Certificate Field Used to Access User Profile",
      "description" : "This field is only used if the <i>Certificate Field Used to Access User Profile</i> attribute is set to <i>other</i>. This field allows a custom certificate field to be used as the basis of the user search.",
      "propertyOrder" : 1600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "certificateAttributeToProfileMapping" : {
      "title" : "Certificate Field Used to Access User Profile",
      "description" : "The certificate module needs to read a value from the client certificate that can be used to search the LDAP server for a matching certificate. ",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sslEnabled" : {
      "title" : "Use SSL/TLS for LDAP Access",
      "description" : "The certificate module will use SSL/TLS to access the LDAP server",
      "propertyOrder" : 1400,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "userBindPassword" : {
      "title" : "LDAP Server Authentication Password",
      "description" : "The password for the authentication user",
      "propertyOrder" : 1300,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "trustedRemoteHosts" : {
      "title" : "Trusted Remote Hosts",
```

```

        "description" : "A list of IP addresses trusted to supply client certificates.<br><br>If SSL/TLS
        is being terminated at a load balancer or at the Distributed Authentication server then this option
        can be used to ensure that only specified <i>trusted</i> hosts (identified by IP address) are allowed
        to supply client certificates to the certificate module,<br><br>Valid values for this list are as
        follows:<ul><li>none</li><li>any</li><li>multiple IP addresses</li></ul><br><br>The default value
        of <i>none</i> disables this functionality",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "certificateAttributeProfileMappingExtension" : {
        "title" : "SubjectAltNameExt Value Type to Access User Profile",
        "description" : "Use the Subject Alternative Name Field in preference to one of the standard
        certificate fields.<br><br>Selecting RFC822Name or UPN will cause this field to have precedence
        over the <i>Certificate Field Used to Access User Profile</i> or <i>Other Certificate Field Used
        to Access User Profile</i> attribute.<br><br><i>NB </i>The client certificate must contain the
        <i>Subject Alternate Name Extension</i> for this function to operate.",
        "propertyOrder" : 1700,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "cacheCRLsInMemory" : {
        "title" : "Cache CRLs in memory",
        "description" : "The CRLs will be cached in memory",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "ldapCertificateAttribute" : {
        "title" : "Subject DN Attribute Used to Search LDAP for Certificates",
        "description" : "This is the attribute used to search the directory for the
        certificate<br><br>The Certificate module will search the directory for the certificate using the
        search filter based on this attribute and the value of the Subject DN taken from the certificate.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "matchCACertificateToCRL" : {
        "title" : "Match CA Certificate to CRL",
        "description" : "The CA certificate that issued the client certificate will also be checked
        against the CRL.",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "clientCertificateHttpRequestName" : {
        "title" : "HTTP Header Name for Client Certificate",
        "description" : "The name of the HTTP request header containing the certificate, only used when
        <i>Trusted Remote Hosts</i> mode is enabled.",
        "propertyOrder" : 1900,
        "required" : true,
    }

```

```

        "type" : "string",
        "exampleValue" : ""
    },
    "userBindDN" : {
        "title" : "LDAP Server Authentication User",
        "description" : "DN of the user used by the module to authenticate to the LDAP server<br><br>The Certificate module authenticates to the LDAP server in order to search for a matching certificate. The DN entered here represents the account used for said authentication and must have read/search access to the LDAP server.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "authenticationLevel" : {
        "title" : "Authentication Level",
        "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "crlMatchingCertificateAttribute" : {
        "title" : "Issuer DN Attribute(s) Used to Search LDAP for CRLs",
        "description" : "This is the name of the attribute taken from the CA certificate that will be used to search the CRL.<br><br>If only one attribute name is specified, the ldap searchfilter will be (attrName=Value_of_the_corresponding_Attribute_from_SubjectDN)<br><br>e.g. SubjectDN of issuer cert 'C=US, CN=Some CA, serialNumber=123456', attribute name specified is 'CN', searchfilter used will be <code>(CN=Some CA)</code><br><br>If several attribute names are specified, they have to be separated by <code>,</code>. The resulting ldap searchfilter value will be a comma separated list of name attribute values, the search attribute will be <code>cn</code><br><br>e.g. SubjectDN of issuer cert 'C=US, CN=Some CA, serialNumber=123456', attribute names specified are 'CN,serialNumber', searchfilter used will be <code>cn=CN=Some CA,serialNumber=123456</code><br><br>The order of the values of the attribute names matter as they must match the value of the <code>cn</code> attribute of a crlDistributionPoint entry in the directory server.",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "ldapSearchStartDN" : {
        "title" : "LDAP Search Start or Base DN",
        "description" : "The start point in the LDAP server for the certificate search<br><br>When entering multiple entries, each entry must be prefixed with a local server name. Multiple entries allow different search Base DNS depending on the OpenAM server in use. The format is:<br><br><code>local server name | base dn</code><br><br>The local server name is the full name of the server from the list of servers and sites.",
        "propertyOrder" : 1100,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "ocspValidationEnabled" : {
        "title" : "OCSP Validation",
    }

```

```

    "description" : "Enable Online Certificate Status Protocol validation for OCSP aware
certificates<br><br>If the certificate contains OCSP validation information then OpenAM will use this
information to check the validity of the certificate as part of the authentication process.<br><br>
<i>NB </i>The OpenAM server must have Internet connectivity for OCSP to work",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "certificateLdapServers" : {
    "title" : "LDAP Server Where Certificates are Stored",
    "description" : "Use this list to set the LDAP server used to search for certificates.
<br><br>The Certificate authentication module will use this list for the LDAP server used to search
for certificates. A single entry must be in the format:<br><br><code>ldap_server:port</code><br>
<br>Multiple entries allow associations between OpenAM servers and a LDAP server. The format is:<br>
<br><code>local server name | server:port</code><br><br>The local server name is the full name of
the server from the list of servers and sites.",
    "propertyOrder" : 1000,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "iplanet-am-auth-cert-gw-cert-preferred" : {
    "title" : "Use only Certificate from HTTP request header",
    "description" : "Strictly use client cert from HTTP header over cert from HTTPS connection/
servlet attribute",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "updateCRLsFromDistributionPoint" : {
    "title" : "Update CA CRLs from CRLDistributionPoint",
    "description" : "Fetch new CA CRLs from CRLDistributionPoint and update it in
Directory Server<br><br>If the CA certificate includes an IssuingDistributionPoint or has an
CRLDistributionPoint extension set OpenAM tries to update the CRLs if need (i.e. CRL is out-of-
date). <br>This property controls if the update should be performed.<br>This property is only used
if CA CRL checking is enabled.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "matchCertificateToCRL" : {
    "title" : "Match Certificate to CRL",
    "description" : "The Client Certificate will be checked against the Certificate Revocation list
held in the directory<br><br>A Certificate Revocation List can be provisioned into the directory.
Having this option enabled will cause all client certificates to be checked against this list.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "crlHttpParameters" : {
    "title" : "HTTP Parameters for CRL Update",

```

```
"description" : "These parameters will be included in any HTTP CRL call to the Certificate Authority<br><br>If the Client or CA certificate contains the Issuing Distribution Point Extension then OpenAM will use this information to retrieve the CRL from the distribution point. This property allow custom HTTP parameters to be included in the CRL request.<br><br>The format of the parameter is as follows:<br><br><code>param1=value1,param2=value</code>",  
  "propertyOrder" : 500,  
  "required" : true,  
  "type" : "string",  
  "exampleValue" : ""  
  }  
}  
}
```

1.31.1.2. delete

Usage:

```
am> delete CertificateModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.31.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action CertificateModule --realm Realm --actionName getAllTypes
```

1.31.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action CertificateModule --realm Realm --actionName getCreatableTypes
```

1.31.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action CertificateModule --realm Realm --actionName nextdescendents
```


1.31.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query CertificateModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.31.1.7. read

Usage:

```
am> read CertificateModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.31.1.8. update

Usage:

```
am> update CertificateModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "matchCertificateInLdap" : {
      "title" : "Match Certificate in LDAP",
      "description" : "The client certificate must exist in the directory for the authentication to be successful.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  },
}
```

```

"otherCertificateAttributeToProfileMapping" : {
  "title" : "Other Certificate Field Used to Access User Profile",
  "description" : "This field is only used if the <i>Certificate Field Used to Access User Profile</i> attribute is set to <i>other</i>. This field allows a custom certificate field to be used as the basis of the user search.",
  "propertyOrder" : 1600,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"certificateAttributeToProfileMapping" : {
  "title" : "Certificate Field Used to Access User Profile",
  "description" : "The certificate module needs to read a value from the client certificate that can be used to search the LDAP server for a matching certificate. ",
  "propertyOrder" : 1500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"sslEnabled" : {
  "title" : "Use SSL/TLS for LDAP Access",
  "description" : "The certificate module will use SSL/TLS to access the LDAP server",
  "propertyOrder" : 1400,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"userBindPassword" : {
  "title" : "LDAP Server Authentication Password",
  "description" : "The password for the authentication user",
  "propertyOrder" : 1300,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"trustedRemoteHosts" : {
  "title" : "Trusted Remote Hosts",
  "description" : "A list of IP addresses trusted to supply client certificates.<br><br>If SSL/TLS is being terminated at a load balancer or at the Distributed Authentication server then this option can be used to ensure that only specified <i>trusted</i> hosts (identified by IP address) are allowed to supply client certificates to the certificate module,<br><br>Valid values for this list are as follows:<ul><li>none</li><li>any</li><li>multiple IP addresses</li></ul><br><br>The default value of <i>none</i> disables this functionality",
  "propertyOrder" : 1800,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"certificateAttributeProfileMappingExtension" : {
  "title" : "SubjectAltNameExt Value Type to Access User Profile",
  "description" : "Use the Subject Alternative Name Field in preference to one of the standard certificate fields.<br><br>Selecting RFC822Name or UPN will cause this field to have precedence over the <i>Certificate Field Used to Access User Profile</i> or <i>Other Certificate Field Used to Access User Profile</i> attribute.<br><br><i>NB </i><i>The client certificate must contain the <i>Subject Alternate Name Extension</i> for this function to operate.",

```

```

    "propertyOrder" : 1700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "cacheCRLsInMemory" : {
    "title" : "Cache CRLs in memory",
    "description" : "The CRLs will be cached in memory",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ldapCertificateAttribute" : {
    "title" : "Subject DN Attribute Used to Search LDAP for Certificates",
    "description" : "This is the attribute used to search the directory for the
certificate<br><br>The Certificate module will search the directory for the certificate using the
search filter based on this attribute and the value of the Subject DN taken from the certificate.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "matchCACertificateToCRL" : {
    "title" : "Match CA Certificate to CRL",
    "description" : "The CA certificate that issued the client certificate will also be checked
against the CRL.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "clientCertificateHttpHeaderName" : {
    "title" : "HTTP Header Name for Client Certificate",
    "description" : "The name of the HTTP request header containing the certificate, only used when
<i>Trusted Remote Hosts</i> mode is enabled.",
    "propertyOrder" : 1900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userBindDN" : {
    "title" : "LDAP Server Authentication User",
    "description" : "DN of the user used by the module to authenticate to the LDAP server<br><br>The
Certificate module authenticates to the LDAP server in order to search for a matching certificate.
The DN entered here represents the account used for said authentication and must have read/search
access to the LDAP server.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 2100,
    "required" : true,

```

```

        "type" : "integer",
        "exampleValue" : ""
    },
    "crlMatchingCertificateAttribute" : {
        "title" : "Issuer DN Attribute(s) Used to Search LDAP for CRLs",
        "description" : "This is the name of the attribute taken from the CA certificate that will
        be used to search the CRL.<br><br>If only one attribute name is specified, the ldap searchfilter
        will be (attrName=Value_of_the_corresponding_Attribute_from_SubjectDN)<br><br>e.g. SubjectDN of issuer
        cert 'C=US, CN=Some CA, serialNumber=123456',attribute name specified is 'CN', searchfilter used
        will be <code>(CN=Some CA)</code><br><br>If several attribute names are specified, they have
        to be separated by <code>,</code>. The resulting ldap searchfilter value will be a comma separated
        list of name attribute values, the search attribute will be <code>cn</code><br><br>e.g. SubjectDN of
        issuer cert 'C=US, CN=Some CA, serialNumber=123456',attribute names specified are 'CN,serialNumber',
        searchfilter used will be <code>cn=CN=Some CA,serialNumber=123456</code><br><br>The order of the values
        of the attribute names matter as they must match the value of the <code>cn</code> attribute of a
        crlDistributionPoint entry in the directory server.",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "ldapSearchStartDN" : {
        "title" : "LDAP Search Start or Base DN",
        "description" : "The start point in the LDAP server for the certificate search<br><br>When
        entering multiple entries, each entry must be prefixed with a local server name. Multiple entries
        allow different search Base DN's depending on the OpenAM server in use. The format is:<br><br>
        <code>local server name | base dn</code><br><br>The local server name is the full name of the
        server from the list of servers and sites.",
        "propertyOrder" : 1100,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "ocspValidationEnabled" : {
        "title" : "OCSP Validation",
        "description" : "Enable Online Certificate Status Protocol validation for OCSP aware
        certificates<br><br>If the certificate contains OCSP validation information then OpenAM will use this
        information to check the validity of the certificate as part of the authentication process.<br><br>
        <i>NB </i>The OpenAM server must have Internet connectivity for OCSP to work",
        "propertyOrder" : 900,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "certificateLdapServers" : {
        "title" : "LDAP Server Where Certificates are Stored",
        "description" : "Use this list to set the LDAP server used to search for certificates.
        <br><br>The Certificate authentication module will use this list for the LDAP server used to search
        for certificates. A single entry must be in the format:<br><br><code>ldap_server:port</code><br>
        <br>Multiple entries allow associations between OpenAM servers and a LDAP server. The format is:<br>
        <code>local server name | server:port</code><br><br>The local server name is the full name of
        the server from the list of servers and sites.",
        "propertyOrder" : 1000,
        "required" : true,
        "items" : {
            "type" : "string"
        }
    }
}

```

```

    },
    "type" : "array",
    "exampleValue" : ""
  },
  "iplanet-am-auth-cert-gw-cert-preferred" : {
    "title" : "Use only Certificate from HTTP request header",
    "description" : "Strictly use client cert from HTTP header over cert from HTTPS connection/
servlet attribute",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "updateCRLsFromDistributionPoint" : {
    "title" : "Update CA CRLs from CRLDistributionPoint",
    "description" : "Fetch new CA CRLs from CRLDistributionPoint and update it in
Directory Server<br><br>If the CA certificate includes an IssuingDistributionPoint or has an
CRLDistributionPoint extension set OpenAM tries to update the CRLs if needed (i.e. CRL is out-of-
date). <br></>This property controls if the update should be performed.<br></>This property is only used
if CA CRL checking is enabled.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "matchCertificateToCRL" : {
    "title" : "Match Certificate to CRL",
    "description" : "The Client Certificate will be checked against the Certificate Revocation list
held in the directory<br><br>A Certificate Revocation List can be provisioned into the directory.
Having this option enabled will cause all client certificates to be checked against this list.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "crlHttpParameters" : {
    "title" : "HTTP Parameters for CRL Update",
    "description" : "These parameters will be included in any HTTP CRL call to the Certificate
Authority<br><br>If the Client or CA certificate contains the Issuing Distribution Point Extension
then OpenAM will use this information to retrieve the CRL from the distribution point. This property
allow custom HTTP parameters to be included in the CRL request.<br><br>The format of the parameter
is as follows:<br><br><code>param1=value1,param2=value</code>",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}

```

1.31.2. Global Operations

Resource path: </global-config/authentication/modules/certificate>

Resource version: 1.0

1.31.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action CertificateModule --global --actionName getAllTypes
```

1.31.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action CertificateModule --global --actionName getCreatableTypes
```

1.31.2.3. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action CertificateModule --global --actionName nextdescendants
```

1.31.2.4. read

Usage:

```
am> read CertificateModule --global
```

1.31.2.5. update

Usage:

```
am> update CertificateModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "matchCACertificateToCRL" : {
          "title" : "Match CA Certificate to CRL",
          "description" : "The CA certificate that issued the client certificate will also be checked against the CRL.",
          "propertyOrder" : 600,

```

```

        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "iplanet-am-auth-cert-gw-cert-preferred" : {
        "title" : "Use only Certificate from HTTP request header",
        "description" : "Strictly use client cert from HTTP header over cert from HTTPS connection/
servlet attribute",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "authenticationLevel" : {
        "title" : "Authentication Level",
        "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    },
    "matchCertificateInLdap" : {
        "title" : "Match Certificate in LDAP",
        "description" : "The client certificate must exist in the directory for the authentication
to be successful.",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "sslEnabled" : {
        "title" : "Use SSL/TLS for LDAP Access",
        "description" : "The certificate module will use SSL/TLS to access the LDAP server",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "otherCertificateAttributeToProfileMapping" : {
        "title" : "Other Certificate Field Used to Access User Profile",
        "description" : "This field is only used if the <i>Certificate Field Used to Access User
Profile</i> attribute is set to <i>other</i>. This field allows a custom certificate field to be used
as the basis of the user search.",
        "propertyOrder" : 1600,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    },
    "cacheCRLsInMemory" : {
        "title" : "Cache CRLs in memory",
        "description" : "The CRLs will be cached in memory",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "matchCertificateToCRL" : {

```

```

        "title" : "Match Certificate to CRL",
        "description" : "The Client Certificate will be checked against the Certificate Revocation
list held in the directory<br><br>A Certificate Revocation List can be provisioned into the
directory. Having this option enabled will cause all client certificates to be checked against this
list.",
        "propertyOrder" : 300,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "ldapCertificateAttribute" : {
        "title" : "Subject DN Attribute Used to Search LDAP for Certificates",
        "description" : "This is the attribute used to search the directory for the
certificate<br><br>The Certificate module will search the directory for the certificate using the
search filter based on this attribute and the value of the Subject DN taken from the certificate.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "ldapSearchStartDN" : {
        "title" : "LDAP Search Start or Base DN",
        "description" : "The start point in the LDAP server for the certificate search<br><br>When
entering multiple entries, each entry must be prefixed with a local server name. Multiple entries
allow different search Base DN's depending on the OpenAM server in use. The format is:<br><br>
<code>local server name | base dn</code><br><br>The local server name is the full name of the
server from the list of servers and sites.",
        "propertyOrder" : 1100,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "trustedRemoteHosts" : {
        "title" : "Trusted Remote Hosts",
        "description" : "A list of IP addresses trusted to supply client certificates.<br><br>If
SSL/TLS is being terminated at a load balancer or at the Distributed Authentication server then this
option can be used to ensure that only specified <i>trusted</i> hosts (identified by IP address) are
allowed to supply client certificates to the certificate module,<br><br>Valid values for this list
are as follows:<ul><li>none</li><li>any</li><li>multiple IP addresses</li></ul><br><br>The default
value of <i>none</i> disables this functionality",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "updateCRLsFromDistributionPoint" : {
        "title" : "Update CA CRLs from CRLDistributionPoint",
        "description" : "Fetch new CA CRLs from CRLDistributionPoint and update it in
Directory Server<br><br>If the CA certificate includes an IssuingDistributionPoint or has an
CRLDistributionPoint extension set OpenAM tries to update the CRLs if need (i.e. CRL is out-of-
date). <br><br>This property controls if the update should be performed.<br><br>This property is only used
if CA CRL checking is enabled.",
        "propertyOrder" : 800,
    }
}

```



```

        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "crlMatchingCertificateAttribute" : {
        "title" : "Issuer DN Attribute(s) Used to Search LDAP for CRLs",
        "description" : "This is the name of the attribute taken from the CA certificate that will
        be used to search the CRL.<br><br>If only one attribute name is specified, the ldap searchfilter
        will be (attrName=Value_of_the_corresponding_Attribute_from_SubjectDN)<br>e.g. SubjectDN of issuer
        cert 'C=US, CN=Some CA, serialNumber=123456',attribute name specified is 'CN', searchfilter used
        will be <code>(CN=Some CA)</code><br><br>If serveral attribute names are specified, they have
        to separated by <code>,</code>. The resulting ldap searchfilter value will be a comma separated
        list of name attribute values, the search attribute will be <code>cn</code><br>e.g. SubjectDN of
        issuer cert 'C=US, CN=Some CA, serialNumber=123456',attribute names specified are 'CN,serialNumber',
        searchfilter used will be <code>cn=CN=Some CA,serialNumber=123456</code><br>The order of the values
        of the attribute names matter as they must match the value of the <code>cn</code> attribute of a
        crlDistributionPoint entry in the directory server.",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "crlHttpParameters" : {
        "title" : "HTTP Parameters for CRL Update",
        "description" : "These parameters will be included in any HTTP CRL call to the Certificate
        Authority<br><br>If the Client or CA certificate contains the Issuing Distribution Point Extension
        then OpenAM will use this information to retrieve the CRL from the distribution point. This property
        allow custom HTTP parameters to be included in the CRL request.<br><br>The format of the parameter
        is as follows:<br><br><code>param1=value1,param2=value</code>",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "userBindPassword" : {
        "title" : "LDAP Server Authentication Password",
        "description" : "The password for the authentication user",
        "propertyOrder" : 1300,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "clientCertificateHttpHeaderName" : {
        "title" : "HTTP Header Name for Client Certificate",
        "description" : "The name of the HTTP request header containing the certificate, only used
        when <i>Trusted Remote Hosts</i> mode is enabled.",
        "propertyOrder" : 1900,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "userBindDN" : {
        "title" : "LDAP Server Authentication User",
        "description" : "DN of the user used by the module to authenticate to the LDAP
        server<br><br>The Certificate module authenticates to the LDAP server in order to search for a
        matching certificate. The DN entered here represents the account used for said authentication and
        must have read/search access to the LDAP server.",
        "propertyOrder" : 1200,
    }

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "certificateAttributeProfileMappingExtension" : {
    "title" : "SubjectAltNameExt Value Type to Access User Profile",
    "description" : "Use the Subject Alternative Name Field in preference to one of the standard
certificate fields.<br><br>Selecting RFC822Name or UPN will cause this field to have precedence
over the <i>Certificate Field Used to Access User Profile</i> or <i>Other Certificate Field Used
to Access User Profile</i> attribute.<br><br><i>NB </i>The client certificate must contain the
<i>Subject Alternate Name Extension</i> for this function to operate.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
},
"certificateAttributeToProfileMapping" : {
  "title" : "Certificate Field Used to Access User Profile",
  "description" : "The certificate module needs to read a value from the client certificate
that can be used to search the LDAP server for a matching certificate. ",
  "propertyOrder" : 1500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"ocspValidationEnabled" : {
  "title" : "OCSP Validation",
  "description" : "Enable Online Certificate Status Protocol validation for OCSP aware
certificates<br><br>If the certificate contains OCSP validation information then OpenAM will use this
information to check the validity of the certificate as part of the authentication process.<br><br>
<i>NB </i>The OpenAM server must have Internet connectivity for OCSP to work",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"certificateLdapServers" : {
  "title" : "LDAP Server Where Certificates are Stored",
  "description" : "Use this list to set the LDAP server used to search for certificates.
<br><br>The Certificate authentication module will use this list for the LDAP server used to search
for certificates. A single entry must be in the format:<br><br><code>ldap_server:port</code><br>
<br><br>Multiple entries allow associations between OpenAM servers and a LDAP server. The format is:<br>
<br><code>local server name | server:port</code><br><br>The local server name is the full name of
the server from the list of servers and sites.",
  "propertyOrder" : 1000,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}
}

```

1.32. ChoiceCollector

1.32.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/ChoiceCollectorNode`

Resource version: `1.0`

1.32.1.1. create

Usage:

```
am> create ChoiceCollector --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "choices" : {
      "title" : "Choices",
      "description" : "List of values that represents the choices for the user",
      "propertyOrder" : 100,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "defaultChoice" : {
      "title" : "Default Choice",
      "description" : "The default selected choice value",
      "propertyOrder" : 200,
      "type" : "string",
      "exampleValue" : ""
    },
    "prompt" : {
      "title" : "Prompt",
      "description" : "Prompt displayed on the choice page",
      "propertyOrder" : 300,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "choices", "defaultChoice", "prompt" ]
}
```

1.32.1.2. delete

Usage:

```
am> delete ChoiceCollector --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.32.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ChoiceCollector --realm Realm --actionName getAllTypes
```

1.32.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ChoiceCollector --realm Realm --actionName getCreatableTypes
```

1.32.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action ChoiceCollector --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.32.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ChoiceCollector --realm Realm --actionName nextdescendents
```

1.32.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ChoiceCollector --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.32.1.8. read

Usage:

```
am> read ChoiceCollector --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.32.1.9. update

Usage:

```
am> update ChoiceCollector --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "choices" : {
      "title" : "Choices",
      "description" : "List of values that represents the choices for the user",
      "propertyOrder" : 100,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "defaultChoice" : {
      "title" : "Default Choice",
      "description" : "The default selected choice value",
      "propertyOrder" : 200,
      "type" : "string",
      "exampleValue" : ""
    },
    "prompt" : {
      "title" : "Prompt",
      "description" : "Prompt displayed on the choice page",
      "propertyOrder" : 300,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "choices", "defaultChoice", "prompt" ]
}
```

1.33. CircleOfTrust

1.33.1. Realm Operations

Resource path: `/realm-config/federation/circlesoftrust`

Resource version: `1.0`

1.33.1.1. create

Usage:

```
am> create CircleOfTrust --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "status" : {
      "title" : "Status",
      "description" : "",
      "propertyOrder" : 200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "description" : {
      "title" : "Description",
      "description" : "",
      "propertyOrder" : 100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "saml2ReaderServiceUrl" : {
      "title" : "SAML2 Reader Service URL",
      "description" : "Location of the SAML2 Reader service that reads the cookie from the Common Domain.",
      "propertyOrder" : 500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "saml2WriterServiceUrl" : {
```

```
    "title" : "SAML2 Writer Service URL",
    "description" : "Location of the SAML2 Writer service that writes the cookie to the Common
Domain.",
    "propertyOrder" : 400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "trustedProviders" : {
    "title" : "Entity Providers",
    "description" : "Minimum requirements for a circle of trust are one identity provider and one
service provider.",
    "propertyOrder" : 300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
}
```

1.33.1.2. delete

Usage:

```
am> delete CircleOfTrust --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.33.1.3. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query CircleOfTrust --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.33.1.4. read

Usage:


```
am> read CircleOfTrust --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.33.1.5. update

Usage:

```
am> update CircleOfTrust --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "status" : {
      "title" : "Status",
      "description" : "",
      "propertyOrder" : 200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "description" : {
      "title" : "Description",
      "description" : "",
      "propertyOrder" : 100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "saml2ReaderServiceUrl" : {
      "title" : "SAML2 Reader Service URL",
      "description" : "Location of the SAML2 Reader service that reads the cookie from the Common Domain.",
      "propertyOrder" : 500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "saml2WriterServiceUrl" : {
      "title" : "SAML2 Writer Service URL",
      "description" : "Location of the SAML2 Writer service that writes the cookie to the Common Domain.",

```

```
    "propertyOrder" : 400,  
    "required" : false,  
    "type" : "string",  
    "exampleValue" : ""  
  },  
  "trustedProviders" : {  
    "title" : "Entity Providers",  
    "description" : "Minimum requirements for a circle of trust are one identity provider and one  
service provider.",  
    "propertyOrder" : 300,  
    "required" : false,  
    "items" : {  
      "type" : "string"  
    },  
    "type" : "array",  
    "exampleValue" : ""  
  }  
}
```

1.34. CommonFederationConfiguration

1.34.1. Global Operations

Resource path: `/global-config/services/federation/common`

Resource version: `1.0`

1.34.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action CommonFederationConfiguration --global --actionName getAllTypes
```

1.34.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action CommonFederationConfiguration --global --actionName getCreatableTypes
```

1.34.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action CommonFederationConfiguration --global --actionName nextdescendents
```

1.34.1.4. read

Usage:

```
am> read CommonFederationConfiguration --global
```

1.34.1.5. update

Usage:

```
am> update CommonFederationConfiguration --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "monitoring" : {
      "type" : "object",
      "title" : "Monitoring",
      "propertyOrder" : 3,
      "properties" : {
        "monitoringSaml2Class" : {
          "title" : "Monitoring Provider Class for SAML2",
          "description" : "The SAML2 engine uses this class to gain access to the monitoring system.<br><br>The default implementation uses the built-in OpenAM monitoring system. A custom implementation must implement the <code>com.sun.identity.plugin.monitoring.FedMonSAML2Svc</code> interface.",
          "propertyOrder" : 2100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "monitoringSaml1Class" : {
          "title" : "Monitoring Provider Class for SAML1",
          "description" : "The SAMLv1 engine uses this class to gain access to the monitoring system.<br><br>The default implementation uses the built-in OpenAM monitoring system. A custom implementation must implement the <code>com.sun.identity.plugin.monitoring.FedMonSAML1Svc</code> interface.",
          "propertyOrder" : 2000,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "monitoringIdffClass" : {
          "title" : "Monitoring Provider Class for ID-FF",
          "description" : "The ID-FF engine uses this class to gain access to the monitoring system.<br><br>The default implementation uses the built-in OpenAM monitoring system. A custom
```

```

implementation must implement the <code>com.sun.identity.plugin.monitoring.FedMonIDFFSvc</code>
interface.",
  "propertyOrder" : 2200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"monitoringAgentClass" : {
  "title" : "Monitoring Agent Provider Class",
  "description" : "The Federation system uses this class to gain access to the monitoring
system.<br><br>The default implementation uses the built-in OpenAM monitoring system. A custom
implementation must implement the <code>com.sun.identity.plugin.monitoring.FedMonAgent</code>
interface.",
  "propertyOrder" : 1900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"algorithms" : {
  "type" : "object",
  "title" : "Algorithms",
  "propertyOrder" : 2,
  "properties" : {
    "DigestAlgorithm" : {
      "title" : "XML digest algorithm",
      "description" : "The default digest algorithm to use in signing XML.",
      "propertyOrder" : 1200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "signatureAlgorithm" : {
      "title" : "XML signature algorithm",
      "description" : "The algorithm used to sign XML documents.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "QuerySignatureAlgorithmEC" : {
      "title" : "Query String signature algorithm (EC)",
      "description" : "The default signature algorithm to use in case of EC keys.",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "canonicalizationAlgorithm" : {
      "title" : "XML canonicalization algorithm",
      "description" : "The algorithm used to canonicalize XML documents.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "QuerySignatureAlgorithmDSA" : {
      "title" : "Query String signature algorithm (DSA)",

```

```

    "description" : "The default signature algorithm to use in case of DSA keys.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "transformationAlgorithm" : {
    "title" : "XML transformation algorithm",
    "description" : "The algorithm used to transform XML documents.",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "QuerySignatureAlgorithmRSA" : {
    "title" : "Query String signature algorithm (RSA)",
    "description" : "The default signature algorithm to use in case of RSA keys.",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"implementationClasses" : {
  "type" : "object",
  "title" : "Implementation Classes",
  "propertyOrder" : 1,
  "properties" : {
    "sessionProviderClass" : {
      "title" : "SessionProvider SPI implementation class",
      "description" : "The Federation system uses this class to interface with the session service.<br><br>The default implementation uses the standard authentication and SSO APIs to access the session service. A custom implementation must implement the <code>com.sun.identity.plugin.session.SessionProvider</code> interface.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "datastoreClass" : {
      "title" : "Datastore SPI implementation class",
      "description" : "The Federation system uses this class to get/set user profile attributes.<br><br>The default implementation uses the Identity repository APIs to access user profile attributes. A custom implementation must implement the <code>com.sun.identity.plugin.datastore.DataStoreProvider</code> interface. ",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "signatureProviderClass" : {
      "title" : "SignatureProvider SPI implementation class",
      "description" : "The Federation system uses this class to digitally sign SAML documents.<br><br>The default implementation uses the XERCES APIs to sign the documents. A custom implementation must implement the <code>com.sun.identity.saml.xmlsig.SignatureProvider</code> interface.",
      "propertyOrder" : 700,
      "required" : true,

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "keyProviderClass" : {
    "title" : "KeyProvider SPI implementation class",
    "description" : "The Federation system uses this class to provide access to the
underlying Java keystore.<br><br>The default implementation uses the Java Cryptographic
Engine to provide access to the Java keystore. A custom implementation must implement the
<code>com.sun.identity.saml.xmlsig.KeyProvider</code> interface.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "configurationClass" : {
    "title" : "ConfigurationInstance SPI implementation class",
    "description" : "The Federation system uses this class to fetch
service configuration.<br><br>The default implementation uses the SMS APIs
to access service configuration. A custom implementation must implement the
<code>com.sun.identity.plugin.configuration.ConfigurationInstance</code> interface.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "passwordDecoderClass" : {
    "title" : "PasswordDecoder SPI implementation class",
    "description" : "The Federation system uses this class to decode password
encoded by OpenAM.<br><br>The default implementation uses the internal OpenAM
decryption API to decode passwords. A custom implementation must implement the
<code>com.sun.identity.saml.xmlsig.PasswordDecoder</code> interface.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "loggerClass" : {
    "title" : "Logger SPI implementation class",
    "description" : "The Federation system uses this class to record log entries.<br><br>The
default implementation uses the Logging APIs to record log entries. A custom implementation must
implement the <code>com.sun.identity.plugin.log.Logger</code> interface.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"generalConfig" : {
  "type" : "object",
  "title" : "General Configuration",
  "propertyOrder" : 0,
  "properties" : {
    "certificateChecking" : {
      "title" : "Check presence of certificates",
      "description" : "Enable checking of certificates against local copy<br><br>Whether to verify
that the partner's signing certificate included in the Federation XML document is the same as the one
stored in the said partner's meta data.",
      "propertyOrder" : 900,

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "samlErrorPageUrl" : {
    "title" : "SAML Error Page URL",
    "description" : "OpenAM redirects users here when an error occurs in the SAML2
engine.<br><br>Both relative and absolute URLs are supported. Users are redirected to an absolute URL
using the configured HTTP Binding whereas relative URLs are displayed within the request.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "samlErrorPageHttpBinding" : {
    "title" : "SAML Error Page HTTP Binding",
    "description" : "The possible values are HTTP-Redirect or HTTP-POST.",
    "propertyOrder" : 1800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "maxContentLength" : {
    "title" : "Maximum allowed content length",
    "description" : "The maximum content length allowed in federation communications, in
bytes.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
}
}
}
}
}

```

1.35. ConditionTypes

1.35.1. Realm Operations

Service for querying and reading the environment condition types stored in OpenAM. Environment condition types describe the JSON representation of environment conditions that you can use in policy definitions

Resource path: `/conditiontypes`

Resource version: `1.0`

1.35.1.1. query

Query the list of environment condition types

Usage:

```
am> query ConditionTypes --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.35.1.2. read

Read an individual environment condition type by providing the unique identifier title

Usage:

```
am> read ConditionTypes --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.36. CreatePassword

1.36.1. Realm Operations

Resource path: [/realm-config/authentication/authenticationtrees/nodes/CreatePasswordNode](#)

Resource version: 1.0

1.36.1.1. create

Usage:

```
am> create CreatePassword --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:


```
{
  "type" : "object",
  "properties" : {
    "minPasswordLength" : {
      "title" : "minPasswordLength",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "minPasswordLength" ]
}
```

1.36.1.2. delete

Usage:

```
am> delete CreatePassword --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.36.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action CreatePassword --realm Realm --actionName getAllTypes
```

1.36.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action CreatePassword --realm Realm --actionName getCreatableTypes
```

1.36.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action CreatePassword --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.36.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action CreatePassword --realm Realm --actionName nextdescendents
```

1.36.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query CreatePassword --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.36.1.8. read

Usage:

```
am> read CreatePassword --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.36.1.9. update

Usage:

```
am> update CreatePassword --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "minPasswordLength" : {
      "title" : "minPasswordLength",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "minPasswordLength" ]
}
```

1.37. Csv

1.37.1. Realm Operations

Resource path: </realm-config/services/audit/CSV>

Resource version: 1.0

1.37.1.1. create

Usage:

```
am> create Csv --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "csvSecurity" : {
      "type" : "object",
      "title" : "Tamper Evident Configuration",
      "propertyOrder" : 6,
      "properties" : {
        "securityFilename" : {
          "title" : "Certificate Store Location",
          "description" : "Path to Java keystore.",
          "propertyOrder" : 1800,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "securityEnabled" : {
          "title" : "Is Enabled",
          "description" : "Enables the CSV tamper evident feature.",
          "propertyOrder" : 1700,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "securitySignatureInterval" : {
          "title" : "Signature Interval",
          "description" : "Signature generation interval, in seconds.",
          "propertyOrder" : 2000,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "securityPassword" : {
          "title" : "Certificate Store Password",
          "description" : "Password for Java keystore.",
          "propertyOrder" : 1900,
          "required" : false,
          "type" : "string",
          "format" : "password",
          "exampleValue" : ""
        }
      }
    },
    "csvFileRetention" : {
      "type" : "object",
      "title" : "File Retention",
      "propertyOrder" : 4,
      "properties" : {
        "retentionMinFreeSpaceRequired" : {
          "title" : "Minimum Free Space Required",
          "description" : "Minimum amount of disk space required, in bytes, on the system where audit files are stored. A negative or zero value indicates this policy is disabled.",
          "propertyOrder" : 1400,
          "required" : true,
          "type" : "string",
```

```

    "exampleValue" : ""
  },
  "retentionMaxDiskSpaceToUse" : {
    "title" : "Maximum Disk Space",
    "description" : "The maximum amount of disk space the audit files can occupy, in bytes. A
negative or zero value indicates this policy is disabled.",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "retentionMaxNumberOfHistoryFiles" : {
    "title" : "Maximum Number of Historical Files",
    "description" : "Maximum number of backup audit files allowed. A value of <code>-1</code>
disables pruning of old history files.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"commonHandler" : {
  "type" : "object",
  "title" : "General Handler Configuration",
  "propertyOrder" : 0,
  "properties" : {
    "enabled" : {
      "title" : "Enabled",
      "description" : "Enables or disables an audit event handler.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "topics" : {
      "title" : "Topics",
      "description" : "List of topics handled by an audit event handler.",
      "propertyOrder" : 400,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
},
"csvFileRotation" : {
  "type" : "object",
  "title" : "File Rotation",
  "propertyOrder" : 3,
  "properties" : {
    "rotationFilePrefix" : {
      "title" : "File Rotation Prefix",
      "description" : "Prefix to prepend to audit files when rotating audit files.",
      "propertyOrder" : 800,
      "required" : false,
      "type" : "string",

```

```

    "exampleValue" : ""
  },
  "rotationEnabled" : {
    "title" : "Rotation Enabled",
    "description" : "Enables and disables audit file rotation.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "rotationMaxFileSize" : {
    "title" : "Maximum File Size",
    "description" : "Maximum size, in bytes, which an audit file can grow to before rotation is
triggered. A negative or zero value indicates this policy is disabled.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "rotationInterval" : {
    "title" : "Rotation Interval",
    "description" : "Interval to trigger audit file rotations, in seconds. A negative or zero
value disables this feature.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "rotationTimes" : {
    "title" : "Rotation Times",
    "description" : "Durations after midnight to trigger file rotation, in seconds.",
    "propertyOrder" : 1100,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "rotationFileSuffix" : {
    "title" : "File Rotation Suffix",
    "description" : "Suffix to append to audit files when they are rotated. Suffix should be a
timestamp.",
    "propertyOrder" : 900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"csvConfig" : {
  "type" : "object",
  "title" : "CSV Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "location" : {
      "title" : "Log Directory",
      "description" : "Directory in which to store audit log CSV files.",
      "propertyOrder" : 500,

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 2100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"csvBuffering" : {
  "type" : "object",
  "title" : "Buffering",
  "propertyOrder" : 5,
  "properties" : {
    "bufferingAutoFlush" : {
      "title" : "Flush Each Event Immediately",
      "description" : "Performance may be improved by writing all buffered events before
flushing.",
      "propertyOrder" : 1600,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "bufferingEnabled" : {
      "title" : "Buffering Enabled",
      "description" : "Enables or disables buffering.",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
}
}
}

```

1.37.1.2. delete

Usage:

```
am> delete Csv --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.37.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Csv --realm Realm --actionName getAllTypes
```

1.37.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Csv --realm Realm --actionName getCreatableTypes
```

1.37.1.5. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Csv --realm Realm --actionName nextdescendants
```

1.37.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Csv --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.37.1.7. read

Usage:

```
am> read Csv --realm Realm --id id
```


Parameters:

--id

The unique identifier for the resource.

1.37.1.8. update

Usage:

```
am> update Csv --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "csvSecurity" : {
      "type" : "object",
      "title" : "Tamper Evident Configuration",
      "propertyOrder" : 6,
      "properties" : {
        "securityFilename" : {
          "title" : "Certificate Store Location",
          "description" : "Path to Java keystore.",
          "propertyOrder" : 1800,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "securityEnabled" : {
          "title" : "Is Enabled",
          "description" : "Enables the CSV tamper evident feature.",
          "propertyOrder" : 1700,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "securitySignatureInterval" : {
          "title" : "Signature Interval",
          "description" : "Signature generation interval, in seconds.",
          "propertyOrder" : 2000,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "securityPassword" : {
          "title" : "Certificate Store Password",
```

```

        "description" : "Password for Java keystore.",
        "propertyOrder" : 1900,
        "required" : false,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    }
}
},
"csvFileRetention" : {
    "type" : "object",
    "title" : "File Retention",
    "propertyOrder" : 4,
    "properties" : {
        "retentionMinFreeSpaceRequired" : {
            "title" : "Minimum Free Space Required",
            "description" : "Minimum amount of disk space required, in bytes, on the system where audit
files are stored. A negative or zero value indicates this policy is disabled.",
            "propertyOrder" : 1400,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "retentionMaxDiskSpaceToUse" : {
            "title" : "Maximum Disk Space",
            "description" : "The maximum amount of disk space the audit files can occupy, in bytes. A
negative or zero value indicates this policy is disabled.",
            "propertyOrder" : 1300,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "retentionMaxNumberOfHistoryFiles" : {
            "title" : "Maximum Number of Historical Files",
            "description" : "Maximum number of backup audit files allowed. A value of <code>-1</code>
disables pruning of old history files.",
            "propertyOrder" : 1200,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}
},
"commonHandler" : {
    "type" : "object",
    "title" : "General Handler Configuration",
    "propertyOrder" : 0,
    "properties" : {
        "enabled" : {
            "title" : "Enabled",
            "description" : "Enables or disables an audit event handler.",
            "propertyOrder" : 300,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        }
    },
    "topics" : {
        "title" : "Topics",
        "description" : "List of topics handled by an audit event handler.",

```

```
        "propertyOrder" : 400,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
},
"csvFileRotation" : {
    "type" : "object",
    "title" : "File Rotation",
    "propertyOrder" : 3,
    "properties" : {
        "rotationFilePrefix" : {
            "title" : "File Rotation Prefix",
            "description" : "Prefix to prepend to audit files when rotating audit files.",
            "propertyOrder" : 800,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "rotationEnabled" : {
            "title" : "Rotation Enabled",
            "description" : "Enables and disables audit file rotation.",
            "propertyOrder" : 600,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "rotationMaxFileSize" : {
            "title" : "Maximum File Size",
            "description" : "Maximum size, in bytes, which an audit file can grow to before rotation is
triggered. A negative or zero value indicates this policy is disabled.",
            "propertyOrder" : 700,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "rotationInterval" : {
            "title" : "Rotation Interval",
            "description" : "Interval to trigger audit file rotations, in seconds. A negative or zero
value disables this feature.",
            "propertyOrder" : 1000,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "rotationTimes" : {
            "title" : "Rotation Times",
            "description" : "Durations after midnight to trigger file rotation, in seconds.",
            "propertyOrder" : 1100,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        }
    }
}
```

```

    },
    "rotationFileSuffix" : {
      "title" : "File Rotation Suffix",
      "description" : "Suffix to append to audit files when they are rotated. Suffix should be a
timestamp.",
      "propertyOrder" : 900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"csvConfig" : {
  "type" : "object",
  "title" : "CSV Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "location" : {
      "title" : "Log Directory",
      "description" : "Directory in which to store audit log CSV files.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 2100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"csvBuffering" : {
  "type" : "object",
  "title" : "Buffering",
  "propertyOrder" : 5,
  "properties" : {
    "bufferingAutoFlush" : {
      "title" : "Flush Each Event Immediately",
      "description" : "Performance may be improved by writing all buffered events before
flushing.",
      "propertyOrder" : 1600,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  },
  "bufferingEnabled" : {

```

```
    "title" : "Buffering Enabled",
    "description" : "Enables or disables buffering.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
}
```

1.37.2. Global Operations

Resource path: `/global-config/services/audit/CSV`

Resource version: `1.0`

1.37.2.1. create

Usage:

```
am> create Csv --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 400,

```

```

        "required" : true,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      }
    },
    "csvFileRetention" : {
      "type" : "object",
      "title" : "File Retention",
      "propertyOrder" : 4,
      "properties" : {
        "retentionMinFreeSpaceRequired" : {
          "title" : "Minimum Free Space Required",
          "description" : "Minimum amount of disk space required, in bytes, on the system where audit
files are stored. A negative or zero value indicates this policy is disabled.",
          "propertyOrder" : 1400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "retentionMaxNumberOfHistoryFiles" : {
          "title" : "Maximum Number of Historical Files",
          "description" : "Maximum number of backup audit files allowed. A value of <code>-1</code>
disables pruning of old history files.",
          "propertyOrder" : 1200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "retentionMaxDiskSpaceToUse" : {
          "title" : "Maximum Disk Space",
          "description" : "The maximum amount of disk space the audit files can occupy, in bytes. A
negative or zero value indicates this policy is disabled.",
          "propertyOrder" : 1300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "csvBuffering" : {
      "type" : "object",
      "title" : "Buffering",
      "propertyOrder" : 5,
      "properties" : {
        "bufferingEnabled" : {
          "title" : "Buffering Enabled",
          "description" : "Enables or disables buffering.",
          "propertyOrder" : 1500,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "bufferingAutoFlush" : {
          "title" : "Flush Each Event Immediately",

```

```

    "description" : "Performance may be improved by writing all buffered events before
flushing.",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"csvFileRotation" : {
  "type" : "object",
  "title" : "File Rotation",
  "propertyOrder" : 3,
  "properties" : {
    "rotationMaxFileSize" : {
      "title" : "Maximum File Size",
      "description" : "Maximum size, in bytes, which an audit file can grow to before rotation is
triggered. A negative or zero value indicates this policy is disabled.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationFileSuffix" : {
      "title" : "File Rotation Suffix",
      "description" : "Suffix to append to audit files when they are rotated. Suffix should be a
timestamp.",
      "propertyOrder" : 900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationTimes" : {
      "title" : "Rotation Times",
      "description" : "Durations after midnight to trigger file rotation, in seconds.",
      "propertyOrder" : 1100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "rotationInterval" : {
      "title" : "Rotation Interval",
      "description" : "Interval to trigger audit file rotations, in seconds. A negative or zero
value disables this feature.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationEnabled" : {
      "title" : "Rotation Enabled",
      "description" : "Enables and disables audit file rotation.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}

```

```
    },
    "rotationFilePrefix" : {
      "title" : "File Rotation Prefix",
      "description" : "Prefix to prepend to audit files when rotating audit files.",
      "propertyOrder" : 800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"csvSecurity" : {
  "type" : "object",
  "title" : "Tamper Evident Configuration",
  "propertyOrder" : 6,
  "properties" : {
    "securityPassword" : {
      "title" : "Certificate Store Password",
      "description" : "Password for Java keystore.",
      "propertyOrder" : 1900,
      "required" : false,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "securityEnabled" : {
      "title" : "Is Enabled",
      "description" : "Enables the CSV tamper evident feature.",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "securitySignatureInterval" : {
      "title" : "Signature Interval",
      "description" : "Signature generation interval, in seconds.",
      "propertyOrder" : 2000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "securityFilename" : {
      "title" : "Certificate Store Location",
      "description" : "Path to Java keystore.",
      "propertyOrder" : 1800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
```



```
"description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
  "propertyOrder" : 2100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
},
"csvConfig" : {
  "type" : "object",
  "title" : "CSV Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "location" : {
      "title" : "Log Directory",
      "description" : "Directory in which to store audit log CSV files.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
```

1.37.2.2. delete

Usage:

```
am> delete Csv --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.37.2.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Csv --global --actionName getAllTypes
```

1.37.2.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Csv --global --actionName getCreatableTypes
```

1.37.2.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Csv --global --actionName nextdescendents
```

1.37.2.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Csv --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.37.2.7. read

Usage:

```
am> read Csv --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.37.2.8. update

Usage:

```
am> update Csv --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 400,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      }
    },
    "csvFileRetention" : {
      "type" : "object",
      "title" : "File Retention",
      "propertyOrder" : 4,
      "properties" : {
        "retentionMinFreeSpaceRequired" : {
          "title" : "Minimum Free Space Required",
          "description" : "Minimum amount of disk space required, in bytes, on the system where audit files are stored. A negative or zero value indicates this policy is disabled.",
          "propertyOrder" : 1400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "retentionMaxNumberOfHistoryFiles" : {
          "title" : "Maximum Number of Historical Files",
          "description" : "Maximum number of backup audit files allowed. A value of <code>-1</code> disables pruning of old history files.",
          "propertyOrder" : 1200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "retentionMaxDiskSpaceToUse" : {
          "title" : "Maximum Disk Space",
```

```

    "description" : "The maximum amount of disk space the audit files can occupy, in bytes. A
negative or zero value indicates this policy is disabled.",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"csvBuffering" : {
  "type" : "object",
  "title" : "Buffering",
  "propertyOrder" : 5,
  "properties" : {
    "bufferingEnabled" : {
      "title" : "Buffering Enabled",
      "description" : "Enables or disables buffering.",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "bufferingAutoFlush" : {
      "title" : "Flush Each Event Immediately",
      "description" : "Performance may be improved by writing all buffered events before
flushing.",
      "propertyOrder" : 1600,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
},
"csvFileRotation" : {
  "type" : "object",
  "title" : "File Rotation",
  "propertyOrder" : 3,
  "properties" : {
    "rotationMaxFileSize" : {
      "title" : "Maximum File Size",
      "description" : "Maximum size, in bytes, which an audit file can grow to before rotation is
triggered. A negative or zero value indicates this policy is disabled.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationFileSuffix" : {
      "title" : "File Rotation Suffix",
      "description" : "Suffix to append to audit files when they are rotated. Suffix should be a
timestamp.",
      "propertyOrder" : 900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "rotationTimes" : {
    "title" : "Rotation Times",
    "description" : "Durations after midnight to trigger file rotation, in seconds.",

```

```

    "propertyOrder" : 1100,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "rotationInterval" : {
    "title" : "Rotation Interval",
    "description" : "Interval to trigger audit file rotations, in seconds. A negative or zero
value disables this feature.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "rotationEnabled" : {
    "title" : "Rotation Enabled",
    "description" : "Enables and disables audit file rotation.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "rotationFilePrefix" : {
    "title" : "File Rotation Prefix",
    "description" : "Prefix to prepend to audit files when rotating audit files.",
    "propertyOrder" : 800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"csvSecurity" : {
  "type" : "object",
  "title" : "Tamper Evident Configuration",
  "propertyOrder" : 6,
  "properties" : {
    "securityPassword" : {
      "title" : "Certificate Store Password",
      "description" : "Password for Java keystore.",
      "propertyOrder" : 1900,
      "required" : false,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "securityEnabled" : {
      "title" : "Is Enabled",
      "description" : "Enables the CSV tamper evident feature.",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "securitySignatureInterval" : {
      "title" : "Signature Interval",

```

```
    "description" : "Signature generation interval, in seconds.",
    "propertyOrder" : 2000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "securityFilename" : {
    "title" : "Certificate Store Location",
    "description" : "Path to Java keystore.",
    "propertyOrder" : 1800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 2100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
},
"csvConfig" : {
  "type" : "object",
  "title" : "CSV Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "location" : {
      "title" : "Log Directory",
      "description" : "Directory in which to store audit log CSV files.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
}
```

1.38. CtsDataStoreProperties

1.38.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/{serverName}/properties/cts`

Resource version: `1.0`

1.38.1.1. read

Usage:

```
am> read CtsDataStoreProperties --global --serverName serverName
```

Parameters:

--serverName

An object of property key-value pairs

1.38.1.2. update

Usage:

```
am> update CtsDataStoreProperties --global --serverName serverName --body body
```

Parameters:

--serverName

An object of property key-value pairs

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.org.forgerock.services.cts.store.common.section" : {
      "title" : "CTS Token Store",
      "type" : "object",
      "propertyOrder" : 0,
      "properties" : {
        "org.forgerock.services.cts.store.location" : {
          "title" : "Store Mode",
          "type" : "object",
          "propertyOrder" : 0,
          "description" : "",

```

```

    "properties" : {
      "value" : {
        "enum" : [ "default", "external" ],
        "options" : {
          "enum_titles" : [ "Default Token Store", "External Token Store" ]
        },
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "org.forgerock.services.cts.store.root.suffix" : {
    "title" : "Root Suffix",
    "type" : "object",
    "propertyOrder" : 1,
    "description" : "",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "org.forgerock.services.cts.store.max.connections" : {
    "title" : "Max Connections",
    "type" : "object",
    "propertyOrder" : 2,
    "description" : "",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "amconfig.org.forgerock.services.cts.store.external.section" : {
    "title" : "External Store Configuration",
    "type" : "object",
    "propertyOrder" : 1,
    "properties" : {
      "org.forgerock.services.cts.store.ssl.enabled" : {
        "title" : "SSL/TLS Enabled",
        "type" : "object",
        "propertyOrder" : 0,
        "description" : ""
      }
    }
  }
}

```



```

    "properties" : {
      "value" : {
        "type" : "boolean",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "org.forgerock.services.cts.store.directory.name" : {
    "title" : "Connection String(s)",
    "type" : "object",
    "propertyOrder" : 1,
    "description" : "An ordered list of connection strings for LDAP directories. Each connection string is composed as follows: <code>HOST:PORT[|SERVERID[|SITEID]]</code>, where server and site IDs are optional parameters that will prioritize that connection to use from the specified nodes. Multiple connection strings should be comma-separated, e.g. <code>host1:389,host2:50389|server1|site1,host3:50389</code>.",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "org.forgerock.services.cts.store.loginid" : {
    "title" : "Login Id",
    "type" : "object",
    "propertyOrder" : 2,
    "description" : "",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "org.forgerock.services.cts.store.password" : {
    "title" : "Password",
    "type" : "object",
    "propertyOrder" : 3,
    "description" : "",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false,
        "format" : "password"
      },
      "inherited" : {

```

```
        "type" : "boolean",
        "required" : true
    }
}
},
"org.forgerock.services.cts.store.heartbeat" : {
    "title" : "Heartbeat",
    "type" : "object",
    "propertyOrder" : 4,
    "description" : "",
    "properties" : {
        "value" : {
            "type" : "integer",
            "required" : false
        },
        "inherited" : {
            "type" : "boolean",
            "required" : true
        }
    }
},
"org.forgerock.services.cts.store.affinity.enabled" : {
    "title" : "Affinity Enabled",
    "type" : "object",
    "propertyOrder" : 5,
    "description" : "Enables affinity based request load balancing when accessing the CTS
servers. It is imperative that the connection string setting is set to the same value for all OpenAM
servers in the deployment when this feature is enabled.",
    "properties" : {
        "value" : {
            "type" : "boolean",
            "required" : false
        },
        "inherited" : {
            "type" : "boolean",
            "required" : true
        }
    }
}
}
}
}
}
```

1.39. Dashboard

1.39.1. Realm Operations

Resource path: [/realm-config/services/dashboard](#)

Resource version: 1.0

1.39.1.1. create

Usage:

```
am> create Dashboard --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "assignedDashboard" : {
      "title" : "Available Dashboard Apps",
      "description" : "List of application dashboard names available by default for realms with the
Dashboard service configured.",
      "propertyOrder" : 700,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.39.1.2. delete

Usage:

```
am> delete Dashboard --realm Realm
```

1.39.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Dashboard --realm Realm --actionName getAllTypes
```

1.39.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Dashboard --realm Realm --actionName getCreatableTypes
```

1.39.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Dashboard --realm Realm --actionName nextdescendents
```

1.39.1.6. read

Usage:

```
am> read Dashboard --realm Realm
```

1.39.1.7. update

Usage:

```
am> update Dashboard --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "assignedDashboard" : {
      "title" : "Available Dashboard Apps",
      "description" : "List of application dashboard names available by default for realms with the
Dashboard service configured.",
      "propertyOrder" : 700,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.39.2. Global Operations

Resource path: `/global-config/services/dashboard`

Resource version: `1.0`

1.39.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Dashboard --global --actionName getAllTypes
```

1.39.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Dashboard --global --actionName getCreatableTypes
```

1.39.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Dashboard --global --actionName nextdescendents
```

1.39.2.4. read

Usage:

```
am> read Dashboard --global
```

1.39.2.5. update

Usage:

```
am> update Dashboard --global --body body
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "assignedDashboard" : {
          "title" : "Available Dashboard Apps",
          "description" : "List of application dashboard names available by default for realms with
the Dashboard service configured.",
          "propertyOrder" : 700,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      },
      "type" : "object",
      "title" : "Realm Defaults"
    }
  }
}
```

1.40. DashboardInstance

1.40.1. Global Operations

Resource path: </global-config/services/dashboard/instances>

Resource version: 1.0

1.40.1.1. create

Usage:

```
am> create DashboardInstance --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
```

```
"properties" : {
  "displayName" : {
    "title" : "Dashboard Display Name",
    "description" : "The application name that displays on the dashboard client.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "name" : {
    "title" : "Dashboard Name",
    "description" : "The application name as it will appear to the administrator for configuring the
dashboard.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "className" : {
    "title" : "Dashboard Class Name",
    "description" : "Identifies how to access the application, for example
<code>SAML2ApplicationClass</code> for a SAML v2.0 application.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "icfIdentifier" : {
    "title" : "ICF Identifier",
    "description" : "",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "icon" : {
    "title" : "Dashboard Icon",
    "description" : "The icon name that will be displayed on the dashboard client identifying the
application.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "login" : {
    "title" : "Dashboard Login",
    "description" : "The URL that takes the user to the application.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.40.1.2. delete

Usage:

```
am> delete DashboardInstance --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.40.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DashboardInstance --global --actionName getAllTypes
```

1.40.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DashboardInstance --global --actionName getCreatableTypes
```

1.40.1.5. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DashboardInstance --global --actionName nextdescendants
```

1.40.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query DashboardInstance --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.40.1.7. read

Usage:

```
am> read DashboardInstance --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.40.1.8. update

Usage:

```
am> update DashboardInstance --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "displayName" : {
      "title" : "Dashboard Display Name",
      "description" : "The application name that displays on the dashboard client.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "name" : {
      "title" : "Dashboard Name",
      "description" : "The application name as it will appear to the administrator for configuring the dashboard.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "className" : {
      "title" : "Dashboard Class Name",
      "description" : "Identifies how to access the application, for example <code>SAML2ApplicationClass</code> for a SAML v2.0 application.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",

```

```
    "exampleValue" : ""
  },
  "icfIdentifier" : {
    "title" : "ICF Identifier",
    "description" : "",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "icon" : {
    "title" : "Dashboard Icon",
    "description" : "The icon name that will be displayed on the dashboard client identifying the
application.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "login" : {
    "title" : "Dashboard Login",
    "description" : "The URL that takes the user to the application.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.41. DashboardUserService

1.41.1. Realm Operations

Resource path: `/users/{user}/services/dashboard`

Resource version: `1.0`

1.41.1.1. create

Usage:

```
am> create DashboardUserService --realm Realm --body body
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "assignedDashboard" : {
      "title" : "Assigned Dashboard",
      "description" : "",
      "propertyOrder" : 800,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.41.1.2. delete

Usage:

```
am> delete DashboardUserService --realm Realm
```

1.41.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DashboardUserService --realm Realm --user user --actionName getAllTypes
```

Parameters:

--user

1.41.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DashboardUserService --realm Realm --user user --actionName getCreatableTypes
```

Parameters:

--user

1.41.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DashboardUserService --realm Realm --user user --actionName nextdescendents
```

Parameters:

--user

1.41.1.6. read

Usage:

```
am> read DashboardUserService --realm Realm
```

1.41.1.7. unassignServices

action.unassignServices.description

Usage:

```
am> action DashboardUserService --realm Realm --body body --user user --actionName unassignServices
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "i18n:api-descriptor/UserServicesResource#schema.description",
  "type" : "object",
  "title" : "i18n:api-descriptor/UserServicesResource#schema.title",
  "properties" : {
    "serviceNames" : {
      "type" : "array",
      "title" : "i18n:api-descriptor/UserServicesResource#schema.servicename.title",
      "description" : "i18n:api-descriptor/UserServicesResource#schema.servicename.description",
      "items" : {
        "type" : "string"
      }
    }
  }
}
```

--user

1.41.1.8. update

Usage:

```
am> update DashboardUserService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "assignedDashboard" : {
      "title" : "Assigned Dashboard",
      "description" : "",
      "propertyOrder" : 800,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.42. Dashboards

1.42.1. Realm Operations

The dashboard service is responsible for returning information from the Dashboard. The only supported operation is read.

Resource path: `/dashboard`

Resource version: `1.0`

1.42.1.1. read

Read dashboard information

Usage:

```
am> read Dashboards --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.43. DataStoreDecision

1.43.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/DataStoreDecisionNode`

Resource version: `1.0`

1.43.1.1. create

Usage:

```
am> create DataStoreDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "required" : [ ]
}
```

1.43.1.2. delete

Usage:

```
am> delete DataStoreDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.43.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DataStoreDecision --realm Realm --actionName getAllTypes
```

1.43.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DataStoreDecision --realm Realm --actionName getCreatableTypes
```

1.43.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action DataStoreDecision --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.43.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DataStoreDecision --realm Realm --actionName nextdescendents
```

1.43.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query DataStoreDecision --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.43.1.8. read

Usage:

```
am> read DataStoreDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.43.1.9. update

Usage:

```
am> update DataStoreDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "required" : [ ]
}
```

1.44. DataStoreModule

1.44.1. Realm Operations

Resource path: </realm-config/authentication/modules/datastore>

Resource version: [1.0](#)

1.44.1.1. create

Usage:

```
am> create DataStoreModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.44.1.2. delete

Usage:

```
am> delete DataStoreModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.44.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DataStoreModule --realm Realm --actionName getAllTypes
```

1.44.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DataStoreModule --realm Realm --actionName getCreatableTypes
```

1.44.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DataStoreModule --realm Realm --actionName nextdescendents
```

1.44.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query DataStoreModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.44.1.7. read

Usage:

```
am> read DataStoreModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.44.1.8. update

Usage:

```
am> update DataStoreModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.44.2. Global Operations

Resource path: `/global-config/authentication/modules/datastore`

Resource version: `1.0`

1.44.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DataStoreModule --global --actionName getAllTypes
```

1.44.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DataStoreModule --global --actionName getCreatableTypes
```

1.44.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DataStoreModule --global --actionName nextdescendents
```

1.44.2.4. read

Usage:

```
am> read DataStoreModule --global
```

1.44.2.5. update

Usage:

```
am> update DataStoreModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        }
      },
      "type" : "object",
      "title" : "Realm Defaults"
    }
  }
}
```

1.45. DecisionCombiners

1.45.1. Realm Operations

Service for querying and reading decision combiners information. Decision combiners describe how to resolve policy decisions when multiple policies apply

Resource path: `/decisioncombiners`

Resource version: `1.0`

1.45.1.1. query

Lists all decision combiners

Usage:

```
am> query DecisionCombiners --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [title]

1.45.1.2. read

Reads an individual decision combiner specified by its name

Usage:

```
am> read DecisionCombiners --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.46. DefaultAdvancedProperties

1.46.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/server-default/properties/advanced`

Resource version: `1.0`

1.46.1.1. read

Usage:

```
am> read DefaultAdvancedProperties --global
```

1.46.1.2. update

Usage:

```
am> update DefaultAdvancedProperties --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "patternProperties" : {
    ".+" : {
      "type" : "string",
      "title" : "Value",
      "description" : "Any string value"
    }
  },
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "An object of property key-value pairs",
  "type" : "object",
  "title" : "Advanced Properties"
}
```

1.47. DefaultCtsDataStoreProperties

1.47.1. Global Operations

An object of property key-value pairs

Resource path: </global-config/servers/server-default/properties/cts>

Resource version: [1.0](#)

1.47.1.1. read

Usage:

```
am> read DefaultCtsDataStoreProperties --global
```

1.47.1.2. update

Usage:

```
am> update DefaultCtsDataStoreProperties --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.org.forgerock.services.cts.store.common.section" : {
      "title" : "CTS Token Store",
      "type" : "object",
      "propertyOrder" : 0,
      "properties" : {
        "org.forgerock.services.cts.store.location" : {
          "enum" : [ "default", "external" ],
          "options" : {
            "enum_titles" : [ "Default Token Store", "External Token Store" ]
          },
          "type" : "string",
          "title" : "Store Mode",
          "propertyOrder" : 0,
          "required" : true,
          "description" : ""
        },
        "org.forgerock.services.cts.store.root.suffix" : {
          "type" : "string",
          "title" : "Root Suffix",
          "propertyOrder" : 1,
          "required" : true,
          "description" : ""
        },
        "org.forgerock.services.cts.store.max.connections" : {
          "type" : "string",
          "title" : "Max Connections",
          "propertyOrder" : 2,
          "required" : true,
          "description" : ""
        }
      }
    },
    "amconfig.org.forgerock.services.cts.store.external.section" : {
      "title" : "External Store Configuration",
      "type" : "object",
      "propertyOrder" : 1,
      "properties" : {
        "org.forgerock.services.cts.store.ssl.enabled" : {
          "type" : "boolean",
          "title" : "SSL/TLS Enabled",
          "propertyOrder" : 0,
          "required" : true,
          "description" : ""
        },
        "org.forgerock.services.cts.store.directory.name" : {
          "type" : "string",

```

```
"title" : "Connection String(s)",
"propertyOrder" : 1,
"required" : true,
"description" : "An ordered list of connection strings for LDAP directories. Each connection
string is composed as follows: <code>HOST:PORT[|SERVERID[|SITEID]]</code>, where server and site
IDs are optional parameters that will prioritize that connection to use from the specified nodes.
Multiple connection strings should be comma-separated, e.g. <code>host1:389,host2:50389|server1|
site1,host3:50389</code>."
},
"org.forgerock.services.cts.store.loginid" : {
"type" : "string",
"title" : "Login Id",
"propertyOrder" : 2,
"required" : true,
"description" : ""
},
"org.forgerock.services.cts.store.password" : {
"type" : "string",
"title" : "Password",
"propertyOrder" : 3,
"required" : true,
"description" : "",
"format" : "password"
},
"org.forgerock.services.cts.store.heartbeat" : {
"type" : "integer",
"title" : "Heartbeat",
"propertyOrder" : 4,
"required" : true,
"description" : ""
},
"org.forgerock.services.cts.store.affinity.enabled" : {
"type" : "boolean",
"title" : "Affinity Enabled",
"propertyOrder" : 5,
"required" : true,
"description" : "Enables affinity based request load balancing when accessing the CTS
servers. It is imperative that the connection string setting is set to the same value for all OpenAM
servers in the deployment when this feature is enabled."
}
}
}
}
```

1.48. DefaultDirectoryConfiguration

1.48.1. Global Operations

Connection details for directory server(s).

Resource path: </global-config/servers/server-default/properties/directoryConfiguration>

Resource version: 1.0

1.48.1.1. read

Usage:

```
am> read DefaultDirectoryConfiguration --global
```

1.48.1.2. update

Usage:

```
am> update DefaultDirectoryConfiguration --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "directoryConfiguration" : {
      "type" : "object",
      "title" : "Directory Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "minConnectionPool" : {
          "title" : "Minimum Connection Pool",
          "propertyOrder" : 0,
          "type" : "number"
        },
        "maxConnectionPool" : {
          "title" : "Maximum Connection Pool",
          "propertyOrder" : 1,
          "type" : "number"
        },
        "bindDn" : {
          "title" : "Bind DN",
          "propertyOrder" : 2,
          "type" : "string"
        },
        "bindPassword" : {
          "title" : "Bind Password",
          "propertyOrder" : 3,
          "type" : "string",
          "format" : "password"
        }
      }
    },
    "directoryServers" : {
      "type" : "array",
      "title" : "Server",
      "propertyOrder" : 1,
      "items" : {
        "type" : "object",
```

```
"required" : [ "serverName", "hostName", "portNumber", "connectionType" ],
"properties" : {
  "serverName" : {
    "title" : "Name",
    "type" : "string",
    "propertyOrder" : 0
  },
  "hostName" : {
    "title" : "Host Name",
    "type" : "string",
    "propertyOrder" : 1
  },
  "portNumber" : {
    "title" : "Port Number",
    "type" : "string",
    "propertyOrder" : 2
  },
  "connectionType" : {
    "type" : "string",
    "enum" : [ "SIMPLE", "SSL" ],
    "options" : {
      "enum_titles" : [ "SIMPLE", "SSL" ]
    }
  },
  "title" : "Connection Type",
  "propertyOrder" : 3
}
}
```

1.49. DefaultGeneralProperties

1.49.1. Global Operations

An object of property key-value pairs

Resource path: [/global-config/servers/server-default/properties/general](#)

Resource version: [1.0](#)

1.49.1.1. read

Usage:

```
am> read DefaultGeneralProperties --global
```

1.49.1.2. update

Usage:

```
am> update DefaultGeneralProperties --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.header.installdir" : {
      "title" : "System",
      "type" : "object",
      "propertyOrder" : 0,
      "properties" : {
        "com.iplanet.services.configpath" : {
          "type" : "string",
          "title" : "Base installation directory",
          "propertyOrder" : 0,
          "required" : true,
          "description" : "Base directory where product's data resides. (property name: com.iplanet.services.configpath)"
        },
        "com.iplanet.am.locale" : {
          "type" : "string",
          "title" : "Default Locale",
          "propertyOrder" : 1,
          "required" : true,
          "description" : "Default locale for the product. (property name: com.iplanet.am.locale)"
        },
        "com.sun.identity.client.notification.url" : {
          "type" : "string",
          "title" : "Notification URL",
          "propertyOrder" : 2,
          "required" : true,
          "description" : "The location of notification service end point. It is usually the product's deployment URI/notificationservice. (property name: com.sun.identity.client.notification.url)"
        },
        "com.iplanet.am.util.xml.validating" : {
          "enum" : [ "on", "off" ],
          "options" : {
            "enum_titles" : [ "On", "Off" ]
          },
          "type" : "string",
          "title" : "XML Validation",
          "propertyOrder" : 3,
          "required" : true,
          "description" : "Specifies if validation is required when parsing XML documents. (property name: com.iplanet.am.util.xml.validating)"
        }
      }
    },
    "amconfig.header.debug" : {
      "title" : "Debugging",
      "type" : "object",
      "propertyOrder" : 1,

```

```
"properties" : {
  "com.ipplanet.services.debug.level" : {
    "enum" : [ "off", "error", "warning", "message" ],
    "options" : {
      "enum_titles" : [ "Off", "Error", "Warning", "Message" ]
    },
    "type" : "string",
    "title" : "Debug Level",
    "propertyOrder" : 0,
    "required" : true,
    "description" : "Debug level for all components in the product. (property name:
com.ipplanet.services.debug.level)"
  },
  "com.sun.services.debug.mergeall" : {
    "enum" : [ "on", "off" ],
    "options" : {
      "enum_titles" : [ "On", "Off" ]
    },
    "type" : "string",
    "title" : "Merge Debug Files",
    "propertyOrder" : 1,
    "required" : true,
    "description" : "On : Directs all debug data to a single file (debug.out); Off : creates
separate per-component debug files (property name : com.sun.services.debug.mergeall)"
  },
  "com.ipplanet.services.debug.directory" : {
    "type" : "string",
    "title" : "Debug Directory",
    "propertyOrder" : 2,
    "required" : true,
    "description" : "Directory where debug files reside. (property name:
com.ipplanet.services.debug.directory)"
  }
},
"amconfig.header.mailserver" : {
  "title" : "Mail Server",
  "type" : "object",
  "propertyOrder" : 2,
  "properties" : {
    "com.ipplanet.am.smtphost" : {
      "type" : "string",
      "title" : "Mail Server Host Name",
      "propertyOrder" : 0,
      "required" : true,
      "description" : "(property name: com.ipplanet.am.smtphost)"
    },
    "com.ipplanet.am.smtpport" : {
      "type" : "integer",
      "title" : "Mail Server Port Number",
      "propertyOrder" : 1,
      "required" : true,
      "description" : "(property name: com.ipplanet.am.smtpport)"
    }
  }
}
}
```

1.50. DefaultSdkProperties

1.50.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/server-default/properties/sdk`

Resource version: `1.0`

1.50.1.1. read

Usage:

```
am> read DefaultSdkProperties --global
```

1.50.1.2. update

Usage:

```
am> update DefaultSdkProperties --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.header.datastore" : {
      "title" : "Data Store",
      "type" : "object",
      "propertyOrder" : 0,
      "properties" : {
        "com.sun.identity.sm.enableDataStoreNotification" : {
          "type" : "boolean",
          "title" : "Enable Datastore Notification",
          "propertyOrder" : 0,
          "required" : true,
          "description" : "Specifies if backend datastore notification is enabled. If
this value is set to 'false', then in-memory notification is enabled. (property name:
com.sun.identity.sm.enableDataStoreNotification)"
        },
        "com.sun.identity.sm.notification.threadpool.size" : {
          "type" : "integer",
          "title" : "Notification Pool Size",
          "propertyOrder" : 1,
          "required" : true,
          "description" : "Specifies the size of the sm notification thread pool (total number of
threads). (property name: com.sun.identity.sm.notification.threadpool.size)"
        }
      }
    }
  }
}
```

```

    }
  },
  "amconfig.header.eventservice" : {
    "title" : "Event Service",
    "type" : "object",
    "propertyOrder" : 1,
    "properties" : {
      "com.iplanet.am.event.connection.num.retries" : {
        "type" : "integer",
        "title" : "Number of retries for Event Service connections",
        "propertyOrder" : 0,
        "required" : true,
        "description" : "Specifies the number of attempts made to successfully re-establish the
Event Service connections. (property name: com.iplanet.am.event.connection.num.retries)"
      },
      "com.iplanet.am.event.connection.delay.between.retries" : {
        "type" : "integer",
        "title" : "Delay between Event Service connection retries",
        "propertyOrder" : 1,
        "required" : true,
        "description" : "Specifies the delay in milliseconds between retries to re-establish the
Event Service connections. (property name: com.iplanet.am.event.connection.delay.between.retries)"
      },
      "com.iplanet.am.event.connection.ldap.error.codes.retries" : {
        "type" : "string",
        "title" : "Error codes for Event Service connection retries",
        "propertyOrder" : 2,
        "required" : true,
        "description" : "This secifies the LDAP exception error codes for which
retries to re-establish Event Service connections will trigger. (property name:
com.iplanet.am.event.connection.ldap.error.codes.retries)"
      },
      "com.sun.am.event.connection.disable.list" : {
        "type" : "string",
        "title" : "Disabled Event Service Connection",
        "propertyOrder" : 3,
        "required" : true,
        "description" : "Specifies which event connection (persistent search) to be disabled. There
are three valid values - aci, sm and um (case insensitive). Multiple values should be separated with
\", \". (property name: com.sun.am.event.connection.disable.list)"
      }
    }
  },
  "amconfig.header.ldapconnection" : {
    "title" : "LDAP Connection",
    "type" : "object",
    "propertyOrder" : 2,
    "properties" : {
      "com.iplanet.am.ldap.connection.num.retries" : {
        "type" : "integer",
        "title" : "Number of retries for LDAP Connection",
        "propertyOrder" : 0,
        "required" : true,
        "description" : "Specifies the number of attempts made to successfully re-establish LDAP
Connection. (property name: com.iplanet.am.ldap.connection.num.retries)"
      },
      "com.iplanet.am.ldap.connection.delay.between.retries" : {
        "type" : "integer",

```

```

    "title" : "Delay between LDAP connection retries",
    "propertyOrder" : 1,
    "required" : true,
    "description" : "Specifies the delay in milliseconds between retries to re-establish the
LDAP connections. (property name: com.iplanet.am.ldap.connection.delay.between.retries)"
  },
  "com.iplanet.am.ldap.connection.ldap.error.codes.retries" : {
    "type" : "string",
    "title" : "Error codes for LDAP connection retries",
    "propertyOrder" : 2,
    "required" : true,
    "description" : "This secifies the LDAP exception error codes for
which retries to re-establish LDAP connections will trigger. (property name:
com.iplanet.am.ldap.connection.ldap.error.codes.retries)"
  }
},
"amconfig.header.cachingreplica" : {
  "title" : "Caching and Replica",
  "type" : "object",
  "propertyOrder" : 3,
  "properties" : {
    "com.iplanet.am.sdk.cache.maxSize" : {
      "type" : "integer",
      "title" : "SDK Caching Max. Size",
      "propertyOrder" : 0,
      "required" : true,
      "description" : "Specifies the size of the cache when SDK caching is enabled. The size
should be an integer greater than 0, or default size (10000) will be used. Changing this value will
reset (clear) the contents of the cache. (property name: com.iplanet.am.sdk.cache.maxSize)"
    }
  }
},
"amconfig.header.sdktimetoliveconfig" : {
  "title" : "Time To Live Configuration",
  "type" : "object",
  "propertyOrder" : 4,
  "properties" : {
    "com.iplanet.am.sdk.cache.entry.expire.enabled" : {
      "type" : "boolean",
      "title" : "Cache Entry Expiration Enabled",
      "propertyOrder" : 0,
      "required" : true,
      "description" : "If this property is set, the cache entries will expire
based on the time specified in User Entry Expiration Time property. (property name:
com.iplanet.am.sdk.cache.entry.expire.enabled)"
    },
    "com.iplanet.am.sdk.cache.entry.user.expire.time" : {
      "type" : "integer",
      "title" : "User Entry Expiration Time",
      "propertyOrder" : 1,
      "required" : true,
      "description" : "This property specifies time in minutes for which the user entries remain
valid in cache after their last modification. After this specified period of time elapses (after the
last modification/read from the directory), the data for the entry that is cached will expire. At
that instant new requests for data for these user entries will result in reading from the Directory.
(property name: com.iplanet.am.sdk.cache.entry.user.expire.time)"
    },
    "com.iplanet.am.sdk.cache.entry.default.expire.time" : {

```

```
    "type" : "integer",
    "title" : "Default Entry Expiration Time",
    "propertyOrder" : 2,
    "required" : true,
    "description" : "This property specifies time in minutes for which the non-user entries
remain valid in cache after their last modification. After this specified period of time elapses
(after the last modification/read from the directory), the data for the entry that is cached will
expire. At that instant new requests for data for these non-user entries will result in reading from
the Directory. (property name: com.ipplanet.am.sdk.cache.entry.default.expire.time)"
  }
}
```

1.51. DefaultSecurityProperties

1.51.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/server-default/properties/security`

Resource version: `1.0`

1.51.1.1. read

Usage:

```
am> read DefaultSecurityProperties --global
```

1.51.1.2. update

Usage:

```
am> update DefaultSecurityProperties --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.header.encryption" : {
      "title" : "Encryption",
      "type" : "object",
      "propertyOrder" : 0,

```



```

    "properties" : {
      "am.encryption.pwd" : {
        "type" : "string",
        "title" : "Password Encryption Key",
        "propertyOrder" : 0,
        "required" : true,
        "description" : "The encryption key value for decrypting passwords stored in the Service
Management System configuration. (property name: am.encryption.pwd)"
      },
      "com.iplanet.security.encryptor" : {
        "type" : "string",
        "title" : "Encryption class",
        "propertyOrder" : 1,
        "required" : true,
        "description" : "The default encryption class. (property name:
com.iplanet.security.encryptor)"
      },
      "com.iplanet.security.SecureRandomFactoryImpl" : {
        "type" : "string",
        "title" : "Secure Random Factory Class",
        "propertyOrder" : 2,
        "required" : true,
        "description" : "This property is used for specifying SecureRandomFactory class. Available
values for this property are com.iplanet.am.util.JSSSecureRandomFactoryImpl that is using JSS
and com.iplanet.am.util.SecureRandomFactoryImpl that is using pure Java only. (property name:
com.iplanet.security.SecureRandomFactoryImpl)"
      }
    }
  },
  "amconfig.header.validation" : {
    "title" : "Validation",
    "type" : "object",
    "propertyOrder" : 1,
    "properties" : {
      "com.iplanet.services.comm.server.pllrequest.maxContentLength" : {
        "type" : "integer",
        "title" : "Platform Low Level Comm. Max. Content Length",
        "propertyOrder" : 0,
        "required" : true,
        "description" : "Maximum content-length for an HttpRequest. (property name:
com.iplanet.services.comm.server.pllrequest.maxContentLength)"
      },
      "com.iplanet.am.clientIPCheckEnabled" : {
        "type" : "boolean",
        "title" : "Client IP Address Check",
        "propertyOrder" : 1,
        "required" : true,
        "description" : "Specifies whether or not the IP address of the client is checked in all
single sign on token creations or validations. (property name: com.iplanet.am.clientIPCheckEnabled)"
      }
    }
  },
  "amconfig.header.cookie" : {
    "title" : "Cookie",
    "type" : "object",
    "propertyOrder" : 2,
    "properties" : {
      "com.iplanet.am.cookie.name" : {
        "type" : "string",

```

```

    "title" : "Cookie Name",
    "propertyOrder" : 0,
    "required" : true,
    "description" : "The cookie name used by Authentication Service to set the valid
session handler ID. This name is used to retrieve the valid session information. (property name:
com.iplanet.am.cookie.name)"
  },
  "com.iplanet.am.cookie.secure" : {
    "type" : "boolean",
    "title" : "Secure Cookie",
    "propertyOrder" : 1,
    "required" : true,
    "description" : "Specifies whether to set cookie in a secure mode in which the browser
will only return the cookie when a secure protocol such as HTTP(s) is used. (property name:
com.iplanet.am.cookie.secure)"
  },
  "com.iplanet.am.cookie.encode" : {
    "type" : "boolean",
    "title" : "Encode Cookie Value",
    "propertyOrder" : 2,
    "required" : true,
    "description" : "Specifies whether to URL encode the cookie value. (property name:
com.iplanet.am.cookie.encode)"
  }
}
},
"amconfig.header.securitykey" : {
  "title" : "Key Store",
  "type" : "object",
  "propertyOrder" : 3,
  "properties" : {
    "com.sun.identity.saml.xmlsig.keystore" : {
      "type" : "string",
      "title" : "Keystore File",
      "propertyOrder" : 0,
      "required" : true,
      "description" : "Specifies the location of the keystore file. (property name:
com.sun.identity.saml.xmlsig.keystore)"
    },
    "com.sun.identity.saml.xmlsig.storetype" : {
      "type" : "string",
      "title" : "Keystore Type",
      "propertyOrder" : 1,
      "required" : true,
      "description" : "Specifies the keystore type. (property name:
com.sun.identity.saml.xmlsig.storetype)"
    },
    "com.sun.identity.saml.xmlsig.storepass" : {
      "type" : "string",
      "title" : "Keystore Password File",
      "propertyOrder" : 2,
      "required" : true,
      "description" : "Specifies the location of the file that contains the password used to
access the keystore file. (property name: com.sun.identity.saml.xmlsig.storepass)"
    },
    "com.sun.identity.saml.xmlsig.keypass" : {
      "type" : "string",
      "title" : "Private Key Password File",
      "propertyOrder" : 3,

```

```

    "required" : true,
    "description" : "Specifies the location of the file that contains the
password used to protect the private key of a generated key pair. (property name:
com.sun.identity.saml.xmlsig.keypass)"
  },
  "com.sun.identity.saml.xmlsig.certalias" : {
    "type" : "string",
    "title" : "Certificate Alias",
    "propertyOrder" : 4,
    "required" : true,
    "description" : "(property name: com.sun.identity.saml.xmlsig.certalias)"
  }
},
"amconfig.header.crlcache" : {
  "title" : "Certificate Revocation List Caching",
  "type" : "object",
  "propertyOrder" : 4,
  "properties" : {
    "com.sun.identity.crl.cache.directory.host" : {
      "type" : "string",
      "title" : "LDAP server host name",
      "propertyOrder" : 0,
      "required" : true,
      "description" : ""
    },
    "com.sun.identity.crl.cache.directory.port" : {
      "type" : "integer",
      "title" : "LDAP server port number",
      "propertyOrder" : 1,
      "required" : true,
      "description" : ""
    },
    "com.sun.identity.crl.cache.directory.ssl" : {
      "type" : "boolean",
      "title" : "SSL/TLS Enabled",
      "propertyOrder" : 2,
      "required" : true,
      "description" : ""
    },
    "com.sun.identity.crl.cache.directory.user" : {
      "type" : "string",
      "title" : "LDAP server bind user name",
      "propertyOrder" : 3,
      "required" : true,
      "description" : ""
    },
    "com.sun.identity.crl.cache.directory.password" : {
      "type" : "string",
      "title" : "LDAP server bind password",
      "propertyOrder" : 4,
      "required" : true,
      "description" : "",
      "format" : "password"
    },
    "com.sun.identity.crl.cache.directory.searchlocs" : {
      "type" : "string",
      "title" : "LDAP search base DN",
      "propertyOrder" : 5,

```

```

        "required" : true,
        "description" : ""
    },
    "com.sun.identity.crl.cache.directory.searchattr" : {
        "type" : "string",
        "title" : "Search Attributes",
        "propertyOrder" : 6,
        "required" : true,
        "description" : "Any DN component of issuer's subjectDN can be used to retrieve CRL from
local LDAP server. It is single value string, like, \"cn\". All Root CA need to use the same search
attribute."
    }
}
},
"amconfig.header.ocsp.check" : {
    "title" : "Online Certificate Status Protocol Check",
    "type" : "object",
    "propertyOrder" : 5,
    "properties" : {
        "com.sun.identity.authentication.ocspCheck" : {
            "type" : "boolean",
            "title" : "Check Enabled",
            "propertyOrder" : 0,
            "required" : true,
            "description" : ""
        },
        "com.sun.identity.authentication.ocsp.responder.url" : {
            "type" : "string",
            "title" : "Responder URL",
            "propertyOrder" : 1,
            "required" : true,
            "description" : ""
        },
        "com.sun.identity.authentication.ocsp.responder.nickname" : {
            "type" : "string",
            "title" : "Certificate Nickname",
            "propertyOrder" : 2,
            "required" : true,
            "description" : ""
        }
    }
}
},
"amconfig.header.deserialisationwhitelist" : {
    "title" : "Object Deserialisation Class Whitelist",
    "type" : "object",
    "propertyOrder" : 6,
    "properties" : {
        "openam.deserialisation.classes.whitelist" : {
            "type" : "string",
            "title" : "Whitelist",
            "propertyOrder" : 0,
            "required" : true,
            "description" : "The list of classes that are considered valid when OpenAM performs
Object deserialisation operations. The defaults should work for most installations. (property name:
openam.deserialisation.classes.whitelist)"
        }
    }
}
}
}
}

```

```
}
```

1.52. DefaultSessionProperties

1.52.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/server-default/properties/session`

Resource version: `1.0`

1.52.1.1. read

Usage:

```
am> read DefaultSessionProperties --global
```

1.52.1.2. update

Usage:

```
am> update DefaultSessionProperties --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.header.sessionthresholds" : {
      "title" : "Session Limits",
      "type" : "object",
      "propertyOrder" : 0,
      "properties" : {
        "org.forgerock.openam.session.service.access.persistence.caching.maxsize" : {
          "type" : "integer",
          "title" : "Maximum Session Cache Size",
          "propertyOrder" : 0,
          "required" : true,
          "description" : "The maximum number of sessions to cache in the per-server internal session cache. (property name: org.forgerock.openam.session.service.access.persistence.caching.maxsize)"
        },
        "com.iplanet.am.session.invalidsessionmaxtime" : {
          "type" : "integer",
          "title" : "Invalidate Session Max Time",
          "propertyOrder" : 1,

```

```

        "required" : true,
        "description" : "Duration in minutes after which the invalid session will be removed
from the session table if it is created and the user does not login. This value should always
be greater than the timeout value in the Authentication module properties file. (property name:
com.iplanet.am.session.invalidsessionmaxtime)"
    }
}
},
"amconfig.header.sessionlogging" : {
    "title" : "Statistics",
    "type" : "object",
    "propertyOrder" : 1,
    "properties" : {
        "com.iplanet.am.stats.interval" : {
            "type" : "integer",
            "title" : "Logging Interval (in seconds)",
            "propertyOrder" : 0,
            "required" : true,
            "description" : "Number of seconds to elapse between statistics logging. The interval
should be at least 5 seconds to avoid CPU saturation. An interval value less than 5 seconds will be
interpreted as 5 seconds. (property name: com.iplanet.am.stats.interval)"
        },
        "com.iplanet.services.stats.state" : {
            "enum" : [ "off", "file", "console" ],
            "options" : {
                "enum_titles" : [ "Off", "File", "Console" ]
            },
            "type" : "string",
            "title" : "State",
            "propertyOrder" : 1,
            "required" : true,
            "description" : "Statistics state 'file' will write to a file under the specified directory,
and 'console' will write into webserver log files. (property name: com.iplanet.services.stats.state)"
        },
        "com.iplanet.services.stats.directory" : {
            "type" : "string",
            "title" : "Directory",
            "propertyOrder" : 2,
            "required" : true,
            "description" : "Directory where the statistic files will be created. Use forward slashes
\"/\" to separate directories, not backslash \"\\\". Spaces in the file name are allowed for Windows.
(property name: com.iplanet.services.stats.directory)"
        },
        "com.sun.am.session.enableHostLookUp" : {
            "type" : "boolean",
            "title" : "Enable Host Lookup",
            "propertyOrder" : 3,
            "required" : true,
            "description" : "Enables or disables host lookup during session logging. (property name:
com.sun.am.session.enableHostLookUp)"
        }
    }
},
"amconfig.header.sessionnotification" : {
    "title" : "Notification",
    "type" : "object",
    "propertyOrder" : 2,
    "properties" : {
        "com.iplanet.am.notification.threadpool.size" : {

```

```

    "type" : "integer",
    "title" : "Notification Pool Size",
    "propertyOrder" : 0,
    "required" : true,
    "description" : "Specifies the size of the notification thread pool (total number of
threads). (property name: com.iplanet.am.notification.threadpool.size)"
  },
  "com.iplanet.am.notification.threadpool.threshold" : {
    "type" : "integer",
    "title" : "Notification Thread Pool Threshold",
    "propertyOrder" : 1,
    "required" : true,
    "description" : "Specifies the maximum task queue length for serving notification threads.
(property name: com.iplanet.am.notification.threadpool.threshold)"
  }
},
"amconfig.header.sessionvalidation" : {
  "title" : "Validation",
  "type" : "object",
  "propertyOrder" : 3,
  "properties" : {
    "com.sun.am.session.caseInsensitiveDN" : {
      "type" : "boolean",
      "title" : "Case Insensitive client DN comparison",
      "propertyOrder" : 0,
      "required" : true,
      "description" : "Specifies if client distinguished name comparison is case insensitive/
sensitive. (property name: com.sun.am.session.caseInsensitiveDN)"
    }
  }
}
}
}
}
}

```

1.53. DefaultUmaDataStoreProperties

1.53.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/server-default/properties/uma`

Resource version: `1.0`

1.53.1.1. read

Usage:

```
am> read DefaultUmaDataStoreProperties --global
```

1.53.1.2. update

Usage:

```
am> update DefaultUmaDataStoreProperties --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.org.forgerock.services.resourcesets.store.common.section" : {
      "title" : "Resource Sets Store",
      "type" : "object",
      "propertyOrder" : 0,
      "properties" : {
        "org.forgerock.services.resourcesets.store.location" : {
          "enum" : [ "default", "external" ],
          "options" : {
            "enum_titles" : [ "Default Token Store", "External Token Store" ]
          },
          "type" : "string",
          "title" : "Store Mode",
          "propertyOrder" : 0,
          "required" : true,
          "description" : ""
        },
        "org.forgerock.services.resourcesets.store.root.suffix" : {
          "type" : "string",
          "title" : "Root Suffix",
          "propertyOrder" : 1,
          "required" : true,
          "description" : ""
        },
        "org.forgerock.services.resourcesets.store.max.connections" : {
          "type" : "string",
          "title" : "Max Connections",
          "propertyOrder" : 2,
          "required" : true,
          "description" : ""
        }
      }
    },
    "amconfig.org.forgerock.services.resourcesets.store.external.section" : {
      "title" : "External Resource Sets Store Configuration",
      "type" : "object",
      "propertyOrder" : 1,
      "properties" : {
        "org.forgerock.services.resourcesets.store.ssl.enabled" : {
          "type" : "boolean",
          "title" : "SSL/TLS Enabled",
          "propertyOrder" : 0,
          "required" : true,
          "description" : ""
        }
      }
    }
  }
}
```



```

    },
    "org.forgerock.services.resourcesets.store.directory.name" : {
      "type" : "string",
      "title" : "Connection String(s)",
      "propertyOrder" : 1,
      "required" : true,
      "description" : "An ordered list of connection strings for LDAP directories. Each connection
string is composed as follows: <code>HOST:PORT[|SERVERID[|SITEID]]</code>, where server and site
IDs are optional parameters that will prioritize that connection to use from the specified nodes.
Multiple connection strings should be comma-separated, e.g. <code>host1:389,host2:50389|server1|
site1,host3:50389</code>."
    },
    "org.forgerock.services.resourcesets.store.loginid" : {
      "type" : "string",
      "title" : "Login Id",
      "propertyOrder" : 2,
      "required" : true,
      "description" : ""
    },
    "org.forgerock.services.resourcesets.store.password" : {
      "type" : "string",
      "title" : "Password",
      "propertyOrder" : 3,
      "required" : true,
      "description" : "",
      "format" : "password"
    },
    "org.forgerock.services.resourcesets.store.heartbeat" : {
      "type" : "integer",
      "title" : "Heartbeat",
      "propertyOrder" : 4,
      "required" : true,
      "description" : ""
    }
  }
},
"amconfig.org.forgerock.services.umaaudit.store.common.section" : {
  "title" : "UMA Audit Store",
  "type" : "object",
  "propertyOrder" : 2,
  "properties" : {
    "org.forgerock.services.umaaudit.store.location" : {
      "enum" : [ "default", "external" ],
      "options" : {
        "enum_titles" : [ "Default Token Store", "External Token Store" ]
      },
      "type" : "string",
      "title" : "Store Mode",
      "propertyOrder" : 0,
      "required" : true,
      "description" : ""
    },
    "org.forgerock.services.umaaudit.store.root.suffix" : {
      "type" : "string",
      "title" : "Root Suffix",
      "propertyOrder" : 1,
      "required" : true,
      "description" : ""
    }
  }
},

```

```

"org.forgerock.services.umaudit.store.max.connections" : {
  "type" : "string",
  "title" : "Max Connections",
  "propertyOrder" : 2,
  "required" : true,
  "description" : ""
}
},
"amconfig.org.forgerock.services.umaudit.store.external.section" : {
  "title" : "External UMA Audit Store Configuration",
  "type" : "object",
  "propertyOrder" : 3,
  "properties" : {
    "org.forgerock.services.umaudit.store.ssl.enabled" : {
      "type" : "boolean",
      "title" : "SSL/TLS Enabled",
      "propertyOrder" : 0,
      "required" : true,
      "description" : ""
    },
    "org.forgerock.services.umaudit.store.directory.name" : {
      "type" : "string",
      "title" : "Connection String(s)",
      "propertyOrder" : 1,
      "required" : true,
      "description" : "An ordered list of connection strings for LDAP directories. Each connection
string is composed as follows: <code>HOST:PORT[|SERVERID[|SITEID]]</code>, where server and site
IDs are optional parameters that will prioritize that connection to use from the specified nodes.
Multiple connection strings should be comma-separated, e.g. <code>host1:389,host2:50389|server1|
site1,host3:50389</code>."
    },
    "org.forgerock.services.umaudit.store.loginid" : {
      "type" : "string",
      "title" : "Login Id",
      "propertyOrder" : 2,
      "required" : true,
      "description" : ""
    },
    "org.forgerock.services.umaudit.store.password" : {
      "type" : "string",
      "title" : "Password",
      "propertyOrder" : 3,
      "required" : true,
      "description" : "",
      "format" : "password"
    },
    "org.forgerock.services.umaudit.store.heartbeat" : {
      "type" : "integer",
      "title" : "Heartbeat",
      "propertyOrder" : 4,
      "required" : true,
      "description" : ""
    }
  }
},
"amconfig.org.forgerock.services.uma.pendingrequests.store.common.section" : {
  "title" : "Pending Requests Store",
  "type" : "object",

```

```

"propertyOrder" : 4,
"properties" : {
  "org.forgerock.services.uma.pendingrequests.store.location" : {
    "enum" : [ "default", "external" ],
    "options" : {
      "enum_titles" : [ "Default Token Store", "External Token Store" ]
    },
    "type" : "string",
    "title" : "Store Mode",
    "propertyOrder" : 0,
    "required" : true,
    "description" : ""
  },
  "org.forgerock.services.uma.pendingrequests.store.root.suffix" : {
    "type" : "string",
    "title" : "Root Suffix",
    "propertyOrder" : 1,
    "required" : true,
    "description" : ""
  },
  "org.forgerock.services.uma.pendingrequests.store.max.connections" : {
    "type" : "string",
    "title" : "Max Connections",
    "propertyOrder" : 2,
    "required" : true,
    "description" : ""
  }
}
},
"amconfig.org.forgerock.services.uma.pendingrequests.store.external.section" : {
  "title" : "External Pending Requests Store Configuration",
  "type" : "object",
  "propertyOrder" : 5,
  "properties" : {
    "org.forgerock.services.uma.pendingrequests.store.ssl.enabled" : {
      "type" : "boolean",
      "title" : "SSL/TLS Enabled",
      "propertyOrder" : 0,
      "required" : true,
      "description" : ""
    },
    "org.forgerock.services.uma.pendingrequests.store.directory.name" : {
      "type" : "string",
      "title" : "Connection String(s)",
      "propertyOrder" : 1,
      "required" : true,
      "description" : "An ordered list of connection strings for LDAP directories. Each connection
string is composed as follows: <code>HOST:PORT[|SERVERID[|SITEID]]</code>, where server and site
IDs are optional parameters that will prioritize that connection to use from the specified nodes.
Multiple connection strings should be comma-separated, e.g. <code>host1:389,host2:50389|server1|
site1,host3:50389</code>."
    },
    "org.forgerock.services.uma.pendingrequests.store.loginid" : {
      "type" : "string",
      "title" : "Login Id",
      "propertyOrder" : 2,
      "required" : true,
      "description" : ""
    }
  }
},

```

```
"org.forgerock.services.uma.pendingrequests.store.password" : {
  "type" : "string",
  "title" : "Password",
  "propertyOrder" : 3,
  "required" : true,
  "description" : "",
  "format" : "password"
},
"org.forgerock.services.uma.pendingrequests.store.heartbeat" : {
  "type" : "integer",
  "title" : "Heartbeat",
  "propertyOrder" : 4,
  "required" : true,
  "description" : ""
}
},
"amconfig.org.forgerock.services.uma.labels.store.common.section" : {
  "title" : "UMA Resource Set Labels Store",
  "type" : "object",
  "propertyOrder" : 6,
  "properties" : {
    "org.forgerock.services.uma.labels.store.location" : {
      "enum" : [ "default", "external" ],
      "options" : {
        "enum_titles" : [ "Default Token Store", "External Token Store" ]
      },
      "type" : "string",
      "title" : "Store Mode",
      "propertyOrder" : 0,
      "required" : true,
      "description" : ""
    },
    "org.forgerock.services.uma.labels.store.root.suffix" : {
      "type" : "string",
      "title" : "Root Suffix",
      "propertyOrder" : 1,
      "required" : true,
      "description" : ""
    },
    "org.forgerock.services.uma.labels.store.max.connections" : {
      "type" : "string",
      "title" : "Max Connections",
      "propertyOrder" : 2,
      "required" : true,
      "description" : ""
    }
  }
},
"amconfig.org.forgerock.services.uma.labels.store.external.section" : {
  "title" : "External Resource Set Labels Store Configuration",
  "type" : "object",
  "propertyOrder" : 7,
  "properties" : {
    "org.forgerock.services.uma.labels.store.ssl.enabled" : {
      "type" : "boolean",
      "title" : "SSL/TLS Enabled",
      "propertyOrder" : 0,
      "required" : true,
```

```
    "description" : ""
  },
  "org.forgerock.services.uma.labels.store.directory.name" : {
    "type" : "string",
    "title" : "Connection String(s)",
    "propertyOrder" : 1,
    "required" : true,
    "description" : "An ordered list of connection strings for LDAP directories. Each connection
string is composed as follows: <code>HOST:PORT[|SERVERID[|SITEID]]</code>, where server and site
IDs are optional parameters that will prioritize that connection to use from the specified nodes.
Multiple connection strings should be comma-separated, e.g. <code>host1:389,host2:50389|server1|
site1,host3:50389</code>."
  },
  "org.forgerock.services.uma.labels.store.loginid" : {
    "type" : "string",
    "title" : "Login Id",
    "propertyOrder" : 2,
    "required" : true,
    "description" : ""
  },
  "org.forgerock.services.uma.labels.store.password" : {
    "type" : "string",
    "title" : "Password",
    "propertyOrder" : 3,
    "required" : true,
    "description" : "",
    "format" : "password"
  },
  "org.forgerock.services.uma.labels.store.heartbeat" : {
    "type" : "integer",
    "title" : "Heartbeat",
    "propertyOrder" : 4,
    "required" : true,
    "description" : ""
  }
}
}
}
}
```

1.54. DeviceIDService

1.54.1. Realm Operations

Resource path: </realm-config/services/deviceIdService>

Resource version: 1.0

1.54.1.1. create

Usage:

```
am> create DeviceIDService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "deviceIdSettingsEncryptionKeystoreType" : {
      "title" : "Key Store Type",
      "description" : "Type of key store to load.<br><br><i>Note:</i> PKCS#11 key stores require hardware support such as a security device or smart card and is not available by default in most JVM installations.<p><p>See the <a href=\"https://docs.oracle.com/javase/8/docs/technotes/guides/security/pllguide.html\" target=\"_blank\">JDK 8 PKCS#11 Reference Guide</a> for more details.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "deviceIdSettingsEncryptionKeystore" : {
      "title" : "Encryption Key Store",
      "description" : "Path to the key store from which to load encryption keys.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "deviceIdSettingsEncryptionKeystoreKeyPairAlias" : {
      "title" : "Key-Pair Alias",
      "description" : "Alias of the certificate and private key in the key store. The private key is used to encrypt and decrypt device profiles.",
      "propertyOrder" : 600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "deviceIdSettingsEncryptionKeystorePrivateKeyPassword" : {
      "title" : "Private Key Password",
      "description" : "Password to unlock the private key.",
      "propertyOrder" : 700,
      "required" : false,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "deviceIdSettingsEncryptionScheme" : {
      "title" : "Device Profile Encryption Scheme",
      "description" : "Encryption scheme to use to secure device profiles stored on the server.<br><br>If enabled, each device profile is encrypted using a unique random secret key using the given strength of AES encryption in CBC mode with PKCS#5 padding. An HMAC-SHA of the given strength (truncated to half-size) is used to ensure integrity protection and authenticated encryption. The unique random key is encrypted with the given RSA key pair and stored with the device profile.<p><p><i>Note:</i> AES-256 may require installation of the JCE Unlimited Strength policy files.",
      "propertyOrder" : 200,

```

```
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "deviceIdAttrName" : {
    "title" : "Profile Storage Attribute",
    "description" : "The user's attribute in which to store Device ID profiles.<br><br>The default attribute is added to the schema when you prepare a user store for use with OpenAM. If you want to use a different attribute, you must make sure to add it to your user store schema prior to enabling the Device ID authentication module. OpenAM must be able to write to the attribute.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "deviceIdSettingsEncryptionKeystorePassword" : {
    "title" : "Key Store Password",
    "description" : "Password to unlock the key store. This password is encrypted when it is saved in the OpenAM configuration. You should modify the default value.",
    "propertyOrder" : 500,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }
}
```

1.54.1.2. delete

Usage:

```
am> delete DeviceIDService --realm Realm
```

1.54.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DeviceIDService --realm Realm --actionName getAllTypes
```

1.54.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DeviceIDService --realm Realm --actionName getCreatableTypes
```

1.54.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DeviceIDService --realm Realm --actionName nextdescendents
```

1.54.1.6. read

Usage:

```
am> read DeviceIDService --realm Realm
```

1.54.1.7. update

Usage:

```
am> update DeviceIDService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "deviceIdSettingsEncryptionKeystoreType" : {
      "title" : "Key Store Type",
      "description" : "Type of key store to load.<br><br><i>Note:</i> PKCS#11 key stores require hardware support such as a security device or smart card and is not available by default in most JVM installations.<p><p>See the <a href=\"https://docs.oracle.com/javase/8/docs/technotes/guides/security/p11guide.html\" target=\"_blank\">JDK 8 PKCS#11 Reference Guide</a> for more details.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "deviceIdSettingsEncryptionKeystore" : {
      "title" : "Encryption Key Store",
      "description" : "Path to the key store from which to load encryption keys.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "deviceIdSettingsEncryptionKeystoreKeyPairAlias" : {
      "title" : "Key-Pair Alias",
      "description" : "Alias of the certificate and private key in the key store. The private key is used to encrypt and decrypt device profiles.",
      "propertyOrder" : 600,
```



```

    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "deviceIdSettingsEncryptionKeystorePrivateKeyPassword" : {
    "title" : "Private Key Password",
    "description" : "Password to unlock the private key.",
    "propertyOrder" : 700,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "deviceIdSettingsEncryptionScheme" : {
    "title" : "Device Profile Encryption Scheme",
    "description" : "Encryption scheme to use to secure device profiles stored on the
server.<br><br>If enabled, each device profile is encrypted using a unique random secret key
using the given strength of AES encryption in CBC mode with PKCS#5 padding. An HMAC-SHA of the
given strength (truncated to half-size) is used to ensure integrity protection and authenticated
encryption. The unique random key is encrypted with the given RSA key pair and stored with the device
profile.<p><p><i>Note:</i> AES-256 may require installation of the JCE Unlimited Strength policy
files.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "deviceIdAttrName" : {
    "title" : "Profile Storage Attribute",
    "description" : "The user's attribute in which to store Device ID profiles.<br><br>The default
attribute is added to the schema when you prepare a user store for use with OpenAM. If you want to
use a different attribute, you must make sure to add it to your user store schema prior to enabling
the Device ID authentication module. OpenAM must be able to write to the attribute.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "deviceIdSettingsEncryptionKeystorePassword" : {
    "title" : "Key Store Password",
    "description" : "Password to unlock the key store. This password is encrypted when it is saved
in the OpenAM configuration. You should modify the default value.",
    "propertyOrder" : 500,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }
}
}
}

```

1.54.2. Global Operations

Resource path: </global-config/services/deviceIdService>

Resource version: 1.0

1.54.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DeviceIDService --global --actionName getAllTypes
```

1.54.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DeviceIDService --global --actionName getCreatableTypes
```

1.54.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DeviceIDService --global --actionName nextdescendents
```

1.54.2.4. read

Usage:

```
am> read DeviceIDService --global
```

1.54.2.5. update

Usage:

```
am> update DeviceIDService --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "deviceIdSettingsEncryptionKeystoreKeyPairAlias" : {
          "title" : "Key-Pair Alias",
          "description" : "Alias of the certificate and private key in the key store. The private key
is used to encrypt and decrypt device profiles.",
          "propertyOrder" : 600,

```

```

    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "deviceIdSettingsEncryptionKeystoreType" : {
    "title" : "Key Store Type",
    "description" : "Type of key store to load.<br><br><i>Note:</i> PKCS#11 key stores require hardware support such as a security device or smart card and is not available by default in most JVM installations.<p><p>See the <a href="https://docs.oracle.com/javase/8/docs/technotes/guides/security/p11guide.html" target="_blank">JDK 8 PKCS#11 Reference Guide</a> for more details.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "deviceIdAttrName" : {
    "title" : "Profile Storage Attribute",
    "description" : "The user's attribute in which to store Device ID profiles.<br><br>The default attribute is added to the schema when you prepare a user store for use with OpenAM. If you want to use a different attribute, you must make sure to add it to your user store schema prior to enabling the Device ID authentication module. OpenAM must be able to write to the attribute.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "deviceIdSettingsEncryptionKeystorePrivateKeyPassword" : {
    "title" : "Private Key Password",
    "description" : "Password to unlock the private key.",
    "propertyOrder" : 700,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "deviceIdSettingsEncryptionScheme" : {
    "title" : "Device Profile Encryption Scheme",
    "description" : "Encryption scheme to use to secure device profiles stored on the server.<br><br>If enabled, each device profile is encrypted using a unique random secret key using the given strength of AES encryption in CBC mode with PKCS#5 padding. An HMAC-SHA of the given strength (truncated to half-size) is used to ensure integrity protection and authenticated encryption. The unique random key is encrypted with the given RSA key pair and stored with the device profile.<p><p><i>Note:</i> AES-256 may require installation of the JCE Unlimited Strength policy files.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "deviceIdSettingsEncryptionKeystorePassword" : {
    "title" : "Key Store Password",
    "description" : "Password to unlock the key store. This password is encrypted when it is saved in the OpenAM configuration. You should modify the default value.",
    "propertyOrder" : 500,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  },

```

```
"deviceIdSettingsEncryptionKeystore" : {
  "title" : "Encryption Key Store",
  "description" : "Path to the key store from which to load encryption keys.",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"type" : "object",
"title" : "Realm Defaults"
}
}
```

1.55. DeviceIdMatchModule

1.55.1. Realm Operations

Resource path: `/realm-config/authentication/modules/deviceidmatch`

Resource version: `1.0`

1.55.1.1. create

Usage:

```
am> create DeviceIdMatchModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "clientScript" : {
      "title" : "Client-side Script",
      "description" : "The client-side script.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
```

```

    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with the authentication module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "clientScriptEnabled" : {
    "title" : "Client-side Script Enabled",
    "description" : "Enable this setting if the client-side script should be executed.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "serverScript" : {
    "title" : "Server-side Script",
    "description" : "The server-side script to execute.<br><br>This script will be run on the server, subsequent to any client script having returned. It can be written in the selected language.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}

```

1.55.1.2. delete

Usage:

```
am> delete DeviceIdMatchModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.55.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DeviceIdMatchModule --realm Realm --actionName getAllTypes
```

1.55.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DeviceIdMatchModule --realm Realm --actionName getCreatableTypes
```

1.55.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DeviceIdMatchModule --realm Realm --actionName nextdescendents
```

1.55.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query DeviceIdMatchModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.55.1.7. read

Usage:

```
am> read DeviceIdMatchModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.55.1.8. update

Usage:

```
am> update DeviceIdMatchModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "clientScript" : {
      "title" : "Client-side Script",
      "description" : "The client-side script.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with the authentication module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "clientScriptEnabled" : {
      "title" : "Client-side Script Enabled",
      "description" : "Enable this setting if the client-side script should be executed.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "serverScript" : {
      "title" : "Server-side Script",
      "description" : "The server-side script to execute.<br><br>This script will be run on the server, subsequent to any client script having returned. It can be written in the selected language.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.55.2. Global Operations

Resource path: </global-config/authentication/modules/deviceidmatch>

Resource version: 1.0

1.55.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DeviceIdMatchModule --global --actionName getAllTypes
```

1.55.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DeviceIdMatchModule --global --actionName getCreatableTypes
```

1.55.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DeviceIdMatchModule --global --actionName nextdescendents
```

1.55.2.4. read

Usage:

```
am> read DeviceIdMatchModule --global
```

1.55.2.5. update

Usage:

```
am> update DeviceIdMatchModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "clientScript" : {
          "title" : "Client-side Script",
          "description" : "The client-side script.",
          "propertyOrder" : 200,
          "required" : true,
```



```

    "type" : "string",
    "exampleValue" : ""
  },
  "clientScriptEnabled" : {
    "title" : "Client-side Script Enabled",
    "description" : "Enable this setting if the client-side script should be executed.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with the authentication
module.<br><br>Each authentication module has an authentication level that can be used to indicate
the level of security associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "serverScript" : {
    "title" : "Server-side Script",
    "description" : "The server-side script to execute.<br><br>This script will be run on
the server, subsequent to any client script having returned. It can be written in the selected
language.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}

```

1.56. DeviceIdSaveModule

1.56.1. Realm Operations

Resource path: `/realm-config/authentication/modules/deviceidsave`

Resource version: `1.0`

1.56.1.1. create

Usage:

```
am> create DeviceIdSaveModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "maxProfilesAllowed" : {
      "title" : "Maximum stored profile quantity",
      "description" : "No more than specified profiles quantity will be stored in user record",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with the authentication module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "autoStoreProfiles" : {
      "title" : "Automatically store new profiles",
      "description" : "Select this checkbox to assume user consent to store every new profile<br><br>If this checkbox is selected user won't be prompted for storing new profiles. After successful OTP confirmation profile will be stored automatically.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
```

1.56.1.2. delete

Usage:

```
am> delete DeviceIdSaveModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.56.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DeviceIdSaveModule --realm Realm --actionName getAllTypes
```

1.56.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DeviceIdSaveModule --realm Realm --actionName getCreatableTypes
```

1.56.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DeviceIdSaveModule --realm Realm --actionName nextdescendents
```

1.56.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query DeviceIdSaveModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.56.1.7. read

Usage:

```
am> read DeviceIdSaveModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.56.1.8. update

Usage:

```
am> update DeviceIdSaveModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "maxProfilesAllowed" : {
      "title" : "Maximum stored profile quantity",
      "description" : "No more than specified profiles quantity will be stored in user record",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with the authentication module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "autoStoreProfiles" : {
      "title" : "Automatically store new profiles",
      "description" : "Select this checkbox to assume user consent to store every new profile<br><br>If this checkbox is selected user won't be prompted for storing new profiles. After successful OTP confirmation profile will be stored automatically.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
```

1.56.2. Global Operations

Resource path: </global-config/authentication/modules/deviceidsave>

Resource version: 1.0

1.56.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action DeviceIdSaveModule --global --actionName getAllTypes
```

1.56.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action DeviceIdSaveModule --global --actionName getCreatableTypes
```

1.56.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action DeviceIdSaveModule --global --actionName nextdescendents
```

1.56.2.4. read

Usage:

```
am> read DeviceIdSaveModule --global
```

1.56.2.5. update

Usage:

```
am> update DeviceIdSaveModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with the authentication
module.<br><br>Each authentication module has an authentication level that can be used to indicate
the level of security associated with the module; 0 is the lowest (and the default).",
```

```
    "propertyOrder" : 300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "maxProfilesAllowed" : {
    "title" : "Maximum stored profile quantity",
    "description" : "No more than specified profiles quantity will be stored in user record",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "autoStoreProfiles" : {
    "title" : "Automatically store new profiles",
    "description" : "Select this checkbox to assume user consent to store every new
profile<br><br>If this checkbox is selected user won't be prompted for storing new profiles. After
successful OTP confirmation profile will be stored automatically.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
```

1.57. DirectoryConfiguration

1.57.1. Global Operations

Connection details for directory server(s).

Resource path: `/global-config/servers/{serverName}/properties/directoryConfiguration`

Resource version: `1.0`

1.57.1.1. read

Usage:

```
am> read DirectoryConfiguration --global --serverName serverName
```

Parameters:

`--serverName`

Connection details for directory server(s).

1.57.1.2. update

Usage:

```
am> update DirectoryConfiguration --global --serverName serverName --body body
```

Parameters:

--serverName

Connection details for directory server(s).

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "directoryConfiguration" : {
      "type" : "object",
      "title" : "Directory Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "minConnectionPool" : {
          "title" : "Minimum Connection Pool",
          "propertyOrder" : 0,
          "type" : "number"
        },
        "maxConnectionPool" : {
          "title" : "Maximum Connection Pool",
          "propertyOrder" : 1,
          "type" : "number"
        },
        "bindDn" : {
          "title" : "Bind DN",
          "propertyOrder" : 2,
          "type" : "string"
        },
        "bindPassword" : {
          "title" : "Bind Password",
          "propertyOrder" : 3,
          "type" : "string",
          "format" : "password"
        }
      }
    },
    "directoryServers" : {
      "type" : "array",
      "title" : "Server",
      "propertyOrder" : 1,
      "items" : {
        "type" : "object",
        "required" : [ "serverName", "hostName", "portNumber", "connectionType" ],
        "properties" : {
```

```
"serverName" : {
  "title" : "Name",
  "type" : "string",
  "propertyOrder" : 0
},
"hostName" : {
  "title" : "Host Name",
  "type" : "string",
  "propertyOrder" : 1
},
"portNumber" : {
  "title" : "Port Number",
  "type" : "string",
  "propertyOrder" : 2
},
"connectionType" : {
  "type" : "string",
  "enum" : [ "SIMPLE", "SSL" ],
  "options" : {
    "enum_titles" : [ "SIMPLE", "SSL" ]
  },
  "title" : "Connection Type",
  "propertyOrder" : 3
}
}
}
}
}
```

1.58. ElasticSearch

1.58.1. Realm Operations

Resource path: [/realm-config/services/audit/Elasticsearch](#)

Resource version: [1.0](#)

1.58.1.1. create

Usage:

```
am> create ElasticSearch --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "elasticsearchAuthentication" : {
      "type" : "object",
      "title" : "Authentication",
      "propertyOrder" : 3,
      "properties" : {
        "password" : {
          "title" : "Password",
          "description" : "Specifies the password to access the Elasticsearch server.<p><p>Required if Elasticsearch Shield authentication is configured.",
          "propertyOrder" : 5600,
          "required" : true,
          "type" : "string",
          "format" : "password",
          "exampleValue" : ""
        },
        "username" : {
          "title" : "Username",
          "description" : "Specifies the username to access the Elasticsearch server.<p><p>Required if Elasticsearch Shield authentication is configured.",
          "propertyOrder" : 5500,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 5000,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 4900,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        }
      }
    }
  }
},
```

```

"elasticsearchConfig" : {
  "type" : "object",
  "title" : "Elasticsearch Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "index" : {
      "title" : "Elasticsearch Index",
      "description" : "Specifies the name of the Elasticsearch index to be used for OpenAM audit
logging.",
      "propertyOrder" : 5400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sslEnabled" : {
      "title" : "SSL Enabled",
      "description" : "Specifies whether SSL is configured on the Elasticsearch server.<p><p>If
SSL is enabled, be sure to import the CA certificate used to sign Elasticsearch node certificates
into the Java keystore on the host that runs OpenAM before attempting to log audit events to
Elasticsearch.",
      "propertyOrder" : 5300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "port" : {
      "title" : "Server Port",
      "description" : "Specifies the port number used to access Elasticsearch's REST API.",
      "propertyOrder" : 5200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "host" : {
      "title" : "Server Hostname",
      "description" : "Host name or IP address of the Elasticsearch server.",
      "propertyOrder" : 5100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 6100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}

```

```
},
"elasticsearchBuffering" : {
  "type" : "object",
  "title" : "Buffering",
  "propertyOrder" : 4,
  "properties" : {
    "batchSize" : {
      "title" : "Batch Size",
      "description" : "Maximum number of events that can be buffered (default: 10000)",
      "propertyOrder" : 5800,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "writeInterval" : {
      "title" : "Write interval (in milliseconds)",
      "description" : "Specifies the interval in milliseconds at which buffered events are written
to Elasticsearch.",
      "propertyOrder" : 6000,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "maxEvents" : {
      "title" : "Queue Capacity",
      "description" : "Maximum number of audit logs in the batch queue. Additional audit events
are dropped.",
      "propertyOrder" : 5900,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "bufferingEnabled" : {
      "title" : "Buffering Enabled",
      "description" : "",
      "propertyOrder" : 5700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
}
}
```

1.58.1.2. delete

Usage:

```
am> delete ElasticSearch --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.58.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ElasticSearch --realm Realm --actionName getAllTypes
```

1.58.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ElasticSearch --realm Realm --actionName getCreatableTypes
```

1.58.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ElasticSearch --realm Realm --actionName nextdescendents
```

1.58.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ElasticSearch --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.58.1.7. read

Usage:

```
am> read ElasticSearch --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.58.1.8. update

Usage:

```
am> update ElasticSearch --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "elasticsearchAuthentication" : {
      "type" : "object",
      "title" : "Authentication",
      "propertyOrder" : 3,
      "properties" : {
        "password" : {
          "title" : "Password",
          "description" : "Specifies the password to access the Elasticsearch server.<p><p>Required if
Elasticsearch Shield authentication is configured.",
          "propertyOrder" : 5600,
          "required" : true,
          "type" : "string",
          "format" : "password",
          "exampleValue" : ""
        },
        "username" : {
          "title" : "Username",
          "description" : "Specifies the username to access the Elasticsearch server.<p><p>Required if
Elasticsearch Shield authentication is configured.",
          "propertyOrder" : 5500,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 5000,
          "required" : true,
          "items" : {
            "type" : "string"
          }
        }
      }
    }
  }
}
```

```

    "type" : "array",
    "exampleValue" : ""
  },
  "enabled" : {
    "title" : "Enabled",
    "description" : "Enables or disables an audit event handler.",
    "propertyOrder" : 4900,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"elasticsearchConfig" : {
  "type" : "object",
  "title" : "Elasticsearch Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "index" : {
      "title" : "Elasticsearch Index",
      "description" : "Specifies the name of the Elasticsearch index to be used for OpenAM audit
logging.",
      "propertyOrder" : 5400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sslEnabled" : {
      "title" : "SSL Enabled",
      "description" : "Specifies whether SSL is configured on the Elasticsearch server.<p><p>If
SSL is enabled, be sure to import the CA certificate used to sign Elasticsearch node certificates
into the Java keystore on the host that runs OpenAM before attempting to log audit events to
Elasticsearch.",
      "propertyOrder" : 5300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "port" : {
      "title" : "Server Port",
      "description" : "Specifies the port number used to access Elasticsearch's REST API.",
      "propertyOrder" : 5200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "host" : {
      "title" : "Server Hostname",
      "description" : "Host name or IP address of the Elasticsearch server.",
      "propertyOrder" : 5100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",

```

```
    "propertyOrder" : 1,
    "properties" : {
      "handlerFactory" : {
        "title" : "Factory Class Name",
        "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
        "propertyOrder" : 6100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      }
    }
  },
  "elasticsearchBuffering" : {
    "type" : "object",
    "title" : "Buffering",
    "propertyOrder" : 4,
    "properties" : {
      "batchSize" : {
        "title" : "Batch Size",
        "description" : "Maximum number of events that can be buffered (default: 10000)",
        "propertyOrder" : 5800,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      },
      "writeInterval" : {
        "title" : "Write interval (in milliseconds)",
        "description" : "Specifies the interval in milliseconds at which buffered events are written
to Elasticsearch.",
        "propertyOrder" : 6000,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      },
      "maxEvents" : {
        "title" : "Queue Capacity",
        "description" : "Maximum number of audit logs in the batch queue. Additional audit events
are dropped.",
        "propertyOrder" : 5900,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      },
      "bufferingEnabled" : {
        "title" : "Buffering Enabled",
        "description" : "",
        "propertyOrder" : 5700,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      }
    }
  }
}
}
```

1.58.2. Global Operations

Resource path: `/global-config/services/audit/Elasticsearch`

Resource version: `1.0`

1.58.2.1. create

Usage:

```
am> create ElasticSearch --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "elasticsearchBuffering" : {
      "type" : "object",
      "title" : "Buffering",
      "propertyOrder" : 4,
      "properties" : {
        "writeInterval" : {
          "title" : "Write interval (in milliseconds)",
          "description" : "Specifies the interval in milliseconds at which buffered events are written
to Elasticsearch.",
          "propertyOrder" : 6000,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "bufferingEnabled" : {
          "title" : "Buffering Enabled",
          "description" : "",
          "propertyOrder" : 5700,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        }
      }
    },
    "batchSize" : {
      "title" : "Batch Size",
      "description" : "Maximum number of events that can be buffered (default: 10000)",
      "propertyOrder" : 5800,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```



```

    "maxEvents" : {
      "title" : "Queue Capacity",
      "description" : "Maximum number of audit logs in the batch queue. Additional audit events
are dropped.",
      "propertyOrder" : 5900,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "commonHandlerPlugin" : {
    "type" : "object",
    "title" : "Audit Event Handler Factory",
    "propertyOrder" : 1,
    "properties" : {
      "handlerFactory" : {
        "title" : "Factory Class Name",
        "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
        "propertyOrder" : 6100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      }
    }
  },
  "elasticsearchConfig" : {
    "type" : "object",
    "title" : "Elasticsearch Configuration",
    "propertyOrder" : 2,
    "properties" : {
      "sslEnabled" : {
        "title" : "SSL Enabled",
        "description" : "Specifies whether SSL is configured on the Elasticsearch server.<p><p>If
SSL is enabled, be sure to import the CA certificate used to sign Elasticsearch node certificates
into the Java keystore on the host that runs OpenAM before attempting to log audit events to
Elasticsearch.",
        "propertyOrder" : 5300,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "port" : {
        "title" : "Server Port",
        "description" : "Specifies the port number used to access Elasticsearch's REST API.",
        "propertyOrder" : 5200,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      },
      "index" : {
        "title" : "Elasticsearch Index",
        "description" : "Specifies the name of the Elasticsearch index to be used for OpenAM audit
logging.",
        "propertyOrder" : 5400,
        "required" : true,
        "type" : "string",

```

```

        "exampleValue" : ""
    },
    "host" : {
        "title" : "Server Hostname",
        "description" : "Host name or IP address of the Elasticsearch server.",
        "propertyOrder" : 5100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"commonHandler" : {
    "type" : "object",
    "title" : "General Handler Configuration",
    "propertyOrder" : 0,
    "properties" : {
        "topics" : {
            "title" : "Topics",
            "description" : "List of topics handled by an audit event handler.",
            "propertyOrder" : 5000,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "enabled" : {
            "title" : "Enabled",
            "description" : "Enables or disables an audit event handler.",
            "propertyOrder" : 4900,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        }
    }
}
},
"elasticsearchAuthentication" : {
    "type" : "object",
    "title" : "Authentication",
    "propertyOrder" : 3,
    "properties" : {
        "password" : {
            "title" : "Password",
            "description" : "Specifies the password to access the Elasticsearch server.<p><p>Required if Elasticsearch Shield authentication is configured.",
            "propertyOrder" : 5600,
            "required" : true,
            "type" : "string",
            "format" : "password",
            "exampleValue" : ""
        },
        "username" : {
            "title" : "Username",
            "description" : "Specifies the username to access the Elasticsearch server.<p><p>Required if Elasticsearch Shield authentication is configured.",
            "propertyOrder" : 5500,
            "required" : true,

```

```
        "type" : "string",
        "exampleValue" : ""
      }
    }
  }
}
```

1.58.2.2. delete

Usage:

```
am> delete ElasticSearch --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.58.2.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ElasticSearch --global --actionName getAllTypes
```

1.58.2.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ElasticSearch --global --actionName getCreatableTypes
```

1.58.2.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ElasticSearch --global --actionName nextdescendents
```

1.58.2.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ElasticSearch --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.58.2.7. read

Usage:

```
am> read ElasticSearch --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.58.2.8. update

Usage:

```
am> update ElasticSearch --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "elasticsearchBuffering" : {
      "type" : "object",
      "title" : "Buffering",
      "propertyOrder" : 4,
      "properties" : {
        "writeInterval" : {
          "title" : "Write interval (in milliseconds)",
          "description" : "Specifies the interval in milliseconds at which buffered events are written to Elasticsearch.",
          "propertyOrder" : 6000,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        }
      }
    }
  }
},
```

```

"bufferingEnabled" : {
  "title" : "Buffering Enabled",
  "description" : "",
  "propertyOrder" : 5700,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"batchSize" : {
  "title" : "Batch Size",
  "description" : "Maximum number of events that can be buffered (default: 10000)",
  "propertyOrder" : 5800,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"maxEvents" : {
  "title" : "Queue Capacity",
  "description" : "Maximum number of audit logs in the batch queue. Additional audit events
are dropped.",
  "propertyOrder" : 5900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}
}
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 6100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"elasticsearchConfig" : {
  "type" : "object",
  "title" : "Elasticsearch Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "sslEnabled" : {
      "title" : "SSL Enabled",
      "description" : "Specifies whether SSL is configured on the Elasticsearch server.<p><p>If
SSL is enabled, be sure to import the CA certificate used to sign Elasticsearch node certificates
into the Java keystore on the host that runs OpenAM before attempting to log audit events to
Elasticsearch.",
      "propertyOrder" : 5300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}

```

```

    },
    "port" : {
      "title" : "Server Port",
      "description" : "Specifies the port number used to access Elasticsearch's REST API.",
      "propertyOrder" : 5200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    },
    "index" : {
      "title" : "Elasticsearch Index",
      "description" : "Specifies the name of the Elasticsearch index to be used for OpenAM audit
logging.",
      "propertyOrder" : 5400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "host" : {
      "title" : "Server Hostname",
      "description" : "Host name or IP address of the Elasticsearch server.",
      "propertyOrder" : 5100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"commonHandler" : {
  "type" : "object",
  "title" : "General Handler Configuration",
  "propertyOrder" : 0,
  "properties" : {
    "topics" : {
      "title" : "Topics",
      "description" : "List of topics handled by an audit event handler.",
      "propertyOrder" : 5000,
      "required" : true,
      "items" : {
        "type" : "string"
      },
    },
    "type" : "array",
    "exampleValue" : ""
  },
},
"enabled" : {
  "title" : "Enabled",
  "description" : "Enables or disables an audit event handler.",
  "propertyOrder" : 4900,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
}
}
},
"elasticsearchAuthentication" : {
  "type" : "object",
  "title" : "Authentication",
  "propertyOrder" : 3,
  "properties" : {

```

```
"password" : {
  "title" : "Password",
  "description" : "Specifies the password to access the Elasticsearch server.<p><p>Required if
Elasticsearch Shield authentication is configured.",
  "propertyOrder" : 5600,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"username" : {
  "title" : "Username",
  "description" : "Specifies the username to access the Elasticsearch server.<p><p>Required if
Elasticsearch Shield authentication is configured.",
  "propertyOrder" : 5500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
}
}
```

1.59. EmailService

1.59.1. Realm Operations

Resource path: `/realm-config/services/email`

Resource version: `1.0`

1.59.1.1. create

Usage:

```
am> create EmailService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "emailAddressAttribute" : {
      "title" : "Email Attribute Name",
      "description" : "Specifies the profile attribute from which to retrieve the end user's email
address.",

```

```
"propertyOrder" : 800,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"password" : {
  "title" : "Mail Server Authentication Password",
  "description" : "Specifies the password for the SMTP user name.",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"subject" : {
  "title" : "Email Subject",
  "description" : "Specifies a subject for notification messages. If you do not set this, OpenAM
does not set the subject for notification messages.",
  "propertyOrder" : 900,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"emailImplClassName" : {
  "title" : "Email Message Implementation Class",
  "description" : "Specifies the class that sends email notifications, such as those sent for user
registration and forgotten passwords.",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"hostname" : {
  "title" : "Mail Server Host Name",
  "description" : "Specifies the fully qualified domain name of the SMTP mail server through which
to send email notifications.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : "smtp.example.com"
},
"sslState" : {
  "title" : "Mail Server Secure Connection",
  "description" : "Specifies whether to connect to the SMTP mail server using SSL.",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"from" : {
  "title" : "Email From Address",
  "description" : "Specifies the address from which to send email notifications.",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "string",
  "exampleValue" : "no-reply@example.com"
},
"message" : {
  "title" : "Email Content",
```



```
"description" : "Specifies content for notification messages. If you do not set this, OpenAM includes only the confirmation URL in the mail body.",
"propertyOrder" : 1000,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"port" : {
"title" : "Mail Server Host Port",
"description" : "Specifies the port number for the SMTP mail server.",
"propertyOrder" : 300,
"required" : true,
"type" : "integer",
"exampleValue" : ""
},
"username" : {
"title" : "Mail Server Authentication Username",
"description" : "Specifies the user name for the SMTP mail server.",
"propertyOrder" : 400,
"required" : true,
"type" : "string",
"exampleValue" : "username"
}
}
```

1.59.1.2. delete

Usage:

```
am> delete EmailService --realm Realm
```

1.59.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action EmailService --realm Realm --actionName getAllTypes
```

1.59.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action EmailService --realm Realm --actionName getCreatableTypes
```

1.59.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action EmailService --realm Realm --actionName nextdescendents
```

1.59.1.6. read

Usage:

```
am> read EmailService --realm Realm
```

1.59.1.7. update

Usage:

```
am> update EmailService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "emailAddressAttribute" : {
      "title" : "Email Attribute Name",
      "description" : "Specifies the profile attribute from which to retrieve the end user's email address.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "password" : {
      "title" : "Mail Server Authentication Password",
      "description" : "Specifies the password for the SMTP user name.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "subject" : {
      "title" : "Email Subject",
      "description" : "Specifies a subject for notification messages. If you do not set this, OpenAM does not set the subject for notification messages.",
      "propertyOrder" : 900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "emailImplClassName" : {
      "title" : "Email Message Implementation Class",
```

```
"description" : "Specifies the class that sends email notifications, such as those sent for user
registration and forgotten passwords.",
"propertyOrder" : 100,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"hostname" : {
"title" : "Mail Server Host Name",
"description" : "Specifies the fully qualified domain name of the SMTP mail server through which
to send email notifications.",
"propertyOrder" : 200,
"required" : true,
"type" : "string",
"exampleValue" : "smtp.example.com"
},
"sslState" : {
"title" : "Mail Server Secure Connection",
"description" : "Specifies whether to connect to the SMTP mail server using SSL.",
"propertyOrder" : 600,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"from" : {
"title" : "Email From Address",
"description" : "Specifies the address from which to send email notifications.",
"propertyOrder" : 700,
"required" : true,
"type" : "string",
"exampleValue" : "no-reply@example.com"
},
"message" : {
"title" : "Email Content",
"description" : "Specifies content for notification messages. If you do not set this, OpenAM
includes only the confirmation URL in the mail body.",
"propertyOrder" : 1000,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"port" : {
"title" : "Mail Server Host Port",
"description" : "Specifies the port number for the SMTP mail server.",
"propertyOrder" : 300,
"required" : true,
"type" : "integer",
"exampleValue" : ""
},
"username" : {
"title" : "Mail Server Authentication Username",
"description" : "Specifies the user name for the SMTP mail server.",
"propertyOrder" : 400,
"required" : true,
"type" : "string",
"exampleValue" : "username"
}
}
```

```
}
```

1.59.2. Global Operations

Resource path: `/global-config/services/email`

Resource version: `1.0`

1.59.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action EmailService --global --actionName getAllTypes
```

1.59.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action EmailService --global --actionName getCreatableTypes
```

1.59.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action EmailService --global --actionName nextdescendents
```

1.59.2.4. read

Usage:

```
am> read EmailService --global
```

1.59.2.5. update

Usage:

```
am> update EmailService --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "port" : {
          "title" : "Mail Server Host Port",
          "description" : "Specifies the port number for the SMTP mail server.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "username" : {
          "title" : "Mail Server Authentication Username",
          "description" : "Specifies the user name for the SMTP mail server.",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "string",
          "exampleValue" : "username"
        },
        "from" : {
          "title" : "Email From Address",
          "description" : "Specifies the address from which to send email notifications.",
          "propertyOrder" : 700,
          "required" : true,
          "type" : "string",
          "exampleValue" : "no-reply@example.com"
        },
        "emailImplClassName" : {
          "title" : "Email Message Implementation Class",
          "description" : "Specifies the class that sends email notifications, such as those sent for
user registration and forgotten passwords.",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "password" : {
          "title" : "Mail Server Authentication Password",
          "description" : "Specifies the password for the SMTP user name.",
          "propertyOrder" : 500,
          "required" : true,
          "type" : "string",
          "format" : "password",
          "exampleValue" : ""
        },
        "hostname" : {
          "title" : "Mail Server Host Name",
          "description" : "Specifies the fully qualified domain name of the SMTP mail server through
which to send email notifications.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "string",
          "exampleValue" : "smtp.example.com"
        }
      }
    }
  }
}
```

```

    },
    "subject" : {
      "title" : "Email Subject",
      "description" : "Specifies a subject for notification messages. If you do not set this,
OpenAM does not set the subject for notification messages.",
      "propertyOrder" : 900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "message" : {
      "title" : "Email Content",
      "description" : "Specifies content for notification messages. If you do not set this, OpenAM
includes only the confirmation URL in the mail body.",
      "propertyOrder" : 1000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "emailAddressAttribute" : {
      "title" : "Email Attribute Name",
      "description" : "Specifies the profile attribute from which to retrieve the end user's email
address.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sslState" : {
      "title" : "Mail Server Secure Connection",
      "description" : "Specifies whether to connect to the SMTP mail server using SSL.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "type" : "object",
  "title" : "Realm Defaults"
}
}
}

```

1.60. FailureURL

1.60.1. Realm Operations

Resource path: </realm-config/authentication/authenticationtrees/nodes/SetFailureUrlNode>

Resource version: 1.0

1.60.1.1. create

Usage:

```
am> create FailureURL --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "failureUrl" : {
      "title" : "Failure URL",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "failureUrl" ]
}
```

1.60.1.2. delete

Usage:

```
am> delete FailureURL --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.60.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action FailureURL --realm Realm --actionName getAllTypes
```

1.60.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action FailureURL --realm Realm --actionName getCreatableTypes
```

1.60.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action FailureURL --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.60.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action FailureURL --realm Realm --actionName nextdescendents
```

1.60.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query FailureURL --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.60.1.8. read

Usage:

```
am> read FailureURL --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.60.1.9. update

Usage:

```
am> update FailureURL --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "failureUrl" : {
      "title" : "Failure URL",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "failureUrl" ]
}
```

1.61. FederationModule

1.61.1. Realm Operations

Resource path: `/realm-config/authentication/modules/federation`

Resource version: `1.0`

1.61.1.1. create

Usage:

```
am> create FederationModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.61.1.2. delete

Usage:

```
am> delete FederationModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.61.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action FederationModule --realm Realm --actionName getAllTypes
```

1.61.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action FederationModule --realm Realm --actionName getCreatableTypes
```

1.61.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action FederationModule --realm Realm --actionName nextdescendents
```

1.61.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query FederationModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.61.1.7. read

Usage:

```
am> read FederationModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.61.1.8. update

Usage:

```
am> update FederationModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.61.2. Global Operations

Resource path: `/global-config/authentication/modules/federation`

Resource version: `1.0`

1.61.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action FederationModule --global --actionName getAllTypes
```

1.61.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action FederationModule --global --actionName getCreatableTypes
```

1.61.2.3. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action FederationModule --global --actionName nextdescendants
```

1.61.2.4. read

Usage:

```
am> read FederationModule --global
```

1.61.2.5. update

Usage:

```
am> update FederationModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        }
      },
      "type" : "object",
      "title" : "Realm Defaults"
    }
  }
}
```

1.62. ForgottenPassword

1.62.1. Realm Operations

Self Service endpoint for retrieving a forgotten password

Resource path: </selfservice/forgottenPassword>

Resource version: [1.0](#)

1.62.1.1. read

Initialise the forgotten password reclamation process. A set of requirements will be returned that will need to be fulfilled and sent to the submitRequirements action.

Usage:

```
am> read ForgottenPassword --realm Realm
```

1.62.1.2. submitRequirements

Submit some fulfilled requirements. Returns either a completion status, or a token along with some more requirements. If requirements are returned, they should be submitted with the token as a fresh request to this action.

Usage:

```
am> action ForgottenPassword --realm Realm --body body --actionName submitRequirements
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema": "http://json-schema.org/draft-04/schema#",
  "description": "The structure of a request to the submitRequirements action.",
  "type": "object",
  "title": "Submit requirements structure",
  "properties": {
    "token": {
      "type": "string",
      "title": "Token",
      "description": "The token returned from the previous submitRequirements request."
    },
    "input": {
      "type": "object",
      "title": "Input",
      "description": "The input as collected from the user that has forgotten their password. This object must conform to the JSON Schema of the requirements property from the last response.",
      "patternProperties": {
        ".*": {
          "type": "any",
          "title": "Input Property",
          "description": "Valid content according to the received JSON Schema."
        }
      }
    }
  },
  "required": [ "input" ]
}
```

1.63. ForgottenUsername

1.63.1. Realm Operations

Self Service endpoint for retrieving a forgotten username

Resource path: `/selfservice/forgottenUsername`

Resource version: `1.0`

1.63.1.1. read

Initialise the forgotten username reclamation process. A set of requirements will be returned that will need to be fulfilled and sent to the `submitRequirements` action.

Usage:

```
am> read ForgottenUsername --realm Realm
```

1.63.1.2. submitRequirements

Submit some fulfilled requirements. Returns either a completion status, or a token along with some more requirements. If requirements are returned, they should be submitted with the token as a fresh request to this action.

Usage:

```
am> action ForgottenUsername --realm Realm --body body --actionName submitRequirements
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "The structure of a request to the submitRequirements action.",
  "type" : "object",
  "title" : "Submit requirements structure",
  "properties" : {
    "token" : {
      "type" : "string",
      "title" : "Token",
      "description" : "The token returned from the previous submitRequirements request."
    },
    "input" : {
      "type" : "object",
      "title" : "Input",
      "description" : "The input as collected from the user that has forgotten their username. This
object must conform to the JSON Schema of the requirements property from the last response.",
      "patternProperties" : {
        ".*" : {
          "type" : "any",
          "title" : "Input Property",
          "description" : "Valid content according to the received JSON Schema."
        }
      }
    }
  }
},
"required" : [ "input" ]
}
```

1.64. GeneralProperties

1.64.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/{serverName}/properties/general`

Resource version: `1.0`

1.64.1.1. read

Usage:

```
am> read GeneralProperties --global --serverName serverName
```

Parameters:

`--serverName`

An object of property key-value pairs

1.64.1.2. update

Usage:

```
am> update GeneralProperties --global --serverName serverName --body body
```

Parameters:

--serverName

An object of property key-value pairs

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.header.site" : {
      "title" : "Site",
      "type" : "object",
      "propertyOrder" : 0,
      "properties" : {
        "singleChoiceSite" : {
          "enum" : null,
          "options" : {
            "enum_titles" : null
          },
          "type" : "string",
          "title" : "Parent Site",
          "propertyOrder" : 0,
          "required" : false,
          "description" : "Parent Site"
        }
      }
    },
    "amconfig.header.installdir" : {
      "title" : "System",
      "type" : "object",
      "propertyOrder" : 1,
      "properties" : {
        "com.iplanet.services.configpath" : {
          "title" : "Base installation directory",
          "type" : "object",
          "propertyOrder" : 0,
          "description" : "Base directory where product's data resides. (property name: com.iplanet.services.configpath)",
          "properties" : {
            "value" : {
              "type" : "string",
              "required" : false
            },
            "inherited" : {
              "type" : "boolean",
              "required" : true
            }
          }
        }
      }
    }
  }
}
```

```

    },
    "com.iplanet.am.locale" : {
      "title" : "Default Locale",
      "type" : "object",
      "propertyOrder" : 1,
      "description" : "Default locale for the product. (property name: com.iplanet.am.locale)",
      "properties" : {
        "value" : {
          "type" : "string",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    },
    "com.sun.identity.client.notification.url" : {
      "title" : "Notification URL",
      "type" : "object",
      "propertyOrder" : 2,
      "description" : "The location of notification service end point. It is usually the product's
deployment URI/notificationservice. (property name: com.sun.identity.client.notification.url)",
      "properties" : {
        "value" : {
          "type" : "string",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    },
    "com.iplanet.am.util.xml.validating" : {
      "title" : "XML Validation",
      "type" : "object",
      "propertyOrder" : 3,
      "description" : "Specifies if validation is required when parsing XML documents. (property
name: com.iplanet.am.util.xml.validating)",
      "properties" : {
        "value" : {
          "enum" : [ "on", "off" ],
          "options" : {
            "enum_titles" : [ "On", "Off" ]
          },
          "type" : "string",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
},
"amconfig.header.debug" : {
  "title" : "Debugging",

```

```

"type" : "object",
"propertyOrder" : 2,
"properties" : {
  "com.iplanet.services.debug.level" : {
    "title" : "Debug Level",
    "type" : "object",
    "propertyOrder" : 0,
    "description" : "Debug level for all components in the product. (property name:
com.iplanet.services.debug.level)",
    "properties" : {
      "value" : {
        "enum" : [ "off", "error", "warning", "message" ],
        "options" : {
          "enum_titles" : [ "Off", "Error", "Warning", "Message" ]
        },
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "com.sun.services.debug.mergeall" : {
    "title" : "Merge Debug Files",
    "type" : "object",
    "propertyOrder" : 1,
    "description" : "On : Directs all debug data to a single file (debug.out); Off : creates
separate per-component debug files (property name : com.sun.services.debug.mergeall)",
    "properties" : {
      "value" : {
        "enum" : [ "on", "off" ],
        "options" : {
          "enum_titles" : [ "On", "Off" ]
        },
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "com.iplanet.services.debug.directory" : {
    "title" : "Debug Directory",
    "type" : "object",
    "propertyOrder" : 2,
    "description" : "Directory where debug files reside. (property name:
com.iplanet.services.debug.directory)",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
}

```

```
    }
  }
}
},
"amconfig.header.mailserver" : {
  "title" : "Mail Server",
  "type" : "object",
  "propertyOrder" : 3,
  "properties" : {
    "com.ipplanet.am.smtphost" : {
      "title" : "Mail Server Host Name",
      "type" : "object",
      "propertyOrder" : 0,
      "description" : "(property name: com.ipplanet.am.smtphost)",
      "properties" : {
        "value" : {
          "type" : "string",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  },
  "com.ipplanet.am.smtpport" : {
    "title" : "Mail Server Port Number",
    "type" : "object",
    "propertyOrder" : 1,
    "description" : "(property name: com.ipplanet.am.smtpport)",
    "properties" : {
      "value" : {
        "type" : "integer",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
}
}
}
}
```

1.65. GenericLDAPv3

1.65.1. Realm Operations

Resource path: </realm-config/services/id-repositories/LDAPv3>

Resource version: 1.0

1.65.1.1. create

Usage:

```
am> create GenericLDAPv3 --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "cachecontrol" : {
      "type" : "object",
      "title" : "Cache Control",
      "propertyOrder" : 9,
      "properties" : {
        "sun-idrepo-ldapv3-dncache-enabled" : {
          "title" : "DN Cache",
          "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
          "propertyOrder" : 5900,
          "required" : false,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-dncache-size" : {
          "title" : "DN Cache Size",
          "description" : "In DN items, only used when DN Cache is enabled.",
          "propertyOrder" : 6000,
          "required" : false,
          "type" : "integer",
          "exampleValue" : ""
        }
      }
    },
    "ldapsettings" : {
      "type" : "object",
      "title" : "Server Settings",
      "propertyOrder" : 0,
      "properties" : {
        "sun-idrepo-ldapv3-config-max-result" : {
          "title" : "Maximum Results Returned from Search",
          "description" : "",

```

```

    "propertyOrder" : 1500,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-organization_name" : {
    "title" : "LDAP Organization DN",
    "description" : "",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-ldap-server" : {
    "title" : "LDAP Server",
    "description" : "Format: LDAP server host name:port | server_ID | site_ID",
    "propertyOrder" : 600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-behera-support-enabled" : {
    "title" : "Behera Support Enabled",
    "description" : "When enabled, Behera draft control will be used in the outgoing requests for operations that may modify password value. This will allow OpenAM to display password policy related error messages when password policies are not met.",
    "propertyOrder" : 6100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-heartbeat-timeunit" : {
    "title" : "LDAP Connection Heartbeat Time Unit",
    "description" : "Defines the time unit corresponding to the Heartbeat Interval setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then it may take up to the interval period before the problem is detected. Use along with the Heartbeat Interval parameter to define the exact interval.",
    "propertyOrder" : 1400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-heartbeat-interval" : {
    "title" : "LDAP Connection Heartbeat Interval",
    "description" : "Specifies how often should OpenAM send a heartbeat request to the directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then it may take up to the interval period before the problem is detected. Use along with the Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in disabling heartbeat requests.",
    "propertyOrder" : 1300,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
}

```

```

"sun-idrepo-ldapv3-config-connection-mode" : {
  "title" : "LDAP Connection Mode",
  "description" : "Defines which protocol/operation is used to establish the connection to
the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
  "propertyOrder" : 1000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-search-scope" : {
  "title" : "LDAPv3 Plug-in Search Scope",
  "description" : "",
  "propertyOrder" : 2000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-authpw" : {
  "title" : "LDAP Bind Password",
  "description" : "",
  "propertyOrder" : 800,
  "required" : false,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-time-limit" : {
  "title" : "Search Timeout",
  "description" : "In seconds.",
  "propertyOrder" : 1600,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-connection_pool_max_size" : {
  "title" : "LDAP Connection Pool Maximum Size",
  "description" : "",
  "propertyOrder" : 1200,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-authid" : {
  "title" : "LDAP Bind DN",
  "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
  "propertyOrder" : 700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"userconfig" : {
  "type" : "object",
  "title" : "User Configuration",

```

```
"propertyOrder" : 3,
"properties" : {
  "sun-idrepo-ldapv3-config-user-attributes" : {
    "title" : "LDAP User Attributes",
    "description" : "",
    "propertyOrder" : 2400,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-isactive" : {
    "title" : "Attribute Name of User Status",
    "description" : "",
    "propertyOrder" : 2600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-inactive" : {
    "title" : "User Status Inactive Value",
    "description" : "",
    "propertyOrder" : 2800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-users-search-filter" : {
    "title" : "LDAP Users Search Filter",
    "description" : "",
    "propertyOrder" : 2200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-active" : {
    "title" : "User Status Active Value",
    "description" : "",
    "propertyOrder" : 2700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-user-objectclass" : {
    "title" : "LDAP User Object Class",
    "description" : "",
    "propertyOrder" : 2300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-users-search-attribute" : {
    "title" : "LDAP Users Search Attribute",
    "description" : "",
```



```

        "propertyOrder" : 2100,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-people-container-value" : {
        "title" : "LDAP People Container Value",
        "description" : "",
        "propertyOrder" : 5100,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-people-container-name" : {
        "title" : "LDAP People Container Naming Attribute",
        "description" : "",
        "propertyOrder" : 5000,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
        "title" : "Create User Attribute Mapping",
        "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
        "propertyOrder" : 2500,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"pluginconfig" : {
    "type" : "object",
    "title" : "Plug-in Configuration",
    "propertyOrder" : 2,
    "properties" : {
        "sunIdRepoAttributeMapping" : {
            "title" : "Attribute Name Mapping",
            "description" : "",
            "propertyOrder" : 1800,
            "required" : false,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "sunIdRepoClass" : {
            "title" : "LDAPv3 Repository Plug-in Class Name",
            "description" : "",
            "propertyOrder" : 1700,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "sunIdRepoSupportedOperations" : {

```

```

    "title" : "LDAPv3 Plug-in Supported Types and Operations",
    "description" : "",
    "propertyOrder" : 1900,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
},
"groupconfig" : {
  "type" : "object",
  "title" : "Group Configuration",
  "propertyOrder" : 5,
  "properties" : {
    "sun-idrepo-ldapv3-config-dftgroupmember" : {
      "title" : "Default Group Member's User DN",
      "description" : "User automatically added when group is created.",
      "propertyOrder" : 3800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-attributes" : {
      "title" : "LDAP Groups Attributes",
      "description" : "",
      "propertyOrder" : 3400,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-memberurl" : {
      "title" : "Attribute Name of Group Member URL",
      "description" : "",
      "propertyOrder" : 3700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-groups-search-attribute" : {
      "title" : "LDAP Groups Search Attribute",
      "description" : "",
      "propertyOrder" : 2900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-groups-search-filter" : {
      "title" : "LDAP Groups Search Filter",
      "description" : "",
      "propertyOrder" : 3000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}

```

```
},
"sun-idrepo-ldapv3-config-group-container-value" : {
  "title" : "LDAP Groups Container Value",
  "description" : "",
  "propertyOrder" : 3200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-container-name" : {
  "title" : "LDAP Groups Container Naming Attribute",
  "description" : "",
  "propertyOrder" : 3100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-uniquemember" : {
  "title" : "Attribute Name of Unique Member",
  "description" : "",
  "propertyOrder" : 3600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-objectclass" : {
  "title" : "LDAP Groups Object Class",
  "description" : "",
  "propertyOrder" : 3300,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-memberof" : {
  "title" : "Attribute Name for Group Membership",
  "description" : "",
  "propertyOrder" : 3500,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"persistentsearch" : {
  "type" : "object",
  "title" : "Persistent Search Controls",
  "propertyOrder" : 7,
  "properties" : {
    "sun-idrepo-ldapv3-config-psearch-filter" : {
      "title" : "Persistent Search Filter",
      "description" : "",
      "propertyOrder" : 5600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
```

```

"sun-idrepo-ldapv3-config-psearchbase" : {
  "title" : "Persistent Search Base DN",
  "description" : "",
  "propertyOrder" : 5500,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-psearch-scope" : {
  "title" : "Persistent Search Scope",
  "description" : "",
  "propertyOrder" : 5700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"errorhandling" : {
  "type" : "object",
  "title" : "Error Handling Configuration",
  "propertyOrder" : 8,
  "properties" : {
    "com.iplanet.am.ldap.connection.delay.between.retries" : {
      "title" : "The Delay Time Between Retries",
      "description" : "In milliseconds.",
      "propertyOrder" : 5800,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
},
"authentication" : {
  "type" : "object",
  "title" : "Authentication Configuration",
  "propertyOrder" : 4,
  "properties" : {
    "sun-idrepo-ldapv3-config-auth-naming-attr" : {
      "title" : "Authentication Naming Attribute",
      "description" : "",
      "propertyOrder" : 5200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
}
}

```

1.65.1.2. delete

Usage:

```
am> delete GenericLDAPv3 --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.65.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action GenericLDAPv3 --realm Realm --actionName getAllTypes
```

1.65.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action GenericLDAPv3 --realm Realm --actionName getCreatableTypes
```

1.65.1.5. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action GenericLDAPv3 --realm Realm --actionName nextdescendants
```

1.65.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query GenericLDAPv3 --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.65.1.7. read

Usage:

```
am> read GenericLDAPv3 --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.65.1.8. update

Usage:

```
am> update GenericLDAPv3 --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "cachecontrol" : {
      "type" : "object",
      "title" : "Cache Control",
      "propertyOrder" : 9,
      "properties" : {
        "sun-idrepo-ldapv3-dncache-enabled" : {
          "title" : "DN Cache",
          "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
          "propertyOrder" : 5900,
          "required" : false,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-dncache-size" : {
          "title" : "DN Cache Size",
          "description" : "In DN items, only used when DN Cache is enabled.",
          "propertyOrder" : 6000,
          "required" : false,
          "type" : "integer",
          "exampleValue" : ""
        }
      }
    },
    "ldapsettings" : {
      "type" : "object",
      "title" : "Server Settings",
      "propertyOrder" : 0,
    }
  }
}
```

```

"properties" : {
  "sun-idrepo-ldapv3-config-max-result" : {
    "title" : "Maximum Results Returned from Search",
    "description" : "",
    "propertyOrder" : 1500,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-organization_name" : {
    "title" : "LDAP Organization DN",
    "description" : "",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-ldap-server" : {
    "title" : "LDAP Server",
    "description" : "Format: LDAP server host name:port | server_ID | site_ID",
    "propertyOrder" : 600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-behera-support-enabled" : {
    "title" : "Behera Support Enabled",
    "description" : "When enabled, Behera draft control will be used in the outgoing requests for operations that may modify password value. This will allow OpenAM to display password policy related error messages when password policies are not met.",
    "propertyOrder" : 6100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-heartbeat-timeunit" : {
    "title" : "LDAP Connection Heartbeat Time Unit",
    "description" : "Defines the time unit corresponding to the Heartbeat Interval setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then it may take up to the interval period before the problem is detected. Use along with the Heartbeat Interval parameter to define the exact interval.",
    "propertyOrder" : 1400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-heartbeat-interval" : {
    "title" : "LDAP Connection Heartbeat Interval",
    "description" : "Specifies how often should OpenAM send a heartbeat request to the directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then it may take up to the interval period before the problem is detected. Use along with the Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in disabling heartbeat requests.",
    "propertyOrder" : 1300,

```

```

    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection-mode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Defines which protocol/operation is used to establish the connection to
the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
    "propertyOrder" : 1000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-search-scope" : {
    "title" : "LDAPv3 Plug-in Search Scope",
    "description" : "",
    "propertyOrder" : 2000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-authpw" : {
    "title" : "LDAP Bind Password",
    "description" : "",
    "propertyOrder" : 800,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-time-limit" : {
    "title" : "Search Timeout",
    "description" : "In seconds.",
    "propertyOrder" : 1600,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
    "title" : "LDAP Connection Pool Maximum Size",
    "description" : "",
    "propertyOrder" : 1200,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-authid" : {
    "title" : "LDAP Bind DN",
    "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
    "propertyOrder" : 700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}

```



```
},
"userconfig" : {
  "type" : "object",
  "title" : "User Configuration",
  "propertyOrder" : 3,
  "properties" : {
    "sun-idrepo-ldapv3-config-user-attributes" : {
      "title" : "LDAP User Attributes",
      "description" : "",
      "propertyOrder" : 2400,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-isactive" : {
      "title" : "Attribute Name of User Status",
      "description" : "",
      "propertyOrder" : 2600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-inactive" : {
      "title" : "User Status Inactive Value",
      "description" : "",
      "propertyOrder" : 2800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-users-search-filter" : {
      "title" : "LDAP Users Search Filter",
      "description" : "",
      "propertyOrder" : 2200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-active" : {
      "title" : "User Status Active Value",
      "description" : "",
      "propertyOrder" : 2700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-user-objectclass" : {
      "title" : "LDAP User Object Class",
      "description" : "",
      "propertyOrder" : 2300,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

```

    },
    "sun-idrepo-ldapv3-config-users-search-attribute" : {
      "title" : "LDAP Users Search Attribute",
      "description" : "",
      "propertyOrder" : 2100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "sun-idrepo-ldapv3-config-people-container-value" : {
      "title" : "LDAP People Container Value",
      "description" : "",
      "propertyOrder" : 5100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "sun-idrepo-ldapv3-config-people-container-name" : {
      "title" : "LDAP People Container Naming Attribute",
      "description" : "",
      "propertyOrder" : 5000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
      "title" : "Create User Attribute Mapping",
      "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
      "propertyOrder" : 2500,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
},
"pluginconfig" : {
  "type" : "object",
  "title" : "Plug-in Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "sunIdRepoAttributeMapping" : {
      "title" : "Attribute Name Mapping",
      "description" : "",
      "propertyOrder" : 1800,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
  },
  "type" : "array",
  "exampleValue" : ""
},
"sunIdRepoClass" : {
  "title" : "LDAPv3 Repository Plug-in Class Name",
  "description" : "",
  "propertyOrder" : 1700,
  "required" : true,

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "sunIdRepoSupportedOperations" : {
    "title" : "LDAPv3 Plug-in Supported Types and Operations",
    "description" : "",
    "propertyOrder" : 1900,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
},
"groupconfig" : {
  "type" : "object",
  "title" : "Group Configuration",
  "propertyOrder" : 5,
  "properties" : {
    "sun-idrepo-ldapv3-config-dftgroupmember" : {
      "title" : "Default Group Member's User DN",
      "description" : "User automatically added when group is created.",
      "propertyOrder" : 3800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-attributes" : {
      "title" : "LDAP Groups Attributes",
      "description" : "",
      "propertyOrder" : 3400,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-memberurl" : {
      "title" : "Attribute Name of Group Member URL",
      "description" : "",
      "propertyOrder" : 3700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-groups-search-attribute" : {
      "title" : "LDAP Groups Search Attribute",
      "description" : "",
      "propertyOrder" : 2900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-groups-search-filter" : {
      "title" : "LDAP Groups Search Filter",
      "description" : "",

```

```

    "propertyOrder" : 3000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-container-value" : {
    "title" : "LDAP Groups Container Value",
    "description" : "",
    "propertyOrder" : 3200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-container-name" : {
    "title" : "LDAP Groups Container Naming Attribute",
    "description" : "",
    "propertyOrder" : 3100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-uniquemember" : {
    "title" : "Attribute Name of Unique Member",
    "description" : "",
    "propertyOrder" : 3600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-objectclass" : {
    "title" : "LDAP Groups Object Class",
    "description" : "",
    "propertyOrder" : 3300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-memberof" : {
    "title" : "Attribute Name for Group Membership",
    "description" : "",
    "propertyOrder" : 3500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"persistentsearch" : {
  "type" : "object",
  "title" : "Persistent Search Controls",
  "propertyOrder" : 7,
  "properties" : {
    "sun-idrepo-ldapv3-config-psearch-filter" : {
      "title" : "Persistent Search Filter",
      "description" : "",
      "propertyOrder" : 5600,

```

```
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-psearchbase" : {
    "title" : "Persistent Search Base DN",
    "description" : "",
    "propertyOrder" : 5500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-psearch-scope" : {
    "title" : "Persistent Search Scope",
    "description" : "",
    "propertyOrder" : 5700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"errorhandling" : {
  "type" : "object",
  "title" : "Error Handling Configuration",
  "propertyOrder" : 8,
  "properties" : {
    "com.iplanet.am.ldap.connection.delay.between.retries" : {
      "title" : "The Delay Time Between Retries",
      "description" : "In milliseconds.",
      "propertyOrder" : 5800,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
},
"authentication" : {
  "type" : "object",
  "title" : "Authentication Configuration",
  "propertyOrder" : 4,
  "properties" : {
    "sun-idrepo-ldapv3-config-auth-naming-attr" : {
      "title" : "Authentication Naming Attribute",
      "description" : "",
      "propertyOrder" : 5200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
```

1.66. GetSessionData

1.66.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/SessionDataNode`

Resource version: `1.0`

1.66.1.1. create

Usage:

```
am> create GetSessionData --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "sessionDataKey" : {
      "title" : "Session Data Key",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    },
    "sharedStateKey" : {
      "title" : "Shared State Key",
      "description" : "",
      "propertyOrder" : 200,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "sharedStateKey", "sessionDataKey" ]
}
```

1.66.1.2. delete

Usage:

```
am> delete GetSessionData --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.66.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action GetSessionData --realm Realm --actionName getAllTypes
```

1.66.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action GetSessionData --realm Realm --actionName getCreatableTypes
```

1.66.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action GetSessionData --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.66.1.6. nextDescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action GetSessionData --realm Realm --actionName nextdescendents
```

1.66.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query GetSessionData --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.66.1.8. read

Usage:

```
am> read GetSessionData --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.66.1.9. update

Usage:

```
am> update GetSessionData --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:


```
{
  "type" : "object",
  "properties" : {
    "sessionDataKey" : {
      "title" : "Session Data Key",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    },
    "sharedStateKey" : {
      "title" : "Shared State Key",
      "description" : "",
      "propertyOrder" : 200,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "sharedStateKey", "sessionDataKey" ]
}
```

1.67. GlobalScripts

1.67.1. Global Operations

Resource path: `/global-config/services/scripting/globalScript`

Resource version: `1.0`

1.67.1.1. create

Usage:

```
am> create GlobalScripts --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "description" : {
      "title" : "Script description",
      "description" : "An optional text string to help identify the script",

```

```

    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "language" : {
    "title" : "Script language",
    "description" : "The language the script is written in - JAVASCRIPT or GROOVY",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "createdBy" : {
    "title" : "Created by",
    "description" : "A string containing the universal identifier DN of the subject that created the
script",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "lastModifiedDate" : {
    "title" : "Last modification date",
    "description" : "A string containing the last modified date and time, in ISO 8601 format. If
the script has not been modified since it was created, this property will have the same value as
creationDate",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "name" : {
    "title" : "Script name",
    "description" : "The name provided for the script",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "lastModifiedBy" : {
    "title" : "Last modifier",
    "description" : "A string containing the universal identifier DN of the subject that most
recently updated the script. If the script has not been modified since it was created, this property
will have the same value as createdBy",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "context" : {
    "title" : "Script type",
    "description" : "The script type. Supported values are: POLICY_CONDITION : Policy Condition
AUTHENTICATION_SERVER_SIDE : Server-side Authentication AUTHENTICATION_CLIENT_SIDE : Client-side
Authentication - Note Client-side scripts must be written in JavaScript OIDC_CLAIMS : OIDC Claims",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }

```

```
    },
    "script" : {
      "title" : "Script",
      "description" : "The source code of the script. The source code is in UTF-8 format and encoded
into Base64",
      "propertyOrder" : null,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "creationDate" : {
      "title" : "Creation date",
      "description" : "An integer containing the creation date and time, in ISO 8601 format",
      "propertyOrder" : null,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.67.1.2. delete

Usage:

```
am> delete GlobalScripts --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.67.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action GlobalScripts --global --actionName getAllTypes
```

1.67.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action GlobalScripts --global --actionName getCreatableTypes
```

1.67.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action GlobalScripts --global --actionName nextdescendents
```

1.67.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query GlobalScripts --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.67.1.7. read

Usage:

```
am> read GlobalScripts --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.67.1.8. update

Usage:

```
am> update GlobalScripts --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "description" : {
      "title" : "Script description",
      "description" : "An optional text string to help identify the script",
      "propertyOrder" : null,
    }
  }
}
```

```

        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "language" : {
        "title" : "Script language",
        "description" : "The language the script is written in - JAVASCRIPT or GROOVY",
        "propertyOrder" : null,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "createdBy" : {
        "title" : "Created by",
        "description" : "A string containing the universal identifier DN of the subject that created the
script",
        "propertyOrder" : null,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "lastModifiedDate" : {
        "title" : "Last modification date",
        "description" : "A string containing the last modified date and time, in ISO 8601 format. If
the script has not been modified since it was created, this property will have the same value as
creationDate",
        "propertyOrder" : null,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "name" : {
        "title" : "Script name",
        "description" : "The name provided for the script",
        "propertyOrder" : null,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "lastModifiedBy" : {
        "title" : "Last modifier",
        "description" : "A string containing the universal identifier DN of the subject that most
recently updated the script. If the script has not been modified since it was created, this property
will have the same value as createdBy",
        "propertyOrder" : null,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "context" : {
        "title" : "Script type",
        "description" : "The script type. Supported values are: POLICY_CONDITION : Policy Condition
AUTHENTICATION_SERVER_SIDE : Server-side Authentication AUTHENTICATION_CLIENT_SIDE : Client-side
Authentication - Note Client-side scripts must be written in JavaScript OIDC_CLAIMS : OIDC Claims",
        "propertyOrder" : null,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    },

```

```
"script" : {
  "title" : "Script",
  "description" : "The source code of the script. The source code is in UTF-8 format and encoded
into Base64",
  "propertyOrder" : null,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"creationDate" : {
  "title" : "Creation date",
  "description" : "An integer containing the creation date and time, in ISO 8601 format",
  "propertyOrder" : null,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
```

1.68. Globalization

1.68.1. Realm Operations

Resource path: `/realm-config/services/globalization`

Resource version: `1.0`

1.68.1.1. create

Usage:

```
am> create Globalization --realm Realm --body body
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonNameFormats" : {
      "title" : "Auto Generated Common Name Format",
      "description" : "Use this list to configure how OpenAM formats names shown in the console banner.<br><br>This setting allows the name of the authenticated user shown in the OpenAM console banner to be customised based on the locale of the user.",
      "propertyOrder" : 300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.68.1.2. delete

Usage:

```
am> delete Globalization --realm Realm
```

1.68.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Globalization --realm Realm --actionName getAllTypes
```

1.68.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Globalization --realm Realm --actionName getCreatableTypes
```

1.68.1.5. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Globalization --realm Realm --actionName nextdescendants
```

1.68.1.6. read

Usage:

```
am> read Globalization --realm Realm
```

1.68.1.7. update

Usage:

```
am> update Globalization --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonNameFormats" : {
      "title" : "Auto Generated Common Name Format",
      "description" : "Use this list to configure how OpenAM formats names shown in the console banner.<br><br>This setting allows the name of the authenticated user shown in the OpenAM console banner to be customised based on the locale of the user.",
      "propertyOrder" : 300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.68.2. Global Operations

Resource path: [/global-config/services/globalization](#)

Resource version: 1.0

1.68.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Globalization --global --actionName getAllTypes
```


1.68.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Globalization --global --actionName getCreatableTypes
```

1.68.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Globalization --global --actionName nextdescendents
```

1.68.2.4. read

Usage:

```
am> read Globalization --global
```

1.68.2.5. update

Usage:

```
am> update Globalization --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "charsetMappings" : {
      "title" : "Charsets Supported by Each Locale",
      "description" : "This table lets you configure the order of supported character sets used for
each supported locale. Change the settings only if the defaults are not appropriate.",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-identity-g11n-settings-charset-alias-mapping" : {
      "title" : "Charset Aliases",
      "description" : "Use this list to map between different character set names used in Java and in
MIME."
    }
  }
}
```

```
"propertyOrder" : 200,  
"required" : true,  
"items" : {  
  "type" : "string"  
},  
"type" : "array",  
"exampleValue" : ""  
},  
"defaults" : {  
  "properties" : {  
    "commonNameFormats" : {  
      "title" : "Auto Generated Common Name Format",  
      "description" : "Use this list to configure how OpenAM formats names shown in the console  
banner.<br><br>This setting allows the name of the authenticated user shown in the OpenAM console  
banner to be customised based on the locale of the user.",  
      "propertyOrder" : 300,  
      "required" : true,  
      "items" : {  
        "type" : "string"  
      },  
      "type" : "array",  
      "exampleValue" : ""  
    }  
  },  
  "type" : "object",  
  "title" : "Realm Defaults"  
}  
}  
}
```

1.69. GraphiteReporter

1.69.1. Global Operations

Resource path: [/global-config/services/monitoring/graphite](#)

Resource version: [1.0](#)

1.69.1.1. create

Usage:

```
am> create GraphiteReporter --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "frequency" : {
      "title" : "Frequency",
      "description" : "The frequency (in seconds) at which metrics should be published.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "port" : {
      "title" : "Port",
      "description" : "The port of the Graphite server to which metrics should be published.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "host" : {
      "title" : "Hostname",
      "description" : "The hostname of the Graphite server to which metrics should be published.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.69.1.2. delete

Usage:

```
am> delete GraphiteReporter --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.69.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action GraphiteReporter --global --actionName getAllTypes
```

1.69.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action GraphiteReporter --global --actionName getCreatableTypes
```

1.69.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action GraphiteReporter --global --actionName nextdescendents
```

1.69.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query GraphiteReporter --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.69.1.7. read

Usage:

```
am> read GraphiteReporter --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.69.1.8. update

Usage:

```
am> update GraphiteReporter --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "frequency" : {
      "title" : "Frequency",
      "description" : "The frequency (in seconds) at which metrics should be published.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "port" : {
      "title" : "Port",
      "description" : "The port of the Graphite server to which metrics should be published.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "host" : {
      "title" : "Hostname",
      "description" : "The hostname of the Graphite server to which metrics should be published.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.70. HOTPGenerator

1.70.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/OneTimePasswordGeneratorNode`

Resource version: `1.0`

1.70.1.1. create

Usage:

```
am> create HOTPGenerator --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "length" : {
      "title" : "One Time Password Length",
      "description" : "The length in characters of the one time password.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "length" ]
}
```

1.70.1.2. delete

Usage:

```
am> delete HOTPGenerator --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.70.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action HOTPGenerator --realm Realm --actionName getAllTypes
```

1.70.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action HOTPGenerator --realm Realm --actionName getCreatableTypes
```

1.70.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action HOTPGenerator --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.70.1.6. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action HOTPGenerator --realm Realm --actionName nextdescendants
```

1.70.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query HOTPGenerator --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.70.1.8. read

Usage:

```
am> read HOTPGenerator --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.70.1.9. update

Usage:

```
am> update HOTPGenerator --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "length" : {
      "title" : "One Time Password Length",
      "description" : "The length in characters of the one time password.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "length" ]
}
```

1.71. HotpModule

1.71.1. Realm Operations

Resource path: `/realm-config/authentication/modules/hotp`

Resource version: `1.0`

1.71.1.1. create

Usage:

```
am> create HotpModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "otpDeliveryMethod" : {
      "title" : "One Time Password Delivery",
      "description" : "The mechanism used to deliver the One Time Password",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpFromAddress" : {
      "title" : "Email From Address",
      "description" : "Emails from the HOTP Authentication module will come from this address.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpHostPort" : {
      "title" : "Mail Server Host Port",
      "description" : "The port of the mail server.<br><br>The default port for SMTP is 25, if using
SSL the default port is 465.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "otpMaxRetry" : {
      "title" : "One Time Password Max Retry",
      "description" : "The number of times entry of the OTP may be attempted. Minimum is 1 maximum is
10 and default is 3.",
      "propertyOrder" : null,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "otpValidityDuration" : {
      "title" : "One Time Password Validity Length",
      "description" : "This One Time Password will remain valid for this period (in minutes)",
      "propertyOrder" : 900,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

```
"mobileCarrierAttribute" : {
  "title" : "Mobile Carrier Attribute Name",
  "description" : "This is the attribute name used for a mobile carrier domain for sending SMS
messages",
  "propertyOrder" : 1300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"smtpUserPassword" : {
  "title" : "Mail Server Authentication Password",
  "description" : "The password to use if the mail server is using SMTP authentication",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"smtpUsername" : {
  "title" : "Mail Server Authentication Username",
  "description" : "The username to use if the mail server is using SMTP authentication",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"smtpHostname" : {
  "title" : "Mail Server Host Name",
  "description" : "The name of the mail server; OpenAM will use SMTP to send the messages.",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"smtpSslEnabled" : {
  "title" : "Mail Server Secure Connection ",
  "description" : "This setting controls whether the authentication module communicates with the
mail server using SSL/TLS",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"userProfileTelephoneAttribute" : {
  "title" : "Mobile Phone Number Attribute Name",
  "description" : "This is the attribute name used for a requested text message",
  "propertyOrder" : 1200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"userProfileEmailAttribute" : {
  "title" : "Email Attribute Name",
  "description" : "This is the attribute name used by the OTP to email the user",
  "propertyOrder" : 1400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
}
```

```
"smsGatewayClass" : {
  "title" : "SMS Gateway Implementation Class",
  "description" : "The HOTP authentication module uses this class to send SMS
messages.<br><br>The SMS gateway class must implement the following interface<br><br>
<code>com.sun.identity.authentication.modules.hotp.SMSGateway</code>",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"otpLength" : {
  "title" : "One Time Password Length ",
  "description" : "The length of the generated One Time Password (in digits)",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"autoSendOTP" : {
  "title" : "Auto Send OTP Code",
  "description" : "Select this checkbox if the OTP should be sent automatically",
  "propertyOrder" : 1500,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
}
}
```

1.71.1.2. delete

Usage:

```
am> delete HotpModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.71.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action HotpModule --realm Realm --actionName getAllTypes
```

1.71.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action HotpModule --realm Realm --actionName getCreatableTypes
```

1.71.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action HotpModule --realm Realm --actionName nextdescendents
```

1.71.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query HotpModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.71.1.7. read

Usage:

```
am> read HotpModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.71.1.8. update

Usage:

```
am> update HotpModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "otpDeliveryMethod" : {
      "title" : "One Time Password Delivery",
      "description" : "The mechanism used to deliver the One Time Password",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpFromAddress" : {
      "title" : "Email From Address",
      "description" : "Emails from the HOTP Authentication module will come from this address.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpHostPort" : {
      "title" : "Mail Server Host Port",
      "description" : "The port of the mail server.<br><br>The default port for SMTP is 25, if using
SSL the default port is 465.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "otpMaxRetry" : {
      "title" : "One Time Password Max Retry",
      "description" : "The number of times entry of the OTP may be attempted. Minimum is 1 maximum is
10 and default is 3.",
      "propertyOrder" : null,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "otpValidityDuration" : {
      "title" : "One Time Password Validity Length",
      "description" : "This One Time Password will remain valid for this period (in minutes)",
      "propertyOrder" : 900,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

```
"mobileCarrierAttribute" : {
  "title" : "Mobile Carrier Attribute Name",
  "description" : "This is the attribute name used for a mobile carrier domain for sending SMS
messages",
  "propertyOrder" : 1300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"smtpUserPassword" : {
  "title" : "Mail Server Authentication Password",
  "description" : "The password to use if the mail server is using SMTP authentication",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"smtpUsername" : {
  "title" : "Mail Server Authentication Username",
  "description" : "The username to use if the mail server is using SMTP authentication",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"smtpHostname" : {
  "title" : "Mail Server Host Name",
  "description" : "The name of the mail server; OpenAM will use SMTP to send the messages.",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"smtpSslEnabled" : {
  "title" : "Mail Server Secure Connection ",
  "description" : "This setting controls whether the authentication module communicates with the
mail server using SSL/TLS",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"userProfileTelephoneAttribute" : {
  "title" : "Mobile Phone Number Attribute Name",
  "description" : "This is the attribute name used for a requested text message",
  "propertyOrder" : 1200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"userProfileEmailAttribute" : {
  "title" : "Email Attribute Name",
  "description" : "This is the attribute name used by the OTP to email the user",
  "propertyOrder" : 1400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
},
```

```
"smsGatewayClass" : {
  "title" : "SMS Gateway Implementation Class",
  "description" : "The HOTP authentication module uses this class to send SMS
messages.<br><br>The SMS gateway class must implement the following interface<br><br>
<code>com.sun.identity.authentication.modules.hotp.SMSGateway</code>",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"otpLength" : {
  "title" : "One Time Password Length ",
  "description" : "The length of the generated One Time Password (in digits)",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"autoSendOTP" : {
  "title" : "Auto Send OTP Code",
  "description" : "Select this checkbox if the OTP should be sent automatically",
  "propertyOrder" : 1500,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
}
}
}
```

1.71.2. Global Operations

Resource path: `/global-config/authentication/modules/hotp`

Resource version: `1.0`

1.71.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action HotpModule --global --actionName getAllTypes
```

1.71.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action HotpModule --global --actionName getCreatableTypes
```

1.71.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action HotpModule --global --actionName nextdescendents
```

1.71.2.4. read

Usage:

```
am> read HotpModule --global
```

1.71.2.5. update

Usage:

```
am> update HotpModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "autoSendOTP" : {
          "title" : "Auto Send OTP Code",
          "description" : "Select this checkbox if the OTP should be sent automatically",
          "propertyOrder" : 1500,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "otpDeliveryMethod" : {
          "title" : "One Time Password Delivery",
          "description" : "The mechanism used to deliver the One Time Password",
          "propertyOrder" : 1100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "smtpUsername" : {
          "title" : "Mail Server Authentication Username",
          "description" : "The username to use if the mail server is using SMTP authentication",
          "propertyOrder" : 500,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    }
  }
}
```



```

    },
    "smsGatewayClass" : {
      "title" : "SMS Gateway Implementation Class",
      "description" : "The HOTP authentication module uses this class to send SMS
messages.<br><br>The SMS gateway class must implement the following interface<br><br/>
<code>com.sun.identity.authentication.modules.hotp.SMSGateway</code>",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "userProfileTelephoneAttribute" : {
      "title" : "Mobile Phone Number Attribute Name",
      "description" : "This is the attribute name used for a requested text message",
      "propertyOrder" : 1200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpUserPassword" : {
      "title" : "Mail Server Authentication Password",
      "description" : "The password to use if the mail server is using SMTP authentication",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "otpLength" : {
      "title" : "One Time Password Length ",
      "description" : "The length of the generated One Time Password (in digits)",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpHostPort" : {
      "title" : "Mail Server Host Port",
      "description" : "The port of the mail server.<br><br>The default port for SMTP is 25, if
using SSL the default port is 465.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "otpMaxRetry" : {
      "title" : "One Time Password Max Retry",
      "description" : "The number of times entry of the OTP may be attempted. Minimum is 1 maximum
is 10 and default is 3.",
      "propertyOrder" : null,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",

```

```

    "propertyOrder" : 100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "smtpSslEnabled" : {
    "title" : "Mail Server Secure Connection ",
    "description" : "This setting controls whether the authentication module communicates with
the mail server using SSL/TLS",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "UserProfileEmailAttribute" : {
    "title" : "Email Attribute Name",
    "description" : "This is the attribute name used by the OTP to email the user",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "otpValidityDuration" : {
    "title" : "One Time Password Validity Length",
    "description" : "This One Time Password will remain valid for this period (in minutes)",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "smtpFromAddress" : {
    "title" : "Email From Address",
    "description" : "Emails from the HOTP Authentication module will come from this address.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "mobileCarrierAttribute" : {
    "title" : "Mobile Carrier Attribute Name",
    "description" : "This is the attribute name used for a mobile carrier domain for sending SMS
messages",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpHostname" : {
    "title" : "Mail Server Host Name",
    "description" : "The name of the mail server; OpenAM will use SMTP to send the messages.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}

```

```
}  
}
```

1.72. HttpBasicModule

1.72.1. Realm Operations

Resource path: `/realm-config/authentication/modules/httpbasic`

Resource version: `1.0`

1.72.1.1. create

Usage:

```
am> create HttpBasicModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "backendModuleName" : {
      "title" : "Backend Module Name",
      "description" : "The name of the module that will be used to perform the authentication<br><br>The HTTP Basic authentication module collect the credentials from the user and will then supply said credentials to the backend authentication module using the shared state. ",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.72.1.2. delete

Usage:

```
am> delete HttpBasicModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.72.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action HttpBasicModule --realm Realm --actionName getAllTypes
```

1.72.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action HttpBasicModule --realm Realm --actionName getCreatableTypes
```

1.72.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action HttpBasicModule --realm Realm --actionName nextdescendents
```

1.72.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query HttpBasicModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.72.1.7. read

Usage:

```
am> read HttpBasicModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.72.1.8. update

Usage:

```
am> update HttpBasicModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "backendModuleName" : {
      "title" : "Backend Module Name",
      "description" : "The name of the module that will be used to perform the authentication<br><br>The HTTP Basic authentication module collect the credentials from the user and will then supply said credentials to the backend authentication module using the shared state. ",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.72.2. Global Operations

Resource path: `/global-config/authentication/modules/httpbasic`

Resource version: `1.0`

1.72.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action HttpBasicModule --global --actionName getAllTypes
```

1.72.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action HttpBasicModule --global --actionName getCreatableTypes
```

1.72.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action HttpBasicModule --global --actionName nextdescendents
```

1.72.2.4. read

Usage:

```
am> read HttpBasicModule --global
```

1.72.2.5. update

Usage:

```
am> update HttpBasicModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "backendModuleName" : {
          "title" : "Backend Module Name",
          "description" : "The name of the module that will be used to perform the authentication<br><br>The HTTP Basic authentication module collect the credentials from the user and will then supply said credentials to the backend authentication module using the shared state. ",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      },
      "type" : "object",
      "title" : "Realm Defaults"
    }
  }
}
```

1.73. IDMProvisioning

1.73.1. Realm Operations

Resource path: `/realm-config/services/idm-integration`

Resource version: `1.0`

1.73.1.1. create

Usage:

```
am> create IDMProvisioning --realm Realm --body body
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "provisioningSigningKeyAlias" : {
      "title" : "Signing Key Alias",
      "description" : "Alias of the signing symmetric key in AM's default keystore. Must be a
duplicate of the symmetric key used by IDM.",
      "propertyOrder" : 2240,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "provisioningEncryptionKeyAlias" : {
      "title" : "Encryption Key Alias",
      "description" : "Alias of the encryption asymmetric key in AM's default keystore. Must be a
duplicate of the asymmetric key used by IDM.",
      "propertyOrder" : 2250,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "idmDeploymentUrl" : {
      "title" : "Deployment URL",
      "description" : "URL of the IDM deployment.",
      "propertyOrder" : 2200,
      "required" : true,
      "type" : "string",
      "exampleValue" : "https://openidm.example.com"
    },
    "provisioningEncryptionMethod" : {
      "title" : "Encryption Method",
      "description" : "JWT encryption method.",

```



```
    "propertyOrder" : 2280,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "enabled" : {
    "title" : "Enabled",
    "description" : "",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "provisioningSigningAlgorithm" : {
    "title" : "Signing Algorithm",
    "description" : "JWT signing algorithm.",
    "propertyOrder" : 2260,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "provisioningEncryptionAlgorithm" : {
    "title" : "Encryption Algorithm",
    "description" : "JWT encryption algorithm.",
    "propertyOrder" : 2270,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
```

1.73.1.2. delete

Usage:

```
am> delete IDMProvisioning --realm Realm
```

1.73.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action IDMProvisioning --realm Realm --actionName getAllTypes
```

1.73.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action IDMProvisioning --realm Realm --actionName getCreatableTypes
```

1.73.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action IDMProvisioning --realm Realm --actionName nextdescendents
```

1.73.1.6. read

Usage:

```
am> read IDMProvisioning --realm Realm
```

1.73.1.7. update

Usage:

```
am> update IDMProvisioning --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "provisioningSigningKeyAlias" : {
      "title" : "Signing Key Alias",
      "description" : "Alias of the signing symmetric key in AM's default keystore. Must be a
duplicate of the symmetric key used by IDM.",
      "propertyOrder" : 2240,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "provisioningEncryptionKeyAlias" : {
      "title" : "Encryption Key Alias",
      "description" : "Alias of the encryption asymmetric key in AM's default keystore. Must be a
duplicate of the asymmetric key used by IDM.",
      "propertyOrder" : 2250,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "idmDeploymentUrl" : {
      "title" : "Deployment URL",
      "description" : "URL of the IDM deployment.",
      "propertyOrder" : 2200,
      "required" : true,
      "type" : "string",
      "exampleValue" : "https://openidm.example.com"
    }
  }
}
```

```
    },
    "provisioningEncryptionMethod" : {
      "title" : "Encryption Method",
      "description" : "JWT encryption method.",
      "propertyOrder" : 2280,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "enabled" : {
      "title" : "Enabled",
      "description" : "",
      "propertyOrder" : 2100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    },
    "provisioningSigningAlgorithm" : {
      "title" : "Signing Algorithm",
      "description" : "JWT signing algorithm.",
      "propertyOrder" : 2260,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "provisioningEncryptionAlgorithm" : {
      "title" : "Encryption Algorithm",
      "description" : "JWT encryption algorithm.",
      "propertyOrder" : 2270,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.73.2. Global Operations

Resource path: `/global-config/services/idm-integration`

Resource version: `1.0`

1.73.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action IDMProvisioning --global --actionName getAllTypes
```

1.73.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action IDMProvisioning --global --actionName getCreatableTypes
```

1.73.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action IDMProvisioning --global --actionName nextdescendents
```

1.73.2.4. read

Usage:

```
am> read IDMProvisioning --global
```

1.73.2.5. update

Usage:

```
am> update IDMProvisioning --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "",
          "propertyOrder" : 2100,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "provisioningSigningKeyAlias" : {
          "title" : "Signing Key Alias",
          "description" : "Alias of the signing symmetric key in AM's default keystore. Must be a duplicate of the symmetric key used by IDM.",
          "propertyOrder" : 2240,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    }
  }
}
```

```

"provisioningEncryptionAlgorithm" : {
  "title" : "Encryption Algorithm",
  "description" : "JWT encryption algorithm.",
  "propertyOrder" : 2270,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"provisioningSigningAlgorithm" : {
  "title" : "Signing Algorithm",
  "description" : "JWT signing algorithm.",
  "propertyOrder" : 2260,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"provisioningEncryptionMethod" : {
  "title" : "Encryption Method",
  "description" : "JWT encryption method.",
  "propertyOrder" : 2280,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"provisioningEncryptionKeyAlias" : {
  "title" : "Encryption Key Alias",
  "description" : "Alias of the encryption asymmetric key in AM's default keystore. Must be a
duplicate of the asymmetric key used by IDM.",
  "propertyOrder" : 2250,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"idmDeploymentUrl" : {
  "title" : "Deployment URL",
  "description" : "URL of the IDM deployment.",
  "propertyOrder" : 2200,
  "required" : true,
  "type" : "string",
  "exampleValue" : "https://openidm.example.com"
}
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}

```

1.74. IdRepository

1.74.1. Realm Operations

Resource path: </realm-config/services/id-repositories>

Resource version: 1.0

1.74.1.1. create

Usage:

```
am> create IdRepository --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "sunIdRepoAttributeCombiner" : {
      "title" : "Attribute Combiner plug-in",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sunIdRepoAttributeValidator" : {
      "title" : "Attribute Validator Plug-in",
      "description" : "",
      "propertyOrder" : 300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.74.1.2. delete

Usage:

```
am> delete IdRepository --realm Realm
```

1.74.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action IdRepository --realm Realm --actionName getAllTypes
```

1.74.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action IdRepository --realm Realm --actionName getCreatableTypes
```

1.74.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action IdRepository --realm Realm --actionName nextdescendents
```

1.74.1.6. read

Usage:

```
am> read IdRepository --realm Realm
```

1.74.1.7. update

Usage:

```
am> update IdRepository --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "sunIdRepoAttributeCombiner" : {
      "title" : "Attribute Combiner plug-in",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sunIdRepoAttributeValidator" : {
      "title" : "Attribute Validator Plug-in",
      "description" : "",
      "propertyOrder" : 300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.74.2. Global Operations

Resource path: `/global-config/services/id-repositories`

Resource version: `1.0`

1.74.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action IdRepository --global --actionName getAllTypes
```

1.74.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action IdRepository --global --actionName getCreatableTypes
```

1.74.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action IdRepository --global --actionName nextdescendents
```

1.74.2.4. read

Usage:

```
am> read IdRepository --global
```

1.74.2.5. update

Usage:

```
am> update IdRepository --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "sunIdRepoAttributeCombiner" : {
          "title" : "Attribute Combiner plug-in",
          "description" : "",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "sunIdRepoAttributeValidator" : {
          "title" : "Attribute Validator Plug-in",
          "description" : "",
          "propertyOrder" : 300,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      }
    },
    "type" : "object",
    "title" : "Realm Defaults"
  }
}
```

1.75. IdRepositoryUser

1.75.1. Global Operations

Resource path: `/global-config/services/id-repositories/user`

Resource version: `1.0`

1.75.1.1. create

Usage:

```
am> create IdRepositoryUser --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "iplanet-am-user-success-url" : {
      "title" : "Success URL",
      "description" : "URL or ClientType|URL if client specific. URL without http(s) protocol will be
appended to the current URI.",
      "propertyOrder" : 10100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "userPassword" : {
      "title" : "Password",
      "description" : "",
      "propertyOrder" : 9400,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "iplanet-am-user-alias-list" : {
      "title" : "User Alias List",
      "description" : "",
      "propertyOrder" : 10000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```
"postalAddress" : {
  "title" : "Home Address",
  "description" : "",
  "propertyOrder" : 9800,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sunIdentityMSISDNNumber" : {
  "title" : "MSISDN Number",
  "description" : "",
  "propertyOrder" : 10300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"inetUserStatus" : {
  "title" : "User Status",
  "description" : "",
  "propertyOrder" : 9900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"roles" : {
  "title" : "Roles",
  "description" : "",
  "propertyOrder" : 10400,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"mail" : {
  "title" : "Email Address",
  "description" : "",
  "propertyOrder" : 9500,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"cn" : {
  "title" : "Full Name",
  "description" : "",
  "propertyOrder" : 9200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sn" : {
  "title" : "Last Name",
  "description" : "",
  "propertyOrder" : 9100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
},
```

```
"iplanet-am-user-failure-url" : {
  "title" : "Failure URL",
  "description" : "URL or ClientType|URL if client specific. URL without http(s) protocol will be
  appended to the current URI.",
  "propertyOrder" : 10200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"telephoneNumber" : {
  "title" : "Telephone Number",
  "description" : "",
  "propertyOrder" : 9700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"employeeNumber" : {
  "title" : "Employee Number",
  "description" : "",
  "propertyOrder" : 9600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"givenName" : {
  "title" : "First Name",
  "description" : "",
  "propertyOrder" : 9000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"dn" : {
  "title" : "DN",
  "description" : "",
  "propertyOrder" : 9300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
```

1.75.1.2. delete

Usage:

```
am> delete IdRepositoryUser --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.75.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action IdRepositoryUser --global --actionName getAllTypes
```

1.75.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action IdRepositoryUser --global --actionName getCreatableTypes
```

1.75.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action IdRepositoryUser --global --actionName nextdescendents
```

1.75.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query IdRepositoryUser --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.75.1.7. read

Usage:

```
am> read IdRepositoryUser --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.75.1.8. update

Usage:

```
am> update IdRepositoryUser --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "iplanet-am-user-success-url" : {
      "title" : "Success URL",
      "description" : "URL or ClientType|URL if client specific. URL without http(s) protocol will be
appended to the current URI.",
      "propertyOrder" : 10100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "userPassword" : {
      "title" : "Password",
      "description" : "",
      "propertyOrder" : 9400,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "iplanet-am-user-alias-list" : {
      "title" : "User Alias List",
      "description" : "",
      "propertyOrder" : 10000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "postalAddress" : {
      "title" : "Home Address",
      "description" : "",
      "propertyOrder" : 9800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sunIdentityMSISDNNumber" : {
      "title" : "MSISDN Number",
      "description" : "",
      "propertyOrder" : 10300,
      "required" : false,

```

```
    "type" : "string",
    "exampleValue" : ""
  },
  "inetUserStatus" : {
    "title" : "User Status",
    "description" : "",
    "propertyOrder" : 9900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "roles" : {
    "title" : "Roles",
    "description" : "",
    "propertyOrder" : 10400,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "mail" : {
    "title" : "Email Address",
    "description" : "",
    "propertyOrder" : 9500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "cn" : {
    "title" : "Full Name",
    "description" : "",
    "propertyOrder" : 9200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sn" : {
    "title" : "Last Name",
    "description" : "",
    "propertyOrder" : 9100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "iplanet-am-user-failure-url" : {
    "title" : "Failure URL",
    "description" : "URL or ClientType|URL if client specific. URL without http(s) protocol will be
appended to the current URI.",
    "propertyOrder" : 10200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "telephoneNumber" : {
    "title" : "Telephone Number",
    "description" : "",
    "propertyOrder" : 9700,
```

```
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "employeeNumber" : {
    "title" : "Employee Number",
    "description" : "",
    "propertyOrder" : 9600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "givenName" : {
    "title" : "First Name",
    "description" : "",
    "propertyOrder" : 9000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "dn" : {
    "title" : "DN",
    "description" : "",
    "propertyOrder" : 9300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.76. IdffEntity

1.76.1. Realm Operations

Resource path: `/realm-config/federation/entityproviders/idff`

Resource version: `1.0`

1.76.1.1. create

Usage:

```
am> create IdffEntity --realm Realm --id id --body body
```

Parameters:

`--id`

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "entityConfig" : {
      "title" : "Entity Configuration",
      "description" : "",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "metadata" : {
      "title" : "Metadata",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.76.1.2. delete

Usage:

```
am> delete IdffEntity --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.76.1.3. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query IdffEntity --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.76.1.4. read

Usage:

```
am> read IdffEntity --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.76.1.5. update

Usage:

```
am> update IdffEntity --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "entityConfig" : {
      "title" : "Entity Configuration",
      "description" : "",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "metadata" : {
      "title" : "Metadata",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.77. InnerTreeEvaluator

1.77.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/InnerTreeEvaluatorNode`

Resource version: `1.0`

1.77.1.1. create

Usage:

```
am> create InnerTreeEvaluator --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "tree" : {
      "title" : "Tree Name",
      "description" : "The name of the tree that will be evaluated.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "tree" ]
}
```

1.77.1.2. delete

Usage:

```
am> delete InnerTreeEvaluator --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.77.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action InnerTreeEvaluator --realm Realm --actionName getAllTypes
```

1.77.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action InnerTreeEvaluator --realm Realm --actionName getCreatableTypes
```

1.77.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action InnerTreeEvaluator --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.77.1.6. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action InnerTreeEvaluator --realm Realm --actionName nextdescendants
```

1.77.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query InnerTreeEvaluator --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.77.1.8. read

Usage:

```
am> read InnerTreeEvaluator --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.77.1.9. update

Usage:

```
am> update InnerTreeEvaluator --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "tree" : {
      "title" : "Tree Name",
      "description" : "The name of the tree that will be evaluated.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "tree" ]
}
```

1.78. J2EEAgentGroups

1.78.1. Realm Operations

Agent Groups handler that is responsible for managing agent groups

Resource path: `/realm-config/agents/groups/J2EEAgent`

Resource version: `1.0`

1.78.1.1. create

Usage:

```
am> create J2EEAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "applicationJ2EEAgentConfig" : {
      "type" : "object",
      "title" : "Application",
      "propertyOrder" : 1,
      "properties" : {
        "applicationLogoutHandlers" : {
          "title" : "Application Logout Handler",
          "description" : "An application-specific Map that identifies a handler to be used for logout processing. (property name: com.sun.identity.agents.config.logout.application.handler) <br>Valid key: the web application name. <br>Valid value: the application logout handler class name. <br>For this property, a global value can be set to apply to all the applications that don't have their own specific logout handler. <br>Hot-swap: Yes <br> Examples: <br>To set a global application logout handler: leave Map Key field empty, and enter the global application logout handler class name GlobalApplicationLogoutHandler in Corresponding Map Value field. <br>To set the logout handler for application BankApp: enter BankApp in Map Key field, and enter the application logout handler class name BankAppLogoutHandler in Corresponding Map Value field.",
          "propertyOrder" : 5900,
          "required" : false,
          "patternProperties" : {
            ".*" : {
              "type" : "string"
            }
          }
        },
        "type" : "object",
        "exampleValue" : ""
      }
    }
  }
}
```

```

    },
    "responseAttributeMap" : {
      "title" : "Response Attribute Mapping",
      "description" : "Maps the policy response attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.response.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of response attribute uid under name CUSTOM-USER-NAME: enter uid in Map Key field,
and enter CUSTOM-USER-NAME in Corresponding Map Value field.",
      "propertyOrder" : 9200,
      "required" : false,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "sessionAttributeFetchMode" : {
    "title" : "Session Attribute Fetch Mode",
    "description" : "The mode of fetching session attributes. (property name:
com.sun.identity.agents.config.session.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 8900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "notEnforcedUrisCacheEnabled" : {
    "title" : "Not Enforced URIs Cache Enabled",
    "description" : "Enables the caching of the Not Enforced URIs list evaluation results.
(property name: com.sun.identity.agents.config.notenforced.uri.cache.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 7700,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "responseAttributeFetchMode" : {
    "title" : "Response Attribute Fetch Mode",
    "description" : "The mode of fetching policy response attributes. (property name:
com.sun.identity.agents.config.response.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 9100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "notEnforcedIpsCacheEnabled" : {
    "title" : "Not Enforced IP Cache Flag",
    "description" : "Enable caching of not-enforced IP list evaluation results. (property name:
com.sun.identity.agents.config.notenforced.ip.cache.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 8100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "profileAttributeFetchMode" : {
    "title" : "Profile Attribute Fetch Mode",
    "description" : "The mode of fetching profile attributes. (property name:
com.sun.identity.agents.config.profile.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 8700,

```

```

    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "cookieAttributeMultiValueSeparator" : {
    "title" : "Cookie Separator Character",
    "description" : "Character that will be used to separate multiple
values of the same attribute when it is being set as a cookie. (property name:
com.sun.identity.agents.config.attribute.cookie.separator) <br>Hot-swap: Yes",
    "propertyOrder" : 8300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "logoutEntryUri" : {
    "title" : "Logout Entry URI",
    "description" : "An application-specific Map that identifies a URI to be used as an entry
point after successful logout and subsequent successful authentication if applicable. (property name:
com.sun.identity.agents.config.logout.entry.uri) <br>Valid key: the web application name. <br>Valid
value: the logout entry URI. <br>For this property, a global value can be set to apply to all the
applications that don't have their own specific logout entry URI. <br>Hot-swap: Yes <br> Examples:
<br>To set a global application logout entry URI: leave Map Key field empty, and enter the global
application logout entry URI /welcome.html in Corresponding Map Value field. <br> To set the logout
entry URI for application BankApp: enter BankApp in Map Key field, and enter the logout entry URI /
BankApp/welcome.html in Corresponding Map Value field.",
    "propertyOrder" : 6300,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "applicationLogoutUris" : {
    "title" : "Application Logout URI",
    "description" : "An application-specific Map that identifies a request URI which indicates
a logout event. (property name: com.sun.identity.agents.config.logout.uri) <br>Valid key: the web
application name. <br>Valid value: the application logout URI. <br>For this property, a global value
can be set to apply to all the applications that don't have their own specific logout URI. <br>Hot-
swap: Yes <br> Examples: <br>To set a global application logout URI: leave Map Key field empty, and
enter the global application logout URI /logout.jsp in Corresponding Map Value field. <br> To set the
logout URI for application BankApp: enter BankApp in Map Key field, and enter the application logout
URI /BankApp/logout.jsp in Corresponding Map Value field.",
    "propertyOrder" : 6000,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "useInternalLogin" : {
    "title" : "Use Internal Login",

```



```

        "description" : "Set to false if want to customize Login Content File instead of default
        internal content provided. (property name: com.sun.identity.agents.config.login.use.internal)
        <br>Hot-swap: Yes",
        "propertyOrder" : 3000,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "notEnforcedUrisCacheSize" : {
        "title" : "Not Enforced URIs Cache Size",
        "description" : "Size of the cache to be used if caching of not enforced URI list evaluation
        results is enabled. (property name: com.sun.identity.agents.config.notenforced.uri.cache.size)
        <br>Hot-swap: Yes",
        "propertyOrder" : 7800,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "loginFormUri" : {
        "title" : "Login Form URI",
        "description" : "List of absolute URIs corresponding to an application's web.xml form-
        login-page element. (property name: com.sun.identity.agents.config.login.form) <br>Hot-swap: Yes <br>
        Example: <br> /BankApp/jsp/login.jsp",
        "propertyOrder" : 2800,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "continuousSecurityHeaders" : {
        "title" : "Continuous Security Headers",
        "description" : "The name of the headers in the user's original request, that will be sent
        as part of the payload during policy evaluation, which can then be accessed via the 'environment'
        variable in a policy script. The 'key' is the name of the header to be sent, and the 'value' is the
        name which it will appear as in the policy evaluation script.It is possible to map multiple headers
        to the same name (they will simply appear as an array in the evaluation script). If the header
        doesn't exist, then the empty string will be sent.",
        "propertyOrder" : 3211,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "notEnforcedIpsCacheSize" : {
        "title" : "Not Enforced IP Cache Size",
        "description" : "Size of the cache to be used if Not Enforced IP Cache Flag is enabled.
        (property name: com.sun.identity.agents.config.notenforced.ip.cache.size) <br>Hot-swap: Yes",
        "propertyOrder" : 8200,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "loginContentFile" : {

```

```

    "title" : "Login Content File Name",
    "description" : "Complete path and name of custom login content file. (property name:
com.sun.identity.agents.config.login.content.file) <br>Hot-swap: Yes",
    "propertyOrder" : 3100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "logoutIntrospection" : {
    "title" : "Logout Introspect Enabled",
    "description" : "Allows the Agent to search HTTP request body to locate logout parameter.
(property name: com.sun.identity.agents.config.logout.introspect.enabled) <br>Hot-swap: Yes",
    "propertyOrder" : 6200,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "resourceAccessDeniedUri" : {
    "title" : "Resource Access Denied URI",
    "description" : "An application-specific Map that identifies a URI of the customized access
denied page. (property name: com.sun.identity.agents.config.access.denied.uri) <br>Valid key: the
web application name. <br>Valid value: the customized application access denied page URI. <br>For
this property, a global value can be set to apply to all the applications that don't have their own
specific access denied page. <br>Hot-swap: Yes <br> Examples: <br>To set a global access denied page:
leave Map Key field empty, and enter the global access denied page URI /sample/accessdenied.html in
Corresponding Map Value field. <br> To set the access denied page URI for application BankApp: enter
BankApp in Map Key field, and enter the application access denied page URI /BankApp/accessdenied.html
in Corresponding Map Value field.",
    "propertyOrder" : 2700,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"sessionAttributeMap" : {
  "title" : "Session Attribute Mapping",
  "description" : "Maps the session attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.session.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of session attribute UserToken under name CUSTOM-userid: enter UserToken in Map
Key field, and enter CUSTOM-userid in Corresponding Map Value field.",
  "propertyOrder" : 9000,
  "required" : false,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  }
},
"type" : "object",
"exampleValue" : ""
},
"notEnforcedIps" : {
  "title" : "Not Enforced Client IP List",
  "description" : "No authentication and authorization protection from agent
are required for the requests coming from these client IP addresses. (property name:

```

```

com.sun.identity.agents.config.notenforced.ip) <br>Hot-swap: Yes <br> Examples: <br> 192.18.145.*
<br> 192.18.146.123",
  "propertyOrder" : 7900,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"notEnforcedRuleCompoundSeparator" : {
  "title" : "Not Enforced Compound Rule Separator",
  "description" : "Specifies a separator for not enforced compound rules (Agent 5 only). The
format for compound rules requires a list of IP rules, a separator (by default the | character),
and a list of URI rules. For example, GET 192.168.1.1-192.168.4.3 | /images/* Configure a
different separator (for example, &&) when working with the REGEX keyword to avoid invalid regular
expressions.",
  "propertyOrder" : 7450,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"invertNotEnforcedUris" : {
  "title" : "Invert Not Enforced URIs",
  "description" : "Inverts protection of URIs specified in Not Enforced URIs list. When
set to true, it indicates that the URIs specified should be enforced and all other URIs should be
not enforced by the Agent. (property name: com.sun.identity.agents.config.notenforced.uri.invert)
<br>Hot-swap: Yes",
  "propertyOrder" : 7600,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"privilegedSessionAttribute" : {
  "title" : "Privileged Session Attribute",
  "description" : "(Not used in Agent 5 onwards) <br>List of session property
names which hold privileged attributes for the authenticated user. (property name:
com.sun.identity.agents.config.privileged.session.attribute) <br>Hot-swap: Yes <br> Example: <br>
UserToken",
  "propertyOrder" : 9700,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"shortenedPrivilegeAttributeValues" : {
  "title" : "Shortened privilege attribute values",
  "description" : "When using privileged attribute type, this setting will ensure that
the membership details will be stored in a shortened format and not in the default universal ID
format.<br><br>By default the agent maps identity memberships using their universal IDs (e.g.
id=admin,ou=group,dc=openam,dc=forgerock,dc=org), however this may not be always acceptable. Using
this setting the identity membership details will be mapped in a shortened format, only including the
group's/role's name (e.g. admin). Be aware that in case there are both roles and groups in the data
store, this setting will make them indistinguishable from each other, i.e. if there is a group and a
role with the same name it will not be possible to differentiate them.",
  "propertyOrder" : 13600,
  "required" : false,

```

```

        "type" : "boolean",
        "exampleValue" : ""
    },
    "continuousSecurityCookies" : {
        "title" : "Continuous Security Cookies",
        "description" : "The name of the cookies to be sent as part of the payload during policy
evaluation, which can be accessed via the 'environment' variable in a policy script. The 'key' is
the name of the cookie to be sent, and the 'value' is the name which it will appear as in the policy
evaluation script. It is possible to map multiple cookies to the same name (they will simply appear
as an array in the evaluation script). If the cookie doesn't exist, then the empty string will be
sent.",
        "propertyOrder" : 3210,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "logoutRequestParameters" : {
        "title" : "Logout Request Parameter",
        "description" : "An application-specific Map that identifies a parameter
which when present in the HTTP request indicates a logout event. (property name:
com.sun.identity.agents.config.logout.request.param) <br>Valid key: the web application name.
<br>Valid value: the logout request parameter. <br>For this property, a global value can be set to
apply to all the applications that don't have their own specific logout request parameter. <br>Hot-
swap: Yes <br> Examples: <br>To set a global application logout request parameter: Leave Map Key
field empty, and enter the global application logout request parameter logoutparam in Corresponding
Map Value field. <br> To set the logout request parameter for application BankApp: enter BankApp in
Map Key field, and enter the logout request parameter logoutparam in Corresponding Map Value field.",
        "propertyOrder" : 6100,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "defaultPrivilegedAttributes" : {
        "title" : "Default Privileged Attribute",
        "description" : "(Not used in Agent 5 onwards) <br>List of privileged
attributes that will be granted to all users who have a valid AM session. (property name:
com.sun.identity.agents.config.default.privileged.attribute) <br>Hot-swap: Yes <br> Example: <br>
AUTHENTICATED_USERS",
        "propertyOrder" : 9400,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "invertNotEnforcedIps" : {
        "title" : "Not Enforced IP Invert List",

```

```

      "description" : "Client IP Addresses to invert protection of IP
addresses listed in the related Not Enforced Client IP List. (property name:
com.sun.identity.agents.config.notenforced.ip.invert) <br>Hot-swap: Yes",
      "propertyOrder" : 8000,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "privilegedAttributeMappingEnabled" : {
      "title" : "Enable Privileged Attribute Mapping",
      "description" : "(Not used in Agent 5 onwards) <br>Enable a mapping from
the original value of an attribute to another value. To satisfy container-specific
restrictions on character set being used in certain configuration files. (property name:
com.sun.identity.agents.config.privileged.attribute.mapping.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 9800,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "privilegedAttributeType" : {
      "title" : "Privileged Attribute Type",
      "description" : "(Not used in Agent 5 onwards) <br>List of
privileged attribute types that will be fetched for each user. (property name:
com.sun.identity.agents.config.privileged.attribute.type) <br>Hot-swap: Yes <br> Example: <br>
Group",
      "propertyOrder" : 9500,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "loginErrorUri" : {
      "title" : "Login Error URI",
      "description" : "List of absolute URIs corresponding to an application's web.xml form-error-
page element. (property name: com.sun.identity.agents.config.login.error.uri) <br>Hot-swap: Yes <br>
Example: <br> /BankApp/jsp/error.jsp",
      "propertyOrder" : 2900,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "notEnforcedUrisRefreshSessionIdleTime" : {
      "title" : "Refresh Session Idle Time",
      "description" : "Indicates if opensso session idle time should be refreshed or reset for not
enforced URIs. (property name: com.sun.identity.agents.config.notenforced.refresh.session.idletime)
<br>Hot-swap: Yes",
      "propertyOrder" : 8600,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "customLogoutHandlers" : {
      "title" : "Custom Logout Handler",

```

```

    "description" : "Application specific logout handler to log out a user with the application
server. (property name: com.sun.identity.agents.config.logout.handler) <br>Valid key: the web
application name. <br>Valid value: the logout handler class name. <br>Hot-swap: Yes <br> Example:
<br>To set logout handler for application BankApp: enter BankApp in Map Key field, and enter logout
handler class name BankLogoutHandler in Corresponding Map Value field.",
    "propertyOrder" : 3300,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "customVerificationHandlers" : {
    "title" : "Custom Verification Handler",
    "description" : "Application specific verification handler to validate the user credentials
with the local repository. (property name: com.sun.identity.agents.config.verification.handler)
<br>Valid key: the web application name. <br>Valid value: the verification handler class name.
<br>Hot-swap: Yes <br> Example: <br> To set verification handler for application BankApp: enter
BankApp in Map Key field, and enter verification handler class name BankVerificationHandler in
Corresponding Map Value field.",
    "propertyOrder" : 3400,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "cookieAttributeUrlEncoded" : {
    "title" : "Attribute Cookie Encode",
    "description" : "Indicates if the value of the attribute should be URL encoded before being
set as a cookie. (property name: com.sun.identity.agents.config.attribute.cookie.encode) <br>Hot-
swap: Yes",
    "propertyOrder" : 8500,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "customAuthenticationHandlers" : {
    "title" : "Custom Authentication Handler",
    "description" : "Application specific authentication handler to authenticate the logged
on user with the application server. (property name: com.sun.identity.agents.config.auth.handler)
<br>Valid key: the web application name. <br>Valid value: the authentication handler class
name. <br>Hot-swap: Yes <br>Example: <br>To set authentication handler for application BankApp:
enter BankApp in Map Key field, and enter authentication handler class name BankAuthHandler in
Corresponding Map Value field.",
    "propertyOrder" : 3200,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",

```

```

        "exampleValue" : ""
    },
    "notEnforcedUris" : {
        "title" : "Not Enforced URIs",
        "description" : "List of URIs for which protection is not enforced by the Agent. (property
name: com.sun.identity.agents.config.notenforced.uri) <br>Hot-swap: Yes <br> Examples: <br> /BankApp/
public/* <br> /BankApp/images/*",
        "propertyOrder" : 7500,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "profileAttributeMap" : {
        "title" : "Profile Attribute Mapping",
        "description" : "Maps the profile attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.profile.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of profile attribute cn under name CUSTOM-Common-Name: enter cn in Map Key field,
and enter CUSTOM-Common-Name in Corresponding Map Value field. <br> To populate the value of profile
attribute mail under name CUSTOM-Email: enter mail in Map Key field, and enter CUSTOM-Email in
Corresponding Map Value field.",
        "propertyOrder" : 8800,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "privilegedAttributeMap" : {
        "title" : "Privileged Attribute Mapping",
        "description" : "(Not used in Agent 5 onwards) <br>Map if using Enable Privileged
Attribute Mapping. (property name: com.sun.identity.agents.config.privileged.attribute.mapping)
<br>Hot-swap: Yes <br> Examples: <br> To map UUID id=manager,ou=group,dc=openam,dc=forgerock,dc=org
to the principal name am_manager_role specified in webapp's deployment descriptor: enter
id=manager,ou=group,dc=openam,dc=forgerock,dc=org in Map Key field, and enter am_manager_role in
Corresponding Map Value field. <br> To map UUID id=employee,ou=group,dc=openam,dc=forgerock,dc=org
to the principal name am_employee_role specified in webapp's deployment descriptor: enter
id=employee,ou=group,dc=openam,dc=forgerock,dc=org in Map Key field, and enter am_employee_role in
Corresponding Map Value field.",
        "propertyOrder" : 9900,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "headerAttributeDateFormat" : {
        "title" : "Fetch Attribute Date Format",
    }

```

```

        "description" : "Format of date attribute values to be used when the attribute is
being set as HTTP header. Format is based on java.text.SimpleDateFormat. (property name:
com.sun.identity.agents.config.attribute.date.format) <br>Hot-swap: Yes",
        "propertyOrder" : 8400,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "privilegedAttributesToLowerCase" : {
        "title" : "Privileged Attributes To Lower Case",
        "description" : "(Not used in Agent 5 onwards) <br>Maps the privileged
attribute types to whether they should be converted to lowercase. (property name:
com.sun.identity.agents.config.privileged.attribute.lowercase) <br> Valid Keys: the privileged
attribute types, such as Group, Role. <br>Valid value: true, false. <br>Hot-swap: Yes <br> Example:
<br> Enter Group in Map Key field, and enter false in Corresponding Map Value field.",
        "propertyOrder" : 9600,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    }
}
},
"globalJ2EEAgentConfig" : {
    "type" : "object",
    "title" : "Global",
    "propertyOrder" : 0,
    "properties" : {
        "auditLogLocation" : {
            "title" : "Audit Log Location",
            "description" : "Specifies where audit messages should be logged. (property name:
com.sun.identity.agents.config.log.disposition) <br>Hot-swap: Yes",
            "propertyOrder" : 1600,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "localAuditRotationSize" : {
            "title" : "Local Audit Log Rotation Size",
            "description" : "Size limit when a local audit log file is rotated to a new file. (property
name: com.sun.identity.agents.config.local.log.size) <br>Hot-swap: Yes",
            "propertyOrder" : 1900,
            "required" : false,
            "type" : "integer",
            "exampleValue" : ""
        },
        "customResponseHeader" : {
            "title" : "Custom Response Header",
            "description" : "Map specifies the custom headers that are set by the Agent on the client
browser. The key is the header name and the value represents the header value. (property name:
com.sun.identity.agents.config.response.header) <br>Hot-swap: Yes <br> Example: <br> To set the
custom header Cache-Control to value no-cache: enter Cache-Control in Map Key field, and enter no-
cache in Corresponding Map Value field.",
            "propertyOrder" : 7000,
            "required" : false,

```



```

    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "auditAccessType" : {
    "title" : "Audit Access Types",
    "description" : "Types of messages to log based on user URL access attempts. (property name: com.sun.identity.agents.config.audit.accesstype) <br>Hot-swap: Yes",
    "propertyOrder" : 1500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "httpSessionBinding" : {
    "title" : "HTTP Session Binding",
    "description" : "If true will invalidate the http session when login has failed, user has no SSO session, or principal user name does not match SSO user name. (property name: com.sun.identity.agents.config.httpsession.binding) <br>Hot-swap: Yes",
    "propertyOrder" : 3500,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cdssoRootUrl" : {
    "title" : "Agent Root URL for CDSSO",
    "description" : "The agent root URL for CDSSO. The valid value is in the following format: <br>protocol://hostname:port/<br> The protocol represents the protocol used, such as http or https. The hostname represents the host name of the machine on which the agent resides. The port represents the port number on which the agent is installed. The slash following the port number is required.",
    "propertyOrder" : 22700,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "fqdnDefault" : {
    "title" : "FQDN Default",
    "description" : "Fully qualified hostname that the users should use in order to access resources. (property name: com.sun.identity.agents.config.fqdn.default) <br>Hot-swap: Yes",
    "propertyOrder" : 6500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "filterMode" : {
    "title" : "Agent Filter Mode",
    "description" : "Specifies the mode of operation of the Filter. (property name: com.sun.identity.agents.config.filter.mode) <br>Valid key: the web application name. <br>Valid values: ALL, J2EE_POLICY (Not used in Agent 5 onwards), URL_POLICY, SSO_ONLY, NONE <br>For this property, a global value can be set to apply to all the applications that don't have their own specific filter mode. <br>Hot-swap: No <br>Examples: <br>To set ALL as the global filter mode: leave Map Key field empty, and enter ALL in Corresponding Map Value field. <br>To set URL_POLICY

```

```

as the filter mode for application BankApp: enter BankApp in Map Key field, and enter URL_POLICY in
Corresponding Map Value field.",
  "propertyOrder" : 500,
  "required" : false,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"loginAttemptLimit" : {
  "title" : "Login Attempt Limit",
  "description" : "Limit of failed login attempts for a user's single browser session until
triggering the blocking of the user request. Value of 0 disables this feature. (property name:
com.sun.identity.agents.config.login.attempt.limit) <br>Hot-swap: Yes",
  "propertyOrder" : 4400,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"fqdnMapping" : {
  "title" : "FQDN Virtual Host Map",
  "description" : "Maps virtual, invalid, or partial hostnames, and IP addresses to the FQDN
to access protected resources. (property name: com.sun.identity.agents.config.fqdn.mapping) <br>Hot-
swap: Yes <br> Examples: <br> To map the partial hostname myserver to myserver.mydomain.com: enter
myserver in the Map Key field and myserver.mydomain.com in the Corresponding Map Value field. To map
a virtual server rst.hostname.com that points to the actual server abc.hostname.com: enter valid1 in
the Map Key field and rst.hostname.com in the Corresponding Map Value field.",
  "propertyOrder" : 6600,
  "required" : false,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"websocketConnectionIntervalInMinutes" : {
  "title" : "Web Socket Connection Interval",
  "description" : "Interval in minutes by which agents reopen their web socket connection to
ensure a fair distribution of connections across AM servers. (Agent 5 only).",
  "propertyOrder" : 12105,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"fqdnCheck" : {
  "title" : "FQDN Check",
  "description" : "Enables checking of fqdn default value and fqdn map values. (property name:
com.sun.identity.agents.config.fqdn.check.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 6400,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"agentNotificationUrl" : {

```

```
"title" : "Agent Notification URL",
"description" : "URL used by agent to register notification listeners. (property name:
com.sun.identity.client.notification.url) <br>Hot-swap: No",
"propertyOrder" : 300,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"configurationReloadInterval" : {
"title" : "Configuration Reload Interval",
"description" : "Interval in seconds between configuration reloads. (property name:
com.sun.identity.agents.config.load.interval) <br>Hot-swap: Yes",
"propertyOrder" : 1200,
"required" : false,
"type" : "integer",
"exampleValue" : ""
},
"userTokenName" : {
"title" : "User Token Name",
"description" : "Session property name for user-ID of the authenticated user in session.
(property name: com.sun.identity.agents.config.user.token) <br>Hot-swap: Yes",
"propertyOrder" : 900,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"remoteLogFilename" : {
"title" : "Remote Log File Name",
"description" : "Name of file stored on AM server that contains agent audit messages.
(property name: com.sun.identity.agents.config.remote.logfile) <br>Hot-swap: Yes",
"propertyOrder" : 1700,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"status" : {
"title" : "Status",
"description" : "Status of the agent configuration.",
"propertyOrder" : 200,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"userAttributeName" : {
"title" : "User Attribute Name",
"description" : "Name of the attribute which contains the user-ID. (property name:
com.sun.identity.agents.config.user.attribute.name) <br>Hot-swap: Yes",
"propertyOrder" : 700,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"userPrincipalFlag" : {
"title" : "User Principal Flag",
"description" : "Use principal instead of just the user-ID for authenticating the user.
(property name: com.sun.identity.agents.config.user.principal) <br>Hot-swap: Yes",
"propertyOrder" : 800,
"required" : false,
"type" : "boolean",
```

```

    "exampleValue" : ""
  },
  "debugLevel" : {
    "title" : "Agent Debug Level",
    "description" : "Specifies type of agent debug messages to log. (property name:
com.ipplanet.services.debug.level) <br>Hot-swap: Yes",
    "propertyOrder" : 10000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "localAuditLogRotation" : {
    "title" : "Rotate Local Audit Log",
    "description" : "Flag to indicate that audit log files should be rotated when reaching a
certain size. (property name: com.sun.identity.agents.config.local.log.rotate) <br>Hot-swap: Yes",
    "propertyOrder" : 1800,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "jwtName" : {
    "title" : "JWT Cookie Name",
    "description" : "The name used by the agent to set the OIDC JWT on the user's browser.
(Agent 5 only).",
    "propertyOrder" : 11201,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "agentConfigChangeNotificationsEnabled" : {
    "title" : "Agent Configuration Change Notification",
    "description" : "Enable agent to receive notification messages from AM server for
configuration changes. (property name: com.sun.identity.agents.config.change.notification.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 12100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "redirectAttemptLimit" : {
    "title" : "Redirect Attempt Limit",
    "description" : "Number of successive single point redirects that a user can make using a
single browser session which will trigger the blocking of the user request. Set to 0 to disable this
feature. (property name: com.sun.identity.agents.config.redirect.attempt.limit) <br>Hot-swap: Yes",
    "propertyOrder" : 7100,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "userMappingMode" : {
    "title" : "User Mapping Mode",
    "description" : "Specifies mechanism agent uses to determine user-ID. (property name:
com.sun.identity.agents.config.user.mapping.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}

```

```

    },
    "amServicesJ2EEAgent" : {
        "type" : "object",
        "title" : "AM Services",
        "propertyOrder" : 3,
        "properties" : {
            "authServiceHost" : {
                "title" : "AM Authentication Service Host Name",
                "description" : "Host name to be used by the AM authentication service. (property name:
com.ipplanet.am.server.host) <br>Hot-swap: No",
                "propertyOrder" : 11000,
                "required" : false,
                "type" : "string",
                "exampleValue" : ""
            },
            "userDataCacheNotifications" : {
                "title" : "Enable Notification of User Data Caches",
                "description" : "Enable notifications for amsdk and IdRepo Caches. (property name:
com.sun.identity.idm.remote.notification.enabled) <br>Hot-swap: No",
                "propertyOrder" : 10500,
                "required" : false,
                "type" : "boolean",
                "exampleValue" : ""
            },
            "policyNotifications" : {
                "title" : "Enable Policy Notifications",
                "description" : "Enable Notifications for remote policy client. (property name:
com.sun.identity.agents.notification.enabled) <br>Hot-swap: No",
                "propertyOrder" : 11200,
                "required" : false,
                "type" : "boolean",
                "exampleValue" : ""
            },
            "loginUrlPrioritized" : {
                "title" : "Login URL Prioritized",
                "description" : "Specifies if failover sequence for Login URLs or CDSSO
URLs should be prioritized as defined in the AM Login URL list. (property name:
com.sun.identity.agents.config.login.url.prioritized) <br>Hot-swap: Yes",
                "propertyOrder" : 3800,
                "required" : false,
                "type" : "boolean",
                "exampleValue" : ""
            },
            "logoutProbeTimeout" : {
                "title" : "Logout URL Probe Timeout",
                "description" : "The connect timeout value in milliseconds, if also Logout URL Probe is set
to true. (property name: com.sun.identity.agents.config.logout.url.probe.timeout) <br>Hot-swap: Yes",
                "propertyOrder" : 12700,
                "required" : false,
                "type" : "integer",
                "exampleValue" : ""
            },
            "conditionalLoginUrl" : {
                "title" : "AM Conditional Login URL",
                "description" : "(Only used in Agent 5 onwards) (property name:
org.forgerock.openam.agents.config.conditional.login.url) <br>Hot-swap: Yes <br> Examples: <br>
match?url?param1=value1&param2=value2 <br> match/path|?param1=value1&param2=value2&param3=value3",
                "propertyOrder" : 4010,
                "required" : false,
            }
        }
    }

```

```

        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "policyActionBooleanValues" : {
        "title" : "Policy Client Boolean Action Values",
        "description" : "Boolean action values for policy action names. (property name: com.sun.identity.policy.client.booleanActionValues) <br>Hot-swap: No",
        "propertyOrder" : 11500,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "urlPolicyEnvJsessionParameters" : {
        "title" : "URL Policy Env jsession Parameters",
        "description" : "List of HTTP SESSION attributes whose names and values will be set in the environment map for URL policy evaluation at AM server. (property name: com.sun.identity.agents.config.policy.env.jsession.param) <br>Hot-swap: Yes <br> Examples: <br> name <br> phonenumber",
        "propertyOrder" : 12000,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "amLogoutUrl" : {
        "title" : "AM Logout URL",
        "description" : "AM logout page URL. (property name: com.sun.identity.agents.config.logout.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/opensso/UI/Logout",
        "propertyOrder" : 12400,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "serviceDataCacheTime" : {
        "title" : "Service Data Cache Time",
        "description" : "Cache update time in minutes for service configuration data. If set to '0' no updates happen. (property name: com.sun.identity.sm.cacheTime) <br>Hot-swap: No",
        "propertyOrder" : 10800,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "serviceDataCacheNotifications" : {
        "title" : "Enable Notification of Service Data Caches",
        "description" : "Enable the notifications for service management caches. (property name: com.sun.identity.sm.notification.enabled) <br>Hot-swap: No",
        "propertyOrder" : 10700,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    }

```

```

    },
    "useRedirectForCompositeAdvice" : {
      "title" : "Use HTTP-Redirect for composite advice",
      "description" : "Configure remote policy client to use HTTP-redirect instead of HTTP-POST
for composite advices. (property name: com.sun.identity.agents.config.policy.advice.use.redirect)
<br>Hot-swap: Yes",
      "propertyOrder" : 13000,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "probeLoginUrl" : {
      "title" : "Login URL Probe",
      "description" : "Specifies if agent will check the availability of these urls before
redirecting to them. (property name: com.sun.identity.agents.config.login.url.probe.enabled) <br>Hot-
swap: Yes",
      "propertyOrder" : 3900,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "UserDataCachePollingTime" : {
      "title" : "User Data Cache Polling Time",
      "description" : "Cache update time in minutes for user management data. If set to '0' no
updates happen. (property name: com.iplanet.am.sdk.remote.pollingTime) <br>Hot-swap: No",
      "propertyOrder" : 10600,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authServicePort" : {
      "title" : "AM Authentication Service Port",
      "description" : "Port to be used by the AM authentication service. (property name:
com.iplanet.am.server.port) <br>Hot-swap: No",
      "propertyOrder" : 11100,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "urlPolicyEnvGetParameters" : {
      "title" : "URL Policy Env GET Parameters",
      "description" : "List of HTTP GET request parameters whose names and values will
be set in the environment map for URL policy evaluation at AM server. (property name:
com.sun.identity.agents.config.policy.env.get.param) <br>Hot-swap: Yes <br> Examples: <br> name <br>
phonenummer",
      "propertyOrder" : 11800,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "amLoginUrl" : {
      "title" : "AM Login URL",
      "description" : "AM login page URL. (property name:
com.sun.identity.agents.config.login.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Login",
      "propertyOrder" : 3700,

```

```

    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "policyClientClockSkew" : {
    "title" : "Policy Client Clock Skew",
    "description" : "Time in seconds which is allowed to accommodate the time difference
between the AM server machine and the remote policy client machine. (property name:
com.sun.identity.policy.client.clockSkew) <br>Hot-swap: No",
    "propertyOrder" : 11700,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "clientPollingPeriod" : {
    "title" : "Client Polling Period",
    "description" : "(Not used in Agent 5 onwards) <br>Time in seconds after which the
session client will request update of cached session information from the server. (property name:
com.iplanet.am.session.client.polling.period) <br>Hot-swap: No",
    "propertyOrder" : 10300,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "conditionalLogoutUrl" : {
    "title" : "AM Conditional Logout URL",
    "description" : "(Only used in Agent 5 onwards) (property name:
org.forgerock.openam.agents.config.conditional.logout.url) <br>Hot-swap: Yes <br> Examples: <br>
match?url?param1=value1&param2=value2 <br> match/path|?param1=value1&param2=value2&param3=value3",
    "propertyOrder" : 12550,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "logoutUrlPrioritized" : {
    "title" : "Logout URL Prioritized",
    "description" : "Specifies if failover sequence for Logout URLs
should be prioritized as defined in the AM Login URL list. (property name:
com.sun.identity.agents.config.logout.url.prioritized) <br>Hot-swap: Yes",
    "propertyOrder" : 12500,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "policyClientCacheMode" : {
    "title" : "Policy Client Cache Mode",
    "description" : "Mode of caching to be used by remote policy client. (property name:
com.sun.identity.policy.client.cacheMode) <br>Hot-swap: No",
    "propertyOrder" : 11400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
}

```



```
"policyEvaluationRealm" : {
  "title" : "Realm",
  "description" : "Which realm to start evaluating from. (property name:
org.forgerock.openam.agents.config.policy.evaluation.realm) <br>Hot-swap: Yes",
  "propertyOrder" : 5400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"enableClientPolling" : {
  "title" : "Enable Client Polling",
  "description" : "Specifies if the session client must use polling for
updating session information and not depend upon server notifications. (property name:
com.iplanet.am.session.client.polling.enable) <br>Hot-swap: No",
  "propertyOrder" : 10200,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"authServiceProtocol" : {
  "title" : "AM Authentication Service Protocol",
  "description" : "Protocol to be used by the AM authentication service. (property name:
com.iplanet.am.server.protocol) <br>Hot-swap: No",
  "propertyOrder" : 10900,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"policyEvaluationApplication" : {
  "title" : "Application",
  "description" : "Which application contains the policies to evaluate with. (property name:
org.forgerock.openam.agents.config.policy.evaluation.application) <br>Hot-swap: Yes",
  "propertyOrder" : 5500,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"loginProbeTimeout" : {
  "title" : "Login URL Probe Timeout",
  "description" : "The connect timeout value in milliseconds, if also Login URL Probe is set
to true. (property name: com.sun.identity.agents.config.login.url.probe.timeout) <br>Hot-swap: Yes",
  "propertyOrder" : 4000,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"policyClientResourceComparators" : {
  "title" : "Policy Client Resource Comparators",
  "description" : "Resource Comparators to be used for different service names. (property
name: com.sun.identity.policy.client.resourceComparators) <br>Hot-swap: No",
  "propertyOrder" : 11600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"urlPolicyEnvPostParameters" : {
  "title" : "URL Policy Env POST Parameters",
  "description" : "List of HTTP POST request parameters whose names and values
will be set in the environment map for URL policy evaluation at AM server. (property name:
```

```

com.sun.identity.agents.config.policy.env.post.param) <br>Hot-swap: Yes <br> Examples: <br> name <br>
phonenumner",
    "propertyOrder" : 11900,
    "required" : false,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"policyClientPollingInterval" : {
    "title" : "Policy Client Polling Interval",
    "description" : "Duration in minutes after which the cached entries are refreshed by remote
policy client. (property name: com.sun.identity.agents.polling.interval) <br>Hot-swap: No",
    "propertyOrder" : 11300,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
},
"probeLogoutUrl" : {
    "title" : "Logout URL Probe",
    "description" : "Specifies if agent will check the availability of these urls before
redirecting to them. (property name: com.sun.identity.agents.config.logout.url.probe.enabled)
<br>Hot-swap: Yes",
    "propertyOrder" : 12600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
}
}
},
"advancedJ2EEAgentConfig" : {
    "type" : "object",
    "title" : "Advanced",
    "propertyOrder" : 5,
    "properties" : {
        "webServiceResponseProcessor" : {
            "title" : "Web Service Response Processor",
            "description" : "An implementation class of interface
com.sun.identity.agents.filter.IWebServiceResponseProcessor that can be used to process the web-
service responses. (property name: com.sun.identity.agents.config.webservice.responseprocessor)
<br>Hot-swap: Yes",
            "propertyOrder" : 2400,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "clientIpHeader" : {
            "title" : "Client IP Address Header",
            "description" : "HTTP header name that holds the IP address of the client. (property name:
com.sun.identity.agents.config.client.ip.header) <br>Hot-swap: Yes",
            "propertyOrder" : 1000,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "xssDetectionRedirectUri" : {
            "title" : "XSS detection redirect URI",

```

```

    "description" : "An application-specific Map that identifies a URI of the customized page if
XSS code has been detected. (property name: com.sun.identity.agents.config.xss.redirect.uri) <br>Hot-
swap: Yes <br>Examples: <br>To set a redirect target for application BankApp: enter BankApp in Map Key
field, and enter a redirect URI in Corresponding Map Value field.",
    "propertyOrder" : 12900,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "clientHostnameHeader" : {
    "title" : "Client Hostname Header",
    "description" : "HTTP header name that holds the Hostname of the client. (property name:
com.sun.identity.agents.config.client.hostname.header) <br>Hot-swap: Yes",
    "propertyOrder" : 1100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "webServiceProcessGetEnabled" : {
    "title" : "Web Service Process GET Enable",
    "description" : "Flag to indicates if the processing of HTTP GET requests for Web Service
endpoints is enabled. (property name: com.sun.identity.agents.config.webservice.process.get.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 2200,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "customProperties" : {
    "title" : "Custom Properties",
    "description" : "Additional properties that allow users to augment the set of properties
supported by agent. (property name: com.sun.identity.agents.config.freeformproperties) <br>Hot-
swap: Yes <br> Examples: <br> customproperty=custom-value1 <br> customlist[0]=customlist-
value-0 <br> customlist[1]=customlist-value-1 <br> custommap[key1]=custommap-value-1 <br>
custommap[key2]=custommap-value-2",
    "propertyOrder" : 12200,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "postDataPreserveCacheEntryMaxEntries" : {
    "title" : "PDP Maximum Number of Cache Entries",
    "description" : "Maximum number of entries to hold in the PDP cache (Property name:
org.forgerock.openam.agents.config.postdata.preserve.cache.entry.max.entries) (Agent 5 only).",
    "propertyOrder" : 13550,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "alternativeAgentProtocol" : {
    "title" : "Alternative Agent Protocol",

```

```

        "description" : "Protocol being used (http/https) by the client browsers to communicate with
        the Agent protected server if different from the actual protocol used by the server. (property name:
        com.sun.identity.agents.config.agent.protocol) <br>Hot-swap: Yes",
        "propertyOrder" : 4300,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "webServiceAuthorizationErrorContentFile" : {
        "title" : "Web Service Authorization Error Content File",
        "description" : "The name of file that contains content used by the
        Agent to generate an authorization error fault for clients. (property name:
        com.sun.identity.agents.config.webservice.autherror.content) <br>Hot-swap: Yes",
        "propertyOrder" : 2600,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "webServiceEnabled" : {
        "title" : "Web Service Enable",
        "description" : "Flag specifies if Web Service processing is enabled. (property name:
        com.sun.identity.agents.config.webservice.enable) <br>Hot-swap: Yes",
        "propertyOrder" : 2000,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "alternativeAgentHostname" : {
        "title" : "Alternative Agent Host Name",
        "description" : "Host name identifying the Agent protected server to the client browsers
        if different from the actual host name. (property name: com.sun.identity.agents.config.agent.host)
        <br>Hot-swap: Yes",
        "propertyOrder" : 4100,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "jbossWebAuthenticationAvailable" : {
        "title" : "Web Authentication Available",
        "description" : "(Not used in Agent 5 onwards) <br>Enable agent to make programmatic
        authentication with the JBoss web container using WebAuthentication feature. (property name:
        com.sun.identity.agents.config.jboss.webauth.available) <br>Hot-swap: Yes",
        "propertyOrder" : 12300,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "postDataCacheTtl" : {
        "title" : "PDP entry TTL",
        "description" : "This value tells how long a given POST entry should be
        stored in the local cache (in milliseconds), default value is 300000. (property name:
        com.sun.identity.agents.config.postdata.preserve.cache.entry.ttl)",
        "propertyOrder" : 13300,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "webServiceAuthenticator" : {
        "title" : "Web Service Authenticator",
    }

```

```

    "description" : "An implementation class of interface
com.sun.identity.agents.filter.IWebServiceAuthenticator that can be used to authenticate web-service
requests. (property name: com.sun.identity.agents.config.webservice.authenticator) <br>Hot-swap:
Yes",
    "propertyOrder" : 2300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "webServiceEndpoints" : {
    "title" : "Web Service End Points",
    "description" : "A list of Web Application end points that represent Web Services. (property
name: com.sun.identity.agents.config.webservice.endpoint) <br>Hot-swap: Yes",
    "propertyOrder" : 2100,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "alternativeAgentPort" : {
    "title" : "Alternative Agent Port Name",
    "description" : "Port number identifying the Agent protected server listening
port to the client browsers if different from the actual listening port. (property name:
com.sun.identity.agents.config.agent.port) <br>Hot-swap: Yes",
    "propertyOrder" : 4200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "postDataStickySessionMode" : {
    "title" : "PDP Stickysession mode",
    "description" : "The PDP mechanism needs sticky loadbalancing, the URL mode
will append a querystring, while the Cookie mode will create a cookie. (property name:
com.sun.identity.agents.config.postdata.preserve.sticky.session.mode)",
    "propertyOrder" : 13400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "postDataStickySessionKeyValue" : {
    "title" : "PDP Stickysession key-value",
    "description" : "The provided key-value pair will be used for adding
to the URL or creating the cookie. <br>Example: <br>Set 'lb=server1' to append
to the querystring or to have 'lb' cookie with 'server1' value. (property name:
com.sun.identity.agents.config.postdata.preserve.sticky.session.value)",
    "propertyOrder" : 13500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "postDataPreserveCacheEntryMaxTotalSizeMb" : {
    "title" : "PDP Maximum Cache Size",
    "description" : "Maximum size of the PDP cache, in megabytes (Property name:
org.forgerock.openam.agents.config.postdata.preserve.cache.entry.max.total.size.mb). (Agent 5 only)",
    "propertyOrder" : 13600,
    "required" : false,
    "type" : "integer",

```

```

    "exampleValue" : ""
  },
  "missingPostDataPreservationEntryUri" : {
    "title" : "Missing PDP entry URI",
    "description" : "An application-specific URI Map that is used in case the referenced
PDP entry cannot be found in the local cache (due to ttl). In such cases it will redirect
to the specified URI, otherwise it will show a HTTP 403 Forbidden error. (property name:
com.sun.identity.agents.config.postdata.preservice.cache.noentry.url)<br>Examples: <br>To set a
redirect target for application BankApp: enter Bankapp in Map Key field and enter a redirect URI in
corresponding Map Value field.",
    "propertyOrder" : 13200,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "possibleXssCodeElements" : {
    "title" : "Possible XSS code elements",
    "description" : "If one of these strings occurs in the request, the client is redirected to
an error page. (property name: com.sun.identity.agents.config.xss.code.elements) <br>Hot-swap: Yes",
    "propertyOrder" : 12800,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "webServiceInternalErrorContentFile" : {
    "title" : "Web Service Internal Error Content File",
    "description" : "The name of file that contains content used by
the Agent to generate an internal error fault for clients. (property name:
com.sun.identity.agents.config.webservice.internalerror.content) <br>Hot-swap: Yes",
    "propertyOrder" : 2500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "postDataPreservation" : {
    "title" : "Post Data Preservation enabled",
    "description" : "Post Data Preservation functionality basically stores any POST
data before redirecting the user to the login screen and after successful login the agent
will generate a page that autosubmits the same POST to the original URL. (property name:
com.sun.identity.agents.config.postdata.preserve.enable)",
    "propertyOrder" : 13100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"ssoJ2EEAgentConfig" : {
  "type" : "object",
  "title" : "SSO",
  "propertyOrder" : 2,
  "properties" : {
    "cdssoRedirectUri" : {

```

```

    "title" : "CDSSO Redirect URI",
    "description" : "An intermediate URI that is used by the Agent for processing CDSSO
requests. (property name: com.sun.identity.agents.config.cdssso.redirect.uri) <br>Hot-swap: Yes",
    "propertyOrder" : 5100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "ssoCacheEnabled" : {
    "title" : "SSO Cache Enable",
    "description" : "Specifies if the SSO Cache is active for the agent.
Cache is used through public APIs exposed by the agent SDK. (property name:
com.sun.identity.agents.config.amsso.cache.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 4500,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cdssoClockSkew" : {
    "title" : "CDSSO Clock Skew",
    "description" : "Time in seconds to be used by the Agent to determine the validity of the
CDSSO AuthnResponse assertion. (property name: com.sun.identity.agents.config.cdssso.clock.skew)
<br>Hot-swap: Yes",
    "propertyOrder" : 5300,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "cdssso" : {
    "title" : "Cross Domain SSO",
    "description" : "Enables Cross Domain Single SignOn. (property name:
com.sun.identity.agents.config.cdssso.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 5000,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cdsssoTrustedIdProvider" : {
    "title" : "CDSSO Trusted ID Provider",
    "description" : "List of AM Server/ID providers that should be trusted
by the agent, when evaluating the CDC Liberty Responses. (property name:
com.sun.identity.agents.config.cdssso.trusted.id.provider) <br>Hot-swap: Yes <br> Example: <br>
http://host:port/opensso/cdcservlet",
    "propertyOrder" : 5600,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "cookieResetNames" : {
    "title" : "Cookies Reset Name List",
    "description" : "Cookie names that will be reset by the Agent if Cookie Reset is enabled.
(property name: com.sun.identity.agents.config.cdssso.cookie.reset.name) <br>Hot-swap: Yes",
    "propertyOrder" : 4700,
    "required" : false,
    "items" : {
      "type" : "string"
    }
  }

```

```

    },
    "type" : "array",
    "exampleValue" : ""
  },
  "cdssoSecureCookies" : {
    "title" : "CDSSO Secure Enable",
    "description" : "The SSO Token cookie set by the agent in the different domains in CDSSO
mode will be marked secure. Only transmitted if the communications channel with host is a secure one.
(property name: com.sun.identity.agents.config.cdsso.secure.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 5700,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "amCookieName" : {
    "title" : "Cookie Name",
    "description" : "Name of the SSO Token cookie used between the AM server and the Agent.
(property name: com.iplanet.am.cookie.name) <br>Hot-swap: No",
    "propertyOrder" : 10100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "cdssoUrls" : {
    "title" : "CDSSO Servlet URL",
    "description" : "List of URLs of the available CDSSO controllers that may be used by the
Agent for CDSSO processing. (property name: com.sun.identity.agents.config.cdsso.cdcservlet.url)
<br>Hot-swap: Yes <br> Example: <br> http://host:port/opensso/cdcservlet",
    "propertyOrder" : 5200,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "cookieResetEnabled" : {
    "title" : "Cookie Reset",
    "description" : "Agent resets cookies in the response before redirecting to authentication.
(property name: com.sun.identity.agents.config.cookie.reset.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 4600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cookieResetDomains" : {
    "title" : "Cookies Reset Domain Map",
    "description" : "Maps cookie names specified in Cookie Reset Name List to value
being the domain of this cookie to be used when a reset event occurs. (property name:
com.sun.identity.agents.config.cookie.reset.domain) <br>Hot-swap: Yes",
    "propertyOrder" : 4800,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  }
}

```



```

    },
    "cdssoDomainList" : {
      "title" : "CDSSO Domain List",
      "description" : "Domains for which cookies have to be set in a CDSSO scenario. (property
name: com.sun.identity.agents.config.cdsso.domain) <br>Hot-swap: Yes <br> Example: <br> .sun.com",
      "propertyOrder" : 5800,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "cookieResetPaths" : {
      "title" : "Cookies Reset Path Map",
      "description" : "Maps cookie names specified in Cookie Reset Name List to value
being the path of this cookie to be used when a reset event occurs. (property name:
com.sun.identity.agents.config.cookie.reset.path) <br>Hot-swap: Yes",
      "propertyOrder" : 4900,
      "required" : false,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : ""
    }
  }
},
"miscJ2EEAgentConfig" : {
  "type" : "object",
  "title" : "Miscellaneous",
  "propertyOrder" : 4,
  "properties" : {
    "legacyUserAgentSupport" : {
      "title" : "Legacy User Agent Support Enable",
      "description" : "Enables support for legacy user agents (browser). (property name:
com.sun.identity.agents.config.legacy.support.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 6700,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "localeCountry" : {
      "title" : "Locale Country",
      "description" : "(property name: com.sun.identity.agents.config.locale.country) <br>Hot-
swap: No",
      "propertyOrder" : 1400,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "portCheckEnabled" : {
      "title" : "Port Check Enable",
      "description" : "Indicates if port check functionality is enabled or disabled. (property
name: com.sun.identity.agents.config.port.check.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 7200,
      "required" : false,

```

```

    "type" : "boolean",
    "exampleValue" : ""
  },
  "encryptionProvider" : {
    "title" : "Encryption Provider",
    "description" : "Specifies the encryption provider implementation to be used by the Agent.
(property name: com.iplanet.security.encryptor) <br>Hot-swap: No",
    "propertyOrder" : 10400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "legacyUserAgentList" : {
    "title" : "Legacy User Agent List",
    "description" : "List of user agent header values that identify legacy
browsers. Entries in this list can have wild card character '*'. (property name:
com.sun.identity.agents.config.legacy.user.agent) <br>Hot-swap: Yes",
    "propertyOrder" : 6800,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "bypassPrincipalList" : {
    "title" : "Bypass Principal List",
    "description" : "List of principals that are bypassed by the Agent for authentication and
search purposes. (property name: com.sun.identity.agents.config.bypass.principal) <br>Hot-swap: Yes
<br> Examples: <br> guest <br> testuser",
    "propertyOrder" : 9300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "ignorePathInfo" : {
    "title" : "Ignore Path Info in Request URL",
    "description" : "The path info will be stripped from the request URL while doing Not
Enforced List check and url policy evaluation if the value is set to true. (property name:
com.sun.identity.agents.config.ignore.path.info) <br>Hot-swap: Yes",
    "propertyOrder" : 18600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "legacyRedirectUri" : {
    "title" : "Legacy User Agent Redirect URI",
    "description" : "An intermediate URI used by the Agent to redirect legacy user agent
requests. (property name: com.sun.identity.agents.config.legacy.redirect.uri) <br>Hot-swap: Yes",
    "propertyOrder" : 6900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "gotoParameterName" : {
    "title" : "Goto Parameter Name",

```

```
"description" : "Property used only when CDSSO is enabled. Default value should be changed only when the login URL has a landing page specified <br> Example : com.sun.identity.agents.config.cdssso.cdcservlet.url = http://host:port/opensso/cdcservlet?goto=http://agent:port/landing.jsp <br> The parameter is used by the Agent to append the original request URL to this cdcservlet URL. This parameter is consumed by the landing page to redirect to the original URL. (property name: com.sun.identity.agents.config.redirect.param) <br>Hot-swap: Yes <br> Example: com.sun.identity.agents.config.redirect.param = goto2<br> The complete URL sent for authentication will be <br> http://host:port/opensso/cdcservlet?goto=http://agent:port/landing.jsp?goto2=http://agent.port/original.jsp",
  "propertyOrder" : 3600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"portCheckFile" : {
  "title" : "Port Check File",
  "description" : "Name or complete path of a file that has the necessary content needed to handle requests that need port correction. (property name: com.sun.identity.agents.config.port.check.file) <br>Hot-swap: Yes",
  "propertyOrder" : 7300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"portCheckSetting" : {
  "title" : "Port Check Setting",
  "description" : "Map of port versus protocol entries with the key being the listening port number and value being the listening protocol to be used by the Agent to identify requests with invalid port numbers. (property name: com.sun.identity.agents.config.port.check.setting) <br>Hot-swap: Yes <br> Example: <br> To map port 80 to protocol http: enter 80 in Map Key field, and enter http in Corresponding Map Value field.",
  "propertyOrder" : 7400,
  "required" : false,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  }
},
"type" : "object",
"exampleValue" : ""
},
"localeLanguage" : {
  "title" : "Locale Language",
  "description" : "(property name: com.sun.identity.agents.config.locale.language) <br>Hot-swap: No",
  "propertyOrder" : 1300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
}
}
}
```

1.78.1.2. delete

Usage:

```
am> delete J2EEAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.78.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action J2EEAgentGroups --realm Realm --actionName getAllTypes
```

1.78.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action J2EEAgentGroups --realm Realm --actionName getCreatableTypes
```

1.78.1.5. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action J2EEAgentGroups --realm Realm --actionName nextdescendants
```

1.78.1.6. query

Querying the agent groups of a specific type

Usage:

```
am> query J2EEAgentGroups --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.78.1.7. read

Usage:

```
am> read J2EEAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.78.1.8. update

Usage:

```
am> update J2EEAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "applicationJ2EEAgentConfig" : {
      "type" : "object",
      "title" : "Application",
      "propertyOrder" : 1,
      "properties" : {
        "applicationLogoutHandlers" : {
          "title" : "Application Logout Handler",
          "description" : "An application-specific Map that identifies a handler to be used for logout
processing. (property name: com.sun.identity.agents.config.logout.application.handler) <br>Valid
key: the web application name. <br>Valid value: the application logout handler class name. <br>For
this property, a global value can be set to apply to all the applications that don't have their own
specific logout handler. <br>Hot-swap: Yes <br>Examples: <br>To set a global application logout
handler: leave Map Key field empty, and enter the global application logout handler class name
GlobalApplicationLogoutHandler in Corresponding Map Value field. <br>To set the logout handler for
application BankApp: enter BankApp in Map Key field, and enter the application logout handler class
name BankAppLogoutHandler in Corresponding Map Value field.",
          "propertyOrder" : 5900,
          "required" : false,
          "patternProperties" : {
            ".*" : {
              "type" : "string"
            }
          }
        },
        "type" : "object",
        "exampleValue" : ""
      }
    },
    "responseAttributeMap" : {
```

```

    "title" : "Response Attribute Mapping",
    "description" : "Maps the policy response attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.response.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of response attribute uid under name CUSTOM-USER-NAME: enter uid in Map Key field,
and enter CUSTOM-USER-NAME in Corresponding Map Value field.",
    "propertyOrder" : 9200,
    "required" : false,
    "patternProperties" : {
        ".*" : {
            "type" : "string"
        }
    },
    "type" : "object",
    "exampleValue" : ""
},
"sessionAttributeFetchMode" : {
    "title" : "Session Attribute Fetch Mode",
    "description" : "The mode of fetching session attributes. (property name:
com.sun.identity.agents.config.session.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 8900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
},
"notEnforcedUrisCacheEnabled" : {
    "title" : "Not Enforced URIs Cache Enabled",
    "description" : "Enables the caching of the Not Enforced URIs list evaluation results.
(property name: com.sun.identity.agents.config.notenforced.uri.cache.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 7700,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
},
"responseAttributeFetchMode" : {
    "title" : "Response Attribute Fetch Mode",
    "description" : "The mode of fetching policy response attributes. (property name:
com.sun.identity.agents.config.response.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 9100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
},
"notEnforcedIpsCacheEnabled" : {
    "title" : "Not Enforced IP Cache Flag",
    "description" : "Enable caching of not-enforced IP list evaluation results. (property name:
com.sun.identity.agents.config.notenforced.ip.cache.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 8100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
},
"profileAttributeFetchMode" : {
    "title" : "Profile Attribute Fetch Mode",
    "description" : "The mode of fetching profile attributes. (property name:
com.sun.identity.agents.config.profile.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 8700,
    "required" : false,
    "type" : "string",

```

```

        "exampleValue" : ""
    },
    "cookieAttributeMultiValueSeparator" : {
        "title" : "Cookie Separator Character",
        "description" : "Character that will be used to separate multiple
values of the same attribute when it is being set as a cookie. (property name:
com.sun.identity.agents.config.attribute.cookie.separator) <br>Hot-swap: Yes",
        "propertyOrder" : 8300,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "logoutEntryUri" : {
        "title" : "Logout Entry URI",
        "description" : "An application-specific Map that identifies a URI to be used as an entry
point after successful logout and subsequent successful authentication if applicable. (property name:
com.sun.identity.agents.config.logout.entry.uri) <br>Valid key: the web application name. <br>Valid
value: the logout entry URI. <br>For this property, a global value can be set to apply to all the
applications that don't have their own specific logout entry URI. <br>Hot-swap: Yes <br> Examples:
<br>To set a global application logout entry URI: leave Map Key field empty, and enter the global
application logout entry URI /welcome.html in Corresponding Map Value field. <br> To set the logout
entry URI for application BankApp: enter BankApp in Map Key field, and enter the logout entry URI /
BankApp/welcome.html in Corresponding Map Value field.",
        "propertyOrder" : 6300,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "applicationLogoutUris" : {
        "title" : "Application Logout URI",
        "description" : "An application-specific Map that identifies a request URI which indicates
a logout event. (property name: com.sun.identity.agents.config.logout.uri) <br>Valid key: the web
application name. <br>Valid value: the application logout URI. <br>For this property, a global value
can be set to apply to all the applications that don't have their own specific logout URI. <br>Hot-
swap: Yes <br> Examples: <br>To set a global application logout URI: leave Map Key field empty, and
enter the global application logout URI /logout.jsp in Corresponding Map Value field. <br> To set the
logout URI for application BankApp: enter BankApp in Map Key field, and enter the application logout
URI /BankApp/logout.jsp in Corresponding Map Value field.",
        "propertyOrder" : 6000,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "useInternalLogin" : {
        "title" : "Use Internal Login",
        "description" : "Set to false if want to customize Login Content File instead of default
internal content provided. (property name: com.sun.identity.agents.config.login.use.internal)
<br>Hot-swap: Yes",
        "propertyOrder" : 3000,
    }

```

```

        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "notEnforcedUriCacheSize" : {
        "title" : "Not Enforced URIs Cache Size",
        "description" : "Size of the cache to be used if caching of not enforced URI list evaluation
results is enabled. (property name: com.sun.identity.agents.config.notenforced.uri.cache.size)
<br>Hot-swap: Yes",
        "propertyOrder" : 7800,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "loginFormUri" : {
        "title" : "Login Form URI",
        "description" : "List of absolute URIs corresponding to an application's web.xml form-
login-page element. (property name: com.sun.identity.agents.config.login.form) <br>Hot-swap: Yes <br>
Example: <br> /BankApp/jsp/login.jsp",
        "propertyOrder" : 2800,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "continuousSecurityHeaders" : {
        "title" : "Continuous Security Headers",
        "description" : "The name of the headers in the user's original request, that will be sent
as part of the payload during policy evaluation, which can then be accessed via the 'environment'
variable in a policy script. The 'key' is the name of the header to be sent, and the 'value' is the
name which it will appear as in the policy evaluation script. It is possible to map multiple headers
to the same name (they will simply appear as an array in the evaluation script). If the header
doesn't exist, then the empty string will be sent.",
        "propertyOrder" : 3211,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "notEnforcedIpsCacheSize" : {
        "title" : "Not Enforced IP Cache Size",
        "description" : "Size of the cache to be used if Not Enforced IP Cache Flag is enabled.
(property name: com.sun.identity.agents.config.notenforced.ip.cache.size) <br>Hot-swap: Yes",
        "propertyOrder" : 8200,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "loginContentFile" : {
        "title" : "Login Content File Name",
        "description" : "Complete path and name of custom login content file. (property name:
com.sun.identity.agents.config.login.content.file) <br>Hot-swap: Yes",
        "propertyOrder" : 3100,
    
```



```

        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "logoutIntrospection" : {
        "title" : "Logout Introspect Enabled",
        "description" : "Allows the Agent to search HTTP request body to locate logout parameter.
(property name: com.sun.identity.agents.config.logout.introspect.enabled) <br>Hot-swap: Yes",
        "propertyOrder" : 6200,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "resourceAccessDeniedUri" : {
        "title" : "Resource Access Denied URI",
        "description" : "An application-specific Map that identifies a URI of the customized access
denied page. (property name: com.sun.identity.agents.config.access.denied.uri) <br>Valid key: the
web application name. <br>Valid value: the customized application access denied page URI. <br>For
this property, a global value can be set to apply to all the applications that don't have their own
specific access denied page. <br>Hot-swap: Yes <br> Examples: <br>To set a global access denied page:
leave Map Key field empty, and enter the global access denied page URI /sample/accessdenied.html in
Corresponding Map Value field. <br> To set the access denied page URI for application BankApp: enter
BankApp in Map Key field, and enter the application access denied page URI /BankApp/accessdenied.html
in Corresponding Map Value field.",
        "propertyOrder" : 2700,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        }
    },
    "type" : "object",
    "exampleValue" : ""
},
"sessionAttributeMap" : {
    "title" : "Session Attribute Mapping",
    "description" : "Maps the session attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.session.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of session attribute UserToken under name CUSTOM-userid: enter UserToken in Map
Key field, and enter CUSTOM-userid in Corresponding Map Value field.",
    "propertyOrder" : 9000,
    "required" : false,
    "patternProperties" : {
        ".*" : {
            "type" : "string"
        }
    }
},
"type" : "object",
"exampleValue" : ""
},
"notEnforcedIps" : {
    "title" : "Not Enforced Client IP List",
    "description" : "No authentication and authorization protection from agent
are required for the requests coming from these client IP addresses. (property name:
com.sun.identity.agents.config.notenforced.ip) <br>Hot-swap: Yes <br> Examples: <br> 192.18.145.*
<br> 192.18.146.123",
    "propertyOrder" : 7900,
    "required" : false,

```

```

    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "notEnforcedRuleCompoundSeparator" : {
    "title" : "Not Enforced Compound Rule Separator",
    "description" : "Specifies a separator for not enforced compound rules (Agent 5 only). The
format for compound rules requires a list of IP rules, a separator (by default the | character),
and a list of URI rules. For example, GET 192.168.1.1-192.168.4.3 | /images/* Configure a
different separator (for example, &&) when working with the REGEX keyword to avoid invalid regular
expressions.",
    "propertyOrder" : 7450,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "invertNotEnforcedUris" : {
    "title" : "Invert Not Enforced URIs",
    "description" : "Inverts protection of URIs specified in Not Enforced URIs list. When
set to true, it indicates that the URIs specified should be enforced and all other URIs should be
not enforced by the Agent. (property name: com.sun.identity.agents.config.notenforced.uri.invert)
<br>Hot-swap: Yes",
    "propertyOrder" : 7600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "privilegedSessionAttribute" : {
    "title" : "Privileged Session Attribute",
    "description" : "(Not used in Agent 5 onwards) <br>List of session property
names which hold privileged attributes for the authenticated user. (property name:
com.sun.identity.agents.config.privileged.session.attribute) <br>Hot-swap: Yes <br> Example: <br>
UserToken",
    "propertyOrder" : 9700,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "shortenedPrivilegeAttributeValues" : {
    "title" : "Shortened privilege attribute values",
    "description" : "When using privileged attribute type, this setting will ensure that
the membership details will be stored in a shortened format and not in the default universal ID
format.<br><br>By default the agent maps identity memberships using their universal IDs (e.g.
id=admin,ou=group,dc=openam,dc=forgerock,dc=org), however this may not be always acceptable. Using
this setting the identity membership details will be mapped in a shortened format, only including the
group's/role's name (e.g. admin). Be aware that in case there are both roles and groups in the data
store, this setting will make them indistinguishable from each other, i.e. if there is a group and a
role with the same name it will not be possible to differentiate them.",
    "propertyOrder" : 13600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "continuousSecurityCookies" : {

```

```

    "title" : "Continuous Security Cookies",
    "description" : "The name of the cookies to be sent as part of the payload during policy
evaluation, which can be accessed via the 'environment' variable in a policy script. The 'key' is
the name of the cookie to be sent, and the 'value' is the name which it will appear as in the policy
evaluation script. It is possible to map multiple cookies to the same name (they will simply appear
as an array in the evaluation script). If the cookie doesn't exist, then the empty string will be
sent.",
    "propertyOrder" : 3210,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "logoutRequestParameters" : {
    "title" : "Logout Request Parameter",
    "description" : "An application-specific Map that identifies a parameter
which when present in the HTTP request indicates a logout event. (property name:
com.sun.identity.agents.config.logout.request.param) <br>Valid key: the web application name.
<br>Valid value: the logout request parameter. <br>For this property, a global value can be set to
apply to all the applications that don't have their own specific logout request parameter. <br>Hot-
swap: Yes <br> Examples: <br>To set a global application logout request parameter: leave Map Key
field empty, and enter the global application logout request parameter logoutparam in Corresponding
Map Value field. <br> To set the logout request parameter for application BankApp: enter BankApp in
Map Key field, and enter the logout request parameter logoutparam in Corresponding Map Value field.",
    "propertyOrder" : 6100,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "defaultPrivilegedAttributes" : {
    "title" : "Default Privileged Attribute",
    "description" : "(Not used in Agent 5 onwards) <br>List of privileged
attributes that will be granted to all users who have a valid AM session. (property name:
com.sun.identity.agents.config.default.privileged.attribute) <br>Hot-swap: Yes <br> Example: <br>
AUTHENTICATED_USERS",
    "propertyOrder" : 9400,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "invertNotEnforcedIps" : {
    "title" : "Not Enforced IP Invert List",
    "description" : "Client IP Addresses to invert protection of IP
addresses listed in the related Not Enforced Client IP List. (property name:
com.sun.identity.agents.config.notenforced.ip.invert) <br>Hot-swap: Yes",
    "propertyOrder" : 8000,
    "required" : false,

```

```

    "type" : "boolean",
    "exampleValue" : ""
  },
  "privilegedAttributeMappingEnabled" : {
    "title" : "Enable Privileged Attribute Mapping",
    "description" : "(Not used in Agent 5 onwards) <br>Enable a mapping from
the original value of an attribute to another value. To satisfy container-specific
restrictions on character set being used in certain configuration files. (property name:
com.sun.identity.agents.config.privileged.attribute.mapping.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 9800,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "privilegedAttributeType" : {
    "title" : "Privileged Attribute Type",
    "description" : "(Not used in Agent 5 onwards) <br>List of
privileged attribute types that will be fetched for each user. (property name:
com.sun.identity.agents.config.privileged.attribute.type) <br>Hot-swap: Yes <br> Example: <br>
Group",
    "propertyOrder" : 9500,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "loginErrorUri" : {
    "title" : "Login Error URI",
    "description" : "List of absolute URIs corresponding to an application's web.xml form-error-
page element. (property name: com.sun.identity.agents.config.login.error.uri) <br>Hot-swap: Yes <br>
Example: <br> /BankApp/jsp/error.jsp",
    "propertyOrder" : 2900,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "notEnforcedUriRefreshSessionIdleTime" : {
    "title" : "Refresh Session Idle Time",
    "description" : "Indicates if opensso session idle time should be refreshed or reset for not
enforced URIs. (property name: com.sun.identity.agents.config.notenforced.refresh.session.idletime)
<br>Hot-swap: Yes",
    "propertyOrder" : 8600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "customLogoutHandlers" : {
    "title" : "Custom Logout Handler",
    "description" : "Application specific logout handler to log out a user with the application
server. (property name: com.sun.identity.agents.config.logout.handler) <br>Valid key: the web
application name. <br>Valid value: the logout handler class name. <br>Hot-swap: Yes <br> Example:
<br><br>To set logout handler for application BankApp: enter BankApp in Map Key field, and enter logout
handler class name BankLogoutHandler in Corresponding Map Value field.",
    "propertyOrder" : 3300,

```

```

"required" : false,
"patternProperties" : {
  ".*" : {
    "type" : "string"
  }
},
"type" : "object",
"exampleValue" : ""
},
"customVerificationHandlers" : {
  "title" : "Custom Verification Handler",
  "description" : "Application specific verification handler to validate the user credentials
with the local repository. (property name: com.sun.identity.agents.config.verification.handler)
<br>Valid key: the web application name. <br>Valid value: the verification handler class name.
<br>Hot-swap: Yes <br> Example: <br> To set verification handler for application BankApp: enter
BankApp in Map Key field, and enter verification handler class name BankVerificationHandler in
Corresponding Map Value field.",
  "propertyOrder" : 3400,
  "required" : false,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"cookieAttributeUrlEncoded" : {
  "title" : "Attribute Cookie Encode",
  "description" : "Indicates if the value of the attribute should be URL encoded before being
set as a cookie. (property name: com.sun.identity.agents.config.attribute.cookie.encode) <br>Hot-
swap: Yes",
  "propertyOrder" : 8500,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"customAuthenticationHandlers" : {
  "title" : "Custom Authentication Handler",
  "description" : "Application specific authentication handler to authenticate the logged
on user with the application server. (property name: com.sun.identity.agents.config.auth.handler)
<br>Valid key: the web application name. <br>Valid value: the authentication handler class
name. <br>Hot-swap: Yes <br>Example: <br>To set authentication handler for application BankApp:
enter BankApp in Map Key field, and enter authentication handler class name BankAuthHandler in
Corresponding Map Value field.",
  "propertyOrder" : 3200,
  "required" : false,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"notEnforcedUris" : {
  "title" : "Not Enforced URIs",

```

```

        "description" : "List of URIs for which protection is not enforced by the Agent. (property
        name: com.sun.identity.agents.config.notenforced.uri) <br>Hot-swap: Yes <br> Examples: <br> /BankApp/
        public/* <br> /BankApp/images/*",
        "propertyOrder" : 7500,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "profileAttributeMap" : {
        "title" : "Profile Attribute Mapping",
        "description" : "Maps the profile attributes to be populated
        under specific names for the currently authenticated user. (property name:
        com.sun.identity.agents.config.profile.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
        populate the value of profile attribute cn under name CUSTOM-Common-Name: enter cn in Map Key field,
        and enter CUSTOM-Common-Name in Corresponding Map Value field. <br> To populate the value of profile
        attribute mail under name CUSTOM-Email: enter mail in Map Key field, and enter CUSTOM-Email in
        Corresponding Map Value field.",
        "propertyOrder" : 8800,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        }
    },
    "type" : "object",
    "exampleValue" : ""
},
"privilegedAttributeMap" : {
    "title" : "Privileged Attribute Mapping",
    "description" : "(Not used in Agent 5 onwards) <br>Map if using Enable Privileged
    Attribute Mapping. (property name: com.sun.identity.agents.config.privileged.attribute.mapping)
    <br>Hot-swap: Yes <br> Examples: <br> To map UUID id=manager,ou=group,dc=openam,dc=forgerock,dc=org
    to the principal name am_manager_role specified in webapp's deployment descriptor: enter
    id=manager,ou=group,dc=openam,dc=forgerock,dc=org in Map Key field, and enter am_manager_role in
    Corresponding Map Value field. <br> To map UUID id=employee,ou=group,dc=openam,dc=forgerock,dc=org
    to the principal name am_employee_role specified in webapp's deployment descriptor: enter
    id=employee,ou=group,dc=openam,dc=forgerock,dc=org in Map Key field, and enter am_employee_role in
    Corresponding Map Value field.",
    "propertyOrder" : 9900,
    "required" : false,
    "patternProperties" : {
        ".*" : {
            "type" : "string"
        }
    }
},
"type" : "object",
"exampleValue" : ""
},
"headerAttributeDateFormat" : {
    "title" : "Fetch Attribute Date Format",
    "description" : "Format of date attribute values to be used when the attribute is
    being set as HTTP header. Format is based on java.text.SimpleDateFormat. (property name:
    com.sun.identity.agents.config.attribute.date.format) <br>Hot-swap: Yes",
    "propertyOrder" : 8400,
    "required" : false,
    "type" : "string",

```

```

    "exampleValue" : ""
  },
  "privilegedAttributesToLowerCase" : {
    "title" : "Privileged Attributes To Lower Case",
    "description" : "(Not used in Agent 5 onwards) <br>Maps the privileged
attribute types to whether they should be converted to lowercase. (property name:
com.sun.identity.agents.config.privileged.attribute.lowercase) <br> Valid Keys: the privileged
attribute types, such as Group, Role. <br>Valid value: true, false. <br>Hot-swap: Yes <br> Example:
<br> Enter Group in Map Key field, and enter false in Corresponding Map Value field.",
    "propertyOrder" : 9600,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  }
}
},
"globalJ2EEAgentConfig" : {
  "type" : "object",
  "title" : "Global",
  "propertyOrder" : 0,
  "properties" : {
    "auditLogLocation" : {
      "title" : "Audit Log Location",
      "description" : "Specifies where audit messages should be logged. (property name:
com.sun.identity.agents.config.log.disposition) <br>Hot-swap: Yes",
      "propertyOrder" : 1600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "localAuditRotationSize" : {
      "title" : "Local Audit Log Rotation Size",
      "description" : "Size limit when a local audit log file is rotated to a new file. (property
name: com.sun.identity.agents.config.local.log.size) <br>Hot-swap: Yes",
      "propertyOrder" : 1900,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "customResponseHeader" : {
      "title" : "Custom Response Header",
      "description" : "Map specifies the custom headers that are set by the Agent on the client
browser. The key is the header name and the value represents the header value. (property name:
com.sun.identity.agents.config.response.header) <br>Hot-swap: Yes <br> Example: <br> To set the
custom header Cache-Control to value no-cache: enter Cache-Control in Map Key field, and enter no-
cache in Corresponding Map Value field.",
      "propertyOrder" : 7000,
      "required" : false,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
    }
  }
}

```

```

        "exampleValue" : ""
    },
    "auditAccessType" : {
        "title" : "Audit Access Types",
        "description" : "Types of messages to log based on user URL access attempts. (property name:
com.sun.identity.agents.config.audit.accesstype) <br>Hot-swap: Yes",
        "propertyOrder" : 1500,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "httpSessionBinding" : {
        "title" : "HTTP Session Binding",
        "description" : "If true will invalidate the http session when login has failed,
user has no SSO session, or principal user name does not match SSO user name. (property name:
com.sun.identity.agents.config.httpsession.binding) <br>Hot-swap: Yes",
        "propertyOrder" : 3500,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "cdssoRootUrl" : {
        "title" : "Agent Root URL for CDSSO",
        "description" : "The agent root URL for CDSSO. The valid value is in the following format:
<br>protocol://hostname:port/<br>The protocol represents the protocol used, such as http or https.
The hostname represents the host name of the machine on which the agent resides. The port represents
the port number on which the agent is installed. The slash following the port number is required.",
        "propertyOrder" : 22700,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "fqdnDefault" : {
        "title" : "FQDN Default",
        "description" : "Fully qualified hostname that the users should use in order to access
resources. (property name: com.sun.identity.agents.config.fqdn.default) <br>Hot-swap: Yes",
        "propertyOrder" : 6500,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "filterMode" : {
        "title" : "Agent Filter Mode",
        "description" : "Specifies the mode of operation of the Filter. (property name:
com.sun.identity.agents.config.filter.mode) <br>Valid key: the web application name. <br>Valid
values: ALL, J2EE_POLICY (Not used in Agent 5 onwards), URL_POLICY, SSO_ONLY, NONE <br>For this
property, a global value can be set to apply to all the applications that don't have their own
specific filter mode. <br>Hot-swap: No <br>Examples: <br>To set ALL as the global filter mode:
leave Map Key field empty, and enter ALL in Corresponding Map Value field. <br>To set URL_POLICY
as the filter mode for application BankApp: enter BankApp in Map Key field, and enter URL_POLICY in
Corresponding Map Value field.",
        "propertyOrder" : 500,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        }
    }

```



```

    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"loginAttemptLimit" : {
  "title" : "Login Attempt Limit",
  "description" : "Limit of failed login attempts for a user's single browser session until triggering the blocking of the user request. Value of 0 disables this feature. (property name: com.sun.identity.agents.config.login.attempt.limit) <br>Hot-swap: Yes",
  "propertyOrder" : 4400,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"fqdnMapping" : {
  "title" : "FQDN Virtual Host Map",
  "description" : "Maps virtual, invalid, or partial hostnames, and IP addresses to the FQDN to access protected resources. (property name: com.sun.identity.agents.config.fqdn.mapping) <br>Hot-swap: Yes <br> Examples: <br> To map the partial hostname myserver to myserver.mydomain.com: enter myserver in the Map Key field and myserver.mydomain.com in the Corresponding Map Value field. To map a virtual server rst.hostname.com that points to the actual server abc.hostname.com: enter valid1 in the Map Key field and rst.hostname.com in the Corresponding Map Value field.",
  "propertyOrder" : 6600,
  "required" : false,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  }
},
"type" : "object",
"exampleValue" : ""
},
"websocketConnectionIntervalInMinutes" : {
  "title" : "Web Socket Connection Interval",
  "description" : "Interval in minutes by which agents reopen their web socket connection to ensure a fair distribution of connections across AM servers. (Agent 5 only).",
  "propertyOrder" : 12105,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"fqdnCheck" : {
  "title" : "FQDN Check",
  "description" : "Enables checking of fqdn default value and fqdn map values. (property name: com.sun.identity.agents.config.fqdn.check.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 6400,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"agentNotificationUrl" : {
  "title" : "Agent Notification URL",
  "description" : "URL used by agent to register notification listeners. (property name: com.sun.identity.client.notification.url) <br>Hot-swap: No",
  "propertyOrder" : 300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}

```

```

    },
    "configurationReloadInterval" : {
      "title" : "Configuration Reload Interval",
      "description" : "Interval in seconds between configuration reloads. (property name:
com.sun.identity.agents.config.load.interval) <br>Hot-swap: Yes",
      "propertyOrder" : 1200,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "userTokenName" : {
      "title" : "User Token Name",
      "description" : "Session property name for user-ID of the authenticated user in session.
(property name: com.sun.identity.agents.config.user.token) <br>Hot-swap: Yes",
      "propertyOrder" : 900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "remoteLogFilename" : {
      "title" : "Remote Log File Name",
      "description" : "Name of file stored on AM server that contains agent audit messages.
(property name: com.sun.identity.agents.config.remote.logfile) <br>Hot-swap: Yes",
      "propertyOrder" : 1700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "status" : {
      "title" : "Status",
      "description" : "Status of the agent configuration.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "userAttributeName" : {
      "title" : "User Attribute Name",
      "description" : "Name of the attribute which contains the user-ID. (property name:
com.sun.identity.agents.config.user.attribute.name) <br>Hot-swap: Yes",
      "propertyOrder" : 700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "userPrincipalFlag" : {
      "title" : "User Principal Flag",
      "description" : "Use principal instead of just the user-ID for authenticating the user.
(property name: com.sun.identity.agents.config.user.principal) <br>Hot-swap: Yes",
      "propertyOrder" : 800,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "debugLevel" : {
      "title" : "Agent Debug Level",
      "description" : "Specifies type of agent debug messages to log. (property name:
com.iplanet.services.debug.level) <br>Hot-swap: Yes",
      "propertyOrder" : 10000,

```

```

    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "localAuditLogRotation" : {
    "title" : "Rotate Local Audit Log",
    "description" : "Flag to indicate that audit log files should be rotated when reaching a
certain size. (property name: com.sun.identity.agents.config.local.log.rotate) <br>Hot-swap: Yes",
    "propertyOrder" : 1800,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "jwtName" : {
    "title" : "JWT Cookie Name",
    "description" : "The name used by the agent to set the OIDC JWT on the user's browser.
(Agent 5 only).",
    "propertyOrder" : 11201,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "agentConfigChangeNotificationsEnabled" : {
    "title" : "Agent Configuration Change Notification",
    "description" : "Enable agent to receive notification messages from AM server for
configuration changes. (property name: com.sun.identity.agents.config.change.notification.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 12100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "redirectAttemptLimit" : {
    "title" : "Redirect Attempt Limit",
    "description" : "Number of successive single point redirects that a user can make using a
single browser session which will trigger the blocking of the user request. Set to 0 to disable this
feature. (property name: com.sun.identity.agents.config.redirect.attempt.limit) <br>Hot-swap: Yes",
    "propertyOrder" : 7100,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "userMappingMode" : {
    "title" : "User Mapping Mode",
    "description" : "Specifies mechanism agent uses to determine user-ID. (property name:
com.sun.identity.agents.config.user.mapping.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"amServicesJ2EEAgent" : {
  "type" : "object",
  "title" : "AM Services",
  "propertyOrder" : 3,
  "properties" : {
    "authServiceHost" : {

```

```

        "title" : "AM Authentication Service Host Name",
        "description" : "Host name to be used by the AM authentication service. (property name:
com.ipplanet.am.server.host) <br>Hot-swap: No",
        "propertyOrder" : 11000,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "userDataCacheNotifications" : {
        "title" : "Enable Notification of User Data Caches",
        "description" : "Enable notifications for amsdk and IdRepo Caches. (property name:
com.sun.identity.idm.remote.notification.enabled) <br>Hot-swap: No",
        "propertyOrder" : 10500,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "policyNotifications" : {
        "title" : "Enable Policy Notifications",
        "description" : "Enable Notifications for remote policy client. (property name:
com.sun.identity.agents.notification.enabled) <br>Hot-swap: No",
        "propertyOrder" : 11200,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "loginUrlPrioritized" : {
        "title" : "Login URL Prioritized",
        "description" : "Specifies if failover sequence for Login URLs or CDSSO
URLs should be prioritized as defined in the AM Login URL list. (property name:
com.sun.identity.agents.config.login.url.prioritized) <br>Hot-swap: Yes",
        "propertyOrder" : 3800,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "logoutProbeTimeout" : {
        "title" : "Logout URL Probe Timeout",
        "description" : "The connect timeout value in milliseconds, if also Logout URL Probe is set
to true. (property name: com.sun.identity.agents.config.logout.url.probe.timeout) <br>Hot-swap: Yes",
        "propertyOrder" : 12700,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "conditionalLoginUrl" : {
        "title" : "AM Conditional Login URL",
        "description" : "(Only used in Agent 5 onwards) (property name:
org.forgerock.openam.agents.config.conditional.login.url) <br>Hot-swap: Yes <br> Examples: <br>
match?url?param1=value1&param2=value2 <br> match/path|?param1=value1&param2=value2&param3=value3",
        "propertyOrder" : 4010,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "policyActionBooleanValues" : {

```

```

        "title" : "Policy Client Boolean Action Values",
        "description" : "Boolean action values for policy action names. (property name:
com.sun.identity.policy.client.booleanActionValues) <br>Hot-swap: No",
        "propertyOrder" : 11500,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "urlPolicyEnvJsessionParameters" : {
        "title" : "URL Policy Env jsession Parameters",
        "description" : "List of HTTP SESSION attributes whose names and values will
be set in the environment map for URL policy evaluation at AM server. (property name:
com.sun.identity.agents.config.policy.env.jsession.param) <br>Hot-swap: Yes <br> Examples: <br> name
<br> phonenumber",
        "propertyOrder" : 12000,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "amLogoutUrl" : {
        "title" : "AM Logout URL",
        "description" : "AM logout page URL. (property name:
com.sun.identity.agents.config.logout.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Logout",
        "propertyOrder" : 12400,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "serviceDataCacheTime" : {
        "title" : "Service Data Cache Time",
        "description" : "Cache update time in minutes for service configuration data. If set to '0'
no updates happen. (property name: com.sun.identity.sm.cacheTime) <br>Hot-swap: No",
        "propertyOrder" : 10800,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "serviceDataCacheNotifications" : {
        "title" : "Enable Notification of Service Data Caches",
        "description" : "Enable the notifications for service management caches. (property name:
com.sun.identity.sm.notification.enabled) <br>Hot-swap: No",
        "propertyOrder" : 10700,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "useRedirectForCompositeAdvice" : {
        "title" : "Use HTTP-Redirect for composite advice",
        "description" : "Configure remote policy client to use HTTP-redirect instead of HTTP-POST
for composite advices. (property name: com.sun.identity.agents.config.policy.advice.use.redirect)
<br>Hot-swap: Yes",
        "propertyOrder" : 13000,
    }

```

```
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "probeLoginUrl" : {
    "title" : "Login URL Probe",
    "description" : "Specifies if agent will check the availability of these urls before
redirecting to them. (property name: com.sun.identity.agents.config.login.url.probe.enabled) <br>Hot-
swap: Yes",
    "propertyOrder" : 3900,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "UserDataCachePollingTime" : {
    "title" : "User Data Cache Polling Time",
    "description" : "Cache update time in minutes for user management data. If set to '0' no
updates happen. (property name: com.iplanet.am.sdk.remote.pollingTime) <br>Hot-swap: No",
    "propertyOrder" : 10600,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "authServicePort" : {
    "title" : "AM Authentication Service Port",
    "description" : "Port to be used by the AM authentication service. (property name:
com.iplanet.am.server.port) <br>Hot-swap: No",
    "propertyOrder" : 11100,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "urlPolicyEnvGetParameters" : {
    "title" : "URL Policy Env GET Parameters",
    "description" : "List of HTTP GET request parameters whose names and values will
be set in the environment map for URL policy evaluation at AM server. (property name:
com.sun.identity.agents.config.policy.env.get.param) <br>Hot-swap: Yes <br> Examples: <br> name <br>
phonenummer",
    "propertyOrder" : 11800,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "amLoginUrl" : {
    "title" : "AM Login URL",
    "description" : "AM login page URL. (property name:
com.sun.identity.agents.config.login.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Login",
    "propertyOrder" : 3700,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
}
```

```

"policyClientClockSkew" : {
  "title" : "Policy Client Clock Skew",
  "description" : "Time in seconds which is allowed to accommodate the time difference
between the AM server machine and the remote policy client machine. (property name:
com.sun.identity.policy.client.clockSkew) <br>Hot-swap: No",
  "propertyOrder" : 11700,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"clientPollingPeriod" : {
  "title" : "Client Polling Period",
  "description" : "(Not used in Agent 5 onwards) <br>Time in seconds after which the
session client will request update of cached session information from the server. (property name:
com.iplanet.am.session.client.polling.period) <br>Hot-swap: No",
  "propertyOrder" : 10300,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"conditionalLogoutUrl" : {
  "title" : "AM Conditional Logout URL",
  "description" : "(Only used in Agent 5 onwards) (property name:
org.forgerock.openam.agents.config.conditional.logout.url) <br>Hot-swap: Yes <br> Examples: <br>
match?url?param1=value1&param2=value2 <br> match/path|?param1=value1&param2=value2&param3=value3",
  "propertyOrder" : 12550,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"logoutUrlPrioritized" : {
  "title" : "Logout URL Prioritized",
  "description" : "Specifies if failover sequence for Logout URLs
should be prioritized as defined in the AM Login URL list. (property name:
com.sun.identity.agents.config.logout.url.prioritized) <br>Hot-swap: Yes",
  "propertyOrder" : 12500,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"policyClientCacheMode" : {
  "title" : "Policy Client Cache Mode",
  "description" : "Mode of caching to be used by remote policy client. (property name:
com.sun.identity.policy.client.cacheMode) <br>Hot-swap: No",
  "propertyOrder" : 11400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"policyEvaluationRealm" : {
  "title" : "Realm",
  "description" : "Which realm to start evaluating from. (property name:
org.forgerock.openam.agents.config.policy.evaluation.realm) <br>Hot-swap: Yes",
  "propertyOrder" : 5400,
  "required" : false,
  "type" : "string",

```

```

    "exampleValue" : ""
  },
  "enableClientPolling" : {
    "title" : "Enable Client Polling",
    "description" : "Specifies if the session client must use polling for
updating session information and not depend upon server notifications. (property name:
com.ipplanet.am.session.client.polling.enable) <br>Hot-swap: No",
    "propertyOrder" : 10200,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "authServiceProtocol" : {
    "title" : "AM Authentication Service Protocol",
    "description" : "Protocol to be used by the AM authentication service. (property name:
com.ipplanet.am.server.protocol) <br>Hot-swap: No",
    "propertyOrder" : 10900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "policyEvaluationApplication" : {
    "title" : "Application",
    "description" : "Which application contains the policies to evaluate with. (property name:
org.forgerock.openam.agents.config.policy.evaluation.application) <br>Hot-swap: Yes",
    "propertyOrder" : 5500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "loginProbeTimeout" : {
    "title" : "Login URL Probe Timeout",
    "description" : "The connect timeout value in milliseconds, if also Login URL Probe is set
to true. (property name: com.sun.identity.agents.config.login.url.probe.timeout) <br>Hot-swap: Yes",
    "propertyOrder" : 4000,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "policyClientResourceComparators" : {
    "title" : "Policy Client Resource Comparators",
    "description" : "Resource Comparators to be used for different service names. (property
name: com.sun.identity.policy.client.resourceComparators) <br>Hot-swap: No",
    "propertyOrder" : 11600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "urlPolicyEnvPostParameters" : {
    "title" : "URL Policy Env POST Parameters",
    "description" : "List of HTTP POST request parameters whose names and values
will be set in the environment map for URL policy evaluation at AM server. (property name:
com.sun.identity.agents.config.policy.env.post.param) <br>Hot-swap: Yes <br> Examples: <br> name <br>
phonenumber",
    "propertyOrder" : 11900,
    "required" : false,
    "items" : {
      "type" : "string"
    }
  },
},

```



```

        "type" : "array",
        "exampleValue" : ""
    },
    "policyClientPollingInterval" : {
        "title" : "Policy Client Polling Interval",
        "description" : "Duration in minutes after which the cached entries are refreshed by remote
policy client. (property name: com.sun.identity.agents.polling.interval) <br>Hot-swap: No",
        "propertyOrder" : 11300,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "probeLogoutUrl" : {
        "title" : "Logout URL Probe",
        "description" : "Specifies if agent will check the availability of these urls before
redirecting to them. (property name: com.sun.identity.agents.config.logout.url.probe.enabled)
<br>Hot-swap: Yes",
        "propertyOrder" : 12600,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"advancedJ2EEAgentConfig" : {
    "type" : "object",
    "title" : "Advanced",
    "propertyOrder" : 5,
    "properties" : {
        "webServiceResponseProcessor" : {
            "title" : "Web Service Response Processor",
            "description" : "An implementation class of interface
com.sun.identity.agents.filter.IWebServiceResponseProcessor that can be used to process the web-
service responses. (property name: com.sun.identity.agents.config.webservice.responseprocessor)
<br>Hot-swap: Yes",
            "propertyOrder" : 2400,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "clientIpHeader" : {
            "title" : "Client IP Address Header",
            "description" : "HTTP header name that holds the IP address of the client. (property name:
com.sun.identity.agents.config.client.ip.header) <br>Hot-swap: Yes",
            "propertyOrder" : 1000,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "xssDetectionRedirectUri" : {
            "title" : "XSS detection redirect URI",
            "description" : "An application-specific Map that identifies a URI of the customized page if
XSS code has been detected. (property name: com.sun.identity.agents.config.xss.redirect.uri) <br>Hot-
swap: Yes <br>Examples: <br>To set a redirect target for application BankApp: enter BankApp in Map Key
field, and enter a redirect URI in Corresponding Map Value field.",
            "propertyOrder" : 12900,
            "required" : false,
            "patternProperties" : {
                ".*" : {

```

```

        "type" : "string"
    },
    },
    "type" : "object",
    "exampleValue" : ""
},
"clientHostnameHeader" : {
    "title" : "Client Hostname Header",
    "description" : "HTTP header name that holds the Hostname of the client. (property name: com.sun.identity.agents.config.client.hostname.header) <br>Hot-swap: Yes",
    "propertyOrder" : 1100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
},
"webServiceProcessGetEnabled" : {
    "title" : "Web Service Process GET Enable",
    "description" : "Flag to indicates if the processing of HTTP GET requests for Web Service endpoints is enabled. (property name: com.sun.identity.agents.config.webservice.process.get.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 2200,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
},
"customProperties" : {
    "title" : "Custom Properties",
    "description" : "Additional properties that allow users to augment the set of properties supported by agent. (property name: com.sun.identity.agents.config.freeformproperties) <br>Hot-swap: Yes <br> Examples: <br> customproperty=custom-value1 <br> customlist[0]=customlist-value-0 <br> customlist[1]=customlist-value-1 <br> custommap[key1]=custommap-value-1 <br> custommap[key2]=custommap-value-2",
    "propertyOrder" : 12200,
    "required" : false,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"postDataPreserveCacheEntryMaxEntries" : {
    "title" : "PDP Maximum Number of Cache Entries",
    "description" : "Maximum number of entries to hold in the PDP cache (Property name: org.forgerock.openam.agents.config.postdata.preserve.cache.entry.max.entries) (Agent 5 only).",
    "propertyOrder" : 13550,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
},
"alternativeAgentProtocol" : {
    "title" : "Alternative Agent Protocol",
    "description" : "Protocol being used (http/https) by the client browsers to communicate with the Agent protected server if different from the actual protocol used by the server. (property name: com.sun.identity.agents.config.agent.protocol) <br>Hot-swap: Yes",
    "propertyOrder" : 4300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
},
},

```

```

"webServiceAuthorizationErrorContentFile" : {
  "title" : "Web Service Authorization Error Content File",
  "description" : "The name of file that contains content used by the
Agent to generate an authorization error fault for clients. (property name:
com.sun.identity.agents.config.webservice.autherror.content) <br>Hot-swap: Yes",
  "propertyOrder" : 2600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"webServiceEnabled" : {
  "title" : "Web Service Enable",
  "description" : "Flag specifies if Web Service processing is enabled. (property name:
com.sun.identity.agents.config.webservice.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 2000,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"alternativeAgentHostname" : {
  "title" : "Alternative Agent Host Name",
  "description" : "Host name identifying the Agent protected server to the client browsers
if different from the actual host name. (property name: com.sun.identity.agents.config.agent.host)
<br>Hot-swap: Yes",
  "propertyOrder" : 4100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"jbossWebAuthenticationAvailable" : {
  "title" : "Web Authentication Available",
  "description" : "(Not used in Agent 5 onwards) <br>Enable agent to make programmatic
authentication with the JBoss web container using WebAuthentication feature. (property name:
com.sun.identity.agents.config.jboss.webauth.available) <br>Hot-swap: Yes",
  "propertyOrder" : 12300,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"postDataCacheTtl" : {
  "title" : "PDP entry TTL",
  "description" : "This value tells how long a given POST entry should be
stored in the local cache (in milliseconds), default value is 300000. (property name:
com.sun.identity.agents.config.postdata.preserve.cache.entry.ttl)",
  "propertyOrder" : 13300,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"webServiceAuthenticator" : {
  "title" : "Web Service Authenticator",
  "description" : "An implementation class of interface
com.sun.identity.agents.filter.IWebServiceAuthenticator that can be used to authenticate web-service
requests. (property name: com.sun.identity.agents.config.webservice.authenticator) <br>Hot-swap:
Yes",
  "propertyOrder" : 2300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}

```

```

    },
    "webServiceEndpoints" : {
      "title" : "Web Service End Points",
      "description" : "A list of Web Application end points that represent Web Services. (property
name: com.sun.identity.agents.config.webservice.endpoint) <br>Hot-swap: Yes",
      "propertyOrder" : 2100,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "alternativeAgentPort" : {
      "title" : "Alternative Agent Port Name",
      "description" : "Port number identifying the Agent protected server listening
port to the client browsers if different from the actual listening port. (property name:
com.sun.identity.agents.config.agent.port) <br>Hot-swap: Yes",
      "propertyOrder" : 4200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "postDataStickySessionMode" : {
      "title" : "PDP Sticky session mode",
      "description" : "The PDP mechanism needs sticky loadbalancing, the URL mode
will append a querystring, while the Cookie mode will create a cookie. (property name:
com.sun.identity.agents.config.postdata.preserve.stickysession.mode)",
      "propertyOrder" : 13400,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "postDataStickySessionKeyValue" : {
      "title" : "PDP Sticky session key-value",
      "description" : "The provided key-value pair will be used for adding
to the URL or creating the cookie. <br>Example: <br>Set 'lb=server1' to append
to the querystring or to have 'lb' cookie with 'server1' value. (property name:
com.sun.identity.agents.config.postdata.preserve.stickysession.value)",
      "propertyOrder" : 13500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "postDataPreserveCacheEntryMaxTotalSizeMb" : {
      "title" : "PDP Maximum Cache Size",
      "description" : "Maximum size of the PDP cache, in megabytes (Property name:
org.forgerock.openam.agents.config.postdata.preserve.cache.entry.max.total.size.mb). (Agent 5 only)",
      "propertyOrder" : 13600,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "missingPostDataPreservationEntryUri" : {
      "title" : "Missing PDP entry URI",
      "description" : "An application-specific URI Map that is used in case the referenced
PDP entry cannot be found in the local cache (due to ttl). In such cases it will redirect
to the specified URI, otherwise it will show a HTTP 403 Forbidden error. (property name:
com.sun.identity.agents.config.postdata.preservce.cache.noentry.url)<br>Examples: <br>To set a

```

```

redirect target for application BankApp: enter Bankapp in Map Key field and enter a redirect URI in
corresponding Map Value field.",
    "propertyOrder" : 13200,
    "required" : false,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"possibleXssCodeElements" : {
    "title" : "Possible XSS code elements",
    "description" : "If one of these strings occurs in the request, the client is redirected to
an error page. (property name: com.sun.identity.agents.config.xss.code.elements) <br>Hot-swap: Yes",
    "propertyOrder" : 12800,
    "required" : false,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"webServiceInternalErrorContentFile" : {
    "title" : "Web Service Internal Error Content File",
    "description" : "The name of file that contains content used by
the Agent to generate an internal error fault for clients. (property name:
com.sun.identity.agents.config.webservice.internalerror.content) <br>Hot-swap: Yes",
    "propertyOrder" : 2500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
},
"postDataPreservation" : {
    "title" : "Post Data Preservation enabled",
    "description" : "Post Data Preservation functionality basically stores any POST
data before redirecting the user to the login screen and after successful login the agent
will generate a page that autosubmits the same POST to the original URL. (property name:
com.sun.identity.agents.config.postdata.preserve.enable)",
    "propertyOrder" : 13100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
}
}
},
"ssoJ2EEAgentConfig" : {
    "type" : "object",
    "title" : "SSO",
    "propertyOrder" : 2,
    "properties" : {
        "cdssoRedirectUri" : {
            "title" : "CDSSO Redirect URI",
            "description" : "An intermediate URI that is used by the Agent for processing CDSSO
requests. (property name: com.sun.identity.agents.config.cdsso.redirect.uri) <br>Hot-swap: Yes",
            "propertyOrder" : 5100,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        }
    }
},

```

```

"ssoCacheEnabled" : {
  "title" : "SSO Cache Enable",
  "description" : "Specifies if the SSO Cache is active for the agent.
Cache is used through public APIs exposed by the agent SDK. (property name:
com.sun.identity.agents.config.amsso.cache.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 4500,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"cdssoClockSkew" : {
  "title" : "CDSSO Clock Skew",
  "description" : "Time in seconds to be used by the Agent to determine the validity of the
CDSSO AuthnResponse assertion. (property name: com.sun.identity.agents.config.cdsso.clock.skew)
<br>Hot-swap: Yes",
  "propertyOrder" : 5300,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"cdsso" : {
  "title" : "Cross Domain SSO",
  "description" : "Enables Cross Domain Single SignOn. (property name:
com.sun.identity.agents.config.cdsso.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 5000,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"cdssoTrustedIdProvider" : {
  "title" : "CDSSO Trusted ID Provider",
  "description" : "List of AM Server/ID providers that should be trusted
by the agent, when evaluating the CDC Liberty Responses. (property name:
com.sun.identity.agents.config.cdsso.trusted.id.provider) <br>Hot-swap: Yes <br> Example: <br>
http://host:port/opensso/cdcservlet",
  "propertyOrder" : 5600,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"cookieResetNames" : {
  "title" : "Cookies Reset Name List",
  "description" : "Cookie names that will be reset by the Agent if Cookie Reset is enabled.
(property name: com.sun.identity.agents.config.cdsso.cookie.reset.name) <br>Hot-swap: Yes",
  "propertyOrder" : 4700,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"cdssoSecureCookies" : {
  "title" : "CDSSO Secure Enable",

```

```

    "description" : "The SSO Token cookie set by the agent in the different domains in CDSSO
mode will be marked secure. Only transmitted if the communications channel with host is a secure one.
(property name: com.sun.identity.agents.config.cdsso.secure.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 5700,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "amCookieName" : {
    "title" : "Cookie Name",
    "description" : "Name of the SSO Token cookie used between the AM server and the Agent.
(property name: com.iplanet.am.cookie.name) <br>Hot-swap: No",
    "propertyOrder" : 10100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "cdssoUrls" : {
    "title" : "CDSSO Servlet URL",
    "description" : "List of URLs of the available CDSSO controllers that may be used by the
Agent for CDSSO processing. (property name: com.sun.identity.agents.config.cdsso.cdcservlet.url)
<br>Hot-swap: Yes <br> Example: <br> http://host:port/opensso/cdcservlet",
    "propertyOrder" : 5200,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "cookieResetEnabled" : {
    "title" : "Cookie Reset",
    "description" : "Agent resets cookies in the response before redirecting to authentication.
(property name: com.sun.identity.agents.config.cookie.reset.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 4600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cookieResetDomains" : {
    "title" : "Cookies Reset Domain Map",
    "description" : "Maps cookie names specified in Cookie Reset Name List to value
being the domain of this cookie to be used when a reset event occurs. (property name:
com.sun.identity.agents.config.cookie.reset.domain) <br>Hot-swap: Yes",
    "propertyOrder" : 4800,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "cdssoDomainList" : {
    "title" : "CDSSO Domain List",
    "description" : "Domains for which cookies have to be set in a CDSSO scenario. (property
name: com.sun.identity.agents.config.cdsso.domain) <br>Hot-swap: Yes <br> Example: <br> .sun.com",
    "propertyOrder" : 5800,

```

```

        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "cookieResetPaths" : {
        "title" : "Cookies Reset Path Map",
        "description" : "Maps cookie names specified in Cookie Reset Name List to value
being the path of this cookie to be used when a reset event occurs. (property name:
com.sun.identity.agents.config.cookie.reset.path) <br>Hot-swap: Yes",
        "propertyOrder" : 4900,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    }
}
},
"miscJ2EEAgentConfig" : {
    "type" : "object",
    "title" : "Miscellaneous",
    "propertyOrder" : 4,
    "properties" : {
        "legacyUserAgentSupport" : {
            "title" : "Legacy User Agent Support Enable",
            "description" : "Enables support for legacy user agents (browser). (property name:
com.sun.identity.agents.config.legacy.support.enable) <br>Hot-swap: Yes",
            "propertyOrder" : 6700,
            "required" : false,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "localeCountry" : {
            "title" : "Locale Country",
            "description" : "(property name: com.sun.identity.agents.config.locale.country) <br>Hot-
swap: No",
            "propertyOrder" : 1400,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "portCheckEnabled" : {
            "title" : "Port Check Enable",
            "description" : "Indicates if port check functionality is enabled or disabled. (property
name: com.sun.identity.agents.config.port.check.enable) <br>Hot-swap: Yes",
            "propertyOrder" : 7200,
            "required" : false,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "encryptionProvider" : {
            "title" : "Encryption Provider",
    
```



```

    "description" : "Specifies the encryption provider implementation to be used by the Agent.
(property name: com.ipianet.security.encryptor) <br>Hot-swap: No",
    "propertyOrder" : 10400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "legacyUserAgentList" : {
    "title" : "Legacy User Agent List",
    "description" : "List of user agent header values that identify legacy
browsers. Entries in this list can have wild card character '*'. (property name:
com.sun.identity.agents.config.legacy.user.agent) <br>Hot-swap: Yes",
    "propertyOrder" : 6800,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "bypassPrincipallist" : {
    "title" : "Bypass Principal List",
    "description" : "List of principals that are bypassed by the Agent for authentication and
search purposes. (property name: com.sun.identity.agents.config.bypass.principal) <br>Hot-swap: Yes
<br> Examples: <br> guest <br> testuser",
    "propertyOrder" : 9300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "ignorePathInfo" : {
    "title" : "Ignore Path Info in Request URL",
    "description" : "The path info will be stripped from the request URL while doing Not
Enforced List check and url policy evaluation if the value is set to true. (property name:
com.sun.identity.agents.config.ignore.path.info) <br>Hot-swap: Yes",
    "propertyOrder" : 18600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "legacyRedirectUri" : {
    "title" : "Legacy User Agent Redirect URI",
    "description" : "An intermediate URI used by the Agent to redirect legacy user agent
requests. (property name: com.sun.identity.agents.config.legacy.redirect.uri) <br>Hot-swap: Yes",
    "propertyOrder" : 6900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "gotoParameterName" : {
    "title" : "Goto Parameter Name",
    "description" : "Property used only when CDSSO is enabled. Default value
should be changed only when the login URL has a landing page specified <br> Example :
com.sun.identity.agents.config.cdsso.cdcservlet.url = http://host:port/opensso/cdcservlet?
goto=http://agent:port/landing.jsp <br> The parameter is used by the Agent to append the original
request URL to this cdcservlet URL. This parameter is consumed by the landing page to redirect to

```

```
the original URL. (property name: com.sun.identity.agents.config.redirect.param) <br>Hot-swap: Yes
<br> Example: com.sun.identity.agents.config.redirect.param = goto2<br> The complete URL sent for
authentication will be <br> http://host:port/opensso/cdcservlet?goto=http://agent:port/landing.jsp?
goto2=http://agent.port/original.jsp",
  "propertyOrder" : 3600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"portCheckFile" : {
  "title" : "Port Check File",
  "description" : "Name or complete path of a file that has the necessary
content needed to handle requests that need port correction. (property name:
com.sun.identity.agents.config.port.check.file) <br>Hot-swap: Yes",
  "propertyOrder" : 7300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"portCheckSetting" : {
  "title" : "Port Check Setting",
  "description" : "Map of port versus protocol entries with the key being the listening port
number and value being the listening protocol to be used by the Agent to identify requests with
invalid port numbers. (property name: com.sun.identity.agents.config.port.check.setting) <br>Hot-
swap: Yes <br> Example: <br> To map port 80 to protocol http: enter 80 in Map Key field, and enter
http in Corresponding Map Value field.",
  "propertyOrder" : 7400,
  "required" : false,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"localeLanguage" : {
  "title" : "Locale Language",
  "description" : "(property name: com.sun.identity.agents.config.locale.language) <br>Hot-
swap: No",
  "propertyOrder" : 1300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
}
}
```

1.79. J2eeAgents

1.79.1. Realm Operations

Agents handler that is responsible for managing agents

Resource path: `/realm-config/agents/J2EEAgent`

Resource version: `1.0`

1.79.1.1. create

Usage:

```
am> create J2eeAgents --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amServicesJ2EEAgent" : {
      "type" : "object",
      "title" : "AM Services",
      "propertyOrder" : 3,
      "properties" : {
        "amLoginUrl" : {
          "title" : "AM Login URL",
          "description" : "AM login page URL. (property name:
com.sun.identity.agents.config.login.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Login",
          "propertyOrder" : 3700,
          "items" : {
            "type" : "string"
          },
          "type" : "object",
          "exampleValue" : "",
          "properties" : {
            "inherited" : {
              "type" : "boolean",
              "required" : true
            },
            "value" : {
              "type" : "array",
              "required" : false
            }
          }
        }
      }
    }
  }
}
```

```

    }
  },
  "policyActionBooleanValues" : {
    "title" : "Policy Client Boolean Action Values",
    "description" : "Boolean action values for policy action names. (property name:
com.sun.identity.policy.client.booleanActionValues) <br>Hot-swap: No",
    "propertyOrder" : 11500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "loginProbeTimeout" : {
    "title" : "Login URL Probe Timeout",
    "description" : "The connect timeout value in milliseconds, if also Login URL Probe is set
to true. (property name: com.sun.identity.agents.config.login.url.probe.timeout) <br>Hot-swap: Yes",
    "propertyOrder" : 4000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "urlPolicyEnvPostParameters" : {
    "title" : "URL Policy Env POST Parameters",
    "description" : "List of HTTP POST request parameters whose names and values
will be set in the environment map for URL policy evaluation at AM server. (property name:
com.sun.identity.agents.config.policy.env.post.param) <br>Hot-swap: Yes <br> Examples: <br> name <br>
phoneNumber",
    "propertyOrder" : 11900,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  }
}

```

```

    },
    "policyClientResourceComparators" : {
      "title" : "Policy Client Resource Comparators",
      "description" : "Resource Comparators to be used for different service names. (property
name: com.sun.identity.policy.client.resourceComparators) <br>Hot-swap: No",
      "propertyOrder" : 11600,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "logoutProbeTimeout" : {
      "title" : "Logout URL Probe Timeout",
      "description" : "The connect timeout value in milliseconds, if also Logout URL Probe is set
to true. (property name: com.sun.identity.agents.config.logout.url.probe.timeout) <br>Hot-swap: Yes",
      "propertyOrder" : 12700,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : false
        }
      }
    },
    "urlPolicyEnvJsessionParameters" : {
      "title" : "URL Policy Env jsession Parameters",
      "description" : "List of HTTP SESSION attributes whose names and values will
be set in the environment map for URL policy evaluation at AM server. (property name:
com.sun.identity.agents.config.policy.env.jsession.param) <br>Hot-swap: Yes <br> Examples: <br> name
<br> phonenumber",
      "propertyOrder" : 12000,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "array",
          "required" : false
        }
      }
    }
  }

```

```
    }
  },
  "amLogoutUrl" : {
    "title" : "AM Logout URL",
    "description" : "AM logout page URL. (property name:
com.sun.identity.agents.config.logout.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Logout",
    "propertyOrder" : 12400,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "authServiceProtocol" : {
    "title" : "AM Authentication Service Protocol",
    "description" : "Protocol to be used by the AM authentication service. (property name:
com.ipplanet.am.server.protocol) <br>Hot-swap: No",
    "propertyOrder" : 10900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "probeLogoutUrl" : {
    "title" : "Logout URL Probe",
    "description" : "Specifies if agent will check the availability of these urls before
redirecting to them. (property name: com.sun.identity.agents.config.logout.url.probe.enabled)
<br>Hot-swap: Yes",
    "propertyOrder" : 12600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  }
}
```

```

    }
  },
  "conditionalLogoutUrl" : {
    "title" : "AM Conditional Logout URL",
    "description" : "(Only used in Agent 5 onwards) (property name:
org.forgerock.openam.agents.config.conditional.logout.url) <br>Hot-swap: Yes <br> Examples: <br>
match|url?param1=value1&param2=value2 <br> match/path|?param1=value1&param2=value2&param3=value3",
    "propertyOrder" : 12550,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "loginUrlPrioritized" : {
    "title" : "Login URL Prioritized",
    "description" : "Specifies if failover sequence for Login URLs or CDSSO
URLs should be prioritized as defined in the AM Login URL list. (property name:
com.sun.identity.agents.config.login.url.prioritized) <br>Hot-swap: Yes",
    "propertyOrder" : 3800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "logoutUrlPrioritized" : {
    "title" : "Logout URL Prioritized",
    "description" : "Specifies if failover sequence for Logout URLs
should be prioritized as defined in the AM Login URL list. (property name:
com.sun.identity.agents.config.logout.url.prioritized) <br>Hot-swap: Yes",
    "propertyOrder" : 12500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  }
}

```

```

    }
  },
  "clientPollingPeriod" : {
    "title" : "Client Polling Period",
    "description" : "(Not used in Agent 5 onwards) <br>Time in seconds after which the
session client will request update of cached session information from the server. (property name:
com.ipplanet.am.session.client.polling.period) <br>Hot-swap: No",
    "propertyOrder" : 10300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "policyClientClockSkew" : {
    "title" : "Policy Client Clock Skew",
    "description" : "Time in seconds which is allowed to accommodate the time difference
between the AM server machine and the remote policy client machine. (property name:
com.sun.identity.policy.client.clockSkew) <br>Hot-swap: No",
    "propertyOrder" : 11700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "policyEvaluationRealm" : {
    "title" : "Realm",
    "description" : "Which realm to start evaluating from. (property name:
org.forgerock.openam.agents.config.policy.evaluation.realm) <br>Hot-swap: Yes",
    "propertyOrder" : 5400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  }
},
}

```



```

"policyClientCacheMode" : {
  "title" : "Policy Client Cache Mode",
  "description" : "Mode of caching to be used by remote policy client. (property name:
com.sun.identity.policy.client.cacheMode) <br>Hot-swap: No",
  "propertyOrder" : 11400,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"authServiceHost" : {
  "title" : "AM Authentication Service Host Name",
  "description" : "Host name to be used by the AM authentication service. (property name:
com.iplanet.am.server.host) <br>Hot-swap: No",
  "propertyOrder" : 11000,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"useRedirectForCompositeAdvice" : {
  "title" : "Use HTTP-Redirect for composite advice",
  "description" : "Configure remote policy client to use HTTP-redirect instead of HTTP-POST
for composite advices. (property name: com.sun.identity.agents.config.policy.advice.use.redirect)
<br>Hot-swap: Yes",
  "propertyOrder" : 13000,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"authServicePort" : {
  "title" : "AM Authentication Service Port",
  "description" : "Port to be used by the AM authentication service. (property name:
com.iplanet.am.server.port) <br>Hot-swap: No",

```

```

    "propertyOrder" : 11100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "serviceDataCacheNotifications" : {
    "title" : "Enable Notification of Service Data Caches",
    "description" : "Enable the notifications for service management caches. (property name: com.sun.identity.sm.notification.enabled) <br>Hot-swap: No",
    "propertyOrder" : 10700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "userDataCacheNotifications" : {
    "title" : "Enable Notification of User Data Caches",
    "description" : "Enable notifications for amsdk and IdRepo Caches. (property name: com.sun.identity.idm.remote.notification.enabled) <br>Hot-swap: No",
    "propertyOrder" : 10500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "enableClientPolling" : {
    "title" : "Enable Client Polling",
    "description" : "Specifies if the session client must use polling for updating session information and not depend upon server notifications. (property name: com.iplanet.am.session.client.polling.enable) <br>Hot-swap: No",
    "propertyOrder" : 10200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {

```

```
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"probeLoginUrl" : {
  "title" : "Login URL Probe",
  "description" : "Specifies if agent will check the availability of these urls before
redirecting to them. (property name: com.sun.identity.agents.config.login.url.probe.enabled) <br>Hot-
swap: Yes",
  "propertyOrder" : 3900,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"policyClientPollingInterval" : {
  "title" : "Policy Client Polling Interval",
  "description" : "Duration in minutes after which the cached entries are refreshed by remote
policy client. (property name: com.sun.identity.agents.polling.interval) <br>Hot-swap: No",
  "propertyOrder" : 11300,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : false
    }
  }
},
"policyNotifications" : {
  "title" : "Enable Policy Notifications",
  "description" : "Enable Notifications for remote policy client. (property name:
com.sun.identity.agents.notification.enabled) <br>Hot-swap: No",
  "propertyOrder" : 11200,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
```

```

        "value" : {
          "type" : "boolean",
          "required" : false
        }
      },
    },
    "serviceDataCacheTime" : {
      "title" : "Service Data Cache Time",
      "description" : "Cache update time in minutes for service configuration data. If set to '0'
no updates happen. (property name: com.sun.identity.sm.cacheTime) <br>Hot-swap: No",
      "propertyOrder" : 10800,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : false
        }
      }
    },
    "policyEvaluationApplication" : {
      "title" : "Application",
      "description" : "Which application contains the policies to evaluate with. (property name:
org.forgerock.openam.agents.config.policy.evaluation.application) <br>Hot-swap: Yes",
      "propertyOrder" : 5500,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "conditionalLoginUrl" : {
      "title" : "AM Conditional Login URL",
      "description" : "(Only used in Agent 5 onwards) (property name:
org.forgerock.openam.agents.config.conditional.login.url) <br>Hot-swap: Yes <br> Examples: <br>
match|url?param1=value1&param2=value2 <br> match/path|?param1=value1&param2=value2&param3=value3",
      "propertyOrder" : 4010,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {

```

```
        "type" : "array",
        "required" : false
    }
  },
  "urlPolicyEnvGetParameters" : {
    "title" : "URL Policy Env GET Parameters",
    "description" : "List of HTTP GET request parameters whose names and values will
be set in the environment map for URL policy evaluation at AM server. (property name:
com.sun.identity.agents.config.policy.env.get.param) <br>Hot-swap: Yes <br> Examples: <br> name <br>
onenumber",
    "propertyOrder" : 11800,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "userDataCachePollingTime" : {
    "title" : "User Data Cache Polling Time",
    "description" : "Cache update time in minutes for user management data. If set to '0' no
updates happen. (property name: com.iplanet.am.sdk.remote.pollingTime) <br>Hot-swap: No",
    "propertyOrder" : 10600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  }
},
"applicationJ2EEAgentConfig" : {
  "type" : "object",
  "title" : "Application",
  "propertyOrder" : 1,
  "properties" : {
    "logoutRequestParameters" : {
      "title" : "Logout Request Parameter",
      "description" : "An application-specific Map that identifies a parameter
which when present in the HTTP request indicates a logout event. (property name:
com.sun.identity.agents.config.logout.request.param) <br>Valid key: the web application name.
<br>Valid value: the logout request parameter. <br>For this property, a global value can be set to
```

apply to all the applications that don't have their own specific logout request parameter.
Hot-swap: Yes
 Examples:
To set a global application logout request parameter: Leave Map Key field empty, and enter the global application logout request parameter logoutparam in Corresponding Map Value field.
 To set the logout request parameter for application BankApp: enter BankApp in Map Key field, and enter the logout request parameter logoutparam in Corresponding Map Value field.",

```

    "propertyOrder" : 6100,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "defaultPrivilegedAttributes" : {
    "title" : "Default Privileged Attribute",
    "description" : "(Not used in Agent 5 onwards) <br>List of privileged
attributes that will be granted to all users who have a valid AM session. (property name:
com.sun.identity.agents.config.default.privileged.attribute) <br>Hot-swap: Yes <br> Example: <br>
AUTHENTICATED_USERS",
    "propertyOrder" : 9400,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "notEnforcedUris" : {
    "title" : "Not Enforced URIs",
    "description" : "List of URIs for which protection is not enforced by the Agent. (property
name: com.sun.identity.agents.config.notenforced.uri) <br>Hot-swap: Yes <br> Examples: <br> /BankApp/
public/* <br> /BankApp/images/*",
    "propertyOrder" : 7500,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {

```

```

    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"responseAttributeMap" : {
  "title" : "Response Attribute Mapping",
  "description" : "Maps the policy response attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.response.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of response attribute uid under name CUSTOM-USER-NAME: enter uid in Map Key field,
and enter CUSTOM-USER-NAME in Corresponding Map Value field.",
  "propertyOrder" : 9200,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  }
},
"notEnforcedUrisRefreshSessionIdleTime" : {
  "title" : "Refresh Session Idle Time",
  "description" : "Indicates if opensso session idle time should be refreshed or reset for not
enforced URIs. (property name: com.sun.identity.agents.config.notenforced.refresh.session.idletime)
<br>Hot-swap: Yes",
  "propertyOrder" : 8600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"shortenedPrivilegeAttributeValues" : {
  "title" : "Shortened privilege attribute values",
  "description" : "When using privileged attribute type, this setting will ensure that
the membership details will be stored in a shortened format and not in the default universal ID

```

format.

By default the agent maps identity memberships using their universal IDs (e.g. id=admin,ou=group,dc=openam,dc=forgerock,dc=org), however this may not be always acceptable. Using this setting the identity membership details will be mapped in a shortened format, only including the group's/role's name (e.g. admin). Be aware that in case there are both roles and groups in the data store, this setting will make them indistinguishable from each other, i.e. if there is a group and a role with the same name it will not be possible to differentiate them.",

```

        "propertyOrder" : 13600,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "profileAttributeMap" : {
        "title" : "Profile Attribute Mapping",
        "description" : "Maps the profile attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.profile.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of profile attribute cn under name CUSTOM-Common-Name: enter cn in Map Key field,
and enter CUSTOM-Common-Name in Corresponding Map Value field. <br> To populate the value of profile
attribute mail under name CUSTOM-Email: enter mail in Map Key field, and enter CUSTOM-Email in
Corresponding Map Value field.",
        "propertyOrder" : 8800,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "object",
                "required" : false
            }
        }
    },
    "privilegedAttributesToLowerCase" : {
        "title" : "Privileged Attributes To Lower Case",
        "description" : "(Not used in Agent 5 onwards) <br>Maps the privileged
attribute types to whether they should be converted to lowercase. (property name:
com.sun.identity.agents.config.privileged.attribute.tolowercase) <br> Valid Keys: the privileged
attribute types, such as Group, Role. <br>Valid value: true, false. <br>Hot-swap: Yes <br> Example:
<br> Enter Group in Map Key field, and enter false in Corresponding Map Value field.",
        "propertyOrder" : 9600,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        }
    }
}

```



```

    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  }
},
"notEnforcedUriCacheEnabled" : {
  "title" : "Not Enforced URIs Cache Enabled",
  "description" : "Enables the caching of the Not Enforced URIs list evaluation results.
(property name: com.sun.identity.agents.config.notenforced.uri.cache.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 7700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"applicationLogoutUri" : {
  "title" : "Application Logout URI",
  "description" : "An application-specific Map that identifies a request URI which indicates
a logout event. (property name: com.sun.identity.agents.config.logout.uri) <br>Valid key: the web
application name. <br>Valid value: the application logout URI. <br>For this property, a global value
can be set to apply to all the applications that don't have their own specific logout URI. <br>Hot-
swap: Yes <br>Examples: <br>To set a global application logout URI: leave Map Key field empty, and
enter the global application logout URI /logout.jsp in Corresponding Map Value field. <br> To set the
logout URI for application BankApp: enter BankApp in Map Key field, and enter the application logout
URI /BankApp/logout.jsp in Corresponding Map Value field.",
  "propertyOrder" : 6000,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  }
},
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "object",
    "required" : false
  }
}

```

```

    }
  },
  "loginFormUri" : {
    "title" : "Login Form URI",
    "description" : "List of absolute URIs corresponding to an application's web.xml form-
login-page element. (property name: com.sun.identity.agents.config.login.form) <br>Hot-swap: Yes <br>
Example: <br> /BankApp/jsp/login.jsp",
    "propertyOrder" : 2800,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "notEnforcedIpsCacheEnabled" : {
    "title" : "Not Enforced IP Cache Flag",
    "description" : "Enable caching of not-enforced IP list evaluation results. (property name:
com.sun.identity.agents.config.notenforced.ip.cache.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 8100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "resourceAccessDeniedUri" : {
    "title" : "Resource Access Denied URI",
    "description" : "An application-specific Map that identifies a URI of the customized access
denied page. (property name: com.sun.identity.agents.config.access.denied.uri) <br>Valid key: the
web application name. <br>Valid value: the customized application access denied page URI. <br>For
this property, a global value can be set to apply to all the applications that don't have their own
specific access denied page. <br>Hot-swap: Yes <br> Examples: <br>To set a global access denied page:
leave Map Key field empty, and enter the global access denied page URI /sample/accessdenied.html in
Corresponding Map Value field. <br> To set the access denied page URI for application BankApp: enter
BankApp in Map Key field, and enter the application access denied page URI /BankApp/accessdenied.html
in Corresponding Map Value field.",
    "propertyOrder" : 2700,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    }
  }
}

```

```

    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "notEnforcedRuleCompoundSeparator" : {
    "title" : "Not Enforced Compound Rule Separator",
    "description" : "Specifies a separator for not enforced compound rules (Agent 5 only). The
format for compound rules requires a list of IP rules, a separator (by default the | character),
and a list of URI rules. For example, GET 192.168.1.1-192.168.4.3 | /images/* Configure a
different separator (for example, &&) when working with the REGEX keyword to avoid invalid regular
expressions.",
    "propertyOrder" : 7450,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "loginErrorUri" : {
    "title" : "Login Error URI",
    "description" : "List of absolute URIs corresponding to an application's web.xml form-error-
page element. (property name: com.sun.identity.agents.config.login.error.uri) <br>Hot-swap: Yes <br>
Example: <br> /BankApp/jsp/error.jsp",
    "propertyOrder" : 2900,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "headerAttributeDateFormat" : {
    "title" : "Fetch Attribute Date Format",

```

```

      "description" : "Format of date attribute values to be used when the attribute is
being set as HTTP header. Format is based on java.text.SimpleDateFormat. (property name:
com.sun.identity.agents.config.attribute.date.format) <br>Hot-swap: Yes",
      "propertyOrder" : 8400,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "logoutEntryUri" : {
      "title" : "Logout Entry URI",
      "description" : "An application-specific Map that identifies a URI to be used as an entry
point after successful logout and subsequent successful authentication if applicable. (property name:
com.sun.identity.agents.config.logout.entry.uri) <br>Valid key: the web application name. <br>Valid
value: the logout entry URI. <br>For this property, a global value can be set to apply to all the
applications that don't have their own specific logout entry URI. <br>Hot-swap: Yes <br> Examples:
<br>To set a global application logout entry URI: leave Map Key field empty, and enter the global
application logout entry URI /welcome.html in Corresponding Map Value field. <br> To set the logout
entry URI for application BankApp: enter BankApp in Map Key field, and enter the logout entry URI /
BankApp/welcome.html in Corresponding Map Value field.",
      "propertyOrder" : 6300,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "object",
          "required" : false
        }
      }
    },
    "cookieAttributeMultiValueSeparator" : {
      "title" : "Cookie Separator Character",
      "description" : "Character that will be used to separate multiple
values of the same attribute when it is being set as a cookie. (property name:
com.sun.identity.agents.config.attribute.cookie.separator) <br>Hot-swap: Yes",
      "propertyOrder" : 8300,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
}

```

```

    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  },
  "continuousSecurityHeaders" : {
    "title" : "Continuous Security Headers",
    "description" : "The name of the headers in the user's original request, that will be sent
as part of the payload during policy evaluation, which can then be accessed via the 'environment'
variable in a policy script. The 'key' is the name of the header to be sent, and the 'value' is the
name which it will appear as in the policy evaluation script. It is possible to map multiple headers
to the same name (they will simply appear as an array in the evaluation script). If the header
doesn't exist, then the empty string will be sent.",
    "propertyOrder" : 3211,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "privilegedSessionAttribute" : {
    "title" : "Privileged Session Attribute",
    "description" : "(Not used in Agent 5 onwards) <br>List of session property
names which hold privileged attributes for the authenticated user. (property name:
com.sun.identity.agents.config.privileged.session.attribute) <br>Hot-swap: Yes <br> Example: <br>
UserToken",
    "propertyOrder" : 9700,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "privilegedAttributeMap" : {
    "title" : "Privileged Attribute Mapping",

```

```

"description" : "(Not used in Agent 5 onwards) <br>Map if using Enable Privileged
Attribute Mapping. (property name: com.sun.identity.agents.config.privileged.attribute.mapping)
<br>Hot-swap: Yes <br> Examples: <br> To map UUID id=manager,ou=group,dc=openam,dc=forgerock,dc=org
to the principal name am_manager_role specified in webapp's deployment descriptor: enter
id=manager,ou=group,dc=openam,dc=forgerock,dc=org in Map Key field, and enter am_manager_role in
Corresponding Map Value field. <br> To map UUID id=employee,ou=group,dc=openam,dc=forgerock,dc=org
to the principal name am_employee_role specified in webapp's deployment descriptor: enter
id=employee,ou=group,dc=openam,dc=forgerock,dc=org in Map Key field, and enter am_employee_role in
Corresponding Map Value field.",
  "propertyOrder" : 9900,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  }
},
"profileAttributeFetchMode" : {
  "title" : "Profile Attribute Fetch Mode",
  "description" : "The mode of fetching profile attributes. (property name:
com.sun.identity.agents.config.profile.attribute.fetch.mode) <br>Hot-swap: Yes",
  "propertyOrder" : 8700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"privilegedAttributeMappingEnabled" : {
  "title" : "Enable Privileged Attribute Mapping",
  "description" : "(Not used in Agent 5 onwards) <br>Enable a mapping from
the original value of an attribute to another value. To satisfy container-specific
restrictions on character set being used in certain configuration files. (property name:
com.sun.identity.agents.config.privileged.attribute.mapping.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 9800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}

```

```

    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  },
  "sessionAttributeMap" : {
    "title" : "Session Attribute Mapping",
    "description" : "Maps the session attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.session.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of session attribute UserToken under name CUSTOM-userid: enter UserToken in Map
Key field, and enter CUSTOM-userid in Corresponding Map Value field.",
    "propertyOrder" : 9000,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "applicationLogoutHandlers" : {
    "title" : "Application Logout Handler",
    "description" : "An application-specific Map that identifies a handler to be used for logout
processing. (property name: com.sun.identity.agents.config.logout.application.handler) <br>Valid
key: the web application name. <br>Valid value: the application logout handler class name. <br>For
this property, a global value can be set to apply to all the applications that don't have their own
specific logout handler. <br>Hot-swap: Yes <br> Examples: <br>To set a global application logout
handler: leave Map Key field empty, and enter the global application logout handler class name
GlobalApplicationLogoutHandler in Corresponding Map Value field. <br>To set the logout handler for
application BankApp: enter BankApp in Map Key field, and enter the application logout handler class
name BankAppLogoutHandler in Corresponding Map Value field.",
    "propertyOrder" : 5900,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",

```

```

        "required" : false
    }
}
},
"notEnforcedUrisCacheSize" : {
    "title" : "Not Enforced URIs Cache Size",
    "description" : "Size of the cache to be used if caching of not enforced URI list evaluation
results is enabled. (property name: com.sun.identity.agents.config.notenforced.uri.cache.size)
<br>Hot-swap: Yes",
    "propertyOrder" : 7800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
},
"notEnforcedIpsCacheSize" : {
    "title" : "Not Enforced IP Cache Size",
    "description" : "Size of the cache to be used if Not Enforced IP Cache Flag is enabled.
(property name: com.sun.identity.agents.config.notenforced.ip.cache.size) <br>Hot-swap: Yes",
    "propertyOrder" : 8200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
},
"logoutIntrospection" : {
    "title" : "Logout Introspect Enabled",
    "description" : "Allows the Agent to search HTTP request body to locate logout parameter.
(property name: com.sun.identity.agents.config.logout.introspect.enabled) <br>Hot-swap: Yes",
    "propertyOrder" : 6200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
}
},

```



```
"invertNotEnforcedIps" : {
  "title" : "Not Enforced IP Invert List",
  "description" : "Client IP Addresses to invert protection of IP
addresses listed in the related Not Enforced Client IP List. (property name:
com.sun.identity.agents.config.notenforced.ip.invert) <br>Hot-swap: Yes",
  "propertyOrder" : 8000,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"invertNotEnforcedUris" : {
  "title" : "Invert Not Enforced URIs",
  "description" : "Inverts protection of URIs specified in Not Enforced URIs list. When
set to true, it indicates that the URIs specified should be enforced and all other URIs should be
not enforced by the Agent. (property name: com.sun.identity.agents.config.notenforced.uri.invert)
<br>Hot-swap: Yes",
  "propertyOrder" : 7600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"responseAttributeFetchMode" : {
  "title" : "Response Attribute Fetch Mode",
  "description" : "The mode of fetching policy response attributes. (property name:
com.sun.identity.agents.config.response.attribute.fetch.mode) <br>Hot-swap: Yes",
  "propertyOrder" : 9100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"continuousSecurityCookies" : {
  "title" : "Continuous Security Cookies",
```

```

    "description" : "The name of the cookies to be sent as part of the payload during policy
evaluation, which can be accessed via the 'environment' variable in a policy script. The 'key' is
the name of the cookie to be sent, and the 'value' is the name which it will appear as in the policy
evaluation script. It is possible to map multiple cookies to the same name (they will simply appear
as an array in the evaluation script). If the cookie doesn't exist, then the empty string will be
sent.",
    "propertyOrder" : 3210,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "loginContentFile" : {
    "title" : "Login Content File Name",
    "description" : "Complete path and name of custom login content file. (property name:
com.sun.identity.agents.config.login.content.file) <br>Hot-swap: Yes",
    "propertyOrder" : 3100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "cookieAttributeUrlEncoded" : {
    "title" : "Attribute Cookie Encode",
    "description" : "Indicates if the value of the attribute should be URL encoded before being
set as a cookie. (property name: com.sun.identity.agents.config.attribute.cookie.encode) <br>Hot-
swap: Yes",
    "propertyOrder" : 8500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  }
}

```

```

    }
  },
  "customAuthenticationHandlers" : {
    "title" : "Custom Authentication Handler",
    "description" : "Application specific authentication handler to authenticate the logged
on user with the application server. (property name: com.sun.identity.agents.config.auth.handler)
<br>Valid key: the web application name. <br>Valid value: the authentication handler class
name. <br>Hot-swap: Yes <br>Example: <br>To set authentication handler for application BankApp:
enter BankApp in Map Key field, and enter authentication handler class name BankAuthHandler in
Corresponding Map Value field.",
    "propertyOrder" : 3200,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "sessionAttributeFetchMode" : {
    "title" : "Session Attribute Fetch Mode",
    "description" : "The mode of fetching session attributes. (property name:
com.sun.identity.agents.config.session.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 8900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "useInternalLogin" : {
    "title" : "Use Internal Login",
    "description" : "Set to false if want to customize Login Content File instead of default
internal content provided. (property name: com.sun.identity.agents.config.login.use.internal)
<br>Hot-swap: Yes",
    "propertyOrder" : 3000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",

```

```

    "required" : true
  },
  "value" : {
    "type" : "boolean",
    "required" : false
  }
},
"privilegedAttributeType" : {
  "title" : "Privileged Attribute Type",
  "description" : "(Not used in Agent 5 onwards) <br>List of
privileged attribute types that will be fetched for each user. (property name:
com.sun.identity.agents.config.privileged.attribute.type) <br>Hot-swap: Yes <br> Example: <br>
Group",
  "propertyOrder" : 9500,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"notEnforcedIps" : {
  "title" : "Not Enforced Client IP List",
  "description" : "No authentication and authorization protection from agent
are required for the requests coming from these client IP addresses. (property name:
com.sun.identity.agents.config.notenforced.ip) <br>Hot-swap: Yes <br> Examples: <br> 192.18.145.*
<br> 192.18.146.123",
  "propertyOrder" : 7900,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"customLogoutHandlers" : {
  "title" : "Custom Logout Handler",
  "description" : "Application specific logout handler to log out a user with the application
server. (property name: com.sun.identity.agents.config.logout.handler) <br>Valid key: the web
application name. <br>Valid value: the logout handler class name. <br>Hot-swap: Yes <br> Example:

```

```

<br>To set logout handler for application BankApp: enter BankApp in Map Key field, and enter logout
handler class name BankLogoutHandler in Corresponding Map Value field.",
    "propertyOrder" : 3300,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "customVerificationHandlers" : {
    "title" : "Custom Verification Handler",
    "description" : "Application specific verification handler to validate the user credentials
with the local repository. (property name: com.sun.identity.agents.config.verification.handler)
<br>Valid key: the web application name. <br>Valid value: the verification handler class name.
<br>Hot-swap: Yes <br> Example: <br> To set verification handler for application BankApp: enter
BankApp in Map Key field, and enter verification handler class name BankVerificationHandler in
Corresponding Map Value field.",
    "propertyOrder" : 3400,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  }
}
},
"globalJ2EEAgentConfig" : {
  "type" : "object",
  "title" : "Global",
  "propertyOrder" : 0,
  "properties" : {
    "fqdnMapping" : {
      "title" : "FQDN Virtual Host Map",
      "description" : "Maps virtual, invalid, or partial hostnames, and IP addresses to the FQDN
to access protected resources. (property name: com.sun.identity.agents.config.fqdn.mapping) <br>Hot-

```

```

swap: Yes <br> Examples: <br> To map the partial hostname myserver to myserver.mydomain.com: enter
myserver in the Map Key field and myserver.mydomain.com in the Corresponding Map Value field. To map
a virtual server rst.hostname.com that points to the actual server abc.hostname.com: enter valid1 in
the Map Key field and rst.hostname.com in the Corresponding Map Value field.",
  "propertyOrder" : 6600,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  }
},
"agentConfigChangeNotificationsEnabled" : {
  "title" : "Agent Configuration Change Notification",
  "description" : "Enable agent to receive notification messages from AM server for
configuration changes. (property name: com.sun.identity.agents.config.change.notification.enable)
<br>Hot-swap: Yes",
  "propertyOrder" : 12100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"userpassword" : {
  "title" : "Password",
  "description" : "",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"filterMode" : {
  "title" : "Agent Filter Mode",
  "description" : "Specifies the mode of operation of the Filter. (property name:
com.sun.identity.agents.config.filter.mode) <br>Valid key: the web application name. <br>Valid
values: ALL, J2EE_POLICY (Not used in Agent 5 onwards), URL_POLICY, SSO_ONLY, NONE <br>For this
property, a global value can be set to apply to all the applications that don't have their own
specific filter mode. <br>Hot-swap: No <br>Examples: <br>To set ALL as the global filter mode:
leave Map Key field empty, and enter ALL in Corresponding Map Value field. <br>To set URL_POLICY

```

```

as the filter mode for application BankApp: enter BankApp in Map Key field, and enter URL_POLICY in
Corresponding Map Value field.",
    "propertyOrder" : 500,
    "patternProperties" : {
        ".*" : {
            "type" : "string"
        }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "object",
            "required" : false
        }
    }
},
"websocketConnectionIntervalInMinutes" : {
    "title" : "Web Socket Connection Interval",
    "description" : "Interval in minutes by which agents reopen their web socket connection to
ensure a fair distribution of connections across AM servers. (Agent 5 only).",
    "propertyOrder" : 12105,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
},
"fqdnCheck" : {
    "title" : "FQDN Check",
    "description" : "Enables checking of fqdn default value and fqdn map values. (property name:
com.sun.identity.agents.config.fqdn.check.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 6400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
},
"remoteLogFilename" : {
    "title" : "Remote Log File Name",

```

```

    "description" : "Name of file stored on AM server that contains agent audit messages.
(property name: com.sun.identity.agents.config.remote.logfile) <br>Hot-swap: Yes",
    "propertyOrder" : 1700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "userMappingMode" : {
    "title" : "User Mapping Mode",
    "description" : "Specifies mechanism agent uses to determine user-ID. (property name:
com.sun.identity.agents.config.user.mapping.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "customResponseHeader" : {
    "title" : "Custom Response Header",
    "description" : "Map specifies the custom headers that are set by the Agent on the client
browser. The key is the header name and the value represents the header value. (property name:
com.sun.identity.agents.config.response.header) <br>Hot-swap: Yes <br> Example: <br> To set the
custom header Cache-Control to value no-cache: enter Cache-Control in Map Key field, and enter no-
cache in Corresponding Map Value field.",
    "propertyOrder" : 7000,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  }
}

```



```

    },
    "debugLevel" : {
      "title" : "Agent Debug Level",
      "description" : "Specifies type of agent debug messages to log. (property name:
com.iplanet.services.debug.level) <br>Hot-swap: Yes",
      "propertyOrder" : 10000,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "localAuditRotationSize" : {
      "title" : "Local Audit Log Rotation Size",
      "description" : "Size limit when a local audit log file is rotated to a new file. (property
name: com.sun.identity.agents.config.local.log.size) <br>Hot-swap: Yes",
      "propertyOrder" : 1900,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : false
        }
      }
    },
    "loginAttemptLimit" : {
      "title" : "Login Attempt Limit",
      "description" : "Limit of failed login attempts for a user's single browser session until
triggering the blocking of the user request. Value of 0 disables this feature. (property name:
com.sun.identity.agents.config.login.attempt.limit) <br>Hot-swap: Yes",
      "propertyOrder" : 4400,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : false
        }
      }
    },
    "userTokenName" : {
      "title" : "User Token Name",

```

```

    "description" : "Session property name for user-ID of the authenticated user in session.
(property name: com.sun.identity.agents.config.user.token) <br>Hot-swap: Yes",
    "propertyOrder" : 900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "fqdnDefault" : {
    "title" : "FQDN Default",
    "description" : "Fully qualified hostname that the users should use in order to access
resources. (property name: com.sun.identity.agents.config.fqdn.default) <br>Hot-swap: Yes",
    "propertyOrder" : 6500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "redirectAttemptLimit" : {
    "title" : "Redirect Attempt Limit",
    "description" : "Number of successive single point redirects that a user can make using a
single browser session which will trigger the blocking of the user request. Set to 0 to disable this
feature. (property name: com.sun.identity.agents.config.redirect.attempt.limit) <br>Hot-swap: Yes",
    "propertyOrder" : 7100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "auditLogLocation" : {
    "title" : "Audit Log Location",
    "description" : "Specifies where audit messages should be logged. (property name:
com.sun.identity.agents.config.log.disposition) <br>Hot-swap: Yes",
    "propertyOrder" : 1600,
    "type" : "object",

```

```

    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "userPrincipalFlag" : {
    "title" : "User Principal Flag",
    "description" : "Use principal instead of just the user-ID for authenticating the user.
(property name: com.sun.identity.agents.config.user.principal) <br>Hot-swap: Yes",
    "propertyOrder" : 800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "userAttributeName" : {
    "title" : "User Attribute Name",
    "description" : "Name of the attribute which contains the user-ID. (property name:
com.sun.identity.agents.config.user.attribute.name) <br>Hot-swap: Yes",
    "propertyOrder" : 700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "repositoryLocation" : {
    "title" : "Location of Agent Configuration Repository",
    "description" : "Indicates agent's configuration located either on agent's host or centrally
on AM server.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "jwtName" : {
    "title" : "JWT Cookie Name",

```

```

    "description" : "The name used by the agent to set the OIDC JWT on the user's browser.
    (Agent 5 only).",
    "propertyOrder" : 11201,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "configurationReloadInterval" : {
    "title" : "Configuration Reload Interval",
    "description" : "Interval in seconds between configuration reloads. (property name:
    com.sun.identity.agents.config.load.interval) <br>Hot-swap: Yes",
    "propertyOrder" : 1200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "agentgroup" : {
    "title" : "Group",
    "description" : "Add the agent to a group to allow inheritance of property values from the
    group. <br>Changing the group will update inherited property values. <br>Inherited property values
    are copied to the agent.",
    "propertyOrder" : 50,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "auditAccessType" : {
    "title" : "Audit Access Types",
    "description" : "Types of messages to log based on user URL access attempts. (property name:
    com.sun.identity.agents.config.audit.accesstype) <br>Hot-swap: Yes",
    "propertyOrder" : 1500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  }
}

```

```

    }
  },
  "localAuditLogRotation" : {
    "title" : "Rotate Local Audit Log",
    "description" : "Flag to indicate that audit log files should be rotated when reaching a
certain size. (property name: com.sun.identity.agents.config.local.log.rotate) <br>Hot-swap: Yes",
    "propertyOrder" : 1800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "cdssoRootUrl" : {
    "title" : "Agent Root URL for CDSSO",
    "description" : "The agent root URL for CDSSO. The valid value is in the following format:
<br>protocol://hostname:port/<br>The protocol represents the protocol used, such as http or https.
The hostname represents the host name of the machine on which the agent resides. The port represents
the port number on which the agent is installed. The slash following the port number is required.",
    "propertyOrder" : 22700,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "httpSessionBinding" : {
    "title" : "HTTP Session Binding",
    "description" : "If true will invalidate the http session when login has failed,
user has no SSO session, or principal user name does not match SSO user name. (property name:
com.sun.identity.agents.config.httpsession.binding) <br>Hot-swap: Yes",
    "propertyOrder" : 3500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",

```

```

        "required" : false
    }
}
},
"agentNotificationUrl" : {
    "title" : "Agent Notification URL",
    "description" : "URL used by agent to register notification listeners. (property name:
com.sun.identity.client.notification.url) <br>Hot-swap: No",
    "propertyOrder" : 300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
},
"status" : {
    "title" : "Status",
    "description" : "Status of the agent configuration.",
    "propertyOrder" : 200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : true
        }
    }
}
}
},
"ssoJ2EEAgentConfig" : {
    "type" : "object",
    "title" : "SSO",
    "propertyOrder" : 2,
    "properties" : {
        "cookieResetDomains" : {
            "title" : "Cookies Reset Domain Map",
            "description" : "Maps cookie names specified in Cookie Reset Name List to value
being the domain of this cookie to be used when a reset event occurs. (property name:
com.sun.identity.agents.config.cookie.reset.domain) <br>Hot-swap: Yes",
            "propertyOrder" : 4800,
            "patternProperties" : {
                ".*" : {
                    "type" : "string"
                }
            }
        },
        "type" : "object",
        "exampleValue" : "",

```

```

    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "ssoCacheEnabled" : {
    "title" : "SSO Cache Enable",
    "description" : "Specifies if the SSO Cache is active for the agent.
Cache is used through public APIs exposed by the agent SDK. (property name:
com.sun.identity.agents.config.amssso.cache.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 4500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "cdssoUrls" : {
    "title" : "CDSSO Servlet URL",
    "description" : "List of URLs of the available CDSSO controllers that may be used by the
Agent for CDSSO processing. (property name: com.sun.identity.agents.config.cdsso.cdcervlet.url)
<br>Hot-swap: Yes <br> Example: <br> http://host:port/opensso/cdcervlet",
    "propertyOrder" : 5200,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "cdssoRedirectUri" : {
    "title" : "CDSSO Redirect URI",
    "description" : "An intermediate URI that is used by the Agent for processing CDSSO
requests. (property name: com.sun.identity.agents.config.cdsso.redirect.uri) <br>Hot-swap: Yes",
    "propertyOrder" : 5100,
    "type" : "object",
    "exampleValue" : "",

```

```

    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "cookieResetPaths" : {
    "title" : "Cookies Reset Path Map",
    "description" : "Maps cookie names specified in Cookie Reset Name List to value
being the path of this cookie to be used when a reset event occurs. (property name:
com.sun.identity.agents.config.cookie.reset.path) <br>Hot-swap: Yes",
    "propertyOrder" : 4900,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "cdssoClockSkew" : {
    "title" : "CDSSO Clock Skew",
    "description" : "Time in seconds to be used by the Agent to determine the validity of the
CDSSO AuthnResponse assertion. (property name: com.sun.identity.agents.config.cdsso.clock.skew)
<br>Hot-swap: Yes",
    "propertyOrder" : 5300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "amCookieName" : {
    "title" : "Cookie Name",
    "description" : "Name of the SSO Token cookie used between the AM server and the Agent.
(property name: com.iplanet.am.cookie.name) <br>Hot-swap: No",
    "propertyOrder" : 10100,

```



```

    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "cdssoTrustedIdProvider" : {
    "title" : "CDSO Trusted ID Provider",
    "description" : "List of AM Server/ID providers that should be trusted
by the agent, when evaluating the CDC Liberty Responses. (property name:
com.sun.identity.agents.config.cdsso.trusted.id.provider) <br>Hot-swap: Yes <br> Example: <br>
http://host:port/opensso/cdcservlet",
    "propertyOrder" : 5600,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "cookieResetEnabled" : {
    "title" : "Cookie Reset",
    "description" : "Agent resets cookies in the response before redirecting to authentication.
(property name: com.sun.identity.agents.config.cookie.reset.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 4600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "cookieResetNames" : {
    "title" : "Cookies Reset Name List",
    "description" : "Cookie names that will be reset by the Agent if Cookie Reset is enabled.
(property name: com.sun.identity.agents.config.cdsso.cookie.reset.name) <br>Hot-swap: Yes",
    "propertyOrder" : 4700,

```

```
"items" : {
  "type" : "string"
},
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "array",
    "required" : false
  }
}
},
"cdsso" : {
  "title" : "Cross Domain SSO",
  "description" : "Enables Cross Domain Single SignOn. (property name:
com.sun.identity.agents.config.cdsso.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 5000,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"cdssoDomainList" : {
  "title" : "CDSSO Domain List",
  "description" : "Domains for which cookies have to be set in a CDSSO scenario. (property
name: com.sun.identity.agents.config.cdsso.domain) <br>Hot-swap: Yes <br> Example: <br> .sun.com",
  "propertyOrder" : 5800,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"cdssoSecureCookies" : {
  "title" : "CDSSO Secure Enable",
```

```

    "description" : "The SSO Token cookie set by the agent in the different domains in CDSSO
mode will be marked secure. Only transmitted if the communications channel with host is a secure one.
(property name: com.sun.identity.agents.config.cdsso.secure.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 5700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  }
},
"miscJ2EEAgentConfig" : {
  "type" : "object",
  "title" : "Miscellaneous",
  "propertyOrder" : 4,
  "properties" : {
    "legacyUserAgentSupport" : {
      "title" : "Legacy User Agent Support Enable",
      "description" : "Enables support for legacy user agents (browser). (property name:
com.sun.identity.agents.config.legacy.support.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 6700,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    }
  }
},
"encryptionProvider" : {
  "title" : "Encryption Provider",
  "description" : "Specifies the encryption provider implementation to be used by the Agent.
(property name: com.iplanet.security.encryptor) <br>Hot-swap: No",
  "propertyOrder" : 10400,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
}
}

```

```

    },
    "portCheckFile" : {
      "title" : "Port Check File",
      "description" : "Name or complete path of a file that has the necessary
content needed to handle requests that need port correction. (property name:
com.sun.identity.agents.config.port.check.file) <br>Hot-swap: Yes",
      "propertyOrder" : 7300,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "portCheckSetting" : {
      "title" : "Port Check Setting",
      "description" : "Map of port versus protocol entries with the key being the listening port
number and value being the listening protocol to be used by the Agent to identify requests with
invalid port numbers. (property name: com.sun.identity.agents.config.port.check.setting) <br>Hot-
swap: Yes <br> Example: <br> To map port 80 to protocol http: enter 80 in Map Key field, and enter
http in Corresponding Map Value field.",
      "propertyOrder" : 7400,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "object",
          "required" : false
        }
      }
    },
    "portCheckEnabled" : {
      "title" : "Port Check Enable",
      "description" : "Indicates if port check functionality is enabled or disabled. (property
name: com.sun.identity.agents.config.port.check.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 7200,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {

```

```

        "type" : "boolean",
        "required" : false
    }
}
},
"gotoParameterName" : {
    "title" : "Goto Parameter Name",
    "description" : "Property used only when CDSSO is enabled. Default value
should be changed only when the login URL has a landing page specified <br> Example :
com.sun.identity.agents.config.cdssso.cdcservlet.url = http://host:port/opensso/cdcservlet?
goto=http://agent:port/landing.jsp <br> The parameter is used by the Agent to append the original
request URL to this cdcservlet URL. This parameter is consumed by the landing page to redirect to
the original URL. (property name: com.sun.identity.agents.config.redirect.param) <br>Hot-swap: Yes
<br> Example: com.sun.identity.agents.config.redirect.param = goto2<br> The complete URL sent for
authentication will be <br> http://host:port/opensso/cdcservlet?goto=http://agent:port/landing.jsp?
goto2=http://agent.port/original.jsp",
    "propertyOrder" : 3600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
}
},
"bypassPrincipallist" : {
    "title" : "Bypass Principal List",
    "description" : "List of principals that are bypassed by the Agent for authentication and
search purposes. (property name: com.sun.identity.agents.config.bypass.principal) <br>Hot-swap: Yes
<br> Examples: <br> guest <br> testuser",
    "propertyOrder" : 9300,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "array",
            "required" : false
        }
    }
}
},
"localeCountry" : {
    "title" : "Locale Country",
    "description" : "(property name: com.sun.identity.agents.config.locale.country) <br>Hot-
swap: No",
    "propertyOrder" : 1400,
    "type" : "object",
    "exampleValue" : "",

```

```

        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "legacyUserAgentList" : {
        "title" : "Legacy User Agent List",
        "description" : "List of user agent header values that identify legacy
browsers. Entries in this list can have wild card character '*'. (property name:
com.sun.identity.agents.config.legacy.user.agent) <br>Hot-swap: Yes",
        "propertyOrder" : 6800,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "ignorePathInfo" : {
        "title" : "Ignore Path Info in Request URL",
        "description" : "The path info will be stripped from the request URL while doing Not
Enforced List check and url policy evaluation if the value is set to true. (property name:
com.sun.identity.agents.config.ignore.path.info) <br>Hot-swap: Yes",
        "propertyOrder" : 18600,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "legacyRedirectUri" : {
        "title" : "Legacy User Agent Redirect URI",
        "description" : "An intermediate URI used by the Agent to redirect legacy user agent
requests. (property name: com.sun.identity.agents.config.legacy.redirect.uri) <br>Hot-swap: Yes",
        "propertyOrder" : 6900,
        "type" : "object",
        "exampleValue" : "",
    }

```

```

        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "localeLanguage" : {
        "title" : "Locale Language",
        "description" : "(property name: com.sun.identity.agents.config.locale.language) <br>Hot-
swap: No",
        "propertyOrder" : 1300,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    }
},
"advancedJ2EEAgentConfig" : {
    "type" : "object",
    "title" : "Advanced",
    "propertyOrder" : 5,
    "properties" : {
        "webServiceAuthorizationErrorContentFile" : {
            "title" : "Web Service Authorization Error Content File",
            "description" : "The name of file that contains content used by the
Agent to generate an authorization error fault for clients. (property name:
com.sun.identity.agents.config.webservice.autherror.content) <br>Hot-swap: Yes",
            "propertyOrder" : 2600,
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                },
                "value" : {
                    "type" : "string",
                    "required" : false
                }
            }
        }
    }
},
"clientIpHeader" : {
    "title" : "Client IP Address Header",
    "description" : "HTTP header name that holds the IP address of the client. (property name:
com.sun.identity.agents.config.client.ip.header) <br>Hot-swap: Yes",

```

```

    "propertyOrder" : 1000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "alternativeAgentProtocol" : {
    "title" : "Alternative Agent Protocol",
    "description" : "Protocol being used (http/https) by the client browsers to communicate with
the Agent protected server if different from the actual protocol used by the server. (property name:
com.sun.identity.agents.config.agent.protocol) <br>Hot-swap: Yes",
    "propertyOrder" : 4300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "postDataPreserveCacheEntryMaxTotalSizeMb" : {
    "title" : "PDP Maximum Cache Size",
    "description" : "Maximum size of the PDP cache, in megabytes (Property name:
org.forgerock.openam.agents.config.postdata.preserve.cache.entry.max.total.size.mb). (Agent 5 only)",
    "propertyOrder" : 13600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "webServiceEndpoints" : {
    "title" : "Web Service End Points",
    "description" : "A list of Web Application end points that represent Web Services. (property
name: com.sun.identity.agents.config.webservice.endpoint) <br>Hot-swap: Yes",
    "propertyOrder" : 2100,
    "items" : {
      "type" : "string"
    }
  },

```



```

        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "possibleXssCodeElements" : {
        "title" : "Possible XSS code elements",
        "description" : "If one of these strings occurs in the request, the client is redirected to
an error page. (property name: com.sun.identity.agents.config.xss.code.elements) <br>Hot-swap: Yes",
        "propertyOrder" : 12800,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "postDataStickySessionMode" : {
        "title" : "PDP Sticky session mode",
        "description" : "The PDP mechanism needs sticky loadbalancing, the URL mode
will append a querystring, while the Cookie mode will create a cookie. (property name:
com.sun.identity.agents.config.postdata.preserve.stickysession.mode)",
        "propertyOrder" : 13400,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "webServiceProcessGetEnabled" : {
        "title" : "Web Service Process GET Enable",
        "description" : "Flag to indicates if the processing of HTTP GET requests for Web Service
endpoints is enabled. (property name: com.sun.identity.agents.config.webservice.process.get.enable)
<br>Hot-swap: Yes",
        "propertyOrder" : 2200,
    }
}

```

```

        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "customProperties" : {
        "title" : "Custom Properties",
        "description" : "Additional properties that allow users to augment the set of properties supported by agent. (property name: com.sun.identity.agents.config.freeformproperties) <br>Hot-swap: Yes <br> Examples: <br> customproperty=custom-value1 <br> customlist[0]=customlist-value-0 <br> customlist[1]=customlist-value-1 <br> custommap[key1]=custommap-value-1 <br> custommap[key2]=custommap-value-2",
        "propertyOrder" : 12200,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "alternativeAgentPort" : {
        "title" : "Alternative Agent Port Name",
        "description" : "Port number identifying the Agent protected server listening port to the client browsers if different from the actual listening port. (property name: com.sun.identity.agents.config.agent.port) <br>Hot-swap: Yes",
        "propertyOrder" : 4200,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "postDataPreserveCacheEntryMaxEntries" : {
        "title" : "PDP Maximum Number of Cache Entries",

```

```

    "description" : "Maximum number of entries to hold in the PDP cache (Property name:
org.forgerock.openam.agents.config.postdata.preserve.cache.entry.max.entries) (Agent 5 only).",
    "propertyOrder" : 13550,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "postDataCacheTtl" : {
    "title" : "PDP entry TTL",
    "description" : "This value tells how long a given POST entry should be
stored in the local cache (in milliseconds), default value is 300000. (property name:
com.sun.identity.agents.config.postdata.preserve.cache.entry.ttl)",
    "propertyOrder" : 13300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "webServiceAuthenticator" : {
    "title" : "Web Service Authenticator",
    "description" : "An implementation class of interface
com.sun.identity.agents.filter.IWebServiceAuthenticator that can be used to authenticate web-service
requests. (property name: com.sun.identity.agents.config.webservice.authenticator) <br>Hot-swap:
Yes",
    "propertyOrder" : 2300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "xssDetectionRedirectUri" : {
    "title" : "XSS detection redirect URI",
    "description" : "An application-specific Map that identifies a URI of the customized page if
XSS code has been detected. (property name: com.sun.identity.agents.config.xss.redirect.uri) <br>Hot-

```

swap: Yes
Examples:
To set a redirect target for application BankApp: enter BankApp in Map Key field, and enter a redirect URI in Corresponding Map Value field.",

```

    "propertyOrder" : 12900,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "webServiceInternalErrorContentFile" : {
    "title" : "Web Service Internal Error Content File",
    "description" : "The name of file that contains content used by
the Agent to generate an internal error fault for clients. (property name:
com.sun.identity.agents.config.webservice.internalerror.content) <br>Hot-swap: Yes",
    "propertyOrder" : 2500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "webServiceResponseProcessor" : {
    "title" : "Web Service Response Processor",
    "description" : "An implementation class of interface
com.sun.identity.agents.filter.IWebServiceResponseProcessor that can be used to process the web-
service responses. (property name: com.sun.identity.agents.config.webservice.responseprocessor)
<br>Hot-swap: Yes",
    "propertyOrder" : 2400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  }
}

```

```

    },
    "clientHostnameHeader" : {
      "title" : "Client Hostname Header",
      "description" : "HTTP header name that holds the Hostname of the client. (property name:
com.sun.identity.agents.config.client.hostname.header) <br>Hot-swap: Yes",
      "propertyOrder" : 1100,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "alternativeAgentHostname" : {
      "title" : "Alternative Agent Host Name",
      "description" : "Host name identifying the Agent protected server to the client browsers
if different from the actual host name. (property name: com.sun.identity.agents.config.agent.host)
<br>Hot-swap: Yes",
      "propertyOrder" : 4100,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "webServiceEnabled" : {
      "title" : "Web Service Enable",
      "description" : "Flag specifies if Web Service processing is enabled. (property name:
com.sun.identity.agents.config.webservice.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 2000,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    },
    "postDataStickySessionKeyValue" : {
      "title" : "PDP Stickysession key-value",

```

```

        "description" : "The provided key-value pair will be used for adding
to the URL or creating the cookie. <br>Example: <br>Set 'lb=server1' to append
to the querystring or to have 'lb' cookie with 'server1' value. (property name:
com.sun.identity.agents.config.postdata.preserve.sticky.session.value)",
        "propertyOrder" : 13500,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "missingPostDataPreservationEntryUri" : {
        "title" : "Missing PDP entry URI",
        "description" : "An application-specific URI Map that is used in case the referenced
PDP entry cannot be found in the local cache (due to ttl). In such cases it will redirect
to the specified URI, otherwise it will show a HTTP 403 Forbidden error. (property name:
com.sun.identity.agents.config.postdata.preserve.cache.noentry.url)<br>Examples: <br>To set a
redirect target for application BankApp: enter Bankapp in Map Key field and enter a redirect URI in
corresponding Map Value field.",
        "propertyOrder" : 13200,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "postDataPreservation" : {
        "title" : "Post Data Preservation enabled",
        "description" : "Post Data Preservation functionality basically stores any POST
data before redirecting the user to the login screen and after successful login the agent
will generate a page that autosubmits the same POST to the original URL. (property name:
com.sun.identity.agents.config.postdata.preserve.enable)",
        "propertyOrder" : 13100,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
            }
        }
    }
}

```

```
        "required" : false
      }
    },
    "jbossWebAuthenticationAvailable" : {
      "title" : "WebAuthentication Available",
      "description" : "(Not used in Agent 5 onwards) <br>Enable agent to make programmatic
authentication with the JBoss web container using WebAuthentication feature. (property name:
com.sun.identity.agents.config.jboss.webauth.available) <br>Hot-swap: Yes",
      "propertyOrder" : 12300,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    }
  }
}
```

1.79.1.2. delete

Usage:

```
am> delete J2eeAgents --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.79.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action J2eeAgents --realm Realm --actionName getAllTypes
```

1.79.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action J2eeAgents --realm Realm --actionName getCreatableTypes
```

1.79.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action J2eeAgents --realm Realm --actionName nextdescendents
```

1.79.1.6. query

Querying the agents of a specific type

Usage:

```
am> query J2eeAgents --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.79.1.7. read

Usage:

```
am> read J2eeAgents --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.79.1.8. update

Usage:

```
am> update J2eeAgents --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "amServicesJ2EEAgent" : {
      "type" : "object",
      "title" : "AM Services",
      "propertyOrder" : 3,
      "properties" : {
        "amLoginUrl" : {
          "title" : "AM Login URL",
          "description" : "AM login page URL. (property name:
com.sun.identity.agents.config.login.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Login",
          "propertyOrder" : 3700,
          "items" : {
            "type" : "string"
          },
          "type" : "object",
          "exampleValue" : "",
          "properties" : {
            "inherited" : {
              "type" : "boolean",
              "required" : true
            },
            "value" : {
              "type" : "array",
              "required" : false
            }
          }
        },
        "policyActionBooleanValues" : {
          "title" : "Policy Client Boolean Action Values",
          "description" : "Boolean action values for policy action names. (property name:
com.sun.identity.policy.client.booleanActionValues) <br>Hot-swap: No",
          "propertyOrder" : 11500,
          "type" : "object",
          "exampleValue" : "",
          "properties" : {
            "inherited" : {
              "type" : "boolean",
              "required" : true
            },
            "value" : {
              "type" : "string",
              "required" : false
            }
          }
        },
        "loginProbeTimeout" : {
          "title" : "Login URL Probe Timeout",
          "description" : "The connect timeout value in milliseconds, if also Login URL Probe is set
to true. (property name: com.sun.identity.agents.config.login.url.probe.timeout) <br>Hot-swap: Yes",
          "propertyOrder" : 4000,
          "type" : "object",
          "exampleValue" : "",

```

```

    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "urlPolicyEnvPostParameters" : {
    "title" : "URL Policy Env POST Parameters",
    "description" : "List of HTTP POST request parameters whose names and values
will be set in the environment map for URL policy evaluation at AM server. (property name:
com.sun.identity.agents.config.policy.env.post.param) <br>Hot-swap: Yes <br> Examples: <br> name <br>
phonenumber",
    "propertyOrder" : 11900,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "policyClientResourceComparators" : {
    "title" : "Policy Client Resource Comparators",
    "description" : "Resource Comparators to be used for different service names. (property
name: com.sun.identity.policy.client.resourceComparators) <br>Hot-swap: No",
    "propertyOrder" : 11600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "logoutProbeTimeout" : {
    "title" : "Logout URL Probe Timeout",
    "description" : "The connect timeout value in milliseconds, if also Logout URL Probe is set
to true. (property name: com.sun.identity.agents.config.logout.url.probe.timeout) <br>Hot-swap: Yes",
    "propertyOrder" : 12700,
    "type" : "object",
    "exampleValue" : "",

```

```

    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "urlPolicyEnvJsessionParameters" : {
    "title" : "URL Policy Env jsession Parameters",
    "description" : "List of HTTP SESSION attributes whose names and values will
be set in the environment map for URL policy evaluation at AM server. (property name:
com.sun.identity.agents.config.policy.env.jsession.param) <br>Hot-swap: Yes <br> Examples: <br> name
<br> phonenumber",
    "propertyOrder" : 12000,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "amLogoutUrl" : {
    "title" : "AM Logout URL",
    "description" : "AM logout page URL. (property name:
com.sun.identity.agents.config.logout.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
openseo/UI/Logout",
    "propertyOrder" : 12400,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "authServiceProtocol" : {
    "title" : "AM Authentication Service Protocol",

```

```

    "description" : "Protocol to be used by the AM authentication service. (property name:
com.ipplanet.am.server.protocol) <br>Hot-swap: No",
    "propertyOrder" : 10900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "probeLogoutUrl" : {
    "title" : "Logout URL Probe",
    "description" : "Specifies if agent will check the availability of these urls before
redirecting to them. (property name: com.sun.identity.agents.config.logout.url.probe.enabled)
<br>Hot-swap: Yes",
    "propertyOrder" : 12600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "conditionalLogoutUrl" : {
    "title" : "AM Conditional Logout URL",
    "description" : "(Only used in Agent 5 onwards) (property name:
org.forgerock.openam.agents.config.conditional.logout.url) <br>Hot-swap: Yes <br> Examples: <br>
match?url?param1=value1&param2=value2 <br> match/path?param1=value1&param2=value2&param3=value3",
    "propertyOrder" : 12550,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "loginUrlPrioritized" : {
    "title" : "Login URL Prioritized",

```

```

    "description" : "Specifies if failover sequence for Login URLs or CDSSO
URLs should be prioritized as defined in the AM Login URL list. (property name:
com.sun.identity.agents.config.login.url.prioritized) <br>Hot-swap: Yes",
    "propertyOrder" : 3800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "logoutUrlPrioritized" : {
    "title" : "Logout URL Prioritized",
    "description" : "Specifies if failover sequence for Logout URLs
should be prioritized as defined in the AM Login URL list. (property name:
com.sun.identity.agents.config.logout.url.prioritized) <br>Hot-swap: Yes",
    "propertyOrder" : 12500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "clientPollingPeriod" : {
    "title" : "Client Polling Period",
    "description" : "(Not used in Agent 5 onwards) <br>Time in seconds after which the
session client will request update of cached session information from the server. (property name:
com.iplanet.am.session.client.polling.period) <br>Hot-swap: No",
    "propertyOrder" : 10300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "policyClientClockSkew" : {
    "title" : "Policy Client Clock Skew",

```

```

    "description" : "Time in seconds which is allowed to accommodate the time difference
between the AM server machine and the remote policy client machine. (property name:
com.sun.identity.policy.client.clockSkew) <br>Hot-swap: No",
    "propertyOrder" : 11700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "policyEvaluationRealm" : {
    "title" : "Realm",
    "description" : "Which realm to start evaluating from. (property name:
org.forgerock.openam.agents.config.policy.evaluation.realm) <br>Hot-swap: Yes",
    "propertyOrder" : 5400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "policyClientCacheMode" : {
    "title" : "Policy Client Cache Mode",
    "description" : "Mode of caching to be used by remote policy client. (property name:
com.sun.identity.policy.client.cacheMode) <br>Hot-swap: No",
    "propertyOrder" : 11400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "authServiceHost" : {
    "title" : "AM Authentication Service Host Name",
    "description" : "Host name to be used by the AM authentication service. (property name:
com.ipplanet.am.server.host) <br>Hot-swap: No",
    "propertyOrder" : 11000,
    "type" : "object",

```

```

        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "useRedirectForCompositeAdvice" : {
        "title" : "Use HTTP-Redirect for composite advice",
        "description" : "Configure remote policy client to use HTTP-redirect instead of HTTP-POST
for composite advices. (property name: com.sun.identity.agents.config.policy.advice.use.redirect)
<br>Hot-swap: Yes",
        "propertyOrder" : 13000,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "authServicePort" : {
        "title" : "AM Authentication Service Port",
        "description" : "Port to be used by the AM authentication service. (property name:
com.ipplanet.am.server.port) <br>Hot-swap: No",
        "propertyOrder" : 11100,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "integer",
                "required" : false
            }
        }
    },
    "serviceDataCacheNotifications" : {
        "title" : "Enable Notification of Service Data Caches",
        "description" : "Enable the notifications for service management caches. (property name:
com.sun.identity.sm.notification.enabled) <br>Hot-swap: No",
        "propertyOrder" : 10700,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
    
```

```

        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "userDataCacheNotifications" : {
    "title" : "Enable Notification of User Data Caches",
    "description" : "Enable notifications for amsdk and IdRepo Caches. (property name:
com.sun.identity.idm.remote.notification.enabled) <br>Hot-swap: No",
    "propertyOrder" : 10500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "enableClientPolling" : {
    "title" : "Enable Client Polling",
    "description" : "Specifies if the session client must use polling for
updating session information and not depend upon server notifications. (property name:
com.ipplanet.am.session.client.polling.enable) <br>Hot-swap: No",
    "propertyOrder" : 10200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "probeLoginUrl" : {
    "title" : "Login URL Probe",
    "description" : "Specifies if agent will check the availability of these urls before
redirecting to them. (property name: com.sun.identity.agents.config.login.url.probe.enabled) <br>Hot-
swap: Yes",
    "propertyOrder" : 3900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {

```



```
        "type" : "boolean",
        "required" : false
    }
}
},
"policyClientPollingInterval" : {
    "title" : "Policy Client Polling Interval",
    "description" : "Duration in minutes after which the cached entries are refreshed by remote
policy client. (property name: com.sun.identity.agents.polling.interval) <br>Hot-swap: No",
    "propertyOrder" : 11300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
}
},
"policyNotifications" : {
    "title" : "Enable Policy Notifications",
    "description" : "Enable Notifications for remote policy client. (property name:
com.sun.identity.agents.notification.enabled) <br>Hot-swap: No",
    "propertyOrder" : 11200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
}
},
"serviceDataCacheTime" : {
    "title" : "Service Data Cache Time",
    "description" : "Cache update time in minutes for service configuration data. If set to '0'
no updates happen. (property name: com.sun.identity.sm.cacheTime) <br>Hot-swap: No",
    "propertyOrder" : 10800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
}
},
}
```

```
"policyEvaluationApplication" : {
  "title" : "Application",
  "description" : "Which application contains the policies to evaluate with. (property name:
org.forgerock.openam.agents.config.policy.evaluation.application) <br>Hot-swap: Yes",
  "propertyOrder" : 5500,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"conditionalLoginUrl" : {
  "title" : "AM Conditional Login URL",
  "description" : "(Only used in Agent 5 onwards) (property name:
org.forgerock.openam.agents.config.conditional.login.url) <br>Hot-swap: Yes <br> Examples: <br>
match|url?param1=value1&param2=value2 <br> match/path|?param1=value1&param2=value2&param3=value3",
  "propertyOrder" : 4010,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"urlPolicyEnvGetParameters" : {
  "title" : "URL Policy Env GET Parameters",
  "description" : "List of HTTP GET request parameters whose names and values will
be set in the environment map for URL policy evaluation at AM server. (property name:
com.sun.identity.agents.config.policy.env.get.param) <br>Hot-swap: Yes <br> Examples: <br> name <br>
phoneNumber",
  "propertyOrder" : 11800,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
```

```

        "required" : false
    }
}
},
"userDataCachePollingTime" : {
    "title" : "User Data Cache Polling Time",
    "description" : "Cache update time in minutes for user management data. If set to '0' no
updates happen. (property name: com.iplanet.am.sdk.remote.pollingTime) <br>Hot-swap: No",
    "propertyOrder" : 10600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
}
}
},
"applicationJ2EEAgentConfig" : {
    "type" : "object",
    "title" : "Application",
    "propertyOrder" : 1,
    "properties" : {
        "logoutRequestParameters" : {
            "title" : "Logout Request Parameter",
            "description" : "An application-specific Map that identifies a parameter
which when present in the HTTP request indicates a logout event. (property name:
com.sun.identity.agents.config.logout.request.param) <br>Valid key: the web application name.
<br>Valid value: the logout request parameter. <br>For this property, a global value can be set to
apply to all the applications that don't have their own specific logout request parameter. <br>Hot-
swap: Yes <br> Examples: <br>To set a global application logout request parameter: leave Map Key
field empty, and enter the global application logout request parameter logoutparam in Corresponding
Map Value field. <br> To set the logout request parameter for application BankApp: enter BankApp in
Map Key field, and enter the logout request parameter logoutparam in Corresponding Map Value field.",
            "propertyOrder" : 6100,
            "patternProperties" : {
                ".*" : {
                    "type" : "string"
                }
            },
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                },
                "value" : {
                    "type" : "object",
                    "required" : false
                }
            }
        }
    }
}
},

```

```

"defaultPrivilegedAttributes" : {
  "title" : "Default Privileged Attribute",
  "description" : "(Not used in Agent 5 onwards) <br>List of privileged
attributes that will be granted to all users who have a valid AM session. (property name:
com.sun.identity.agents.config.default.privileged.attribute) <br>Hot-swap: Yes <br> Example: <br>
AUTHENTICATED_USERS",
  "propertyOrder" : 9400,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"notEnforcedUris" : {
  "title" : "Not Enforced URIs",
  "description" : "List of URIs for which protection is not enforced by the Agent. (property
name: com.sun.identity.agents.config.notenforced.uri) <br>Hot-swap: Yes <br> Examples: <br> /BankApp/
public/* <br> /BankApp/images/*",
  "propertyOrder" : 7500,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"responseAttributeMap" : {
  "title" : "Response Attribute Mapping",
  "description" : "Maps the policy response attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.response.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of response attribute uid under name CUSTOM-USER-NAME: enter uid in Map Key field,
and enter CUSTOM-USER-NAME in Corresponding Map Value field.",
  "propertyOrder" : 9200,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  }
},
"type" : "object",

```

```

"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "object",
    "required" : false
  }
}
},
"notEnforcedUriRefreshSessionIdleTime" : {
  "title" : "Refresh Session Idle Time",
  "description" : "Indicates if opensso session idle time should be refreshed or reset for not
enforced URIs. (property name: com.sun.identity.agents.config.notenforced.refresh.session.idletime)
<br>Hot-swap: Yes",
  "propertyOrder" : 8600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"shortenedPrivilegeAttributeValues" : {
  "title" : "Shortened privilege attribute values",
  "description" : "When using privileged attribute type, this setting will ensure that
the membership details will be stored in a shortened format and not in the default universal ID
format.<br><br>By default the agent maps identity memberships using their universal IDs (e.g.
id=admin,ou=group,dc=openam,dc=forgerock,dc=org), however this may not be always acceptable. Using
this setting the identity membership details will be mapped in a shortened format, only including the
group's/role's name (e.g. admin). Be aware that in case there are both roles and groups in the data
store, this setting will make them indistinguishable from each other, i.e. if there is a group and a
role with the same name it will not be possible to differentiate them.",
  "propertyOrder" : 13600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"profileAttributeMap" : {
  "title" : "Profile Attribute Mapping",
  "description" : "Maps the profile attributes to be populated
under specific names for the currently authenticated user. (property name:

```

```

com.sun.identity.agents.config.profile.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of profile attribute cn under name CUSTOM-Common-Name: enter cn in Map Key field,
and enter CUSTOM-Common-Name in Corresponding Map Value field. <br> To populate the value of profile
attribute mail under name CUSTOM-Email: enter mail in Map Key field, and enter CUSTOM-Email in
Corresponding Map Value field.",
  "propertyOrder" : 8800,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  }
},
"privilegedAttributesToLowerCase" : {
  "title" : "Privileged Attributes To Lower Case",
  "description" : "(Not used in Agent 5 onwards) <br>Maps the privileged
attribute types to whether they should be converted to lowercase. (property name:
com.sun.identity.agents.config.privileged.attribute.lowercase) <br> Valid Keys: the privileged
attribute types, such as Group, Role. <br>Valid value: true, false. <br>Hot-swap: Yes <br> Example:
<br> Enter Group in Map Key field, and enter false in Corresponding Map Value field.",
  "propertyOrder" : 9600,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  }
},
"notEnforcedUriCacheEnabled" : {
  "title" : "Not Enforced URIs Cache Enabled",
  "description" : "Enables the caching of the Not Enforced URIs list evaluation results.
(property name: com.sun.identity.agents.config.notenforced.uri.cache.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 7700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {

```

```

        "type" : "boolean",
        "required" : true
    },
    "value" : {
        "type" : "boolean",
        "required" : false
    }
}
},
"applicationLogoutUri" : {
    "title" : "Application Logout URI",
    "description" : "An application-specific Map that identifies a request URI which indicates
a logout event. (property name: com.sun.identity.agents.config.logout.uri) <br>Valid key: the web
application name. <br>Valid value: the application logout URI. <br>For this property, a global value
can be set to apply to all the applications that don't have their own specific logout URI. <br>Hot-
swap: Yes <br> Examples: <br>To set a global application logout URI: leave Map Key field empty, and
enter the global application logout URI /logout.jsp in Corresponding Map Value field. <br> To set the
logout URI for application BankApp: enter BankApp in Map Key field, and enter the application logout
URI /BankApp/logout.jsp in Corresponding Map Value field.",
    "propertyOrder" : 6000,
    "patternProperties" : {
        ".*" : {
            "type" : "string"
        }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "object",
            "required" : false
        }
    }
}
},
"loginFormUri" : {
    "title" : "Login Form URI",
    "description" : "List of absolute URIs corresponding to an application's web.xml form-
login-page element. (property name: com.sun.identity.agents.config.login.form) <br>Hot-swap: Yes <br>
Example: <br> /BankApp/jsp/login.jsp",
    "propertyOrder" : 2800,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "array",
            "required" : false
        }
    }
}
}

```

```

    },
    "notEnforcedIpsCacheEnabled" : {
      "title" : "Not Enforced IP Cache Flag",
      "description" : "Enable caching of not-enforced IP list evaluation results. (property name: com.sun.identity.agents.config.notenforced.ip.cache.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 8100,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    },
    "resourceAccessDeniedUri" : {
      "title" : "Resource Access Denied URI",
      "description" : "An application-specific Map that identifies a URI of the customized access denied page. (property name: com.sun.identity.agents.config.access.denied.uri) <br>Valid key: the web application name. <br>Valid value: the customized application access denied page URI. <br>For this property, a global value can be set to apply to all the applications that don't have their own specific access denied page. <br>Hot-swap: Yes <br> Examples: <br>To set a global access denied page: leave Map Key field empty, and enter the global access denied page URI /sample/accessdenied.html in Corresponding Map Value field. <br> To set the access denied page URI for application BankApp: enter BankApp in Map Key field, and enter the application access denied page URI /BankApp/accessdenied.html in Corresponding Map Value field.",
      "propertyOrder" : 2700,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "object",
          "required" : false
        }
      }
    },
    "notEnforcedRuleCompoundSeparator" : {
      "title" : "Not Enforced Compound Rule Separator",
      "description" : "Specifies a separator for not enforced compound rules (Agent 5 only). The format for compound rules requires a list of IP rules, a separator (by default the | character), and a list of URI rules. For example, GET 192.168.1.1-192.168.4.3 | /images/* Configure a different separator (for example, &&) when working with the REGEX keyword to avoid invalid regular expressions.",
      "propertyOrder" : 7450,
      "type" : "object",
      "exampleValue" : "",

```



```

    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "loginErrorUri" : {
    "title" : "Login Error URI",
    "description" : "List of absolute URIs corresponding to an application's web.xml form-error-
page element. (property name: com.sun.identity.agents.config.login.error.uri) <br>Hot-swap: Yes <br>
Example: <br> /BankApp/jsp/error.jsp",
    "propertyOrder" : 2900,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "headerAttributeDateFormat" : {
    "title" : "Fetch Attribute Date Format",
    "description" : "Format of date attribute values to be used when the attribute is
being set as HTTP header. Format is based on java.text.SimpleDateFormat. (property name:
com.sun.identity.agents.config.attribute.date.format) <br>Hot-swap: Yes",
    "propertyOrder" : 8400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "logoutEntryUri" : {
    "title" : "Logout Entry URI",
    "description" : "An application-specific Map that identifies a URI to be used as an entry
point after successful logout and subsequent successful authentication if applicable. (property name:
com.sun.identity.agents.config.logout.entry.uri) <br>Valid key: the web application name. <br>Valid
value: the logout entry URI. <br>For this property, a global value can be set to apply to all the
applications that don't have their own specific logout entry URI. <br>Hot-swap: Yes <br> Examples:

```


To set a global application logout entry URI: leave Map Key field empty, and enter the global application logout entry URI /welcome.html in Corresponding Map Value field.
 To set the logout entry URI for application BankApp: enter BankApp in Map Key field, and enter the logout entry URI /BankApp/welcome.html in Corresponding Map Value field.",

```

    "propertyOrder" : 6300,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "cookieAttributeMultiValueSeparator" : {
    "title" : "Cookie Separator Character",
    "description" : "Character that will be used to separate multiple
values of the same attribute when it is being set as a cookie. (property name:
com.sun.identity.agents.config.attribute.cookie.separator) <br>Hot-swap: Yes",
    "propertyOrder" : 8300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "continuousSecurityHeaders" : {
    "title" : "Continuous Security Headers",
    "description" : "The name of the headers in the user's original request, that will be sent
as part of the payload during policy evaluation, which can then be accessed via the 'environment'
variable in a policy script. The 'key' is the name of the header to be sent, and the 'value' is the
name which it will appear as in the policy evaluation script.It is possible to map multiple headers
to the same name (they will simply appear as an array in the evaluation script). If the header
doesn't exist, then the empty string will be sent.",
    "propertyOrder" : 3211,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {

```

```

        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "object",
            "required" : false
        }
    }
},
"privilegedSessionAttribute" : {
    "title" : "Privileged Session Attribute",
    "description" : "(Not used in Agent 5 onwards) <br>List of session property
names which hold privileged attributes for the authenticated user. (property name:
com.sun.identity.agents.config.privileged.session.attribute) <br>Hot-swap: Yes <br> Example: <br>
UserToken",
    "propertyOrder" : 9700,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "array",
            "required" : false
        }
    }
},
"privilegedAttributeMap" : {
    "title" : "Privileged Attribute Mapping",
    "description" : "(Not used in Agent 5 onwards) <br>Map if using Enable Privileged
Attribute Mapping. (property name: com.sun.identity.agents.config.privileged.attribute.mapping)
<br>Hot-swap: Yes <br> Examples: <br> To map UUID id=manager,ou=group,dc=openam,dc=forgerock,dc=org
to the principal name am_manager_role specified in webapp's deployment descriptor: enter
id=manager,ou=group,dc=openam,dc=forgerock,dc=org in Map Key field, and enter am_manager_role in
Corresponding Map Value field. <br> To map UUID id=employee,ou=group,dc=openam,dc=forgerock,dc=org
to the principal name am_employee_role specified in webapp's deployment descriptor: enter
id=employee,ou=group,dc=openam,dc=forgerock,dc=org in Map Key field, and enter am_employee_role in
Corresponding Map Value field.",
    "propertyOrder" : 9900,
    "patternProperties" : {
        ".*" : {
            "type" : "string"
        }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "object",

```

```

        "required" : false
    }
}
},
"profileAttributeFetchMode" : {
    "title" : "Profile Attribute Fetch Mode",
    "description" : "The mode of fetching profile attributes. (property name:
com.sun.identity.agents.config.profile.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 8700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
},
"privilegedAttributeMappingEnabled" : {
    "title" : "Enable Privileged Attribute Mapping",
    "description" : "(Not used in Agent 5 onwards) <br>Enable a mapping from
the original value of an attribute to another value. To satisfy container-specific
restrictions on character set being used in certain configuration files. (property name:
com.sun.identity.agents.config.privileged.attribute.mapping.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 9800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
},
"sessionAttributeMap" : {
    "title" : "Session Attribute Mapping",
    "description" : "Maps the session attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.session.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of session attribute UserToken under name CUSTOM-userid: enter UserToken in Map
Key field, and enter CUSTOM-userid in Corresponding Map Value field.",
    "propertyOrder" : 9000,
    "patternProperties" : {
        ".*" : {
            "type" : "string"
        }
    }
},
"type" : "object",
"exampleValue" : "",
"properties" : {
    "inherited" : {

```

```

        "type" : "boolean",
        "required" : true
    },
    "value" : {
        "type" : "object",
        "required" : false
    }
},
"applicationLogoutHandlers" : {
    "title" : "Application Logout Handler",
    "description" : "An application-specific Map that identifies a handler to be used for logout
processing. (property name: com.sun.identity.agents.config.logout.application.handler) <br>Valid
key: the web application name. <br>Valid value: the application logout handler class name. <br>For
this property, a global value can be set to apply to all the applications that don't have their own
specific logout handler. <br>Hot-swap: Yes <br> Examples: <br>To set a global application logout
handler: leave Map Key field empty, and enter the global application logout handler class name
GlobalApplicationLogoutHandler in Corresponding Map Value field. <br>To set the logout handler for
application BankApp: enter BankApp in Map Key field, and enter the application logout handler class
name BankAppLogoutHandler in Corresponding Map Value field.",
    "propertyOrder" : 5900,
    "patternProperties" : {
        ".*" : {
            "type" : "string"
        }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "object",
            "required" : false
        }
    }
},
"notEnforcedUrisCacheSize" : {
    "title" : "Not Enforced URIs Cache Size",
    "description" : "Size of the cache to be used if caching of not enforced URI list evaluation
results is enabled. (property name: com.sun.identity.agents.config.notenforced.uri.cache.size)
<br>Hot-swap: Yes",
    "propertyOrder" : 7800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
},
"notEnforcedIpsCacheSize" : {

```

```

    "title" : "Not Enforced IP Cache Size",
    "description" : "Size of the cache to be used if Not Enforced IP Cache Flag is enabled.
(property name: com.sun.identity.agents.config.notenforced.ip.cache.size) <br>Hot-swap: Yes",
    "propertyOrder" : 8200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "logoutIntrospection" : {
    "title" : "Logout Introspect Enabled",
    "description" : "Allows the Agent to search HTTP request body to locate logout parameter.
(property name: com.sun.identity.agents.config.logout.introspect.enabled) <br>Hot-swap: Yes",
    "propertyOrder" : 6200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "invertNotEnforcedIps" : {
    "title" : "Not Enforced IP Invert List",
    "description" : "Client IP Addresses to invert protection of IP
addresses listed in the related Not Enforced Client IP List. (property name:
com.sun.identity.agents.config.notenforced.ip.invert) <br>Hot-swap: Yes",
    "propertyOrder" : 8000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "invertNotEnforcedUris" : {
    "title" : "Invert Not Enforced URIs",
    "description" : "Inverts protection of URIs specified in Not Enforced URIs list. When
set to true, it indicates that the URIs specified should be enforced and all other URIs should be

```

```

not enforced by the Agent. (property name: com.sun.identity.agents.config.notenforced.uri.invert)
<br>Hot-swap: Yes",
  "propertyOrder" : 7600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"responseAttributeFetchMode" : {
  "title" : "Response Attribute Fetch Mode",
  "description" : "The mode of fetching policy response attributes. (property name:
com.sun.identity.agents.config.response.attribute.fetch.mode) <br>Hot-swap: Yes",
  "propertyOrder" : 9100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"continuousSecurityCookies" : {
  "title" : "Continuous Security Cookies",
  "description" : "The name of the cookies to be sent as part of the payload during policy
evaluation, which can be accessed via the 'environment' variable in a policy script. The 'key' is
the name of the cookie to be sent, and the 'value' is the name which it will appear as in the policy
evaluation script. It is possible to map multiple cookies to the same name (they will simply appear
as an array in the evaluation script). If the cookie doesn't exist, then the empty string will be
sent.",
  "propertyOrder" : 3210,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  }
}

```

```

    }
  },
  "loginContentFile" : {
    "title" : "Login Content File Name",
    "description" : "Complete path and name of custom login content file. (property name:
com.sun.identity.agents.config.login.content.file) <br>Hot-swap: Yes",
    "propertyOrder" : 3100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "cookieAttributeUrlEncoded" : {
    "title" : "Attribute Cookie Encode",
    "description" : "Indicates if the value of the attribute should be URL encoded before being
set as a cookie. (property name: com.sun.identity.agents.config.attribute.cookie.encode) <br>Hot-
swap: Yes",
    "propertyOrder" : 8500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "customAuthenticationHandlers" : {
    "title" : "Custom Authentication Handler",
    "description" : "Application specific authentication handler to authenticate the logged
on user with the application server. (property name: com.sun.identity.agents.config.auth.handler)
<br>Valid key: the web application name. <br>Valid value: the authentication handler class
name. <br>Hot-swap: Yes <br>Example: <br>To set authentication handler for application BankApp:
enter BankApp in Map Key field, and enter authentication handler class name BankAuthHandler in
Corresponding Map Value field.",
    "propertyOrder" : 3200,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}

```



```

    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  },
  "sessionAttributeFetchMode" : {
    "title" : "Session Attribute Fetch Mode",
    "description" : "The mode of fetching session attributes. (property name:
com.sun.identity.agents.config.session.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 8900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "useInternalLogin" : {
    "title" : "Use Internal Login",
    "description" : "Set to false if want to customize Login Content File instead of default
internal content provided. (property name: com.sun.identity.agents.config.login.use.internal)
<br>Hot-swap: Yes",
    "propertyOrder" : 3000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "privilegedAttributeType" : {
    "title" : "Privileged Attribute Type",
    "description" : "(Not used in Agent 5 onwards) <br>List of
privileged attribute types that will be fetched for each user. (property name:
com.sun.identity.agents.config.privileged.attribute.type) <br>Hot-swap: Yes <br> Example: <br>
Group",
    "propertyOrder" : 9500,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",

```

```

    "required" : true
  },
  "value" : {
    "type" : "array",
    "required" : false
  }
},
"notEnforcedIps" : {
  "title" : "Not Enforced Client IP List",
  "description" : "No authentication and authorization protection from agent
are required for the requests coming from these client IP addresses. (property name:
com.sun.identity.agents.config.notenforced.ip) <br>Hot-swap: Yes <br> Examples: <br> 192.18.145.*
<br> 192.18.146.123",
  "propertyOrder" : 7900,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"customLogoutHandlers" : {
  "title" : "Custom Logout Handler",
  "description" : "Application specific logout handler to log out a user with the application
server. (property name: com.sun.identity.agents.config.logout.handler) <br>Valid key: the web
application name. <br>Valid value: the logout handler class name. <br>Hot-swap: Yes <br> Example:
<br>To set logout handler for application BankApp: enter BankApp in Map Key field, and enter logout
handler class name BankLogoutHandler in Corresponding Map Value field.",
  "propertyOrder" : 3300,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  }
},
"customVerificationHandlers" : {
  "title" : "Custom Verification Handler",

```

```

        "description" : "Application specific verification handler to validate the user credentials
with the local repository. (property name: com.sun.identity.agents.config.verification.handler)
<br>Valid key: the web application name. <br>Valid value: the verification handler class name.
<br>Hot-swap: Yes <br> Example: <br> To set verification handler for application BankApp: enter
BankApp in Map Key field, and enter verification handler class name BankVerificationHandler in
Corresponding Map Value field.",
        "propertyOrder" : 3400,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "object",
                "required" : false
            }
        }
    }
},
"globalJ2EEAgentConfig" : {
    "type" : "object",
    "title" : "Global",
    "propertyOrder" : 0,
    "properties" : {
        "fqdnMapping" : {
            "title" : "FQDN Virtual Host Map",
            "description" : "Maps virtual, invalid, or partial hostnames, and IP addresses to the FQDN
to access protected resources. (property name: com.sun.identity.agents.config.fqdn.mapping) <br>Hot-
swap: Yes <br> Examples: <br> To map the partial hostname myserver to myserver.mydomain.com: enter
myserver in the Map Key field and myserver.mydomain.com in the Corresponding Map Value field. To map
a virtual server rst.hostname.com that points to the actual server abc.hostname.com: enter valid1 in
the Map Key field and rst.hostname.com in the Corresponding Map Value field.",
            "propertyOrder" : 6600,
            "patternProperties" : {
                ".*" : {
                    "type" : "string"
                }
            },
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                },
                "value" : {
                    "type" : "object",
                    "required" : false
                }
            }
        }
    }
},

```

```

"agentConfigChangeNotificationsEnabled" : {
  "title" : "Agent Configuration Change Notification",
  "description" : "Enable agent to receive notification messages from AM server for
configuration changes. (property name: com.sun.identity.agents.config.change.notification.enable)
<br>Hot-swap: Yes",
  "propertyOrder" : 12100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"userpassword" : {
  "title" : "Password",
  "description" : "",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"filterMode" : {
  "title" : "Agent Filter Mode",
  "description" : "Specifies the mode of operation of the Filter. (property name:
com.sun.identity.agents.config.filter.mode) <br>Valid key: the web application name. <br>Valid
values: ALL, J2EE_POLICY (Not used in Agent 5 onwards), URL_POLICY, SSO_ONLY, NONE <br>For this
property, a global value can be set to apply to all the applications that don't have their own
specific filter mode. <br>Hot-swap: No <br>Examples: <br>To set ALL as the global filter mode:
leave Map Key field empty, and enter ALL in Corresponding Map Value field. <br>To set URL_POLICY
as the filter mode for application BankApp: enter BankApp in Map Key field, and enter URL_POLICY in
Corresponding Map Value field.",
  "propertyOrder" : 500,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  }
},
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "object",
    "required" : false
  }
}
},
"websocketConnectionIntervalInMinutes" : {
  "title" : "Web Socket Connection Interval",

```

```
"description" : "Interval in minutes by which agents reopen their web socket connection to ensure a fair distribution of connections across AM servers. (Agent 5 only).",
"propertyOrder" : 12105,
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "integer",
    "required" : false
  }
}
},
"fqdnCheck" : {
  "title" : "FQDN Check",
  "description" : "Enables checking of fqdn default value and fqdn map values. (property name: com.sun.identity.agents.config.fqdn.check.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 6400,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"remoteLogFilename" : {
  "title" : "Remote Log File Name",
  "description" : "Name of file stored on AM server that contains agent audit messages. (property name: com.sun.identity.agents.config.remote.logfile) <br>Hot-swap: Yes",
  "propertyOrder" : 1700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"userMappingMode" : {
  "title" : "User Mapping Mode",
  "description" : "Specifies mechanism agent uses to determine user-ID. (property name: com.sun.identity.agents.config.user.mapping.mode) <br>Hot-swap: Yes",
  "propertyOrder" : 600,
  "type" : "object",
  "exampleValue" : "",
```

```

    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "customResponseHeader" : {
    "title" : "Custom Response Header",
    "description" : "Map specifies the custom headers that are set by the Agent on the client browser. The key is the header name and the value represents the header value. (property name: com.sun.identity.agents.config.response.header) <br>Hot-swap: Yes <br> Example: <br> To set the custom header Cache-Control to value no-cache: enter Cache-Control in Map Key field, and enter no-cache in Corresponding Map Value field.",
    "propertyOrder" : 7000,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "debugLevel" : {
    "title" : "Agent Debug Level",
    "description" : "Specifies type of agent debug messages to log. (property name: com.iplanet.services.debug.level) <br>Hot-swap: Yes",
    "propertyOrder" : 10000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "localAuditRotationSize" : {
    "title" : "Local Audit Log Rotation Size",
    "description" : "Size limit when a local audit log file is rotated to a new file. (property name: com.sun.identity.agents.config.local.log.size) <br>Hot-swap: Yes",

```

```

    "propertyOrder" : 1900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "loginAttemptLimit" : {
    "title" : "Login Attempt Limit",
    "description" : "Limit of failed login attempts for a user's single browser session until triggering the blocking of the user request. Value of 0 disables this feature. (property name: com.sun.identity.agents.config.login.attempt.limit) <br>Hot-swap: Yes",
    "propertyOrder" : 4400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "userTokenName" : {
    "title" : "User Token Name",
    "description" : "Session property name for user-ID of the authenticated user in session. (property name: com.sun.identity.agents.config.user.token) <br>Hot-swap: Yes",
    "propertyOrder" : 900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "fqdnDefault" : {
    "title" : "FQDN Default",
    "description" : "Fully qualified hostname that the users should use in order to access resources. (property name: com.sun.identity.agents.config.fqdn.default) <br>Hot-swap: Yes",
    "propertyOrder" : 6500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {

```

```

    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"redirectAttemptLimit" : {
  "title" : "Redirect Attempt Limit",
  "description" : "Number of successive single point redirects that a user can make using a
single browser session which will trigger the blocking of the user request. Set to 0 to disable this
feature. (property name: com.sun.identity.agents.config.redirect.attempt.limit) <br>Hot-swap: Yes",
  "propertyOrder" : 7100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : false
    }
  }
},
"auditLogLocation" : {
  "title" : "Audit Log Location",
  "description" : "Specifies where audit messages should be logged. (property name:
com.sun.identity.agents.config.log.disposition) <br>Hot-swap: Yes",
  "propertyOrder" : 1600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"userPrincipalFlag" : {
  "title" : "User Principal Flag",
  "description" : "Use principal instead of just the user-ID for authenticating the user.
(property name: com.sun.identity.agents.config.user.principal) <br>Hot-swap: Yes",
  "propertyOrder" : 800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},

```



```

        "value" : {
            "type" : "boolean",
            "required" : false
        }
    },
    "userAttributeName" : {
        "title" : "User Attribute Name",
        "description" : "Name of the attribute which contains the user-ID. (property name:
com.sun.identity.agents.config.user.attribute.name) <br>Hot-swap: Yes",
        "propertyOrder" : 700,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "repositoryLocation" : {
        "title" : "Location of Agent Configuration Repository",
        "description" : "Indicates agent's configuration located either on agent's host or centrally
on AM server.",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "jwtName" : {
        "title" : "JWT Cookie Name",
        "description" : "The name used by the agent to set the OIDC JWT on the user's browser.
(Agent 5 only).",
        "propertyOrder" : 11201,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "configurationReloadInterval" : {
        "title" : "Configuration Reload Interval",
        "description" : "Interval in seconds between configuration reloads. (property name:
com.sun.identity.agents.config.load.interval) <br>Hot-swap: Yes",
        "propertyOrder" : 1200,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {

```

```

    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : false
    }
  }
},
"agentgroup" : {
  "title" : "Group",
  "description" : "Add the agent to a group to allow inheritance of property values from the
group. <br>Changing the group will update inherited property values. <br>Inherited property values
are copied to the agent.",
  "propertyOrder" : 50,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"auditAccessType" : {
  "title" : "Audit Access Types",
  "description" : "Types of messages to log based on user URL access attempts. (property name:
com.sun.identity.agents.config.audit.accesstype) <br>Hot-swap: Yes",
  "propertyOrder" : 1500,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"localAuditLogRotation" : {
  "title" : "Rotate Local Audit Log",
  "description" : "Flag to indicate that audit log files should be rotated when reaching a
certain size. (property name: com.sun.identity.agents.config.local.log.rotate) <br>Hot-swap: Yes",
  "propertyOrder" : 1800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"cdssoRootUrl" : {
  "title" : "Agent Root URL for CDSO",

```

```
"description" : "The agent root URL for CDSSO. The valid value is in the following format:  
<br>protocol://hostname:port/<br> The protocol represents the protocol used, such as http or https.  
The hostname represents the host name of the machine on which the agent resides. The port represents  
the port number on which the agent is installed. The slash following the port number is required.",  
  "propertyOrder" : 22700,  
  "items" : {  
    "type" : "string"  
  },  
  "type" : "object",  
  "exampleValue" : "",  
  "properties" : {  
    "inherited" : {  
      "type" : "boolean",  
      "required" : true  
    },  
    "value" : {  
      "type" : "array",  
      "required" : false  
    }  
  }  
},  
  "httpSessionBinding" : {  
    "title" : "HTTP Session Binding",  
    "description" : "If true will invalidate the http session when login has failed,  
user has no SSO session, or principal user name does not match SSO user name. (property name:  
com.sun.identity.config.httpsession.binding) <br>Hot-swap: Yes",  
    "propertyOrder" : 3500,  
    "type" : "object",  
    "exampleValue" : "",  
    "properties" : {  
      "inherited" : {  
        "type" : "boolean",  
        "required" : true  
      },  
      "value" : {  
        "type" : "boolean",  
        "required" : false  
      }  
    }  
  },  
  "agentNotificationUrl" : {  
    "title" : "Agent Notification URL",  
    "description" : "URL used by agent to register notification listeners. (property name:  
com.sun.identity.client.notification.url) <br>Hot-swap: No",  
    "propertyOrder" : 300,  
    "type" : "object",  
    "exampleValue" : "",  
    "properties" : {  
      "inherited" : {  
        "type" : "boolean",  
        "required" : true  
      },  
      "value" : {  
        "type" : "string",  
        "required" : false  
      }  
    }  
  }  
},  
  "status" : {
```

```

    "title" : "Status",
    "description" : "Status of the agent configuration.",
    "propertyOrder" : 200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  }
},
"ssoJ2EEAgentConfig" : {
  "type" : "object",
  "title" : "SSO",
  "propertyOrder" : 2,
  "properties" : {
    "cookieResetDomains" : {
      "title" : "Cookies Reset Domain Map",
      "description" : "Maps cookie names specified in Cookie Reset Name List to value
being the domain of this cookie to be used when a reset event occurs. (property name:
com.sun.identity.agents.config.cookie.reset.domain) <br>Hot-swap: Yes",
      "propertyOrder" : 4800,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "object",
          "required" : false
        }
      }
    },
    "ssoCacheEnabled" : {
      "title" : "SSO Cache Enable",
      "description" : "Specifies if the SSO Cache is active for the agent.
Cache is used through public APIs exposed by the agent SDK. (property name:
com.sun.identity.agents.config.amsso.cache.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 4500,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
}

```

```

    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  },
  "cdssoUrls" : {
    "title" : "CDSSO Servlet URL",
    "description" : "List of URLs of the available CDSSO controllers that may be used by the
Agent for CDSSO processing. (property name: com.sun.identity.agents.config.cdsso.cdcservlet.url)
<br>Hot-swap: Yes <br> Example: <br> http://host:port/opensso/cdcservlet",
    "propertyOrder" : 5200,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "cdssoRedirectUri" : {
    "title" : "CDSSO Redirect URI",
    "description" : "An intermediate URI that is used by the Agent for processing CDSSO
requests. (property name: com.sun.identity.agents.config.cdsso.redirect.uri) <br>Hot-swap: Yes",
    "propertyOrder" : 5100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "cookieResetPaths" : {
    "title" : "Cookies Reset Path Map",
    "description" : "Maps cookie names specified in Cookie Reset Name List to value
being the path of this cookie to be used when a reset event occurs. (property name:
com.sun.identity.agents.config.cookie.reset.path) <br>Hot-swap: Yes",
    "propertyOrder" : 4900,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    }
  },
  "type" : "object",

```

```

    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "cdssoClockSkew" : {
    "title" : "CDSSO Clock Skew",
    "description" : "Time in seconds to be used by the Agent to determine the validity of the
CDSSO AuthnResponse assertion. (property name: com.sun.identity.agents.config.cdsso.clock.skew)
<br>Hot-swap: Yes",
    "propertyOrder" : 5300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "amCookieName" : {
    "title" : "Cookie Name",
    "description" : "Name of the SSO Token cookie used between the AM server and the Agent.
(property name: com.iplanet.am.cookie.name) <br>Hot-swap: No",
    "propertyOrder" : 10100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "cdssoTrustedIdProvider" : {
    "title" : "CDSSO Trusted ID Provider",
    "description" : "List of AM Server/ID providers that should be trusted
by the agent, when evaluating the CDC Liberty Responses. (property name:
com.sun.identity.agents.config.cdsso.trusted.id.provider) <br>Hot-swap: Yes <br> Example: <br>
http://host:port/opensso/cdcservlet",
    "propertyOrder" : 5600,
    "items" : {
      "type" : "string"
    }
  },

```

```

        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "cookieResetEnabled" : {
        "title" : "Cookie Reset",
        "description" : "Agent resets cookies in the response before redirecting to authentication.
(property name: com.sun.identity.agents.config.cookie.reset.enable) <br>Hot-swap: Yes",
        "propertyOrder" : 4600,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "cookieResetNames" : {
        "title" : "Cookies Reset Name List",
        "description" : "Cookie names that will be reset by the Agent if Cookie Reset is enabled.
(property name: com.sun.identity.agents.config.cdsso.cookie.reset.name) <br>Hot-swap: Yes",
        "propertyOrder" : 4700,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "cdsso" : {
        "title" : "Cross Domain SSO",
        "description" : "Enables Cross Domain Single SignOn. (property name:
com.sun.identity.agents.config.cdsso.enable) <br>Hot-swap: Yes",
        "propertyOrder" : 5000,
        "type" : "object",
        "exampleValue" : "",
    
```

```

    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "cdssoDomainList" : {
    "title" : "CDSSO Domain List",
    "description" : "Domains for which cookies have to be set in a CDSSO scenario. (property
name: com.sun.identity.agents.config.cdsso.domain) <br>Hot-swap: Yes <br> Example: <br> .sun.com",
    "propertyOrder" : 5800,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "cdssoSecureCookies" : {
    "title" : "CDSSO Secure Enable",
    "description" : "The SSO Token cookie set by the agent in the different domains in CDSSO
mode will be marked secure. Only transmitted if the communications channel with host is a secure one.
(property name: com.sun.identity.agents.config.cdsso.secure.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 5700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  }
},
"miscJ2EEAgentConfig" : {
  "type" : "object",
  "title" : "Miscellaneous",
  "propertyOrder" : 4,
  "properties" : {
    "legacyUserAgentSupport" : {

```



```

    "title" : "Legacy User Agent Support Enable",
    "description" : "Enables support for legacy user agents (browser). (property name:
com.sun.identity.agents.config.legacy.support.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 6700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "encryptionProvider" : {
    "title" : "Encryption Provider",
    "description" : "Specifies the encryption provider implementation to be used by the Agent.
(property name: com.ipanet.security.encryptor) <br>Hot-swap: No",
    "propertyOrder" : 10400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "portCheckFile" : {
    "title" : "Port Check File",
    "description" : "Name or complete path of a file that has the necessary
content needed to handle requests that need port correction. (property name:
com.sun.identity.agents.config.port.check.file) <br>Hot-swap: Yes",
    "propertyOrder" : 7300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "portCheckSetting" : {
    "title" : "Port Check Setting",
    "description" : "Map of port versus protocol entries with the key being the listening port
number and value being the listening protocol to be used by the Agent to identify requests with
invalid port numbers. (property name: com.sun.identity.agents.config.port.check.setting) <br>Hot-

```

```

swap: Yes <br> Example: <br> To map port 80 to protocol http: enter 80 in Map Key field, and enter
http in Corresponding Map Value field.",
  "propertyOrder" : 7400,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "object",
      "required" : false
    }
  }
},
"portCheckEnabled" : {
  "title" : "Port Check Enable",
  "description" : "Indicates if port check functionality is enabled or disabled. (property
name: com.sun.identity.agents.config.port.check.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 7200,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"gotoParameterName" : {
  "title" : "Goto Parameter Name",
  "description" : "Property used only when CDSSO is enabled. Default value
should be changed only when the login URL has a landing page specified <br> Example :
com.sun.identity.agents.config.cdssso.cdcservlet.url = http://host:port/opensso/cdcservlet?
goto=http://agent:port/landing.jsp <br> The parameter is used by the Agent to append the original
request URL to this cdcservlet URL. This parameter is consumed by the landing page to redirect to
the original URL. (property name: com.sun.identity.agents.config.redirect.param) <br>Hot-swap: Yes
<br> Example: com.sun.identity.agents.config.redirect.param = goto2<br> The complete URL sent for
authentication will be <br> http://host:port/opensso/cdcservlet?goto=http://agent:port/landing.jsp?
goto2=http://agent.port/original.jsp",
  "propertyOrder" : 3600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {

```

```

        "type" : "string",
        "required" : false
    }
}
},
"bypassPrincipallist" : {
    "title" : "Bypass Principal List",
    "description" : "List of principals that are bypassed by the Agent for authentication and
search purposes. (property name: com.sun.identity.agents.config.bypass.principal) <br>Hot-swap: Yes
<br> Examples: <br> guest <br> testuser",
    "propertyOrder" : 9300,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "array",
            "required" : false
        }
    }
},
"localeCountry" : {
    "title" : "Locale Country",
    "description" : "(property name: com.sun.identity.agents.config.locale.country) <br>Hot-
swap: No",
    "propertyOrder" : 1400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
},
"legacyUserAgentList" : {
    "title" : "Legacy User Agent List",
    "description" : "List of user agent header values that identify legacy
browsers. Entries in this list can have wild card character '*'. (property name:
com.sun.identity.agents.config.legacy.user.agent) <br>Hot-swap: Yes",
    "propertyOrder" : 6800,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",

```

```

        "required" : true
    },
    "value" : {
        "type" : "array",
        "required" : false
    }
},
"ignorePathInfo" : {
    "title" : "Ignore Path Info in Request URL",
    "description" : "The path info will be stripped from the request URL while doing Not
Enforced List check and url policy evaluation if the value is set to true. (property name:
com.sun.identity.agents.config.ignore.path.info) <br>Hot-swap: Yes",
    "propertyOrder" : 18600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
},
"legacyRedirectUri" : {
    "title" : "Legacy User Agent Redirect URI",
    "description" : "An intermediate URI used by the Agent to redirect legacy user agent
requests. (property name: com.sun.identity.agents.config.legacy.redirect.uri) <br>Hot-swap: Yes",
    "propertyOrder" : 6900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
},
"localeLanguage" : {
    "title" : "Locale Language",
    "description" : "(property name: com.sun.identity.agents.config.locale.language) <br>Hot-
swap: No",
    "propertyOrder" : 1300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",

```

```

        "required" : false
    }
}
},
"advancedJ2EEAgentConfig" : {
    "type" : "object",
    "title" : "Advanced",
    "propertyOrder" : 5,
    "properties" : {
        "webServiceAuthorizationErrorContentFile" : {
            "title" : "Web Service Authorization Error Content File",
            "description" : "The name of file that contains content used by the
Agent to generate an authorization error fault for clients. (property name:
com.sun.identity.agents.config.webservice.autherror.content) <br>Hot-swap: Yes",
            "propertyOrder" : 2600,
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                },
                "value" : {
                    "type" : "string",
                    "required" : false
                }
            }
        },
        "clientIpHeader" : {
            "title" : "Client IP Address Header",
            "description" : "HTTP header name that holds the IP address of the client. (property name:
com.sun.identity.agents.config.client.ip.header) <br>Hot-swap: Yes",
            "propertyOrder" : 1000,
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                },
                "value" : {
                    "type" : "string",
                    "required" : false
                }
            }
        },
        "alternativeAgentProtocol" : {
            "title" : "Alternative Agent Protocol",
            "description" : "Protocol being used (http/https) by the client browsers to communicate with
the Agent protected server if different from the actual protocol used by the server. (property name:
com.sun.identity.agents.config.agent.protocol) <br>Hot-swap: Yes",
            "propertyOrder" : 4300,
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",

```

```

        "required" : true
    },
    "value" : {
        "type" : "string",
        "required" : false
    }
}
},
"postDataPreserveCacheEntryMaxTotalSizeMb" : {
    "title" : "PDP Maximum Cache Size",
    "description" : "Maximum size of the PDP cache, in megabytes (Property name:
org.forgerock.openam.agents.config.postdata.preserve.cache.entry.max.total.size.mb). (Agent 5 only)",
    "propertyOrder" : 13600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
}
},
"webServiceEndpoints" : {
    "title" : "Web Service End Points",
    "description" : "A list of Web Application end points that represent Web Services. (property
name: com.sun.identity.agents.config.webservice.endpoint) <br>Hot-swap: Yes",
    "propertyOrder" : 2100,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "array",
            "required" : false
        }
    }
}
},
"possibleXssCodeElements" : {
    "title" : "Possible XSS code elements",
    "description" : "If one of these strings occurs in the request, the client is redirected to
an error page. (property name: com.sun.identity.agents.config.xss.code.elements) <br>Hot-swap: Yes",
    "propertyOrder" : 12800,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {

```

```

        "type" : "boolean",
        "required" : true
    },
    "value" : {
        "type" : "array",
        "required" : false
    }
}
},
"postDataStickySessionMode" : {
    "title" : "PDP StickySession mode",
    "description" : "The PDP mechanism needs sticky loadbalancing, the URL mode
will append a querystring, while the Cookie mode will create a cookie. (property name:
com.sun.identity.agents.config.postdata.preserve.stickysession.mode)",
    "propertyOrder" : 13400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
},
"webServiceProcessGetEnabled" : {
    "title" : "Web Service Process GET Enable",
    "description" : "Flag to indicates if the processing of HTTP GET requests for Web Service
endpoints is enabled. (property name: com.sun.identity.agents.config.webservice.process.get.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 2200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
},
"customProperties" : {
    "title" : "Custom Properties",
    "description" : "Additional properties that allow users to augment the set of properties
supported by agent. (property name: com.sun.identity.agents.config.freeformproperties) <br>Hot-
swap: Yes <br> Examples: <br> customproperty=custom-value1 <br> customlist[0]=customlist-
value-0 <br> customlist[1]=customlist-value-1 <br> custommap[key1]=custommap-value-1 <br>
custommap[key2]=custommap-value-2",
    "propertyOrder" : 12200,
    "items" : {
        "type" : "string"
    },
    "type" : "object",

```

```

        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "alternativeAgentPort" : {
        "title" : "Alternative Agent Port Name",
        "description" : "Port number identifying the Agent protected server listening
port to the client browsers if different from the actual listening port. (property name:
com.sun.identity.agents.config.agent.port) <br>Hot-swap: Yes",
        "propertyOrder" : 4200,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "postDataPreserveCacheEntryMaxEntries" : {
        "title" : "PDP Maximum Number of Cache Entries",
        "description" : "Maximum number of entries to hold in the PDP cache (Property name:
org.forgerock.openam.agents.config.postdata.preserve.cache.entry.max.entries) (Agent 5 only).",
        "propertyOrder" : 13550,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "integer",
                "required" : false
            }
        }
    },
    "postDataCacheTtl" : {
        "title" : "PDP entry TTL",
        "description" : "This value tells how long a given POST entry should be
stored in the local cache (in milliseconds), default value is 300000. (property name:
com.sun.identity.agents.config.postdata.preserve.cache.entry.ttl)",
        "propertyOrder" : 13300,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {

```



```

        "type" : "boolean",
        "required" : true
    },
    "value" : {
        "type" : "integer",
        "required" : false
    }
},
"webServiceAuthenticator" : {
    "title" : "Web Service Authenticator",
    "description" : "An implementation class of interface
com.sun.identity.agents.filter.IWebServiceAuthenticator that can be used to authenticate web-service
requests. (property name: com.sun.identity.agents.config.webservice.authenticator) <br>Hot-swap:
Yes",
    "propertyOrder" : 2300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
},
"xssDetectionRedirectUri" : {
    "title" : "XSS detection redirect URI",
    "description" : "An application-specific Map that identifies a URI of the customized page if
XSS code has been detected. (property name: com.sun.identity.agents.config.xss.redirect.uri) <br>Hot-
swap: Yes <br>Examples: <br>To set a redirect target for application BankApp: enter BankApp in Map Key
field, and enter a redirect URI in Corresponding Map Value field.",
    "propertyOrder" : 12900,
    "patternProperties" : {
        ".*" : {
            "type" : "string"
        }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "object",
            "required" : false
        }
    }
},
"webServiceInternalErrorContentFile" : {
    "title" : "Web Service Internal Error Content File",
    "description" : "The name of file that contains content used by
the Agent to generate an internal error fault for clients. (property name:
com.sun.identity.agents.config.webservice.internalerror.content) <br>Hot-swap: Yes",

```

```

    "propertyOrder" : 2500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "webServiceResponseProcessor" : {
    "title" : "Web Service Response Processor",
    "description" : "An implementation class of interface
com.sun.identity.agents.filter.IWebServiceResponseProcessor that can be used to process the web-
service responses. (property name: com.sun.identity.agents.config.webservice.responseprocessor)
<br>Hot-swap: Yes",
    "propertyOrder" : 2400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "clientHostnameHeader" : {
    "title" : "Client Hostname Header",
    "description" : "HTTP header name that holds the Hostname of the client. (property name:
com.sun.identity.agents.config.client.hostname.header) <br>Hot-swap: Yes",
    "propertyOrder" : 1100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "alternativeAgentHostname" : {
    "title" : "Alternative Agent Host Name",
    "description" : "Host name identifying the Agent protected server to the client browsers
if different from the actual host name. (property name: com.sun.identity.agents.config.agent.host)
<br>Hot-swap: Yes",
    "propertyOrder" : 4100,
    "type" : "object",

```

```

        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "webServiceEnabled" : {
        "title" : "Web Service Enable",
        "description" : "Flag specifies if Web Service processing is enabled. (property name: com.sun.identity.agents.config.webservice.enable) <br>Hot-swap: Yes",
        "propertyOrder" : 2000,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "postDataStickySessionKeyValue" : {
        "title" : "PDP Stickysession key-value",
        "description" : "The provided key-value pair will be used for adding to the URL or creating the cookie. <br>Example: <br>Set 'lb=server1' to append to the querystring or to have 'lb' cookie with 'server1' value. (property name: com.sun.identity.agents.config.postdata.preserve.stickysession.value)",
        "propertyOrder" : 13500,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "missingPostDataPreservationEntryUri" : {
        "title" : "Missing PDP entry URI",
        "description" : "An application-specific URI Map that is used in case the referenced PDP entry cannot be found in the local cache (due to ttl). In such cases it will redirect to the specified URI, otherwise it will show a HTTP 403 Forbidden error. (property name: com.sun.identity.agents.config.postdata.preserve.cache.noentry.url)<br>Examples: <br>To set a redirect target for application BankApp: enter Bankapp in Map Key field and enter a redirect URI in corresponding Map Value field.",
        "propertyOrder" : 13200,
    }
}

```

```
"items" : {
  "type" : "string"
},
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "array",
    "required" : false
  }
}
},
"postDataPreservation" : {
  "title" : "Post Data Preservation enabled",
  "description" : "Post Data Preservation functionality basically stores any POST
data before redirecting the user to the login screen and after successful login the agent
will generate a page that autosubmits the same POST to the original URL. (property name:
com.sun.identity.agents.config.postdata.preserve.enable)",
  "propertyOrder" : 13100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"jbossWebAuthenticationAvailable" : {
  "title" : "WebAuthentication Available",
  "description" : "(Not used in Agent 5 onwards) <br>Enable agent to make programmatic
authentication with the JBoss web container using WebAuthentication feature. (property name:
com.sun.identity.agents.config.jboss.webauth.available) <br>Hot-swap: Yes",
  "propertyOrder" : 12300,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
}
}
}
}
}
```

```
}
```

1.80. Jdbc

1.80.1. Realm Operations

Resource path: `/realm-config/services/audit/JDBC`

Resource version: `1.0`

1.80.1.1. create

Usage:

```
am> create Jdbc --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type": "object",
  "properties": {
    "jdbcDatabaseConfig": {
      "type": "object",
      "title": "Database Configuration",
      "propertyOrder": 2,
      "properties": {
        "idleTimeout": {
          "title": "Maximum Connection Idle Timeout (seconds)",
          "description": "Specifies the maximum idle time before the connection is closed, in seconds.",
          "propertyOrder": 3900,
          "required": true,
          "type": "string",
          "exampleValue": ""
        },
        "username": {
          "title": "Database Username",
          "description": "Specifies the username to access the database server.",
          "propertyOrder": 3600,
          "required": true,
          "type": "string",
          "exampleValue": ""
        }
      }
    }
  }
}
```

```
"jdbcUrl" : {
  "title" : "JDBC Database URL",
  "description" : "URL of the JDBC database.",
  "propertyOrder" : 3400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"maxLifetime" : {
  "title" : "Maximum Connection Time (seconds)",
  "description" : "Specifies the maximum time a JDBC connection can be open, in seconds.",
  "propertyOrder" : 4000,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"connectionTimeout" : {
  "title" : "Connection Timeout (seconds)",
  "description" : "Specifies the maximum wait time before failing the connection, in
seconds.",
  "propertyOrder" : 3800,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"databaseType" : {
  "title" : "Database Type",
  "description" : "Select the database to use for logging audit events.<br><br>Identifies the
database in use, for example MySQL, Oracle, or SQL.",
  "propertyOrder" : 3300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"password" : {
  "title" : "Database Password",
  "description" : "Specifies the password to access the database server.",
  "propertyOrder" : 3700,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"driverClassName" : {
  "title" : "JDBC Driver",
  "description" : "Fully qualified JDBC driver class name.",
  "propertyOrder" : 3500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"maxPoolSize" : {
  "title" : "Maximum Connections",
  "description" : "Specifies the maximum number of connections in the connection pool.",
  "propertyOrder" : 4200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
},
```

```

        "minIdle" : {
            "title" : "Minimum Idle Connections",
            "description" : "Specifies the minimum number of idle connections in the connection pool.",
            "propertyOrder" : 4100,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    },
    "jdbcBuffering" : {
        "type" : "object",
        "title" : "Buffering",
        "propertyOrder" : 3,
        "properties" : {
            "bufferingMaxBatchedEvents" : {
                "title" : "Max Batched Events",
                "description" : "Specifies the maximum number of batched statements the database can support
per connection.",
                "propertyOrder" : 4700,
                "required" : true,
                "type" : "string",
                "exampleValue" : ""
            },
            "bufferingWriterThreads" : {
                "title" : "Writer Threads",
                "description" : "Specifies the number of threads used to write the buffered events.",
                "propertyOrder" : 4600,
                "required" : true,
                "type" : "string",
                "exampleValue" : ""
            },
            "bufferingEnabled" : {
                "title" : "Buffering Enabled",
                "description" : "Enables or disables audit event buffering.",
                "propertyOrder" : 4300,
                "required" : true,
                "type" : "boolean",
                "exampleValue" : ""
            },
            "bufferingWriteInterval" : {
                "title" : "Write Interval",
                "description" : "Specifies the interval (seconds) at which buffered events are written to
the database.",
                "propertyOrder" : 4500,
                "required" : true,
                "type" : "string",
                "exampleValue" : ""
            },
            "bufferingMaxSize" : {
                "title" : "Buffer Size (number of events)",
                "description" : "Size of the queue where events are buffered before they are written to
the database.<br><br>This queue has to be big enough to store all incoming events that have not yet
been written to the database.<p>If the queue reaches capacity, the process will block until a write
occurs.",
                "propertyOrder" : 4400,
                "required" : true,
                "type" : "string",
                "exampleValue" : ""
            }
        }
    }
}

```

```

    }
  },
  "commonHandlerPlugin" : {
    "type" : "object",
    "title" : "Audit Event Handler Factory",
    "propertyOrder" : 1,
    "properties" : {
      "handlerFactory" : {
        "title" : "Factory Class Name",
        "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
        "propertyOrder" : 4800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      }
    }
  },
  "commonHandler" : {
    "type" : "object",
    "title" : "General Handler Configuration",
    "propertyOrder" : 0,
    "properties" : {
      "topics" : {
        "title" : "Topics",
        "description" : "List of topics handled by an audit event handler.",
        "propertyOrder" : 3200,
        "required" : true,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      },
      "enabled" : {
        "title" : "Enabled",
        "description" : "Enables or disables an audit event handler.",
        "propertyOrder" : 3100,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      }
    }
  }
}
}
}
}
}

```

1.80.1.2. delete

Usage:

```
am> delete Jdbc --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.80.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Jdbc --realm Realm --actionName getAllTypes
```

1.80.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Jdbc --realm Realm --actionName getCreatableTypes
```

1.80.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Jdbc --realm Realm --actionName nextdescendents
```

1.80.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Jdbc --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.80.1.7. read

Usage:

```
am> read Jdbc --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.80.1.8. update

Usage:

```
am> update Jdbc --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "jdbcDatabaseConfig" : {
      "type" : "object",
      "title" : "Database Configuration",
      "propertyOrder" : 2,
      "properties" : {
        "idleTimeout" : {
          "title" : "Maximum Connection Idle Timeout (seconds)",
          "description" : "Specifies the maximum idle time before the connection is closed, in
seconds.",
          "propertyOrder" : 3900,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "username" : {
          "title" : "Database Username",
          "description" : "Specifies the username to access the database server.",
          "propertyOrder" : 3600,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      },
      "jdbcUrl" : {
        "title" : "JDBC Database URL",
        "description" : "URL of the JDBC database.",
        "propertyOrder" : 3400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "maxLifetime" : {
        "title" : "Maximum Connection Time (seconds)",
        "description" : "Specifies the maximum time a JDBC connection can be open, in seconds."
      }
    }
  }
}
```

```

        "propertyOrder" : 4000,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "connectionTimeout" : {
        "title" : "Connection Timeout (seconds)",
        "description" : "Specifies the maximum wait time before failing the connection, in
seconds.",
        "propertyOrder" : 3800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "databaseType" : {
        "title" : "Database Type",
        "description" : "Select the database to use for logging audit events.<br><br>Identifies the
database in use, for example MySQL, Oracle, or SQL.",
        "propertyOrder" : 3300,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "password" : {
        "title" : "Database Password",
        "description" : "Specifies the password to access the database server.",
        "propertyOrder" : 3700,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "driverClassName" : {
        "title" : "JDBC Driver",
        "description" : "Fully qualified JDBC driver class name.",
        "propertyOrder" : 3500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "maxPoolSize" : {
        "title" : "Maximum Connections",
        "description" : "Specifies the maximum number of connections in the connection pool.",
        "propertyOrder" : 4200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "minIdle" : {
        "title" : "Minimum Idle Connections",
        "description" : "Specifies the minimum number of idle connections in the connection pool.",
        "propertyOrder" : 4100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"jdbcBuffering" : {

```

```

"type" : "object",
"title" : "Buffering",
"propertyOrder" : 3,
"properties" : {
  "bufferingMaxBatchedEvents" : {
    "title" : "Max Batched Events",
    "description" : "Specifies the maximum number of batched statements the database can support
per connection.",
    "propertyOrder" : 4700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "bufferingWriterThreads" : {
    "title" : "Writer Threads",
    "description" : "Specifies the number of threads used to write the buffered events.",
    "propertyOrder" : 4600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "bufferingEnabled" : {
    "title" : "Buffering Enabled",
    "description" : "Enables or disables audit event buffering.",
    "propertyOrder" : 4300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "bufferingWriteInterval" : {
    "title" : "Write Interval",
    "description" : "Specifies the interval (seconds) at which buffered events are written to
the database.",
    "propertyOrder" : 4500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "bufferingMaxSize" : {
    "title" : "Buffer Size (number of events)",
    "description" : "Size of the queue where events are buffered before they are written to
the database.<br><br>This queue has to be big enough to store all incoming events that have not yet
been written to the database.<p>If the queue reaches capacity, the process will block until a write
occurs.",
    "propertyOrder" : 4400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",

```

```
"description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
"propertyOrder" : 4800,
"required" : true,
"type" : "string",
"exampleValue" : ""
}
},
"commonHandler" : {
"type" : "object",
"title" : "General Handler Configuration",
"propertyOrder" : 0,
"properties" : {
"topics" : {
"title" : "Topics",
"description" : "List of topics handled by an audit event handler.",
"propertyOrder" : 3200,
"required" : true,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"enabled" : {
"title" : "Enabled",
"description" : "Enables or disables an audit event handler.",
"propertyOrder" : 3100,
"required" : true,
"type" : "boolean",
"exampleValue" : ""
}
}
}
}
}
```

1.80.2. Global Operations

Resource path: `/global-config/services/audit/JDBC`

Resource version: **1.0**

1.80.2.1. create

Usage:

```
am> create Jdbc --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 3200,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 3100,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        }
      }
    },
    "commonHandlerPlugin" : {
      "type" : "object",
      "title" : "Audit Event Handler Factory",
      "propertyOrder" : 1,
      "properties" : {
        "handlerFactory" : {
          "title" : "Factory Class Name",
          "description" : "The fully qualified class name of the factory responsible for creating the Audit Event Handler. The class must implement org.forgerock.openam.audit.AuditEventHandlerFactory.",
          "propertyOrder" : 4800,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "jdbcBuffering" : {
      "type" : "object",
      "title" : "Buffering",
      "propertyOrder" : 3,
      "properties" : {
```

```

"bufferingWriterThreads" : {
  "title" : "Writer Threads",
  "description" : "Specifies the number of threads used to write the buffered events.",
  "propertyOrder" : 4600,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"bufferingEnabled" : {
  "title" : "Buffering Enabled",
  "description" : "Enables or disables audit event buffering.",
  "propertyOrder" : 4300,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"bufferingMaxBatchedEvents" : {
  "title" : "Max Batched Events",
  "description" : "Specifies the maximum number of batched statements the database can support
per connection.",
  "propertyOrder" : 4700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"bufferingWriteInterval" : {
  "title" : "Write Interval",
  "description" : "Specifies the interval (seconds) at which buffered events are written to
the database.",
  "propertyOrder" : 4500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"bufferingMaxSize" : {
  "title" : "Buffer Size (number of events)",
  "description" : "Size of the queue where events are buffered before they are written to
the database.<br><br>This queue has to be big enough to store all incoming events that have not yet
been written to the database.<p>If the queue reaches capacity, the process will block until a write
occurs.",
  "propertyOrder" : 4400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"jdbcDatabaseConfig" : {
  "type" : "object",
  "title" : "Database Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "idleTimeout" : {
      "title" : "Maximum Connection Idle Timeout (seconds)",
      "description" : "Specifies the maximum idle time before the connection is closed, in
seconds.",
      "propertyOrder" : 3900,
      "required" : true,
      "type" : "string",

```

```
    "exampleValue" : ""
  },
  "databaseType" : {
    "title" : "Database Type",
    "description" : "Select the database to use for logging audit events.<br><br>Identifies the
database in use, for example MySQL, Oracle, or SQL.",
    "propertyOrder" : 3300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "minIdle" : {
    "title" : "Minimum Idle Connections",
    "description" : "Specifies the minimum number of idle connections in the connection pool.",
    "propertyOrder" : 4100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "maxPoolSize" : {
    "title" : "Maximum Connections",
    "description" : "Specifies the maximum number of connections in the connection pool.",
    "propertyOrder" : 4200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "connectionTimeout" : {
    "title" : "Connection Timeout (seconds)",
    "description" : "Specifies the maximum wait time before failing the connection, in
seconds.",
    "propertyOrder" : 3800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "username" : {
    "title" : "Database Username",
    "description" : "Specifies the username to access the database server.",
    "propertyOrder" : 3600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "driverClassName" : {
    "title" : "JDBC Driver",
    "description" : "Fully qualified JDBC driver class name.",
    "propertyOrder" : 3500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "password" : {
    "title" : "Database Password",
    "description" : "Specifies the password to access the database server.",
    "propertyOrder" : 3700,
    "required" : true,
    "type" : "string",
    "format" : "password",
```



```
    "exampleValue" : ""
  },
  "maxLifetime" : {
    "title" : "Maximum Connection Time (seconds)",
    "description" : "Specifies the maximum time a JDBC connection can be open, in seconds.",
    "propertyOrder" : 4000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "jdbcUrl" : {
    "title" : "JDBC Database URL",
    "description" : "URL of the JDBC database.",
    "propertyOrder" : 3400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.80.2.2. delete

Usage:

```
am> delete Jdbc --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.80.2.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Jdbc --global --actionName getAllTypes
```

1.80.2.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Jdbc --global --actionName getCreatableTypes
```

1.80.2.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Jdbc --global --actionName nextdescendents
```

1.80.2.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Jdbc --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.80.2.7. read

Usage:

```
am> read Jdbc --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.80.2.8. update

Usage:

```
am> update Jdbc --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 3200,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 3100,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        }
      }
    },
    "commonHandlerPlugin" : {
      "type" : "object",
      "title" : "Audit Event Handler Factory",
      "propertyOrder" : 1,
      "properties" : {
        "handlerFactory" : {
          "title" : "Factory Class Name",
          "description" : "The fully qualified class name of the factory responsible for creating the Audit Event Handler. The class must implement <code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
          "propertyOrder" : 4800,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "jdbcBuffering" : {
      "type" : "object",
      "title" : "Buffering",
      "propertyOrder" : 3,
      "properties" : {
        "bufferingWriterThreads" : {
          "title" : "Writer Threads",
          "description" : "Specifies the number of threads used to write the buffered events.",
          "propertyOrder" : 4600,

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "bufferingEnabled" : {
    "title" : "Buffering Enabled",
    "description" : "Enables or disables audit event buffering.",
    "propertyOrder" : 4300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "bufferingMaxBatchedEvents" : {
    "title" : "Max Batched Events",
    "description" : "Specifies the maximum number of batched statements the database can support
per connection.",
    "propertyOrder" : 4700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "bufferingWriteInterval" : {
    "title" : "Write Interval",
    "description" : "Specifies the interval (seconds) at which buffered events are written to
the database.",
    "propertyOrder" : 4500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "bufferingMaxSize" : {
    "title" : "Buffer Size (number of events)",
    "description" : "Size of the queue where events are buffered before they are written to
the database.<br><br>This queue has to be big enough to store all incoming events that have not yet
been written to the database.<p>If the queue reaches capacity, the process will block until a write
occurs.",
    "propertyOrder" : 4400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"jdbcDatabaseConfig" : {
  "type" : "object",
  "title" : "Database Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "idleTimeout" : {
      "title" : "Maximum Connection Idle Timeout (seconds)",
      "description" : "Specifies the maximum idle time before the connection is closed, in
seconds.",
      "propertyOrder" : 3900,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "databaseType" : {
      "title" : "Database Type",

```

```

        "description" : "Select the database to use for logging audit events.<br><br>Identifies the
        database in use, for example MySQL, Oracle, or SQL.",
        "propertyOrder" : 3300,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "minIdle" : {
        "title" : "Minimum Idle Connections",
        "description" : "Specifies the minimum number of idle connections in the connection pool.",
        "propertyOrder" : 4100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "maxPoolSize" : {
        "title" : "Maximum Connections",
        "description" : "Specifies the maximum number of connections in the connection pool.",
        "propertyOrder" : 4200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "connectionTimeout" : {
        "title" : "Connection Timeout (seconds)",
        "description" : "Specifies the maximum wait time before failing the connection, in
seconds.",
        "propertyOrder" : 3800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "username" : {
        "title" : "Database Username",
        "description" : "Specifies the username to access the database server.",
        "propertyOrder" : 3600,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "driverClassName" : {
        "title" : "JDBC Driver",
        "description" : "Fully qualified JDBC driver class name.",
        "propertyOrder" : 3500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "password" : {
        "title" : "Database Password",
        "description" : "Specifies the password to access the database server.",
        "propertyOrder" : 3700,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "maxLifetime" : {
        "title" : "Maximum Connection Time (seconds)",
    
```

```

    "description" : "Specifies the maximum time a JDBC connection can be open, in seconds.",
    "propertyOrder" : 4000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "jdbcUrl" : {
    "title" : "JDBC Database URL",
    "description" : "URL of the JDBC database.",
    "propertyOrder" : 3400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}
}
}

```

1.81. JdbcModule

1.81.1. Realm Operations

Resource path: `/realm-config/authentication/modules/jdbc`

Resource version: `1.0`

1.81.1.1. create

Usage:

```
am> create JdbcModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "connectionType" : {
      "title" : "Connection Type",
      "description" : "Controls how the authentication module will obtain the JDBC connection to
the database.<br><br>If the connection type is non-persistent JDBC connection then the JDBC driver
must be available to the OpenAM web-app. If the connection type is JNDI, the OpenAM web application

```

```

deployment descriptor <code>web.xml</code> must be updated to include the correct JNDI JDBC resource
information. The J2EE container must also be configured with the correct JNDI JDBC configuration.",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"passwordColumn" : {
  "title" : "Password Column Name",
  "description" : "The name of the column in the database containing the user
passwords<br><br>This property will be used to retrieve the correct column containing the password
from the results table returned by the database",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"connectionPoolJndiName" : {
  "title" : "Connection Pool JNDI Name",
  "description" : "The JNDI URL to the JDBC connection pool<br><br>The JNDI URL refers to the
JDBC connection pool created in the J2EE container for the authentication database.<br><br><i>NB </
i>Only used when connection type is JNDI",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"password" : {
  "title" : "Database Password",
  "description" : "The password used to authenticate to the database<br><br><i>NB </i>Only used
when connection type is JDBC",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"jdbcUrl" : {
  "title" : "JDBC URL",
  "description" : "The JDBC URL used to initialise the JDBC driver<br><br><i>NB </i>Only used when
connection type is JDBC",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"username" : {
  "title" : "Database Username",
  "description" : "This username will be used to authenticate to the database<br><br><i>NB </
i>Only used when connection type is JDBC",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"passwordStatement" : {
  "title" : "Prepared Statement",
  "description" : "The SQL statement used to search the database for user passwords<br><br>The
SQL statement used to search the database for the user password. A single property of the supplied

```

```

username is provided by the module. The result of the search should be a single row that contains the
password for the user under the specified column.",
  "propertyOrder" : 800,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"passwordTransformClass" : {
  "title" : "Class to Transform Password Syntax",
  "description" : "This class is used to transform the supplied credentials from the
database.<br><br>The default implementation for this property is <code>ClearTextTransform</
code> that performs no transformation. If the supplied credentials need to be transformed
before comparing with the password field retrieved from the database, a custom implementation
should be provided. Any custom implementation must implement the following interface
<code>com.sun.identity.authentication.modules.jdbc.JDBCPasswordSyntaxTransform</code>",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"jdbcDriver" : {
  "title" : "JDBC Driver",
  "description" : "The classname of the JDBC driver to use.<br><br>The fully qualified class name
of the JDBC driver to use to connect to the database. Only Oracle or MySQL drivers are supported.
JDBC drivers for other database may work, but the database will be treated as if it was Oracle.<br>
<br><i>NB </i>Only used when connection type is JDBC",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}
}
}
}

```

1.81.1.2. delete

Usage:

```
am> delete JdbcModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.81.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action JdbcModule --realm Realm --actionName getAllTypes
```

1.81.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action JdbcModule --realm Realm --actionName getCreatableTypes
```

1.81.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action JdbcModule --realm Realm --actionName nextdescendents
```

1.81.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query JdbcModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.81.1.7. read

Usage:

```
am> read JdbcModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.81.1.8. update

Usage:

```
am> update JdbcModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "connectionType" : {
      "title" : "Connection Type",
      "description" : "Controls how the authentication module will obtain the JDBC connection to
the database.<br><br>If the connection type is non-persistent JDBC connection then the JDBC driver
must be available to the OpenAM web-app. If the connection type is JNDI, the OpenAM web application
deployment descriptor <code>web.xml</code> must be updated to include the correct JNDI JDBC resource
information. The J2EE container must also be configured with the correct JNDI JDBC configuration.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "passwordColumn" : {
      "title" : "Password Column Name",
      "description" : "The name of the column in the database containing the user
passwords<br><br>This property will be used to retrieve the correct column containing the password
from the results table returned by the database",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "connectionPoolJndiName" : {
      "title" : "Connection Pool JNDI Name",
      "description" : "The JNDI URL to the JDBC connection pool<br><br>The JNDI URL refers to the
JDBC connection pool created in the J2EE container for the authentication database.<br><br><i>NB </i>
Only used when connection type is JNDI",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "password" : {
      "title" : "Database Password",
      "description" : "The password used to authenticate to the database<br><br><i>NB </i>
Only used
when connection type is JDBC",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",

```

```

    "format" : "password",
    "exampleValue" : ""
  },
  "jdbcUrl" : {
    "title" : "JDBC URL",
    "description" : "The JDBC URL used to initialise the JDBC driver<br><br><i>NB </i>Only used when
connection type is JDBC",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "username" : {
    "title" : "Database Username",
    "description" : "This username will be used to authenticate to the database<br><br><i>NB </i>
i>Only used when connection type is JDBC",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "passwordStatement" : {
    "title" : "Prepared Statement",
    "description" : "The SQL statement used to search the database for user passwords<br><br>The
SQL statement used to search the database for the user password. A single property of the supplied
username is provided by the module. The result of the search should be a single row that contains the
password for the user under the specified column.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "passwordTransformClass" : {
    "title" : "Class to Transform Password Syntax",
    "description" : "This class is used to transform the supplied credentials from the
database.<br><br>The default implementation for this property is <code>ClearTextTransform</
code> that performs no transformation. If the supplied credentials need to be transformed
before comparing with the password field retrieved from the database, a custom implementation
should be provided. Any custom implementation must implement the following interface
<code>com.sun.identity.authentication.modules.jdbc.JDBCPasswordSyntaxTransform</code>",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "jdbcDriver" : {
    "title" : "JDBC Driver",
    "description" : "The classname of the JDBC driver to use.<br><br>The fully qualified class name
of the JDBC driver to use to connect to the database. Only Oracle or MySQL drivers are supported.
JDBC drivers for other database may work, but the database will be treated as if it was Oracle.<br>
><br><i>NB </i>Only used when connection type is JDBC",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",

```

```
"description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
"propertyOrder" : 1000,
"required" : true,
"type" : "integer",
"exampleValue" : ""
}
}
}
```

1.81.2. Global Operations

Resource path: `/global-config/authentication/modules/jdbc`

Resource version: `1.0`

1.81.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action JdbcModule --global --actionName getAllTypes
```

1.81.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action JdbcModule --global --actionName getCreatableTypes
```

1.81.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action JdbcModule --global --actionName nextdescendents
```

1.81.2.4. read

Usage:

```
am> read JdbcModule --global
```

1.81.2.5. update

Usage:

```
am> update JdbcModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "connectionType" : {
          "title" : "Connection Type",
          "description" : "Controls how the authentication module will obtain the JDBC connection to the database.<br><br>If the connection type is non-persistent JDBC connection then the JDBC driver must be available to the OpenAM web-app. If the connection type is JNDI, the OpenAM web application deployment descriptor <code>web.xml</code> must be updated to include the correct JNDI JDBC resource information. The J2EE container must also be configured with the correct JNDI JDBC configuration.",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "password" : {
          "title" : "Database Password",
          "description" : "The password used to authenticate to the database<br><br><i>NB </i>Only used when connection type is JDBC",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "string",
          "format" : "password",
          "exampleValue" : ""
        },
        "jdbcDriver" : {
          "title" : "JDBC Driver",
          "description" : "The classname of the JDBC driver to use.<br><br>The fully qualified class name of the JDBC driver to use to connect to the database. Only Oracle or MySQL drivers are supported. JDBC drivers for other database may work, but the database will be treated as if it was Oracle.<br><br><i>NB </i>Only used when connection type is JDBC",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 1000,
          "required" : true,
          "type" : "integer",

```

```

    "exampleValue" : ""
  },
  "jdbcUrl" : {
    "title" : "JDBC URL",
    "description" : "The JDBC URL used to initialise the JDBC driver<br><br><i>NB </i>Only used
when connection type is JDBC",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "passwordStatement" : {
    "title" : "Prepared Statement",
    "description" : "The SQL statement used to search the database for user passwords<br><br>The
SQL statement used to search the database for the user password. A single property of the supplied
username is provided by the module. The result of the search should be a single row that contains the
password for the user under the specified column.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "passwordTransformClass" : {
    "title" : "Class to Transform Password Syntax",
    "description" : "This class is used to transform the supplied credentials from the
database.<br><br>The default implementation for this property is <code>ClearTextTransform</
code> that performs no transformation. If the supplied credentials need to be transformed
before comparing with the password field retrieved from the database, a custom implementation
should be provided. Any custom implementation must implement the following interface
<code>com.sun.identity.authentication.modules.jdbc.JDBCPasswordSyntaxTransform</code>",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "username" : {
    "title" : "Database Username",
    "description" : "This username will be used to authenticate to the database<br><br><i>NB </
i>Only used when connection type is JDBC",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "connectionPoolJndiName" : {
    "title" : "Connection Pool JNDI Name",
    "description" : "The JNDI URL to the JDBC connection pool<br><br>The JNDI URL refers to the
JDBC connection pool created in the J2EE container for the authentication database.<br><br><i>NB </
i>Only used when connection type is JNDI",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "passwordColumn" : {
    "title" : "Password Column Name",
    "description" : "The name of the column in the database containing the user
passwords<br><br>This property will be used to retrieve the correct column containing the password
from the results table returned by the database",

```

```
        "propertyOrder" : 700,  
        "required" : true,  
        "type" : "string",  
        "exampleValue" : ""  
    }  
},  
"type" : "object",  
"title" : "Realm Defaults"  
}  
}
```

1.82. Jms

1.82.1. Realm Operations

Resource path: [/realm-config/services/audit/JMS](#)

Resource version: [1.0](#)

1.82.1.1. create

Usage:

```
am> create Jms --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "type" : "object",  
  "properties" : {  
    "batchEvents" : {  
      "type" : "object",  
      "title" : "Batch Events",  
      "propertyOrder" : 3,  
      "properties" : {  
        "pollTimeoutSec" : {  
          "title" : "Polling Timeout",  
          "description" : "Worker thread waiting period (seconds) for the next event, before going  
idle.",  
          "propertyOrder" : 7400,  
          "required" : true,  
          "type" : "integer",
```

```

    "exampleValue" : ""
  },
  "shutdownTimeoutSec" : {
    "title" : "Shutdown Timeout",
    "description" : "Application waiting period (seconds) for worker thread termination.",
    "propertyOrder" : 7500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "maxBatchedEvents" : {
    "title" : "Max Batched",
    "description" : "Maximum number of events per batch.",
    "propertyOrder" : 7100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "insertTimeoutSec" : {
    "title" : "Insert Timeout",
    "description" : "Waiting period (seconds) for available capacity, when a new event enters
the queue.",
    "propertyOrder" : 7300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "batchCapacity" : {
    "title" : "Capacity",
    "description" : "Maximum event count in the batch queue; additional events are dropped.",
    "propertyOrder" : 7000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "batchThreadCount" : {
    "title" : "Thread Count",
    "description" : "Number of concurrent threads that pull events from the batch queue.",
    "propertyOrder" : 7200,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "batchEnabled" : {
    "title" : "Batch enabled",
    "description" : "Boolean for batch delivery of audit events.",
    "propertyOrder" : 6900,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"commonHandler" : {
  "type" : "object",
  "title" : "General Handler Configuration",
  "propertyOrder" : 0,
  "properties" : {
    "topics" : {

```



```

    "title" : "Topics",
    "description" : "List of topics handled by an audit event handler.",
    "propertyOrder" : 6300,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "enabled" : {
    "title" : "Enabled",
    "description" : "Enables or disables an audit event handler.",
    "propertyOrder" : 6200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"jmsConfiguration" : {
  "type" : "object",
  "title" : "JMS Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "jndiConnectionFactoryName" : {
      "title" : "JMS Connection Factory Name",
      "description" : "Specifies the JNDI lookup name for the connection factory exposed by your
JMS message broker. OpenAM performs a JNDI lookup on this name to locate your broker's connection
factory.<p><p>See the documentation for your JMS message broker for the required value.<p>The default
is the connection factory name for Apache ActiveMQ.",
      "propertyOrder" : 6800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sessionMode" : {
      "title" : "Session Mode",
      "description" : "Specifies the JMS session acknowledgement mode: <code>AUTO</code>,
<code>CLIENT</code>, or <code>DUPS_OK</code>.<p><ul><li>Auto mode guarantees once-only delivery of
JMS messages used to transmit audit events.</li><li>Duplicates OK mode ensures that messages are
delivered at least once.</li><li>Client mode does not ensure delivery.</li></ul><p>Use the default
setting unless your JMS broker implementation requires otherwise. See your broker documentation for
more information.",
      "propertyOrder" : 6500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "jndiContextProperties" : {
      "title" : "JNDI Context Properties",
      "description" : "Specifies JNDI properties that OpenAM uses to connect to the JMS message
broker to which OpenAM will publish audit events.<p><p>OpenAM acts as a JMS client, using a JMS
connection factory to connect to your JMS message broker. In order for OpenAM to connect to the
broker, the JNDI context properties must conform to those needed by the broker. See the documentation
for your JMS message broker for required values.<p>The default properties are example properties for
connecting to Apache ActiveMQ.",
      "propertyOrder" : 6600,
      "required" : true,

```

```

    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "deliveryMode" : {
    "title" : "Delivery Mode",
    "description" : "Specifies whether JMS messages used to transmit audit events use persistent or non-persistent delivery.<p><p>With persistent delivery, the JMS provider ensures that messages are not lost in transit in case of a provider failure by logging messages to storage when they are sent.<p>Specify the delivery mode as persistent if it is unacceptable for delivery of audit events to be lost in JMS transit. If the possible loss of audit events is acceptable, choose non-persistent delivery, which provides better performance.",
    "propertyOrder" : 6400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "jndiTopicName" : {
    "title" : "JMS Topic Name",
    "description" : "JNDI lookup name for the JMS topic",
    "propertyOrder" : 6700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory responsible for creating the Audit Event Handler. The class must implement <code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 7600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
}

```

1.82.1.2. delete

Usage:

```
am> delete Jms --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.82.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Jms --realm Realm --actionName getAllTypes
```

1.82.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Jms --realm Realm --actionName getCreatableTypes
```

1.82.1.5. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Jms --realm Realm --actionName nextdescendants
```

1.82.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Jms --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.82.1.7. read

Usage:

```
am> read Jms --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.82.1.8. update

Usage:

```
am> update Jms --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "batchEvents" : {
      "type" : "object",
      "title" : "Batch Events",
      "propertyOrder" : 3,
      "properties" : {
        "pollTimeoutSec" : {
          "title" : "Polling Timeout",
          "description" : "Worker thread waiting period (seconds) for the next event, before going
idle.",
          "propertyOrder" : 7400,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "shutdownTimeoutSec" : {
          "title" : "Shutdown Timeout",
          "description" : "Application waiting period (seconds) for worker thread termination.",
          "propertyOrder" : 7500,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "maxBatchedEvents" : {
          "title" : "Max Batched",
          "description" : "Maximum number of events per batch.",
          "propertyOrder" : 7100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "insertTimeoutSec" : {
```

```
    "title" : "Insert Timeout",
    "description" : "Waiting period (seconds) for available capacity, when a new event enters
the queue.",
    "propertyOrder" : 7300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "batchCapacity" : {
    "title" : "Capacity",
    "description" : "Maximum event count in the batch queue; additional events are dropped.",
    "propertyOrder" : 7000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "batchThreadCount" : {
    "title" : "Thread Count",
    "description" : "Number of concurrent threads that pull events from the batch queue.",
    "propertyOrder" : 7200,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "batchEnabled" : {
    "title" : "Batch enabled",
    "description" : "Boolean for batch delivery of audit events.",
    "propertyOrder" : 6900,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"commonHandler" : {
  "type" : "object",
  "title" : "General Handler Configuration",
  "propertyOrder" : 0,
  "properties" : {
    "topics" : {
      "title" : "Topics",
      "description" : "List of topics handled by an audit event handler.",
      "propertyOrder" : 6300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "enabled" : {
      "title" : "Enabled",
      "description" : "Enables or disables an audit event handler.",
      "propertyOrder" : 6200,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
```

```

    },
    "jmsConfiguration" : {
      "type" : "object",
      "title" : "JMS Configuration",
      "propertyOrder" : 2,
      "properties" : {
        "jndiConnectionFactoryName" : {
          "title" : "JMS Connection Factory Name",
          "description" : "Specifies the JNDI lookup name for the connection factory exposed by your
          JMS message broker. OpenAM performs a JNDI lookup on this name to locate your broker's connection
          factory.<p><p>See the documentation for your JMS message broker for the required value.<p>The default
          is the connection factory name for Apache ActiveMQ.",
          "propertyOrder" : 6800,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "sessionMode" : {
          "title" : "Session Mode",
          "description" : "Specifies the JMS session acknowledgement mode: <code>AUTO</code>,
          <code>CLIENT</code>, or <code>DUPS_OK</code>.<p><ul><li>Auto mode guarantees once-only delivery of
          JMS messages used to transmit audit events.</li><li>Duplicates OK mode ensures that messages are
          delivered at least once.</li><li>Client mode does not ensure delivery.</li></ul><p>Use the default
          setting unless your JMS broker implementation requires otherwise. See your broker documentation for
          more information.",
          "propertyOrder" : 6500,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "jndiContextProperties" : {
          "title" : "JNDI Context Properties",
          "description" : "Specifies JNDI properties that OpenAM uses to connect to the JMS message
          broker to which OpenAM will publish audit events.<p><p>OpenAM acts as a JMS client, using a JMS
          connection factory to connect to your JMS message broker. In order for OpenAM to connect to the
          broker, the JNDI context properties must conform to those needed by the broker. See the documentation
          for your JMS message broker for required values.<p>The default properties are example properties for
          connecting to Apache ActiveMQ.",
          "propertyOrder" : 6600,
          "required" : true,
          "patternProperties" : {
            ".*" : {
              "type" : "string"
            }
          }
        },
        "deliveryMode" : {
          "title" : "Delivery Mode",
          "description" : "Specifies whether JMS messages used to transmit audit events use persistent
          or non-persistent delivery.<p><p>With persistent delivery, the JMS provider ensures that messages
          are not lost in transit in case of a provider failure by logging messages to storage when they are
          sent.<p>Specify the delivery mode as persistent if it is unacceptable for delivery of audit events
          to be lost in JMS transit. If the possible loss of audit events is acceptable, choose non-persistent
          delivery, which provides better performance.",
          "propertyOrder" : 6400,
          "required" : true,
          "type" : "string",

```

```
        "exampleValue" : ""
    },
    "jndiTopicName" : {
        "title" : "JMS Topic Name",
        "description" : "JNDI lookup name for the JMS topic",
        "propertyOrder" : 6700,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"commonHandlerPlugin" : {
    "type" : "object",
    "title" : "Audit Event Handler Factory",
    "propertyOrder" : 1,
    "properties" : {
        "handlerFactory" : {
            "title" : "Factory Class Name",
            "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
            "propertyOrder" : 7600,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}
}
}
```

1.82.2. Global Operations

Resource path: `/global-config/services/audit/JMS`

Resource version: `1.0`

1.82.2.1. create

Usage:

```
am> create Jms --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 6200,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 6300,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      }
    },
    "jmsConfiguration" : {
      "type" : "object",
      "title" : "JMS Configuration",
      "propertyOrder" : 2,
      "properties" : {
        "jndiContextProperties" : {
          "title" : "JNDI Context Properties",
          "description" : "Specifies JNDI properties that OpenAM uses to connect to the JMS message broker to which OpenAM will publish audit events.<p><p>OpenAM acts as a JMS client, using a JMS connection factory to connect to your JMS message broker. In order for OpenAM to connect to the broker, the JNDI context properties must conform to those needed by the broker. See the documentation for your JMS message broker for required values.<p><p>The default properties are example properties for connecting to Apache ActiveMQ.",
          "propertyOrder" : 6600,
          "required" : true,
          "patternProperties" : {
            ".*" : {
              "type" : "string"
            }
          }
        },
        "type" : "object",
        "exampleValue" : ""
      }
    },
    "sessionMode" : {
      "title" : "Session Mode",
      "description" : "Specifies the JMS session acknowledgement mode: <code>AUTO</code>, <code>CLIENT</code>, or <code>DUPS_OK</code>.<p><ul><li>Auto mode guarantees once-only delivery of JMS messages used to transmit audit events.</li><li>Duplicates OK mode ensures that messages are delivered at least once.</li><li>Client mode does not ensure delivery.</li></ul><p>Use the default
  
```



```

setting unless your JMS broker implementation requires otherwise. See your broker documentation for
more information.",
    "propertyOrder" : 6500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"deliveryMode" : {
    "title" : "Delivery Mode",
    "description" : "Specifies whether JMS messages used to transmit audit events use persistent
or non-persistent delivery.<p><p>With persistent delivery, the JMS provider ensures that messages
are not lost in transit in case of a provider failure by logging messages to storage when they are
sent.<p>Specify the delivery mode as persistent if it is unacceptable for delivery of audit events
to be lost in JMS transit. If the possible loss of audit events is acceptable, choose non-persistent
delivery, which provides better performance.",
    "propertyOrder" : 6400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"jndiTopicName" : {
    "title" : "JMS Topic Name",
    "description" : "JNDI lookup name for the JMS topic",
    "propertyOrder" : 6700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"jndiConnectionFactoryName" : {
    "title" : "JMS Connection Factory Name",
    "description" : "Specifies the JNDI lookup name for the connection factory exposed by your
JMS message broker. OpenAM performs a JNDI lookup on this name to locate your broker's connection
factory.<p><p>See the documentation for your JMS message broker for the required value.<p>The default
is the connection factory name for Apache ActiveMQ.",
    "propertyOrder" : 6800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
}
}
},
"commonHandlerPlugin" : {
    "type" : "object",
    "title" : "Audit Event Handler Factory",
    "propertyOrder" : 1,
    "properties" : {
        "handlerFactory" : {
            "title" : "Factory Class Name",
            "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
            "propertyOrder" : 7600,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}
},
"batchEvents" : {

```

```
"type" : "object",
"title" : "Batch Events",
"propertyOrder" : 3,
"properties" : {
  "batchThreadCount" : {
    "title" : "Thread Count",
    "description" : "Number of concurrent threads that pull events from the batch queue.",
    "propertyOrder" : 7200,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "maxBatchedEvents" : {
    "title" : "Max Batched",
    "description" : "Maximum number of events per batch.",
    "propertyOrder" : 7100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "shutdownTimeoutSec" : {
    "title" : "Shutdown Timeout",
    "description" : "Application waiting period (seconds) for worker thread termination.",
    "propertyOrder" : 7500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "batchEnabled" : {
    "title" : "Batch enabled",
    "description" : "Boolean for batch delivery of audit events.",
    "propertyOrder" : 6900,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "batchCapacity" : {
    "title" : "Capacity",
    "description" : "Maximum event count in the batch queue; additional events are dropped.",
    "propertyOrder" : 7000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "insertTimeoutSec" : {
    "title" : "Insert Timeout",
    "description" : "Waiting period (seconds) for available capacity, when a new event enters
the queue.",
    "propertyOrder" : 7300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "pollTimeoutSec" : {
    "title" : "Polling Timeout",
    "description" : "Worker thread waiting period (seconds) for the next event, before going
idle.",
    "propertyOrder" : 7400,
    "required" : true,
```

```
    "type" : "integer",  
    "exampleValue" : ""  
  }  
}  
}  
}
```

1.82.2.2. delete

Usage:

```
am> delete Jms --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.82.2.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Jms --global --actionName getAllTypes
```

1.82.2.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Jms --global --actionName getCreatableTypes
```

1.82.2.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Jms --global --actionName nextdescendents
```

1.82.2.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Jms --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.82.2.7. read

Usage:

```
am> read Jms --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.82.2.8. update

Usage:

```
am> update Jms --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 6200,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "topics" : {
```

```

        "title" : "Topics",
        "description" : "List of topics handled by an audit event handler.",
        "propertyOrder" : 6300,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"jmsConfiguration" : {
    "type" : "object",
    "title" : "JMS Configuration",
    "propertyOrder" : 2,
    "properties" : {
        "jndiContextProperties" : {
            "title" : "JNDI Context Properties",
            "description" : "Specifies JNDI properties that OpenAM uses to connect to the JMS message broker to which OpenAM will publish audit events.<p><p>OpenAM acts as a JMS client, using a JMS connection factory to connect to your JMS message broker. In order for OpenAM to connect to the broker, the JNDI context properties must conform to those needed by the broker. See the documentation for your JMS message broker for required values.<p>The default properties are example properties for connecting to Apache ActiveMQ.",
            "propertyOrder" : 6600,
            "required" : true,
            "patternProperties" : {
                ".*" : {
                    "type" : "string"
                }
            },
            "type" : "object",
            "exampleValue" : ""
        },
        "sessionMode" : {
            "title" : "Session Mode",
            "description" : "Specifies the JMS session acknowledgement mode: <code>AUTO</code>, <code>CLIENT</code>, or <code>DUPS_OK</code>.<p><ul><li>Auto mode guarantees once-only delivery of JMS messages used to transmit audit events.</li><li>Duplicates OK mode ensures that messages are delivered at least once.</li><li>Client mode does not ensure delivery.</li></ul><p>Use the default setting unless your JMS broker implementation requires otherwise. See your broker documentation for more information.",
            "propertyOrder" : 6500,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "deliveryMode" : {
            "title" : "Delivery Mode",
            "description" : "Specifies whether JMS messages used to transmit audit events use persistent or non-persistent delivery.<p><p>With persistent delivery, the JMS provider ensures that messages are not lost in transit in case of a provider failure by logging messages to storage when they are sent.<p>Specify the delivery mode as persistent if it is unacceptable for delivery of audit events to be lost in JMS transit. If the possible loss of audit events is acceptable, choose non-persistent delivery, which provides better performance.",
            "propertyOrder" : 6400,
            "required" : true,
            "type" : "string",

```

```

    "exampleValue" : ""
  },
  "jndiTopicName" : {
    "title" : "JMS Topic Name",
    "description" : "JNDI lookup name for the JMS topic",
    "propertyOrder" : 6700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "jndiConnectionFactoryName" : {
    "title" : "JMS Connection Factory Name",
    "description" : "Specifies the JNDI lookup name for the connection factory exposed by your
JMS message broker. OpenAM performs a JNDI lookup on this name to locate your broker's connection
factory.<p><p>See the documentation for your JMS message broker for the required value.<p>The default
is the connection factory name for Apache ActiveMQ.",
    "propertyOrder" : 6800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 7600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
},
"batchEvents" : {
  "type" : "object",
  "title" : "Batch Events",
  "propertyOrder" : 3,
  "properties" : {
    "batchThreadCount" : {
      "title" : "Thread Count",
      "description" : "Number of concurrent threads that pull events from the batch queue.",
      "propertyOrder" : 7200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "maxBatchedEvents" : {
      "title" : "Max Batched",
      "description" : "Maximum number of events per batch.",
      "propertyOrder" : 7100,
      "required" : true,
      "type" : "integer",

```

```

    "exampleValue" : ""
  },
  "shutdownTimeoutSec" : {
    "title" : "Shutdown Timeout",
    "description" : "Application waiting period (seconds) for worker thread termination.",
    "propertyOrder" : 7500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "batchEnabled" : {
    "title" : "Batch enabled",
    "description" : "Boolean for batch delivery of audit events.",
    "propertyOrder" : 6900,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "batchCapacity" : {
    "title" : "Capacity",
    "description" : "Maximum event count in the batch queue; additional events are dropped.",
    "propertyOrder" : 7000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "insertTimeoutSec" : {
    "title" : "Insert Timeout",
    "description" : "Waiting period (seconds) for available capacity, when a new event enters
the queue.",
    "propertyOrder" : 7300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "pollTimeoutSec" : {
    "title" : "Polling Timeout",
    "description" : "Worker thread waiting period (seconds) for the next event, before going
idle.",
    "propertyOrder" : 7400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
}
}

```

1.83. Json

1.83.1. Realm Operations

Resource path: `/realm-config/services/audit/JSON`

Resource version: `1.0`

1.83.1.1. create

Usage:

```
am> create Json --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 400,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      }
    },
    "jsonFileRotation" : {
      "type" : "object",
      "title" : "File Rotation",
      "propertyOrder" : 3,
      "properties" : {
        "rotationInterval" : {
          "title" : "Rotation Interval",
```



```
"description" : "Interval to trigger audit file rotations, in seconds. A negative or zero
value disables this feature.",
"propertyOrder" : 1000,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"rotationTimes" : {
"title" : "Rotation Times",
"description" : "Durations after midnight to trigger file rotation, in seconds.",
"propertyOrder" : 1100,
"required" : true,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"rotationFilePrefix" : {
"title" : "File Rotation Prefix",
"description" : "Prefix to prepend to audit files when rotating audit files.",
"propertyOrder" : 800,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"rotationEnabled" : {
"title" : "Rotation Enabled",
"description" : "Enables and disables audit file rotation.",
"propertyOrder" : 600,
"required" : true,
"type" : "boolean",
"exampleValue" : ""
},
"rotationFileSuffix" : {
"title" : "File Rotation Suffix",
"description" : "Suffix to append to audit files when they are rotated. Suffix should be a
timestamp.",
"propertyOrder" : 900,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"rotationMaxFileSize" : {
"title" : "Maximum File Size",
"description" : "Maximum size, in bytes, which an audit file can grow to before rotation is
triggered. A negative or zero value indicates this policy is disabled.",
"propertyOrder" : 700,
"required" : true,
"type" : "string",
"exampleValue" : ""
}
}
},
"commonHandlerPlugin" : {
"type" : "object",
"title" : "Audit Event Handler Factory",
"propertyOrder" : 1,
"properties" : {
```

```

        "handlerFactory" : {
            "title" : "Factory Class Name",
            "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
            "propertyOrder" : 1900,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    },
    "jsonBuffering" : {
        "type" : "object",
        "title" : "Buffering",
        "propertyOrder" : 5,
        "properties" : {
            "bufferingMaxSize" : {
                "title" : "Batch Size",
                "description" : "Maximum number of events that can be buffered (default/minimum: 100000)",
                "propertyOrder" : 1500,
                "required" : true,
                "type" : "string",
                "exampleValue" : ""
            },
            "bufferingWriteInterval" : {
                "title" : "Write interval",
                "description" : "Interval at which buffered events are written to a file, in milliseconds.",
                "propertyOrder" : 1600,
                "required" : true,
                "type" : "string",
                "exampleValue" : ""
            }
        }
    },
    "jsonFileRetention" : {
        "type" : "object",
        "title" : "File Retention",
        "propertyOrder" : 4,
        "properties" : {
            "retentionMaxDiskSpaceToUse" : {
                "title" : "Maximum Disk Space",
                "description" : "The maximum amount of disk space the audit files can occupy, in bytes. A
negative or zero value indicates this policy is disabled.",
                "propertyOrder" : 1300,
                "required" : true,
                "type" : "string",
                "exampleValue" : ""
            },
            "retentionMinFreeSpaceRequired" : {
                "title" : "Minimum Free Space Required",
                "description" : "Minimum amount of disk space required, in bytes, on the system where audit
files are stored. A negative or zero value indicates this policy is disabled.",
                "propertyOrder" : 1400,
                "required" : true,
                "type" : "string",
                "exampleValue" : ""
            }
        },
        "retentionMaxNumberOfHistoryFiles" : {
    
```

```

        "title" : "Maximum Number of Historical Files",
        "description" : "Maximum number of backup audit files allowed. A value of <code>-1</code>
disables pruning of old history files.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
  },
  "jsonConfig" : {
    "type" : "object",
    "title" : "JSON Configuration",
    "propertyOrder" : 2,
    "properties" : {
      "elasticsearchCompatible" : {
        "title" : "ElasticSearch JSON Format Compatible",
        "description" : "JSON format should be transformed to be compatible with ElasticSearch
format restrictions.",
        "propertyOrder" : 1700,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "rotationRetentionCheckInterval" : {
        "title" : "File Rotation Retention Check Interval",
        "description" : "Interval to check time-based file rotation policies, in seconds.",
        "propertyOrder" : 1800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "location" : {
        "title" : "Log Directory",
        "description" : "Directory in which to store audit log JSON files.",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      }
    }
  }
}
}
}
}

```

1.83.1.2. delete

Usage:

```
am> delete Json --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.83.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Json --realm Realm --actionName getAllTypes
```

1.83.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Json --realm Realm --actionName getCreatableTypes
```

1.83.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Json --realm Realm --actionName nextdescendents
```

1.83.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Json --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.83.1.7. read

Usage:

```
am> read Json --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.83.1.8. update

Usage:

```
am> update Json --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 400,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      }
    },
    "jsonFileRotation" : {
      "type" : "object",
      "title" : "File Rotation",
      "propertyOrder" : 3,
      "properties" : {
        "rotationInterval" : {
          "title" : "Rotation Interval",
          "description" : "Interval to trigger audit file rotations, in seconds. A negative or zero value disables this feature.",
          "propertyOrder" : 1000,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    }
  }
}
```

```

    },
    "rotationTimes" : {
      "title" : "Rotation Times",
      "description" : "Durations after midnight to trigger file rotation, in seconds.",
      "propertyOrder" : 1100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "rotationFilePrefix" : {
      "title" : "File Rotation Prefix",
      "description" : "Prefix to prepend to audit files when rotating audit files.",
      "propertyOrder" : 800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationEnabled" : {
      "title" : "Rotation Enabled",
      "description" : "Enables and disables audit file rotation.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "rotationFileSuffix" : {
      "title" : "File Rotation Suffix",
      "description" : "Suffix to append to audit files when they are rotated. Suffix should be a
timestamp.",
      "propertyOrder" : 900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationMaxFileSize" : {
      "title" : "Maximum File Size",
      "description" : "Maximum size, in bytes, which an audit file can grow to before rotation is
triggered. A negative or zero value indicates this policy is disabled.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 1900,

```

```

        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
},
"jsonBuffering" : {
    "type" : "object",
    "title" : "Buffering",
    "propertyOrder" : 5,
    "properties" : {
        "bufferingMaxSize" : {
            "title" : "Batch Size",
            "description" : "Maximum number of events that can be buffered (default/minimum: 100000)",
            "propertyOrder" : 1500,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "bufferingWriteInterval" : {
            "title" : "Write interval",
            "description" : "Interval at which buffered events are written to a file, in milliseconds.",
            "propertyOrder" : 1600,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
},
"jsonFileRetention" : {
    "type" : "object",
    "title" : "File Retention",
    "propertyOrder" : 4,
    "properties" : {
        "retentionMaxDiskSpaceToUse" : {
            "title" : "Maximum Disk Space",
            "description" : "The maximum amount of disk space the audit files can occupy, in bytes. A
negative or zero value indicates this policy is disabled.",
            "propertyOrder" : 1300,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "retentionMinFreeSpaceRequired" : {
            "title" : "Minimum Free Space Required",
            "description" : "Minimum amount of disk space required, in bytes, on the system where audit
files are stored. A negative or zero value indicates this policy is disabled.",
            "propertyOrder" : 1400,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "retentionMaxNumberOfHistoryFiles" : {
            "title" : "Maximum Number of Historical Files",
            "description" : "Maximum number of backup audit files allowed. A value of <code>-1</code>
disables pruning of old history files.",
            "propertyOrder" : 1200,
            "required" : true,
            "type" : "string",

```

```

    "exampleValue" : ""
  }
}
},
"jsonConfig" : {
  "type" : "object",
  "title" : "JSON Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "elasticsearchCompatible" : {
      "title" : "ElasticSearch JSON Format Compatible",
      "description" : "JSON format should be transformed to be compatible with ElasticSearch
format restrictions.",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "rotationRetentionCheckInterval" : {
      "title" : "File Rotation Retention Check Interval",
      "description" : "Interval to check time-based file rotation policies, in seconds.",
      "propertyOrder" : 1800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "location" : {
      "title" : "Log Directory",
      "description" : "Directory in which to store audit log JSON files.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
}
}

```

1.83.2. Global Operations

Resource path: `/global-config/services/audit/JSON`

Resource version: `1.0`

1.83.2.1. create

Usage:

```
am> create Json --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "jsonFileRetention" : {
      "type" : "object",
      "title" : "File Retention",
      "propertyOrder" : 4,
      "properties" : {
        "retentionMaxDiskSpaceToUse" : {
          "title" : "Maximum Disk Space",
          "description" : "The maximum amount of disk space the audit files can occupy, in bytes. A
negative or zero value indicates this policy is disabled.",
          "propertyOrder" : 1300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "retentionMinFreeSpaceRequired" : {
          "title" : "Minimum Free Space Required",
          "description" : "Minimum amount of disk space required, in bytes, on the system where audit
files are stored. A negative or zero value indicates this policy is disabled.",
          "propertyOrder" : 1400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "retentionMaxNumberOfHistoryFiles" : {
          "title" : "Maximum Number of Historical Files",
          "description" : "Maximum number of backup audit files allowed. A value of <code>-1</code>
disables pruning of old history files.",
          "propertyOrder" : 1200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 400,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",

```

```
    "exampleValue" : ""
  },
  "enabled" : {
    "title" : "Enabled",
    "description" : "Enables or disables an audit event handler.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"jsonFileRotation" : {
  "type" : "object",
  "title" : "File Rotation",
  "propertyOrder" : 3,
  "properties" : {
    "rotationInterval" : {
      "title" : "Rotation Interval",
      "description" : "Interval to trigger audit file rotations, in seconds. A negative or zero
value disables this feature.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationTimes" : {
      "title" : "Rotation Times",
      "description" : "Durations after midnight to trigger file rotation, in seconds.",
      "propertyOrder" : 1100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "rotationFilePrefix" : {
      "title" : "File Rotation Prefix",
      "description" : "Prefix to prepend to audit files when rotating audit files.",
      "propertyOrder" : 800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationMaxFileSize" : {
      "title" : "Maximum File Size",
      "description" : "Maximum size, in bytes, which an audit file can grow to before rotation is
triggered. A negative or zero value indicates this policy is disabled.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationFileSuffix" : {
      "title" : "File Rotation Suffix",
      "description" : "Suffix to append to audit files when they are rotated. Suffix should be a
timestamp.",
      "propertyOrder" : 900,
```

```

    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "rotationEnabled" : {
    "title" : "Rotation Enabled",
    "description" : "Enables and disables audit file rotation.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"jsonConfig" : {
  "type" : "object",
  "title" : "JSON Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "rotationRetentionCheckInterval" : {
      "title" : "File Rotation Retention Check Interval",
      "description" : "Interval to check time-based file rotation policies, in seconds.",
      "propertyOrder" : 1800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "location" : {
      "title" : "Log Directory",
      "description" : "Directory in which to store audit log JSON files.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "elasticsearchCompatible" : {
      "title" : "ElasticSearch JSON Format Compatible",
      "description" : "JSON format should be transformed to be compatible with ElasticSearch
format restrictions.",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
},
"jsonBuffering" : {
  "type" : "object",
  "title" : "Buffering",
  "propertyOrder" : 5,
  "properties" : {
    "bufferingWriteInterval" : {
      "title" : "Write interval",
      "description" : "Interval at which buffered events are written to a file, in milliseconds.",
      "propertyOrder" : 1600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},

```

```
"bufferingMaxSize" : {
  "title" : "Batch Size",
  "description" : "Maximum number of events that can be buffered (default/minimum: 100000)",
  "propertyOrder" : 1500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 1900,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
```

1.83.2.2. delete

Usage:

```
am> delete Json --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.83.2.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Json --global --actionName getAllTypes
```

1.83.2.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Json --global --actionName getCreatableTypes
```

1.83.2.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Json --global --actionName nextdescendents
```

1.83.2.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Json --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.83.2.7. read

Usage:

```
am> read Json --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.83.2.8. update

Usage:

```
am> update Json --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "jsonFileRetention" : {
      "type" : "object",
      "title" : "File Retention",
      "propertyOrder" : 4,
      "properties" : {
        "retentionMaxDiskSpaceToUse" : {
          "title" : "Maximum Disk Space",
          "description" : "The maximum amount of disk space the audit files can occupy, in bytes. A
negative or zero value indicates this policy is disabled.",
          "propertyOrder" : 1300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "retentionMinFreeSpaceRequired" : {
          "title" : "Minimum Free Space Required",
          "description" : "Minimum amount of disk space required, in bytes, on the system where audit
files are stored. A negative or zero value indicates this policy is disabled.",
          "propertyOrder" : 1400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "retentionMaxNumberOfHistoryFiles" : {
          "title" : "Maximum Number of Historical Files",
          "description" : "Maximum number of backup audit files allowed. A value of <code>-1</code>
disables pruning of old history files.",
          "propertyOrder" : 1200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 400,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "enabled" : {
          "title" : "Enabled",

```

```
    "description" : "Enables or disables an audit event handler.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"jsonFileRotation" : {
  "type" : "object",
  "title" : "File Rotation",
  "propertyOrder" : 3,
  "properties" : {
    "rotationInterval" : {
      "title" : "Rotation Interval",
      "description" : "Interval to trigger audit file rotations, in seconds. A negative or zero
value disables this feature.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationTimes" : {
      "title" : "Rotation Times",
      "description" : "Durations after midnight to trigger file rotation, in seconds.",
      "propertyOrder" : 1100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "rotationFilePrefix" : {
      "title" : "File Rotation Prefix",
      "description" : "Prefix to prepend to audit files when rotating audit files.",
      "propertyOrder" : 800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationMaxFileSize" : {
      "title" : "Maximum File Size",
      "description" : "Maximum size, in bytes, which an audit file can grow to before rotation is
triggered. A negative or zero value indicates this policy is disabled.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationFileSuffix" : {
      "title" : "File Rotation Suffix",
      "description" : "Suffix to append to audit files when they are rotated. Suffix should be a
timestamp.",
      "propertyOrder" : 900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  },
}
```

```

    "rotationEnabled" : {
      "title" : "Rotation Enabled",
      "description" : "Enables and disables audit file rotation.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  },
  "jsonConfig" : {
    "type" : "object",
    "title" : "JSON Configuration",
    "propertyOrder" : 2,
    "properties" : {
      "rotationRetentionCheckInterval" : {
        "title" : "File Rotation Retention Check Interval",
        "description" : "Interval to check time-based file rotation policies, in seconds.",
        "propertyOrder" : 1800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "location" : {
        "title" : "Log Directory",
        "description" : "Directory in which to store audit log JSON files.",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "elasticsearchCompatible" : {
        "title" : "ElasticSearch JSON Format Compatible",
        "description" : "JSON format should be transformed to be compatible with ElasticSearch
format restrictions.",
        "propertyOrder" : 1700,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      }
    }
  },
  "jsonBuffering" : {
    "type" : "object",
    "title" : "Buffering",
    "propertyOrder" : 5,
    "properties" : {
      "bufferingWriteInterval" : {
        "title" : "Write interval",
        "description" : "Interval at which buffered events are written to a file, in milliseconds.",
        "propertyOrder" : 1600,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "bufferingMaxSize" : {
        "title" : "Batch Size",
        "description" : "Maximum number of events that can be buffered (default/minimum: 100000)",
        "propertyOrder" : 1500,

```



```

        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
},
"commonHandlerPlugin" : {
    "type" : "object",
    "title" : "Audit Event Handler Factory",
    "propertyOrder" : 1,
    "properties" : {
        "handlerFactory" : {
            "title" : "Factory Class Name",
            "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
            "propertyOrder" : 1900,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}
}
}
}
}

```

1.84. JwtProofOfPossessionModule

1.84.1. Realm Operations

Resource path: `/realm-config/authentication/modules/authJwtPoP`

Resource version: `1.0`

1.84.1.1. create

Usage:

```
am> create JwtProofOfPossessionModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
```

```
"type" : "object",
"properties" : {
  "responseEncryptionMethod" : {
    "title" : "Response Encryption Scheme",
    "description" : "Key exchange method to use for responses: ephemeral elliptic curve Diffie-Hellman (ECDHE) key agreement or using a pre-shared key (PSK) from the subject's JWK Set.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "enableTlsSessionBinding" : {
    "title" : "Use TLS Session Binding",
    "description" : "If enabled the response must arrive in the same TLS (HTTPS) session as the challenge was issued.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "challengeSigningKey" : {
    "title" : "Challenge Signing Key",
    "description" : "Name of the key (in the AM keystore) to use to sign challenges.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "subjectJwkSetAttr" : {
    "title" : "Subject JWK Set Attribute",
    "description" : "Subject profile attribute that contains a JWK Set of confirmation and encryption keys.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "responseEncryptionCipher" : {
    "title" : "Response Encryption Cipher",
    "description" : "The authenticated encryption (AEAD) scheme to use for the response.",
    "propertyOrder" : 350,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.",
    "propertyOrder" : 10000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
```

1.84.1.2. delete

Usage:

```
am> delete JwtProofOfPossessionModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.84.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action JwtProofOfPossessionModule --realm Realm --actionName getAllTypes
```

1.84.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action JwtProofOfPossessionModule --realm Realm --actionName getCreatableTypes
```

1.84.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action JwtProofOfPossessionModule --realm Realm --actionName nextdescendents
```

1.84.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query JwtProofOfPossessionModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.84.1.7. read

Usage:

```
am> read JwtProofOfPossessionModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.84.1.8. update

Usage:

```
am> update JwtProofOfPossessionModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "responseEncryptionMethod" : {
      "title" : "Response Encryption Scheme",
      "description" : "Key exchange method to use for responses: ephemeral elliptic curve Diffie-Hellman (ECDHE) key agreement or using a pre-shared key (PSK) from the subject's JWK Set.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "enableTlsSessionBinding" : {
      "title" : "Use TLS Session Binding",
      "description" : "If enabled the response must arrive in the same TLS (HTTPS) session as the challenge was issued.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "challengeSigningKey" : {
      "title" : "Challenge Signing Key",
      "description" : "Name of the key (in the AM keystore) to use to sign challenges.",
      "propertyOrder" : 200,
      "required" : true,

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "subjectJwkSetAttr" : {
    "title" : "Subject JWK Set Attribute",
    "description" : "Subject profile attribute that contains a JWK Set of confirmation and
encryption keys.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "responseEncryptionCipher" : {
    "title" : "Response Encryption Cipher",
    "description" : "The authenticated encryption (AEAD) scheme to use for the response.",
    "propertyOrder" : 350,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.",
    "propertyOrder" : 10000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
}

```

1.84.2. Global Operations

Resource path: `/global-config/authentication/modules/authJwtPop`

Resource version: `1.0`

1.84.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action JwtProofOfPossessionModule --global --actionName getAllTypes
```

1.84.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action JwtProofOfPossessionModule --global --actionName getCreatableTypes
```

1.84.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action JwtProofOfPossessionModule --global --actionName nextdescendents
```

1.84.2.4. read

Usage:

```
am> read JwtProofOfPossessionModule --global
```

1.84.2.5. update

Usage:

```
am> update JwtProofOfPossessionModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "responseEncryptionMethod" : {
          "title" : "Response Encryption Scheme",
          "description" : "Key exchange method to use for responses: ephemeral elliptic curve Diffie-Hellman (ECDHE) key agreement or using a pre-shared key (PSK) from the subject's JWK Set.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "responseEncryptionCipher" : {
          "title" : "Response Encryption Cipher",
          "description" : "The authenticated encryption (AEAD) scheme to use for the response.",
          "propertyOrder" : 350,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "subjectJwkSetAttr" : {
          "title" : "Subject JWK Set Attribute",
          "description" : "Subject profile attribute that contains a JWK Set of confirmation and encryption keys.",
          "propertyOrder" : 100,
          "required" : true,

```

```
    "type" : "string",
    "exampleValue" : ""
  },
  "enableTlsSessionBinding" : {
    "title" : "Use TLS Session Binding",
    "description" : "If enabled the response must arrive in the same TLS (HTTPS) session as the
challenge was issued.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "challengeSigningKey" : {
    "title" : "Challenge Signing Key",
    "description" : "Name of the key (in the AM keystore) to use to sign challenges.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.",
    "propertyOrder" : 10000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
```

1.85. KbaQuestions

1.85.1. Realm Operations

KBA resource is responsible for delivering up configured security questions.

Resource path: [/selfservice/kba](#)

Resource version: [1.0](#)

1.85.1.1. read

Read the configured security questions.

Usage:

```
am> read KbaQuestions --realm Realm
```

1.86. LDAPDecision

1.86.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/LdapDecisionNode`

Resource version: `1.0`

1.86.1.1. create

Usage:

```
am> create LDAPDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userCreationAttrs" : {
      "title" : "User Creation Attributes",
      "description" : "This list lets you map (external) attribute names from the LDAP directory
server to (internal) attribute names used by AM. <br><br>The format of this property is:
<br><code>local attr1|external attr1</code>",
      "propertyOrder" : 1200,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "searchFilterAttributes" : {
      "title" : "Attributes Used to Search for a User to be Authenticated",
      "description" : "Specifies the attributes used to match an entry in the directory server to
the credentials provided by the user. <br><br>The default value of <code>uid</code> will form the
following search filter of <code>uid=user</code>. Specifying multiple values such as <code>uid/</code>
and <code>cn</code> causes the node to create a search filter of <code>(|(uid=user)(cn=user))</code>.
<br><br>Multiple attribute values allow the user to authenticate with any one of the values.
For example, if you have both <code>uid</code> and <code>mail</code>, then Barbara Jensen can
authenticate with either <code>bjensen</code> or <code>bjensen@example.com</code>.",
      "propertyOrder" : 700,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
```



```

    "exampleValue" : ""
  },
  "adminDn" : {
    "title" : "Bind User DN",
    "description" : "Specify the user DN used to bind to the LDAP user data store.
<br><em>Note:</em> <code>cn=Directory Manager</code> should not be used in production systems.",
    "propertyOrder" : 400,
    "type" : "string",
    "exampleValue" : ""
  },
  "heartbeatInterval" : {
    "title" : "LDAP Connection Heartbeat Interval",
    "description" : "Specifies how often AM should send a heartbeat request to the directory server
to ensure that the connection does not remain idle. <br><br>Some network administrators configure
firewalls and load balancers to drop connections that are idle for too long. You can turn this off
by setting the value to <code>0</code> or to a negative number. Set the units for the interval in the
LDAP Connection Heartbeat Time Unit property.",
    "propertyOrder" : 1600,
    "type" : "integer",
    "exampleValue" : ""
  },
  "searchScope" : {
    "title" : "Search Scope",
    "description" : "Specifies the extent of searching for users in the directory server.
<br><br>Scope <code>OBJECT</code> means search only the entry specified as the DN to Start User
Search, whereas <code>ONELEVEL</code> means search only the entries that are directly children of
that object. <code>SUBTREE</code> means search the entry specified and every entry under it.",
    "propertyOrder" : 900,
    "type" : "string",
    "exampleValue" : ""
  },
  "minimumPasswordLength" : {
    "title" : "Minimum Password Length",
    "description" : "Specifies the minimum acceptable password length.",
    "propertyOrder" : 1300,
    "type" : "integer",
    "exampleValue" : ""
  },
  "heartbeatTimeUnit" : {
    "title" : "LDAP Connection Heartbeat Time Unit",
    "description" : "Specifies the time unit corresponding to LDAP Connection Heartbeat
Interval.<br><br> Default: Seconds",
    "propertyOrder" : 1700,
    "type" : "string",
    "exampleValue" : ""
  },
  "ldapConnectionMode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Specifies whether to use SSL or StartTLS to connect to the LDAP user data
store. <br><br>AM must be able to trust the certificates used.",
    "propertyOrder" : 1000,
    "type" : "string",
    "exampleValue" : ""
  },
  "trustAllServerCertificates" : {
    "title" : "Trust All Server Certificates",
    "description" : "When enabled, blindly trust server certificates, including self-signed test
certificates. <br><br><em>Note:</em> Use this feature with care as it bypasses the normal certificate
verification process",

```

```

        "propertyOrder" : 1500,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "accountSearchBaseDn" : {
        "title" : "DN to Start User Search",
        "description" : "Specify the DN from which to start the user search.<br><br>More specific DNs,
such as <code>ou=sales,dc=example,dc=com</code>, result in better search performance.If multiple
entries exist in the store with identical attribute values, ensure this property is specific enough
to return only one entry.",
        "propertyOrder" : 300,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "secondaryServers" : {
        "title" : "Secondary LDAP Server",
        "description" : "Specify one or more secondary directory servers. <br><br>Specify
each directory server in the following format: <br><code>host:port</code><br><br>Secondary
servers are used when none of the primary servers are available.<br><br>For example,
<code>directory_services_backup.example.com</code>.",
        "propertyOrder" : 200,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "primaryServers" : {
        "title" : "Primary LDAP Server",
        "description" : "Specify one or more primary directory servers. <br><br>Specify each
directory server in the following format: <br><code>host:port</code><br><br>For example,
<code>directory_services.example.com:389</code>.",
        "propertyOrder" : 100,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "returnUserDn" : {
        "title" : "Return User DN to DataStore",
        "description" : "When enabled, the node returns the DN rather than the User ID.",
        "propertyOrder" : 1100,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "userProfileAttribute" : {
        "title" : "Attribute Used to Retrieve User Profile",
        "description" : "Specifies the attribute used to retrieve the profile of a user from the
directory server. <br><br>The user search will have already happened, as specified by the Attributes
Used to Search for a User to be Authenticated and User Search Filter properties.",
        "propertyOrder" : 600,
        "type" : "string",
        "exampleValue" : ""
    },
    "adminPassword" : {

```

```

    "title" : "Bind User Password",
    "description" : "Specify the password of the account used to bind to the LDAP user data store.",
    "propertyOrder" : 500,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "userSearchFilter" : {
    "title" : "User Search Filter",
    "description" : "Specifies an additional filter to append to user searches.
<br><br>For example, searching for <code>mail</code> and specifying a User Search Filter of
<code>(objectClass=inetOrgPerson)</code>, causes AM to use <code>&(mail=<replaceable>address</
replaceable>)(objectClass=inetOrgPerson)</code> as the resulting search filter, where
<replaceable>address</replaceable> is the mail address provided by the user.",
    "propertyOrder" : 800,
    "type" : "string",
    "exampleValue" : ""
  },
  "beheraEnabled" : {
    "title" : "LDAP Behera Password Policy Support",
    "description" : "Enables support for modern LDAP password policies. <br><br>LDAP Behera Password
policies are supported by modern LDAP servers such as DS. If this functionality is disabled then only
the older Netscape VCHU password policy standard will be enforced.",
    "propertyOrder" : 1400,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ldapOperationsTimeout" : {
    "title" : "LDAP Operations Timeout",
    "description" : "Defines the timeout in milliseconds that AM should wait for a response from the
directory server.<br><br> Default: <code>0</code> (No timeout).",
    "propertyOrder" : 1800,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"required" : [ "ldapConnectionMode", "accountSearchBaseDn", "returnUserDn",
"trustAllServerCertificates", "userProfileAttribute", "beheraEnabled", "userCreationAttrs",
"adminDn", "ldapOperationsTimeout", "searchFilterAttributes", "minimumPasswordLength",
"primaryServers", "heartbeatInterval", "secondaryServers", "adminPassword", "searchScope",
"heartbeatTimeUnit" ]
}

```

1.86.1.2. delete

Usage:

```
am> delete LDAPDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.86.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action LDAPDecision --realm Realm --actionName getAllTypes
```

1.86.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action LDAPDecision --realm Realm --actionName getCreatableTypes
```

1.86.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action LDAPDecision --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.86.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action LDAPDecision --realm Realm --actionName nextdescendents
```

1.86.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query LDAPDecision --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.86.1.8. read

Usage:

```
am> read LDAPDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.86.1.9. update

Usage:

```
am> update LDAPDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userCreationAttrs" : {
      "title" : "User Creation Attributes",
      "description" : "This list lets you map (external) attribute names from the LDAP directory
server to (internal) attribute names used by AM. <br><br>The format of this property is:
<br><code>local attr1|external attr1</code>",
      "propertyOrder" : 1200,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "searchFilterAttributes" : {
      "title" : "Attributes Used to Search for a User to be Authenticated",
      "description" : "Specifies the attributes used to match an entry in the directory server to
the credentials provided by the user. <br><br>The default value of <code>uid</code> will form the
following search filter of <code>uid=user</code>. Specifying multiple values such as <code>uid/</code>
and <code>cn</code> causes the node to create a search filter of <code>(|(uid=user)(cn=user))</code>.
<br><br>Multiple attribute values allow the user to authenticate with any one of the values.
```

For example, if you have both `uid` and `mail`, then Barbara Jensen can authenticate with either `bjensen` or `bjensen@example.com`."

```

    "propertyOrder" : 700,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "adminDn" : {
    "title" : "Bind User DN",
    "description" : "Specify the user DN used to bind to the LDAP user data store.
<br><br><em>Note:</em> <code>cn=Directory Manager</code> should not be used in production systems.",
    "propertyOrder" : 400,
    "type" : "string",
    "exampleValue" : ""
  },
  "heartbeatInterval" : {
    "title" : "LDAP Connection Heartbeat Interval",
    "description" : "Specifies how often AM should send a heartbeat request to the directory server
to ensure that the connection does not remain idle. <br><br>Some network administrators configure
firewalls and load balancers to drop connections that are idle for too long. You can turn this off
by setting the value to <code>0</code> or to a negative number. Set the units for the interval in the
LDAP Connection Heartbeat Time Unit property.",
    "propertyOrder" : 1600,
    "type" : "integer",
    "exampleValue" : ""
  },
  "searchScope" : {
    "title" : "Search Scope",
    "description" : "Specifies the extent of searching for users in the directory server.
<br><br>Scope <code>OBJECT</code> means search only the entry specified as the DN to Start User
Search, whereas <code>ONELEVEL</code> means search only the entries that are directly children of
that object. <code>SUBTREE</code> means search the entry specified and every entry under it.",
    "propertyOrder" : 900,
    "type" : "string",
    "exampleValue" : ""
  },
  "minimumPasswordLength" : {
    "title" : "Minimum Password Length",
    "description" : "Specifies the minimum acceptable password length.",
    "propertyOrder" : 1300,
    "type" : "integer",
    "exampleValue" : ""
  },
  "heartbeatTimeUnit" : {
    "title" : "LDAP Connection Heartbeat Time Unit",
    "description" : "Specifies the time unit corresponding to LDAP Connection Heartbeat
Interval.<br><br> Default: Seconds",
    "propertyOrder" : 1700,
    "type" : "string",
    "exampleValue" : ""
  },
  "ldapConnectionMode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Specifies whether to use SSL or StartTLS to connect to the LDAP user data
store. <br><br>AM must be able to trust the certificates used.",
    "propertyOrder" : 1000,
    "type" : "string",

```

```
    "exampleValue" : ""
  },
  "trustAllServerCertificates" : {
    "title" : "Trust All Server Certificates",
    "description" : "When enabled, blindly trust server certificates, including self-signed test certificates. <br><br><em>Note:</em> Use this feature with care as it bypasses the normal certificate verification process",
    "propertyOrder" : 1500,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "accountSearchBaseDn" : {
    "title" : "DN to Start User Search",
    "description" : "Specify the DN from which to start the user search.<br><br>More specific DN's, such as <code>ou=sales,dc=example,dc=com</code>, result in better search performance.If multiple entries exist in the store with identical attribute values, ensure this property is specific enough to return only one entry.",
    "propertyOrder" : 300,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "secondaryServers" : {
    "title" : "Secondary LDAP Server",
    "description" : "Specify one or more secondary directory servers. <br><br>Specify each directory server in the following format: <br><code>host:port</code><br><br>Secondary servers are used when none of the primary servers are available.<br><br>For example, <code>directory_services_backup.example.com</code>.",
    "propertyOrder" : 200,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "primaryServers" : {
    "title" : "Primary LDAP Server",
    "description" : "Specify one or more primary directory servers. <br><br>Specify each directory server in the following format: <br><code>host:port</code><br><br>For example, <code>directory_services.example.com:389</code>.",
    "propertyOrder" : 100,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "returnUserDn" : {
    "title" : "Return User DN to DataStore",
    "description" : "When enabled, the node returns the DN rather than the User ID.",
    "propertyOrder" : 1100,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userProfileAttribute" : {
    "title" : "Attribute Used to Retrieve User Profile",
```

```

    "description" : "Specifies the attribute used to retrieve the profile of a user from the
directory server. <br><br>The user search will have already happened, as specified by the Attributes
Used to Search for a User to be Authenticated and User Search Filter properties.",
    "propertyOrder" : 600,
    "type" : "string",
    "exampleValue" : ""
  },
  "adminPassword" : {
    "title" : "Bind User Password",
    "description" : "Specify the password of the account used to bind to the LDAP user data store.",
    "propertyOrder" : 500,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "userSearchFilter" : {
    "title" : "User Search Filter",
    "description" : "Specifies an additional filter to append to user searches.
<br><br>For example, searching for <code>mail</code> and specifying a User Search Filter of
<code>(objectClass=inetOrgPerson)</code>, causes AM to use <code>&(mail=<replaceable>address</
replaceable>)(objectClass=inetOrgPerson)</code> as the resulting search filter, where
<replaceable>address</replaceable> is the mail address provided by the user.",
    "propertyOrder" : 800,
    "type" : "string",
    "exampleValue" : ""
  },
  "beheraEnabled" : {
    "title" : "LDAP Behera Password Policy Support",
    "description" : "Enables support for modern LDAP password policies. <br><br>LDAP Behera Password
policies are supported by modern LDAP servers such as DS. If this functionality is disabled then only
the older Netscape VCHU password policy standard will be enforced.",
    "propertyOrder" : 1400,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ldapOperationsTimeout" : {
    "title" : "LDAP Operations Timeout",
    "description" : "Defines the timeout in milliseconds that AM should wait for a response from the
directory server.<br><br>Default: <code>0</code> (No timeout).",
    "propertyOrder" : 1800,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"required" : [ "ldapConnectionMode", "accountSearchBaseDn", "returnUserDn",
"trustAllServerCertificates", "userProfileAttribute", "beheraEnabled", "userCreationAttrs",
"adminDn", "ldapOperationsTimeout", "searchFilterAttributes", "minimumPasswordLength",
"primaryServers", "heartbeatInterval", "secondaryServers", "adminPassword", "searchScope",
"heartbeatTimeUnit" ]
}

```


1.87. LdapModule

1.87.1. Realm Operations

Resource path: `/realm-config/authentication/modules/ldap`

Resource version: `1.0`

1.87.1.1. create

Usage:

```
am> create LdapModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "connectionHeartbeatTimeUnit" : {
      "title" : "LDAP Connection Heartbeat Time Unit",
      "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
it may take up to the interval period before the problem is detected. Use along with the Heartbeat
Interval parameter to define the exact interval.",
      "propertyOrder" : 1800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "userBindDN" : {
      "title" : "Bind User DN",
      "description" : "The DN of an admin user used by the module to authentication to the LDAP
server<br><br>The LDAP module requires an administration account in order to perform functionality
such as password reset.<br><br><i>NB </i><code>cn=Directory Manager</code> should not be used in
production systems.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "connectionHeartbeatInterval" : {
      "title" : "LDAP Connection Heartbeat Interval",
```

```

    "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
error) then it may take up to the interval period before the problem is detected. Use along with the
Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
disabling heartbeat requests.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default). ",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "userBindPassword" : {
    "title" : "Bind User Password",
    "description" : "The password of the administration account.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "userSearchAttributes" : {
    "title" : "Attributes Used to Search for a User to be Authenticated",
    "description" : "The attributes specified in this list form the LDAP search filter.<br><br>The
default value of uid will form the following search filter of <code>uid=<i>user</i></code>, if there
are multiple values such as uid and cn, the module will create a search filter as follows <code>(|
(uid=<i>user</i>)(cn=<i>user</i>))</code>",
    "propertyOrder" : 700,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "searchScope" : {
    "title" : "Search Scope",
    "description" : "The level in the Directory Server that will be searched for a matching
user profile.<br><br>This attribute controls how the directory is searched.<br><br>
<ul><li><code>OBJECT</code>: Only the Base DN is searched.</li><li><code>ONELEVEL</code>: Only the
single level below (and not the Base DN) is searched</li><li><code>SUBTREE</code>: The Base DN and
all levels below are searched</li></ul>",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "profileAttributeMappings" : {
    "title" : "User Creation Attributes",

```

```

        "description" : "Controls the mapping of local attribute to external attribute for dynamic
        profile creation.<br><br>If dynamic profile creation is enabled; this feature allows for a mapping
        between the attribute/values retrieved from the users authenticated profile and the attribute/values
        that will be provisioned into their matching account in the data store.<br><br>The format of this
        property is: <br><br><code> local attr|external attr</code>",
        "propertyOrder" : 1300,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "operationTimeout" : {
        "title" : "LDAP operations timeout",
        "description" : "Defines the timeout in seconds OpenAM should wait for a response of the
        Directory Server - <code>0</code> means no timeout.<br><br>If the Directory Server's host is down
        completely or the TCP connection became stale OpenAM waits until operation timeouts from the OS or
        the JVM are applied. However this setting allows more granular control within OpenAM itself. A value
        of <code>0</code> means NO timeout is applied on OpenAM level and the timeouts from the JVM or OS
        will apply.",
        "propertyOrder" : 1900,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "trustAllServerCertificates" : {
        "title" : "Trust All Server Certificates",
        "description" : "Enables a <code>X509TrustManager</code> that trusts all
        certificates.<br><br>This feature will allow the LDAP authentication module to connect to LDAP
        servers protected by self signed or invalid certificates (such as invalid hostname).<br><br><i>NB
        </i>Use this feature with care as it bypasses the normal certificate verification process",
        "propertyOrder" : 1600,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "returnUserDN" : {
        "title" : "Return User DN to DataStore",
        "description" : "Controls whether the DN or the username is returned as the authentication
        principal.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "userSearchStartDN" : {
        "title" : "DN to Start User Search",
        "description" : "The search for accounts to be authenticated start from this base DN <br><br>For
        a single server just enter the Base DN to be searched. Multiple OpenAM servers can have different
        base DN's for the search The format is as follows:<br><br><code>local server name | search DN</
        code><br><br><i>NB </i>The local server name is the full name of the server from the list of servers
        and sites.",
        "propertyOrder" : 300,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
    }

```

```

        "exampleValue" : ""
    },
    "userSearchFilter" : {
        "title" : "User Search Filter",
        "description" : "This search filter will be appended to the standard user search
        filter.<br><br>This attribute can be used to append a custom search filter to the standard filter.
        For example: <code>(objectClass=person)</code>would result in the following user search filter:<br>
        <code>(&(uid=<i>user</i>)(objectClass=person))</code>",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    },
    "secondaryLdapServer" : {
        "title" : "Secondary LDAP Server",
        "description" : "Use this list to set the secondary (failover) LDAP server used for
        authentication.<br><br>If the primary LDAP server fails, the LDAP authentication module will failover
        to the secondary server. A single entry must be in the format:<br><br><code>ldap_server:port</
        code><br><br>Multiple entries allow associations between OpenAM servers and a LDAP server. The
        format is:<br><br><code>local server name | server:port</code><br><br><i>NB </i>The local server
        name is the full name of the server from the list of servers and sites.",
        "propertyOrder" : 200,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    },
    "minimumPasswordLength" : {
        "title" : "Minimum Password Length",
        "description" : "Enforced when the user is resetting their password as part of the
        authentication.<br><br>If the user needs to reset their password as part of the authentication
        process, the authentication module can enforce a minimum password length. This is separate from any
        password length controls from the underlying LDAP server. If the external LDAP server password policy
        is enforcing password length, set this value to 0 to avoid confusion.",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    },
    "beheraPasswordPolicySupportEnabled" : {
        "title" : "LDAP Behera Password Policy Support",
        "description" : "Enables support for modern LDAP password policies<br><br>LDAP Behera Password
        policies are supported by modern LDAP servers such as OpenDJ. If this functionality is disabled then
        only the older Netscape VCHU password policy standard will be enforced.",
        "propertyOrder" : 1500,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "userProfileRetrievalAttribute" : {
        "title" : "Attribute Used to Retrieve User Profile",
        "description" : "The LDAP module will use this attribute to search of the profile of an
        authenticated user.<br><br>This is the attribute used to find the profile of the authenticated user.
        Normally this will be the same attribute used to find the user account. The value will be the name of
        the user used for authentication.",
        "propertyOrder" : 600,
        "required" : true,
    }
}

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "primaryLdapServer" : {
    "title" : "Primary LDAP Server",
    "description" : "Use this list to set the primary LDAP server used for authentication.
<br><br>The LDAP authentication module will use this list as the primary server for authentication. A
single entry must be in the format:<br><br><code>ldap_server:port</code><br><br>Multiple entries
allow associations between OpenAM servers and a LDAP server. The format is:<br><br><code>local
server name | server:port</code><br><br>The local server name is the full name of the server from
the list of servers and sites.",
    "propertyOrder" : 100,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "openam-auth-ldap-connection-mode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Defines which protocol/operation is used to establish the connection to the
LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}

```

1.87.1.2. delete

Usage:

```
am> delete LdapModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.87.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action LdapModule --realm Realm --actionName getAllTypes
```

1.87.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action LdapModule --realm Realm --actionName getCreatableTypes
```

1.87.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action LdapModule --realm Realm --actionName nextdescendents
```

1.87.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query LdapModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.87.1.7. read

Usage:

```
am> read LdapModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.87.1.8. update

Usage:

```
am> update LdapModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "connectionHeartbeatTimeUnit" : {
      "title" : "LDAP Connection Heartbeat Time Unit",
      "description" : "Defines the time unit corresponding to the Heartbeat Interval
      setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
      to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
      it may take up to the interval period before the problem is detected. Use along with the Heartbeat
      Interval parameter to define the exact interval.",
      "propertyOrder" : 1800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "userBindDN" : {
      "title" : "Bind User DN",
      "description" : "The DN of an admin user used by the module to authentication to the LDAP
      server<br><br>The LDAP module requires an administration account in order to perform functionality
      such as password reset.<br></><i>NB </i><code>cn=Directory Manager</code> should not be used in
      production systems.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "connectionHeartbeatInterval" : {
      "title" : "LDAP Connection Heartbeat Interval",
      "description" : "Specifies how often should OpenAM send a heartbeat request to the
      directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
      request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
      error) then it may take up to the interval period before the problem is detected. Use along with the
      Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
      disabling heartbeat requests.",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
      authentication module has an authentication level that can be used to indicate the level of security
      associated with the module; 0 is the lowest (and the default). ",
      "propertyOrder" : 2000,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "userBindPassword" : {
      "title" : "Bind User Password",
```

```

        "description" : "The password of the administration account.",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "userSearchAttributes" : {
        "title" : "Attributes Used to Search for a User to be Authenticated",
        "description" : "The attributes specified in this list form the LDAP search filter.<br><br>The default value of uid will form the following search filter of <code>uid=<i>user</i></code>, if there are multiple values such as uid and cn, the module will create a search filter as follows <code>(|(uid=<i>user</i>)(cn=<i>user</i>))</code>",
        "propertyOrder" : 700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "searchScope" : {
        "title" : "Search Scope",
        "description" : "The level in the Directory Server that will be searched for a matching user profile.<br><br>This attribute controls how the directory is searched.<br><br><ul><li><code>OBJECT</code>: Only the Base DN is searched.</li><li><code>ONELEVEL</code>: Only the single level below (and not the Base DN) is searched</li><li><code>SUBTREE</code>: The Base DN and all levels below are searched</li></ul>",
        "propertyOrder" : 900,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "profileAttributeMappings" : {
        "title" : "User Creation Attributes",
        "description" : "Controls the mapping of local attribute to external attribute for dynamic profile creation.<br><br>If dynamic profile creation is enabled; this feature allows for a mapping between the attribute/values retrieved from the users authenticated profile and the attribute/values that will be provisioned into their matching account in the data store.<br><br>The format of this property is: <br><br><code> local attr1|external attr1</code>",
        "propertyOrder" : 1300,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "operationTimeout" : {
        "title" : "LDAP operations timeout",
        "description" : "Defines the timeout in seconds OpenAM should wait for a response of the Directory Server - <code>0</code> means no timeout.<br><br>If the Directory Server's host is down completely or the TCP connection became stale OpenAM waits until operation timeouts from the OS or the JVM are applied. However this setting allows more granular control within OpenAM itself. A value of <code>0</code> means NO timeout is applied on OpenAM level and the timeouts from the JVM or OS will apply.",
        "propertyOrder" : 1900,
        "required" : true,
        "type" : "integer",
    }
}

```



```

    "exampleValue" : ""
  },
  "trustAllServerCertificates" : {
    "title" : "Trust All Server Certificates",
    "description" : "Enables a X509TrustManager that trusts all
certificates.<br><br>This feature will allow the LDAP authentication module to connect to LDAP
servers protected by self signed or invalid certificates (such as invalid hostname).<br><br><i>NB
</i>Use this feature with care as it bypasses the normal certificate verification process",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "returnUserDN" : {
    "title" : "Return User DN to DataStore",
    "description" : "Controls whether the DN or the username is returned as the authentication
principal.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userSearchStartDN" : {
    "title" : "DN to Start User Search",
    "description" : "The search for accounts to be authenticated start from this base DN <br><br>For
a single server just enter the Base DN to be searched. Multiple OpenAM servers can have different
base DNS for the search The format is as follows:<br><br><code>local server name | search DN</
code><br><br><i>NB </i>The local server name is the full name of the server from the list of servers
and sites.",
    "propertyOrder" : 300,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "userSearchFilter" : {
    "title" : "User Search Filter",
    "description" : "This search filter will be appended to the standard user search
filter.<br><br>This attribute can be used to append a custom search filter to the standard filter.
For example: <code>(objectClass=person)</code>would result in the following user search filter:<br>
<br><code>(&(uid=<i>user</i>)(objectClass=person))</code>",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "secondaryLdapServer" : {
    "title" : "Secondary LDAP Server",
    "description" : "Use this list to set the secondary (failover) LDAP server used for
authentication.<br><br>If the primary LDAP server fails, the LDAP authentication module will failover
to the secondary server. A single entry must be in the format:<br><br><code>ldap_server:port</
code><br><br>Multiple entries allow associations between OpenAM servers and a LDAP server. The
format is:<br><br><code>local server name | server:port</code><br><br><i>NB </i>The local server
name is the full name of the server from the list of servers and sites.",
    "propertyOrder" : 200,
    "required" : true,
    "items" : {

```

```

        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"minimumPasswordLength" : {
    "title" : "Minimum Password Length",
    "description" : "Enforced when the user is resetting their password as part of the authentication.<br><br>If the user needs to reset their password as part of the authentication process, the authentication module can enforce a minimum password length. This is separate from any password length controls from the underlying LDAP server. If the external LDAP server password policy is enforcing password length, set this value to 0 to avoid confusion.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"beheraPasswordPolicySupportEnabled" : {
    "title" : "LDAP Behera Password Policy Support",
    "description" : "Enables support for modern LDAP password policies<br><br>LDAP Behera Password policies are supported by modern LDAP servers such as OpenDJ. If this functionality is disabled then only the older Netscape VCHU password policy standard will be enforced.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"userProfileRetrievalAttribute" : {
    "title" : "Attribute Used to Retrieve User Profile",
    "description" : "The LDAP module will use this attribute to search of the profile of an authenticated user.<br><br>This is the attribute used to find the profile of the authenticated user. Normally this will be the same attribute used to find the user account. The value will be the name of the user used for authentication.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"primaryLdapServer" : {
    "title" : "Primary LDAP Server",
    "description" : "Use this list to set the primary LDAP server used for authentication.<br><br>The LDAP authentication module will use this list as the primary server for authentication. A single entry must be in the format:<br><br><code>ldap_server:port</code><br><br>Multiple entries allow associations between OpenAM servers and a LDAP server. The format is:<br><br><code>local server name | server:port</code><br><br>The local server name is the full name of the server from the list of servers and sites.",
    "propertyOrder" : 100,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"openam-auth-ldap-connection-mode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Defines which protocol/operation is used to establish the connection to the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and passwords are transferred in <b>cleartext</b> over the network.<br><br>If 'LDAPS' is selected, the
    
```

```
connection is secured via SSL or TLS. <br/> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
}
```

1.87.2. Global Operations

Resource path: `/global-config/authentication/modules/ldap`

Resource version: `1.0`

1.87.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action LdapModule --global --actionName getAllTypes
```

1.87.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action LdapModule --global --actionName getCreatableTypes
```

1.87.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action LdapModule --global --actionName nextdescendents
```

1.87.2.4. read

Usage:

```
am> read LdapModule --global
```

1.87.2.5. update

Usage:

```
am> update LdapModule --global --body body
```

Parameters:
--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "userBindPassword" : {
          "title" : "Bind User Password",
          "description" : "The password of the administration account.",
          "propertyOrder" : 500,
          "required" : true,
          "type" : "string",
          "format" : "password",
          "exampleValue" : ""
        },
        "openam-auth-ldap-connection-mode" : {
          "title" : "LDAP Connection Mode",
          "description" : "Defines which protocol/operation is used to establish the connection to the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by using StartTLS extended operation.",
          "propertyOrder" : 1000,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "userBindDN" : {
          "title" : "Bind User DN",
          "description" : "The DN of an admin user used by the module to authentication to the LDAP server.<br><br>The LDAP module requires an administration account in order to perform functionality such as password reset.<br><br><i>NB </i><code>cn=Directory Manager</code> should not be used in production systems.",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "connectionHeartbeatInterval" : {
          "title" : "LDAP Connection Heartbeat Interval",
          "description" : "Specifies how often should OpenAM send a heartbeat request to the directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then it may take up to the interval period before the problem is detected. Use along with the Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in disabling heartbeat requests.",
          "propertyOrder" : 1700,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        }
      }
    }
  }
}
```

```

    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
      "propertyOrder" : 2000,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "minimumPasswordLength" : {
      "title" : "Minimum Password Length",
      "description" : "Enforced when the user is resetting their password as part of the authentication.<br><br>If the user needs to reset their password as part of the authentication process, the authentication module can enforce a minimum password length. This is separate from any password length controls from the underlying LDAP server. If the external LDAP server password policy is enforcing password length, set this value to 0 to avoid confusion.",
      "propertyOrder" : 1400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "beheraPasswordPolicySupportEnabled" : {
      "title" : "LDAP Behera Password Policy Support",
      "description" : "Enables support for modern LDAP password policies<br><br>LDAP Behera Password policies are supported by modern LDAP servers such as OpenDJ. If this functionality is disabled then only the older Netscape VCHU password policy standard will be enforced.",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "userSearchFilter" : {
      "title" : "User Search Filter",
      "description" : "This search filter will be appended to the standard user search filter.<br><br>This attribute can be used to append a custom search filter to the standard filter. For example: <code>(objectClass=person)</code>would result in the following user search filter:<br><br><code>(&(uid=<i>user</i>)(objectClass=person))</code>",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "userProfileRetrievalAttribute" : {
      "title" : "Attribute Used to Retrieve User Profile",
      "description" : "The LDAP module will use this attribute to search of the profile of an authenticated user.<br><br>This is the attribute used to find the profile of the authenticated user. Normally this will be the same attribute used to find the user account. The value will be the name of the user used for authentication.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "secondaryLdapServer" : {
      "title" : "Secondary LDAP Server",
      "description" : "Use this list to set the secondary (failover) LDAP server used for authentication.<br><br>If the primary LDAP server fails, the LDAP authentication module will failover
    
```

to the secondary server. A single entry must be in the format:
`ldap_server:port`
 Multiple entries allow associations between OpenAM servers and a LDAP server. The format is:
`local server name | server:port`
 The local server name is the full name of the server from the list of servers and sites.",

```

        "propertyOrder" : 200,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "connectionHeartbeatTimeUnit" : {
        "title" : "LDAP Connection Heartbeat Time Unit",
        "description" : "Defines the time unit corresponding to the Heartbeat Interval setting.  

        This setting controls how often OpenAM should send a heartbeat search request to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then it may take up to the interval period before the problem is detected. Use along with the Heartbeat Interval parameter to define the exact interval.",
        "propertyOrder" : 1800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "userSearchAttributes" : {
        "title" : "Attributes Used to Search for a User to be Authenticated",
        "description" : "The attributes specified in this list form the LDAP search filter.  

        The default value of uid will form the following search filter of uid=<i>user/</i>, if there are multiple values such as uid and cn, the module will create a search filter as follows (|uid=<i>user/</i>)(cn=<i>user/</i>)|",
        "propertyOrder" : 700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "primaryLdapServer" : {
        "title" : "Primary LDAP Server",
        "description" : "Use this list to set the primary LDAP server used for authentication.  

        The LDAP authentication module will use this list as the primary server for authentication. A single entry must be in the format:  

ldap_server:port  

        Multiple entries allow associations between OpenAM servers and a LDAP server. The format is:  

local server name | server:port  

        The local server name is the full name of the server from the list of servers and sites.",
        "propertyOrder" : 100,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "profileAttributeMappings" : {
        "title" : "User Creation Attributes",
        "description" : "Controls the mapping of local attribute to external attribute for dynamic profile creation.  

        If dynamic profile creation is enabled; this feature allows for a mapping between the attribute/values retrieved from the users authenticated profile and the attribute/values
    
```

that will be provisioned into their matching account in the data store.

The format of this property is:

<code> local attr|external attr</code>",

```

    "propertyOrder" : 1300,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "operationTimeout" : {
    "title" : "LDAP operations timeout",
    "description" : "Defines the timeout in seconds OpenAM should wait for a response of the
Directory Server - <code>0</code> means no timeout.<br/><br/>If the Directory Server's host is down
completely or the TCP connection became stale OpenAM waits until operation timeouts from the OS or
the JVM are applied. However this setting allows more granular control within OpenAM itself. A value
of <code>0</code> means NO timeout is applied on OpenAM level and the timeouts from the JVM or OS
will apply.",
    "propertyOrder" : 1900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "userSearchStartDN" : {
    "title" : "DN to Start User Search",
    "description" : "The search for accounts to be authenticated start from this base DN
<br/><br/>For a single server just enter the Base DN to be searched. Multiple OpenAM servers can have
different base DNS for the search The format is as follows:<br/><br/><code>local server name | search
DN</code><br/><br/><i>NB </i>The local server name is the full name of the server from the list of
servers and sites.",
    "propertyOrder" : 300,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "searchScope" : {
    "title" : "Search Scope",
    "description" : "The level in the Directory Server that will be searched for a
matching user profile.<br/><br/>This attribute controls how the directory is searched.<br/><br/>
<ul><li><code>OBJECT</code>: Only the Base DN is searched.</li><li><code>ONELEVEL</code>: Only the
single level below (and not the Base DN) is searched</li><li><code>SUBTREE</code>: The Base DN and
all levels below are searched</li></ul>",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "trustAllServerCertificates" : {
    "title" : "Trust All Server Certificates",
    "description" : "Enables a <code>X509TrustManager</code> that trusts all
certificates.<br/><br/>This feature will allow the LDAP authentication module to connect to LDAP
servers protected by self signed or invalid certificates (such as invalid hostname).<br/><br/><i>NB
</i>Use this feature with care as it bypasses the normal certificate verification process",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "boolean",

```

```
        "exampleValue" : ""
      },
      "returnUserDN" : {
        "title" : "Return User DN to DataStore",
        "description" : "Controls whether the DN or the username is returned as the authentication
principal.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      }
    },
    "type" : "object",
    "title" : "Realm Defaults"
  }
}
```

1.88. LegacyUserSelfService

1.88.1. Realm Operations

Resource path: `/realm-config/services/security`

Resource version: `1.0`

1.88.1.1. create

Usage:

```
am> create LegacyUserSelfService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userRegisteredDestination" : {
      "title" : "Destination After Successful Self-Registration",
      "description" : "Specifies the behavior when self-registration has successfully completed.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "selfRegistrationEnabled" : {
      "title" : "Self-Registration for Users",
```



```

    "description" : "If enabled, new users can sign up using a REST API client.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "selfServiceEnabled" : {
    "title" : "Legacy Self-Service REST Endpoint",
    "description" : "Specify whether to enable the legacy self-service endpoint.<p>OpenAM supports two User Self-Service components: the Legacy User Self-Service, which is based on a Java SDK and is available in OpenAM versions prior to OpenAM 13, and a common REST-based/XUI-based User Self-Service available in OpenAM 13 and later.<p>The Legacy User Self-Service will be deprecated in a future release.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "selfRegistrationConfirmationUrl" : {
    "title" : "Self-Registration Confirmation Email URL",
    "description" : "This page handles the HTTP GET request when the user clicks the link sent by email in the confirmation request.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "selfRegistrationTokenLifetime" : {
    "title" : "Self-Registration Token LifeTime (seconds)",
    "description" : "Maximum life time for the token allowing User Self-Registration using the REST API.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "forgotPasswordConfirmationUrl" : {
    "title" : "Forgot Password Confirmation Email URL",
    "description" : "This page handles the HTTP GET request when the user clicks the link sent by email in the confirmation request.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "protectedUserAttributes" : {
    "title" : "Protected User Attributes",
    "description" : "A list of user profile attributes. Users modifying any of the attributes in this list will be required to enter a password as confirmation before the change is accepted. This option applies to XUI deployments only.",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "forgotPasswordEnabled" : {

```

```
    "title" : "Forgot Password for Users",
    "description" : "If enabled, users can assign themselves a new password using a REST API
client.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "forgotPasswordTokenLifetime" : {
    "title" : "Forgot Password Token Lifetime (seconds)",
    "description" : "Maximum life time for the token that allows a user to process a forgotten
password using the REST API.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
```

1.88.1.2. delete

Usage:

```
am> delete LegacyUserSelfService --realm Realm
```

1.88.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action LegacyUserSelfService --realm Realm --actionName getAllTypes
```

1.88.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action LegacyUserSelfService --realm Realm --actionName getCreatableTypes
```

1.88.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action LegacyUserSelfService --realm Realm --actionName nextdescendents
```

1.88.1.6. read

Usage:

```
am> read LegacyUserSelfService --realm Realm
```

1.88.1.7. update

Usage:

```
am> update LegacyUserSelfService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userRegisteredDestination" : {
      "title" : "Destination After Successful Self-Registration",
      "description" : "Specifies the behavior when self-registration has successfully completed.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "selfRegistrationEnabled" : {
      "title" : "Self-Registration for Users",
      "description" : "If enabled, new users can sign up using a REST API client.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "selfServiceEnabled" : {
      "title" : "Legacy Self-Service REST Endpoint",
      "description" : "Specify whether to enable the legacy self-service endpoint.<p>OpenAM supports two User Self-Service components: the Legacy User Self-Service, which is based on a Java SDK and is available in OpenAM versions prior to OpenAM 13, and a common REST-based/XUI-based User Self-Service available in OpenAM 13 and later.<p>The Legacy User Self-Service will be deprecated in a future release.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "selfRegistrationConfirmationUrl" : {
      "title" : "Self-Registration Confirmation Email URL",
      "description" : "This page handles the HTTP GET request when the user clicks the link sent by email in the confirmation request.",
      "propertyOrder" : 400,
      "required" : true,

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "selfRegistrationTokenLifetime" : {
    "title" : "Self-Registration Token LifeTime (seconds)",
    "description" : "Maximum life time for the token allowing User Self-Registration using the REST
API.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "forgotPasswordConfirmationUrl" : {
    "title" : "Forgot Password Confirmation Email URL",
    "description" : "This page handles the HTTP GET request when the user clicks the link sent by
email in the confirmation request.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "protectedUserAttributes" : {
    "title" : "Protected User Attributes",
    "description" : "A list of user profile attributes. Users modifying any of the attributes in
this list will be required to enter a password as confirmation before the change is accepted. This
option applies to XUI deployments only.",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "forgotPasswordEnabled" : {
    "title" : "Forgot Password for Users",
    "description" : "If enabled, users can assign themselves a new password using a REST API
client.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "forgotPasswordTokenLifetime" : {
    "title" : "Forgot Password Token Lifetime (seconds)",
    "description" : "Maximum life time for the token that allows a user to process a forgotten
password using the REST API.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
}

```

1.88.2. Global Operations

Resource path: `/global-config/services/security`

Resource version: `1.0`

1.88.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action LegacyUserSelfService --global --actionName getAllTypes
```

1.88.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action LegacyUserSelfService --global --actionName getCreatableTypes
```

1.88.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action LegacyUserSelfService --global --actionName nextdescendents
```

1.88.2.4. read

Usage:

```
am> read LegacyUserSelfService --global
```

1.88.2.5. update

Usage:

```
am> update LegacyUserSelfService --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
```

```

"properties" : {
  "forgotPasswordConfirmationUrl" : {
    "title" : "Forgot Password Confirmation Email URL",
    "description" : "This page handles the HTTP GET request when the user clicks the link sent
by email in the confirmation request.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "selfRegistrationEnabled" : {
    "title" : "Self-Registration for Users",
    "description" : "If enabled, new users can sign up using a REST API client.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "protectedUserAttributes" : {
    "title" : "Protected User Attributes",
    "description" : "A list of user profile attributes. Users modifying any of the attributes in
this list will be required to enter a password as confirmation before the change is accepted. This
option applies to XUI deployments only.",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "forgotPasswordEnabled" : {
    "title" : "Forgot Password for Users",
    "description" : "If enabled, users can assign themselves a new password using a REST API
client.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userRegisteredDestination" : {
    "title" : "Destination After Successful Self-Registration",
    "description" : "Specifies the behavior when self-registration has successfully completed.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "selfRegistrationConfirmationUrl" : {
    "title" : "Self-Registration Confirmation Email URL",
    "description" : "This page handles the HTTP GET request when the user clicks the link sent
by email in the confirmation request.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "forgotPasswordTokenLifetime" : {
    "title" : "Forgot Password Token Lifetime (seconds)",

```

```

    "description" : "Maximum life time for the token that allows a user to process a forgotten
password using the REST API.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "selfServiceEnabled" : {
    "title" : "Legacy Self-Service REST Endpoint",
    "description" : "Specify whether to enable the legacy self-service endpoint.<p>OpenAM
supports two User Self-Service components: the Legacy User Self-Service, which is based on a Java
SDK and is available in OpenAM versions prior to OpenAM 13, and a common REST-based/XUI-based User
Self-Service available in OpenAM 13 and later.<p>The Legacy User Self-Service will be deprecated in a
future release.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "selfRegistrationTokenLifetime" : {
    "title" : "Self-Registration Token LifeTime (seconds)",
    "description" : "Maximum life time for the token allowing User Self-Registration using the
REST API.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}

```

1.89. Logging

1.89.1. Global Operations

Resource path: `/global-config/services/logging`

Resource version: `1.0`

1.89.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Logging --global --actionName getAllTypes
```

1.89.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Logging --global --actionName getCreatableTypes
```

1.89.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Logging --global --actionName nextdescendents
```

1.89.1.4. read

Usage:

```
am> read Logging --global
```

1.89.1.5. update

Usage:

```
am> update Logging --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "general" : {
      "type" : "object",
      "title" : "General",
      "propertyOrder" : 0,
      "properties" : {
        "signaturePeriod" : {
          "title" : "Log Signature Time",
          "description" : "The frequency (in seconds) that OpenAM will digitally sign the log records.<br><br>When secure logging is enabled, this is the period that OpenAM will digitally signed the contents of the log files. The log signatures form the basis of the log file integrity checking.",
          "propertyOrder" : 2100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
      }
    },
  }
},
```



```

"bufferTime" : {
  "title" : "Buffer Time",
  "description" : "The maximum time (in seconds) OpenAM will hold log records in memory before
flushing to the underlying repository.",
  "propertyOrder" : 2900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"bufferSize" : {
  "title" : "Buffer Size",
  "description" : "The number of log records held in memory before the log records will be
flushed to the logfile or the database.",
  "propertyOrder" : 2700,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"fields" : {
  "title" : "Configurable Log Fields",
  "description" : "Controls the fields that are logged by OpenAM.<br><br>This property is the
list of fields that are logged by default. Administrators can choose to limit the information logged
by OpenAM.",
  "propertyOrder" : 1900,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"verifyPeriod" : {
  "title" : "Log Verification Frequency",
  "description" : "The frequency (in seconds) that OpenAM verifies security of the log
files.<br><br>When secure logging is enabled, this is the period that OpenAM will check the integrity
of the log files.",
  "propertyOrder" : 2000,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"jdkLoggingLevel" : {
  "title" : "Logging Level",
  "description" : "Control the level of JDK logging within OpenAM. ",
  "propertyOrder" : 3100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"security" : {
  "title" : "Secure Logging",
  "description" : "Enable or Disable secure logging.<br><br>Enabling this setting will cause
OpenAM to digitally sign and verify the contents of the log files to help prevent and detect log file
tampering. A certificate must be configured for this functionality to be enabled. ",
  "propertyOrder" : 2200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},

```

```

"type" : {
  "title" : "Logging Type",
  "description" : "Specifies whether to log to a database, Syslog, or to the filing
system.<br><br>If you choose database then be sure to set the connection attributes correctly,
including the JDBC driver to use.",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"resolveHostName" : {
  "title" : "Log Record Resolve Host Name",
  "description" : "Enable this to have OpenAM perform a DNS host lookup to populate the host
name field for log records.<br><br><i>Note:</i> Enabling this functionality will increase the load of
the logging system and the OpenAM host must have DNS configured. ",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"filesPerKeystore" : {
  "title" : "Number of Files per Archive",
  "description" : "Controls the number of logs files that will be archived by the secure
logging system.",
  "propertyOrder" : 2600,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"buffering" : {
  "title" : "Time Buffering",
  "description" : "Enable or Disable log buffering<br><br>When enabled OpenAM holds all log
records in a memory buffer that it periodically flush to the repository. The period is set in the
<i>Buffer Time</i> property.",
  "propertyOrder" : 3000,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"status" : {
  "title" : "Log Status",
  "description" : "Enable the OpenAM logging system.<p><p>OpenAM supports two Audit Logging
Services: the legacy Logging Service, which is based on a Java SDK and is available in OpenAM
versions prior to OpenAM 13.5, and a new common REST-based Audit Logging Service available from
OpenAM 13.5.<p><p>The legacy Logging Service will be deprecated in a future release.",
  "propertyOrder" : 800,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"certificateStore" : {
  "title" : "Logging Certificate Store Location",
  "description" : "The path to the Java keystore containing the logging system
certificate.<br><br>The secure logging system will use the certificate alias of <code>Logger</code>
to locate the certificate in the specified keystore.",
  "propertyOrder" : 2400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}

```

```

    },
    "signingAlgorithm" : {
      "title" : "Secure Logging Signing Algorithm ",
      "description" : "Determines the algorithm used to digitally sign the log records.",
      "propertyOrder" : 2300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"database" : {
  "type" : "object",
  "title" : "Database",
  "propertyOrder" : 2,
  "properties" : {
    "password" : {
      "title" : "Database User Password",
      "description" : "When logging to a database, set this to the password used to connect to the
database. If this attribute is incorrectly set, OpenAM performance suffers.",
      "propertyOrder" : 1200,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "user" : {
      "title" : "Database User Name",
      "description" : "When logging to a database, set this to the user name used to connect to
the database. If this attribute is incorrectly set, OpenAM performance suffers.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "driver" : {
      "title" : "Database Driver Name",
      "description" : "When logging to a database, set this to the class name of the JDBC driver
used to connect to the database.<br><br>The default is for Oracle. OpenAM also works with the MySQL
database driver.",
      "propertyOrder" : 1300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "databaseFailureMemoryBufferSize" : {
      "title" : "DB Failure Memory Buffer Size",
      "description" : "Max number of log records held in memory if DB logging fails.<br><br>This
is the maximum number of log records that will be held in memory if the database is unavailable.
When the buffer is full, new log records cause the oldest record in the buffer to be cleared. OpenAM
monitoring records the number of log entries cleared when the database was unavailable.<br><br>If
the value of this property is less than that of the <i>Buffer Size</i> then the buffer size value
will take precedence. ",
      "propertyOrder" : 2800,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "maxRecords" : {

```

```

        "title" : "Maximum Number of Records",
        "description" : "The maximum number of records read from the logs via the Logging API",
        "propertyOrder" : 2500,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    }
},
"syslog" : {
    "type" : "object",
    "title" : "Syslog",
    "propertyOrder" : 3,
    "properties" : {
        "protocol" : {
            "title" : "Syslog transport protocol",
            "description" : "The protocol to use to connect to the syslog server.",
            "propertyOrder" : 1600,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "facility" : {
            "title" : "Syslog facility",
            "description" : "Syslog uses the facility level to determine the type of program that is
logging the message.",
            "propertyOrder" : 1700,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "port" : {
            "title" : "Syslog server port",
            "description" : "The port number the syslog server is configured to listen to.",
            "propertyOrder" : 1500,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "host" : {
            "title" : "Syslog server host",
            "description" : "The URL or IP address of the syslog server, for example <code>http://
mysyslog.example.com</code>, or <code>localhost</code>.",
            "propertyOrder" : 1400,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "timeout" : {
            "title" : "Syslog connection timeout",
            "description" : "The amount of time to wait when attempting to connect to the syslog server
before reporting a failure, in seconds.",
            "propertyOrder" : 1800,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        }
    }
}
},

```

```

"file" : {
  "type" : "object",
  "title" : "File",
  "propertyOrder" : 1,
  "properties" : {
    "location" : {
      "title" : "Log File Location",
      "description" : "The path to the location of the log files<br><br>This property controls
the location of the log files; the value of this property varies on whether File or DB logging is
in use:<p><ul><li>File: The full pathname to the directory containing the log files.</li><li>DB: The
JDBC URL to the database used to store the log file database.</li></ul>",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationEnabled" : {
      "title" : "Log Rotation",
      "description" : "Enable log rotation to cause new log files to be created when configured
thresholds are reached, such as <i>Maximum Log Size</i> or <i>Logfile Rotation Interval</i>.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "numberHistoryFiles" : {
      "title" : "Number of History Files",
      "description" : "Sets the number of history files for each log that OpenAM keeps, including
time-based histories.<p><p>The previously live file is moved and is included in the history count,
and a new log is created to serve as the live log file. Any log file in the history count that goes
over the number specified here will be deleted.<p><p>For time-based logs, a new set of logs will be
created when OpenAM is started because of the time-based file names that are used.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "prefix" : {
      "title" : "Logfile Rotation Prefix",
      "description" : "The name of the log files will be prefixed with the supplied
value.<br><br>This field defines the log file prefix. The prefix will be added to the name of all
logfiles.<br><br><i>Note:</i> Only used when time-based log rotation is enabled.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "rotationInterval" : {
      "title" : "Logfile Rotation Interval",
      "description" : "The rotation interval (in minutes).<br><br>The rotation interval determines
the frequency of when the log files will be rotated. If the value is <code>-1</code>, then time based
rotation is disabled and log file size based rotation is enabled.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "suffix" : {
      "title" : "Logfile Rotation Suffix",

```

```

      "description" : "The name of the log files will be suffixed with the supplied  

value.<br><br>This field defines the log file suffix. If no suffix is provided, then the following  

default suffix format will be used: <code>-MM.dd.yy-kk.mm</code>. The suffix allows use of Date  

and Time patterns defined in <a href=\"http://download.oracle.com/javase/6/docs/api/java/text/  

SimpleDateFormat.html\"><code>SimpleDateFormat</code></a><p><p><i>Note:</i> This field is only used if  

the time based rotation is enabled.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "maxFileSize" : {
      "title" : "Maximum Log Size",
      "description" : "Maximum size of a log file, in bytes.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
}
}
}
}

```

1.90. MembershipModule

1.90.1. Realm Operations

Resource path: `/realm-config/authentication/modules/membership`

Resource version: `1.0`

1.90.1.1. create

Usage:

```
am> create MembershipModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
```

```

"properties" : {
  "minimumPasswordLength" : {
    "title" : "Minimum Password Length",
    "description" : "The minimum length of the user password.<br><br>Setting this value to 0
disables this functionality.<br><br><i>NB </i>This feature is separate from any password policy in
the underlying data store",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "defaultUserRoles" : {
    "title" : "Default User Roles",
    "description" : "The role DN's that will be assigned to the user.<br><br><i>NB </i>Roles are
only supported in Sun Directory Server Enterprise Edition",
    "propertyOrder" : 200,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "defaultUserStatus" : {
    "title" : "User Status After Registration",
    "description" : "Determines if the user account should be automatically active after
registration completes.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
}

```

1.90.1.2. delete

Usage:

```
am> delete MembershipModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.90.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action MembershipModule --realm Realm --actionName getAllTypes
```

1.90.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action MembershipModule --realm Realm --actionName getCreatableTypes
```

1.90.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action MembershipModule --realm Realm --actionName nextdescendents
```

1.90.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query MembershipModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.90.1.7. read

Usage:

```
am> read MembershipModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.90.1.8. update

Usage:

```
am> update MembershipModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "minimumPasswordLength" : {
      "title" : "Minimum Password Length",
      "description" : "The minimum length of the user password.<br><br>Setting this value to 0
disables this functionality.<br><br><i>NB </i>This feature is separate from any password policy in
the underlying data store",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "defaultUserRoles" : {
      "title" : "Default User Roles",
      "description" : "The role DN's that will be assigned to the user.<br><br><i>NB </i>Roles are
only supported in Sun Directory Server Enterprise Edition",
      "propertyOrder" : 200,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "defaultUserStatus" : {
      "title" : "User Status After Registration",
      "description" : "Determines if the user account should be automatically active after
registration completes.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 400,
      "required" : true,

```

```
    "type" : "integer",  
    "exampleValue" : ""  
  }  
}  
}
```

1.90.2. Global Operations

Resource path: `/global-config/authentication/modules/membership`

Resource version: `1.0`

1.90.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action MembershipModule --global --actionName getAllTypes
```

1.90.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action MembershipModule --global --actionName getCreatableTypes
```

1.90.2.3. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action MembershipModule --global --actionName nextdescendants
```

1.90.2.4. read

Usage:

```
am> read MembershipModule --global
```

1.90.2.5. update

Usage:

```
am> update MembershipModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "minimumPasswordLength" : {
          "title" : "Minimum Password Length",
          "description" : "The minimum length of the user password.<br><br>Setting this value to 0 disables this functionality.<br><br><i>NB </i>This feature is separate from any password policy in the underlying data store",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "defaultUserRoles" : {
          "title" : "Default User Roles",
          "description" : "The role DN's that will be assigned to the user.<br><br><i>NB </i>Roles are only supported in Sun Directory Server Enterprise Edition",
          "propertyOrder" : 200,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "defaultUserStatus" : {
          "title" : "User Status After Registration",
          "description" : "Determines if the user account should be automatically active after registration completes.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "type" : "object",
    "title" : "Realm Defaults"
  }
}
```

1.91. Meter

1.91.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/MeterNode`

Resource version: `1.0`

1.91.1.1. create

Usage:

```
am> create Meter --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "metricKey" : {
      "title" : "Metric Key",
      "description" : "Identifier of metric to update when this node is processed.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "metricKey" ]
}
```

1.91.1.2. delete

Usage:

```
am> delete Meter --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.91.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Meter --realm Realm --actionName getAllTypes
```

1.91.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Meter --realm Realm --actionName getCreatableTypes
```

1.91.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action Meter --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.91.1.6. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Meter --realm Realm --actionName nextdescendants
```

1.91.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Meter --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.91.1.8. read

Usage:

```
am> read Meter --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.91.1.9. update

Usage:

```
am> update Meter --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "metricKey" : {
      "title" : "Metric Key",
      "description" : "Identifier of metric to update when this node is processed.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "metricKey" ]
}
```

1.92. ModifyAuthLevel

1.92.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/ModifyAuthLevelNode`

Resource version: `1.0`

1.92.1.1. create

Usage:

```
am> create ModifyAuthLevel --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authLevelIncrement" : {
      "title" : "Value To Add",
      "description" : "Value which is added to the authentication level.Value may be negative to decrease the authentication level.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "authLevelIncrement" ]
}
```

1.92.1.2. delete

Usage:

```
am> delete ModifyAuthLevel --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.92.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ModifyAuthLevel --realm Realm --actionName getAllTypes
```

1.92.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ModifyAuthLevel --realm Realm --actionName getCreatableTypes
```

1.92.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action ModifyAuthLevel --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.92.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ModifyAuthLevel --realm Realm --actionName nextdescendents
```

1.92.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ModifyAuthLevel --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.92.1.8. read

Usage:

```
am> read ModifyAuthLevel --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.92.1.9. update

Usage:

```
am> update ModifyAuthLevel --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authLevelIncrement" : {
      "title" : "Value To Add",
      "description" : "Value which is added to the authentication level.Value may be negative to
decrease the authentication level.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "authLevelIncrement" ]
}
```

1.93. Monitoring

1.93.1. Global Operations

Resource path: `/global-config/services/monitoring`

Resource version: `1.0`

1.93.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Monitoring --global --actionName getAllTypes
```

1.93.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Monitoring --global --actionName getCreatableTypes
```

1.93.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Monitoring --global --actionName nextdescendents
```

1.93.1.4. read

Usage:

```
am> read Monitoring --global
```

1.93.1.5. update

Usage:

```
am> update Monitoring --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "enabled" : {
      "title" : "Monitoring Status",
      "description" : "Enable / Disable the monitoring system",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "sessionHistoryWindowSize" : {
      "title" : "Session monitoring history size",
      "description" : "Size of the window of most recent session operations to record to expose via monitoring system. Valid range is 100 - 1000000.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authfilePath" : {
      "title" : "Monitoring HTTP interface authentication file path",
      "description" : "Path to the monitoring system authentication file<br><br>The <code>openam_mon_auth</code> file contains the username and password of the account used to protect the monitoring interfaces. The default username is <code>demo</code> with a password of <code>changeit</code>. Use the <code>ampassword</code> command to encrypt a new password.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "rmiEnabled" : {
      "title" : "Monitoring RMI interface status",
      "description" : "Enable / Disable the JMX access to the monitoring system",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "rmiPort" : {
      "title" : "Monitoring RMI Port",
      "description" : "Port number for the JMX monitoring interface",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "httpPort" : {
      "title" : "Monitoring HTTP Port",
      "description" : "Port number for the HTTP monitoring interface",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

```
"snmpPort" : {
  "title" : "Monitoring SNMP Port",
  "description" : "Port number for the SNMP monitoring interface",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"httpEnabled" : {
  "title" : "Monitoring HTTP interface status",
  "description" : "Enable / Disable the HTTP access to the monitoring system ",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"snmpEnabled" : {
  "title" : "Monitoring SNMP interface status",
  "description" : "Enable / Disable the SNMP access to the monitoring system",
  "propertyOrder" : 800,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"policyHistoryWindowSize" : {
  "title" : "Policy evaluation monitoring history size",
  "description" : "Size of the window of most recent policy evaluations to record to expose via
monitoring system. Valid range is 100 - 1000000.",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}
}
```

1.94. MsisdnModule

1.94.1. Realm Operations

Resource path: `/realm-config/authentication/modules/msisdn`

Resource version: `1.0`

1.94.1.1. create

Usage:

```
am> create MsisdnModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "returnUserDN" : {
      "title" : "Return User DN to DataStore",
      "description" : "Controls whether the DN or the username is returned as the authentication principal.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "ldapUserBindPassword" : {
      "title" : "LDAP Server Authentication Password",
      "description" : "The password for the authentication user",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "ldapUserBindDN" : {
      "title" : "LDAP Server Authentication User ",
      "description" : "DN of the user used by the module to authenticate to the LDAP server<br><br>The MSISDN module authenticates to the LDAP server in order to search for a matching number. The DN entered here represents the account used for said authentication and must have read/search access to the LDAP server.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "ldapProviderUrl" : {
      "title" : "LDAP Server and Port ",
      "description" : "Use this list to set the LDAP server used to search for the MSISDN number. <br><br>The MSISDN authentication module will use this list as the server that is searched for a matching MSISDN number. A single entry must be in the format:<br><br><code>ldap_server:port</code><br><br>Multiple entries allow associations between OpenAM servers and a LDAP server. The format is:<br><br><code>local server name | server:port</code><br><br>The local server name is the full name of the server from the list of servers and sites.",
      "propertyOrder" : 300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "trustedGatewayIPAddresses" : {
      "title" : "Trusted Gateway IP Address",
```

```

    "description" : "The list of IP address that are trusted to send MSISDN authentication
requests.<br><br>The client IP address of the authentication request is checked against this list, if
the client IP is not listed then the authentication module will fail.<br><br><i>NB </i>If the list
is empty then all hosts will be trusted.",
    "propertyOrder" : 100,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"baseSearchDN" : {
    "title" : "LDAP Start Search DN",
    "description" : "The start point in the LDAP server for the MSISDN search<br><br>When entering
multiple entries, each entry must be prefixed with a local server name. Multiple entries allow
different search Base DN's depending on the OpenAM server in use. The format is:<br><br><code>local
server name | base dn</code><br><br>The local server name is the full name of the server from the
list of servers and sites.",
    "propertyOrder" : 400,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
},
"ldapSslEnabled" : {
    "title" : "SSL/TLS for LDAP Access",
    "description" : "",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"msisdnUserNamingAttribute" : {
    "title" : "LDAP Attribute Used to Retrieve User Profile",
    "description" : "The name of the attribute returned from the user profile matched against the
supplied MSISDN number",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"msisdnParameterNames" : {
    "title" : "MSISDN Number Search Parameter Name",
    "description" : "Name of the HTTP cookie, header or query parameter containing the MSISDN
number<br><br>The MSISDN authentication module will check the incoming HTTP cookie, header or
query parameter of the request for the MSISDN number. The order of checking is as follows:<br><br>

```

```

<<ol><li>Cookie</li><li>Header</li><li>Query</li></ol><br/><br/><i>NB </i>The <i>MSISDN Header Search
Attribute</i> controls what elements of the request is searched",
  "propertyOrder" : 200,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"userProfileMsisdnAttribute" : {
  "title" : "Attribute To Use To Search LDAP",
  "description" : "The name of the attribute searched in the user profiles for the MSISDN number",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"msisdnRequestSearchLocations" : {
  "title" : "MSISDN Header Search Attribute",
  "description" : "Controls the elements that are searched by the authentication module ",
  "propertyOrder" : 900,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
}
}
}

```

1.94.1.2. delete

Usage:

```
am> delete MsisdnModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.94.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action MsisdnModule --realm Realm --actionName getAllTypes
```

1.94.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action MsisdnModule --realm Realm --actionName getCreatableTypes
```

1.94.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action MsisdnModule --realm Realm --actionName nextdescendents
```

1.94.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query MsisdnModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.94.1.7. read

Usage:

```
am> read MsisdnModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.94.1.8. update

Usage:

```
am> update MsisdnModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "returnUserDN" : {
      "title" : "Return User DN to DataStore",
      "description" : "Controls whether the DN or the username is returned as the authentication principal.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "ldapUserBindPassword" : {
      "title" : "LDAP Server Authentication Password",
      "description" : "The password for the authentication user",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "ldapUserBindDN" : {
      "title" : "LDAP Server Authentication User ",
      "description" : "DN of the user used by the module to authenticate to the LDAP server<br><br>The MSISDN module authenticates to the LDAP server in order to search for a matching number. The DN entered here represents the account used for said authentication and must have read/search access to the LDAP server.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "ldapProviderUrl" : {
      "title" : "LDAP Server and Port ",
      "description" : "Use this list to set the LDAP server used to search for the MSISDN number. <br><br>The MSISDN authentication module will use this list as the server that is searched for a matching MSISDN number. A single entry must be in the format:<br><br><code>ldap_server:port</code><br><br>Multiple entries allow associations between OpenAM servers and a LDAP server. The format is:<br><br><code>local server name | server:port</code><br><br>The local server name is the full name of the server from the list of servers and sites.",
      "propertyOrder" : 300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "trustedGatewayIPAddresses" : {
      "title" : "Trusted Gateway IP Address",
```

```

    "description" : "The list of IP address that are trusted to send MSISDN authentication
requests.<br><br>The client IP address of the authentication request is checked against this list, if
the client IP is not listed then the authentication module will fail.<br><br><i>NB </i>If the list
is empty then all hosts will be trusted.",
    "propertyOrder" : 100,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"baseSearchDN" : {
    "title" : "LDAP Start Search DN",
    "description" : "The start point in the LDAP server for the MSISDN search<br><br>When entering
multiple entries, each entry must be prefixed with a local server name. Multiple entries allow
different search Base DN's depending on the OpenAM server in use. The format is:<br><br><code>local
server name | base dn</code><br><br>The local server name is the full name of the server from the
list of servers and sites.",
    "propertyOrder" : 400,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
},
"ldapSslEnabled" : {
    "title" : "SSL/TLS for LDAP Access",
    "description" : "",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"msisdnUserNamingAttribute" : {
    "title" : "LDAP Attribute Used to Retrieve User Profile",
    "description" : "The name of the attribute returned from the user profile matched against the
supplied MSISDN number",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"msisdnParameterNames" : {
    "title" : "MSISDN Number Search Parameter Name",
    "description" : "Name of the HTTP cookie, header or query parameter containing the MSISDN
number<br><br>The MSISDN authentication module will check the incoming HTTP cookie, header or
query parameter of the request for the MSISDN number. The order of checking is as follows:<br><br>

```

```

<<ol><li>Cookie</li><li>Header</li><li>Query</li></ol><br/><br/><i>NB </i>The <i>MSISDN Header Search
Attribute</i> controls what elements of the request is searched",
  "propertyOrder" : 200,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"userProfileMsisdnAttribute" : {
  "title" : "Attribute To Use To Search LDAP",
  "description" : "The name of the attribute searched in the user profiles for the MSISDN number",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"msisdnRequestSearchLocations" : {
  "title" : "MSISDN Header Search Attribute",
  "description" : "Controls the elements that are searched by the authentication module ",
  "propertyOrder" : 900,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
}
}
}

```

1.94.2. Global Operations

Resource path: `/global-config/authentication/modules/msisdn`

Resource version: `1.0`

1.94.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action MsisdnModule --global --actionName getAllTypes
```

1.94.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action MsisdnModule --global --actionName getCreatableTypes
```

1.94.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action MsisdnModule --global --actionName nextdescendents
```

1.94.2.4. read

Usage:

```
am> read MsisdnModule --global
```

1.94.2.5. update

Usage:

```
am> update MsisdnModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "msisdnRequestSearchLocations" : {
          "title" : "MSISDN Header Search Attribute",
          "description" : "Controls the elements that are searched by the authentication module ",
          "propertyOrder" : 900,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "ldapProviderUrl" : {
          "title" : "LDAP Server and Port ",
          "description" : "Use this list to set the LDAP server used to search for the MSISDN number.
          <br><br>The MSISDN authentication module will use this list as the server that is searched for a
          matching MSISDN number. A single entry must be in the format:<br><br><code>ldap_server:port</
          code><br><br>Multiple entries allow associations between OpenAM servers and a LDAP server. The
          format is:<br><br><code>local server name | server:port</code><br><br>The local server name is
          the full name of the server from the list of servers and sites.",
          "propertyOrder" : 300,
          "required" : true,
          "items" : {
            "type" : "string"
          }
        }
      }
    }
  }
}
```

```

    },
    "type" : "array",
    "exampleValue" : ""
  },
  "msisdnParameterNames" : {
    "title" : "MSISDN Number Search Parameter Name",
    "description" : "Name of the HTTP cookie, header or query parameter containing the MSISDN
number<br><br>The MSISDN authentication module will check the incoming HTTP cookie, header or
query parameter of the request for the MSISDN number. The order of checking is as follows:<br><br>
<ol><li>Cookie</li><li>Header</li><li>Query</li></ol><br><br><i>NB </i>The <i>MSISDN Header Search
Attribute</i> controls what elements of the request is searched",
    "propertyOrder" : 200,
    "required" : true,
    "items" : {
      "type" : "string"
    },
  },
  "type" : "array",
  "exampleValue" : ""
},
"ldapUserBindDN" : {
  "title" : "LDAP Server Authentication User ",
  "description" : "DN of the user used by the module to authenticate to the LDAP
server<br><br>The MSISDN module authenticates to the LDAP server in order to search for a matching
number. The DN entered here represents the account used for said authentication and must have read/
search access to the LDAP server.",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 1200,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"baseSearchDN" : {
  "title" : "LDAP Start Search DN",
  "description" : "The start point in the LDAP server for the MSISDN search<br><br>When
entering multiple entries, each entry must be prefixed with a local server name. Multiple entries
allow different search Base DN's depending on the OpenAM server in use. The format is:<br><br>
<code>local server name | base dn</code><br><br>The local server name is the full name of the
server from the list of servers and sites.",
  "propertyOrder" : 400,
  "required" : true,
  "items" : {
    "type" : "string"
  },
},
"type" : "array",
"exampleValue" : ""
},
"ldapSslEnabled" : {
  "title" : "SSL/TLS for LDAP Access",
  "description" : "",
  "propertyOrder" : 800,

```

```

        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "ldapUserBindPassword" : {
        "title" : "LDAP Server Authentication Password",
        "description" : "The password for the authentication user",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "msisdnUserNamingAttribute" : {
        "title" : "LDAP Attribute Used to Retrieve User Profile",
        "description" : "The name of the attribute returned from the user profile matched against
the supplied MSISDN number",
        "propertyOrder" : 1000,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "userProfileMsisdnAttribute" : {
        "title" : "Attribute To Use To Search LDAP",
        "description" : "The name of the attribute searched in the user profiles for the MSISDN
number",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "trustedGatewayIPAddresses" : {
        "title" : "Trusted Gateway IP Address",
        "description" : "The list of IP address that are trusted to send MSISDN authentication
requests.<br><br>The client IP address of the authentication request is checked against this list, if
the client IP is not listed then the authentication module will fail.<br><br><i>NB </i>If the list
is empty then all hosts will be trusted.",
        "propertyOrder" : 100,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "returnUserDN" : {
        "title" : "Return User DN to DataStore",
        "description" : "Controls whether the DN or the username is returned as the authentication
principal.",
        "propertyOrder" : 1100,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"type" : "object",
"title" : "Realm Defaults"
}
}

```

```
}
```

1.95. MultiFederationProtocol

1.95.1. Global Operations

Resource path: `/global-config/services/federation/multi`

Resource version: `1.0`

1.95.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action MultiFederationProtocol --global --actionName getAllTypes
```

1.95.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action MultiFederationProtocol --global --actionName getCreatableTypes
```

1.95.1.3. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action MultiFederationProtocol --global --actionName nextdescendants
```

1.95.1.4. read

Usage:

```
am> read MultiFederationProtocol --global
```

1.95.1.5. update

Usage:

```
am> update MultiFederationProtocol --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "singleLogoutHandlerList" : {
      "title" : "Single Logout Handler List",
      "description" : "List of Logout handlers for each supported federation protocol<br><br>The multi-federation protocol engine supports Single Logout. Each federation protocol requires a different single logout handler. Logout handler must implement the <code>com.sun.identity.multiprotocol.SingleLogoutHandler</code> interface.",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.96. Naming

1.96.1. Global Operations

Resource path: [/global-config/services/naming](#)

Resource version: [1.0](#)

1.96.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Naming --global --actionName getAllTypes
```

1.96.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Naming --global --actionName getCreatableTypes
```


1.96.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Naming --global --actionName nextdescendents
```

1.96.1.4. read

Usage:

```
am> read Naming --global
```

1.96.1.5. update

Usage:

```
am> update Naming --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "generalConfig" : {
      "type" : "object",
      "title" : "General Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "sessionUrl" : {
          "title" : "Session Service URL",
          "description" : "Specifies the endpoint used by the session service.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authUrl" : {
          "title" : "Authentication Service URL",
          "description" : "Specifies the endpoint used by the authentication service.",
          "propertyOrder" : 500,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "profileUrl" : {
          "title" : "Profile Service URL",
          "description" : "Specifies the endpoint used by the profile service.<p><p>This attribute is deprecated.",

```

```
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "loggingUrl" : {
    "title" : "Logging Service URL",
    "description" : "Specifies the endpoint used by the logging service.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "policyUrl" : {
    "title" : "Policy Service URL",
    "description" : "Specifies the endpoint used by the policy service.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"endpointConfig" : {
  "type" : "object",
  "title" : "Endpoint Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "federationAssertionManagerUrl" : {
      "title" : "Federation Assertion Manager Service URL",
      "description" : "Specifies the ID-FF assertion manager endpoint.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "securityTokenManagerUrl" : {
      "title" : "Security Token Manager URL",
      "description" : "Specifies the security token manager endpoint.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "stsMexUrl" : {
      "title" : "Security Token Service MEX Endpoint URL",
      "description" : "Specifies the STS MEX endpoint.",
      "propertyOrder" : 1600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "jaxwsUrl" : {
      "title" : "Identity Web Services Endpoint URL",
      "description" : "Specifies the endpoint for the Identity WSDL services.",
      "propertyOrder" : 1300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```
},
"stsUrl" : {
  "title" : "Security Token Service Endpoint URL",
  "description" : "Specifies the STS endpoint.",
  "propertyOrder" : 1500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"idsvcsRestUrl" : {
  "title" : "Identity REST Services Endpoint URL",
  "description" : "Specifies the endpoint for the Identity REST services.",
  "propertyOrder" : 1400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"federationConfig" : {
  "type" : "object",
  "title" : "Federation Configuration",
  "propertyOrder" : 1,
  "properties" : {
    "jaxrpcUrl" : {
      "title" : "JAXRPC Endpoint URL",
      "description" : "Specifies the JAXRPC endpoint URL used by the remote IDM/SMS APIs.",
      "propertyOrder" : 1200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "samlAssertionManagerUrl" : {
      "title" : "SAML Assertion Manager Service URL",
      "description" : "Specifies the SAML v1 assertion service endpoint.",
      "propertyOrder" : 900,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "samlPostServletUrl" : {
      "title" : "SAML Web Profile/POST Service URL",
      "description" : "Specifies the SAML v1 Web Profile endpoint.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "samlAwareServletUrl" : {
      "title" : "SAML Web Profile/Artifact Service URL",
      "description" : "Specifies the SAML v1 endpoint.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "samlSoapReceiverUrl" : {
      "title" : "SAML SOAP Service URL",
      "description" : "Specifies the SAML v1 SOAP service endpoint.",

```

```
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
```

1.97. OAuth20

1.97.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/SocialNode`

Resource version: `1.0`

1.97.1.1. create

Usage:

```
am> create OAuth20 --realm Realm --id id --body body
```

Parameters:

`--id`

The unique identifier for the resource.

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "cfgAttributeMappingClasses" : {
      "title" : "Attribute Mapper",
      "description" : "Name of the class that implements the attribute
mapping This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided. A custom attribute mapper must implement the
org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper interface. Provided
implementations are: org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper
org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the
openid scope)",
      "propertyOrder" : 1400,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
    }
  }
}
```

```
    "exampleValue" : ""
  },
  "scopeDelimiter" : {
    "title" : "Scope Delimiter",
    "description" : "Delimiter used to separate scope values. Default value is space.",
    "propertyOrder" : 700,
    "type" : "string",
    "exampleValue" : ""
  },
  "issuer" : {
    "title" : "Token Issuer",
    "description" : "Required when the 'openid' scope is included. Value must match the iss field in issued ID Token e.g. accounts.google.com The issuer value MUST be provided when OAuth 2.0 Mix-Up Mitigation is enabled.",
    "propertyOrder" : 1900,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter <p>For more information on the OAuth client_id parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
    "propertyOrder" : 200,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "clientId" : {
    "title" : "Client ID",
    "description" : "OAuth client_id parameter<p> For more information on the OAuth client_id parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
    "propertyOrder" : 100,
    "type" : "string",
    "exampleValue" : ""
  },
  "cfgAccountProviderClass" : {
    "title" : "Account Provider",
    "description" : "Name of the class implementing the account provider. This class is used by the module to find the account from the attributes mapped by the Account Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface. String constructor parameters can be provided by appending | separated values.",
    "propertyOrder" : 1200,
    "type" : "string",
    "exampleValue" : ""
  },
  "scopeString" : {
    "title" : "OAuth Scope",
    "description" : "List of user profile properties<p>According to the OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the client application requires. The list depends on the permissions that the resource owner grants to the client application. Some authorization servers use non-standard separators for scopes.",
    "propertyOrder" : 600,
    "type" : "string",
    "exampleValue" : ""
  },
  "basicAuth" : {
    "title" : "Use Basic Auth",
    "description" : "When enabled, the client will use basic auth for authenticating with the social auth provider. Enabled by default.",
```

```

    "propertyOrder" : 1100,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saveUserAttributesToSession" : {
    "title" : "Save Attributes in the Session",
    "description" : "If this option is enabled, the attributes configured in the attribute mapper
will be saved into the OpenAM session",
    "propertyOrder" : 1700,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cfgMixUpMitigation" : {
    "title" : "OAuth 2.0 Mix-Up Mitigation Enabled",
    "description" : "Enables OAuth 2.0 mix-up mitigation The authorization server must support
the OAuth 2.0 Mix-Up Mitigation draft (https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
mitigation-01#section-3.1), otherwise OpenAM will fail to validate responses from the authorization
server. If only the OAuth 2.0 protocol is utilized, make sure that the accepted issuer value is set
in the \"Token Issuer\" setting.",
    "propertyOrder" : 1800,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL <p> This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider NB This URL should return JSON objects in
response",
    "propertyOrder" : 500,
    "type" : "string",
    "exampleValue" : ""
  },
  "cfgAttributeMappingConfiguration" : {
    "title" : "Attribute Mapper Configuration",
    "description" : "Mapping of OAuth attributes to local OpenAM attributes Attribute configuration
that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data
store in the OpenAM. Example: OAuth2.0_attribute=local_attribute",
    "propertyOrder" : 1600,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "cfgAccountMapperConfiguration" : {
    "title" : "Account Mapper Configuration",
    "description" : "Mapping of OAuth account to local OpenAM account Attribute configuration that
will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data
store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
    "propertyOrder" : 1500,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  }

```

```

},
"tokenEndpoint" : {
  "title" : "Access Token Endpoint URL",
  "description" : "OAuth access token endpoint URL This is the URL endpoint for access token
retrieval provided by the OAuth Identity Provider.Refer to the RFC 6749 (http://tools.ietf.org/html/
rfc6749#section-3.2), section 3.2",
  "propertyOrder" : 400,
  "type" : "string",
  "exampleValue" : ""
},
},
"provider" : {
  "title" : "Social Provider",
  "description" : "Social Provider for which this module is being setup.",
  "propertyOrder" : 900,
  "type" : "string",
  "exampleValue" : ""
},
},
"redirectURI" : {
  "title" : "Redirect URL",
  "description" : "",
  "propertyOrder" : 800,
  "type" : "string",
  "exampleValue" : ""
},
},
"authenticationIdKey" : {
  "title" : "Auth ID Key",
  "description" : "",
  "propertyOrder" : 1000,
  "type" : "string",
  "exampleValue" : ""
},
},
"authorizeEndpoint" : {
  "title" : "Authentication Endpoint URL",
  "description" : "OAuth authentication endpoint URL <p> This is the URL endpoint for OAuth
authentication provided by the OAuth Identity Provider",
  "propertyOrder" : 300,
  "type" : "string",
  "exampleValue" : ""
},
},
"cfgAccountMapperClass" : {
  "title" : "Account Mapper",
  "description" : "Name of the class implementing the attribute mapping for the
account search. This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM. The class must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.
Provided implementations are:
<code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper
org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</code>(can only be used when
using the openid scope) String constructor parameters can be provided by appending | separated
values.",
  "propertyOrder" : 1300,
  "type" : "string",
  "exampleValue" : ""
}
},
},
"required" : [ "cfgAttributeMappingConfiguration", "scopeDelimiter", "clientId", "provider",
"clientSecret", "cfgAccountMapperClass", "issuer", "authorizeEndpoint", "cfgMixUpMitigation",
"cfgAccountProviderClass", "saveUserAttributesToSession", "authenticationIdKey",

```

```
"basicAuth", "redirectURI", "scopeString", "cfgAttributeMappingClasses", "tokenEndpoint",  
"cfgAccountMapperConfiguration", "userInfoEndpoint" ]  
}
```

1.97.1.2. delete

Usage:

```
am> delete OAuth20 --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.97.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OAuth20 --realm Realm --actionName getAllTypes
```

1.97.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OAuth20 --realm Realm --actionName getCreatableTypes
```

1.97.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action OAuth20 --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "type" : "object",  
  "title" : "Some configuration of the node. This does not need to be complete against the  
  configuration schema."  
}
```


1.97.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OAuth20 --realm Realm --actionName nextdescendents
```

1.97.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query OAuth20 --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.97.1.8. read

Usage:

```
am> read OAuth20 --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.97.1.9. update

Usage:

```
am> update OAuth20 --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "cfgAttributeMappingClasses" : {
      "title" : "Attribute Mapper",
      "description" : "Name of the class that implements the attribute mapping This class maps the OAuth properties into OpenAM properties. A custom attribute mapper can be provided. A custom attribute mapper must implement the org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper interface. Provided implementations are: org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the openid scope)",
      "propertyOrder" : 1400,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "scopeDelimiter" : {
      "title" : "Scope Delimiter",
      "description" : "Delimiter used to separate scope values. Default value is space.",
      "propertyOrder" : 700,
      "type" : "string",
      "exampleValue" : ""
    },
    "issuer" : {
      "title" : "Token Issuer",
      "description" : "Required when the 'openid' scope is included. Value must match the iss field in issued ID Token e.g. accounts.google.com The issuer value MUST be provided when OAuth 2.0 Mix-Up Mitigation is enabled.",
      "propertyOrder" : 1900,
      "type" : "string",
      "exampleValue" : ""
    },
    "clientSecret" : {
      "title" : "Client Secret",
      "description" : "OAuth client_secret parameter <p>For more information on the OAuth client_id parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
      "propertyOrder" : 200,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "clientId" : {
      "title" : "Client ID",
      "description" : "OAuth client_id parameter<p> For more information on the OAuth client_id parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    },
    "cfgAccountProviderClass" : {
      "title" : "Account Provider",
```

```

    "description" : "Name of the class implementing the account provider. This class is
used by the module to find the account from the attributes mapped by the Account Mapper
<code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.
String constructor parameters can be provided by appending | separated values.",
    "propertyOrder" : 1200,
    "type" : "string",
    "exampleValue" : ""
  },
  "scopeString" : {
    "title" : "OAuth Scope",
    "description" : "List of user profile properties<p>According to the OAuth 2.0 Authorization
Framework, scope is a space-separated list of user profile attributes that the client application
requires. The list depends on the permissions that the resource owner grants to the client
application. Some authorization servers use non-standard separators for scopes.",
    "propertyOrder" : 600,
    "type" : "string",
    "exampleValue" : ""
  },
  "basicAuth" : {
    "title" : "Use Basic Auth",
    "description" : "When enabled, the client will use basic auth for authenticating with the social
auth provider. Enabled by default.",
    "propertyOrder" : 1100,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saveUserAttributesToSession" : {
    "title" : "Save Attributes in the Session",
    "description" : "If this option is enabled, the attributes configured in the attribute mapper
will be saved into the OpenAM session",
    "propertyOrder" : 1700,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cfgMixUpMitigation" : {
    "title" : "OAuth 2.0 Mix-Up Mitigation Enabled",
    "description" : "Enables OAuth 2.0 mix-up mitigation The authorization server must support
the OAuth 2.0 Mix-Up Mitigation draft (https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
mitigation-01#section-3.1), otherwise OpenAM will fail to validate responses from the authorization
server. If only the OAuth 2.0 protocol is utilized, make sure that the accepted issuer value is set
in the \"Token Issuer\" setting.",
    "propertyOrder" : 1800,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL <p> This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider NB This URL should return JSON objects in
response",
    "propertyOrder" : 500,
    "type" : "string",
    "exampleValue" : ""
  },
  "cfgAttributeMappingConfiguration" : {
    "title" : "Attribute Mapper Configuration",
    "description" : "Mapping of OAuth attributes to local OpenAM attributes Attribute configuration
that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data
store in the OpenAM. Example: OAuth2.0_attribute=local_attribute",

```

```

        "propertyOrder" : 1600,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "cfgAccountMapperConfiguration" : {
        "title" : "Account Mapper Configuration",
        "description" : "Mapping of OAuth account to local OpenAM account Attribute configuration that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
        "propertyOrder" : 1500,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "tokenEndpoint" : {
        "title" : "Access Token Endpoint URL",
        "description" : "OAuth access token endpoint URL This is the URL endpoint for access token retrieval provided by the OAuth Identity Provider. Refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-3.2), section 3.2",
        "propertyOrder" : 400,
        "type" : "string",
        "exampleValue" : ""
    },
    "provider" : {
        "title" : "Social Provider",
        "description" : "Social Provider for which this module is being setup.",
        "propertyOrder" : 900,
        "type" : "string",
        "exampleValue" : ""
    },
    "redirectURI" : {
        "title" : "Redirect URL",
        "description" : "",
        "propertyOrder" : 800,
        "type" : "string",
        "exampleValue" : ""
    },
    "authenticationIdKey" : {
        "title" : "Auth ID Key",
        "description" : "",
        "propertyOrder" : 1000,
        "type" : "string",
        "exampleValue" : ""
    },
    "authorizeEndpoint" : {
        "title" : "Authentication Endpoint URL",
        "description" : "OAuth authentication endpoint URL <p> This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
        "propertyOrder" : 300,
        "type" : "string",
    }

```

```
    "exampleValue" : ""
  },
  "cfgAccountMapperClass" : {
    "title" : "Account Mapper",
    "description" : "Name of the class implementing the attribute mapping for the
account search. This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM. The class must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.
Provided implementations are:
<code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper
org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</code>(can only be used when
using the openid scope) String constructor parameters can be provided by appending | separated
values.",
    "propertyOrder" : 1300,
    "type" : "string",
    "exampleValue" : ""
  }
},
"required" : [ "cfgAttributeMappingConfiguration", "scopeDelimiter", "clientId", "provider",
"clientSecret", "cfgAccountMapperClass", "issuer", "authorizeEndpoint", "cfgMixUpMitigation",
"cfgAccountProviderClass", "saveUserAttributesToSession", "authenticationIdKey",
"basicAuth", "redirectURI", "scopeString", "cfgAttributeMappingClasses", "tokenEndpoint",
"cfgAccountMapperConfiguration", "userInfoEndpoint" ]
}
```

1.98. OAuth2ClientAgentGroups

1.98.1. Realm Operations

Agent Groups handler that is responsible for managing agent groups

Resource path: `/realm-config/agents/groups/OAuth2Client`

Resource version: `1.0`

1.98.1.1. create

Usage:

```
am> create OAuth2ClientAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
```

```

"type" : "object",
"properties" : {
  "signEnc0Auth2ClientConfig" : {
    "type" : "object",
    "title" : "Signing and Encryption",
    "propertyOrder" : 3,
    "properties" : {
      "requestParameterEncryptedEncryptionAlgorithm" : {
        "title" : "Request parameter encryption method",
        "description" : "JWE enc algorithm for encrypting the request parameter.<br><br>AM supports
the following token encryption algorithms:<ul><li><code>A128GCM</code>, <code>A192GCM</code>,
and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated encryption mode.</
li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES
encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
        "propertyOrder" : 27700,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "publicKeyLocation" : {
        "title" : "Public key selector",
        "description" : "Select the public key for this client to come from either the jwks_uri,
manual jwks or X509 field.",
        "propertyOrder" : 25700,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "userinfoEncryptedResponseAlg" : {
        "title" : "User info encrypted response algorithm",
        "description" : "JWE algorithm for encrypting UserInfo Responses. If both signing and
encryption are requested, the response will be signed then encrypted, with the result being a Nested
JWT. The default, if omitted, is that no encryption is performed.",
        "propertyOrder" : 27300,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
      },
      "idTokenEncryptionEnabled" : {
        "title" : "Enable ID Token Encryption",
        "description" : "Select to enable ID token encryption.",
        "propertyOrder" : 24600,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "idTokenEncryptionMethod" : {
        "title" : "ID Token Encryption Method",
        "description" : "Encryption method the ID Token for this client must be encrypted with.",
        "propertyOrder" : 24800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "idTokenPublicEncryptionKey" : {
        "title" : "Client ID Token Public Encryption Key",
        "description" : "A Base64 encoded public key for encrypting ID Tokens.",
        "propertyOrder" : 24900,
        "required" : false,
    
```

```

        "type" : "string",
        "exampleValue" : ""
    },
    "requestParameterSignedAlg" : {
        "title" : "Request parameter signing algorithm",
        "description" : "JWS algorithm for signing the request parameter.",
        "propertyOrder" : 27500,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "jwksCacheTimeout" : {
        "title" : "JWKS URI content cache timeout in ms",
        "description" : "To avoid loading the JWKS URI content for every token encryption, the JWKS content is cached. This timeout defines the maximum of time the JWKS URI content can be cached before being refreshed.",
        "propertyOrder" : 24110,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "idTokenSignedResponseAlg" : {
        "title" : "ID Token Signing Algorithm",
        "description" : "Algorithm the ID Token for this client must be signed with.",
        "propertyOrder" : 24500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "clientJwtPublicKey" : {
        "title" : "Client JWT Bearer Public Key",
        "description" : "A Base64 encoded X509 certificate, containing the public key, represented as a UTF-8 PEM file, of the key pair for signing the Client Bearer JWT.",
        "propertyOrder" : 25400,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "tokenEndpointAuthSigningAlgorithm" : {
        "title" : "Token Endpoint Authentication Signing Algorithm",
        "description" : "The JWS algorithm that MUST be used for signing the JWT used to authenticate the Client at the Token Endpoint for the private_key_jwt and client_secret_jwt authentication methods. All Token Requests using these authentication methods from this Client MUST be rejected, if the JWT is not signed with this algorithm.",
        "propertyOrder" : 24130,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "userinfoEncryptedResponseEncryptionAlgorithm" : {
        "title" : "User info encrypted response encryption algorithm",
        "description" : "JWE enc algorithm for encrypting UserInfo Responses. If userinfo encrypted response algorithm is specified, the default for this value is A128CBC-HS256. When user info encrypted response encryption is included, user info encrypted response algorithm MUST also be provided.<br><br>AM supports the following token encryption algorithms:<ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
        "propertyOrder" : 27400,
    }

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "requestParameterEncryptedAlg" : {
    "title" : "Request parameter encryption algorithm",
    "description" : "JWE algorithm for encrypting the request parameter.",
    "propertyOrder" : 27600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "jwkStoreCacheMissCacheTime" : {
    "title" : "JWKS URI content cache miss cache time",
    "description" : "To avoid loading the JWKS URI content for every token signature verification, especially when the kid is not in the jwks content already cached, the JWKS content will be cache for a minimum period of time. This cache miss cache time defines the minimum of time the JWKS URI content is cache.",
    "propertyOrder" : 24120,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "jwksUri" : {
    "title" : "Json Web Key URI",
    "description" : "The uri that contains the client's public keys in Json Web Key format.",
    "propertyOrder" : 24100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userinfoResponseFormat" : {
    "title" : "User info response format.",
    "description" : "The user info endpoint offers different output format. See http://openid.net/specs/openid-connect-core-1_0.html#UserInfoResponse",
    "propertyOrder" : 27100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userinfoSignedResponseAlg" : {
    "title" : "User info signed response algorithm",
    "description" : "JWS algorithm for signing UserInfo Responses. If this is specified, the response will be JWT <a href=\"https://tools.ietf.org/html/rfc7519\">JWT</a> serialized, and signed using JWS. The default, if omitted, is for the UserInfo Response to return the Claims as a UTF-8 encoded JSON object using the application/json content-type.",
    "propertyOrder" : 27200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "idTokenEncryptionAlgorithm" : {
    "title" : "ID Token Encryption Algorithm",
    "description" : "Algorithm the ID Token for this client must be encrypted with.",
    "propertyOrder" : 24700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
},

```



```

"jwkSet" : {
  "title" : "Json Web Key",
  "description" : "Raw JSON Web Key value containing the client's public keys.",
  "propertyOrder" : 24200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
},
"coreOpenIDClientConfig" : {
  "type" : "object",
  "title" : "OpenID Connect",
  "propertyOrder" : 2,
  "properties" : {
    "defaultAcrValues" : {
      "title" : "Default ACR values",
      "description" : "Default requested Authentication Context Class Reference
values.<br><br>Array of strings that specifies the default acr values that the OP is being requested
to use for processing requests from this Client, with the values appearing in order of preference.
The Authentication Context Class satisfied by the authentication performed is returned as the
acr Claim Value in the issued ID Token. The acr Claim is requested as a Voluntary Claim by this
parameter. The acr_values_supported discovery element contains a list of the acr values supported by
this server. Values specified in the acr_values request parameter or an individual acr Claim request
override these default values.",
      "propertyOrder" : 25650,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "postLogoutRedirectUri" : {
      "title" : "Post Logout Redirect URIs",
      "description" : "URIs that can be redirected to after the client logout process.",
      "propertyOrder" : 25000,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "defaultMaxAgeEnabled" : {
      "title" : "Default Max Age Enabled",
      "description" : "Whether or not the default max age is enforced.",
      "propertyOrder" : 25600,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "clientSessionUri" : {
      "title" : "Client Session URI",
      "description" : "This is the URI that will be used to check messages sent to the session
management endpoints. This URI must match the origin of the message",
      "propertyOrder" : 25200,
      "required" : false,
      "type" : "string",

```

```

    "exampleValue" : ""
  },
  "jwtTokenLifetime" : {
    "title" : "OpenID Connect JWT Token Lifetime (seconds)",
    "description" : "The time in seconds a JWT is valid for. <i>NB</i> If this field is set to
zero, JWT Token Lifetime of the OAuth2 Provider is used instead of.",
    "propertyOrder" : 26100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "defaultMaxAge" : {
    "title" : "Default Max Age",
    "description" : "Minimum value 1. Sets the maximum length of time in seconds a session
may be active after the authorization service has succeeded before the user must actively re-
authenticate.",
    "propertyOrder" : 25500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "claims" : {
    "title" : "Claim(s)",
    "description" : "List of claim name translations, which will override those specified for
the AS. Claims are values that are presented to the user to inform them what data is being made
available to the Client.<br><br>Claims may be entered as simple strings or pipe separated strings
representing the internal claim name, locale, and localized description; e.g. \"name|en|Your full
name\". Locale strings are in the format <code>language + \"_\" + country + \"_\" + variant</code>,
e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description is displayed to all
users having undefined locales. e.g. \"name|Your full name\". <i>NB</i> If the description is also
omitted, nothing is displayed to all users, e.g. specifying \"name|\" would allow the claim \"name\"
to be used by the client, but would not display it to the user when it was requested.<p>If a value is
not given here, the value will be computed from the OAuth 2 Provider settings.</p>",
    "propertyOrder" : 23400,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"advancedOAuth2ClientConfig" : {
  "type" : "object",
  "title" : "Advanced",
  "propertyOrder" : 1,
  "properties" : {
    "isConsentImplied" : {
      "title" : "Implied consent",
      "description" : "When enabled, the resource owner will not be asked for consent during
authorization flows. The OAuth2 Provider must be configured to allow clients to skip consent.",
      "propertyOrder" : 26200,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "contacts" : {
      "title" : "Contacts",

```

```

    "description" : "Email addresses of users who can administrate this client.",
    "propertyOrder" : 23900,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sectorIdentifierUri" : {
    "title" : "Sector Identifier URI",
    "description" : "The Host component of this URL is used in the computation of pairwise
Subject Identifiers.",
    "propertyOrder" : 24300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "name" : {
    "title" : "Display name",
    "description" : "A client name that may be relevant to the resource owner when considering
approval.<br><br>The name may be entered as a single string or as pipe separated strings for
locale and localized name; e.g. \n\nThe ExampleCo Intranet\n". Locale strings are in the format
<code>language + \"_\" + country + \"_\" + variant</code>, e.g. en, en_GB, en_US_WIN. If the locale
is omitted, the name is displayed to all users having undefined locales. e.g. \n\nThe ExampleCo
Intranet\n".",
    "propertyOrder" : 23500,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "updateAccessToken" : {
    "title" : "Access Token",
    "description" : "The access token used to update the client.",
    "propertyOrder" : 25100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "subjectType" : {
    "title" : "Subject Type",
    "description" : "The subject type added to responses for this client.",
    "propertyOrder" : 24400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenEndpointAuthMethod" : {
    "title" : "Token Endpoint Authentication Method",
    "description" : "The authentication method with which a client authenticates to the
authorization server at the token endpoint. The authentication method applies to OIDC requests with
the openid scope.",
    "propertyOrder" : 24000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}

```

```
},
  "descriptions" : {
    "title" : "Display description",
    "description" : "A description of the client or other information that may be relevant
to the resource owner when considering approval.<br><br>The description may be entered as a single
string or as pipe separated strings for locale and localized name; e.g. \"en|The company intranet
is requesting the following access permission\". Locale strings are in the format <code>language
+ \"_\" + country + \"_\" + variant</code>, e.g. en_GB, en_US_WIN. If the locale is omitted,
the description is displayed to all users having undefined locales. e.g. \"The company intranet is
requesting the following access permission\".",
    "propertyOrder" : 23600,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "mixUpMitigation" : {
    "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
    "description" : "Enables OAuth 2.0 mix-up mitigation on the authorization server
side.<br><br>Enable this setting only if this OAuth 2.0 client supports the <a href=\"https://
tools.ietf.org/html/draft-ietf-oauth-mix-up-mitigation-01\">OAuth 2.0 Mix-Up Mitigation draft</a>,
otherwise AM will fail to validate access token requests received from this client.",
    "propertyOrder" : 26300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "responseTypes" : {
    "title" : "Response Types",
    "description" : "Response types this client will support and use.",
    "propertyOrder" : 23800,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "requestUris" : {
    "title" : "Request uris",
    "description" : "Array of request_uri values that are pre-registered by the RP for use at
the OP.<br><br>The entire Request URI MUST NOT exceed 512 ASCII characters. Otherwise the value will
be ignored.",
    "propertyOrder" : 23700,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"coreOAuth2ClientConfig" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
}
```

```

"properties" : {
  "redirectionUris" : {
    "title" : "Redirection URIs",
    "description" : "Redirection URIs (optional for confidential clients). Complete URIs or URIs
consisting of protocol + authority + path are registered so that the OAuth 2.0 provider can trust
that tokens are sent to trusted entities. If multiple URI's are registered, the client MUST specify
the URI that the user should be redirected to following approval. May not contain a fragment (#).",
    "propertyOrder" : 23200,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "status" : {
    "title" : "Status",
    "description" : "Status of the agent configuration.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "accessTokenLifetime" : {
    "title" : "Access Token Lifetime (seconds)",
    "description" : "The time in seconds an access token is valid for. <i>NB</i> If this field
is set to zero, Access Token Lifetime of the OAuth2 Provider is used instead of.",
    "propertyOrder" : 26000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "defaultScopes" : {
    "title" : "Default Scope(s)",
    "description" : "Default Scope(s). Scopes automatically given to tokens.<br><br>Default
Scopes may be entered as simple strings or pipe separated strings representing the internal scope
name, locale, and localized description; e.g. \"read|en|Permission to view email messages in your
account\". Locale strings are in the format <code>language + \"_\" + country + \"_\" + variant</
code>, e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description is displayed to
all users having undefined locales. e.g. \"read|Permission to view email messages in your account
\". <i>NB</i> If the description is also omitted, nothing is displayed to all users, e.g. specifying
\"read|\" would allow the scope \"read\" to be used by the client, but would not display it to the
user when it was requested.",
    "propertyOrder" : 23700,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "clientType" : {
    "title" : "Client type",
    "description" : "Type of OAuth 2.0 client. Confidential clients can keep their password
secret, and are typically web apps or other server-based clients. Public clients run the risk
of exposing their password to a host or user agent, such as rich browser applications or desktop
clients.",
    "propertyOrder" : 23100,
    "required" : true,

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "authorizationCodeLifetime" : {
    "title" : "Authorization Code Lifetime (seconds)",
    "description" : "The time in seconds an authorization code is valid for. <i>NB</i> If this
field is set to zero, Authorization Code Lifetime of the OAuth2 Provider is used instead of.",
    "propertyOrder" : 25800,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "refreshTokenLifetime" : {
    "title" : "Refresh Token Lifetime (seconds)",
    "description" : "The time in seconds a refresh token is valid for. <i>NB</i> If this field
is set to zero, Refresh Token Lifetime of the OAuth2 Provider is used instead. If this field is set
to -1, the token will never expire.",
    "propertyOrder" : 25900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "scopes" : {
    "title" : "Scope(s)",
    "description" : "Scope(s). Scopes are strings that are presented to the user for approval
and included in tokens so that the protected resource may make decisions about what to give access
to.<br><br>Scopes may be entered as simple strings or pipe separated strings representing the
internal scope name, locale, and localized description; e.g. \"read|en|Permission to view email
messages in your account\". Locale strings are in the format <code>language + \"_\" + country + \"_\"
+ variant</code>, e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description
is displayed to all users having undefined locales. e.g. \"read|Permission to view email messages in
your account\". <i>NB</i> If the description is also omitted, nothing is displayed to all users, e.g.
specifying \"read|\" would allow the scope \"read|\" to be used by the client, but would not display
it to the user when it was requested.",
    "propertyOrder" : 23300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "clientName" : {
    "title" : "Client Name",
    "description" : "This value is a readable name for this client.",
    "propertyOrder" : 25300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"coreUmaClientConfig" : {
  "type" : "object",
  "title" : "UMA",
  "propertyOrder" : 4,

```

```
    "properties" : {
      "claimsRedirectionUri" : {
        "title" : "Claims Redirection URIs",
        "description" : "Redirection URIs for returning to the client from UMA claims collection
(not yet supported). If multiple URIs are registered, the client MUST specify the URI that the user
should be redirected to following approval. May not contain a fragment (#).",
        "propertyOrder" : 23200,
        "required" : false,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      }
    }
  }
}
```

1.98.1.2. delete

Usage:

```
am> delete OAuth2ClientAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.98.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OAuth2ClientAgentGroups --realm Realm --actionName getAllTypes
```

1.98.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OAuth2ClientAgentGroups --realm Realm --actionName getCreatableTypes
```

1.98.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OAuth2ClientAgentGroups --realm Realm --actionName nextdescendents
```

1.98.1.6. query

Querying the agent groups of a specific type

Usage:

```
am> query OAuth2ClientAgentGroups --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.98.1.7. read

Usage:

```
am> read OAuth2ClientAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.98.1.8. update

Usage:

```
am> update OAuth2ClientAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "signEncOAuth2ClientConfig" : {
      "type" : "object",
      "title" : "Signing and Encryption",
      "propertyOrder" : 3,
      "properties" : {
```



```

"requestParameterEncryptedEncryptionAlgorithm" : {
  "title" : "Request parameter encryption method",
  "description" : "JWE enc algorithm for encrypting the request parameter.<br><br>AM supports
the following token encryption algorithms:<ul><li><code>A128GCM</code>, <code>A192GCM</code>,
and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated encryption mode.</
li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES
encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 27700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"publicKeyLocation" : {
  "title" : "Public key selector",
  "description" : "Select the public key for this client to come from either the jwks_uri,
manual jwks or X509 field.",
  "propertyOrder" : 25700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"userinfoEncryptedResponseAlg" : {
  "title" : "User info encrypted response algorithm",
  "description" : "JWE algorithm for encrypting UserInfo Responses. If both signing and
encryption are requested, the response will be signed then encrypted, with the result being a Nested
JWT. The default, if omitted, is that no encryption is performed.",
  "propertyOrder" : 27300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"idTokenEncryptionEnabled" : {
  "title" : "Enable ID Token Encryption",
  "description" : "Select to enable ID token encryption.",
  "propertyOrder" : 24600,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"idTokenEncryptionMethod" : {
  "title" : "ID Token Encryption Method",
  "description" : "Encryption method the ID Token for this client must be encrypted with.",
  "propertyOrder" : 24800,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"idTokenPublicEncryptionKey" : {
  "title" : "Client ID Token Public Encryption Key",
  "description" : "A Base64 encoded public key for encrypting ID Tokens.",
  "propertyOrder" : 24900,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"requestParameterSignedAlg" : {
  "title" : "Request parameter signing algorithm",
  "description" : "JWS algorithm for signing the request parameter.",
  "propertyOrder" : 27500,

```

```

    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "jwksCacheTimeout" : {
    "title" : "JWKS URI content cache timeout in ms",
    "description" : "To avoid loading the JWKS URI content for every token encryption, the JWKS
content is cached. This timeout defines the maximum of time the JWKS URI content can be cached before
being refreshed.",
    "propertyOrder" : 24110,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "idTokenSignedResponseAlg" : {
    "title" : "ID Token Signing Algorithm",
    "description" : "Algorithm the ID Token for this client must be signed with.",
    "propertyOrder" : 24500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientJwtPublicKey" : {
    "title" : "Client JWT Bearer Public Key",
    "description" : "A Base64 encoded X509 certificate, containing the public key, represented
as a UTF-8 PEM file, of the key pair for signing the Client Bearer JWT.",
    "propertyOrder" : 25400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenEndpointAuthSigningAlgorithm" : {
    "title" : "Token Endpoint Authentication Signing Algorithm",
    "description" : "The JWS algorithm that MUST be used for signing the JWT used to
authenticate the Client at the Token Endpoint for the private_key_jwt and client_secret_jwt
authentication methods. All Token Requests using these authentication methods from this Client MUST
be rejected, if the JWT is not signed with this algorithm.",
    "propertyOrder" : 24130,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userinfoEncryptedResponseEncryptionAlgorithm" : {
    "title" : "User info encrypted response encryption algorithm",
    "description" : "JWE enc algorithm for encrypting UserInfo Responses. If userinfo encrypted
response algorithm is specified, the default for this value is A128CBC-HS256. When user info
encrypted response encryption is included, user info encrypted response algorithm MUST also be
provided.<br><br>AM supports the following token encryption algorithms:<ul><li><code>A128GCM</code>,
<code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated
encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-
HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
    "propertyOrder" : 27400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "requestParameterEncryptedAlg" : {
    "title" : "Request parameter encryption algorithm",
    "description" : "JWE algorithm for encrypting the request parameter.",

```

```
"propertyOrder" : 27600,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"jwkStoreCacheMissCacheTime" : {
  "title" : "JWKS URI content cache miss cache time",
  "description" : "To avoid loading the JWKS URI content for every token signature
verification, especially when the kid is not in the jwks content already cached, the JWKS content
will be cache for a minimum period of time. This cache miss cache time defines the minimum of time
the JWKS URI content is cache.",
  "propertyOrder" : 24120,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"jwksUri" : {
  "title" : "Json Web Key URI",
  "description" : "The uri that contains the client's public keys in Json Web Key format.",
  "propertyOrder" : 24100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"userinfoResponseFormat" : {
  "title" : "User info response format.",
  "description" : "The user info endpoint offers different output format. See http://
openid.net/specs/openid-connect-core-1_0.html#UserInfoResponse",
  "propertyOrder" : 27100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"userinfoSignedResponseAlg" : {
  "title" : "User info signed response algorithm",
  "description" : "JWS algorithm for signing UserInfo Responses. If this is specified, the
response will be JWT <a href=\"https://tools.ietf.org/html/rfc7519\">JWT</a> serialized, and signed
using JWS. The default, if omitted, is for the UserInfo Response to return the Claims as a UTF-8
encoded JSON object using the application/json content-type.",
  "propertyOrder" : 27200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"idTokenEncryptionAlgorithm" : {
  "title" : "ID Token Encryption Algorithm",
  "description" : "Algorithm the ID Token for this client must be encrypted with.",
  "propertyOrder" : 24700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"jwkSet" : {
  "title" : "Json Web Key",
  "description" : "Raw JSON Web Key value containing the client's public keys.",
  "propertyOrder" : 24200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
```

```

    }
  },
  "coreOpenIDClientConfig" : {
    "type" : "object",
    "title" : "OpenID Connect",
    "propertyOrder" : 2,
    "properties" : {
      "defaultAcrValues" : {
        "title" : "Default ACR values",
        "description" : "Default requested Authentication Context Class Reference
values.<br><br>Array of strings that specifies the default acr values that the OP is being requested
to use for processing requests from this Client, with the values appearing in order of preference.
The Authentication Context Class satisfied by the authentication performed is returned as the
acr Claim Value in the issued ID Token. The acr Claim is requested as a Voluntary Claim by this
parameter. The acr_values_supported discovery element contains a list of the acr values supported by
this server. Values specified in the acr_values request parameter or an individual acr Claim request
override these default values.",
        "propertyOrder" : 25650,
        "required" : false,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      },
      "postLogoutRedirectUri" : {
        "title" : "Post Logout Redirect URIs",
        "description" : "URIs that can be redirected to after the client logout process.",
        "propertyOrder" : 25000,
        "required" : false,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      },
      "defaultMaxAgeEnabled" : {
        "title" : "Default Max Age Enabled",
        "description" : "Whether or not the default max age is enforced.",
        "propertyOrder" : 25600,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "clientSessionUri" : {
        "title" : "Client Session URI",
        "description" : "This is the URI that will be used to check messages sent to the session
management endpoints. This URI must match the origin of the message",
        "propertyOrder" : 25200,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
      },
      "jwtTokenLifetime" : {
        "title" : "OpenID Connect JWT Token Lifetime (seconds)",
        "description" : "The time in seconds a JWT is valid for. <i>NB</i> If this field is set to
zero, JWT Token Lifetime of the OAuth2 Provider is used instead of.",
        "propertyOrder" : 26100,

```

```

    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "defaultMaxAge" : {
    "title" : "Default Max Age",
    "description" : "Minimum value 1. Sets the maximum length of time in seconds a session
may be active after the authorization service has succeeded before the user must actively re-
authenticate.",
    "propertyOrder" : 25500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "claims" : {
    "title" : "Claim(s)",
    "description" : "List of claim name translations, which will override those specified for
the AS. Claims are values that are presented to the user to inform them what data is being made
available to the Client.<br><br>Claims may be entered as simple strings or pipe separated strings
representing the internal claim name, locale, and localized description; e.g. \"name|en|Your full
name\". Locale strings are in the format <code>language + \"_\" + country + \"_\" + variant</code>,
e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description is displayed to all
users having undefined locales. e.g. \"name|Your full name\". <i>NB</i> If the description is also
omitted, nothing is displayed to all users, e.g. specifying \"name|\" would allow the claim \"name\"
to be used by the client, but would not display it to the user when it was requested.<p>If a value is
not given here, the value will be computed from the OAuth 2 Provider settings.</p>",
    "propertyOrder" : 23400,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"advancedOAuth2ClientConfig" : {
  "type" : "object",
  "title" : "Advanced",
  "propertyOrder" : 1,
  "properties" : {
    "isConsentImplied" : {
      "title" : "Implied consent",
      "description" : "When enabled, the resource owner will not be asked for consent during
authorization flows. The OAuth2 Provider must be configured to allow clients to skip consent.",
      "propertyOrder" : 26200,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "contacts" : {
      "title" : "Contacts",
      "description" : "Email addresses of users who can administrate this client.",
      "propertyOrder" : 23900,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",

```

```

    "exampleValue" : ""
  },
  "sectorIdentifierUri" : {
    "title" : "Sector Identifier URI",
    "description" : "The Host component of this URL is used in the computation of pairwise
Subject Identifiers.",
    "propertyOrder" : 24300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "name" : {
    "title" : "Display name",
    "description" : "A client name that may be relevant to the resource owner when considering
approval.<br><br>The name may be entered as a single string or as pipe separated strings for
locale and localized name; e.g. \n|The ExampleCo Intranet|. Locale strings are in the format
<code>language + \"_\" + country + \"_\" + variant</code>, e.g. en, en_GB, en_US_WIN. If the locale
is omitted, the name is displayed to all users having undefined locales. e.g. \n|The ExampleCo
Intranet|.\"",
    "propertyOrder" : 23500,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "updateAccessToken" : {
    "title" : "Access Token",
    "description" : "The access token used to update the client.",
    "propertyOrder" : 25100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "subjectType" : {
    "title" : "Subject Type",
    "description" : "The subject type added to responses for this client.",
    "propertyOrder" : 24400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenEndpointAuthMethod" : {
    "title" : "Token Endpoint Authentication Method",
    "description" : "The authentication method with which a client authenticates to the
authorization server at the token endpoint. The authentication method applies to OIDC requests with
the openid scope.",
    "propertyOrder" : 24000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "descriptions" : {
    "title" : "Display description",
    "description" : "A description of the client or other information that may be relevant
to the resource owner when considering approval.<br><br>The description may be entered as a single
string or as pipe separated strings for locale and localized name; e.g. \n|The company intranet
is requesting the following access permission|. Locale strings are in the format <code>language

```

```

+ \"_\" + country + \"_\" + variant</code>, e.g. en, en_GB, en_US_WIN. If the locale is omitted,
the description is displayed to all users having undefined locales. e.g. \"The company intranet is
requesting the following access permission\".",
  "propertyOrder" : 23600,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"mixUpMitigation" : {
  "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
  "description" : "Enables OAuth 2.0 mix-up mitigation on the authorization server
side.<br><br>Enable this setting only if this OAuth 2.0 client supports the <a href=\"https://
tools.ietf.org/html/draft-ietf-oauth-mix-up-mitigation-01\">OAuth 2.0 Mix-Up Mitigation draft</a>,
otherwise AM will fail to validate access token requests received from this client.",
  "propertyOrder" : 26300,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"responseTypes" : {
  "title" : "Response Types",
  "description" : "Response types this client will support and use.",
  "propertyOrder" : 23800,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"requestUris" : {
  "title" : "Request uris",
  "description" : "Array of request_uri values that are pre-registered by the RP for use at
the OP.<br><br>The entire Request URI MUST NOT exceed 512 ASCII characters. Otherwise the value will
be ignored.",
  "propertyOrder" : 23700,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
}
},
"coreOAuth2ClientConfig" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "redirectionUris" : {
      "title" : "Redirection URIs",
      "description" : "Redirection URIs (optional for confidential clients). Complete URIs or URIs
consisting of protocol + authority + path are registered so that the OAuth 2.0 provider can trust
that tokens are sent to trusted entities. If multiple URI's are registered, the client MUST specify
the URI that the user should be redirected to following approval. May not contain a fragment (#).",

```

```

"propertyOrder" : 23200,
"required" : false,
"items" : {
  "type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"status" : {
  "title" : "Status",
  "description" : "Status of the agent configuration.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"accessTokenLifetime" : {
  "title" : "Access Token Lifetime (seconds)",
  "description" : "The time in seconds an access token is valid for. <i>NB</i> If this field
is set to zero, Access Token Lifetime of the OAuth2 Provider is used instead of.",
  "propertyOrder" : 26000,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"defaultScopes" : {
  "title" : "Default Scope(s)",
  "description" : "Default Scope(s). Scopes automatically given to tokens.<br><br>Default
Scopes may be entered as simple strings or pipe separated strings representing the internal scope
name, locale, and localized description; e.g. \"read|en|Permission to view email messages in your
account\". Locale strings are in the format <code>language + \"_\" + country + \"_\" + variant</
code>, e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description is displayed to
all users having undefined locales. e.g. \"read|Permission to view email messages in your account
\". <i>NB</i> If the description is also omitted, nothing is displayed to all users, e.g. specifying
\"read|\" would allow the scope \"read\" to be used by the client, but would not display it to the
user when it was requested.",
  "propertyOrder" : 23700,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"clientType" : {
  "title" : "Client type",
  "description" : "Type of OAuth 2.0 client. Confidential clients can keep their password
secret, and are typically web apps or other server-based clients. Public clients run the risk
of exposing their password to a host or user agent, such as rich browser applications or desktop
clients.",
  "propertyOrder" : 23100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authorizationCodeLifetime" : {
  "title" : "Authorization Code Lifetime (seconds)",
  "description" : "The time in seconds an authorization code is valid for. <i>NB</i> If this
field is set to zero, Authorization Code Lifetime of the OAuth2 Provider is used instead of.",

```



```

        "propertyOrder" : 25800,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "refreshTokenLifetime" : {
        "title" : "Refresh Token Lifetime (seconds)",
        "description" : "The time in seconds a refresh token is valid for. <i>NB</i> If this field
is set to zero, Refresh Token Lifetime of the OAuth2 Provider is used instead. If this field is set
to -1, the token will never expire.",
        "propertyOrder" : 25900,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "scopes" : {
        "title" : "Scope(s)",
        "description" : "Scope(s). Scopes are strings that are presented to the user for approval
and included in tokens so that the protected resource may make decisions about what to give access
to.<br><br>Scopes may be entered as simple strings or pipe separated strings representing the
internal scope name, locale, and localized description; e.g. \"read|Permission to view email
messages in your account\". Locale strings are in the format <code>language + \"_\" + country + \"_\"
+ variant</code>, e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description
is displayed to all users having undefined locales. e.g. \"read|Permission to view email messages in
your account\". <i>NB</i> If the description is also omitted, nothing is displayed to all users, e.g.
specifying \"read\" would allow the scope \"read\" to be used by the client, but would not display
it to the user when it was requested.",
        "propertyOrder" : 23300,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "clientName" : {
        "title" : "Client Name",
        "description" : "This value is a readable name for this client.",
        "propertyOrder" : 25300,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"coreUmaClientConfig" : {
    "type" : "object",
    "title" : "UMA",
    "propertyOrder" : 4,
    "properties" : {
        "claimsRedirectionUris" : {
            "title" : "Claims Redirection URIs",
            "description" : "Redirection URIs for returning to the client from UMA claims collection
(not yet supported). If multiple URIs are registered, the client MUST specify the URI that the user
should be redirected to following approval. May not contain a fragment (#).",
            "propertyOrder" : 23200,

```

```
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
}
```

1.99. OAuth2Clients

1.99.1. Realm Operations

Agents handler that is responsible for managing agents

Resource path: `/realm-config/agents/OAuth2Client`

Resource version: `1.0`

1.99.1.1. create

Usage:

```
am> create OAuth2Clients --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "coreOpenIDClientConfig" : {
      "type" : "object",
      "title" : "OpenID Connect",
      "propertyOrder" : 2,
      "properties" : {
        "jwtTokenLifetime" : {
          "title" : "OpenID Connect JWT Token Lifetime (seconds)",
          "description" : "The time in seconds a JWT is valid for. <i>NB</i> If this field is set to zero, JWT Token Lifetime of the OAuth2 Provider is used instead of.",
          "propertyOrder" : 26100,
          "type" : "object",
```

```

        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "integer",
                "required" : true
            }
        }
    },
    "defaultAcrValues" : {
        "title" : "Default ACR values",
        "description" : "Default requested Authentication Context Class Reference
values.<br><br>Array of strings that specifies the default acr values that the OP is being requested
to use for processing requests from this Client, with the values appearing in order of preference.
The Authentication Context Class satisfied by the authentication performed is returned as the
acr Claim Value in the issued ID Token. The acr Claim is requested as a Voluntary Claim by this
parameter. The acr_values_supported discovery element contains a list of the acr values supported by
this server. Values specified in the acr_values request parameter or an individual acr Claim request
override these default values.",
        "propertyOrder" : 25650,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "defaultMaxAgeEnabled" : {
        "title" : "Default Max Age Enabled",
        "description" : "Whether or not the default max age is enforced.",
        "propertyOrder" : 25600,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : true
            }
        }
    },
    "claims" : {
        "title" : "Claim(s)",
    }

```

"description" : "List of claim name translations, which will override those specified for the AS. Claims are values that are presented to the user to inform them what data is being made available to the Client.

Claims may be entered as simple strings or pipe separated strings representing the internal claim name, locale, and localized description; e.g. \"name|en|Your full name\". Locale strings are in the format <code>language + \"_\" + country + \"_\" + variant</code>, e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description is displayed to all users having undefined locales. e.g. \"name|Your full name\". <i>NB</i> If the description is also omitted, nothing is displayed to all users, e.g. specifying \"name|\" would allow the claim \"name\" to be used by the client, but would not display it to the user when it was requested.<p>If a value is not given here, the value will be computed from the OAuth 2 Provider settings.</p>",

```

    "propertyOrder" : 23400,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "clientSessionUri" : {
    "title" : "Client Session URI",
    "description" : "This is the URI that will be used to check messages sent to the session management endpoints. This URI must match the origin of the message",
    "propertyOrder" : 25200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "defaultMaxAge" : {
    "title" : "Default Max Age",
    "description" : "Minimum value 1. Sets the maximum length of time in seconds a session may be active after the authorization service has succeeded before the user must actively re-authenticate.",
    "propertyOrder" : 25500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {

```

```

        "type" : "integer",
        "required" : true
    }
}
},
"postLogoutRedirectUri" : {
    "title" : "Post Logout Redirect URIs",
    "description" : "URIs that can be redirected to after the client logout process.",
    "propertyOrder" : 25000,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "array",
            "required" : false
        }
    }
}
}
},
"signEnc0Auth2ClientConfig" : {
    "type" : "object",
    "title" : "Signing and Encryption",
    "propertyOrder" : 3,
    "properties" : {
        "idTokenEncryptionEnabled" : {
            "title" : "Enable ID Token Encryption",
            "description" : "Select to enable ID token encryption.",
            "propertyOrder" : 24600,
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                },
                "value" : {
                    "type" : "boolean",
                    "required" : true
                }
            }
        }
    }
},
"jwkStoreCacheMissCacheTime" : {
    "title" : "JWKS URI content cache miss cache time",
    "description" : "To avoid loading the JWKS URI content for every token signature verification, especially when the kid is not in the jwks content already cached, the JWKS content will be cache for a minimum period of time. This cache miss cache time defines the minimum of time the JWKS URI content is cache.",
    "propertyOrder" : 24120,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {

```

```

    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : true
    }
  }
},
"userinfoSignedResponseAlg" : {
  "title" : "User info signed response algorithm",
  "description" : "JWS algorithm for signing UserInfo Responses. If this is specified, the response will be JWT <a href=\"https://tools.ietf.org/html/rfc7519\">JWT</a> serialized, and signed using JWS. The default, if omitted, is for the UserInfo Response to return the Claims as a UTF-8 encoded JSON object using the application/json content-type.",
  "propertyOrder" : 27200,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"tokenEndpointAuthSigningAlgorithm" : {
  "title" : "Token Endpoint Authentication Signing Algorithm",
  "description" : "The JWS algorithm that MUST be used for signing the JWT used to authenticate the Client at the Token Endpoint for the private_key_jwt and client_secret_jwt authentication methods. All Token Requests using these authentication methods from this Client MUST be rejected, if the JWT is not signed with this algorithm.",
  "propertyOrder" : 24130,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"idTokenPublicEncryptionKey" : {
  "title" : "Client ID Token Public Encryption Key",
  "description" : "A Base64 encoded public key for encrypting ID Tokens.",
  "propertyOrder" : 24900,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",

```

```
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    },
    "publicKeyLocation" : {
      "title" : "Public key selector",
      "description" : "Select the public key for this client to come from either the jwks_uri,
manual jwks or X509 field.",
      "propertyOrder" : 25700,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : true
        }
      }
    },
    "jwkSet" : {
      "title" : "Json Web Key",
      "description" : "Raw JSON Web Key value containing the client's public keys.",
      "propertyOrder" : 24200,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "userinfoEncryptedResponseAlg" : {
      "title" : "User info encrypted response algorithm",
      "description" : "JWE algorithm for encrypting UserInfo Responses. If both signing and
encryption are requested, the response will be signed then encrypted, with the result being a Nested
JWT. The default, if omitted, is that no encryption is performed.",
      "propertyOrder" : 27300,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    }
  }
}
```

```

    }
  },
  "idTokenSignedResponseAlg" : {
    "title" : "ID Token Signing Algorithm",
    "description" : "Algorithm the ID Token for this client must be signed with.",
    "propertyOrder" : 24500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  },
  "userinfoResponseFormat" : {
    "title" : "User info response format.",
    "description" : "The user info endpoint offers different output format. See http://openid.net/specs/openid-connect-core-1\_0.html#UserInfoResponse",
    "propertyOrder" : 27100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  },
  "idTokenEncryptionMethod" : {
    "title" : "ID Token Encryption Method",
    "description" : "Encryption method the ID Token for this client must be encrypted with.",
    "propertyOrder" : 24800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  },
  "requestParameterEncryptedEncryptionAlgorithm" : {
    "title" : "Request parameter encryption method",
    "description" : "JWE enc algorithm for encrypting the request parameter.<br><br>AM supports the following token encryption algorithms:<ul><li><code>A128GCM</code>, <code>A192GCM</code>,"
  }
}

```



```

and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 27700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"requestParameterEncryptedAlg" : {
  "title" : "Request parameter encryption algorithm",
  "description" : "JWE algorithm for encrypting the request parameter.",
  "propertyOrder" : 27600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"idTokenEncryptionAlgorithm" : {
  "title" : "ID Token Encryption Algorithm",
  "description" : "Algorithm the ID Token for this client must be encrypted with.",
  "propertyOrder" : 24700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"jwksCacheTimeout" : {
  "title" : "JWKS URI content cache timeout in ms",
  "description" : "To avoid loading the JWKS URI content for every token encryption, the JWKS content is cached. This timeout defines the maximum of time the JWKS URI content can be cached before being refreshed.",
  "propertyOrder" : 24110,
  "type" : "object",
  "exampleValue" : "",

```

```
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "integer",
    "required" : true
  }
},
},
"requestParameterSignedAlg" : {
  "title" : "Request parameter signing algorithm",
  "description" : "JWS algorithm for signing the request parameter.",
  "propertyOrder" : 27500,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
},
"jwksUri" : {
  "title" : "Json Web Key URI",
  "description" : "The uri that contains the client's public keys in Json Web Key format.",
  "propertyOrder" : 24100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
},
"clientJwtPublicKey" : {
  "title" : "Client JWT Bearer Public Key",
  "description" : "A Base64 encoded X509 certificate, containing the public key, represented
as a UTF-8 PEM file, of the key pair for signing the Client Bearer JWT.",
  "propertyOrder" : 25400,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
```

```

        "required" : false
    }
}
},
"userinfoEncryptedResponseEncryptionAlgorithm" : {
    "title" : "User info encrypted response encryption algorithm",
    "description" : "JWE enc algorithm for encrypting UserInfo Responses. If userinfo encrypted
response algorithm is specified, the default for this value is A128CBC-HS256. When user info
encrypted response encryption is included, user info encrypted response algorithm MUST also be
provided.<br><br>AM supports the following token encryption algorithms:<ul><li><code>A128GCM</code>,
<code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated
encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-
HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
    "propertyOrder" : 27400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : true
        }
    }
}
}
}
},
"advanced0Auth2ClientConfig" : {
    "type" : "object",
    "title" : "Advanced",
    "propertyOrder" : 1,
    "properties" : {
        "descriptions" : {
            "title" : "Display description",
            "description" : "A description of the client or other information that may be relevant
to the resource owner when considering approval.<br><br>The description may be entered as a single
string or as pipe separated strings for locale and localized name; e.g. \"en|The company intranet
is requesting the following access permission\". Locale strings are in the format <code>language
+ \"_\" + country + \"_\" + variant</code>, e.g. en, en_GB, en_US_WIN. If the locale is omitted,
the description is displayed to all users having undefined locales. e.g. \"The company intranet
is requesting the following access permission\".",
            "propertyOrder" : 23600,
            "items" : {
                "type" : "string"
            },
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                },
                "value" : {
                    "type" : "array",
                    "required" : false
                }
            }
        }
    }
}
}

```

```

    },
    "updateAccessToken" : {
      "title" : "Access Token",
      "description" : "The access token used to update the client.",
      "propertyOrder" : 25100,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "tokenEndpointAuthMethod" : {
      "title" : "Token Endpoint Authentication Method",
      "description" : "The authentication method with which a client authenticates to the
authorization server at the token endpoint. The authentication method applies to OIDC requests with
the openid scope.",
      "propertyOrder" : 24000,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : true
        }
      }
    },
    "mixUpMitigation" : {
      "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
      "description" : "Enables OAuth 2.0 mix-up mitigation on the authorization server
side.<br><br>Enable this setting only if this OAuth 2.0 client supports the <a href=\"https://
tools.ietf.org/html/draft-ietf-oauth-mix-up-mitigation-01\">OAuth 2.0 Mix-Up Mitigation draft</a>,
otherwise AM will fail to validate access token requests received from this client.",
      "propertyOrder" : 26300,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : true
        }
      }
    },
    "subjectType" : {
      "title" : "Subject Type",

```

```

        "description" : "The subject type added to responses for this client.",
        "propertyOrder" : 24400,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : true
            }
        }
    },
    "requestUris" : {
        "title" : "Request uris",
        "description" : "Array of request_uri values that are pre-registered by the RP for use at
the OP.<br><br>The entire Request URI MUST NOT exceed 512 ASCII characters. Otherwise the value will
be ignored.",
        "propertyOrder" : 23700,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "contacts" : {
        "title" : "Contacts",
        "description" : "Email addresses of users who can administrate this client.",
        "propertyOrder" : 23900,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "sectorIdentifierUri" : {
        "title" : "Sector Identifier URI",
    
```

```

    "description" : "The Host component of this URL is used in the computation of pairwise
Subject Identifiers.",
    "propertyOrder" : 24300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "name" : {
    "title" : "Display name",
    "description" : "A client name that may be relevant to the resource owner when considering
approval.<br><br>The name may be entered as a single string or as pipe separated strings for
locale and localized name; e.g. \"en|The ExampleCo Intranet\". Locale strings are in the format
<code>language + \"_\" + country + \"_\" + variant</code>, e.g. en, en_GB, en_US_WIN. If the locale
is omitted, the name is displayed to all users having undefined locales. e.g. \"The ExampleCo
Intranet\".",
    "propertyOrder" : 23500,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "responseTypes" : {
    "title" : "Response Types",
    "description" : "Response types this client will support and use.",
    "propertyOrder" : 23800,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : true
      }
    }
  }
}

```

```

    }
  },
  "isConsentImplied" : {
    "title" : "Implied consent",
    "description" : "When enabled, the resource owner will not be asked for consent during
authorization flows. The OAuth2 Provider must be configured to allow clients to skip consent.",
    "propertyOrder" : 26200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
}
},
"coreOAuth2ClientConfig" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "clientName" : {
      "title" : "Client Name",
      "description" : "This value is a readable name for this client.",
      "propertyOrder" : 25300,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "array",
          "required" : false
        }
      }
    }
  }
},
"scopes" : {
  "title" : "Scope(s)",
  "description" : "Scope(s). Scopes are strings that are presented to the user for approval
and included in tokens so that the protected resource may make decisions about what to give access
to.<br><br>Scopes may be entered as simple strings or pipe separated strings representing the
internal scope name, locale, and localized description; e.g. \"read|en|Permission to view email
messages in your account\". Locale strings are in the format <code>language + \"_\" + country + \"_\"
+ variant</code>, e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description
is displayed to all users having undefined locales. e.g. \"read|Permission to view email messages in
your account\". <i>NB</i> If the description is also omitted, nothing is displayed to all users, e.g.
specifying \"read|\" would allow the scope \"read\" to be used by the client, but would not display
it to the user when it was requested.",

```

```

"propertyOrder" : 23300,
"items" : {
  "type" : "string"
},
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "array",
    "required" : false
  }
}
},
"redirectionUri" : {
  "title" : "Redirection URIs",
  "description" : "Redirection URIs (optional for confidential clients). Complete URIs or URIs
consisting of protocol + authority + path are registered so that the OAuth 2.0 provider can trust
that tokens are sent to trusted entities. If multiple URI's are registered, the client MUST specify
the URI that the user should be redirected to following approval. May not contain a fragment (#).",
  "propertyOrder" : 23200,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"authorizationCodeLifetime" : {
  "title" : "Authorization Code Lifetime (seconds)",
  "description" : "The time in seconds an authorization code is valid for. <i>NB</i> If this
field is set to zero, Authorization Code Lifetime of the OAuth2 Provider is used instead of.",
  "propertyOrder" : 25800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : true
    }
  }
},
"accessTokenLifetime" : {

```



```

    "title" : "Access Token Lifetime (seconds)",
    "description" : "The time in seconds an access token is valid for. <i>NB</i> If this field
is set to zero, Access Token Lifetime of the OAuth2 Provider is used instead.",
    "propertyOrder" : 26000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : true
      }
    }
  },
  "userpassword" : {
    "title" : "Client secret",
    "description" : "Client secret. Used when the client authenticates to AM.",
    "propertyOrder" : 23000,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "clientType" : {
    "title" : "Client type",
    "description" : "Type of OAuth 2.0 client. Confidential clients can keep their password
secret, and are typically web apps or other server-based clients. Public clients run the risk
of exposing their password to a host or user agent, such as rich browser applications or desktop
clients.",
    "propertyOrder" : 23100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  },
  "refreshTokenLifetime" : {
    "title" : "Refresh Token Lifetime (seconds)",
    "description" : "The time in seconds a refresh token is valid for. <i>NB</i> If this field
is set to zero, Refresh Token Lifetime of the OAuth2 Provider is used instead. If this field is set
to -1, the token will never expire.",
    "propertyOrder" : 25900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },

```

```

        "value" : {
            "type" : "integer",
            "required" : true
        }
    },
    "defaultScopes" : {
        "title" : "Default Scope(s)",
        "description" : "Default Scope(s). Scopes automatically given to tokens.<br><br>Default
        Scopes may be entered as simple strings or pipe separated strings representing the internal scope
        name, locale, and localized description; e.g. \"read|Permission to view email messages in your
        account\". Locale strings are in the format <code>language + \"_\" + country + \"_\" + variant</
        code>, e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description is displayed to
        all users having undefined locales. e.g. \"read|Permission to view email messages in your account
        \". <i>NB</i> If the description is also omitted, nothing is displayed to all users, e.g. specifying
        \"read\" would allow the scope \"read\" to be used by the client, but would not display it to the
        user when it was requested.",
        "propertyOrder" : 23700,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "status" : {
        "title" : "Status",
        "description" : "Status of the agent configuration.",
        "propertyOrder" : 200,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : true
            }
        }
    },
    "agentgroup" : {
        "title" : "Group",
        "description" : "Add the client to a group to allow inheritance of property values from the
        group. <br>Changing the group will update inherited property values. <br>Inherited property values
        are copied to the client.",
        "propertyOrder" : 100,
        "required" : false,
        "type" : "string",
    }
}

```

```

        "exampleValue" : ""
      }
    },
    "coreUmaClientConfig" : {
      "type" : "object",
      "title" : "UMA",
      "propertyOrder" : 4,
      "properties" : {
        "claimsRedirectionUris" : {
          "title" : "Claims Redirection URIs",
          "description" : "Redirection URIs for returning to the client from UMA claims collection
(not yet supported). If multiple URIs are registered, the client MUST specify the URI that the user
should be redirected to following approval. May not contain a fragment (#).",
          "propertyOrder" : 23200,
          "items" : {
            "type" : "string"
          },
          "type" : "object",
          "exampleValue" : "",
          "properties" : {
            "inherited" : {
              "type" : "boolean",
              "required" : true
            },
            "value" : {
              "type" : "array",
              "required" : false
            }
          }
        }
      }
    }
  }
}

```

1.99.1.2. delete

Usage:

```
am> delete OAuth2Clients --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.99.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OAuth2Clients --realm Realm --actionName getAllTypes
```

1.99.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OAuth2Clients --realm Realm --actionName getCreatableTypes
```

1.99.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OAuth2Clients --realm Realm --actionName nextdescendents
```

1.99.1.6. query

Querying the agents of a specific type

Usage:

```
am> query OAuth2Clients --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.99.1.7. read

Usage:

```
am> read OAuth2Clients --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.99.1.8. update

Usage:

```
am> update OAuth2Clients --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "coreOpenIDClientConfig" : {
      "type" : "object",
      "title" : "OpenID Connect",
      "propertyOrder" : 2,
      "properties" : {
        "jwtTokenLifetime" : {
          "title" : "OpenID Connect JWT Token Lifetime (seconds)",
          "description" : "The time in seconds a JWT is valid for. <i>NB</i> If this field is set to zero, JWT Token Lifetime of the OAuth2 Provider is used instead of.",
          "propertyOrder" : 26100,
          "type" : "object",
          "exampleValue" : "",
          "properties" : {
            "inherited" : {
              "type" : "boolean",
              "required" : true
            },
            "value" : {
              "type" : "integer",
              "required" : true
            }
          }
        },
        "defaultAcrValues" : {
          "title" : "Default ACR values",
          "description" : "Default requested Authentication Context Class Reference values.<br><br>Array of strings that specifies the default acr values that the OP is being requested to use for processing requests from this Client, with the values appearing in order of preference. The Authentication Context Class satisfied by the authentication performed is returned as the acr Claim Value in the issued ID Token. The acr Claim is requested as a Voluntary Claim by this parameter. The acr_values_supported discovery element contains a list of the acr values supported by this server. Values specified in the acr_values request parameter or an individual acr Claim request override these default values.",
          "propertyOrder" : 25650,
          "items" : {
            "type" : "string"
          },
          "type" : "object",
          "exampleValue" : "",
          "properties" : {
            "inherited" : {
              "type" : "boolean",
              "required" : true
            },
            "value" : {
              "type" : "array",
              "required" : false
            }
          }
        }
      }
    }
  }
}
```

```

    }
  },
  "defaultMaxAgeEnabled" : {
    "title" : "Default Max Age Enabled",
    "description" : "Whether or not the default max age is enforced.",
    "propertyOrder" : 25600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "claims" : {
    "title" : "Claim(s)",
    "description" : "List of claim name translations, which will override those specified for
the AS. Claims are values that are presented to the user to inform them what data is being made
available to the Client.<br><br>Claims may be entered as simple strings or pipe separated strings
representing the internal claim name, locale, and localized description; e.g. \"name|en|Your full
name\". Locale strings are in the format <code>language + \"_\" + country + \"_\" + variant</code>,
e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description is displayed to all
users having undefined locales. e.g. \"name|Your full name\". <i>NB</i> If the description is also
omitted, nothing is displayed to all users, e.g. specifying \"name|\" would allow the claim \"name\"
to be used by the client, but would not display it to the user when it was requested.<p>If a value is
not given here, the value will be computed from the OAuth 2 Provider settings.</p>",
    "propertyOrder" : 23400,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "clientSessionUri" : {
    "title" : "Client Session URI",
    "description" : "This is the URI that will be used to check messages sent to the session
management endpoints. This URI must match the origin of the message",
    "propertyOrder" : 25200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
}

```

```
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  },
  "defaultMaxAge" : {
    "title" : "Default Max Age",
    "description" : "Minimum value 1. Sets the maximum length of time in seconds a session
may be active after the authorization service has succeeded before the user must actively re-
authenticate.",
    "propertyOrder" : 25500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : true
      }
    }
  },
  "postLogoutRedirectUri" : {
    "title" : "Post Logout Redirect URIs",
    "description" : "URIs that can be redirected to after the client logout process.",
    "propertyOrder" : 25000,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  }
},
"signEnc0Auth2ClientConfig" : {
  "type" : "object",
  "title" : "Signing and Encryption",
  "propertyOrder" : 3,
  "properties" : {
    "idTokenEncryptionEnabled" : {
      "title" : "Enable ID Token Encryption",
      "description" : "Select to enable ID token encryption.",
      "propertyOrder" : 24600,
      "type" : "object",
      "exampleValue" : ""
    }
  }
}
```

```

    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "jwkStoreCacheMissCacheTime" : {
    "title" : "JWKS URI content cache miss cache time",
    "description" : "To avoid loading the JWKS URI content for every token signature verification, especially when the kid is not in the jwks content already cached, the JWKS content will be cache for a minimum period of time. This cache miss cache time defines the minimum of time the JWKS URI content is cache.",
    "propertyOrder" : 24120,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : true
      }
    }
  },
  "userinfoSignedResponseAlg" : {
    "title" : "User info signed response algorithm",
    "description" : "JWS algorithm for signing UserInfo Responses. If this is specified, the response will be JWT <a href=\"https://tools.ietf.org/html/rfc7519\">JWT</a> serialized, and signed using JWS. The default, if omitted, is for the UserInfo Response to return the Claims as a UTF-8 encoded JSON object using the application/json content-type.",
    "propertyOrder" : 27200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "tokenEndpointAuthSigningAlgorithm" : {
    "title" : "Token Endpoint Authentication Signing Algorithm",
    "description" : "The JWS algorithm that MUST be used for signing the JWT used to authenticate the Client at the Token Endpoint for the private_key_jwt and client_secret_jwt authentication methods. All Token Requests using these authentication methods from this Client MUST be rejected, if the JWT is not signed with this algorithm.",
    "propertyOrder" : 24130,
    "type" : "object",

```



```

    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  },
  "idTokenPublicKey" : {
    "title" : "Client ID Token Public Encryption Key",
    "description" : "A Base64 encoded public key for encrypting ID Tokens.",
    "propertyOrder" : 24900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "publicKeyLocation" : {
    "title" : "Public key selector",
    manual jwks or X509 field.",
    "description" : "Select the public key for this client to come from either the jwks_uri,
    "propertyOrder" : 25700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  },
  "jwkSet" : {
    "title" : "Json Web Key",
    "description" : "Raw JSON Web Key value containing the client's public keys.",
    "propertyOrder" : 24200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {

```

```
    "type" : "string",
    "required" : false
  }
},
"userinfoEncryptedResponseAlg" : {
  "title" : "User info encrypted response algorithm",
  "description" : "JWE algorithm for encrypting UserInfo Responses. If both signing and
encryption are requested, the response will be signed then encrypted, with the result being a Nested
JWT. The default, if omitted, is that no encryption is performed.",
  "propertyOrder" : 27300,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"idTokenSignedResponseAlg" : {
  "title" : "ID Token Signing Algorithm",
  "description" : "Algorithm the ID Token for this client must be signed with.",
  "propertyOrder" : 24500,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"userinfoResponseFormat" : {
  "title" : "User info response format.",
  "description" : "The user info endpoint offers different output format. See http://
openid.net/specs/openid-connect-core-1\_0.html#UserInfoResponse",
  "propertyOrder" : 27100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
}
```

```

"idTokenEncryptionMethod" : {
  "title" : "ID Token Encryption Method",
  "description" : "Encryption method the ID Token for this client must be encrypted with.",
  "propertyOrder" : 24800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"requestParameterEncryptedEncryptionAlgorithm" : {
  "title" : "Request parameter encryption method",
  "description" : "JWE enc algorithm for encrypting the request parameter.<br><br>AM supports the following token encryption algorithms:<ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 27700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"requestParameterEncryptedAlg" : {
  "title" : "Request parameter encryption algorithm",
  "description" : "JWE algorithm for encrypting the request parameter.",
  "propertyOrder" : 27600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"idTokenEncryptionAlgorithm" : {
  "title" : "ID Token Encryption Algorithm",
  "description" : "Algorithm the ID Token for this client must be encrypted with.",
  "propertyOrder" : 24700,

```

```

    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  },
  "jwksCacheTimeout" : {
    "title" : "JWKS URI content cache timeout in ms",
    "description" : "To avoid loading the JWKS URI content for every token encryption, the JWKS content is cached. This timeout defines the maximum of time the JWKS URI content can be cached before being refreshed.",
    "propertyOrder" : 24110,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : true
      }
    }
  },
  "requestParameterSignedAlg" : {
    "title" : "Request parameter signing algorithm",
    "description" : "JWS algorithm for signing the request parameter.",
    "propertyOrder" : 27500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "jwksUri" : {
    "title" : "Json Web Key URI",
    "description" : "The uri that contains the client's public keys in Json Web Key format.",
    "propertyOrder" : 24100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
}

```

```

    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"clientJwtPublicKey" : {
  "title" : "Client JWT Bearer Public Key",
  "description" : "A Base64 encoded X509 certificate, containing the public key, represented
as a UTF-8 PEM file, of the key pair for signing the Client Bearer JWT.",
  "propertyOrder" : 25400,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"userinfoEncryptedResponseEncryptionAlgorithm" : {
  "title" : "User info encrypted response encryption algorithm",
  "description" : "JWE enc algorithm for encrypting UserInfo Responses. If userinfo encrypted
response algorithm is specified, the default for this value is A128CBC-HS256. When user info
encrypted response encryption is included, user info encrypted response algorithm MUST also be
provided.<br><br>AM supports the following token encryption algorithms:<ul><li><code>A128GCM</code>,
<code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated
encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-
HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 27400,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
}
}
},
"advanced0Auth2ClientConfig" : {
  "type" : "object",
  "title" : "Advanced",
  "propertyOrder" : 1,
  "properties" : {
    "descriptions" : {
      "title" : "Display description",
      "description" : "A description of the client or other information that may be relevant
to the resource owner when considering approval.<br><br>The description may be entered as a single

```

string or as pipe separated strings for locale and localized name; e.g. `"en|The company intranet is requesting the following access permission\"`. Locale strings are in the format `<code>language + \"_\" + country + \"_\" + variant</code>`, e.g. `en, en_GB, en_US_WIN`. If the locale is omitted, the description is displayed to all users having undefined locales. e.g. `"The company intranet is requesting the following access permission\"`.

```

    "propertyOrder" : 23600,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "updateAccessToken" : {
    "title" : "Access Token",
    "description" : "The access token used to update the client.",
    "propertyOrder" : 25100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "tokenEndpointAuthMethod" : {
    "title" : "Token Endpoint Authentication Method",
    "description" : "The authentication method with which a client authenticates to the
authorization server at the token endpoint. The authentication method applies to OIDC requests with
the openid scope.",
    "propertyOrder" : 24000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  },
  "mixUpMitigation" : {

```

```

    "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
    "description" : "Enables OAuth 2.0 mix-up mitigation on the authorization server
side.<br><br>Enable this setting only if this OAuth 2.0 client supports the <a href=\"https://
tools.ietf.org/html/draft-ietf-oauth-mix-up-mitigation-01\">OAuth 2.0 Mix-Up Mitigation draft</a>,
otherwise AM will fail to validate access token requests received from this client.",
    "propertyOrder" : 26300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "subjectType" : {
    "title" : "Subject Type",
    "description" : "The subject type added to responses for this client.",
    "propertyOrder" : 24400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  },
  "requestUris" : {
    "title" : "Request uris",
    "description" : "Array of request_uri values that are pre-registered by the RP for use at
the OP.<br><br>The entire Request URI MUST NOT exceed 512 ASCII characters. Otherwise the value will
be ignored.",
    "propertyOrder" : 23700,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "contacts" : {

```

```

        "title" : "Contacts",
        "description" : "Email addresses of users who can administrate this client.",
        "propertyOrder" : 23900,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "sectorIdentifierUri" : {
        "title" : "Sector Identifier URI",
        "description" : "The Host component of this URL is used in the computation of pairwise
Subject Identifiers.",
        "propertyOrder" : 24300,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "name" : {
        "title" : "Display name",
        "description" : "A client name that may be relevant to the resource owner when considering
approval.<br><br>The name may be entered as a single string or as pipe separated strings for
locale and localized name; e.g. \n|The ExampleCo Intranet|. Locale strings are in the format
<code>language + \"_\" + country + \"_\" + variant</code>, e.g. en, en_GB, en_US_WIN. If the locale
is omitted, the name is displayed to all users having undefined locales. e.g. \n|The ExampleCo
Intranet|. ",
        "propertyOrder" : 23500,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    }
}

```



```

    }
  },
  "responseTypes" : {
    "title" : "Response Types",
    "description" : "Response types this client will support and use.",
    "propertyOrder" : 23800,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : true
      }
    }
  },
  "isConsentImplied" : {
    "title" : "Implied consent",
    "description" : "When enabled, the resource owner will not be asked for consent during authorization flows. The OAuth2 Provider must be configured to allow clients to skip consent.",
    "propertyOrder" : 26200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
},
"coreOAuth2ClientConfig" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "clientName" : {
      "title" : "Client Name",
      "description" : "This value is a readable name for this client.",
      "propertyOrder" : 25300,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {

```

```

        "type" : "boolean",
        "required" : true
    },
    "value" : {
        "type" : "array",
        "required" : false
    }
}
},
"scopes" : {
    "title" : "Scope(s)",
    "description" : "Scope(s). Scopes are strings that are presented to the user for approval and included in tokens so that the protected resource may make decisions about what to give access to.<br><br>Scopes may be entered as simple strings or pipe separated strings representing the internal scope name, locale, and localized description; e.g. \"read|en|Permission to view email messages in your account\". Locale strings are in the format <code>language + \"_\" + country + \"_\" + variant</code>, e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description is displayed to all users having undefined locales. e.g. \"read|Permission to view email messages in your account\". <i>NB</i> If the description is also omitted, nothing is displayed to all users, e.g. specifying \"read|\" would allow the scope \"read\" to be used by the client, but would not display it to the user when it was requested.",
    "propertyOrder" : 23300,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "array",
            "required" : false
        }
    }
}
},
"redirectionUris" : {
    "title" : "Redirection URIs",
    "description" : "Redirection URIs (optional for confidential clients). Complete URIs or URIs consisting of protocol + authority + path are registered so that the OAuth 2.0 provider can trust that tokens are sent to trusted entities. If multiple URI's are registered, the client MUST specify the URI that the user should be redirected to following approval. May not contain a fragment (#).",
    "propertyOrder" : 23200,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "array",
            "required" : false
        }
    }
}
}

```

```
    },
    "authorizationCodeLifetime" : {
      "title" : "Authorization Code Lifetime (seconds)",
      "description" : "The time in seconds an authorization code is valid for. <i>NB</i> If this
field is set to zero, Authorization Code Lifetime of the OAuth2 Provider is used instead of.",
      "propertyOrder" : 25800,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : true
        }
      }
    },
    "accessTokenLifetime" : {
      "title" : "Access Token Lifetime (seconds)",
      "description" : "The time in seconds an access token is valid for. <i>NB</i> If this field
is set to zero, Access Token Lifetime of the OAuth2 Provider is used instead of.",
      "propertyOrder" : 26000,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : true
        }
      }
    },
    "userpassword" : {
      "title" : "Client secret",
      "description" : "Client secret. Used when the client authenticates to AM.",
      "propertyOrder" : 23000,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "clientType" : {
      "title" : "Client type",
      "description" : "Type of OAuth 2.0 client. Confidential clients can keep their password
secret, and are typically web apps or other server-based clients. Public clients run the risk
of exposing their password to a host or user agent, such as rich browser applications or desktop
clients.",
      "propertyOrder" : 23100,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
```

```

        "required" : true
    },
    "value" : {
        "type" : "string",
        "required" : true
    }
}
},
"refreshTokenLifetime" : {
    "title" : "Refresh Token Lifetime (seconds)",
    "description" : "The time in seconds a refresh token is valid for. <i>NB</i> If this field
is set to zero, Refresh Token Lifetime of the OAuth2 Provider is used instead. If this field is set
to -1, the token will never expire.",
    "propertyOrder" : 25900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : true
        }
    }
}
},
"defaultScopes" : {
    "title" : "Default Scope(s)",
    "description" : "Default Scope(s). Scopes automatically given to tokens.<br><br>Default
Scopes may be entered as simple strings or pipe separated strings representing the internal scope
name, locale, and localized description; e.g. \"read|en|Permission to view email messages in your
account\". Locale strings are in the format <code>language + \"_\" + country + \"_\" + variant</
code>, e.g. en, en_GB, en_US_WIN. If the locale and pipe is omitted, the description is displayed to
all users having undefined locales. e.g. \"read|Permission to view email messages in your account
\". <i>NB</i> If the description is also omitted, nothing is displayed to all users, e.g. specifying
\"read|\" would allow the scope \"read\" to be used by the client, but would not display it to the
user when it was requested.",
    "propertyOrder" : 23700,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "array",
            "required" : false
        }
    }
}
},
"status" : {
    "title" : "Status",
    "description" : "Status of the agent configuration.",
    "propertyOrder" : 200,

```

```
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "string",
    "required" : true
  }
}
},
"agentgroup" : {
  "title" : "Group",
  "description" : "Add the client to a group to allow inheritance of property values from the
group. <br>Changing the group will update inherited property values. <br>Inherited property values
are copied to the client.",
  "propertyOrder" : 100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
},
"coreUmaClientConfig" : {
  "type" : "object",
  "title" : "UMA",
  "propertyOrder" : 4,
  "properties" : {
    "claimsRedirectionUris" : {
      "title" : "Claims Redirection URIs",
      "description" : "Redirection URIs for returning to the client from UMA claims collection
(not yet supported). If multiple URIs are registered, the client MUST specify the URI that the user
should be redirected to following approval. May not contain a fragment (#).",
      "propertyOrder" : 23200,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "array",
          "required" : false
        }
      }
    }
  }
}
}
}
}
```

1.100. OAuth2Module

1.100.1. Realm Operations

Resource path: `/realm-config/authentication/modules/oauth2`

Resource version: `1.0`

1.100.1.1. create

Usage:

```
am> create OAuth2Module --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "logoutBehaviour" : {
      "title" : "Logout options",
      "description" : "Controls how Logout options will be presented to the user.<br><br>The OAuth
module has the following logout options for the user:<br><br><ul><li>Prompt: Prompt the user to
logout from the OAuth 2.0 Provider</li><li>Logout: Logout from the OAuth 2.0 Provider and do not
prompt</li><li>Do not logout: Do not logout the user from the OAuth 2.0 Provider and do not prompt</
li></ul>",
      "propertyOrder" : 2100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "scope" : {
      "title" : "Scope",
      "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth
2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the
client application requires. The list depends on the permissions that the resource owner grants to
the client application.<br><br>Some authorization servers use non-standard separators for scopes.
For example, Facebook takes a comma-separated list.<br><br>Default: <code>email, read_stream</
code> (Facebook example)",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "ssoProxyUrl" : {
```

```

    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be changed
from the default, if an external server is performing the GET to POST proxying. The default is
<code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "accountMapperClass" : {
    "title" : "Account Mapper",
    "description" : "Name of the class implementing the attribute mapping for the account
search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "accessTokenParameterName" : {
    "title" : "OAuth2 Access Token Profile Service Parameter name",
    "description" : "The name of the parameter that will contain the access token value when
accessing the profile service",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "openidConnectContextValue" : {
    "title" : "OpenID Connect validation configuration value",
    "description" : "Required when the 'openid' scope is included. The discovery url, or jwk
url, or the client_secret, corresponding to the selection above.<br><br>If discovery or jwk url
entered, entry must be in valid url format, <br>e.g. https://accounts.google.com/.well-known/openid-
configuration<br><i>NB </i>If client_secret entered, entry is ignored and the value of the Client
Secret is used.",
    "propertyOrder" : 3100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpHostName" : {
    "title" : "SMTP host",
    "description" : "The mail host that will be used by the Email Gateway implementation",
    "propertyOrder" : 2300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userProfileServiceUrl" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL<br><br>This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return
JSON objects in response",

```

```

    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpSslEnabled" : {
    "title" : "SMTP SSL Enabled",
    "description" : "Tick this option if the SMTP Server provides SSL",
    "propertyOrder" : 2700,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "openidConnectIssuer" : {
    "title" : "Token Issuer",
    "description" : "Required when the 'openid' scope is included. Value must match the iss field in issued ID Token<br/>e.g. accounts.google.com<br><br>The issuer value MUST be provided when OAuth 2.0 Mix-Up Mitigation is enabled.",
    "propertyOrder" : 3200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "openidConnectContextType" : {
    "title" : "OpenID Connect validation configuration type",
    "description" : "Required when the 'openid' scope is included. Please select either 1. the issuer discovery url, 2. the issuer jwk url, or 3. the client_secret.",
    "propertyOrder" : 3000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "mailGatewayClass" : {
    "title" : "Mail Server Gateway implementation class",
    "description" : "The class used by the module to send email.<br><br>This class is used by the module to send email. A custom implementation can be provided.<br><br>The custom implementation must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
    "propertyOrder" : 2200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saveAttributesInSession" : {
    "title" : "Save attributes in the session",
    "description" : "If this option is enabled, the attributes configured in the attribute mapper will be saved into the OpenAM session",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "smtpUsername" : {
    "title" : "SMTP User Name",
    "description" : "If the SMTP Service requires authentication, configure the user name here",
    "propertyOrder" : 2500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},

```



```

"attributeMappingClasses" : {
  "title" : "Attribute Mapper",
  "description" : "Name of the class that implements the attribute mapping<br><br>This
class maps the OAuth properties into OpenAM properties. A custom attribute
mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
  "propertyOrder" : 1200,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"promptForPassword" : {
  "title" : "Prompt for password setting and activation code",
  "description" : "Users must set a password and complete the activation flow during dynamic
profile creation.<br><br>If this is enabled, the user must set a password before the system creates
an account dynamically and an activation code will be sent to the user's email address. The account
will be created only if the password and activation code are properly set. <br />If this is disabled,
the account will be created transparently without prompting the user.",
  "propertyOrder" : 1700,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"smtpFromAddress" : {
  "title" : "SMTP From address",
  "description" : "The email address on behalf of whom the messages will be sent",
  "propertyOrder" : 2800,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"anonymousUserName" : {
  "title" : "Anonymous User",
  "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that will
represent the anonymous user. This user account must already exist in the realm.",
  "propertyOrder" : 1900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 2900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"smtpPassword" : {

```

```

        "title" : "SMTP User Password",
        "description" : "The Password of the SMTP User Name",
        "propertyOrder" : 2600,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br>If not selected the users authenticated will be mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
        "propertyOrder" : 1800,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "smtpHostPort" : {
        "title" : "SMTP port",
        "description" : "The TCP port that will be used by the SMTP gateway",
        "propertyOrder" : 2400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "accessTokenEndpointUrl" : {
        "title" : "Access Token Endpoint URL",
        "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "accountMapperConfiguration" : {
        "title" : "Account Mapper Configuration",
        "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute configuration that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
        "propertyOrder" : 1100,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "clientId" : {
        "title" : "Client Id",
        "description" : "OAuth client_id parameter<br><br>For more information on the OAuth client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "string",
    }

```

```

        "exampleValue" : ""
    },
    "mixUpMitigation" : {
        "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
        "description" : "Enables OAuth 2.0 mix-up mitigation<br><br>The authorization
server must support the <a href=\"https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
mitigation-01#section-3.1\">OAuth 2.0 Mix-Up Mitigation draft</a>, otherwise OpenAM will fail to
validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make
sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
        "propertyOrder" : 3300,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "oauth2LogoutServiceUrl" : {
        "title" : "OAuth 2.0 Provider logout service",
        "description" : "The URL of the OAuth Identity Providers Logout service<br><br>OAuth 2.0
Identity Providers can have a logout service. If this logout functionality is required then the URL
of the Logout endpoint should configured here.",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This class
is used by the module to find the account from the attributes mapped by the Account Mapper
<code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br></code>String constructor parameters can be provided by appending <code>|</code> separated
values.",
        "propertyOrder" : 900,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "clientSecret" : {
        "title" : "Client Secret",
        "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "createAccount" : {
        "title" : "Create account if it does not exist",
        "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an account
will be created dynamically.<br><br>If this is enabled, the account mapper could create the account
dynamically if there is no account mapped. Before creating the account, a dialog prompting for
a password and asking for an activation code can be shown if the parameter \"Prompt for password
setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3 alternative
options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM User Data
Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in the
Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
        "propertyOrder" : 1600,
    }
}

```

```

    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "authenticationEndpointUrl" : {
    "title" : "Authentication Endpoint URL",
    "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "attributeMapperConfiguration" : {
    "title" : "Attribute Mapper Configuration",
    "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "oauth2EmailAttribute" : {
    "title" : "Email attribute in OAuth2 Response",
    "description" : "Attribute from the OAuth2 response used to send activation code emails.<br><br>The attribute in the response from the profile service in the OAuth 2.0 Provider that contains the email address of the authenticated user. This address will be used to send an email with an activation code when the accounts are allowed to be created dynamically.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}

```

1.100.1.2. delete

Usage:

```
am> delete OAuth2Module --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.100.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OAuth2Module --realm Realm --actionName getAllTypes
```

1.100.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OAuth2Module --realm Realm --actionName getCreatableTypes
```

1.100.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OAuth2Module --realm Realm --actionName nextdescendents
```

1.100.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query OAuth2Module --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.100.1.7. read

Usage:

```
am> read OAuth2Module --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.100.1.8. update

Usage:

```
am> update OAuth2Module --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "logoutBehaviour" : {
      "title" : "Logout options",
      "description" : "Controls how Logout options will be presented to the user.<br><br>The OAuth
module has the following logout options for the user:<br><br><ul><li>Prompt: Prompt the user to
logout from the OAuth 2.0 Provider</li><li>Logout: Logout from the OAuth 2.0 Provider and do not
prompt</li><li>Do not logout: Do not logout the user from the OAuth 2.0 Provider and do not prompt</
li></ul>",
      "propertyOrder" : 2100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "scope" : {
      "title" : "Scope",
      "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth
2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the
client application requires. The list depends on the permissions that the resource owner grants to
the client application.<br><br>Some authorization servers use non-standard separators for scopes.
For example, Facebook takes a comma-separated list.<br><br>Default: <code>email, read_stream</
code> (Facebook example)",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "ssoProxyUrl" : {
      "title" : "Proxy URL",
      "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be changed
from the default, if an external server is performing the GET to POST proxying. The default is
<code>/openam/oauth2c/OAuthProxy.jsp</code>",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "accountMapperClass" : {
      "title" : "Account Mapper",
      "description" : "Name of the class implementing the attribute mapping for the account
search.<br><br>This class is used by the module to map from the account information
```

received from the OAuth Identity Provider into OpenAM.

The class must implement the `org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper` interface.
Provided implementations are:`org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper``org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper` (can only be used when using the openid scope)String constructor parameters can be provided by appending `|</code> separated values."`

```

    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "accessTokenParameterName" : {
    "title" : "OAuth2 Access Token Profile Service Parameter name",
    "description" : "The name of the parameter that will contain the access token value when accessing the profile service",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "openidConnectContextValue" : {
    "title" : "OpenID Connect validation configuration value",
    "description" : "Required when the 'openid' scope is included. The discovery url, or jwk url, or the client_secret, corresponding to the selection above.<br><br>If discovery or jwk url entered, entry must be in valid url format, <br>e.g. https://accounts.google.com/.well-known/openid-configuration<br><i>NB </i>If client_secret entered, entry is ignored and the value of the Client Secret is used.",
    "propertyOrder" : 3100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpHostName" : {
    "title" : "SMTP host",
    "description" : "The mail host that will be used by the Email Gateway implementation",
    "propertyOrder" : 2300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userProfileServiceUrl" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL<br><br>This URL endpoint provides user profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return JSON objects in response",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpSslEnabled" : {
    "title" : "SMTP SSL Enabled",
    "description" : "Tick this option if the SMTP Server provides SSL",
    "propertyOrder" : 2700,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
},

```

```

"openidConnectIssuer" : {
  "title" : "Token Issuer",
  "description" : "Required when the 'openid' scope is included. Value must match the iss field in
issued ID Token<br>e.g. accounts.google.com<br><br>The issuer value MUST be provided when OAuth 2.0
Mix-Up Mitigation is enabled.",
  "propertyOrder" : 3200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"openidConnectContextType" : {
  "title" : "OpenID Connect validation configuration type",
  "description" : "Required when the 'openid' scope is included. Please select either 1. the
issuer discovery url, 2. the issuer jwk url, or 3. the client_secret.",
  "propertyOrder" : 3000,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"mailGatewayClass" : {
  "title" : "Mail Server Gateway implementation class",
  "description" : "The class used by the module to send email.<br><br>This class is used by the
module to send email. A custom implementation can be provided.<br><br>The custom implementation
must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
  "propertyOrder" : 2200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"saveAttributesInSession" : {
  "title" : "Save attributes in the session",
  "description" : "If this option is enabled, the attributes configured in the attribute mapper
will be saved into the OpenAM session",
  "propertyOrder" : 1400,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"smtptUsername" : {
  "title" : "SMTP User Name",
  "description" : "If the SMTP Service requires authentication, configure the user name here",
  "propertyOrder" : 2500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"attributeMappingClasses" : {
  "title" : "Attribute Mapper",
  "description" : "Name of the class that implements the attribute mapping<br><br>This
class maps the OAuth properties into OpenAM properties. A custom attribute
mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
  "propertyOrder" : 1200,
  "required" : true,

```



```
"items" : {
  "type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"promptForPassword" : {
  "title" : "Prompt for password setting and activation code",
  "description" : "Users must set a password and complete the activation flow during dynamic profile creation.<br><br>If this is enabled, the user must set a password before the system creates an account dynamically and an activation code will be sent to the user's email address. The account will be created only if the password and activation code are properly set. <br />If this is disabled, the account will be created transparently without prompting the user.",
  "propertyOrder" : 1700,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"smtpFromAddress" : {
  "title" : "SMTP From address",
  "description" : "The email address on behalf of whom the messages will be sent",
  "propertyOrder" : 2800,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"anonymousUserName" : {
  "title" : "Anonymous User",
  "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that will represent the anonymous user. This user account must already exist in the realm.",
  "propertyOrder" : 1900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 2900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"smtpPassword" : {
  "title" : "SMTP User Password",
  "description" : "The Password of the SMTP User Name",
  "propertyOrder" : 2600,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"mapToAnonymousUser" : {
  "title" : "Map to anonymous user",
  "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br>>If not selected the users authenticated will be mapped by the
```

```

parameters configured in the account mapper.<br/><br/><i>NB </i>If <i>Create account if it does not
exist</i> is enabled, that parameter takes precedence.",
  "propertyOrder" : 1800,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"smtpHostPort" : {
  "title" : "SMTP port",
  "description" : "The TCP port that will be used by the SMTP gateway",
  "propertyOrder" : 2400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"accessTokenEndpointUrl" : {
  "title" : "Access Token Endpoint URL",
  "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"accountMapperConfiguration" : {
  "title" : "Account Mapper Configuration",
  "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute configuration
that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local
data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
  "propertyOrder" : 1100,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"clientId" : {
  "title" : "Client Id",
  "description" : "OAuth client_id parameter<br><br>For more information on the OAuth client_id
parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank
\">RFC 6749</a>, section 2.3.1",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"mixUpMitigation" : {
  "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
  "description" : "Enables OAuth 2.0 mix-up mitigation<br><br>The authorization
server must support the <a href=\"https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
mitigation-01#section-3.1\">OAuth 2.0 Mix-Up Mitigation draft</a>, otherwise OpenAM will fail to
validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make
sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
  "propertyOrder" : 3300,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
}

```

```

},
"oauth2LogoutServiceUrl" : {
  "title" : "OAuth 2.0 Provider logout service",
  "description" : "The URL of the OAuth Identity Providers Logout service<br><br>OAuth 2.0 Identity Providers can have a logout service. If this logout functionality is required then the URL of the Logout endpoint should configured here.",
  "propertyOrder" : 2000,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"accountProviderClass" : {
  "title" : "Account Provider",
  "description" : "Name of the class implementing the account provider.<br><br>This class is used by the module to find the account from the attributes mapped by the Account Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.<br></>String constructor parameters can be provided by appending <code>|</code> separated values.",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"clientSecret" : {
  "title" : "Client Secret",
  "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"createAccount" : {
  "title" : "Create account if it does not exist",
  "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an account will be created dynamically.<br><br>If this is enabled, the account mapper could create the account dynamically if there is no account mapped. Before creating the account, a dialog prompting for a password and asking for an activation code can be shown if the parameter \"Prompt for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3 alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
  "propertyOrder" : 1600,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"authenticationEndpointUrl" : {
  "title" : "Authentication Endpoint URL",
  "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
}

```

```
"attributeMapperConfiguration" : {
  "title" : "Attribute Mapper Configuration",
  "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
  "propertyOrder" : 1300,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"oauth2EmailAttribute" : {
  "title" : "Email attribute in OAuth2 Response",
  "description" : "Attribute from the OAuth2 response used to send activation code
emails.<br><br>The attribute in the response from the profile service in the OAuth 2.0 Provider that
contains the email address of the authenticated user. This address will be used to send an email with
an activation code when the accounts are allowed to be created dynamically.",
  "propertyOrder" : 1500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
```

1.100.2. Global Operations

Resource path: [/global-config/authentication/modules/oauth2](#)

Resource version: [1.0](#)

1.100.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OAuth2Module --global --actionName getAllTypes
```

1.100.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OAuth2Module --global --actionName getCreatableTypes
```

1.100.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OAuth2Module --global --actionName nextdescendents
```

1.100.2.4. read

Usage:

```
am> read OAuth2Module --global
```

1.100.2.5. update

Usage:

```
am> update OAuth2Module --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "mixUpMitigation" : {
          "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
          "description" : "Enables OAuth 2.0 mix-up mitigation<br><br>The authorization
server must support the <a href=\"https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
mitigation-01#section-3.1\">OAuth 2.0 Mix-Up Mitigation draft</a>, otherwise OpenAM will fail to
validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make
sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
          "propertyOrder" : 3300,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "userProfileServiceUrl" : {
          "title" : "User Profile Service URL",
          "description" : "User profile information URL<br><br>This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return
JSON objects in response",
          "propertyOrder" : 500,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticationLevel" : {
```

```
"title" : "Authentication Level",
"description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
"propertyOrder" : 2900,
"required" : true,
"type" : "integer",
"exampleValue" : ""
},
"anonymousUserName" : {
"title" : "Anonymous User",
"description" : "Username of the OpenAM anonymous user<br><br>The username of the user that will represent the anonymous user. This user account must already exist in the realm.",
"propertyOrder" : 1900,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"oauth2EmailAttribute" : {
"title" : "Email attribute in OAuth2 Response",
"description" : "Attribute from the OAuth2 response used to send activation code emails.<br><br>The attribute in the response from the profile service in the OAuth 2.0 Provider that contains the email address of the authenticated user. This address will be used to send an email with an activation code when the accounts are allowed to be created dynamically.",
"propertyOrder" : 1500,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"accountMapperConfiguration" : {
"title" : "Account Mapper Configuration",
"description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute configuration that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
"propertyOrder" : 1100,
"required" : true,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"accessTokenEndpointUrl" : {
"title" : "Access Token Endpoint URL",
"description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
"propertyOrder" : 400,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"saveAttributesInSession" : {
"title" : "Save attributes in the session",
"description" : "If this option is enabled, the attributes configured in the attribute mapper will be saved into the OpenAM session",
"propertyOrder" : 1400,
"required" : true,
```

```

    "type" : "boolean",
    "exampleValue" : ""
  },
  "smtpUsername" : {
    "title" : "SMTP User Name",
    "description" : "If the SMTP Service requires authentication, configure the user name here",
    "propertyOrder" : 2500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationEndpointUrl" : {
    "title" : "Authentication Endpoint URL",
    "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "createAccount" : {
    "title" : "Create account if it does not exist",
    "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an account will be created dynamically.<br><br>If this is enabled, the account mapper could create the account dynamically if there is no account mapped. Before creating the account, a dialog prompting for a password and asking for an activation code can be shown if the parameter \"Prompt for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3 alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "clientId" : {
    "title" : "Client Id",
    "description" : "OAuth client_id parameter<br><br>For more information on the OAuth client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "mapToAnonymousUser" : {
    "title" : "Map to anonymous user",
    "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br>If not selected the users authenticated will be mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
    "propertyOrder" : 1800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ssoProxyUrl" : {

```

```

    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "accountProviderClass" : {
    "title" : "Account Provider",
    "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br></code>String constructor parameters can be provided by appending <code>|</code> separated
values.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "oauth2LogoutServiceUrl" : {
    "title" : "OAuth 2.0 Provider logout service",
    "description" : "The URL of the OAuth Identity Providers Logout service<br><br>OAuth 2.0
Identity Providers can have a logout service. If this logout functionality is required then the URL
of the Logout endpoint should be configured here.",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpHostName" : {
    "title" : "SMTP host",
    "description" : "The mail host that will be used by the Email Gateway implementation",
    "propertyOrder" : 2300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "scope" : {
    "title" : "Scope",
    "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth
2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the
client application requires. The list depends on the permissions that the resource owner grants to
the client application.<br><br>Some authorization servers use non-standard separators for scopes.
For example, Facebook takes a comma-separated list.<br><br>Default: <code>email, read_stream</
code> (Facebook example)",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpFromAddress" : {
    "title" : "SMTP From address",
    "description" : "The email address on behalf of whom the messages will be sent",
    "propertyOrder" : 2800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}

```



```

    },
    "logoutBehaviour" : {
      "title" : "Logout options",
      "description" : "Controls how Logout options will be presented to the user.<br><br>The OAuth
module has the following logout options for the user:<br><br><ul><li>Prompt: Prompt the user to
logout from the OAuth 2.0 Provider</li><li>Logout: Logout from the OAuth 2.0 Provider and do not
prompt</li><li>Do not logout: Do not logout the user from the OAuth 2.0 Provider and do not prompt</
li></ul>",
      "propertyOrder" : 2100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "smtpSslEnabled" : {
      "title" : "SMTP SSL Enabled",
      "description" : "Tick this option if the SMTP Server provides SSL",
      "propertyOrder" : 2700,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    },
    "clientSecret" : {
      "title" : "Client Secret",
      "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    },
    "accessTokenParameterName" : {
      "title" : "OAuth2 Access Token Profile Service Parameter name",
      "description" : "The name of the parameter that will contain the access token value when
accessing the profile service",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "attributeMapperConfiguration" : {
      "title" : "Attribute Mapper Configuration",
      "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
      "propertyOrder" : 1300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
    },
    },
    "type" : "array",
    "exampleValue" : ""
  },
  },
  "accountMapperClass" : {
    "title" : "Account Mapper",
    "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information

```

received from the OAuth Identity Provider into OpenAM.

The class must implement the `org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper` interface.
Provided implementations are:`org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper``org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper` (can only be used when using the openid scope)String constructor parameters can be provided by appending `|</code> separated values."`

```

    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpHostPort" : {
    "title" : "SMTP port",
    "description" : "The TCP port that will be used by the SMTP gateway",
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpPassword" : {
    "title" : "SMTP User Password",
    "description" : "The Password of the SMTP User Name",
    "propertyOrder" : 2600,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "openidConnectContextType" : {
    "title" : "OpenID Connect validation configuration type",
    "description" : "Required when the 'openid' scope is included. Please select either 1. the issuer discovery url, 2. the issuer jwk url, or 3. the client_secret.",
    "propertyOrder" : 3000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "openidConnectIssuer" : {
    "title" : "Token Issuer",
    "description" : "Required when the 'openid' scope is included. Value must match the iss field in issued ID Token<br/>e.g. accounts.google.com<br/><br/>The issuer value MUST be provided when OAuth 2.0 Mix-Up Mitigation is enabled.",
    "propertyOrder" : 3200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "attributeMappingClasses" : {
    "title" : "Attribute Mapper",
    "description" : "Name of the class that implements the attribute mapping<br/><br/>This class maps the OAuth properties into OpenAM properties. A custom attribute mapper can be provided.<br/><br/>A custom attribute mapper must implement the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.<br/>Provided implementations are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</code> separated values.",

```

```

    "propertyOrder" : 1200,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "promptForPassword" : {
    "title" : "Prompt for password setting and activation code",
    "description" : "Users must set a password and complete the activation flow during dynamic profile creation.<br><br>If this is enabled, the user must set a password before the system creates an account dynamically and an activation code will be sent to the user's email address. The account will be created only if the password and activation code are properly set. <br />If this is disabled, the account will be created transparently without prompting the user.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "openidConnectContextValue" : {
    "title" : "OpenID Connect validation configuration value",
    "description" : "Required when the 'openid' scope is included. The discovery url, or jwk url, or the client_secret, corresponding to the selection above.<br><br>If discovery or jwk url entered, entry must be in valid url format, <br>e.g. https://accounts.google.com/.well-known/openid-configuration<br><i>NB </i>If client_secret entered, entry is ignored and the value of the Client Secret is used.",
    "propertyOrder" : 3100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "mailGatewayClass" : {
    "title" : "Mail Server Gateway implementation class",
    "description" : "The class used by the module to send email.<br><br>This class is used by the module to send email. A custom implementation can be provided.<br><br>The custom implementation must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
    "propertyOrder" : 2200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}
}

```

1.101. OAuth2Provider

1.101.1. Realm Operations

Resource path: `/realm-config/services/oauth-oidc`

Resource version: `1.0`

1.101.1.1. create

Usage:

```
am> create OAuth2Provider --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "advancedOAuth2Config" : {
      "type" : "object",
      "title" : "Advanced",
      "propertyOrder" : 1,
      "properties" : {
        "tokenSigningECDSAKeyAlias" : {
          "title" : "Token Signing ECDSA Public/Private Key Pair Alias",
          "description" : "The list of public/private key pairs used for the elliptic curve algorithms (ES256/ES384/ES512). Add an entry to specify an alias for a specific elliptic curve algorithm, for example ES256|es256Alias.<br><br>Each of the public/private key pairs will be retrieved from the keystore referenced by the property com.sun.identity.saml.xmlsig.keystore.",
          "propertyOrder" : 241,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "tokenCompressionEnabled" : {
          "title" : "Stateless Token Compression",
          "description" : "Whether stateless access and refresh tokens should be compressed.",
          "propertyOrder" : 223,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "customLoginUrlTemplate" : {
          "title" : "Custom Login URL Template",
          "description" : "Custom URL for handling login, to override the default OpenAM login page.<br><br>Supports Freemarker syntax, with the following variables:<table><tr><th>Variable</th><th>Description</th></tr><tr><td><code>gotoUrl</code></td><td><p>The URL to redirect to after login.</p></td></tr><tr><td><code>acrValues</code></td><td><p>The Authentication Context Class Reference (acr) values for the authorization request.</p></td></tr><tr><td><code>realm</code></td><td><p>The OpenAM realm the authorization request was made on.</p></td></tr><tr><td><code>module</code></td><td><p>The name of the OpenAM authentication module requested to perform resource owner authentication.</p></td></tr><tr><td><code>service</code></td><td><p>The name of the OpenAM authentication chain requested to perform resource owner authentication.</p></td></tr></table>
```

```

tr><tr><td><code>locale</code></td><td><p>A space-separated list of locales, ordered by
preference.</p></td></tr></table>The following example template redirects users to a non-OpenAM
front end to handle login, which will then redirect back to the <code>/oauth2/authorize</code>
endpoint with any required parameters:<p> <code>http://mylogin.com/login?goto=${goto}&lt;#if
acrValues??&gt;&amp;acr_values=${acrValues}&lt;#x2F;&lt;#if&gt;&lt;#if realm??&gt;&amp;realm=
${realm}&lt;#x2F;&lt;#if&gt;&lt;#if module??&gt;&amp;module=${module}&lt;#x2F;&lt;#if&gt;&lt;#if
service??&gt;&amp;service=${service}&lt;#x2F;&lt;#if&gt;&lt;#if locale??&gt;&amp;locale=
${locale}&lt;#x2F;&lt;#if&gt;</code><br><b>NOTE</b>: Default OpenAM login page is constructed using
\"Base URL Source\" service.\",
  \"propertyOrder\" : 60,
  \"required\" : false,
  \"type\" : \"string\",
  \"exampleValue\" : \"\"
},
  \"moduleMessageEnabledInPasswordGrant\" : {
    \"title\" : \"Enable Auth Module Messages for Password Credentials Grant\",
    \"description\" : \"If enabled, authentication module failure messages are used to create
Resource Owner Password Credentials Grant failure messages. If disabled, a standard authentication
failed message is used.<br><br>The Password Grant Type requires the <code>grant_type=password</code>
parameter.\",
    \"propertyOrder\" : 440,
    \"required\" : true,
    \"type\" : \"boolean\",
    \"exampleValue\" : \"\"
  },
  \"keypairName\" : {
    \"title\" : \"Token Signing RSA Public/Private Key Pair\",
    \"description\" : \"The public/private key pair used by RS256.<br><br>The
public/private key pair will be retrieved from the keystore referenced by the property
<code>com.sun.identity.saml.xmlsig.keystore</code>.\",
    \"propertyOrder\" : 240,
    \"required\" : true,
    \"type\" : \"string\",
    \"exampleValue\" : \"\"
  },
  \"supportedSubjectTypes\" : {
    \"title\" : \"Subject Types supported\",
    \"description\" : \"List of subject types supported. Valid values are:<ul><li><code>public</
code> - Each client receives the same subject (<code>sub</code>) value.</li><li><code>pairwise</code>
- Each client receives a different subject (<code>sub</code>) value, to prevent correlation between
clients.</li></ul>\",
    \"propertyOrder\" : 150,
    \"required\" : true,
    \"items\" : {
      \"type\" : \"string\"
    },
    \"type\" : \"array\",
    \"exampleValue\" : \"\"
  },
  \"scopeImplementationClass\" : {
    \"title\" : \"Scope Implementation Class\",
    \"description\" : \"The class that contains the required scope implementation, must implement
the <code>org.forgerock.oauth2.core.ScopeValidator</code> interface.\",
    \"propertyOrder\" : 70,
    \"required\" : true,
    \"type\" : \"string\",
    \"exampleValue\" : \"\"
  },
  \"responseTypeClasses\" : {

```

```

    "title" : "Response Type Plugins",
    "description" : "List of plugins that handle the valid <code>response_type</code>
values.<br><br>OAuth 2.0 clients pass response types as parameters to the OAuth 2.0 Authorization
endpoint (<code>/oauth2/authorize</code>) to indicate which grant type is requested from the
provider. For example, the client passes <code>code</code> when requesting an authorization code,
and <code>token</code> when requesting an access token.<p><p>Values in this list take the form
<code>response-type|plugin-class-name</code>.",
    "propertyOrder" : 90,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "tokenEncryptionEnabled" : {
    "title" : "Enable Stateless Token Encryption",
    "description" : "Whether stateless access and refresh tokens should be
encrypted.<br><br>Enabling token encryption will disable token signing as encryption is performed
using direct symmetric encryption.",
    "propertyOrder" : 242,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "codeVerifierEnforced" : {
    "title" : "Code Verifier Parameter Required",
    "description" : "If enabled, requests using the authorization code grant require a
<code>code_challenge</code> attribute.<br><br>For more information, read the <a href=\"https://
tools.ietf.org/html/draft-ietf-oauth-spop-12\">draft specification for this feature</a>.",
    "propertyOrder" : 270,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "defaultScopes" : {
    "title" : "Default Client Scopes",
    "description" : "List of scopes a client will be granted if they request registration
without specifying which scopes they want. Default scopes are NOT auto-granted to clients created
through the OpenAM console.",
    "propertyOrder" : 200,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "modifiedTimestampAttribute" : {
    "title" : "Modified Timestamp Attribute Name",
    "description" : "The identity Data Store attribute used to return modified timestamp
values.",
    "propertyOrder" : 340,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenSigningAlgorithm" : {
    "title" : "OAuth2 Token Signing Algorithm",

```

```

        "description" : "Algorithm used to sign stateless OAuth 2.0 tokens in order to detect tampering.<br><br>OpenAM supports signing algorithms listed in JSON Web Algorithms (JWA): <a href='\"http://tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\">\"alg \\\" (Algorithm) Header Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC with SHA-256.</li><li><code>HS384</code> - HMAC with SHA-384.</li><li><code>HS512</code> - HMAC with SHA-512.</li><li><code>ES256</code> - ECDSA with SHA-256 and NIST standard P-256 elliptic curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and NIST standard P-384 elliptic curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard P-521 elliptic curve.</li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>\",
        "propertyOrder" : 220,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "authenticationAttributes" : {
        "title" : "User Profile Attribute(s) the Resource Owner is Authenticated On",
        "description" : "Names of profile attributes that resource owners use to log in. You can add others to the default, for example <code>mail</code>.",
        "propertyOrder" : 100,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "tokenEncryptionKeyAlias" : {
        "title" : "Token Encryption Secret Key Alias",
        "description" : "The secret key used for encryption.<br><br>The secret key will be retrieved from the keystore referenced by the property <code>com.sun.identity.saml.xmlsig.keystore</code>.",
        "propertyOrder" : 243,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "hashSalt" : {
        "title" : "Subject Identifier Hash Salt",
        "description" : "If <i>pairwise</i> subject types are supported, it is <em>STRONGLY RECOMMENDED</em> to change this value. It is used in the salting of hashes for returning specific <code>sub</code> claims to individuals using the same <code>request_uri</code> or <code>sector_identifier_uri</code>.",
        "propertyOrder" : 260,
        "required" : false,
        "type" : "string",
        "exampleValue" : "changeme"
    },
    "tokenSigningHmacSharedSecret" : {
        "title" : "Token Signing HMAC Shared Secret",
        "description" : "Base64-encoded key used by HS256, HS384 and HS512.",
        "propertyOrder" : 230,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "supportedScopes" : {
        "title" : "Supported Scopes",
        "description" : "The set of supported scopes, with translations.<br><br><p>Scopes may be entered as simple strings or pipe-separated strings representing the internal scope name, locale,
    
```

and localized description.

For example: `read|en|Permission to view email messages in your account`

Locale strings are in the format: `language_country_variant`, for example `en`, `en_GB`, or `en_US_WIN`.

If the locale and pipe is omitted, the description is displayed to all users that have undefined locales.

If the description is also omitted, nothing is displayed on the consent page for the scope. For example specifying `read|` would allow the scope read to be used by the client, but would not display it to the user on the consent page when requested.

```

    "propertyOrder" : 130,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "createdTimestampAttribute" : {
    "title" : "Created Timestamp Attribute Name",
    "description" : "The identity Data Store attribute used to return created timestamp
values.",
    "propertyOrder" : 350,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "displayNameAttribute" : {
    "title" : "User Display Name attribute",
    "description" : "The profile attribute that contains the name to be displayed for the user
on the consent page.",
    "propertyOrder" : 120,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"advancedOIDCConfig" : {
  "type" : "object",
  "title" : "Advanced OpenID Connect",
  "propertyOrder" : 4,
  "properties" : {
    "supportedRequestParameterEncryptionEnc" : {
      "title" : "Request Parameter Encryption Methods Supported",
      "description" : "Encryption methods supported to decrypt Request parameter.<br><br>OpenAM
supports the following Request parameter encryption algorithms:<ul><li><code>A128GCM</code>,
<code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated
encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-
HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
      "propertyOrder" : 444,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "supportedRequestParameterSigningAlgorithms" : {
      "title" : "Request Parameter Signing Algorithms Supported",
      "description" : "Algorithms supported to verify signature of Request parameterOpenAM
supports signing algorithms listed in JSON Web Algorithms (JWA): <a href=\"http://tools.ietf.org/

```



```

html/draft-ietf-jose-json-web-algorithms#section-3.1">\"alg\" (Algorithm) Header Parameter Values
for JWS</a>:<ul><li><code>HS256</code> - HMAC with SHA-256.</li><li><code>HS384</code> - HMAC with
SHA-384.</li><li><code>HS512</code> - HMAC with SHA-512.</li><li><code>ES256</code> - ECDSA with
SHA-256 and NIST standard P-256 elliptic curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and
NIST standard P-384 elliptic curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard
P-521 elliptic curve.</li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>\",
  \"propertyOrder\" : 442,
  \"required\" : true,
  \"items\" : {
    \"type\" : \"string\"
  },
  \"type\" : \"array\",
  \"exampleValue\" : \"\"
},
\"idTokenInfoClientAuthenticationEnabled\" : {
  \"title\" : \"Idtokeninfo Endpoint Requires Client Authentication\",
  \"description\" : \"When enabled, the <code>/oauth2/idtokeninfo</code> endpoint requires
client authentication if the signing algorithm is set to <code>HS256</code>, <code>HS384</code>, or
<code>HS512</code>.\",
  \"propertyOrder\" : 225,
  \"required\" : true,
  \"type\" : \"boolean\",
  \"exampleValue\" : \"\"
},
\"alwaysAddClaimsToToken\" : {
  \"title\" : \"Always Return Claims in ID Tokens\",
  \"description\" : \"If enabled, include scope-derived claims in the <code>id_token</code>,
even if an access token is also returned that could provide access to get the claims from the
<code>userinfo</code> endpoint.<br><br>If not enabled, if an access token is requested the client
must use it to access the <code>userinfo</code> endpoint for scope-derived claims, as they will not
be included in the ID token.\",
  \"propertyOrder\" : 360,
  \"required\" : true,
  \"type\" : \"boolean\",
  \"exampleValue\" : \"\"
},
\"authorisedOpenIdConnectSSOClients\" : {
  \"title\" : \"Authorized OIDC SSO Clients\",
  \"description\" : \"Clients authorized to use OpenID Connect ID tokens as SSO
Tokens.<br><br>Allows clients to act with the full authority of the user. Grant this permission only
to trusted clients.\",
  \"propertyOrder\" : 446,
  \"required\" : true,
  \"items\" : {
    \"type\" : \"string\"
  },
  \"type\" : \"array\",
  \"exampleValue\" : \"\"
},
\"amrMappings\" : {
  \"title\" : \"OpenID Connect id_token amr Values to Auth Module Mappings\",
  \"description\" : \"Specify <code>amr</code> values to be returned in the OpenID Connect
<code>id_token</code>. Once authentication has completed, the authentication modules that were used
from the authentication service will be mapped to the <code>amr</code> values. If you do not require
<code>amr</code> values, or are not providing OpenID Connect tokens, leave this field blank.\",
  \"propertyOrder\" : 330,
  \"required\" : false,
  \"patternProperties\" : {
    \".*\" : { }
  }
}

```

```

    },
    "type" : "object",
    "exampleValue" : ""
  },
  "requireRequestUriRegistration" : {
    "title" : "Require Pre-registered request_uri Values",
    "description" : "When enabled, any <code>request_uri</code> values used must be pre-registered using the <code>request_uris</code> registration parameter.",
    "propertyOrder" : 445,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "supportedRequestParameterEncryptionAlgorithms" : {
    "title" : "Request Parameter Encryption Algorithms Supported",
    "description" : "Encryption algorithms supported to decrypt Request parameter.<br><br>OpenAM supports the following ID token encryption algorithms:<ul><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption Padding (OAEP) with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256 and MGF-1.</li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client secret.</li><li><code>RSA1 5</code> - RSA with PKCS#1 v1.5 padding.</li><li><code>A256KW</code> - AES Key Wrapping with 256-bit key derived from the client secret.</li><li><code>dir</code> - Direct encryption with AES using the hashed client secret.</li><li><code>A192KW</code> - AES Key Wrapping with 192-bit key derived from the client secret.</li></ul>",
    "propertyOrder" : 443,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "claimsParameterSupported" : {
    "title" : "Enable \"claims_parameter_supported\"",
    "description" : "If enabled, clients will be able to request individual claims using the <code>claims</code> request parameter, as per <a href=\"http://openid.net/specs/openid-connect-core-1_0.html#ClaimsParameter\" target=\"_blank\">section 5.5 of the OpenID Connect specification</a>.",
    "propertyOrder" : 250,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "storeOpsTokens" : {
    "title" : "Store Ops Tokens",
    "description" : "Whether OpenAM will store the <i>ops</i> tokens corresponding to OpenID Connect sessions in the CTS store. Note that session management related endpoints will not work when this setting is disabled.",
    "propertyOrder" : 410,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "loaMapping" : {
    "title" : "OpenID Connect acr_values to Auth Chain Mapping",
    "description" : "Maps OpenID Connect ACR values to authentication chains. For more details, see the <a href=\"http://openid.net/specs/openid-connect-core-1_0.html#AuthRequest\" target=\"_blank\">acr_values parameter</a> in the OpenID Connect authentication request specification.",
    "propertyOrder" : 310,

```

```

        "required" : false,
        "patternProperties" : {
            ".*" : { }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "jwksURI" : {
        "title" : "Remote JSON Web Key URL",
        "description" : "The Remote URL where the providers JSON Web Key can be retrieved.<p><p>If
this setting is not configured, then OpenAM provides a local URL to access the public key of the
private key used to sign ID tokens.",
        "propertyOrder" : 140,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "defaultACR" : {
        "title" : "Default ACR values",
        "description" : "Default requested Authentication Context Class Reference
values.<br><br>List of strings that specifies the default acr values that the OP is being requested
to use for processing requests from this Client, with the values appearing in order of preference.
The Authentication Context Class satisfied by the authentication performed is returned as the
acr Claim Value in the issued ID Token. The acr Claim is requested as a Voluntary Claim by this
parameter. The acr_values_supported discovery element contains a list of the acr values supported by
this server. Values specified in the acr_values request parameter or an individual acr Claim request
override these default values.",
        "propertyOrder" : 320,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"coreOIDCConfig" : {
    "type" : "object",
    "title" : "OpenID Connect",
    "propertyOrder" : 3,
    "properties" : {
        "supportedIDTokenSigningAlgorithms" : {
            "title" : "ID Token Signing Algorithms supported",
            "description" : "Algorithms supported to sign OpenID Connect <code>id_tokens</
code>.<p><p>OpenAM supports signing algorithms listed in JSON Web Algorithms (JWA): <a href=\"http://
tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\">\"alg\" (Algorithm) Header
Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC with SHA-256.</li><li><code>HS384</
code> - HMAC with SHA-384.</li><li><code>HS512</code> - HMAC with SHA-512.</li><li><code>ES256</code>
- ECDSA with SHA-256 and NIST standard P-256 elliptic curve.</li><li><code>ES384</code> - ECDSA with
SHA-384 and NIST standard P-384 elliptic curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and
NIST standard P-521 elliptic curve.</li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</
li></ul>",
            "propertyOrder" : 160,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",

```

```

        "exampleValue" : ""
    },
    "supportedIDTokenEncryptionMethods" : {
        "title" : "ID Token Encryption Methods supported",
        "description" : "Encryption methods supported to encrypt OpenID Connect ID tokens
in order to hide its contents.<br><br>OpenAM supports the following ID token encryption
algorithms:<ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> - AES
in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>,
<code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-
SHA-2 for integrity.</li></ul>",
        "propertyOrder" : 180,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "oidcClaimsScript" : {
        "title" : "OIDC Claims Script",
        "description" : "The script that is run when issuing an ID token or making a request to the
<i>userinfo</i> endpoint during OpenID requests.<p><p>The script gathers the scopes and populates
claims, and has access to the access token, the user's identity and, if available, the user's
session.",
        "propertyOrder" : 80,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "tokenEncryptionSigningKeyAlias" : {
        "title" : "Token Encryption RSA Public/Private Key Pair Alias",
        "description" : "The list of public/private key pairs used for the RSA algorithms (RSA1_5/
RSA-OAEP/RSA-OAEP-256). Add an entry to specify an alias for a specific RSA algorithm, for example
<code>RSA1_5|rsa1_5Alias</code>.<br><br>Each of the public/private key pairs will be retrieved from
the keystore referenced by the property <code>com.sun.identity.saml.xmlsig.keystore.</code>.",
        "propertyOrder" : 441,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "jwtTokenLifetime" : {
        "title" : "OpenID Connect JWT Token Lifetime (seconds)",
        "description" : "The amount of time the JWT will be valid for, in seconds.",
        "propertyOrder" : 210,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "supportedIDTokenEncryptionAlgorithms" : {
        "title" : "ID Token Encryption Algorithms supported",
        "description" : "Encryption algorithms supported to encrypt OpenID Connect ID tokens
in order to hide its contents.<br><br>OpenAM supports the following ID token encryption
algorithms:<ul><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption Padding (OAEP)
with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256 and MGF-1.</
li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client secret.</
li><li><code>RSA1_5</code> - RSA with PKCS#1 v1.5 padding.</li><li><code>A256KW</code> - AES
    
```

```

Key Wrapping with 256-bit key derived from the client secret.</li><li><code>dir</code> - Direct
encryption with AES using the hashed client secret.</li><li><code>A192KW</code> - AES Key Wrapping
with 192-bit key derived from the client secret.</li></ul>",
    "propertyOrder" : 170,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"supportedClaims" : {
    "title" : "Supported Claims",
    "description" : "Set of claims supported by the OpenID Connect <code>/oauth2/userinfo</
code> endpoint, with translations.<br><br>Claims may be entered as simple strings or pipe separated
strings representing the internal claim name, locale, and localized description.<p><p>For example:
<code>name|en|Your full name.</code>.<p>Locale strings are in the format: <code>language +
\"_\" + country + \"_\" + variant</code>, for example <code>en</code>, <code>en_GB</code>, or
<code>en_US_WIN</code>. If the locale and pipe is omitted, the description is displayed to all users
that have undefined locales.<p><p>If the description is also omitted, nothing is displayed on the
consent page for the claim. For example specifying <code>family_name</code> would allow the claim
<code>family_name</code> to be used by the client, but would not display it to the user on the
consent page when requested.",
    "propertyOrder" : 190,
    "required" : false,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
}
}
},
"deviceCodeConfig" : {
    "type" : "object",
    "title" : "Device Flow",
    "propertyOrder" : 5,
    "properties" : {
        "devicePollInterval" : {
            "title" : "Device Polling Interval",
            "description" : "The polling frequency for devices waiting for tokens when using the device
code flow.",
            "propertyOrder" : 400,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "deviceCodeLifetime" : {
            "title" : "Device Code Lifetime (seconds)",
            "description" : "The lifetime of the device code, in seconds.",
            "propertyOrder" : 390,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "verificationUrl" : {
            "title" : "Verification URL",
            "description" : "The URL that the user will be instructed to visit to complete their OAuth
2.0 login and consent when using the device code flow.",

```

```

    "propertyOrder" : 370,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "completionUrl" : {
    "title" : "Device Completion URL",
    "description" : "The URL that the user will be sent to on completion of their OAuth 2.0
login and consent when using the device code flow.",
    "propertyOrder" : 380,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"clientDynamicRegistrationConfig" : {
  "type" : "object",
  "title" : "Client Dynamic Registration",
  "propertyOrder" : 2,
  "properties" : {
    "generateRegistrationAccessTokens" : {
      "title" : "Generate Registration Access Tokens",
      "description" : "Whether to generate Registration Access Tokens for clients that register by
using open dynamic client registration. Such tokens allow the client to access the <a href='\"http://
openid.net/specs/openid-connect-registration-1_0.html#ClientConfigurationEndpoint\" target='\"_blank
\">Client Configuration Endpoint</a> as per the OpenID Connect specification. This setting has no
effect if Allow Open Dynamic Client Registration is disabled.",
      "propertyOrder" : 290,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "dynamicClientRegistrationScope" : {
      "title" : "Scope to give access to dynamic client registration",
      "description" : "Mandatory scope required when registering a new OAuth2 client.",
      "propertyOrder" : 455,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "requiredSoftwareStatementAttestedAttributes" : {
      "title" : "Required Software Statement Attested Attributes",
      "description" : "The client attributes that are required to be present in the software
statement JWT when registering an OAuth 2.0 client dynamically. Only applies if Require Software
Statements for Dynamic Client Registration is enabled.<br><br>Leave blank to allow any attributes to
be present.",
      "propertyOrder" : 272,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "dynamicClientRegistrationSoftwareStatementRequired" : {
      "title" : "Require Software Statement for Dynamic Client Registration",
      "description" : "When enabled, a software statement JWT containing at least the <code>iss</
code> (issuer) claim must be provided when registering an OAuth 2.0 client dynamically.",

```

```

        "propertyOrder" : 271,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "allowDynamicRegistration" : {
        "title" : "Allow Open Dynamic Client Registration",
        "description" : "Allow clients to register without an access token. If enabled, you
        should consider adding some form of rate limiting. For more information, see <a href=\"http://
        openid.net/specs/openid-connect-registration-1_0.html#ClientRegistration\" target=\"_blank\">Client
        Registration</a> in the OpenID Connect specification.",
        "propertyOrder" : 280,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"core0Auth2Config" : {
    "type" : "object",
    "title" : "Core",
    "propertyOrder" : 0,
    "properties" : {
        "issueRefreshTokenOnRefreshedToken" : {
            "title" : "Issue Refresh Tokens on Refreshing Access Tokens",
            "description" : "Whether to issue a refresh token when refreshing an access token.",
            "propertyOrder" : 50,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "usePolicyEngineForScope" : {
            "title" : "Use Policy Engine for Scope decisions",
            "description" : "With this setting enabled, the policy engine is consulted for each scope
            value that is requested.<br><br>If a policy returns an action of GRANT=true, the scope is consented
            automatically, and the user is not consulted in a user-interaction flow. If a policy returns an
            action of GRANT=false, the scope is not added to any resulting token, and the user will not see it
            in a user-interaction flow. If no policy returns a value for the GRANT action, then if the grant type
            is user-facing (i.e. authorization or device code flows), the user is asked for consent (or saved
            consent is used), and if the grant type is not user-facing (password or client credentials), the
            scope is not added to any resulting token.",
            "propertyOrder" : 55,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "codeLifetime" : {
            "title" : "Authorization Code Lifetime (seconds)",
            "description" : "The time an authorization code is valid for, in seconds.",
            "propertyOrder" : 10,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "issueRefreshToken" : {
            "title" : "Issue Refresh Tokens",
            "description" : "Whether to issue a refresh token when returning an access token.",
            "propertyOrder" : 40,
            "required" : true,

```

```

    "type" : "boolean",
    "exampleValue" : ""
  },
  "statelessTokensEnabled" : {
    "title" : "Use Stateless Access & Refresh Tokens",
    "description" : "When enabled, OpenAM issues access and refresh tokens that can be inspected
by resource servers.",
    "propertyOrder" : 3,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "accessTokenLifetime" : {
    "title" : "Access Token Lifetime (seconds)",
    "description" : "The time an access token is valid for, in seconds.",
    "propertyOrder" : 30,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "refreshTokenLifetime" : {
    "title" : "Refresh Token Lifetime (seconds)",
    "description" : "The time in seconds a refresh token is valid for. If this field is set to
<code>-1</code>, the token will never expire.",
    "propertyOrder" : 20,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
},
"consent" : {
  "type" : "object",
  "title" : "Consent",
  "propertyOrder" : 6,
  "properties" : {
    "supportedRcsResponseEncryptionMethods" : {
      "title" : "Remote Consent Service Response Encryption Methods Supported",
      "description" : "Encryption methods supported to decrypt Remote Consent Service
responses.<br><br>OpenAM supports the following encryption methods:<ul><li><code>A128GCM</code>,
<code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated
encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-
HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
      "propertyOrder" : 454,
      "required" : true,
      "items" : {
        "type" : "string"
      },
    },
    "type" : "array",
    "exampleValue" : ""
  },
},
"enableRemoteConsent" : {
  "title" : "Enable Remote Consent",
  "description" : "",
  "propertyOrder" : 447,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
},

```



```

"supportedRcsRequestSigningAlgorithms" : {
  "title" : "Remote Consent Service Request Signing Algorithms Supported",
  "description" : "Algorithms supported to sign consent request JWTs for Remote Consent
Services.<br><br>OpenAM supports signing algorithms listed in JSON Web Algorithms (JWA): <a
href=\"http://tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\">\alg
\" (Algorithm) Header Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC with
SHA-256.</li><li><code>HS384</code> - HMAC with SHA-384.</li><li><code>HS512</code> - HMAC
with SHA-512.</li><li><code>ES256</code> - ECDSA with SHA-256 and NIST standard P-256 elliptic
curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and NIST standard P-384 elliptic
curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard P-521 elliptic curve.</
li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>",
  "propertyOrder" : 449,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"supportedRcsRequestEncryptionMethods" : {
  "title" : "Remote Consent Service Request Encryption Methods Supported",
  "description" : "Encryption methods supported to encrypt Remote Consent Service
requests.<br><br>OpenAM supports the following encryption methods:<ul><li><code>A128GCM</code>,
<code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated
encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-
HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 451,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"savedConsentAttribute" : {
  "title" : "Saved Consent Attribute Name",
  "description" : "Name of a multi-valued attribute on resource owner profiles where OpenAM
can save authorization consent decisions.<p><p>When the resource owner chooses to save the decision
to authorize access for a client application, then OpenAM updates the resource owner's profile to
avoid having to prompt the resource owner to grant authorization when the client issues subsequent
authorization requests.",
  "propertyOrder" : 110,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"supportedRcsRequestEncryptionAlgorithms" : {
  "title" : "Remote Consent Service Request Encryption Algorithms Supported",
  "description" : "Encryption algorithms supported to encrypt Remote Consent Service
requests.<br><br>OpenAM supports the following encryption algorithms:<ul><li><code>RSA1_5</code> -
RSA with PKCS#1 v1.5 padding.</li><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption
Padding (OAEP) with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256
and MGF-1.</li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client
secret.</li><li><code>A192KW</code> - AES Key Wrapping with 192-bit key derived from the client
secret.</li><li><code>A256KW</code> - AES Key Wrapping with 256-bit key derived from the client
secret.</li><li><code>dir</code> - Direct encryption with AES using the hashed client secret.</li></
ul>",
  "propertyOrder" : 450,
  "required" : true,

```

```

        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "supportedRcsResponseSigningAlgorithms" : {
        "title" : "Remote Consent Service Response Signing Algorithms Supported",
        "description" : "Algorithms supported to verify signed consent_response JWT from Remote Consent Services.<br><br>OpenAM supports signing algorithms listed in JSON Web Algorithms (JWA): <a href='\"http://tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\"'>\"alg\" (Algorithm) Header Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC with SHA-256.</li><li><code>HS384</code> - HMAC with SHA-384.</li><li><code>HS512</code> - HMAC with SHA-512.</li><li><code>ES256</code> - ECDSA with SHA-256 and NIST standard P-256 elliptic curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and NIST standard P-384 elliptic curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard P-521 elliptic curve.</li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>",
        "propertyOrder" : 452,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "remoteConsentServiceId" : {
        "title" : "Remote Consent Service ID",
        "description" : "The ID of an existing remote consent service agent.",
        "propertyOrder" : 448,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "supportedRcsResponseEncryptionAlgorithms" : {
        "title" : "Remote Consent Service Response Encryption Algorithms Supported",
        "description" : "Encryption algorithms supported to decrypt Remote Consent Service responses.<br><br>OpenAM supports the following encryption algorithms:<ul><li><code>RSA1_5</code> - RSA with PKCS#1 v1.5 padding.</li><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption Padding (OAEP) with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256 and MGF-1.</li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client secret.</li><li><code>A192KW</code> - AES Key Wrapping with 192-bit key derived from the client secret.</li><li><code>A256KW</code> - AES Key Wrapping with 256-bit key derived from the client secret.</li><li><code>dir</code> - Direct encryption with AES using the hashed client secret.</li></ul>",
        "propertyOrder" : 453,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "clientsCanSkipConsent" : {
        "title" : "Allow Clients to Skip Consent",
        "description" : "If enabled, clients may be configured so that the resource owner will not be asked for consent during authorization flows.",
        "propertyOrder" : 420,
        "required" : true,
        "type" : "boolean",
    }

```

```
    "exampleValue" : ""  
  }  
} }  
}
```

1.101.1.2. delete

Usage:

```
am> delete OAuth2Provider --realm Realm
```

1.101.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OAuth2Provider --realm Realm --actionName getAllTypes
```

1.101.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OAuth2Provider --realm Realm --actionName getCreatableTypes
```

1.101.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OAuth2Provider --realm Realm --actionName nextdescendents
```

1.101.1.6. read

Usage:

```
am> read OAuth2Provider --realm Realm
```

1.101.1.7. update

Usage:

```
am> update OAuth2Provider --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "advanced0Auth2Config" : {
      "type" : "object",
      "title" : "Advanced",
      "propertyOrder" : 1,
      "properties" : {
        "tokenSigningECDSAKeyAlias" : {
          "title" : "Token Signing ECDSA Public/Private Key Pair Alias",
          "description" : "The list of public/private key pairs used for the elliptic curve algorithms (ES256/ES384/ES512). Add an entry to specify an alias for a specific elliptic curve algorithm, for example <code>ES256|es256Alias</code>.<br><br>Each of the public/private key pairs will be retrieved from the keystore referenced by the property <code>com.sun.identity.saml.xmlsig.keystore</code>.",
          "propertyOrder" : 241,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "tokenCompressionEnabled" : {
          "title" : "Stateless Token Compression",
          "description" : "Whether stateless access and refresh tokens should be compressed.",
          "propertyOrder" : 223,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "customLoginUrlTemplate" : {
          "title" : "Custom Login URL Template",
          "description" : "Custom URL for handling login, to override the default OpenAM login page.<br><br>Supports Freemarker syntax, with the following variables:<table><tr><th>Variable</th><th>Description</th></tr><tr><td><code>gotoUrl</code></td><td><p>The URL to redirect to after login.</p></td></tr><tr><td><code>acrValues</code></td><td><p>The Authentication Context Class Reference (acr) values for the authorization request.</p></td></tr><tr><td><code>realm</code></td><td><p>The OpenAM realm the authorization request was made on.</p></td></tr><tr><td><code>module</code></td><td><p>The name of the OpenAM authentication module requested to perform resource owner authentication.</p></td></tr><tr><td><code>service</code></td><td><p>The name of the OpenAM authentication chain requested to perform resource owner authentication.</p></td></tr><tr><td><code>locale</code></td><td><p>A space-separated list of locales, ordered by preference.</p></td></tr></table>The following example template redirects users to a non-OpenAM front end to handle login, which will then redirect back to the <code>/oauth2/authorize</code> endpoint with any required parameters:<p> <code>http://mylogin.com/login?goto=${goto}&lt;#if acrValues??&gt;&amp;acr_values=${acrValues}&lt;#x2F;#if&gt;&lt;#if realm??&gt;&amp;realm=${realm}&lt;#x2F;#if&gt;&lt;#if module??&gt;&amp;module=${module}&lt;#x2F;#if&gt;&lt;#if service??&gt;&amp;service=${service}&lt;#x2F;#if&gt;&lt;#if locale??&gt;&amp;locale=${locale}&lt;#x2F;#if&gt;&lt;/code><br><b>NOTE</b>: Default OpenAM login page is constructed using \"Base URL Source\" service.",
          "propertyOrder" : 60,
          "required" : false,
          "type" : "string",

```

```

    "exampleValue" : ""
  },
  "moduleMessageEnabledInPasswordGrant" : {
    "title" : "Enable Auth Module Messages for Password Credentials Grant",
    "description" : "If enabled, authentication module failure messages are used to create Resource Owner Password Credentials Grant failure messages. If disabled, a standard authentication failed message is used.<br><br>The Password Grant Type requires the <code>grant_type=password</code> parameter.",
    "propertyOrder" : 440,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "keypairName" : {
    "title" : "Token Signing RSA Public/Private Key Pair",
    "description" : "The public/private key pair used by RS256.<br><br>The public/private key pair will be retrieved from the keystore referenced by the property <code>com.sun.identity.saml.xmlsig.keystore</code>.",
    "propertyOrder" : 240,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "supportedSubjectTypes" : {
    "title" : "Subject Types supported",
    "description" : "List of subject types supported. Valid values are:<ul><li><code>public</code> - Each client receives the same subject (<code>sub</code>) value.</li><li><code>pairwise</code> - Each client receives a different subject (<code>sub</code>) value, to prevent correlation between clients.</li></ul>",
    "propertyOrder" : 150,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "scopeImplementationClass" : {
    "title" : "Scope Implementation Class",
    "description" : "The class that contains the required scope implementation, must implement the <code>org.forgerock.oauth2.core.ScopeValidator</code> interface.",
    "propertyOrder" : 70,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "responseTypeClasses" : {
    "title" : "Response Type Plugins",
    "description" : "List of plugins that handle the valid <code>response_type</code> values.<br><br>OAuth 2.0 clients pass response types as parameters to the OAuth 2.0 Authorization endpoint (<code>/oauth2/authorize</code>) to indicate which grant type is requested from the provider. For example, the client passes <code>code</code> when requesting an authorization code, and <code>token</code> when requesting an access token.<p><p>Values in this list take the form <code>response-type|plugin-class-name</code>.",
    "propertyOrder" : 90,
    "required" : true,
    "items" : {
      "type" : "string"
    }
  },

```

```

        "type" : "array",
        "exampleValue" : ""
    },
    "tokenEncryptionEnabled" : {
        "title" : "Enable Stateless Token Encryption",
        "description" : "Whether stateless access and refresh tokens should be
encrypted.<br><br>Enabling token encryption will disable token signing as encryption is performed
using direct symmetric encryption.",
        "propertyOrder" : 242,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "codeVerifierEnforced" : {
        "title" : "Code Verifier Parameter Required",
        "description" : "If enabled, requests using the authorization code grant require a
<code>code_challenge</code> attribute.<br><br>For more information, read the <a href=\"https://
tools.ietf.org/html/draft-ietf-oauth-spop-12\">draft specification for this feature</a>.",
        "propertyOrder" : 270,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "defaultScopes" : {
        "title" : "Default Client Scopes",
        "description" : "List of scopes a client will be granted if they request registration
without specifying which scopes they want. Default scopes are NOT auto-granted to clients created
through the OpenAM console.",
        "propertyOrder" : 200,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "modifiedTimestampAttribute" : {
        "title" : "Modified Timestamp Attribute Name",
        "description" : "The identity Data Store attribute used to return modified timestamp
values.",
        "propertyOrder" : 340,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "tokenSigningAlgorithm" : {
        "title" : "OAuth2 Token Signing Algorithm",
        "description" : "Algorithm used to sign stateless OAuth 2.0 tokens in order to detect
tampering.<br><br>OpenAM supports signing algorithms listed in JSON Web Algorithms (JWA):
<a href=\"http://tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\">\alg
\" (Algorithm) Header Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC with
SHA-256.</li><li><code>HS384</code> - HMAC with SHA-384.</li><li><code>HS512</code> - HMAC
with SHA-512.</li><li><code>ES256</code> - ECDSA with SHA-256 and NIST standard P-256 elliptic
curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and NIST standard P-384 elliptic
curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard P-521 elliptic curve.</
li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>",
        "propertyOrder" : 220,
        "required" : true,
        "type" : "string",
    }

```

```

    "exampleValue" : ""
  },
  "authenticationAttributes" : {
    "title" : "User Profile Attribute(s) the Resource Owner is Authenticated On",
    "description" : "Names of profile attributes that resource owners use to log in. You can add
others to the default, for example <code>mail</code>.",
    "propertyOrder" : 100,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "tokenEncryptionKeyAlias" : {
    "title" : "Token Encryption Secret Key Alias",
    "description" : "The secret key used for encryption.<br><br>The secret key will be retrieved
from the keystore referenced by the property <code>com.sun.identity.saml.xmlsig.keystore</code>.",
    "propertyOrder" : 243,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "hashSalt" : {
    "title" : "Subject Identifier Hash Salt",
    "description" : "If <i>pairwise</i> subject types are supported, it is <em>STRONGLY
RECOMMENDED</em> to change this value. It is used in the salting of hashes for returning
specific <code>sub</code> claims to individuals using the same <code>request_uri</code> or
<code>sector_identifier_uri</code>.",
    "propertyOrder" : 260,
    "required" : false,
    "type" : "string",
    "exampleValue" : "changeme"
  },
  "tokenSigningHmacSharedSecret" : {
    "title" : "Token Signing HMAC Shared Secret",
    "description" : "Base64-encoded key used by HS256, HS384 and HS512.",
    "propertyOrder" : 230,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "supportedScopes" : {
    "title" : "Supported Scopes",
    "description" : "The set of supported scopes, with translations.<br><br><p>Scopes may be
entered as simple strings or pipe-separated strings representing the internal scope name, locale,
and localized description.</p><p>For example: <code>read|en|Permission to view email messages in
your account</code></p><p>Locale strings are in the format: <code>language_country_variant</code>,
for example <code>en</code>, <code>en_GB</code>, or <code>en_US_WIN</code>.</p><p>If the locale and
pipe is omitted, the description is displayed to all users that have undefined locales.</p><p>If
the description is also omitted, nothing is displayed on the consent page for the scope. For example
specifying <code>read</code> would allow the scope read to be used by the client, but would not
display it to the user on the consent page when requested.</p>",
    "propertyOrder" : 130,
    "required" : true,
    "items" : {
      "type" : "string"
    },
  },

```

```

        "type" : "array",
        "exampleValue" : ""
    },
    "createdTimestampAttribute" : {
        "title" : "Created Timestamp Attribute Name",
        "description" : "The identity Data Store attribute used to return created timestamp
values.",
        "propertyOrder" : 350,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "displayNameAttribute" : {
        "title" : "User Display Name attribute",
        "description" : "The profile attribute that contains the name to be displayed for the user
on the consent page.",
        "propertyOrder" : 120,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"advancedOIDCConfig" : {
    "type" : "object",
    "title" : "Advanced OpenID Connect",
    "propertyOrder" : 4,
    "properties" : {
        "supportedRequestParameterEncryptionEnc" : {
            "title" : "Request Parameter Encryption Methods Supported",
            "description" : "Encryption methods supported to decrypt Request parameter.<br><br>OpenAM
supports the following Request parameter encryption algorithms:<ul><li><code>A128GCM</code>,
<code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated
encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-
HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
            "propertyOrder" : 444,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "supportedRequestParameterSigningAlgorithms" : {
            "title" : "Request Parameter Signing Algorithms Supported",
            "description" : "Algorithms supported to verify signature of Request parameterOpenAM
supports signing algorithms listed in JSON Web Algorithms (JWA): <a href=\"http://tools.ietf.org/
html/draft-ietf-jose-json-web-algorithms#section-3.1\">\alg\" (Algorithm) Header Parameter Values
for JWS</a><ul><li><code>HS256</code> - HMAC with SHA-256.</li><li><code>HS384</code> - HMAC with
SHA-384.</li><li><code>HS512</code> - HMAC with SHA-512.</li><li><code>ES256</code> - ECDSA with
SHA-256 and NIST standard P-256 elliptic curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and
NIST standard P-384 elliptic curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard
P-521 elliptic curve.</li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>",
            "propertyOrder" : 442,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",

```



```

    "exampleValue" : ""
  },
  "idTokenInfoClientAuthenticationEnabled" : {
    "title" : "Idtokeninfo Endpoint Requires Client Authentication",
    "description" : "When enabled, the <code>/oauth2/idtokeninfo</code> endpoint requires
client authentication if the signing algorithm is set to <code>HS256</code>, <code>HS384</code>, or
<code>HS512</code>.",
    "propertyOrder" : 225,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "alwaysAddClaimsToToken" : {
    "title" : "Always Return Claims in ID Tokens",
    "description" : "If enabled, include scope-derived claims in the <code>id_token</code>,
even if an access token is also returned that could provide access to get the claims from the
<code>userinfo</code> endpoint.<br><br>If not enabled, if an access token is requested the client
must use it to access the <code>userinfo</code> endpoint for scope-derived claims, as they will not
be included in the ID token.",
    "propertyOrder" : 360,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "authorisedOpenIdConnectSSOClients" : {
    "title" : "Authorized OIDC SSO Clients",
    "description" : "Clients authorized to use OpenID Connect ID tokens as SSO
Tokens.<br><br>Allows clients to act with the full authority of the user. Grant this permission only
to trusted clients.",
    "propertyOrder" : 446,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "amrMappings" : {
    "title" : "OpenID Connect id_token amr Values to Auth Module Mappings",
    "description" : "Specify <code>amr</code> values to be returned in the OpenID Connect
<code>id_token</code>. Once authentication has completed, the authentication modules that were used
from the authentication service will be mapped to the <code>amr</code> values. If you do not require
<code>amr</code> values, or are not providing OpenID Connect tokens, leave this field blank.",
    "propertyOrder" : 330,
    "required" : false,
    "patternProperties" : {
      ".*" : { }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "requireRequestUriRegistration" : {
    "title" : "Require Pre-registered request_uri Values",
    "description" : "When enabled, any <code>request_uri</code> values used must be pre-
registered using the <code>request_uris</code> registration parameter.",
    "propertyOrder" : 445,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}

```

```

    },
    "supportedRequestParameterEncryptionAlgorithms" : {
        "title" : "Request Parameter Encryption Algorithms Supported",
        "description" : "Encryption algorithms supported to decrypt Request parameter.<br><br>OpenAM
        supports the following ID token encryption algorithms:<ul><li><code>RSA-OAEP</code> - RSA with
        Optimal Asymmetric Encryption Padding (OAEP) with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</
        code> - RSA with OAEP with SHA-256 and MGF-1.</li><li><code>A128KW</code> - AES Key Wrapping with
        128-bit key derived from the client secret.</li><li><code>RSA1_5</code> - RSA with PKCS#1 v1.5
        padding.</li><li><code>A256KW</code> - AES Key Wrapping with 256-bit key derived from the client
        secret.</li><li><code>dir</code> - Direct encryption with AES using the hashed client secret.</
        li><li><code>A192KW</code> - AES Key Wrapping with 192-bit key derived from the client secret.</li></
        ul>",
        "propertyOrder" : 443,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "claimsParameterSupported" : {
        "title" : "Enable \"claims_parameter_supported\"",
        "description" : "If enabled, clients will be able to request individual claims using the
        <code>claims</code> request parameter, as per <a href=\"http://openid.net/specs/openid-connect-
        core-1_0.html#ClaimsParameter\" target=\"_blank\">section 5.5 of the OpenID Connect specification</
        a>.",
        "propertyOrder" : 250,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "storeOpsTokens" : {
        "title" : "Store Ops Tokens",
        "description" : "Whether OpenAM will store the <i>ops</i> tokens corresponding to OpenID
        Connect sessions in the CTS store. Note that session management related endpoints will not work when
        this setting is disabled.",
        "propertyOrder" : 410,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "loaMapping" : {
        "title" : "OpenID Connect acr_values to Auth Chain Mapping",
        "description" : "Maps OpenID Connect ACR values to authentication chains. For more details,
        see the <a href=\"http://openid.net/specs/openid-connect-core-1_0.html#AuthRequest\" target=\"_blank
        \">acr_values parameter</a> in the OpenID Connect authentication request specification.",
        "propertyOrder" : 310,
        "required" : false,
        "patternProperties" : {
            ".*" : { }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "jwksURI" : {
        "title" : "Remote JSON Web Key URL",
        "description" : "The Remote URL where the providers JSON Web Key can be retrieved.<p><p>If
        this setting is not configured, then OpenAM provides a local URL to access the public key of the
        private key used to sign ID tokens.",
    }
}

```

```

        "propertyOrder" : 140,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "defaultACR" : {
        "title" : "Default ACR values",
        "description" : "Default requested Authentication Context Class Reference
values.<br><br>List of strings that specifies the default acr values that the OP is being requested
to use for processing requests from this Client, with the values appearing in order of preference.
The Authentication Context Class satisfied by the authentication performed is returned as the
acr Claim Value in the issued ID Token. The acr Claim is requested as a Voluntary Claim by this
parameter. The acr_values_supported discovery element contains a list of the acr values supported by
this server. Values specified in the acr_values request parameter or an individual acr Claim request
override these default values.",
        "propertyOrder" : 320,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"coreOIDCConfig" : {
    "type" : "object",
    "title" : "OpenID Connect",
    "propertyOrder" : 3,
    "properties" : {
        "supportedIDTokenSigningAlgorithms" : {
            "title" : "ID Token Signing Algorithms supported",
            "description" : "Algorithms supported to sign OpenID Connect <code>id_tokens</
code>.<p><p>OpenAM supports signing algorithms listed in JSON Web Algorithms (JWA): <a href=\"http://
tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\">\alg\" (Algorithm) Header
Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC with SHA-256.</li><li><code>HS384</
code> - HMAC with SHA-384.</li><li><code>HS512</code> - HMAC with SHA-512.</li><li><code>ES256</code>
- ECDSA with SHA-256 and NIST standard P-256 elliptic curve.</li><li><code>ES384</code> - ECDSA with
SHA-384 and NIST standard P-384 elliptic curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and
NIST standard P-521 elliptic curve.</li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</
li></ul>",
            "propertyOrder" : 160,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "supportedIDTokenEncryptionMethods" : {
            "title" : "ID Token Encryption Methods supported",
            "description" : "Encryption methods supported to encrypt OpenID Connect ID tokens
in order to hide its contents.<br><br>OpenAM supports the following ID token encryption
algorithms:<ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> - AES
in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>,
<code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-
SHA-2 for integrity.</li></ul>",
            "propertyOrder" : 180,
            "required" : true,

```

```

        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "oidcClaimsScript" : {
        "title" : "OIDC Claims Script",
        "description" : "The script that is run when issuing an ID token or making a request to the
        <i>userinfo</i> endpoint during OpenID requests.<p><p>The script gathers the scopes and populates
        claims, and has access to the access token, the user's identity and, if available, the user's
        session.",
        "propertyOrder" : 80,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "tokenEncryptionSigningKeyAlias" : {
        "title" : "Token Encryption RSA Public/Private Key Pair Alias",
        "description" : "The list of public/private key pairs used for the RSA algorithms (RSA1_5/
        RSA-OAEP/RSA-OAEP-256). Add an entry to specify an alias for a specific RSA algorithm, for example
        <code>RSA1_5|rsal_5|alias</code>.<br><br>Each of the public/private key pairs will be retrieved from
        the keystore referenced by the property <code>com.sun.identity.saml.xmlsig.keystore</code>.",
        "propertyOrder" : 441,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "jwtTokenLifetime" : {
        "title" : "OpenID Connect JWT Token Lifetime (seconds)",
        "description" : "The amount of time the JWT will be valid for, in seconds.",
        "propertyOrder" : 210,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "supportedIDTokenEncryptionAlgorithms" : {
        "title" : "ID Token Encryption Algorithms supported",
        "description" : "Encryption algorithms supported to encrypt OpenID Connect ID tokens
        in order to hide its contents.<br><br>OpenAM supports the following ID token encryption
        algorithms:<ul><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption Padding (OAEP)
        with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256 and MGF-1.</
        li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client secret.</
        li><li><code>RSA1_5</code> - RSA with PKCS#1 v1.5 padding.</li><li><code>A256KW</code> - AES
        Key Wrapping with 256-bit key derived from the client secret.</li><li><code>dir</code> - Direct
        encryption with AES using the hashed client secret.</li><li><code>A192KW</code> - AES Key Wrapping
        with 192-bit key derived from the client secret.</li></ul>",
        "propertyOrder" : 170,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "supportedClaims" : {

```

```

    "title" : "Supported Claims",
    "description" : "Set of claims supported by the OpenID Connect <code>/oauth2/userinfo/</code> endpoint, with translations.<br><br>Claims may be entered as simple strings or pipe separated strings representing the internal claim name, locale, and localized description.<p><p>For example: <code>name|en|Your full name.</code>.<p>Locale strings are in the format: <code>language + \"_\" + country + \"_\" + variant</code>, for example <code>en</code>, <code>en_GB</code>, or <code>en_US_WIN</code>. If the locale and pipe is omitted, the description is displayed to all users that have undefined locales.<p><p>If the description is also omitted, nothing is displayed on the consent page for the claim. For example specifying <code>family_name</code> would allow the claim <code>family_name</code> to be used by the client, but would not display it to the user on the consent page when requested.",
    "propertyOrder" : 190,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
},
"deviceCodeConfig" : {
  "type" : "object",
  "title" : "Device Flow",
  "propertyOrder" : 5,
  "properties" : {
    "devicePollInterval" : {
      "title" : "Device Polling Interval",
      "description" : "The polling frequency for devices waiting for tokens when using the device code flow.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "deviceCodeLifetime" : {
      "title" : "Device Code Lifetime (seconds)",
      "description" : "The lifetime of the device code, in seconds.",
      "propertyOrder" : 390,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "verificationUrl" : {
      "title" : "Verification URL",
      "description" : "The URL that the user will be instructed to visit to complete their OAuth 2.0 login and consent when using the device code flow.",
      "propertyOrder" : 370,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "completionUrl" : {
      "title" : "Device Completion URL",
      "description" : "The URL that the user will be sent to on completion of their OAuth 2.0 login and consent when using the device code flow.",
      "propertyOrder" : 380,
      "required" : false,
      "type" : "string",

```

```

        "exampleValue" : ""
    }
}
},
"clientDynamicRegistrationConfig" : {
    "type" : "object",
    "title" : "Client Dynamic Registration",
    "propertyOrder" : 2,
    "properties" : {
        "generateRegistrationAccessTokens" : {
            "title" : "Generate Registration Access Tokens",
            "description" : "Whether to generate Registration Access Tokens for clients that register by using open dynamic client registration. Such tokens allow the client to access the <a href=\"http://openid.net/specs/openid-connect-registration-1_0.html#ClientConfigurationEndpoint\" target=\"_blank\">Client Configuration Endpoint</a> as per the OpenID Connect specification. This setting has no effect if Allow Open Dynamic Client Registration is disabled.",
            "propertyOrder" : 290,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "dynamicClientRegistrationScope" : {
            "title" : "Scope to give access to dynamic client registration",
            "description" : "Mandatory scope required when registering a new OAuth2 client.",
            "propertyOrder" : 455,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "requiredSoftwareStatementAttestedAttributes" : {
            "title" : "Required Software Statement Attested Attributes",
            "description" : "The client attributes that are required to be present in the software statement JWT when registering an OAuth 2.0 client dynamically. Only applies if Require Software Statements for Dynamic Client Registration is enabled.<br><br>Leave blank to allow any attributes to be present.",
            "propertyOrder" : 272,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "dynamicClientRegistrationSoftwareStatementRequired" : {
            "title" : "Require Software Statement for Dynamic Client Registration",
            "description" : "When enabled, a software statement JWT containing at least the <code>iss</code> (issuer) claim must be provided when registering an OAuth 2.0 client dynamically.",
            "propertyOrder" : 271,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "allowDynamicRegistration" : {
            "title" : "Allow Open Dynamic Client Registration",
            "description" : "Allow clients to register without an access token. If enabled, you should consider adding some form of rate limiting. For more information, see <a href=\"http://openid.net/specs/openid-connect-registration-1_0.html#ClientRegistration\" target=\"_blank\">Client Registration</a> in the OpenID Connect specification.",
            "propertyOrder" : 280,

```

```
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"coreOAuth2Config" : {
    "type" : "object",
    "title" : "Core",
    "propertyOrder" : 0,
    "properties" : {
        "issueRefreshTokenOnRefreshedToken" : {
            "title" : "Issue Refresh Tokens on Refreshing Access Tokens",
            "description" : "Whether to issue a refresh token when refreshing an access token.",
            "propertyOrder" : 50,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "usePolicyEngineForScope" : {
            "title" : "Use Policy Engine for Scope decisions",
            "description" : "With this setting enabled, the policy engine is consulted for each scope value that is requested.<br><br>If a policy returns an action of GRANT=true, the scope is consented automatically, and the user is not consulted in a user-interaction flow. If a policy returns an action of GRANT=false, the scope is not added to any resulting token, and the user will not see it in a user-interaction flow. If no policy returns a value for the GRANT action, then if the grant type is user-facing (i.e. authorization or device code flows), the user is asked for consent (or saved consent is used), and if the grant type is not user-facing (password or client credentials), the scope is not added to any resulting token.",
            "propertyOrder" : 55,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "codeLifetime" : {
            "title" : "Authorization Code Lifetime (seconds)",
            "description" : "The time an authorization code is valid for, in seconds.",
            "propertyOrder" : 10,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "issueRefreshToken" : {
            "title" : "Issue Refresh Tokens",
            "description" : "Whether to issue a refresh token when returning an access token.",
            "propertyOrder" : 40,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "statelessTokensEnabled" : {
            "title" : "Use Stateless Access & Refresh Tokens",
            "description" : "When enabled, OpenAM issues access and refresh tokens that can be inspected by resource servers.",
            "propertyOrder" : 3,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        }
    }
},
```

```

"accessTokenLifetime" : {
  "title" : "Access Token Lifetime (seconds)",
  "description" : "The time an access token is valid for, in seconds.",
  "propertyOrder" : 30,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"refreshTokenLifetime" : {
  "title" : "Refresh Token Lifetime (seconds)",
  "description" : "The time in seconds a refresh token is valid for. If this field is set to
<code>-1</code>, the token will never expire.",
  "propertyOrder" : 20,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}
},
"consent" : {
  "type" : "object",
  "title" : "Consent",
  "propertyOrder" : 6,
  "properties" : {
    "supportedRcsResponseEncryptionMethods" : {
      "title" : "Remote Consent Service Response Encryption Methods Supported",
      "description" : "Encryption methods supported to decrypt Remote Consent Service
responses.<br><br>OpenAM supports the following encryption methods:<ul><li><code>A128GCM</code>,
<code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated
encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-
HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
      "propertyOrder" : 454,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "enableRemoteConsent" : {
      "title" : "Enable Remote Consent",
      "description" : "",
      "propertyOrder" : 447,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "supportedRcsRequestSigningAlgorithms" : {
      "title" : "Remote Consent Service Request Signing Algorithms Supported",
      "description" : "Algorithms supported to sign consent JWTs for Remote Consent
Services.<br><br>OpenAM supports signing algorithms listed in JSON Web Algorithms (JWA): <a
href=\"http://tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\">\"alg
\" (Algorithm) Header Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC with
SHA-256.</li><li><code>HS384</code> - HMAC with SHA-384.</li><li><code>HS512</code> - HMAC
with SHA-512.</li><li><code>ES256</code> - ECDSA with SHA-256 and NIST standard P-256 elliptic
curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and NIST standard P-384 elliptic
curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard P-521 elliptic curve.</
li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>",
      "propertyOrder" : 449,

```



```

    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "supportedRcsRequestEncryptionMethods" : {
    "title" : "Remote Consent Service Request Encryption Methods Supported",
    "description" : "Encryption methods supported to encrypt Remote Consent Service requests.<br><br>OpenAM supports the following encryption methods:<ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
    "propertyOrder" : 451,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "savedConsentAttribute" : {
    "title" : "Saved Consent Attribute Name",
    "description" : "Name of a multi-valued attribute on resource owner profiles where OpenAM can save authorization consent decisions.<p><p>When the resource owner chooses to save the decision to authorize access for a client application, then OpenAM updates the resource owner's profile to avoid having to prompt the resource owner to grant authorization when the client issues subsequent authorization requests.",
    "propertyOrder" : 110,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "supportedRcsRequestEncryptionAlgorithms" : {
    "title" : "Remote Consent Service Request Encryption Algorithms Supported",
    "description" : "Encryption algorithms supported to encrypt Remote Consent Service requests.<br><br>OpenAM supports the following encryption algorithms:<ul><li><code>RSA1_5</code> - RSA with PKCS#1 v1.5 padding.</li><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption Padding (OAEP) with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256 and MGF-1.</li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client secret.</li><li><code>A192KW</code> - AES Key Wrapping with 192-bit key derived from the client secret.</li><li><code>A256KW</code> - AES Key Wrapping with 256-bit key derived from the client secret.</li><li><code>dir</code> - Direct encryption with AES using the hashed client secret.</li></ul>",
    "propertyOrder" : 450,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "supportedRcsResponseSigningAlgorithms" : {
    "title" : "Remote Consent Service Response Signing Algorithms Supported",
    "description" : "Algorithms supported to verify signed consent_response JWT from Remote Consent Services.<br><br>OpenAM supports signing algorithms listed in JSON Web Algorithms (JWA): <a href=\"http://tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\">\"alg\" (Algorithm) Header Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC

```

```

with SHA-256.</li><li><code>HS384</code> - HMAC with SHA-384.</li><li><code>HS512</code> -
HMAC with SHA-512.</li><li><code>ES256</code> - ECDSA with SHA-256 and NIST standard P-256
elliptic curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and NIST standard P-384 elliptic
curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard P-521 elliptic curve.</
li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>",
  "propertyOrder" : 452,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"remoteConsentServiceId" : {
  "title" : "Remote Consent Service ID",
  "description" : "The ID of an existing remote consent service agent.",
  "propertyOrder" : 448,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"supportedRcsResponseEncryptionAlgorithms" : {
  "title" : "Remote Consent Service Response Encryption Algorithms Supported",
  "description" : "Encryption algorithms supported to decrypt Remote Consent Service
responses.<br><br>OpenAM supports the following encryption algorithms:<ul><li><code>RSA1_5</code> -
RSA with PKCS#1 v1.5 padding.</li><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption
Padding (OAEP) with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256
and MGF-1.</li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client
secret.</li><li><code>A192KW</code> - AES Key Wrapping with 192-bit key derived from the client
secret.</li><li><code>A256KW</code> - AES Key Wrapping with 256-bit key derived from the client
secret.</li><li><code>dir</code> - Direct encryption with AES using the hashed client secret.</li></
ul>",
  "propertyOrder" : 453,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"clientsCanSkipConsent" : {
  "title" : "Allow Clients to Skip Consent",
  "description" : "If enabled, clients may be configured so that the resource owner will not
be asked for consent during authorization flows.",
  "propertyOrder" : 420,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
}
}
}
}
}
}

```

1.101.2. Global Operations

Resource path: `/global-config/services/oauth-oidc`

Resource version: `1.0`

1.101.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OAuth2Provider --global --actionName getAllTypes
```

1.101.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OAuth2Provider --global --actionName getCreatableTypes
```

1.101.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OAuth2Provider --global --actionName nextdescendents
```

1.101.2.4. read

Usage:

```
am> read OAuth2Provider --global
```

1.101.2.5. update

Usage:

```
am> update OAuth2Provider --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "statelessGrantTokenUpgradeCompatibilityMode" : {
```

```

    "title" : "Stateless Grant Token Upgrade Compatibility Mode",
    "description" : "Enable OpenAM to consume and create stateless OAuth 2.0 tokens in two different
formats simultaneously.<br><br>Enable this option when upgrading OpenAM to allow the new instance
to create and consume stateless OAuth 2.0 tokens in both the previous format, and the new format.
Disable this option once all OpenAM instances in the cluster have been upgraded.",
    "propertyOrder" : 5,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "blacklistPurgeDelay" : {
    "title" : "Blacklist Purge Delay (minutes)",
    "description" : "Length of time to blacklist tokens beyond their expiry time.<br><br>Allows
additional time to account for clock skew to ensure that a token has expired before it is removed
from the blacklist.",
    "propertyOrder" : 2,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "agentIdTokenSigningKeyAlias" : {
    "title" : "ID Token Signing Key Alias for Agent Clients",
    "description" : "The alias for the RSA key that should be used signing ID tokens for Agent
OAuth2 Clients",
    "propertyOrder" : 4,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "blacklistCacheSize" : {
    "title" : "Token Blacklist Cache Size",
    "description" : "Number of blacklisted tokens to cache in memory to speed up blacklist checks
and reduce load on the CTS.",
    "propertyOrder" : 0,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "blacklistPollInterval" : {
    "title" : "Blacklist Poll Interval (seconds)",
    "description" : "How frequently to poll for token blacklist changes from other servers, in
seconds.<br><br>How often each server will poll the CTS for token blacklist changes from other
servers. This is used to maintain a highly compressed view of the overall current token blacklist
improving performance. A lower number will reduce the delay for blacklisted tokens to propagate to
all servers at the cost of increased CTS load. Set to 0 to disable this feature completely.",
    "propertyOrder" : 1,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "idTokenAuthenticitySecret" : {
    "title" : "Authenticity Secret",
    "description" : "A secret to use when signing data that will be sent back to AM so that
authenticity can be assured when they are presented back to OpenAM.",
    "propertyOrder" : 3,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }

```

```

    },
    "defaults" : {
      "properties" : {
        "consent" : {
          "type" : "object",
          "title" : "Consent",
          "propertyOrder" : 6,
          "properties" : {
            "remoteConsentServiceId" : {
              "title" : "Remote Consent Service ID",
              "description" : "The ID of an existing remote consent service agent.",
              "propertyOrder" : 448,
              "required" : false,
              "type" : "string",
              "exampleValue" : ""
            },
            "supportedRcsRequestSigningAlgorithms" : {
              "title" : "Remote Consent Service Request Signing Algorithms Supported",
              "description" : "Algorithms supported to sign consent request JWTs for Remote Consent Services.<br><br>OpenAM supports signing algorithms listed in JSON Web Algorithms (JWA): <a href='\"http://tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\"'>\"alg\" (Algorithm) Header Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC with SHA-256.</li><li><code>HS384</code> - HMAC with SHA-384.</li><li><code>HS512</code> - HMAC with SHA-512.</li><li><code>ES256</code> - ECDSA with SHA-256 and NIST standard P-256 elliptic curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and NIST standard P-384 elliptic curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard P-521 elliptic curve.</li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>",
              "propertyOrder" : 449,
              "required" : true,
              "items" : {
                "type" : "string"
              },
              "type" : "array",
              "exampleValue" : ""
            },
            "supportedRcsRequestEncryptionAlgorithms" : {
              "title" : "Remote Consent Service Request Encryption Algorithms Supported",
              "description" : "Encryption algorithms supported to encrypt Remote Consent Service requests.<br><br>OpenAM supports the following encryption algorithms:<ul><li><code>RSA1_5</code> - RSA with PKCS#1 v1.5 padding.</li><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption Padding (OAEP) with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256 and MGF-1.</li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client secret.</li><li><code>A192KW</code> - AES Key Wrapping with 192-bit key derived from the client secret.</li><li><code>A256KW</code> - AES Key Wrapping with 256-bit key derived from the client secret.</li><li><code>dir</code> - Direct encryption with AES using the hashed client secret.</li></ul>",
              "propertyOrder" : 450,
              "required" : true,
              "items" : {
                "type" : "string"
              },
              "type" : "array",
              "exampleValue" : ""
            },
            "savedConsentAttribute" : {
              "title" : "Saved Consent Attribute Name",
              "description" : "Name of a multi-valued attribute on resource owner profiles where OpenAM can save authorization consent decisions.<p><p>When the resource owner chooses to save the decision to authorize access for a client application, then OpenAM updates the resource owner's

```

```

profile to avoid having to prompt the resource owner to grant authorization when the client issues
subsequent authorization requests.",
  "propertyOrder" : 110,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"supportedRcsRequestEncryptionMethods" : {
  "title" : "Remote Consent Service Request Encryption Methods Supported",
  "description" : "Encryption methods supported to encrypt Remote Consent Service
requests.<br><br>OpenAM supports the following encryption methods:<ul><li><code>A128GCM</code>,
<code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated
encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-
HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 451,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"supportedRcsResponseEncryptionAlgorithms" : {
  "title" : "Remote Consent Service Response Encryption Algorithms Supported",
  "description" : "Encryption algorithms supported to decrypt Remote Consent Service
responses.<br><br>OpenAM supports the following encryption algorithms:<ul><li><code>RSA1_5</code> -
RSA with PKCS#1 v1.5 padding.</li><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption
Padding (OAEP) with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256
and MGF-1.</li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client
secret.</li><li><code>A192KW</code> - AES Key Wrapping with 192-bit key derived from the client
secret.</li><li><code>A256KW</code> - AES Key Wrapping with 256-bit key derived from the client
secret.</li><li><code>dir</code> - Direct encryption with AES using the hashed client secret.</li></ul>",
  "propertyOrder" : 453,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"supportedRcsResponseEncryptionMethods" : {
  "title" : "Remote Consent Service Response Encryption Methods Supported",
  "description" : "Encryption methods supported to decrypt Remote Consent Service
responses.<br><br>OpenAM supports the following encryption methods:<ul><li><code>A128GCM</code>,
<code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated
encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-
HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 454,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"enableRemoteConsent" : {
  "title" : "Enable Remote Consent",
  "description" : "",

```

```

    "propertyOrder" : 447,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "clientsCanSkipConsent" : {
    "title" : "Allow Clients to Skip Consent",
    "description" : "If enabled, clients may be configured so that the resource owner will
not be asked for consent during authorization flows.",
    "propertyOrder" : 420,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "supportedRcsResponseSigningAlgorithms" : {
    "title" : "Remote Consent Service Response Signing Algorithms Supported",
    "description" : "Algorithms supported to verify signed consent_response JWT from
Remote Consent Services.<br><br>OpenAM supports signing algorithms listed in JSON Web Algorithms
(JWA): <a href='\"http://tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\">
\"alg\" (Algorithm) Header Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC
with SHA-256.</li><li><code>HS384</code> - HMAC with SHA-384.</li><li><code>HS512</code> -
HMAC with SHA-512.</li><li><code>ES256</code> - ECDSA with SHA-256 and NIST standard P-256
elliptic curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and NIST standard P-384 elliptic
curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard P-521 elliptic curve.</
li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>",
    "propertyOrder" : 452,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
},
"advanced0Auth2Config" : {
  "type" : "object",
  "title" : "Advanced",
  "propertyOrder" : 1,
  "properties" : {
    "displayNameAttribute" : {
      "title" : "User Display Name attribute",
      "description" : "The profile attribute that contains the name to be displayed for the
user on the consent page.",
      "propertyOrder" : 120,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "scopeImplementationClass" : {
      "title" : "Scope Implementation Class",
      "description" : "The class that contains the required scope implementation, must
implement the <code>org.forgerock.oauth2.core.ScopeValidator</code> interface.",
      "propertyOrder" : 70,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "defaultScopes" : {

```

```

        "title" : "Default Client Scopes",
        "description" : "List of scopes a client will be granted if they request registration
without specifying which scopes they want. Default scopes are NOT auto-granted to clients created
through the OpenAM console.",
        "propertyOrder" : 200,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "codeVerifierEnforced" : {
        "title" : "Code Verifier Parameter Required",
        "description" : "If enabled, requests using the authorization code grant require a
<code>code_challenge</code> attribute.<br><br>For more information, read the <a href=\"https://
tools.ietf.org/html/draft-ietf-oauth-spop-12\">draft specification for this feature</a>.",
        "propertyOrder" : 270,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "responseTypeClasses" : {
        "title" : "Response Type Plugins",
        "description" : "List of plugins that handle the valid <code>response_type</code>
values.<br><br>OAuth 2.0 clients pass response types as parameters to the OAuth 2.0 Authorization
endpoint (<code>/oauth2/authorize</code>) to indicate which grant type is requested from the
provider. For example, the client passes <code>code</code> when requesting an authorization code,
and <code>token</code> when requesting an access token.<p><p>Values in this list take the form
<code>response-type|plugin-class-name</code>.",
        "propertyOrder" : 90,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "tokenSigningECDSAKeyAlias" : {
        "title" : "Token Signing ECDSA Public/Private Key Pair Alias",
        "description" : "The list of public/private key pairs used for the elliptic
curve algorithms (ES256/ES384/ES512). Add an entry to specify an alias for a specific
elliptic curve algorithm, for example <code>ES256|es256Alias</code>.<br><br>Each of the
public/private key pairs will be retrieved from the keystore referenced by the property
<code>com.sun.identity.saml.xmlsig.keystore</code>.",
        "propertyOrder" : 241,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "CreatedTimestampAttribute" : {
        "title" : "Created Timestamp Attribute Name",
        "description" : "The identity Data Store attribute used to return created timestamp
values.",
        "propertyOrder" : 350,
        "required" : false,
    
```



```

        "type" : "string",
        "exampleValue" : ""
    },
    "tokenSigningHmacSharedSecret" : {
        "title" : "Token Signing HMAC Shared Secret",
        "description" : "Base64-encoded key used by HS256, HS384 and HS512.",
        "propertyOrder" : 230,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "tokenEncryptionKeyAlias" : {
        "title" : "Token Encryption Secret Key Alias",
        "description" : "The secret key used for encryption.<br><br>The secret key will be
retrieved from the keystore referenced by the property <code>com.sun.identity.saml.xmlsig.keystore/
code>.",
        "propertyOrder" : 243,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "supportedScopes" : {
        "title" : "Supported Scopes",
        "description" : "The set of supported scopes, with translations.<br><br><p>Scopes may
be entered as simple strings or pipe-separated strings representing the internal scope name, locale,
and localized description.</p><p>For example: <code>read|en|Permission to view email messages in
your account</code></p><p>Locale strings are in the format: <code>language_country_variant</code>,
for example <code>en</code>, <code>en_GB</code>, or <code>en_US_WIN</code>.</p><p>If the locale and
pipe is omitted, the description is displayed to all users that have undefined locales.</p><p>If
the description is also omitted, nothing is displayed on the consent page for the scope. For example
specifying <code>read</code> would allow the scope read to be used by the client, but would not
display it to the user on the consent page when requested.</p>",
        "propertyOrder" : 130,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "tokenSigningAlgorithm" : {
        "title" : "OAuth2 Token Signing Algorithm",
        "description" : "Algorithm used to sign stateless OAuth 2.0 tokens in order to
detect tampering.<br><br>OpenAM supports signing algorithms listed in JSON Web Algorithms
(JWA): <a href='\"http://tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\">
\\alg\\ (Algorithm) Header Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC
with SHA-256.</li><li><code>HS384</code> - HMAC with SHA-384.</li><li><code>HS512</code> -
HMAC with SHA-512.</li><li><code>ES256</code> - ECDSA with SHA-256 and NIST standard P-256
elliptic curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and NIST standard P-384 elliptic
curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard P-521 elliptic curve.</
li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>",
        "propertyOrder" : 220,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "authenticationAttributes" : {
        "title" : "User Profile Attribute(s) the Resource Owner is Authenticated On",
    
```

```

    "description" : "Names of profile attributes that resource owners use to log in. You can
add others to the default, for example <code>mail</code>.",
    "propertyOrder" : 100,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "supportedSubjectTypes" : {
    "title" : "Subject Types supported",
    "description" : "List of subject types supported. Valid values
are:<ul><li><code>public</code> - Each client receives the same subject (<code>sub</code>) value.</
li><li><code>pairwise</code> - Each client receives a different subject (<code>sub</code>) value, to
prevent correlation between clients.</li></ul>",
    "propertyOrder" : 150,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "hashSalt" : {
    "title" : "Subject Identifier Hash Salt",
    "description" : "If <i>pairwise</i> subject types are supported, it is <em>STRONGLY
RECOMMENDED</em> to change this value. It is used in the salting of hashes for returning
specific <code>sub</code> claims to individuals using the same <code>request_uri</code> or
<code>sector_identifier_uri</code>.",
    "propertyOrder" : 260,
    "required" : false,
    "type" : "string",
    "exampleValue" : "changeme"
  },
  "modifiedTimestampAttribute" : {
    "title" : "Modified Timestamp Attribute Name",
    "description" : "The identity Data Store attribute used to return modified timestamp
values.",
    "propertyOrder" : 340,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenEncryptionEnabled" : {
    "title" : "Enable Stateless Token Encryption",
    "description" : "Whether stateless access and refresh tokens should be
encrypted.<br><br>Enabling token encryption will disable token signing as encryption is performed
using direct symmetric encryption.",
    "propertyOrder" : 242,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "keypairName" : {
    "title" : "Token Signing RSA Public/Private Key Pair",
    "description" : "The public/private key pair used by RS256.<br><br>The
public/private key pair will be retrieved from the keystore referenced by the property
<code>com.sun.identity.saml.xmlsig.keystore</code>.",

```

```

    "propertyOrder" : 240,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "customLoginUrlTemplate" : {
    "title" : "Custom Login URL Template",
    "description" : "Custom URL for handling login, to override the default OpenAM login
page.<br><br>Supports Freemarker syntax, with the following variables:<table><tr><th>Variable/<
th><th>Description</th></tr><tr><td><code>gotoUrl</code></td><td><p>The URL to redirect to after
login.</p></td></tr><tr><td><code>acrValues</code></td><td><p>The Authentication Context Class
Reference (acr) values for the authorization request.</p></td></tr><tr><td><code>realm</code></
td><td><p>The OpenAM realm the authorization request was made on.</p></td></tr><tr><td><code>module</
code></td><td><p>The name of the OpenAM authentication module requested to perform resource
owner authentication.</p></td></tr><tr><td><code>service</code></td><td><p>The name of the
OpenAM authentication chain requested to perform resource owner authentication.</p></td></
tr><tr><td><code>locale</code></td><td><p>A space-separated list of locales, ordered by
preference.</p></td></tr></table>The following example template redirects users to a non-OpenAM
front end to handle login, which will then redirect back to the <code>/oauth2/authorize</code>
endpoint with any required parameters:<p> <code>http://mylogin.com/login?goto=${goto}&lt;#if
acrValues??&gt;&acr_values=${acrValues}&lt;#x2F;#if&gt;&lt;#if realm??&gt;&realm=
${realm}&lt;#x2F;#if&gt;&lt;#if module??&gt;&module=${module}&lt;#x2F;#if&gt;&lt;#if
service??&gt;&service=${service}&lt;#x2F;#if&gt;&lt;#if locale??&gt;&locale=
${locale}&lt;#x2F;#if&gt;</code><br><b>NOTE</b>: Default OpenAM login page is constructed using
\"Base URL Source\" service.",
    "propertyOrder" : 60,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenCompressionEnabled" : {
    "title" : "Stateless Token Compression",
    "description" : "Whether stateless access and refresh tokens should be compressed.",
    "propertyOrder" : 223,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "moduleMessageEnabledInPasswordGrant" : {
    "title" : "Enable Auth Module Messages for Password Credentials Grant",
    "description" : "If enabled, authentication module failure messages are used to create
Resource Owner Password Credentials Grant failure messages. If disabled, a standard authentication
failed message is used.<br><br>The Password Grant Type requires the <code>grant_type=password</code>
parameter.",
    "propertyOrder" : 440,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"advancedOIDCConfig" : {
  "type" : "object",
  "title" : "Advanced OpenID Connect",
  "propertyOrder" : 4,
  "properties" : {
    "alwaysAddClaimsToToken" : {
      "title" : "Always Return Claims in ID Tokens",

```

```

        "description" : "If enabled, include scope-derived claims in the <code>id_token</code>, even if an access token is also returned that could provide access to get the claims from the <code>userinfo</code> endpoint.<br><br>If not enabled, if an access token is requested the client must use it to access the <code>userinfo</code> endpoint for scope-derived claims, as they will not be included in the ID token.",
        "propertyOrder" : 360,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "defaultACR" : {
        "title" : "Default ACR values",
        "description" : "Default requested Authentication Context Class Reference values.<br><br>List of strings that specifies the default acr values that the OP is being requested to use for processing requests from this Client, with the values appearing in order of preference. The Authentication Context Class satisfied by the authentication performed is returned as the acr Claim Value in the issued ID Token. The acr Claim is requested as a Voluntary Claim by this parameter. The acr_values_supported discovery element contains a list of the acr values supported by this server. Values specified in the acr_values request parameter or an individual acr Claim request override these default values.",
        "propertyOrder" : 320,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "supportedRequestParameterEncryptionAlgorithms" : {
        "title" : "Request Parameter Encryption Algorithms Supported",
        "description" : "Encryption algorithms supported to decrypt Request parameter.<br><br>OpenAM supports the following ID token encryption algorithms:<ul><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption Padding (OAEP) with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256 and MGF-1.</li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client secret.</li><li><code>RSA1_5</code> - RSA with PKCS#1 v1.5 padding.</li><li><code>A256KW</code> - AES Key Wrapping with 256-bit key derived from the client secret.</li><li><code>dir</code> - Direct encryption with AES using the hashed client secret.</li><li><code>A192KW</code> - AES Key Wrapping with 192-bit key derived from the client secret.</li></ul>",
        "propertyOrder" : 443,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "amrMappings" : {
        "title" : "OpenID Connect id_token amr Values to Auth Module Mappings",
        "description" : "Specify <code>amr</code> values to be returned in the OpenID Connect <code>id_token</code>. Once authentication has completed, the authentication modules that were used from the authentication service will be mapped to the <code>amr</code> values. If you do not require <code>amr</code> values, or are not providing OpenID Connect tokens, leave this field blank.",
        "propertyOrder" : 330,
        "required" : false,
        "patternProperties" : {
            ".*" : { }
        },
        "type" : "object",
    }

```

```

    "exampleValue" : ""
  },
  "supportedRequestParameterSigningAlgorithms" : {
    "title" : "Request Parameter Signing Algorithms Supported",
    "description" : "Algorithms supported to verify signature of Request parameterOpenAM
supports signing algorithms listed in JSON Web Algorithms (JWA): <a href='\"http://tools.ietf.org/
html/draft-ietf-jose-json-web-algorithms#section-3.1\"'>\"alg\" (Algorithm) Header Parameter Values
for JWS</a>:<ul><li><code>HS256</code> - HMAC with SHA-256.</li><li><code>HS384</code> - HMAC with
SHA-384.</li><li><code>HS512</code> - HMAC with SHA-512.</li><li><code>ES256</code> - ECDSA with
SHA-256 and NIST standard P-256 elliptic curve.</li><li><code>ES384</code> - ECDSA with SHA-384 and
NIST standard P-384 elliptic curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and NIST standard
P-521 elliptic curve.</li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</li></ul>",
    "propertyOrder" : 442,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "storeOpsTokens" : {
    "title" : "Store Ops Tokens",
    "description" : "Whether OpenAM will store the <i>ops</i> tokens corresponding to OpenID
Connect sessions in the CTS store. Note that session management related endpoints will not work when
this setting is disabled.",
    "propertyOrder" : 410,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "requireRequestUriRegistration" : {
    "title" : "Require Pre-registered request_uri Values",
    "description" : "When enabled, any <code>request_uri</code> values used must be pre-
registered using the <code>request_uris</code> registration parameter.",
    "propertyOrder" : 445,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "authorisedOpenIdConnectSSOClients" : {
    "title" : "Authorized OIDC SSO Clients",
    "description" : "Clients authorized to use OpenID Connect ID tokens as SSO
Tokens.<br><br>Allows clients to act with the full authority of the user. Grant this permission only
to trusted clients.",
    "propertyOrder" : 446,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "supportedRequestParameterEncryptionEnc" : {
    "title" : "Request Parameter Encryption Methods Supported",
    "description" : "Encryption methods supported to decrypt Request
parameter.<br><br>OpenAM supports the following Request parameter encryption
algorithms:<ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> - AES
in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>,

```

```

<code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-
SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 444,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"loaMapping" : {
  "title" : "OpenID Connect acr_values to Auth Chain Mapping",
  "description" : "Maps OpenID Connect ACR values to authentication chains. For more
details, see the <a href=\"http://openid.net/specs/openid-connect-core-1_0.html#AuthRequest\" target=
\"_blank\">acr_values parameter</a> in the OpenID Connect authentication request specification.",
  "propertyOrder" : 310,
  "required" : false,
  "patternProperties" : {
    ".*" : { }
  },
  "type" : "object",
  "exampleValue" : ""
},
"idTokenInfoClientAuthenticationEnabled" : {
  "title" : "Idtokeninfo Endpoint Requires Client Authentication",
  "description" : "When enabled, the <code>/oauth2/idtokeninfo</code> endpoint requires
client authentication if the signing algorithm is set to <code>HS256</code>, <code>HS384</code>, or
<code>HS512</code>.",
  "propertyOrder" : 225,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"claimsParameterSupported" : {
  "title" : "Enable \"claims_parameter_supported\"",
  "description" : "If enabled, clients will be able to request individual claims using
the <code>claims</code> request parameter, as per <a href=\"http://openid.net/specs/openid-connect-
core-1_0.html#ClaimsParameter\" target=\"_blank\">section 5.5 of the OpenID Connect specification</
a>.",
  "propertyOrder" : 250,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"jksURI" : {
  "title" : "Remote JSON Web Key URL",
  "description" : "The Remote URL where the providers JSON Web Key can be
retrieved.<p><p>If this setting is not configured, then OpenAM provides a local URL to access the
public key of the private key used to sign ID tokens.",
  "propertyOrder" : 140,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"core0Auth2Config" : {
  "type" : "object",
  "title" : "Core",

```

```

"propertyOrder" : 0,
"properties" : {
  "refreshTokenLifetime" : {
    "title" : "Refresh Token Lifetime (seconds)",
    "description" : "The time in seconds a refresh token is valid for. If this field is set
to <code>-1</code>, the token will never expire.",
    "propertyOrder" : 20,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "codeLifetime" : {
    "title" : "Authorization Code Lifetime (seconds)",
    "description" : "The time an authorization code is valid for, in seconds.",
    "propertyOrder" : 10,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "issueRefreshTokenOnRefreshedToken" : {
    "title" : "Issue Refresh Tokens on Refreshing Access Tokens",
    "description" : "Whether to issue a refresh token when refreshing an access token.",
    "propertyOrder" : 50,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "accessTokenLifetime" : {
    "title" : "Access Token Lifetime (seconds)",
    "description" : "The time an access token is valid for, in seconds.",
    "propertyOrder" : 30,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "usePolicyEngineForScope" : {
    "title" : "Use Policy Engine for Scope decisions",
    "description" : "With this setting enabled, the policy engine is consulted for each
scope value that is requested.<br><br>If a policy returns an action of GRANT=true, the scope is
consented automatically, and the user is not consulted in a user-interaction flow. If a policy
returns an action of GRANT=false, the scope is not added to any resulting token, and the user will
not see it in a user-interaction flow. If no policy returns a value for the GRANT action, then
if the grant type is user-facing (i.e. authorization or device code flows), the user is asked for
consent (or saved consent is used), and if the grant type is not user-facing (password or client
credentials), the scope is not added to any resulting token.",
    "propertyOrder" : 55,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "statelessTokensEnabled" : {
    "title" : "Use Stateless Access & Refresh Tokens",
    "description" : "When enabled, OpenAM issues access and refresh tokens that can be
inspected by resource servers.",
    "propertyOrder" : 3,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},

```

```

    "issueRefreshToken" : {
      "title" : "Issue Refresh Tokens",
      "description" : "Whether to issue a refresh token when returning an access token.",
      "propertyOrder" : 40,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  },
  "clientDynamicRegistrationConfig" : {
    "type" : "object",
    "title" : "Client Dynamic Registration",
    "propertyOrder" : 2,
    "properties" : {
      "dynamicClientRegistrationSoftwareStatementRequired" : {
        "title" : "Require Software Statement for Dynamic Client Registration",
        "description" : "When enabled, a software statement JWT containing at least the
<code>iss</code> (issuer) claim must be provided when registering an OAuth 2.0 client dynamically.",
        "propertyOrder" : 271,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "requiredSoftwareStatementAttestedAttributes" : {
        "title" : "Required Software Statement Attested Attributes",
        "description" : "The client attributes that are required to be present in the software
statement JWT when registering an OAuth 2.0 client dynamically. Only applies if Require Software
Statements for Dynamic Client Registration is enabled.<br><br>Leave blank to allow any attributes to
be present.",
        "propertyOrder" : 272,
        "required" : true,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      },
      "generateRegistrationAccessTokens" : {
        "title" : "Generate Registration Access Tokens",
        "description" : "Whether to generate Registration Access Tokens for clients that
register by using open dynamic client registration. Such tokens allow the client to access the <a
href='\"http://openid.net/specs/openid-connect-registration-1_0.html#ClientConfigurationEndpoint\"
target='\"_blank\">Client Configuration Endpoint</a> as per the OpenID Connect specification. This
setting has no effect if Allow Open Dynamic Client Registration is disabled.",
        "propertyOrder" : 290,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "dynamicClientRegistrationScope" : {
        "title" : "Scope to give access to dynamic client registration",
        "description" : "Mandatory scope required when registering a new OAuth2 client.",
        "propertyOrder" : 455,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "allowDynamicRegistration" : {

```



```

        "title" : "Allow Open Dynamic Client Registration",
        "description" : "Allow clients to register without an access token. If enabled, you
should consider adding some form of rate limiting. For more information, see <a href=\"http://
openid.net/specs/openid-connect-registration-1_0.html#ClientRegistration\" target=\"_blank\">Client
Registration</a> in the OpenID Connect specification.",
        "propertyOrder" : 280,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"deviceCodeConfig" : {
    "type" : "object",
    "title" : "Device Flow",
    "propertyOrder" : 5,
    "properties" : {
        "deviceCodeLifetime" : {
            "title" : "Device Code Lifetime (seconds)",
            "description" : "The lifetime of the device code, in seconds.",
            "propertyOrder" : 390,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "verificationUrl" : {
            "title" : "Verification URL",
            "description" : "The URL that the user will be instructed to visit to complete their
OAuth 2.0 login and consent when using the device code flow.",
            "propertyOrder" : 370,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "devicePollInterval" : {
            "title" : "Device Polling Interval",
            "description" : "The polling frequency for devices waiting for tokens when using the
device code flow.",
            "propertyOrder" : 400,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "completionUrl" : {
            "title" : "Device Completion URL",
            "description" : "The URL that the user will be sent to on completion of their OAuth 2.0
login and consent when using the device code flow.",
            "propertyOrder" : 380,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        }
    }
},
"coreOIDCConfig" : {
    "type" : "object",
    "title" : "OpenID Connect",
    "propertyOrder" : 3,
    "properties" : {

```

```

    "supportedIDTokenEncryptionMethods" : {
      "title" : "ID Token Encryption Methods supported",
      "description" : "Encryption methods supported to encrypt OpenID Connect ID
tokens in order to hide its contents.<br><br>OpenAM supports the following ID token encryption
algorithms:<ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> - AES
in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>,
<code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-
SHA-2 for integrity.</li></ul>",
      "propertyOrder" : 180,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "supportedIDTokenEncryptionAlgorithms" : {
      "title" : "ID Token Encryption Algorithms supported",
      "description" : "Encryption algorithms supported to encrypt OpenID Connect ID
tokens in order to hide its contents.<br><br>OpenAM supports the following ID token encryption
algorithms:<ul><li><code>RSA-OAEP</code> - RSA with Optimal Asymmetric Encryption Padding (OAEP)
with SHA-1 and MGF-1.</li><li><code>RSA-OAEP-256</code> - RSA with OAEP with SHA-256 and MGF-1.</
li><li><code>A128KW</code> - AES Key Wrapping with 128-bit key derived from the client secret.</
li><li><code>RSA1_5</code> - RSA with PKCS#1 v1.5 padding.</li><li><code>A256KW</code> - AES
Key Wrapping with 256-bit key derived from the client secret.</li><li><code>dir</code> - Direct
encryption with AES using the hashed client secret.</li><li><code>A192KW</code> - AES Key Wrapping
with 192-bit key derived from the client secret.</li></ul>",
      "propertyOrder" : 170,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "supportedIDTokenSigningAlgorithms" : {
      "title" : "ID Token Signing Algorithms supported",
      "description" : "Algorithms supported to sign OpenID Connect <code>id_tokens</
code>.<p><p>OpenAM supports signing algorithms listed in JSON Web Algorithms (JWA): <a href=\"http://
tools.ietf.org/html/draft-ietf-jose-json-web-algorithms#section-3.1\">\"alg\" (Algorithm) Header
Parameter Values for JWS</a>:<ul><li><code>HS256</code> - HMAC with SHA-256.</li><li><code>HS384</
code> - HMAC with SHA-384.</li><li><code>HS512</code> - HMAC with SHA-512.</li><li><code>ES256</code>
- ECDSA with SHA-256 and NIST standard P-256 elliptic curve.</li><li><code>ES384</code> - ECDSA with
SHA-384 and NIST standard P-384 elliptic curve.</li><li><code>ES512</code> - ECDSA with SHA-512 and
NIST standard P-521 elliptic curve.</li><li><code>RS256</code> - RSASSA-PKCS-v1_5 using SHA-256.</
li></ul>",
      "propertyOrder" : 160,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "oidcClaimsScript" : {
      "title" : "OIDC Claims Script",
      "description" : "The script that is run when issuing an ID token or making a request
to the <i>userinfo</i> endpoint during OpenID requests.<p><p>The script gathers the scopes and

```

```

populates claims, and has access to the access token, the user's identity and, if available, the
user's session.",
  "propertyOrder" : 80,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"jwtTokenLifetime" : {
  "title" : "OpenID Connect JWT Token Lifetime (seconds)",
  "description" : "The amount of time the JWT will be valid for, in seconds.",
  "propertyOrder" : 210,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"supportedClaims" : {
  "title" : "Supported Claims",
  "description" : "Set of claims supported by the OpenID Connect <code>/oauth2/
userinfo</code> endpoint, with translations.<br><br>Claims may be entered as simple strings or pipe
separated strings representing the internal claim name, locale, and localized description.<p><p>For
example: <code>name|en|Your full name.</code>.<p>Locale strings are in the format: <code>language
+ \"_\" + country + \"_\" + variant</code>, for example <code>en</code>, <code>en_GB</code>, or
<code>en_US_WIN</code>. If the locale and pipe is omitted, the description is displayed to all users
that have undefined locales.<p><p>If the description is also omitted, nothing is displayed on the
consent page for the claim. For example specifying <code>family_name</code> would allow the claim
<code>family_name</code> to be used by the client, but would not display it to the user on the
consent page when requested.",
  "propertyOrder" : 190,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"tokenEncryptionSigningKeyAlias" : {
  "title" : "Token Encryption RSA Public/Private Key Pair Alias",
  "description" : "The list of public/private key pairs used for the RSA algorithms
(RSA1_5/RSA-OAEP/RSA-OAEP-256). Add an entry to specify an alias for a specific RSA algorithm,
for example <code>RSA1_5|rsa1_5Alias</code>.<br><br>Each of the public/private key pairs will be
retrieved from the keystore referenced by the property <code>com.sun.identity.saml.xmlsig.keystore</
code>.",
  "propertyOrder" : 441,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
}
}
}
}
"type" : "object",
"title" : "Realm Defaults"
}
}
}
}

```

1.102. OAuth2RemoteConsentAgentGroups

1.102.1. Realm Operations

Agent Groups handler that is responsible for managing agent groups

Resource path: `/realm-config/agents/groups/RemoteConsentAgent`

Resource version: `1.0`

1.102.1.1. create

Usage:

```
am> create OAuth2RemoteConsentAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "remoteConsentRequestEncryptionMethod" : {
      "title" : "Consent request Encryption Method",
      "description" : "Encryption method to be used when encrypting the consent request JWT.",
      "propertyOrder" : 34300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "remoteConsentResponseEncryptionAlgorithm" : {
      "title" : "Consent response encryption algorithm",
      "description" : "The encryption algorithm to be used by the provider when decrypting the remote consent response JWT received from the Remote Consent Service.",
      "propertyOrder" : 34500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "publicKeyLocation" : {
      "title" : "Public key selector",
      "description" : "",
      "propertyOrder" : 34700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```
"remoteConsentResponseEncryptionMethod" : {
  "title" : "Consent response encryption method",
  "description" : "The encryption method to be used by the provider when decrypting the remote
consent response JWT received from the Remote Consent Service.<br><br>AM supports the following token
encryption algorithms: <ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> -
AES in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>,
<code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-
SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 34600,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"remoteConsentResponseSigningAlg" : {
  "title" : "Consent response signing algorithm",
  "description" : "The signing algorithm to be used by the provider when verifying the signature
of the consent response JWT received from the Remote Consent Service.",
  "propertyOrder" : 34400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"requestTimeLimit" : {
  "title" : "Consent Request Time Limit",
  "description" : "The amount of seconds for which the consent request JWT sent to the Remote
Consent Service should be considered valid.",
  "propertyOrder" : 35200,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"remoteConsentRedirectUrl" : {
  "title" : "Redirect URL",
  "description" : "The Remote Consent Service's URL to which the authorization server should
redirect the user in order to obtain their consent.",
  "propertyOrder" : 34000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"jwkSet" : {
  "title" : "Json Web Key",
  "description" : "Raw JSON Web Key value containing the Remote Consent Service's public keys.",
  "propertyOrder" : 35100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"jwksCacheTimeout" : {
  "title" : "JWKS URI content cache timeout in ms",
  "description" : "To avoid loading the JWKS URI content for every operation, the JWKS content is
cached. This timeout defines the maximum amount of time the JWKS URI content can be cached before
being refreshed.",
  "propertyOrder" : 34900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"remoteConsentRequestEncryptionEnabled" : {
```

```

    "title" : "Enable consent request Encryption",
    "description" : "Enables encryption of the consent request JWT.",
    "propertyOrder" : 34100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "remoteConsentRequestEncryptionAlgorithm" : {
    "title" : "Consent request Encryption Algorithm",
    "description" : "Encryption algorithm to be used when encrypting the consent request JWT.",
    "propertyOrder" : 34200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "jwkStoreCacheMissCacheTime" : {
    "title" : "JWKS URI content cache miss cache time",
    "description" : "To avoid loading the JWKS URI content for every operation, especially when
the kid is not in the jwks content already cached, the JWKS content will be cached for a minimum
period of time. This cache miss cache time defines the minimum amount of time the JWKS URI content is
cached.",
    "propertyOrder" : 35000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "jwksUri" : {
    "title" : "Json Web Key URI",
    "description" : "The URI containing the public keys of the Remote Consent Service secret. The
public keys are in the Json Web Key (jwk) format.",
    "propertyOrder" : 34800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "remoteConsentRequestSigningAlgorithm" : {
    "title" : "Consent request Signing Algorithm",
    "description" : "Signing algorithm to be used when signing the consent request JWT.",
    "propertyOrder" : 34500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}

```

1.102.1.2. delete

Usage:

```
am> delete OAuth2RemoteConsentAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.102.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OAuth2RemoteConsentAgentGroups --realm Realm --actionName getAllTypes
```

1.102.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OAuth2RemoteConsentAgentGroups --realm Realm --actionName getCreatableTypes
```

1.102.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OAuth2RemoteConsentAgentGroups --realm Realm --actionName nextdescendents
```

1.102.1.6. query

Querying the agent groups of a specific type

Usage:

```
am> query OAuth2RemoteConsentAgentGroups --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.102.1.7. read

Usage:

```
am> read OAuth2RemoteConsentAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.102.1.8. update

Usage:

```
am> update OAuth2RemoteConsentAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "remoteConsentRequestEncryptionMethod" : {
      "title" : "Consent request Encryption Method",
      "description" : "Encryption method to be used when encrypting the consent request JWT.",
      "propertyOrder" : 34300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "remoteConsentResponseEncryptionAlgorithm" : {
      "title" : "Consent response encryption algorithm",
      "description" : "The encryption algorithm to be used by the provider when decrypting the remote consent response JWT received from the Remote Consent Service.",
      "propertyOrder" : 34500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "publicKeyLocation" : {
      "title" : "Public key selector",
      "description" : "",
      "propertyOrder" : 34700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "remoteConsentResponseEncryptionMethod" : {
      "title" : "Consent response encryption method",
      "description" : "The encryption method to be used by the provider when decrypting the remote consent response JWT received from the Remote Consent Service.<br><br>AM supports the following token encryption algorithms: <ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>, <code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
      "propertyOrder" : 34900,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```



```
"propertyOrder" : 34600,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"remoteConsentResponseSigningAlg" : {
  "title" : "Consent response signing algorithm",
  "description" : "The signing algorithm to be used by the provider when verifying the signature
of the consent response JWT received from the Remote Consent Service.",
  "propertyOrder" : 34400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"requestTimeLimit" : {
  "title" : "Consent Request Time Limit",
  "description" : "The amount of seconds for which the consent request JWT sent to the Remote
Consent Service should be considered valid.",
  "propertyOrder" : 35200,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"remoteConsentRedirectUrl" : {
  "title" : "Redirect URL",
  "description" : "The Remote Consent Service's URL to which the authorization server should
redirect the user in order to obtain their consent.",
  "propertyOrder" : 34000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"jwkSet" : {
  "title" : "Json Web Key",
  "description" : "Raw JSON Web Key value containing the Remote Consent Service's public keys.",
  "propertyOrder" : 35100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"jwksCacheTimeout" : {
  "title" : "JWKS URI content cache timeout in ms",
  "description" : "To avoid loading the JWKS URI content for every operation, the JWKS content is
cached. This timeout defines the maximum amount of time the JWKS URI content can be cached before
being refreshed.",
  "propertyOrder" : 34900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"remoteConsentRequestEncryptionEnabled" : {
  "title" : "Enable consent request Encryption",
  "description" : "Enables encryption of the consent request JWT.",
  "propertyOrder" : 34100,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"remoteConsentRequestEncryptionAlgorithm" : {
```

```
"title" : "Consent request Encryption Algorithm",
"description" : "Encryption algorithm to be used when encrypting the consent request JWT.",
"propertyOrder" : 34200,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"jwkStoreCacheMissCacheTime" : {
"title" : "JWKS URI content cache miss cache time",
"description" : "To avoid loading the JWKS URI content for every operation, especially when
the kid is not in the jwks content already cached, the JWKS content will be cached for a minimum
period of time. This cache miss cache time defines the minimum amount of time the JWKS URI content is
cached.",
"propertyOrder" : 35000,
"required" : true,
"type" : "integer",
"exampleValue" : ""
},
"jwksUri" : {
"title" : "Json Web Key URI",
"description" : "The URI containing the public keys of the Remote Consent Service secret. The
public keys are in the Json Web Key (jwk) format.",
"propertyOrder" : 34800,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"remoteConsentRequestSigningAlgorithm" : {
"title" : "Consent request Signing Algorithm",
"description" : "Signing algorithm to be used when signing the consent request JWT.",
"propertyOrder" : 34500,
"required" : true,
"type" : "string",
"exampleValue" : ""
}
}
}
```

1.103. OAuth2SoftwarePublisherAgentGroups

1.103.1. Realm Operations

Agent Groups handler that is responsible for managing agent groups

Resource path: `/realm-config/agents/groups/SoftwarePublisher`

Resource version: `1.0`

1.103.1.1. create

Usage:

```
am> create OAuth2SoftwarePublisherAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "softwareStatementSigningAlgorithm" : {
      "title" : "Software statement signing Algorithm",
      "description" : "Signing algorithm to be used when verifying software statement signatures.",
      "propertyOrder" : 34500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "jwksCacheTimeout" : {
      "title" : "JWKS URI content cache timeout in ms",
      "description" : "To avoid loading the JWKS URI content for every operation, the JWKS content is cached. This timeout defines the maximum amount of time the JWKS URI content can be cached before being refreshed.",
      "propertyOrder" : 34900,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "jwkStoreCacheMissCacheTime" : {
      "title" : "JWKS URI content cache miss cache time",
      "description" : "To avoid loading the JWKS URI content for every operation, especially when the kid is not in the jwks content already cached, the JWKS content will be cached for a minimum period of time. This cache miss cache time defines the minimum amount of time the JWKS URI content is cached.",
      "propertyOrder" : 35000,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "jwkSet" : {
      "title" : "Json Web Key",
      "description" : "Raw JSON Web Key value containing the Software Publisher's public keys.",
      "propertyOrder" : 35100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "publicKeyLocation" : {
      "title" : "Public key selector",
      "description" : "Select how the Software Publisher's public keys should be retrieved by the provider when validating software statement signatures.",
      "propertyOrder" : 34700,

```

```
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "jwksUri" : {
    "title" : "Json Web Key URI",
    "description" : "The URI that contains the Software Publisher's public keys in Json Web Key
format.",
    "propertyOrder" : 34800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "issuer" : {
    "title" : "Software publisher issuer",
    "description" : "Identifier for the software publisher, generally represented as a URL.",
    "propertyOrder" : 33001,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.103.1.2. delete

Usage:

```
am> delete OAuth2SoftwarePublisherAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.103.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OAuth2SoftwarePublisherAgentGroups --realm Realm --actionName getAllTypes
```

1.103.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OAuth2SoftwarePublisherAgentGroups --realm Realm --actionName getCreatableTypes
```

1.103.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OAuth2SoftwarePublisherAgentGroups --realm Realm --actionName nextdescendents
```

1.103.1.6. query

Querying the agent groups of a specific type

Usage:

```
am> query OAuth2SoftwarePublisherAgentGroups --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.103.1.7. read

Usage:

```
am> read OAuth2SoftwarePublisherAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.103.1.8. update

Usage:

```
am> update OAuth2SoftwarePublisherAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "softwareStatementSigningAlgorithm" : {
      "title" : "Software statement signing Algorithm",
      "description" : "Signing algorithm to be used when verifying software statement signatures.",
      "propertyOrder" : 34500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "jwksCacheTimeout" : {
      "title" : "JWKS URI content cache timeout in ms",
      "description" : "To avoid loading the JWKS URI content for every operation, the JWKS content is cached. This timeout defines the maximum amount of time the JWKS URI content can be cached before being refreshed.",
      "propertyOrder" : 34900,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "jwkStoreCacheMissCacheTime" : {
      "title" : "JWKS URI content cache miss cache time",
      "description" : "To avoid loading the JWKS URI content for every operation, especially when the kid is not in the jwks content already cached, the JWKS content will be cached for a minimum period of time. This cache miss cache time defines the minimum amount of time the JWKS URI content is cached.",
      "propertyOrder" : 35000,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "jwkSet" : {
      "title" : "Json Web Key",
      "description" : "Raw JSON Web Key value containing the Software Publisher's public keys.",
      "propertyOrder" : 35100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "publicKeyLocation" : {
      "title" : "Public key selector",
      "description" : "Select how the Software Publisher's public keys should be retrieved by the provider when validating software statement signatures.",
      "propertyOrder" : 34700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "jwksUri" : {
```

```
    "title" : "Json Web Key URI",
    "description" : "The URI that contains the Software Publisher's public keys in Json Web Key
format.",
    "propertyOrder" : 34800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "issuer" : {
    "title" : "Software publisher issuer",
    "description" : "Identifier for the software publisher, generally represented as a URL.",
    "propertyOrder" : 33001,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
```

1.104. OAuth2UserApplications

1.104.1. Realm Operations

This endpoint exposes a list of all the applications (clients) that the user authorized using OAuth 2.0. Access for those applications can then be revoked on a per-client basis.

Resource path: `/users/{user}/oauth2/applications`

Resource version: `1.0`

1.104.1.1. delete

Delete the tokens for the specified client ID.

Usage:

```
am> delete OAuth2UserApplications --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

This endpoint exposes a list of all the applications (clients) that the user authorized using OAuth 2.0. Access for those applications can then be revoked on a per-client basis.

1.104.1.2. query

Get a list of the applications that have been granted OAuth 2.0 access. Only `_queryFilter=true` is supported.

Usage:

```
am> query OAuth2UserApplications --realm Realm --filter filter --user user
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

--user

This endpoint exposes a list of all the applications (clients) that the user authorized using OAuth 2.0. Access for those applications can then be revoked on a per-client basis.

1.105. OTPCollectorDecision

1.105.1. Realm Operations

Resource path: </realm-config/authentication/authenticationtrees/nodes/OneTimePasswordCollectorDecisionNode>

Resource version: 1.0

1.105.1.1. create

Usage:

```
am> create OTPCollectorDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:


```
{
  "type" : "object",
  "properties" : {
    "passwordExpiryTime" : {
      "title" : "One Time Password Validity Length",
      "description" : "This One Time Password will remain valid for this period in minutes.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "passwordExpiryTime" ]
}
```

1.105.1.2. delete

Usage:

```
am> delete OTPCollectorDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.105.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OTPCollectorDecision --realm Realm --actionName getAllTypes
```

1.105.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OTPCollectorDecision --realm Realm --actionName getCreatableTypes
```

1.105.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action OTPCollectorDecision --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.105.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OTPCollectorDecision --realm Realm --actionName nextdescendents
```

1.105.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query OTPCollectorDecision --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.105.1.8. read

Usage:

```
am> read OTPCollectorDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.105.1.9. update

Usage:

```
am> update OTPCollectorDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "passwordExpiryTime" : {
      "title" : "One Time Password Validity Length",
      "description" : "This One Time Password will remain valid for this period in minutes.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "passwordExpiryTime" ]
}
```

1.106. OTPEmailSender

1.106.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/OneTimePasswordSmtplibSenderNode`

Resource version: `1.0`

1.106.1.1. create

Usage:

```
am> create OTPEmailSender --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "password" : {
      "title" : "Mail Server Authentication Password",
      "description" : "The password to use when the mail server is using SMTP authentication",
      "propertyOrder" : 500,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "hostPort" : {
      "title" : "Mail Server Host Port",
      "description" : "The port of the mail server. The default port for SMTP is 25, if using SSL the default port is 465.",
      "propertyOrder" : 300,
      "type" : "integer",
      "exampleValue" : ""
    },
    "fromEmailAddress" : {
      "title" : "Email From Address",
      "description" : "Emails from the OTP Email Sender node will come from this address.",
      "propertyOrder" : 600,
      "type" : "string",
      "exampleValue" : ""
    },
    "smsGatewayImplementationClass" : {
      "title" : "Gateway Implementation Class",
      "description" : "The OTP Email Sender node uses this class to send email messages. <br><br>The gateway class must implement the following interface: <br><code>com.sun.identity.authentication.modules.hotp.SMSGateway</code>",
      "propertyOrder" : 2200,
      "type" : "string",
      "exampleValue" : ""
    },
    "sslOption" : {
      "title" : "Mail Server Secure Connection",
      "description" : "This setting controls whether the authentication module communicates with the mail server using SSL/TLS.",
      "propertyOrder" : 2100,
      "type" : "string",
      "exampleValue" : ""
    },
    "username" : {
      "title" : "Mail Server Authentication Username",
      "description" : "The username to use when the mail server is using SMTP authentication",
      "propertyOrder" : 400,
      "type" : "string",
      "exampleValue" : ""
    }
  },
}
```

```
"emailAttribute" : {
  "title" : "Email Attribute Name",
  "description" : "This is the attribute name used by the OTP Sender to email the user",
  "propertyOrder" : 1100,
  "type" : "string",
  "exampleValue" : ""
},
"hostName" : {
  "title" : "Mail Server Host Name",
  "description" : "The name of the mail server OpenAM will use to send the messages.",
  "propertyOrder" : 200,
  "type" : "string",
  "exampleValue" : ""
}
},
"required" : [ "password", "hostPort", "fromEmailAddress", "username",
"smsGatewayImplementationClass", "sslOption", "emailAttribute", "hostName" ]
}
```

1.106.1.2. delete

Usage:

```
am> delete OTPEmailSender --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.106.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OTPEmailSender --realm Realm --actionName getAllTypes
```

1.106.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OTPEmailSender --realm Realm --actionName getCreatableTypes
```

1.106.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action OTPEmailSender --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.106.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OTPEmailSender --realm Realm --actionName nextdescendents
```

1.106.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query OTPEmailSender --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.106.1.8. read

Usage:

```
am> read OTPEmailSender --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.106.1.9. update

Usage:

```
am> update OTPEmailSender --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "password" : {
      "title" : "Mail Server Authentication Password",
      "description" : "The password to use when the mail server is using SMTP authentication",
      "propertyOrder" : 500,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "hostPort" : {
      "title" : "Mail Server Host Port",
      "description" : "The port of the mail server. The default port for SMTP is 25, if using SSL the
default port is 465.",
      "propertyOrder" : 300,
      "type" : "integer",
      "exampleValue" : ""
    },
    "fromEmailAddress" : {
      "title" : "Email From Address",
      "description" : "Emails from the OTP Email Sender node will come from this address.",
      "propertyOrder" : 600,
      "type" : "string",
      "exampleValue" : ""
    },
    "smsGatewayImplementationClass" : {
      "title" : "Gateway Implementation Class",
      "description" : "The OTP Email Sender node uses this class to send email
messages. <br><br>The gateway class must implement the following interface:
<br><code>com.sun.identity.authentication.modules.hotp.SMSGateway</code>",
      "propertyOrder" : 2200,
      "type" : "string",
      "exampleValue" : ""
    },
    "sslOption" : {
      "title" : "Mail Server Secure Connection",
      "description" : "This setting controls whether the authentication module communicates with the
mail server using SSL/TLS.",

```

```
    "propertyOrder" : 2100,
    "type" : "string",
    "exampleValue" : ""
  },
  "username" : {
    "title" : "Mail Server Authentication Username",
    "description" : "The username to use when the mail server is using SMTP authentication",
    "propertyOrder" : 400,
    "type" : "string",
    "exampleValue" : ""
  },
  "emailAttribute" : {
    "title" : "Email Attribute Name",
    "description" : "This is the attribute name used by the OTP Sender to email the user",
    "propertyOrder" : 1100,
    "type" : "string",
    "exampleValue" : ""
  },
  "hostName" : {
    "title" : "Mail Server Host Name",
    "description" : "The name of the mail server OpenAM will use to send the messages.",
    "propertyOrder" : 200,
    "type" : "string",
    "exampleValue" : ""
  }
},
"required" : [ "password", "hostPort", "fromEmailAddress", "username",
"smsGatewayImplementationClass", "sslOption", "emailAttribute", "hostName" ]
}
```

1.107. OTPSMSSender

1.107.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/OneTimePasswordSmsSenderNode`

Resource version: `1.0`

1.107.1.1. create

Usage:

```
am> create OTPSMSSender --realm Realm --id id --body body
```

Parameters:

`--id`

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "hostName" : {
      "title" : "Mail Server Host Name",
      "description" : "The name of the mail server OpenAM will use to send the messages.",
      "propertyOrder" : 200,
      "type" : "string",
      "exampleValue" : ""
    },
    "smsGatewayImplementationClass" : {
      "title" : "Gateway Implementation Class",
      "description" : "The OTP SMS Sender node uses this class to send SMS messages. <br><br>The gateway class must implement the following interface: <br><code>com.sun.identity.authentication.modules.hotp.SMSGateway</code>",
      "propertyOrder" : 2200,
      "type" : "string",
      "exampleValue" : ""
    },
    "password" : {
      "title" : "Mail Server Authentication Password",
      "description" : "The password to use when the mail server is using SMTP authentication",
      "propertyOrder" : 500,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "fromEmailAddress" : {
      "title" : "Email From Address",
      "description" : "Emails from the OTP Email Sender node will come from this address.",
      "propertyOrder" : 600,
      "type" : "string",
      "exampleValue" : ""
    },
    "username" : {
      "title" : "Mail Server Authentication Username",
      "description" : "The username to use when the mail server is using SMTP authentication",
      "propertyOrder" : 400,
      "type" : "string",
      "exampleValue" : ""
    },
    "mobileCarrierAttributeName" : {
      "title" : "Mobile Carrier Attribute Name",
      "description" : "This is the attribute name used for a mobile carrier domain for sending SMS messages.",
      "propertyOrder" : 1200,
      "type" : "string",
      "exampleValue" : ""
    },
    "hostPort" : {
      "title" : "Mail Server Host Port",
      "description" : "The port of the mail server. The default port for SMTP is 25, if using SSL the default port is 465.",
      "propertyOrder" : 300,
      "type" : "integer",
```

```
    "exampleValue" : ""
  },
  "sslOption" : {
    "title" : "Mail Server Secure Connection",
    "description" : "This setting controls whether the authentication module communicates with the
mail server using SSL/TLS.",
    "propertyOrder" : 2100,
    "type" : "string",
    "exampleValue" : ""
  },
  "mobilePhoneAttributeName" : {
    "title" : "Mobile Phone Number Attribute Name",
    "description" : "This is the attribute name used for a requested text message.",
    "propertyOrder" : 1100,
    "type" : "string",
    "exampleValue" : ""
  }
},
"required" : [ "hostPort", "hostName", "username", "password", "smsGatewayImplementationClass",
"fromEmailAddress", "sslOption", "mobilePhoneAttributeName" ]
}
```

1.107.1.2. delete

Usage:

```
am> delete OTPSMSSender --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.107.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OTPSMSSender --realm Realm --actionName getAllTypes
```

1.107.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OTPSMSSender --realm Realm --actionName getCreatableTypes
```

1.107.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action OTPSMSSender --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.107.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OTPSMSSender --realm Realm --actionName nextdescendents
```

1.107.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query OTPSMSSender --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.107.1.8. read

Usage:

```
am> read OTPSMSSender --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.107.1.9. update

Usage:

```
am> update OTPSMSSender --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "hostName" : {
      "title" : "Mail Server Host Name",
      "description" : "The name of the mail server OpenAM will use to send the messages.",
      "propertyOrder" : 200,
      "type" : "string",
      "exampleValue" : ""
    },
    "smsGatewayImplementationClass" : {
      "title" : "Gateway Implementation Class",
      "description" : "The OTP SMS Sender node uses this class to send SMS
messages. <br><br>The gateway class must implement the following interface:
<br><code>com.sun.identity.authentication.modules.hotp.SMSGateway</code>",
      "propertyOrder" : 2200,
      "type" : "string",
      "exampleValue" : ""
    },
    "password" : {
      "title" : "Mail Server Authentication Password",
      "description" : "The password to use when the mail server is using SMTP authentication",
      "propertyOrder" : 500,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "fromEmailAddress" : {
      "title" : "Email From Address",
      "description" : "Emails from the OTP Email Sender node will come from this address.",
      "propertyOrder" : 600,
      "type" : "string",
      "exampleValue" : ""
    },
    "username" : {
      "title" : "Mail Server Authentication Username",
      "description" : "The username to use when the mail server is using SMTP authentication",
      "propertyOrder" : 400,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```
"mobileCarrierAttributeName" : {
  "title" : "Mobile Carrier Attribute Name",
  "description" : "This is the attribute name used for a mobile carrier domain for sending SMS
messages.",
  "propertyOrder" : 1200,
  "type" : "string",
  "exampleValue" : ""
},
"hostPort" : {
  "title" : "Mail Server Host Port",
  "description" : "The port of the mail server. The default port for SMTP is 25, if using SSL the
default port is 465.",
  "propertyOrder" : 300,
  "type" : "integer",
  "exampleValue" : ""
},
"sslOption" : {
  "title" : "Mail Server Secure Connection",
  "description" : "This setting controls whether the authentication module communicates with the
mail server using SSL/TLS.",
  "propertyOrder" : 2100,
  "type" : "string",
  "exampleValue" : ""
},
"mobilePhoneAttributeName" : {
  "title" : "Mobile Phone Number Attribute Name",
  "description" : "This is the attribute name used for a requested text message.",
  "propertyOrder" : 1100,
  "type" : "string",
  "exampleValue" : ""
}
},
"required" : [ "hostPort", "hostName", "username", "password", "smsGatewayImplementationClass",
"fromEmailAddress", "sslOption", "mobilePhoneAttributeName" ]
}
```

1.108. OathModule

1.108.1. Realm Operations

Resource path: `/realm-config/authentication/modules/oath`

Resource version: `1.0`

1.108.1.1. create

Usage:

```
am> create OathModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "stepsInWindow" : {
      "title" : "TOTP Time Steps",
      "description" : "The number of time steps to check before and after receiving a OTP.<br><br>This is the number of time step intervals to check the received OTP against both forward in time and back in time. For example, with 2 time steps and a time step interval of 30 seconds the server will allow a clock drift between client and server of 89 seconds. (2-30 second steps and 29 seconds for the interval that the OTP arrived in)",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "lastLoginTimeAttribute" : {
      "title" : "Last Login Time Attribute",
      "description" : "Attribute to store the time of the users last login. This is required if TOTP is chosen as the OATH algorithm.<br><br>This attribute stores the last time a user logged in to prevent time based attacks. The value is stored as a number (Unix Time).",
      "propertyOrder" : 1200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "minimumSecretKeyLength" : {
      "title" : "Minimum Secret Key Length",
      "description" : "Number of hexadecimal characters allowed for the Secret Key.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "addChecksum" : {
      "title" : "Add Checksum Digit",
      "description" : "This adds a checksum digit to the OTP.<br><br>This adds a digit to the end of the OTP generated to be used as a checksum to verify the OTP was generated correctly. This is in addition to the actual password length. You should only set this if your device supports it.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "hotpCounterAttribute" : {
      "title" : "Counter Attribute Name",
      "description" : "The name of the attribute in the user profile to store the user counter. This is required if HOTP is chosen as the OATH algorithm.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```

},
"truncationOffset" : {
  "title" : "Truncation Offset",
  "description" : "This adds an offset to the generation of the OTP.<br><br>This is an option used
by the HOTP algorithm that not all devices support. This should be left default unless you know your
device uses a offset.",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"oathOtpMaxRetry" : {
  "title" : "One Time Password Max Retry",
  "description" : "The number of times entry of the OTP may be attempted. Minimum is 1 maximum is
10 and default is 3.",
  "propertyOrder" : null,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"forgerock-oath-maximum-clock-drift" : {
  "title" : "Maximum Allowed Clock Drift",
  "description" : "Number of time steps a client is allowed to get out of sync with the server
before manual resynchronisation is required. This should be greater than the TOTP Time Steps
value.<br><br>As this checks the time drift over multiple requests it needs to be greater than the
value specified in TOTP Time Steps.",
  "propertyOrder" : 1500,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"oathAlgorithm" : {
  "title" : "OATH Algorithm to Use",
  "description" : "Choose the algorithm your device uses to generate the OTP.<br><br>HOTP uses a
counter value that is incremented every time a new OTP is generated. TOTP generates a new OTP every
few seconds as specified by the time step interval.",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"passwordLength" : {
  "title" : "One Time Password Length ",
  "description" : "The length of the generated OTP in digits. Must be 6 digits or longer.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"forgerock-oath-sharedsecret-implementation-class" : {
  "title" : "The Shared Secret Provider Class",
  "description" : "The fully qualified class name for the Shared Secret Provider
extension.<br><br>The class that is used to process the user profile attribute used to store the user
secret key.",
  "propertyOrder" : 1300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
},

```

```

"timeStepSize" : {
  "title" : "TOTP Time Step Interval",
  "description" : "The TOTP time step in seconds that the OTP device uses to generate the
OTP.<br><br>This is the time interval that one OTP is valid for. For example, if the time step is 30
seconds, then a new OTP will be generated every 30 seconds. This makes a single OTP valid for only 30
seconds.",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"secretKeyAttribute" : {
  "title" : "Secret Key Attribute Name",
  "description" : "The name of the attribute in the user profile to store the user secret key.",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"hotpWindowSize" : {
  "title" : "HOTP Window Size",
  "description" : "The size of the window to resynchronize with the client.<br><br>This sets the
window that the OTP device and the server counter can be out of sync. For example, if the window size
is 100 and the servers last successful login was at counter value 2, then the server will accept a
OTP from the OTP device that is from device counter 3 to 102.",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"forgerock-oath-observed-clock-drift-attribute-name" : {
  "title" : "Clock Drift Attribute Name",
  "description" : "The name of the attribute in the user profile to store the clock drift. If left
empty then clock drift checking is disabled.<br><br>The name of the attribute used to store the last
observed clock drift which is used to indicated when a manual resynchronisation is required.",
  "propertyOrder" : 1400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
}

```

1.108.1.2. delete

Usage:


```
am> delete OathModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.108.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OathModule --realm Realm --actionName getAllTypes
```

1.108.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OathModule --realm Realm --actionName getCreatableTypes
```

1.108.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OathModule --realm Realm --actionName nextdescendents
```

1.108.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query OathModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.108.1.7. read

Usage:

```
am> read OathModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.108.1.8. update

Usage:

```
am> update OathModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "stepsInWindow" : {
      "title" : "TOTP Time Steps",
      "description" : "The number of time steps to check before and after receiving a OTP.<br><br>This is the number of time step intervals to check the received OTP against both forward in time and back in time. For example, with 2 time steps and a time step interval of 30 seconds the server will allow a clock drift between client and server of 89 seconds. (2-30 second steps and 29 seconds for the interval that the OTP arrived in)",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "lastLoginTimeAttribute" : {
      "title" : "Last Login Time Attribute",
      "description" : "Attribute to store the time of the users last login. This is required if TOTP is chosen as the OATH algorithm.<br><br>This attribute stores the last time a user logged in to prevent time based attacks. The value is stored as a number (Unix Time).",
      "propertyOrder" : 1200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "minimumSecretKeyLength" : {
      "title" : "Minimum Secret Key Length",
      "description" : "Number of hexadecimal characters allowed for the Secret Key.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```

},
"addChecksum" : {
  "title" : "Add Checksum Digit",
  "description" : "This adds a checksum digit to the OTP.<br><br>This adds a digit to the end
of the OTP generated to be used as a checksum to verify the OTP was generated correctly. This is in
addition to the actual password length. You should only set this if your device supports it.",
  "propertyOrder" : 800,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"hotpCounterAttribute" : {
  "title" : "Counter Attribute Name",
  "description" : "The name of the attribute in the user profile to store the user counter. This
is required if HOTP is chosen as the OATH algorithm.",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"truncationOffset" : {
  "title" : "Truncation Offset",
  "description" : "This adds an offset to the generation of the OTP.<br><br>This is an option used
by the HOTP algorithm that not all devices support. This should be left default unless you know your
device uses a offset.",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"oathOtpMaxRetry" : {
  "title" : "One Time Password Max Retry",
  "description" : "The number of times entry of the OTP may be attempted. Minimum is 1 maximum is
10 and default is 3.",
  "propertyOrder" : null,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"forgerock-oath-maximum-clock-drift" : {
  "title" : "Maximum Allowed Clock Drift",
  "description" : "Number of time steps a client is allowed to get out of sync with the server
before manual resynchronisation is required. This should be greater than the TOTP Time Steps
value.<br><br>As this checks the time drift over multiple requests it needs to be greater than the
value specified in TOTP Time Steps.",
  "propertyOrder" : 1500,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"oathAlgorithm" : {
  "title" : "OATH Algorithm to Use",
  "description" : "Choose the algorithm your device uses to generate the OTP.<br><br>HOTP uses a
counter value that is incremented every time a new OTP is generated. TOTP generates a new OTP every
few seconds as specified by the time step interval.",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}

```

```

},
"passwordLength" : {
  "title" : "One Time Password Length ",
  "description" : "The length of the generated OTP in digits. Must be 6 digits or longer.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"forgerock-oath-sharedsecret-implementation-class" : {
  "title" : "The Shared Secret Provider Class",
  "description" : "The fully qualified class name for the Shared Secret Provider
extension.<br><br>The class that is used to process the user profile attribute used to store the user
secret key.",
  "propertyOrder" : 1300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"timeStepSize" : {
  "title" : "TOTP Time Step Interval",
  "description" : "The TOTP time step in seconds that the OTP device uses to generate the
OTP.<br><br>This is the time interval that one OTP is valid for. For example, if the time step is 30
seconds, then a new OTP will be generated every 30 seconds. This makes a single OTP valid for only 30
seconds.",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"secretKeyAttribute" : {
  "title" : "Secret Key Attribute Name",
  "description" : "The name of the attribute in the user profile to store the user secret key.",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"hotpWindowSize" : {
  "title" : "HOTP Window Size",
  "description" : "The size of the window to resynchronize with the client.<br><br>This sets the
window that the OTP device and the server counter can be out of sync. For example, if the window size
is 100 and the servers last successful login was at counter value 2, then the server will accept a
OTP from the OTP device that is from device counter 3 to 102.",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
}

```

```
"forgerock-oath-observed-clock-drift-attribute-name" : {
  "title" : "Clock Drift Attribute Name",
  "description" : "The name of the attribute in the user profile to store the clock drift. If left
empty then clock drift checking is disabled.<br><br>The name of the attribute used to store the last
observed clock drift which is used to indicated when a manual resynchronisation is required.",
  "propertyOrder" : 1400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
```

1.108.2. Global Operations

Resource path: `/global-config/authentication/modules/oath`

Resource version: `1.0`

1.108.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OathModule --global --actionName getAllTypes
```

1.108.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OathModule --global --actionName getCreatableTypes
```

1.108.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OathModule --global --actionName nextdescendents
```

1.108.2.4. read

Usage:

```
am> read OathModule --global
```

1.108.2.5. update

Usage:

```
am> update OathModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "lastLoginTimeAttribute" : {
          "title" : "Last Login Time Attribute",
          "description" : "Attribute to store the time of the users last login. This is required if
TOTP is chosen as the OATH algorithm.<br><br>This attribute stores the last time a user logged in to
prevent time based attacks. The value is stored as a number (Unix Time).",
          "propertyOrder" : 1200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "forgerock-oath-maximum-clock-drift" : {
          "title" : "Maximum Allowed Clock Drift",
          "description" : "Number of time steps a client is allowed to get out of sync with the
server before manual resynchronisation is required. This should be greater than the TOTP Time Steps
value.<br><br>As this checks the time drift over multiple requests it needs to be greater than the
value specified in TOTP Time Steps.",
          "propertyOrder" : 1500,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "secretKeyAttribute" : {
          "title" : "Secret Key Attribute Name",
          "description" : "The name of the attribute in the user profile to store the user secret
key.",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "oathAlgorithm" : {
```

```

    "title" : "OATH Algorithm to Use",
    "description" : "Choose the algorithm your device uses to generate the OTP.<br><br>HOTP uses a counter value that is incremented every time a new OTP is generated. TOTP generates a new OTP every few seconds as specified by the time step interval.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "forgerock-oath-observed-clock-drift-attribute-name" : {
    "title" : "Clock Drift Attribute Name",
    "description" : "The name of the attribute in the user profile to store the clock drift. If left empty then clock drift checking is disabled.<br><br>The name of the attribute used to store the last observed clock drift which is used to indicated when a manual resynchronisation is required.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "minimumSecretKeyLength" : {
    "title" : "Minimum Secret Key Length",
    "description" : "Number of hexadecimal characters allowed for the Secret Key.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "stepsInWindow" : {
    "title" : "TOTP Time Steps",
    "description" : "The number of time steps to check before and after receiving a OTP.<br><br>This is the number of time step intervals to check the received OTP against both forward in time and back in time. For example, with 2 time steps and a time step interval of 30 seconds the server will allow a clock drift between client and server of 89 seconds. (2-30 second steps and 29 seconds for the interval that the OTP arrived in)",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "timeStepSize" : {
    "title" : "TOTP Time Step Interval",
    "description" : "The TOTP time step in seconds that the OTP device uses to generate the OTP.<br><br>This is the time interval that one OTP is valid for. For example, if the time step is 30 seconds, then a new OTP will be generated every 30 seconds. This makes a single OTP valid for only 30 seconds.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "truncationOffset" : {
    "title" : "Truncation Offset",
    "description" : "This adds an offset to the generation of the OTP.<br><br>This is an option used by the HOTP algorithm that not all devices support. This should be left default unless you know your device uses a offset.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }

```

```

    },
    "forgerock-oath-sharedsecret-implementation-class" : {
      "title" : "The Shared Secret Provider Class",
      "description" : "The fully qualified class name for the Shared Secret Provider
extension.<br><br>The class that is used to process the user profile attribute used to store the user
secret key.",
      "propertyOrder" : 1300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "hotpWindowSize" : {
      "title" : "HOTP Window Size",
      "description" : "The size of the window to resynchronize with the client.<br><br>This sets
the window that the OTP device and the server counter can be out of sync. For example, if the window
size is 100 and the servers last successful login was at counter value 2, then the server will accept
a OTP from the OTP device that is from device counter 3 to 102.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "passwordLength" : {
      "title" : "One Time Password Length ",
      "description" : "The length of the generated OTP in digits. Must be 6 digits or longer.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "oathOtpMaxRetry" : {
      "title" : "One Time Password Max Retry",
      "description" : "The number of times entry of the OTP may be attempted. Minimum is 1 maximum
is 10 and default is 3.",
      "propertyOrder" : null,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "hotpCounterAttribute" : {
      "title" : "Counter Attribute Name",
      "description" : "The name of the attribute in the user profile to store the user counter.
This is required if HOTP is chosen as the OATH algorithm.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "addChecksum" : {
      "title" : "Add Checksum Digit",
      "description" : "This adds a checksum digit to the OTP.<br><br>This adds a digit to the end
of the OTP generated to be used as a checksum to verify the OTP was generated correctly. This is in
addition to the actual password length. You should only set this if your device supports it.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},

```



```
    "type" : "object",  
    "title" : "Realm Defaults"  
  }  
}
```

1.109. OathUserDevices

1.109.1. Realm Operations

The Oath devices service is responsible for exposing functions to change the collection of OATH authentication devices. The supported methods are action, delete, query

Resource path: `/users/{user}/devices/2fa/oath`

Resource version: `1.0`

1.109.1.1. check

Checks if the user's Authenticator OATH module is 'skippable' and returns the result as a boolean

Usage:

```
am> action OathUserDevices --realm Realm --body body --user user --actionName check
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "$schema" : "http://json-schema.org/draft-04/schema#",  
  "description" : "OATH user device check action request schema",  
  "type" : "object",  
  "title" : "OATH user device check action request schema"  
}
```

--user

The Oath devices service is responsible for exposing functions to change the collection of OATH authentication devices. The supported methods are action, delete, query

1.109.1.2. delete

Delete OATH user device

Usage:

```
am> delete OathUserDevices --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

The Oath devices service is responsible for exposing functions to change the collection of OATH authentication devices. The supported methods are action, delete, query

1.109.1.3. query

Query the user's device profile

Usage:

```
am> query OathUserDevices --realm Realm --filter filter --user user
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

--user

The Oath devices service is responsible for exposing functions to change the collection of OATH authentication devices. The supported methods are action, delete, query

1.109.1.4. reset

Sets the user's 'skippable' selection of Authenticator OATH module to default (NOT_SET) and deletes their profiles attribute

Usage:

```
am> action OathUserDevices --realm Realm --body body --user user --actionName reset
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "OATH user device reset action request schema",
  "type" : "object",
  "title" : "OATH user device reset action request schema"
}
```

--user

The Oath devices service is responsible for exposing functions to change the collection of OATH authentication devices. The supported methods are action, delete, query

1.109.1.5. skip

Sets the user's ability to skip an Authenticator OATH module

Usage:

```
am> action OathUserDevices --realm Realm --body body --user user --actionName skip
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "OATH user device skip action request schema",
  "type" : "object",
  "title" : "OATH user device skip action request schema",
  "properties" : {
    "value" : {
      "type" : "boolean",
      "title" : "Skip OATH module response value",
      "description" : "True if the OATH device is set to skipped"
    }
  },
  "required" : [ "value" ]
}
```

--user

The Oath devices service is responsible for exposing functions to change the collection of OATH authentication devices. The supported methods are action, delete, query

1.110. OpenDJ

1.110.1. Realm Operations

Resource path: </realm-config/services/id-repositories/LDAPv3ForOpenDS>

Resource version: 1.0

1.110.1.1. create

Usage:

```
am> create OpenDJ --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userconfig" : {
      "type" : "object",
      "title" : "User Configuration",
      "propertyOrder" : 3,
      "properties" : {
        "sun-idrepo-ldapv3-config-users-search-attribute" : {
          "title" : "LDAP Users Search Attribute",
          "description" : "",
          "propertyOrder" : 2100,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-active" : {
          "title" : "User Status Active Value",
          "description" : "",
          "propertyOrder" : 2700,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-people-container-name" : {
          "title" : "LDAP People Container Naming Attribute",
          "description" : "",
          "propertyOrder" : 5000,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-people-container-value" : {
          "title" : "LDAP People Container Value",
          "description" : "",
          "propertyOrder" : 5100,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-auth-kba-index-attr" : {
          "title" : "Knowledge Based Authentication Active Index",
          "description" : "",
          "propertyOrder" : 5400,
          "required" : false,
          "type" : "string",

```

```
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-isactive" : {
    "title" : "Attribute Name of User Status",
    "description" : "",
    "propertyOrder" : 2600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-user-attributes" : {
    "title" : "LDAP User Attributes",
    "description" : "",
    "propertyOrder" : 2400,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-auth-kba-attr" : {
    "title" : "Knowledge Based Authentication Attribute Name",
    "description" : "",
    "propertyOrder" : 5300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-inactive" : {
    "title" : "User Status Inactive Value",
    "description" : "",
    "propertyOrder" : 2800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-auth-kba-attempts-attr" : {
    "title" : "Knowledge Based Authentication Attempts Attribute Name",
    "description" : "",
    "propertyOrder" : 5410,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-user-objectclass" : {
    "title" : "LDAP User Object Class",
    "description" : "",
    "propertyOrder" : 2300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
  },
}
```

```

    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-users-search-filter" : {
    "title" : "LDAP Users Search Filter",
    "description" : "",
    "propertyOrder" : 2200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
    "title" : "Create User Attribute Mapping",
    "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
    "propertyOrder" : 2500,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"ldapsettings" : {
  "type" : "object",
  "title" : "Server Settings",
  "propertyOrder" : 0,
  "properties" : {
    "sun-idrepo-ldapv3-config-max-result" : {
      "title" : "Maximum Results Returned from Search",
      "description" : "",
      "propertyOrder" : 1500,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-search-scope" : {
      "title" : "LDAPv3 Plug-in Search Scope",
      "description" : "",
      "propertyOrder" : 2000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-timeunit" : {
      "title" : "LDAP Connection Heartbeat Time Unit",
      "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
it may take up to the interval period before the problem is detected. Use along with the Heartbeat
Interval parameter to define the exact interval.",
      "propertyOrder" : 1400,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-connection-mode" : {
      "title" : "LDAP Connection Mode",

```

```

    "description" : "Defines which protocol/operation is used to establish the connection to
the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
    "propertyOrder" : 1000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
    "title" : "LDAP Connection Pool Maximum Size",
    "description" : "",
    "propertyOrder" : 1200,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-heartbeat-interval" : {
    "title" : "LDAP Connection Heartbeat Interval",
    "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
error) then it may take up to the interval period before the problem is detected. Use along with the
Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
disabling heartbeat requests.",
    "propertyOrder" : 1300,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-organization_name" : {
    "title" : "LDAP Organization DN",
    "description" : "",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-authid" : {
    "title" : "LDAP Bind DN",
    "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
    "propertyOrder" : 700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-ldap-server" : {
    "title" : "LDAP Server",
    "description" : "Format: LDAP server host name:port | server_ID | site_ID",
    "propertyOrder" : 600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
}

```

```

"openam-idrepo-ldapv3-proxied-auth-enabled" : {
  "title" : "Proxied Authorization using Bind DN",
  "description" : "Enable this setting if you have configured the LDAP bind DN account for
proxied authorization (DS proxied-auth privilege). Do not enable this property if the LDAP bind DN
account does not have the proxied-auth privilege granted because the user would not be able to reset
their password. DS and AM log an error when this occurs.",
  "propertyOrder" : 850,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"openam-idrepo-ldapv3-behera-support-enabled" : {
  "title" : "Behera Support Enabled",
  "description" : "When enabled, Behera draft control will be used in the outgoing requests
for operations that may modify password value. This will allow OpenAM to display password policy
related error messages when password policies are not met.",
  "propertyOrder" : 6100,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-authpw" : {
  "title" : "LDAP Bind Password",
  "description" : "",
  "propertyOrder" : 800,
  "required" : false,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-time-limit" : {
  "title" : "Search Timeout",
  "description" : "In seconds.",
  "propertyOrder" : 1600,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
}
}
},
"cachecontrol" : {
  "type" : "object",
  "title" : "Cache Control",
  "propertyOrder" : 9,
  "properties" : {
    "sun-idrepo-ldapv3-dncache-enabled" : {
      "title" : "DN Cache",
      "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
      "propertyOrder" : 5900,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-dncache-size" : {
      "title" : "DN Cache Size",

```



```
    "description" : "In DN items, only used when DN Cache is enabled.",
    "propertyOrder" : 6000,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  }
}
},
"groupconfig" : {
  "type" : "object",
  "title" : "Group Configuration",
  "propertyOrder" : 5,
  "properties" : {
    "sun-idrepo-ldapv3-config-group-container-name" : {
      "title" : "LDAP Groups Container Naming Attribute",
      "description" : "",
      "propertyOrder" : 3100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-groups-search-filter" : {
      "title" : "LDAP Groups Search Filter",
      "description" : "",
      "propertyOrder" : 3000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-memberurl" : {
      "title" : "Attribute Name of Group Member URL",
      "description" : "",
      "propertyOrder" : 3700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-unique-member" : {
      "title" : "Attribute Name of Unique Member",
      "description" : "",
      "propertyOrder" : 3600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-attributes" : {
      "title" : "LDAP Groups Attributes",
      "description" : "",
      "propertyOrder" : 3400,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-objectclass" : {
      "title" : "LDAP Groups Object Class",
      "description" : "",
```

```

    "propertyOrder" : 3300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-memberof" : {
    "title" : "Attribute Name for Group Membership",
    "description" : "",
    "propertyOrder" : 3500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-groups-search-attribute" : {
    "title" : "LDAP Groups Search Attribute",
    "description" : "",
    "propertyOrder" : 2900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-container-value" : {
    "title" : "LDAP Groups Container Value",
    "description" : "",
    "propertyOrder" : 3200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"authentication" : {
  "type" : "object",
  "title" : "Authentication Configuration",
  "propertyOrder" : 4,
  "properties" : {
    "sun-idrepo-ldapv3-config-auth-naming-attr" : {
      "title" : "Authentication Naming Attribute",
      "description" : "",
      "propertyOrder" : 5200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
},
"pluginconfig" : {
  "type" : "object",
  "title" : "Plug-in Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "sunIdRepoClass" : {
      "title" : "LDAPv3 Repository Plug-in Class Name",
      "description" : "",
      "propertyOrder" : 1700,
      "required" : true,

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "sunIdRepoSupportedOperations" : {
    "title" : "LDAPv3 Plug-in Supported Types and Operations",
    "description" : "",
    "propertyOrder" : 1900,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sunIdRepoAttributeMapping" : {
    "title" : "Attribute Name Mapping",
    "description" : "",
    "propertyOrder" : 1800,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"persistentsearch" : {
  "type" : "object",
  "title" : "Persistent Search Controls",
  "propertyOrder" : 7,
  "properties" : {
    "sun-idrepo-ldapv3-config-psearch-filter" : {
      "title" : "Persistent Search Filter",
      "description" : "",
      "propertyOrder" : 5600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-psearchbase" : {
      "title" : "Persistent Search Base DN",
      "description" : "",
      "propertyOrder" : 5500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-psearch-scope" : {
      "title" : "Persistent Search Scope",
      "description" : "",
      "propertyOrder" : 5700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
},
"errorhandling" : {

```

```
"type" : "object",
"title" : "Error Handling Configuration",
"propertyOrder" : 8,
"properties" : {
  "com.iplanet.am.ldap.connection.delay.between.retries" : {
    "title" : "The Delay Time Between Retries",
    "description" : "In milliseconds.",
    "propertyOrder" : 5800,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
```

1.110.1.2. delete

Usage:

```
am> delete OpenDJ --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.110.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OpenDJ --realm Realm --actionName getAllTypes
```

1.110.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OpenDJ --realm Realm --actionName getCreatableTypes
```

1.110.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OpenDJ --realm Realm --actionName nextdescendents
```

1.110.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query OpenDJ --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.110.1.7. read

Usage:

```
am> read OpenDJ --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.110.1.8. update

Usage:

```
am> update OpenDJ --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userconfig" : {
      "type" : "object",
      "title" : "User Configuration",
      "propertyOrder" : 3,
      "properties" : {
        "sun-idrepo-ldapv3-config-users-search-attribute" : {
          "title" : "LDAP Users Search Attribute",
          "description" : "",
          "propertyOrder" : 2100,

```

```
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-active" : {
"title" : "User Status Active Value",
"description" : "",
"propertyOrder" : 2700,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-people-container-name" : {
"title" : "LDAP People Container Naming Attribute",
"description" : "",
"propertyOrder" : 5000,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-people-container-value" : {
"title" : "LDAP People Container Value",
"description" : "",
"propertyOrder" : 5100,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-index-attr" : {
"title" : "Knowledge Based Authentication Active Index",
"description" : "",
"propertyOrder" : 5400,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-isactive" : {
"title" : "Attribute Name of User Status",
"description" : "",
"propertyOrder" : 2600,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-user-attributes" : {
"title" : "LDAP User Attributes",
"description" : "",
"propertyOrder" : 2400,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-attr" : {
"title" : "Knowledge Based Authentication Attribute Name",
"description" : "",
"propertyOrder" : 5300,
```

```

    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-inactive" : {
    "title" : "User Status Inactive Value",
    "description" : "",
    "propertyOrder" : 2800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-auth-kba-attempts-attr" : {
    "title" : "Knowledge Based Authentication Attempts Attribute Name",
    "description" : "",
    "propertyOrder" : 5410,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-user-objectclass" : {
    "title" : "LDAP User Object Class",
    "description" : "",
    "propertyOrder" : 2300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-users-search-filter" : {
    "title" : "LDAP Users Search Filter",
    "description" : "",
    "propertyOrder" : 2200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
    "title" : "Create User Attribute Mapping",
    "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
    "propertyOrder" : 2500,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"ldapsettings" : {

```

```

"type" : "object",
"title" : "Server Settings",
"propertyOrder" : 0,
"properties" : {
  "sun-idrepo-ldapv3-config-max-result" : {
    "title" : "Maximum Results Returned from Search",
    "description" : "",
    "propertyOrder" : 1500,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-search-scope" : {
    "title" : "LDAPv3 Plug-in Search Scope",
    "description" : "",
    "propertyOrder" : 2000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-heartbeat-timeunit" : {
    "title" : "LDAP Connection Heartbeat Time Unit",
    "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
it may take up to the interval period before the problem is detected. Use along with the Heartbeat
Interval parameter to define the exact interval.",
    "propertyOrder" : 1400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection-mode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Defines which protocol/operation is used to establish the connection to
the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
    "propertyOrder" : 1000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
    "title" : "LDAP Connection Pool Maximum Size",
    "description" : "",
    "propertyOrder" : 1200,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-heartbeat-interval" : {
    "title" : "LDAP Connection Heartbeat Interval",
    "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
error) then it may take up to the interval period before the problem is detected. Use along with the

```



```

Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
disabling heartbeat requests.",
  "propertyOrder" : 1300,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-organization_name" : {
  "title" : "LDAP Organization DN",
  "description" : "",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-authid" : {
  "title" : "LDAP Bind DN",
  "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
  "propertyOrder" : 700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-ldap-server" : {
  "title" : "LDAP Server",
  "description" : "Format: LDAP server host name:port | server_ID | site_ID",
  "propertyOrder" : 600,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"openam-idrepo-ldapv3-proxied-auth-enabled" : {
  "title" : "Proxied Authorization using Bind DN",
  "description" : "Enable this setting if you have configured the LDAP bind DN account for
proxied authorization (DS proxied-auth privilege). Do not enable this property if the LDAP bind DN
account does not have the proxied-auth privilege granted because the user would not be able to reset
their password. DS and AM log an error when this occurs.",
  "propertyOrder" : 850,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"openam-idrepo-ldapv3-behera-support-enabled" : {
  "title" : "Behera Support Enabled",
  "description" : "When enabled, Behera draft control will be used in the outgoing requests
for operations that may modify password value. This will allow OpenAM to display password policy
related error messages when password policies are not met.",
  "propertyOrder" : 6100,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-authpw" : {
  "title" : "LDAP Bind Password",
  "description" : "",

```

```

    "propertyOrder" : 800,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-time-limit" : {
    "title" : "Search Timeout",
    "description" : "In seconds.",
    "propertyOrder" : 1600,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"cachecontrol" : {
  "type" : "object",
  "title" : "Cache Control",
  "propertyOrder" : 9,
  "properties" : {
    "sun-idrepo-ldapv3-dncache-enabled" : {
      "title" : "DN Cache",
      "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
      "propertyOrder" : 5900,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-dncache-size" : {
      "title" : "DN Cache Size",
      "description" : "In DN items, only used when DN Cache is enabled.",
      "propertyOrder" : 6000,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
},
"groupconfig" : {
  "type" : "object",
  "title" : "Group Configuration",
  "propertyOrder" : 5,
  "properties" : {
    "sun-idrepo-ldapv3-config-group-container-name" : {
      "title" : "LDAP Groups Container Naming Attribute",
      "description" : "",
      "propertyOrder" : 3100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "sun-idrepo-ldapv3-config-groups-search-filter" : {
    "title" : "LDAP Groups Search Filter",
    "description" : "",

```

```
"propertyOrder" : 3000,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-memberurl" : {
"title" : "Attribute Name of Group Member URL",
"description" : "",
"propertyOrder" : 3700,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-uniquemember" : {
"title" : "Attribute Name of Unique Member",
"description" : "",
"propertyOrder" : 3600,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-attributes" : {
"title" : "LDAP Groups Attributes",
"description" : "",
"propertyOrder" : 3400,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-objectclass" : {
"title" : "LDAP Groups Object Class",
"description" : "",
"propertyOrder" : 3300,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-memberof" : {
"title" : "Attribute Name for Group Membership",
"description" : "",
"propertyOrder" : 3500,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-groups-search-attribute" : {
"title" : "LDAP Groups Search Attribute",
"description" : "",
"propertyOrder" : 2900,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
}
```

```
"sun-idrepo-ldapv3-config-group-container-value" : {
  "title" : "LDAP Groups Container Value",
  "description" : "",
  "propertyOrder" : 3200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
},
"authentication" : {
  "type" : "object",
  "title" : "Authentication Configuration",
  "propertyOrder" : 4,
  "properties" : {
    "sun-idrepo-ldapv3-config-auth-naming-attr" : {
      "title" : "Authentication Naming Attribute",
      "description" : "",
      "propertyOrder" : 5200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"pluginconfig" : {
  "type" : "object",
  "title" : "Plug-in Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "sunIdRepoClass" : {
      "title" : "LDAPv3 Repository Plug-in Class Name",
      "description" : "",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sunIdRepoSupportedOperations" : {
      "title" : "LDAPv3 Plug-in Supported Types and Operations",
      "description" : "",
      "propertyOrder" : 1900,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sunIdRepoAttributeMapping" : {
      "title" : "Attribute Name Mapping",
      "description" : "",
      "propertyOrder" : 1800,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

```

    }
  },
  "persistentsearch" : {
    "type" : "object",
    "title" : "Persistent Search Controls",
    "propertyOrder" : 7,
    "properties" : {
      "sun-idrepo-ldapv3-config-psearch-filter" : {
        "title" : "Persistent Search Filter",
        "description" : "",
        "propertyOrder" : 5600,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
      },
      "sun-idrepo-ldapv3-config-psearchbase" : {
        "title" : "Persistent Search Base DN",
        "description" : "",
        "propertyOrder" : 5500,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
      },
      "sun-idrepo-ldapv3-config-psearch-scope" : {
        "title" : "Persistent Search Scope",
        "description" : "",
        "propertyOrder" : 5700,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
      }
    }
  },
  "errorhandling" : {
    "type" : "object",
    "title" : "Error Handling Configuration",
    "propertyOrder" : 8,
    "properties" : {
      "com.iplanet.am.ldap.connection.delay.between.retries" : {
        "title" : "The Delay Time Between Retries",
        "description" : "In milliseconds.",
        "propertyOrder" : 5800,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
      }
    }
  }
}

```

1.111. OpenIdConnectModule

1.111.1. Realm Operations

Resource path: `/realm-config/authentication/modules/openidconnect`

Resource version: `1.0`

1.111.1.1. create

Usage:

```
am> create OpenIdConnectModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "cryptoContextValue" : {
      "title" : "OpenID Connect validation configuration value",
      "description" : "The discovery url, or jwk url, or the client_secret, corresponding to the
selection above.<br><br>If discovery or jwk url entered, entry must be in valid url format, <br>/>e.g.
https://accounts.google.com/.well-known/openid-configuration<br><i>NB </i>If client_secret entered,
entry is ignored and the value of the Client Secret is used.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "accountProviderClass" : {
      "title" : "Account provider class",
      "description" : "Name of the class implementing the account provider.<br><br>This class
is used by the module to find the account from the attributes mapped by the Account Mapper
<code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "jwtToLdapAttributeMappings" : {
      "title" : "Mapping of jwt attributes to local LDAP attributes",
      "description" : "Format: jwt_attribute=local_ldap_attribute<br><br>Mappings allow jwt entries to
drive principal lookup. This entry determines how to translate between local LDAP attributes and the
entries in the jwt. See <a href=\"http://openid.net/specs/openid-connect-core-1_0.html#ScopeClaims
```

```

\" target=\"_blank\">OpenID Connect Core 1.0 Specification</a> section 5.4 on how to request the
inclusion of additional attributes in issued ID Tokens.",
  "propertyOrder" : 600,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"acceptedAuthorizedParties" : {
  "title" : "List of accepted authorized parties",
  "description" : "A list of case sensitive strings which can be either string or URI
values<br><br>A list of authorized parties which this module will accept ID tokens from. This will be
checked against the authorized party claim of the ID token.",
  "propertyOrder" : 800,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"principalMapperClass" : {
  "title" : "Principal mapper class",
  "description" : "Class which implements mapping of jwt state to a Principal in
the local identity repository<br><br>Any custom implementation must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"cryptoContextType" : {
  "title" : "OpenID Connect validation configuration type",
  "description" : "Please select either 1. the issuer discovery url, 2. the issuer jwk url, or 3.
the client_secret.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"idTokenIssuer" : {
  "title" : "Name of OpenID Connect ID Token Issuer",
  "description" : "Value must match the iss field in issued ID Token",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"idTokenHeaderName" : {
  "title" : "Name of header referencing the ID Token",
  "description" : "",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"clientSecret" : {

```

```

    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 301,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "useSubClaimIfNoMatch" : {
    "title" : "Use \"sub\" claim if no match",
    "description" : "If no account is found that matches, whether to use the \"sub\" claim as the
principal name or (if false) to fail.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "audienceName" : {
    "title" : "Audience name",
    "description" : "A case sensitive string<br><br>The audience name for this OpenID Conenct
module. This will be used to check that the ID token received is intended for this module as an
audience.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}

```

1.111.1.2. delete

Usage:

```
am> delete OpenIdConnectModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.111.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OpenIdConnectModule --realm Realm --actionName getAllTypes
```


1.111.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OpenIdConnectModule --realm Realm --actionName getCreatableTypes
```

1.111.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OpenIdConnectModule --realm Realm --actionName nextdescendents
```

1.111.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query OpenIdConnectModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.111.1.7. read

Usage:

```
am> read OpenIdConnectModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.111.1.8. update

Usage:

```
am> update OpenIdConnectModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "cryptoContextValue" : {
      "title" : "OpenID Connect validation configuration value",
      "description" : "The discovery url, or jwk url, or the client_secret, corresponding to the
selection above.<br><br>If discovery or jwk url entered, entry must be in valid url format, <br/>e.g.
https://accounts.google.com/.well-known/openid-configuration<br/><i>NB </i>If client_secret entered,
entry is ignored and the value of the Client Secret is used.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "accountProviderClass" : {
      "title" : "Account provider class",
      "description" : "Name of the class implementing the account provider.<br><br>This class
is used by the module to find the account from the attributes mapped by the Account Mapper
<code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "jwtToLdapAttributeMappings" : {
      "title" : "Mapping of jwt attributes to local LDAP attributes",
      "description" : "Format: jwt_attribute=local_ldap_attribute<br><br>Mappings allow jwt entries to
drive principal lookup. This entry determines how to translate between local LDAP attributes and the
entries in the jwt. See <a href=\"http://openid.net/specs/openid-connect-core-1_0.html#ScopeClaims
\" target=\"_blank\">OpenID Connect Core 1.0 Specification</a> section 5.4 on how to request the
inclusion of additional attributes in issued ID Tokens.",
      "propertyOrder" : 600,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "acceptedAuthorizedParties" : {
      "title" : "List of accepted authorized parties",
      "description" : "A list of case sensitive strings which can be either string or URI
values<br><br>A list of authorized parties which this module will accept ID tokens from. This will be
checked against the authorized party claim of the ID token.",
      "propertyOrder" : 800,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

```

},
"principalMapperClass" : {
  "title" : "Principal mapper class",
  "description" : "Class which implements mapping of jwt state to a Principal in
the local identity repository<br><br>Any custom implementation must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"cryptoContextType" : {
  "title" : "OpenID Connect validation configuration type",
  "description" : "Please select either 1. the issuer discovery url, 2. the issuer jwk url, or 3.
the client_secret.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
},
"idTokenIssuer" : {
  "title" : "Name of OpenID Connect ID Token Issuer",
  "description" : "Value must match the iss field in issued ID Token",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
},
"idTokenHeaderName" : {
  "title" : "Name of header referencing the ID Token",
  "description" : "",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
},
"clientSecret" : {
  "title" : "Client Secret",
  "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
  "propertyOrder" : 301,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
},
"useSubClaimIfNoMatch" : {
  "title" : "Use \"sub\" claim if no match",
  "description" : "If no account is found that matches, whether to use the \"sub\" claim as the
principal name or (if false) to fail.",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
},
"audienceName" : {
  "title" : "Audience name",

```

```
"description" : "A case sensitive string<br><br>The audience name for this OpenID Conenct  
module. This will be used to check that the ID token received is intended for this module as an  
audience.",  
  "propertyOrder" : 700,  
  "required" : true,  
  "type" : "string",  
  "exampleValue" : ""  
}  
}  
}
```

1.111.2. Global Operations

Resource path: `/global-config/authentication/modules/openidconnect`

Resource version: `1.0`

1.111.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action OpenIdConnectModule --global --actionName getAllTypes
```

1.111.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action OpenIdConnectModule --global --actionName getCreatableTypes
```

1.111.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action OpenIdConnectModule --global --actionName nextdescendents
```

1.111.2.4. read

Usage:

```
am> read OpenIdConnectModule --global
```

1.111.2.5. update

Usage:

```
am> update OpenIdConnectModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "useSubClaimIfNoMatch" : {
          "title" : "Use \"sub\" claim if no match",
          "description" : "If no account is found that matches, whether to use the \"sub\" claim as
the principal name or (if false) to fail.",
          "propertyOrder" : 1000,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "principalMapperClass" : {
          "title" : "Principal mapper class",
          "description" : "Class which implements mapping of jwt state to a Principal
in the local identity repository<br><br>Any custom implementation must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.",
          "propertyOrder" : 900,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "cryptoContextType" : {
          "title" : "OpenID Connect validation configuration type",
          "description" : "Please select either 1. the issuer discovery url, 2. the issuer jwk url, or
3. the client_secret.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "acceptedAuthorizedParties" : {
          "title" : "List of accepted authorized parties",
          "description" : "A list of case sensitive strings which can be either string or URI
values<br><br>A list of authorized parties which this module will accept ID tokens from. This will be
checked against the authorized party claim of the ID token.",
          "propertyOrder" : 800,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      }
    }
  }
}
```

```

"idTokenIssuer" : {
  "title" : "Name of OpenID Connect ID Token Issuer",
  "description" : "Value must match the iss field in issued ID Token",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"idTokenHeaderName" : {
  "title" : "Name of header referencing the ID Token",
  "description" : "",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"cryptoContextValue" : {
  "title" : "OpenID Connect validation configuration value",
  "description" : "The discovery url, or jwk url, or the client_secret, corresponding to the
selection above.<br><br>If discovery or jwk url entered, entry must be in valid url format, <br>e.g.
https://accounts.google.com/.well-known/openid-configuration<br><i>NB </i>If client_secret entered,
entry is ignored and the value of the Client Secret is used.",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"accountProviderClass" : {
  "title" : "Account provider class",
  "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account Mapper
<code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"clientSecret" : {
  "title" : "Client Secret",
  "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
  "propertyOrder" : 301,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"audienceName" : {
  "title" : "Audience name",
  "description" : "A case sensitive string<br><br>The audience name for this OpenID Conenct
module. This will be used to check that the ID token received is intended for this module as an
audience.",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"jwtToLdapAttributeMappings" : {

```

```
    "title" : "Mapping of jwt attributes to local LDAP attributes",
    "description" : "Format: jwt_attribute=local_ldap_attribute<br><br>Mappings allow jwt
entries to drive principal lookup. This entry determines how to translate between local LDAP
attributes and the entries in the jwt. See <a href=\"http://openid.net/specs/openid-connect-
core-1_0.html#ScopeClaims\" target=\"_blank\">OpenID Connect Core 1.0 Specification</a> section 5.4 on
how to request the inclusion of additional attributes in issued ID Tokens.",
    "propertyOrder" : 600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
```

1.112. PageNode

1.112.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/PageNode`

Resource version: `1.0`

1.112.1.1. create

Usage:

```
am> create PageNode --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Authentication tree Page Node",
```

```

"type" : "object",
"title" : "Page Node",
"properties" : {
  "nodes" : {
    "type" : "array",
    "title" : "Page Nodes",
    "description" : "The child nodes, in the order they are returned to the authentication client",
    "items" : {
      "type" : "object",
      "title" : "Child Node",
      "description" : "A node that is used in the page",
      "properties" : {
        "id" : {
          "type" : "string",
          "title" : "Node ID",
          "description" : "ID of the child node"
        },
        "displayName" : {
          "type" : "string",
          "title" : "Display name",
          "description" : "The display name of the child node"
        },
        "nodeType" : {
          "type" : "string",
          "title" : "Node type",
          "description" : "The type of the child node"
        }
      }
    }
  }
},
"required" : [ "nodes" ]
}

```

1.112.1.2. delete

Usage:

```
am> delete PageNode --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.112.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PageNode --realm Realm --actionName getAllTypes
```


1.112.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PageNode --realm Realm --actionName getCreatableTypes
```

1.112.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action PageNode --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.112.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PageNode --realm Realm --actionName nextdescendents
```

1.112.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query PageNode --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.112.1.8. read

Usage:

```
am> read PageNode --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.112.1.9. update

Usage:

```
am> update PageNode --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Authentication tree Page Node",
  "type" : "object",
  "title" : "Page Node",
  "properties" : {
    "nodes" : {
      "type" : "array",
      "title" : "Page Nodes",
      "description" : "The child nodes, in the order they are returned to the authentication client",
      "items" : {
        "type" : "object",
        "title" : "Child Node",
        "description" : "A node that is used in the page",
        "properties" : {
          "id" : {
            "type" : "string",
            "title" : "Node ID",
            "description" : "ID of the child node"
          },
          "displayName" : {
            "type" : "string",
            "title" : "Display name",
            "description" : "The display name of the child node"
          },
          "nodeType" : {
            "type" : "string",
            "title" : "Node type",
            "description" : "The type of the child node"
          }
        }
      }
    }
  }
}
```

```
    }  
  }  
},  
"required" : [ "nodes" ]  
}
```

1.113. PasswordCollector

1.113.1. Realm Operations

Resource path: [/realm-config/authentication/authenticationtrees/nodes/PasswordCollectorNode](#)

Resource version: 1.0

1.113.1.1. create

Usage:

```
am> create PasswordCollector --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "type" : "object",  
  "required" : [ ]  
}
```

1.113.1.2. delete

Usage:

```
am> delete PasswordCollector --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.113.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PasswordCollector --realm Realm --actionName getAllTypes
```

1.113.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PasswordCollector --realm Realm --actionName getCreatableTypes
```

1.113.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action PasswordCollector --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.113.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PasswordCollector --realm Realm --actionName nextdescendents
```

1.113.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query PasswordCollector --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.113.1.8. read

Usage:

```
am> read PasswordCollector --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.113.1.9. update

Usage:

```
am> update PasswordCollector --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "required" : [ ]
}
```

1.114. PendingUmaRequests

1.114.1. Realm Operations

Pending UMA requests provider is responsible for allowing, denying and querying the guest requests for user resources. Available actions are Query, Read, Deny (all requests or one request), Approve (all requests or one request)

Resource path: `/users/{user}/uma/pendingrequests`

Resource version: `1.0`

1.114.1.1. approve

Approve the pending request and grant access to the requesting user.

Usage:

```
am> action PendingUmaRequests --realm Realm --id id --body body --user user --actionName approve
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Approve action request schema.",
  "type" : "object",
  "title" : "Approve action request schema",
  "properties" : {
    "scopes" : {
      "type" : {
        "type" : "array",
        "title" : "Approve request scopes",
        "description" : "The list of the scopes the requesting user gets access to.",
        "items" : {
          "type" : "string"
        }
      }
    }
  },
  "required" : [ "scopes" ]
}
```

--user

Pending UMA requests provider is responsible for allowing, denying and querying the guest requests for user resources. Available actions are Query, Read, Deny (all requests or one request), Approve (all requests or one request)

1.114.1.2. approveAll

Approve every pending requests and grant access to the requesting user.

Usage:

```
am> action PendingUmaRequests --realm Realm --body body --user user --actionName approveAll
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Approve action request schema.",
  "type" : "object",
  "title" : "Approve action request schema",
  "properties" : {
    "scopes" : {
      "type" : {
        "type" : "array",
        "title" : "Approve request scopes",
        "description" : "The list of the scopes the requesting user gets access to.",
        "items" : {
          "type" : "string"
        }
      }
    }
  },
  "required" : [ "scopes" ]
}
```

--user

Pending UMA requests provider is responsible for allowing, denying and querying the guest requests for user resources. Available actions are Query, Read, Deny (all requests or one request), Approve (all requests or one request)

1.114.1.3. query

Query the collection of pending requests.

Usage:

```
am> query PendingUmaRequests --realm Realm --filter filter --user user
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

--user

Pending UMA requests provider is responsible for allowing, denying and querying the guest requests for user resources. Available actions are Query, Read, Deny (all requests or one request), Approve (all requests or one request)

1.114.1.4. read

Read pending request

Usage:

```
am> read PendingUmaRequests --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

Pending UMA requests provider is responsible for allowing, denying and querying the guest requests for user resources. Available actions are Query, Read, Deny (all requests or one request), Approve (all requests or one request)

1.115. PersistentCookieDecision

1.115.1. Realm Operations

Resource path: [/realm-config/authentication/authenticationtrees/nodes/PersistentCookieDecisionNode](#)

Resource version: [1.0](#)

1.115.1.1. create

Usage:

```
am> create PersistentCookieDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "type" : "object",
```



```

"properties" : {
  "useHttpOnlyCookie" : {
    "title" : "Use HTTP Only Cookie",
    "description" : "Sets the persistent cookie as \"HttpOnly\".",
    "propertyOrder" : 400,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "useSecureCookie" : {
    "title" : "Use Secure Cookie",
    "description" : "Sets the persistent cookie as \"Secure\".",
    "propertyOrder" : 300,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "hmacSigningKey" : {
    "title" : "HMAC Signing Key",
    "description" : "Base64-encoded 256-bit key to use for HMAC signing of the cookie.",
    "propertyOrder" : 500,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "idleTimeout" : {
    "title" : "Idle Timeout",
    "description" : "The maximum idle time between requests before the cookie is invalidated, in
hours.",
    "propertyOrder" : 100,
    "type" : "integer",
    "exampleValue" : ""
  },
  "enforceClientIp" : {
    "title" : "Enforce Client IP",
    "description" : "Enforces that the persistent cookie can only be used from the same client IP to
which the cookie was issued.",
    "propertyOrder" : 200,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "persistentCookieName" : {
    "title" : "Persistent Cookie Name",
    "description" : "The name of the persistent cookie.",
    "propertyOrder" : 600,
    "type" : "string",
    "exampleValue" : ""
  }
},
"required" : [ "idleTimeout", "useHttpOnlyCookie", "hmacSigningKey", "enforceClientIp",
"persistentCookieName", "useSecureCookie" ]
}

```

1.115.1.2. delete

Usage:

```
am> delete PersistentCookieDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.115.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PersistentCookieDecision --realm Realm --actionName getAllTypes
```

1.115.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PersistentCookieDecision --realm Realm --actionName getCreatableTypes
```

1.115.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action PersistentCookieDecision --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.115.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PersistentCookieDecision --realm Realm --actionName nextdescendents
```

1.115.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query PersistentCookieDecision --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.115.1.8. read

Usage:

```
am> read PersistentCookieDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.115.1.9. update

Usage:

```
am> update PersistentCookieDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "useHttpOnlyCookie" : {
      "title" : "Use HTTP Only Cookie",
      "description" : "Sets the persistent cookie as \"HttpOnly\".",
      "propertyOrder" : 400,
    }
  }
}
```

```
    "type" : "boolean",
    "exampleValue" : ""
  },
  "useSecureCookie" : {
    "title" : "Use Secure Cookie",
    "description" : "Sets the persistent cookie as \"Secure\".",
    "propertyOrder" : 300,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "hmacSigningKey" : {
    "title" : "HMAC Signing Key",
    "description" : "Base64-encoded 256-bit key to use for HMAC signing of the cookie.",
    "propertyOrder" : 500,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "idleTimeout" : {
    "title" : "Idle Timeout",
    "description" : "The maximum idle time between requests before the cookie is invalidated, in
hours.",
    "propertyOrder" : 100,
    "type" : "integer",
    "exampleValue" : ""
  },
  "enforceClientIp" : {
    "title" : "Enforce Client IP",
    "description" : "Enforces that the persistent cookie can only be used from the same client IP to
which the cookie was issued.",
    "propertyOrder" : 200,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "persistentCookieName" : {
    "title" : "Persistent Cookie Name",
    "description" : "The name of the persistent cookie.",
    "propertyOrder" : 600,
    "type" : "string",
    "exampleValue" : ""
  }
},
"required" : [ "idleTimeout", "useHttpOnlyCookie", "hmacSigningKey", "enforceClientIp",
"persistentCookieName", "useSecureCookie" ]
}
```

1.116. PersistentCookieModule

1.116.1. Realm Operations

Resource path: [/realm-config/authentication/modules/persistentcookie](#)

Resource version: 1.0

1.116.1.1. create

Usage:

```
am> create PersistentCookieModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "hmacKey" : {
      "title" : "HMAC Signing Key",
      "description" : "Base64-encoded 256-bit key to use for HMAC signing of the cookie.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "useSecureCookie" : {
      "title" : "Use secure cookie",
      "description" : "Sets the persistent cookie as \"Secure\"",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "enforceClientIP" : {
      "title" : "Enforce Client IP",
      "description" : "Enforces that the persistent cookie can only be used from the same client IP to which the cookie was issued.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "useHttpOnlyCookie" : {
      "title" : "Use HTTP only cookie",
      "description" : "Sets the persistent cookie as \"HttpOnly\"",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "maxLife" : {
      "title" : "Max Life",
      "description" : "The maximum length of time the persistent cookie is valid for, in hours.",

```

```
    "propertyOrder" : 200,  
    "required" : true,  
    "type" : "integer",  
    "exampleValue" : ""  
  },  
  "idleTimeout" : {  
    "title" : "Idle Timeout",  
    "description" : "The maximum idle time between requests before the cookie is invalidated, in  
hours.",  
    "propertyOrder" : 100,  
    "required" : true,  
    "type" : "integer",  
    "exampleValue" : ""  
  },  
  "cookieName" : {  
    "title" : "Persistent Cookie Name",  
    "description" : "Sets the name of the persistent cookie",  
    "propertyOrder" : null,  
    "required" : true,  
    "type" : "string",  
    "exampleValue" : ""  
  }  
}
```

1.116.1.2. delete

Usage:

```
am> delete PersistentCookieModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.116.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PersistentCookieModule --realm Realm --actionName getAllTypes
```

1.116.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PersistentCookieModule --realm Realm --actionName getCreatableTypes
```

1.116.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PersistentCookieModule --realm Realm --actionName nextdescendents
```

1.116.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query PersistentCookieModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.116.1.7. read

Usage:

```
am> read PersistentCookieModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.116.1.8. update

Usage:

```
am> update PersistentCookieModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "hmacKey" : {
      "title" : "HMAC Signing Key",
      "description" : "Base64-encoded 256-bit key to use for HMAC signing of the cookie.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "useSecureCookie" : {
      "title" : "Use secure cookie",
      "description" : "Sets the persistent cookie as \"Secure\"",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "enforceClientIP" : {
      "title" : "Enforce Client IP",
      "description" : "Enforces that the persistent cookie can only be used from the same client IP to
which the cookie was issued.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "useHttpOnlyCookie" : {
      "title" : "Use HTTP only cookie",
      "description" : "Sets the persistent cookie as \"HttpOnly\"",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "maxLife" : {
      "title" : "Max Life",
      "description" : "The maximum length of time the persistent cookie is valid for, in hours.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "idleTimeout" : {
      "title" : "Idle Timeout",
      "description" : "The maximum idle time between requests before the cookie is invalidated, in
hours.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "cookieName" : {
```



```
"title" : "Persistent Cookie Name",
"description" : "Sets the name of the persistent cookie",
"propertyOrder" : null,
"required" : true,
"type" : "string",
"exampleValue" : ""
}
}
}
```

1.116.2. Global Operations

Resource path: `/global-config/authentication/modules/persistentcookie`

Resource version: `1.0`

1.116.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PersistentCookieModule --global --actionName getAllTypes
```

1.116.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PersistentCookieModule --global --actionName getCreatableTypes
```

1.116.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PersistentCookieModule --global --actionName nextdescendents
```

1.116.2.4. read

Usage:

```
am> read PersistentCookieModule --global
```

1.116.2.5. update

Usage:

```
am> update PersistentCookieModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "useHttpOnlyCookie" : {
          "title" : "Use HTTP only cookie",
          "description" : "Sets the persistent cookie as \"HttpOnly\"",
          "propertyOrder" : 500,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "maxLife" : {
          "title" : "Max Life",
          "description" : "The maximum length of time the persistent cookie is valid for, in hours.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "useSecureCookie" : {
          "title" : "Use secure cookie",
          "description" : "Sets the persistent cookie as \"Secure\"",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "hmacKey" : {
          "title" : "HMAC Signing Key",
          "description" : "Base64-encoded 256-bit key to use for HMAC signing of the cookie.",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "string",
          "format" : "password",
          "exampleValue" : ""
        },
        "idleTimeout" : {
          "title" : "Idle Timeout",
          "description" : "The maximum idle time between requests before the cookie is invalidated, in
hours.",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "integer",
```

```
    "exampleValue" : ""
  },
  "cookieName" : {
    "title" : "Persistent Cookie Name",
    "description" : "Sets the name of the persistent cookie",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "enforceClientIP" : {
    "title" : "Enforce Client IP",
    "description" : "Enforces that the persistent cookie can only be used from the same client
IP to which the cookie was issued.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
```

1.117. Platform

1.117.1. Global Operations

Resource path: `/global-config/services/platform`

Resource version: `1.0`

1.117.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Platform --global --actionName getAllTypes
```

1.117.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Platform --global --actionName getCreatableTypes
```

1.117.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Platform --global --actionName nextdescendents
```

1.117.1.4. read

Usage:

```
am> read Platform --global
```

1.117.1.5. update

Usage:

```
am> update Platform --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "locale" : {
      "title" : "Platform Locale",
      "description" : "Set the fallback locale used when the user locale cannot be determined.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "cookieDomains" : {
      "title" : "Cookie Domains",
      "description" : "Set the list of domains into which OpenAM writes cookies.<br><br>If you set multiple cookie domains, OpenAM still only sets the cookie in the domain the client uses to access OpenAM. If this property is left blank, then the fully qualified domain name of the server is used to set the cookie domain, meaning that a host cookie rather than a domain cookie is set.",
      "propertyOrder" : 200,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.118. Policies

1.118.1. Realm Operations

The Policy resource with copy and move support endpoint is responsible for managing policies. It supports all the operations that previous version of Policy resource endpoint supports - create, read, update, delete, query, evalute and evaluateTree action - with two new actions move and copy for copying and moving policies between realms

Resource path: `/policies`

Resource version: `2.1`

1.118.1.1. copy

Copy a list of policies

Usage:

```
am> action Policies --realm Realm --body body --actionName copy
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Policy copy action schema",
  "type" : "object",
  "title" : "Policy copy action schema",
  "properties" : {
    "from" : {
      "title" : "Copy/move from",
      "description" : "Policy copy/move origin parameters",
      "type" : "object",
      "properties" : {
        "application" : {
          "title" : "Application",
          "description" : "The policy set in which the input policies are located",
          "type" : "string"
        }
      }
    },
    "required" : [ "application" ]
  },
  "to" : {
    "type" : "object",
    "title" : "Copy/Move To",
    "description" : "Policy copy/move destination parameters",
    "properties" : {
      "application" : {
        "title" : "Application",
```

```

    "description" : "The policy set in which to place the output policy. Required when copying
or moving a policy to a different policy set.",
    "type" : "string"
  },
  "realm" : {
    "title" : "Realm",
    "description" : "The realm in which to place the output policy. If not specified, OpenAM
copies or moves the policy within the realm identified in the URL. Required when copying or moving a
policy to a different realm.",
    "type" : "string"
  },
  "namePostfix" : {
    "title" : "Name postfix",
    "description" : "A value appended to output policy names in order to prevent name clashes",
    "type" : "string"
  }
},
"required" : [ "namePostfix" ]
},
"resourceTypeMapping" : {
  "title" : "Resource type mapping",
  "description" : "One or more resource types mappings, where the left side of the mapping
specifies the UUID of a resource type used by the input policies and the right side of the mapping
specifies the UUID of a resource type used by the output policies. The two resource types should have
the same resource patterns",
  "type" : "object",
  "additionalProperties" : {
    "type" : "string"
  }
}
},
"required" : [ "from", "to" ]
}

```

1.118.1.2. create

Create new policy

Usage:

```
am> create Policies --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Json schema for the policy resource",
  "title" : "Policy Resource Schema",
  "type" : "object",

```

```
"properties" : {
  "name" : {
    "title" : "Name",
    "description" : "String matching the name of the application",
    "type" : "string"
  },
  "active" : {
    "title" : "Active flag",
    "description" : "Boolean indicating whether OpenAM considers the policy active for evaluation purposes, defaults to false",
    "type" : "boolean"
  },
  "description" : {
    "title" : "Description",
    "description" : "String describing the policy",
    "type" : "string"
  },
  "applicationName" : {
    "title" : "Application name",
    "description" : "String containing the application name, such as \"iPlanetAMWebAgentService\", or \"mypolicysset\"",
    "type" : "string"
  },
  "actionValues" : {
    "title" : "Action values",
    "description" : "Set of string action names, each set to a boolean indicating whether the action is allowed. Chosen from the available actions provided by the associated Managing Resource Types resource type",
    "type" : "object",
    "additionalProperties" : {
      "type" : "boolean"
    }
  },
  "resources" : {
    "title" : "Resources",
    "description" : "List of the resource name pattern strings to which the policy applies. Must conform to the pattern templates provided by the associated Managing Resource Types resource type",
    "type" : "array",
    "items" : {
      "type" : "string"
    }
  },
  "subject" : {
    "title" : "Subject",
    "description" : "Specifies the subject conditions to which the policy applies, where subjects can be combined by using the built-in types \"AND\", \"OR\", and \"NOT\", and where subject implementations are pluggable",
    "type" : "object"
  },
  "condition" : {
    "title" : "Condition",
    "description" : "Specifies environment conditions, where conditions can be combined by using the built-in types \"AND\", \"OR\", and \"NOT\", and where condition implementations are pluggable",
    "type" : "object",
    "properties" : {
      "type" : {
        "type" : "string"
      }
    },
    "conditions" : {
```

```

        "type" : "array",
        "title" : "Condition",
        "description" : "Specifies environment conditions, where conditions can be combined by using
the built-in types \"AND\", \"OR\", and \"NOT\", and where condition implementations are pluggable",
        "items" : {
            "type" : "object"
        }
    }
},
"resourceTypeUuid" : {
    "title" : "Resource Type UUID",
    "description" : "The UUIDs of the resource type associated with the policy",
    "type" : "string"
},
"resourceAttributes" : {
    "title" : "Resource Attributes",
    "description" : "List of attributes to return with decisions. These attributes are known as
response attributes",
    "type" : "array",
    "items" : {
        "type" : "object"
    }
},
"lastModifiedBy" : {
    "title" : "Last Modified By",
    "description" : "A string containing the universal identifier DN of the subject that most
recently updated the policy",
    "type" : "string"
},
"lastModifiedDate" : {
    "title" : "Last Modified date",
    "description" : "An integer containing the last modified date and time, in number of seconds",
    "type" : "string"
},
"createdBy" : {
    "title" : "Created By",
    "description" : "A string containing the universal identifier DN of the subject that created the
policy",
    "type" : "string"
},
"creationDate" : {
    "title" : "Creation Date",
    "description" : "An integer containing the creation date and time, in number of seconds",
    "type" : "string"
}
}
}

```

1.118.1.3. delete

Delete policy

Usage:

```
am> delete Policies --realm Realm --id id
```


Parameters:

--id

The unique identifier for the resource.

1.118.1.4. evaluate

Request policy decisions for specific resources

Usage:

```
am> action Policies --realm Realm --body body --actionName evaluate
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Evaluate action schema",
  "title" : "Evaluate action schema",
  "type" : "object",
  "properties" : {
    "resources" : {
      "type" : "array",
      "title" : "Resources",
      "description" : "Specifies the list of resources for which to return decisions",
      "items" : {
        "type" : "string"
      }
    },
    "application" : {
      "title" : "Application",
      "description" : "Holds the name of the application, and defaults to \"iPlanetAMWebAgentService\" if not specified",
      "type" : "string"
    },
    "subject" : {
      "title" : "Subject",
      "description" : "Holds an object that represents the subject. You can specify one or more of the following keys. If you specify multiple keys, the subject can have multiple associated principals, and you can use subject conditions corresponding to any type in the request",
      "type" : "object",
      "properties" : {
        "ssoToken" : {
          "title" : "SSOToken",
          "description" : "The value is the SS0 token ID string for the subject",
          "type" : "string"
        },
        "jwt" : {
          "title" : "JWT",
          "description" : "The value is a JWT string",
          "type" : "string"
        }
      }
    }
  }
}
```

```

    "claims" : {
      "title" : "Claims",
      "description" : "The value is an object (map) of JWT claims to their values.",
      "type" : "object",
      "additionalProperties" : {
        "type" : "string"
      }
    }
  },
  "environment" : {
    "title" : "Environment",
    "description" : "Holds a map of keys to lists of values",
    "type" : "object",
    "additionalProperties" : {
      "type" : "array",
      "items" : {
        "type" : "string"
      }
    }
  }
},
"required" : [ "resources", "application" ]
}

```

1.118.1.5. evaluateTree

Request policy decisions for a tree of resources

Usage:

```
am> action Policies --realm Realm --body body --actionName evaluateTree
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Evaluate tree action schema",
  "title" : "Evaluate tree action schema",
  "type" : "object",
  "properties" : {
    "resource" : {
      "title" : "Resource",
      "description" : "Specifies the root resource for the decisions to return",
      "type" : "string"
    },
    "application" : {
      "title" : "Application",
      "description" : "Holds the name of the application, and defaults to \"iPlanetAMWebAgentService\" if not specified",
      "type" : "string"
    },
    "subject" : {

```

```

    "title" : "Subject",
    "description" : "Holds an object that represents the subject. You can specify one or more of the
following keys. If you specify multiple keys, the subject can have multiple associated principals,
and you can use subject conditions corresponding to any type in the request",
    "type" : "object",
    "properties" : {
      "ssoToken" : {
        "title" : "SSOToken",
        "description" : "The value is the SSO token ID string for the subject",
        "type" : "string"
      },
      "jwt" : {
        "title" : "JWT",
        "description" : "The value is a JWT string",
        "type" : "string"
      },
      "claims" : {
        "title" : "Claims",
        "description" : "The value is an object (map) of JWT claims to their values.",
        "type" : "object",
        "additionalProperties" : {
          "type" : "string"
        }
      }
    }
  },
  "environment" : {
    "title" : "Environment",
    "description" : "Holds a map of keys to lists of values",
    "type" : "object",
    "additionalProperties" : {
      "type" : "array",
      "items" : {
        "type" : "string"
      }
    }
  }
},
"required" : [ "resources", "application" ]
}

```

1.118.1.6. move

Move a list of policies

Usage:

```
am> action Policies --realm Realm --body body --actionName move
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",

```

```

"description" : "Policy copy action schema",
"type" : "object",
"title" : "Policy copy action schema",
"properties" : {
  "from" : {
    "title" : "Copy/move from",
    "description" : "Policy copy/move origin parameters",
    "type" : "object",
    "properties" : {
      "application" : {
        "title" : "Application",
        "description" : "The policy set in which the input policies are located",
        "type" : "string"
      }
    }
  },
  "required" : [ "application" ]
},
"to" : {
  "type" : "object",
  "title" : "Copy/Move To",
  "description" : "Policy copy/move destination parameters",
  "properties" : {
    "application" : {
      "title" : "Application",
      "description" : "The policy set in which to place the output policy. Required when copying
or moving a policy to a different policy set.",
      "type" : "string"
    },
    "realm" : {
      "title" : "Realm",
      "description" : "The realm in which to place the output policy. If not specified, OpenAM
copies or moves the policy within the realm identified in the URL. Required when copying or moving a
policy to a different realm.",
      "type" : "string"
    },
    "namePostfix" : {
      "title" : "Name postfix",
      "description" : "A value appended to output policy names in order to prevent name clashes",
      "type" : "string"
    }
  }
},
"required" : [ "namePostfix" ]
},
"resourceTypeMapping" : {
  "title" : "Resource type mapping",
  "description" : "One or more resource types mappings, where the left side of the mapping
specifies the UUID of a resource type used by the input policies and the right side of the mapping
specifies the UUID of a resource type used by the output policies. The two resource types should have
the same resource patterns",
  "type" : "object",
  "additionalProperties" : {
    "type" : "string"
  }
}
},
"required" : [ "from", "to" ]
}

```

1.118.1.7. query

Query the stored policies

Usage:

```
am> query Policies --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.118.1.8. read

Read policy

Usage:

```
am> read Policies --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.118.1.9. update

Update an existing policy

Usage:

```
am> update Policies --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Json schema for the policy resource",
  "title" : "Policy Resource Schema",
  "type" : "object",
  "properties" : {
    "name" : {
      "title" : "Name",
      "description" : "String matching the name of the application",
```

```

    "type" : "string"
  },
  "active" : {
    "title" : "Active flag",
    "description" : "Boolean indicating whether OpenAM considers the policy active for evaluation
purposes, defaults to false",
    "type" : "boolean"
  },
  "description" : {
    "title" : "Description",
    "description" : "String describing the policy",
    "type" : "string"
  },
  "applicationName" : {
    "title" : "Application name",
    "description" : "String containing the application name, such as \"iPlanetAMWebAgentService\",
or \"mypolicyset\"",
    "type" : "string"
  },
  "actionValues" : {
    "title" : "Action values",
    "description" : "Set of string action names, each set to a boolean indicating whether the action
is allowed. Chosen from the available actions provided by the associated Managing Resource Types
resource type",
    "type" : "object",
    "additionalProperties" : {
      "type" : "boolean"
    }
  },
  "resources" : {
    "title" : "Resources",
    "description" : "List of the resource name pattern strings to which the policy applies. Must
conform to the pattern templates provided by the associated Managing Resource Types resource type",
    "type" : "array",
    "items" : {
      "type" : "string"
    }
  },
  "subject" : {
    "title" : "Subject",
    "description" : "Specifies the subject conditions to which the policy applies, where subjects
can be combined by using the built-in types \"AND\", \"OR\", and \"NOT\", and where subject
implementations are pluggable",
    "type" : "object"
  },
  "condition" : {
    "title" : "Condition",
    "description" : "Specifies environment conditions, where conditions can be combined by using the
built-in types \"AND\", \"OR\", and \"NOT\", and where condition implementations are pluggable",
    "type" : "object",
    "properties" : {
      "type" : {
        "type" : "string"
      }
    }
  },
  "conditions" : {
    "type" : "array",
    "title" : "Condition",
    "description" : "Specifies environment conditions, where conditions can be combined by using
the built-in types \"AND\", \"OR\", and \"NOT\", and where condition implementations are pluggable",

```

```
        "items" : {
          "type" : "object"
        }
      }
    },
    "resourceTypeUuid" : {
      "title" : "Resource Type UUID",
      "description" : "The UUIDs of the resource type associated with the policy",
      "type" : "string"
    },
    "resourceAttributes" : {
      "title" : "Resource Attributes",
      "description" : "List of attributes to return with decisions. These attributes are known as response attributes",
      "type" : "array",
      "items" : {
        "type" : "object"
      }
    },
    "lastModifiedBy" : {
      "title" : "Last Modified By",
      "description" : "A string containing the universal identifier DN of the subject that most recently updated the policy",
      "type" : "string"
    },
    "lastModifiedDate" : {
      "title" : "Last Modified date",
      "description" : "An integer containing the last modified date and time, in number of seconds",
      "type" : "string"
    },
    "createdBy" : {
      "title" : "Created By",
      "description" : "A string containing the universal identifier DN of the subject that created the policy",
      "type" : "string"
    },
    "creationDate" : {
      "title" : "Creation Date",
      "description" : "An integer containing the creation date and time, in number of seconds",
      "type" : "string"
    }
  }
}
```

1.119. PolicyAgents

1.119.1. Realm Operations

Agents handler that is responsible for managing agents

Resource path: [/realm-config/agents/2.2_Agent](#)

Resource version: 1.0

1.119.1.1. create

Usage:

```
am> create PolicyAgents --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "cdssoRootUrl" : {
      "title" : "Agent Key Value(s)",
      "description" : "Set the agent properties with a key/value pair. This property is used by AM to receive agent requests for credential assertions about users. Currently, only one property is valid and all other properties will be ignored. Use the following format: <br> agentRootURL=protocol://hostname:port/ <br> The entry must be precise and agentRootURL is case sensitive.",
      "propertyOrder" : 22500,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "array",
          "required" : true
        }
      }
    },
    "description" : {
      "title" : "Description",
      "description" : "",
      "propertyOrder" : 22400,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : true
        }
      }
    }
  }
}
```



```
},
"userpassword" : {
  "title" : "Password",
  "description" : "",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"status" : {
  "title" : "Status",
  "description" : "Status of the agent configuration.",
  "propertyOrder" : 200,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
}
}
}
```

1.119.1.2. delete

Usage:

```
am> delete PolicyAgents --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.119.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PolicyAgents --realm Realm --actionName getAllTypes
```

1.119.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PolicyAgents --realm Realm --actionName getCreatableTypes
```

1.119.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PolicyAgents --realm Realm --actionName nextdescendents
```

1.119.1.6. query

Querying the agents of a specific type

Usage:

```
am> query PolicyAgents --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.119.1.7. read

Usage:

```
am> read PolicyAgents --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.119.1.8. update

Usage:

```
am> update PolicyAgents --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "cdssoRootUrl" : {
      "title" : "Agent Key Value(s)",
      "description" : "Set the agent properties with a key/value pair. This property is used by AM to receive agent requests for credential assertions about users. Currently, only one property is valid and all other properties will be ignored. Use the following format: <br> agentRootURL=protocol://hostname:port/ <br> The entry must be precise and agentRootURL is case sensitive.",
      "propertyOrder" : 22500,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "array",
          "required" : true
        }
      }
    },
    "description" : {
      "title" : "Description",
      "description" : "",
      "propertyOrder" : 22400,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : true
        }
      }
    },
    "userpassword" : {
      "title" : "Password",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "status" : {
      "title" : "Status",
      "description" : "Status of the agent configuration.",

```

```
"propertyOrder" : 200,  
"type" : "object",  
"exampleValue" : "",  
"properties" : {  
  "inherited" : {  
    "type" : "boolean",  
    "required" : true  
  },  
  "value" : {  
    "type" : "string",  
    "required" : true  
  }  
}  
}  
}
```

1.120. PolicyConfiguration

1.120.1. Realm Operations

Resource path: `/realm-config/services/policyconfiguration`

Resource version: `1.0`

1.120.1.1. create

Usage:

```
am> create PolicyConfiguration --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "type" : "object",  
  "properties" : {  
    "userAliasEnabled" : {  
      "title" : "User Alias",  
      "description" : "If enabled, OpenAM can evaluate policy for remote users aliased to local users.",  
      "propertyOrder" : 2000,  
      "required" : true,  
      "type" : "boolean",  
      "exampleValue" : ""  
    },  
    "searchTimeout" : {  
      "title" : "Search Timeout",
```

```

    "description" : "Time after which OpenAM returns an error for an incomplete search, in
seconds.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "ldapServer" : {
    "title" : "Primary LDAP Server",
    "description" : "Configuration directory server host:port that OpenAM searches for policy
information.<p><p>Format: <code>local OpenAM server name | hostname:port</code><p><p>Multiple
entries must be prefixed by local server name. Make sure to place the multiple entries on a single
line and separate the hostname:port URLs with a space. <p><p>For example, openam.example.com|
opendj.example.com:1389 opendj.example.com:2389",
    "propertyOrder" : 400,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "usersSearchScope" : {
    "title" : "LDAP Users Search Scope",
    "description" : "Search scope to find user entries.",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "bindDn" : {
    "title" : "LDAP Bind DN",
    "description" : "Bind DN to connect to the directory server for policy information.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "maximumSearchResults" : {
    "title" : "Maximum Results Returned from Search",
    "description" : "Search limit for LDAP searches.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "connectionPoolMinimumSize" : {
    "title" : "LDAP Connection Pool Minimum Size",
    "description" : "Minimum number of connections in the pool.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "policyHeartbeatTimeUnit" : {
    "title" : "Heartbeat Unit",
    "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>Use this option in case a firewall/loadbalancer can close idle connections, since the
heartbeat requests will ensure that the connections won't become idle.",

```

```

    "propertyOrder" : 1850,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "policyHeartbeatInterval" : {
    "title" : "Heartbeat Interval",
    "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>Use this option in case a firewall/loadbalancer can close idle connections, since
the heartbeat requests will ensure that the connections won't become idle.",
    "propertyOrder" : 1840,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "connectionPoolMaximumSize" : {
    "title" : "LDAP Connection Pool Maximum Size",
    "description" : "Maximum number of connections in the pool.",
    "propertyOrder" : 1800,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "realmSearchFilter" : {
    "title" : "LDAP Organization Search Filter",
    "description" : "Search filter to match organization entries.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sslEnabled" : {
    "title" : "LDAP SSL/TLS",
    "description" : "If enabled, OpenAM connects securely to the directory server. This requires
that you install the directory server certificate.",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "subjectsResultTTL" : {
    "title" : "Subjects Result Time to Live",
    "description" : "Maximum time that OpenAM caches a subject result for evaluating policy
requests, in minutes. A value of <code>0</code> prevents OpenAM from caching subject evaluations for
policy decisions.",
    "propertyOrder" : 1900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "usersSearchFilter" : {
    "title" : "LDAP Users Search Filter",
    "description" : "Search filter to match user entries.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "bindPassword" : {

```

```
"title" : "LDAP Bind Password",
"description" : "Bind password to connect to the directory server for policy information.",
"propertyOrder" : 800,
"required" : true,
"type" : "string",
"format" : "password",
"exampleValue" : ""
},
"usersBaseDn" : {
"title" : "LDAP Users Base DN",
"description" : "Base DN for LDAP Users subject searches.",
"propertyOrder" : 500,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"usersSearchAttribute" : {
"title" : "LDAP Users Search Attribute",
"description" : "Naming attribute for user entries.",
"propertyOrder" : 1300,
"required" : true,
"type" : "string",
"exampleValue" : ""
}
}
}
```

1.120.1.2. delete

Usage:

```
am> delete PolicyConfiguration --realm Realm
```

1.120.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PolicyConfiguration --realm Realm --actionName getAllTypes
```

1.120.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PolicyConfiguration --realm Realm --actionName getCreatableTypes
```

1.120.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PolicyConfiguration --realm Realm --actionName nextdescendents
```

1.120.1.6. read

Usage:

```
am> read PolicyConfiguration --realm Realm
```

1.120.1.7. update

Usage:

```
am> update PolicyConfiguration --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userAliasEnabled" : {
      "title" : "User Alias",
      "description" : "If enabled, OpenAM can evaluate policy for remote users aliased to local users.",
      "propertyOrder" : 2000,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "searchTimeout" : {
      "title" : "Search Timeout",
      "description" : "Time after which OpenAM returns an error for an incomplete search, in seconds.",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "ldapServer" : {
      "title" : "Primary LDAP Server",
      "description" : "Configuration directory server host:port that OpenAM searches for policy information.<p><p>Format: <code>local OpenAM server name | hostname:port</code><p><p>Multiple entries must be prefixed by local server name. Make sure to place the multiple entries on a single line and separate the hostname:port URLs with a space. <p><p>For example, openam.example.com|opendj.example.com:1389 opendj.example.com:2389",
      "propertyOrder" : 400,
      "required" : true,
      "items" : {
        "type" : "string"
      }
    },
  },
}
```



```

    "type" : "array",
    "exampleValue" : ""
  },
  "usersSearchScope" : {
    "title" : "LDAP Users Search Scope",
    "description" : "Search scope to find user entries.",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "bindDn" : {
    "title" : "LDAP Bind DN",
    "description" : "Bind DN to connect to the directory server for policy information.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "maximumSearchResults" : {
    "title" : "Maximum Results Returned from Search",
    "description" : "Search limit for LDAP searches.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "connectionPoolMinimumSize" : {
    "title" : "LDAP Connection Pool Minimum Size",
    "description" : "Minimum number of connections in the pool.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "policyHeartbeatTimeUnit" : {
    "title" : "Heartbeat Unit",
    "description" : "Defines the time unit corresponding to the Heartbeat Interval
    setting.<br><br>Use this option in case a firewall/loadbalancer can close idle connections, since the
    heartbeat requests will ensure that the connections won't become idle.",
    "propertyOrder" : 1850,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "policyHeartbeatInterval" : {
    "title" : "Heartbeat Interval",
    "description" : "Specifies how often should OpenAM send a heartbeat request to the
    directory.<br><br>Use this option in case a firewall/loadbalancer can close idle connections, since
    the heartbeat requests will ensure that the connections won't become idle.",
    "propertyOrder" : 1840,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "connectionPoolMaximumSize" : {
    "title" : "LDAP Connection Pool Maximum Size",
    "description" : "Maximum number of connections in the pool.",
    "propertyOrder" : 1800,

```

```
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "realmSearchFilter" : {
    "title" : "LDAP Organization Search Filter",
    "description" : "Search filter to match organization entries.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sslEnabled" : {
    "title" : "LDAP SSL/TLS",
    "description" : "If enabled, OpenAM connects securely to the directory server. This requires
that you install the directory server certificate.",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "subjectsResultTTL" : {
    "title" : "Subjects Result Time to Live",
    "description" : "Maximum time that OpenAM caches a subject result for evaluating policy
requests, in minutes. A value of <code>0</code> prevents OpenAM from caching subject evaluations for
policy decisions.",
    "propertyOrder" : 1900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "usersSearchFilter" : {
    "title" : "LDAP Users Search Filter",
    "description" : "Search filter to match user entries.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "bindPassword" : {
    "title" : "LDAP Bind Password",
    "description" : "Bind password to connect to the directory server for policy information.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "usersBaseDn" : {
    "title" : "LDAP Users Base DN",
    "description" : "Base DN for LDAP Users subject searches.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "usersSearchAttribute" : {
    "title" : "LDAP Users Search Attribute",
    "description" : "Naming attribute for user entries.",
```

```
"propertyOrder" : 1300,  
"required" : true,  
"type" : "string",  
"exampleValue" : ""  
  }  
}  
}
```

1.120.2. Global Operations

Resource path: `/global-config/services/policyconfiguration`

Resource version: `1.0`

1.120.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PolicyConfiguration --global --actionName getAllTypes
```

1.120.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PolicyConfiguration --global --actionName getCreatableTypes
```

1.120.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PolicyConfiguration --global --actionName nextdescendents
```

1.120.2.4. read

Usage:

```
am> read PolicyConfiguration --global
```

1.120.2.5. update

Usage:

```
am> update PolicyConfiguration --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "realmAliasReferrals" : {
      "title" : "Realm Alias Referrals",
      "description" : "If yes, then OpenAM allows creation of policies for HTTP and HTTPS resources
whose FQDN matches the DNS alias for the realm even when no referral policy exists.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "continueEvaluationOnDeny" : {
      "title" : "Continue Evaluation on Deny Decision",
      "description" : "If no, then OpenAM stops evaluating policy as soon as it reaches a deny
decision.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "resourceComparators" : {
      "title" : "Resource Comparator",
      "description" : "OpenAM uses resource comparators to match resources specified in policy rules.
When setting comparators on the command line, separate fields with <code>|</code> characters.",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "defaults" : {
      "properties" : {
        "policyHeartbeatInterval" : {
          "title" : "Heartbeat Interval",
          "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>Use this option in case a firewall/loadbalancer can close idle connections, since
the heartbeat requests will ensure that the connections won't become idle.",
          "propertyOrder" : 1840,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "bindPassword" : {
          "title" : "LDAP Bind Password",
          "description" : "Bind password to connect to the directory server for policy information.",
          "propertyOrder" : 800,
          "required" : true,

```

```

    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "usersSearchScope" : {
    "title" : "LDAP Users Search Scope",
    "description" : "Search scope to find user entries.",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "connectionPoolMinimumSize" : {
    "title" : "LDAP Connection Pool Minimum Size",
    "description" : "Minimum number of connections in the pool.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "bindDn" : {
    "title" : "LDAP Bind DN",
    "description" : "Bind DN to connect to the directory server for policy information.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "policyHeartbeatTimeUnit" : {
    "title" : "Heartbeat Unit",
    "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>Use this option in case a firewall/loadbalancer can close idle connections, since the
heartbeat requests will ensure that the connections won't become idle.",
    "propertyOrder" : 1850,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "maximumSearchResults" : {
    "title" : "Maximum Results Returned from Search",
    "description" : "Search limit for LDAP searches.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "searchTimeout" : {
    "title" : "Search Timeout",
    "description" : "Time after which OpenAM returns an error for an incomplete search, in
seconds.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "connectionPoolMaximumSize" : {
    "title" : "LDAP Connection Pool Maximum Size",
    "description" : "Maximum number of connections in the pool.",
    "propertyOrder" : 1800,

```

```

    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "usersBaseDn" : {
    "title" : "LDAP Users Base DN",
    "description" : "Base DN for LDAP Users subject searches.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "usersSearchFilter" : {
    "title" : "LDAP Users Search Filter",
    "description" : "Search filter to match user entries.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "realmSearchFilter" : {
    "title" : "LDAP Organization Search Filter",
    "description" : "Search filter to match organization entries.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "subjectsResultTTL" : {
    "title" : "Subjects Result Time to Live",
    "description" : "Maximum time that OpenAM caches a subject result for evaluating policy requests, in minutes. A value of <code>0</code> prevents OpenAM from caching subject evaluations for policy decisions.",
    "propertyOrder" : 1900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "usersSearchAttribute" : {
    "title" : "LDAP Users Search Attribute",
    "description" : "Naming attribute for user entries.",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sslEnabled" : {
    "title" : "LDAP SSL/TLS",
    "description" : "If enabled, OpenAM connects securely to the directory server. This requires that you install the directory server certificate.",
    "propertyOrder" : 1600,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ldapServer" : {
    "title" : "Primary LDAP Server",
    "description" : "Configuration directory server host:port that OpenAM searches for policy information.<p><p>Format: <code>local OpenAM server name | hostname:port</code><p><p>Multiple

```

```

entries must be prefixed by local server name. Make sure to place the multiple entries on a single
line and separate the hostname:port URLs with a space. <p><p>For example, openam.example.com|
opendj.example.com:1389 opendj.example.com:2389",
  "propertyOrder" : 400,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"userAliasEnabled" : {
  "title" : "User Alias",
  "description" : "If enabled, OpenAM can evaluate policy for remote users aliased to local
users.",
  "propertyOrder" : 2000,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
}
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}
}

```

1.121. PollingWaitNode

1.121.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/PollingWaitNode`

Resource version: [1.0](#)

1.121.1.1. create

Usage:

```
am> create PollingWaitNode --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "exitable" : {
      "title" : "Exitable",
      "description" : "Choose whether to display a link which allows the user to leave the node early.
Creates a new outcome.",
      "propertyOrder" : 500,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "spamDetectionEnabled" : {
      "title" : "Enable Spam Detection",
      "description" : "Choose whether spam detection is enforced for this node. Creates a new
outcome.",
      "propertyOrder" : 200,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "secondsToWait" : {
      "title" : "Seconds To Wait",
      "description" : "How many seconds to wait before proceeding to the next node in the tree.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    },
    "waitingMessage" : {
      "title" : "Waiting Message",
      "description" : "Localisation overrides for the waiting message. May use {{time}} to get the
number of seconds remaining. This is a map of locale to message.",
      "propertyOrder" : 400,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "exitMessage" : {
    "title" : "Exit Message",
    "description" : "Localisation overrides for the exit message. The whole string will be displayed
as a link. This is a map of locale to message.",
    "propertyOrder" : 600,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"spamDetectionTolerance" : {
  "title" : "Spam Tolerance",
  "description" : "How many times a user may resubmit to this node before the authentication is
failed.",
  "propertyOrder" : 300,
  "type" : "integer",

```



```
    "exampleValue" : ""
  }
},
"required" : [ "spamDetectionEnabled", "secondsToWait", "spamDetectionTolerance", "exitMessage",
"waitingMessage", "exitable" ]
}
```

1.121.1.2. delete

Usage:

```
am> delete PollingWaitNode --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.121.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PollingWaitNode --realm Realm --actionName getAllTypes
```

1.121.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PollingWaitNode --realm Realm --actionName getCreatableTypes
```

1.121.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action PollingWaitNode --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.121.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PollingWaitNode --realm Realm --actionName nextdescendents
```

1.121.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query PollingWaitNode --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.121.1.8. read

Usage:

```
am> read PollingWaitNode --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.121.1.9. update

Usage:

```
am> update PollingWaitNode --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "exitable" : {
      "title" : "Exitable",
      "description" : "Choose whether to display a link which allows the user to leave the node early.
Creates a new outcome.",
      "propertyOrder" : 500,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "spamDetectionEnabled" : {
      "title" : "Enable Spam Detection",
      "description" : "Choose whether spam detection is enforced for this node. Creates a new
outcome.",
      "propertyOrder" : 200,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "secondsToWait" : {
      "title" : "Seconds To Wait",
      "description" : "How many seconds to wait before proceeding to the next node in the tree.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    },
    "waitingMessage" : {
      "title" : "Waiting Message",
      "description" : "Localisation overrides for the waiting message. May use {{time}} to get the
number of seconds remaining. This is a map of locale to message.",
      "propertyOrder" : 400,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : ""
    },
    "exitMessage" : {
      "title" : "Exit Message",
      "description" : "Localisation overrides for the exit message. The whole string will be displayed
as a link. This is a map of locale to message.",
      "propertyOrder" : 600,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      }
    }
  }
}
```

```
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "spamDetectionTolerance" : {
    "title" : "Spam Tolerance",
    "description" : "How many times a user may resubmit to this node before the authentication is
failed.",
    "propertyOrder" : 300,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"required" : [ "spamDetectionEnabled", "secondsToWait", "spamDetectionTolerance", "exitMessage",
"waitingMessage", "exitable" ]
}
```

1.122. PrometheusReporter

1.122.1. Global Operations

Resource path: `/global-config/services/monitoring/prometheus`

Resource version: `1.0`

1.122.1.1. create

Usage:

```
am> create PrometheusReporter --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "password" : {
      "title" : "Password",
      "description" : "",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "username" : {
      "title" : "Username",
      "description" : "",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "enabled" : {
      "title" : "Enabled",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
```

1.122.1.2. delete

Usage:

```
am> delete PrometheusReporter --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.122.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PrometheusReporter --global --actionName getAllTypes
```

1.122.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PrometheusReporter --global --actionName getCreatableTypes
```

1.122.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PrometheusReporter --global --actionName nextdescendents
```

1.122.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query PrometheusReporter --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.122.1.7. read

Usage:

```
am> read PrometheusReporter --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.122.1.8. update

Usage:

```
am> update PrometheusReporter --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "password" : {
      "title" : "Password",
      "description" : "",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "username" : {
      "title" : "Username",
      "description" : "",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "enabled" : {
      "title" : "Enabled",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
```

1.123. ProvisionDynamicAccount

1.123.1. Realm Operations

Resource path: [/realm-config/authentication/authenticationtrees/nodes/ProvisionDynamicAccountNode](#)

Resource version: [1.0](#)

1.123.1.1. create

Usage:

```
am> create ProvisionDynamicAccount --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "accountProviderClass" : {
      "title" : "Account Provider Class",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "accountProviderClass" ]
}
```

1.123.1.2. delete

Usage:

```
am> delete ProvisionDynamicAccount --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.123.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ProvisionDynamicAccount --realm Realm --actionName getAllTypes
```

1.123.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:


```
am> action ProvisionDynamicAccount --realm Realm --actionName getCreatableTypes
```

1.123.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action ProvisionDynamicAccount --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.123.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ProvisionDynamicAccount --realm Realm --actionName nextdescendents
```

1.123.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ProvisionDynamicAccount --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.123.1.8. read

Usage:

```
am> read ProvisionDynamicAccount --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.123.1.9. update

Usage:

```
am> update ProvisionDynamicAccount --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "accountProviderClass" : {
      "title" : "Account Provider Class",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "accountProviderClass" ]
}
```

1.124. ProvisionIDMAccount

1.124.1. Realm Operations

Resource path: [/realm-config/authentication/authenticationtrees/nodes/ProvisionIdmAccountNode](#)

Resource version: 1.0

1.124.1.1. create

Usage:

```
am> create ProvisionIDMAccount --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "accountProviderClass" : {
      "title" : "Account Provider Class",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "accountProviderClass" ]
}
```

1.124.1.2. delete

Usage:

```
am> delete ProvisionIDMAccount --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.124.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ProvisionIDMAccount --realm Realm --actionName getAllTypes
```

1.124.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ProvisionIDMAccount --realm Realm --actionName getCreatableTypes
```

1.124.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action ProvisionIDMAccount --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.124.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ProvisionIDMAccount --realm Realm --actionName nextdescendents
```

1.124.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ProvisionIDMAccount --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.124.1.8. read

Usage:

```
am> read ProvisionIDMAccount --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.124.1.9. update

Usage:

```
am> update ProvisionIDMAccount --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "accountProviderClass" : {
      "title" : "Account Provider Class",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "accountProviderClass" ]
}
```

1.125. PushNotification

1.125.1. Realm Operations

Resource path: [/realm-config/services/pushNotification](#)

Resource version: [1.0](#)

1.125.1.1. create

Usage:

```
am> create PushNotification --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "mdDuration" : {
      "title" : "Response Cache Duration",
      "description" : "The minimum lifetime to keep unanswered message records in the message dispatcher cache, in seconds. To keep unanswered message records indefinitely, set this property to <code>0</code>. Should be tuned so that it is applicable to the use case of this service. For example, the ForgeRock Authenticator (Push) authentication module has a default timeout of 120 seconds.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "googleEndpoint" : {
      "title" : "SNS Endpoint for GCM",
      "description" : "The Simple Notification Service endpoint in Amazon Resource Name format, used to send push messages over Google Cloud Messaging (GCM).",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : "arn:aws:sns:us-east-1:1234567890:app/GCM/production"
    },
    "appleEndpoint" : {
      "title" : "SNS Endpoint for APNS",
      "description" : "The Simple Notification Service endpoint in Amazon Resource Name format, used to send push messages to the Apple Push Notification Service (APNS).",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : "arn:aws:sns:us-east-1:1234567890:app/APNS/production"
    },
    "secret" : {
      "title" : "SNS Access Key Secret",
      "description" : "Amazon Simple Notification Service Access Key Secret. For more information, see <a href=\"https://aws.amazon.com/developers/access-keys/\">https://aws.amazon.com/developers/access-keys/</a>.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : "wJa1rXUtnFEMI/K7MDENG/bPxRfiCYEXAMPLEKEY"
    },
    "region" : {
      "title" : "SNS Client Region",
      "description" : "Region of your registered Amazon Simple Notification Service client. For more information, see <a href=\"https://docs.aws.amazon.com/general/latest/gr/rande.html\">https://docs.aws.amazon.com/general/latest/gr/rande.html</a>.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "mdCacheSize" : {
```

```

    "title" : "Response Cache Size",
    "description" : "Maximum size of the message dispatcher cache, in number of records. If set
to <code>0</code> the cache can grow indefinitely. If the number of records that need to be stored
exceeds this maximum, then older items in the cache will be removed to make space.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "mdConcurrency" : {
    "title" : "Response Cache Concurrency",
    "description" : "Level of concurrency to use when accessing the message dispatcher cache.
Defaults to <code>16</code>, and must be greater than <code>0</code>. Choose a value to accommodate
as many threads as will ever concurrently access the message dispatcher cache.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "delegateFactory" : {
    "title" : "Message Transport Delegate Factory",
    "description" : "The fully qualified class name of the factory
responsible for creating the PushNotificationDelegate. The class must implement
<code>org.forgerock.openam.services.push.PushNotificationDelegate</code>.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "accessKey" : {
    "title" : "SNS Access Key ID",
    "description" : "Amazon Simple Notification Service Access Key ID. For more information, see
<a href=\"https://aws.amazon.com/developers/access-keys/\">https://aws.amazon.com/developers/access-
keys/</a>.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : "AKIAIOSFODNN7EXAMPLE"
  }
}
}
}

```

1.125.1.2. delete

Usage:

```
am> delete PushNotification --realm Realm
```

1.125.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PushNotification --realm Realm --actionName getAllTypes
```

1.125.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PushNotification --realm Realm --actionName getCreatableTypes
```

1.125.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PushNotification --realm Realm --actionName nextdescendents
```

1.125.1.6. read

Usage:

```
am> read PushNotification --realm Realm
```

1.125.1.7. update

Usage:

```
am> update PushNotification --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "mdDuration" : {
      "title" : "Response Cache Duration",
      "description" : "The minimum lifetime to keep unanswered message records in the message dispatcher cache, in seconds. To keep unanswered message records indefinitely, set this property to <code>0</code>.Should be tuned so that it is applicable to the use case of this service. For example, the ForgeRock Authenticator (Push) authentication module has a default timeout of 120 seconds.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "googleEndpoint" : {
      "title" : "SNS Endpoint for GCM",
      "description" : "The Simple Notification Service endpoint in Amazon Resource Name format, used to send push messages over Google Cloud Messaging (GCM).",
      "propertyOrder" : 400,

```



```

    "required" : true,
    "type" : "string",
    "exampleValue" : "arn:aws:sns:us-east-1:1234567890:app/GCM/production"
  },
  "appleEndpoint" : {
    "title" : "SNS Endpoint for APNS",
    "description" : "The Simple Notification Service endpoint in Amazon Resource Name format, used
to send push messages to the Apple Push Notification Service (APNS).",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : "arn:aws:sns:us-east-1:1234567890:app/APNS/production"
  },
  "secret" : {
    "title" : "SNS Access Key Secret",
    "description" : "Amazon Simple Notification Service Access Key Secret. For more information, see
.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : "wJa1rXUtnFEMI/K7MDENG/bPxRfiCYEXAMPLEKEY"
  },
  "region" : {
    "title" : "SNS Client Region",
    "description" : "Region of your registered Amazon Simple Notification Service client. For
more information, see .",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "mdCacheSize" : {
    "title" : "Response Cache Size",
    "description" : "Maximum size of the message dispatcher cache, in number of records. If set
to 0 the cache can grow indefinitely. If the number of records that need to be stored
exceeds this maximum, then older items in the cache will be removed to make space.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "mdConcurrency" : {
    "title" : "Response Cache Concurrency",
    "description" : "Level of concurrency to use when accessing the message dispatcher cache.
Defaults to 16, and must be greater than 0. Choose a value to accommodate
as many threads as will ever concurrently access the message dispatcher cache.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "delegateFactory" : {
    "title" : "Message Transport Delegate Factory",
    "description" : "The fully qualified class name of the factory
responsible for creating the PushNotificationDelegate. The class must implement
org.forgerock.openam.services.push.PushNotificationDelegate.",
    "propertyOrder" : 600,

```

```
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "accessKey" : {
    "title" : "SNS Access Key ID",
    "description" : "Amazon Simple Notification Service Access Key ID. For more information, see
<a href=\"https://aws.amazon.com/developers/access-keys/\">https://aws.amazon.com/developers/access-
keys/</a>.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : "AKIAIOSFODNN7EXAMPLE"
  }
}
```

1.125.2. Global Operations

Resource path: `/global-config/services/pushNotification`

Resource version: `1.0`

1.125.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PushNotification --global --actionName getAllTypes
```

1.125.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PushNotification --global --actionName getCreatableTypes
```

1.125.2.3. nextDescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PushNotification --global --actionName nextDescendants
```

1.125.2.4. read

Usage:

```
am> read PushNotification --global
```

1.125.2.5. update

Usage:

```
am> update PushNotification --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "delegateFactory" : {
          "title" : "Message Transport Delegate Factory",
          "description" : "The fully qualified class name of the factory
responsible for creating the PushNotificationDelegate. The class must implement
<code>org.forgerock.openam.services.push.PushNotificationDelegate</code>.",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "mdCacheSize" : {
          "title" : "Response Cache Size",
          "description" : "Maximum size of the message dispatcher cache, in number of records. If set
to <code>0</code> the cache can grow indefinitely. If the number of records that need to be stored
exceeds this maximum, then older items in the cache will be removed to make space.",
          "propertyOrder" : 900,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "mdDuration" : {
          "title" : "Response Cache Duration",
          "description" : "The minimum lifetime to keep unanswered message records in the message
dispatcher cache, in seconds. To keep unanswered message records indefinitely, set this property to
<code>0</code>.Should be tuned so that it is applicable to the use case of this service. For example,
the ForgeRock Authenticator (Push) authentication module has a default timeout of 120 seconds.",
          "propertyOrder" : 700,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "secret" : {
          "title" : "SNS Access Key Secret",
          "description" : "Amazon Simple Notification Service Access Key Secret. For more information,
see <a href=\"https://aws.amazon.com/developers/access-keys/\">https://aws.amazon.com/developers/
access-keys</a>.",

```

```

        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : "wJaIrxUtnFEMI/K7MDENG/bPxRfiCYEXAMPLEKEY"
    },
    "region" : {
        "title" : "SNS Client Region",
        "description" : "Region of your registered Amazon Simple Notification Service client. For
more information, see <a href=\"https://docs.aws.amazon.com/general/latest/gr/rande.html\">https://
docs.aws.amazon.com/general/latest/gr/rande.html</a>.",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "googleEndpoint" : {
        "title" : "SNS Endpoint for GCM",
        "description" : "The Simple Notification Service endpoint in Amazon Resource Name format,
used to send push messages over Google Cloud Messaging (GCM).",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : "arn:aws:sns:us-east-1:1234567890:app/GCM/production"
    },
    "mdConcurrency" : {
        "title" : "Response Cache Concurrency",
        "description" : "Level of concurrency to use when accessing the message dispatcher cache.
Defaults to <code>16</code>, and must be greater than <code>0</code>. Choose a value to accommodate
as many threads as will ever concurrently access the message dispatcher cache.",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "appleEndpoint" : {
        "title" : "SNS Endpoint for APNS",
        "description" : "The Simple Notification Service endpoint in Amazon Resource Name format,
used to send push messages to the Apple Push Notification Service (APNS).",
        "propertyOrder" : 300,
        "required" : true,
        "type" : "string",
        "exampleValue" : "arn:aws:sns:us-east-1:1234567890:app/APNS/production"
    },
    "accessKey" : {
        "title" : "SNS Access Key ID",
        "description" : "Amazon Simple Notification Service Access Key ID. For more information, see
<a href=\"https://aws.amazon.com/developers/access-keys/\">https://aws.amazon.com/developers/access-
keys/</a>.",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "string",
        "exampleValue" : "AKIAIOSFODNN7EXAMPLE"
    }
},
"type" : "object",
"title" : "Realm Defaults"
}
}

```

```
}
```

1.126. PushNotificationResponse

1.126.1. Realm Operations

Push Authentication depends on the secure verification of information sent from the server to the client, and from the client to the server. This allows the server to verify that the notification was received by the original device, and for the device to verify that only the server sent out the original request. This endpoint provides the place for the device to return responses to the server to requests received either by QR code or by push notification.

Resource path: `/push/sns/message`

Resource version: `1.0`

1.126.1.1. authenticate

Message sent from device to server in response to a request for authentication sent to the device via Push notification. This message is generally sent from the ForgeRock Authenticator app.

Usage:

```
am> action PushNotificationResponse --realm Realm --body body --actionName authenticate
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "messageId" : {
      "type" : "string",
      "title" : "Message ID",
      "description" : "Unique message identifier"
    },
    "jwt" : {
      "type" : "string",
      "title" : "JWT",
      "description" : "Signed JWT containing claims:\n* `response`: Response to challenge (Base64 encoding of the HmacSHA256 hashing of the decoded shared secret and the decoded challenge)\n* `deny`: Indication that this auth attempt should be shut down (boolean)"
    }
  },
  "required" : [ "messageId", "jwt" ]
}
```

1.126.1.2. register

Message sent from device to server in response to a registration message received on the device via a QR code. This message is generally sent from the ForgeRock Authenticator app.

Usage:

```
am> action PushNotificationResponse --realm Realm --body body --actionName register
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "messageId" : {
      "type" : "string",
      "title" : "Message ID",
      "description" : "Unique message identifier"
    },
    "jwt" : {
      "type" : "string",
      "title" : "JWT",
      "description" : "Signed JWT containing claims:\n* `response`: Response to challenge (Base64 encoding of the HmacSHA256 hashing of the decoded shared secret and the decoded challenge)\n* `mechanismUid`: The device-specific identifier for the just-registered mechanism (string)\n* `deviceId`: The registration token used by GCM or APNS (string)\n* `deviceType`: `android` or `ios` (string)\n* `communicationType`: `gcm` or `apns` (string)"
    }
  },
  "required" : [ "messageId", "jwt" ]
}
```

1.127. PushResultVerifierNode

1.127.1. Realm Operations

Resource path: [/realm-config/authentication/authenticationtrees/nodes/PushResultVerifierNode](#)

Resource version: **1.0**

1.127.1.1. create

Usage:

```
am> create PushResultVerifierNode --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "required" : [ ]
}
```

1.127.1.2. delete

Usage:

```
am> delete PushResultVerifierNode --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.127.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PushResultVerifierNode --realm Realm --actionName getAllTypes
```

1.127.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PushResultVerifierNode --realm Realm --actionName getCreatableTypes
```

1.127.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action PushResultVerifierNode --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.127.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PushResultVerifierNode --realm Realm --actionName nextdescendents
```

1.127.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query PushResultVerifierNode --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.127.1.8. read

Usage:

```
am> read PushResultVerifierNode --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.127.1.9. update

Usage:


```
am> update PushResultVerifierNode --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "required" : [ ]
}
```

1.128. PushSender

1.128.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/PushAuthenticationSenderNode`

Resource version: `1.0`

1.128.1.1. create

Usage:

```
am> create PushSender --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userMessage" : {
      "title" : "User Message",
      "description" : "The message to send to the user. {{user}} and {{issuer}} may be used as wildcards.",
      "propertyOrder" : 200,
    }
  }
}
```

```
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "mandatory" : {
    "title" : "Remove 'skip' option",
    "description" : "If checked, users will no longer be able to skip the module, and must interact
with it.",
    "propertyOrder" : 300,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "messageTimeout" : {
    "title" : "Message Timeout",
    "description" : "The duration (in ms) that the message will time out after.",
    "propertyOrder" : 100,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"required" : [ "messageTimeout", "userMessage", "mandatory" ]
}
```

1.128.1.2. delete

Usage:

```
am> delete PushSender --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.128.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action PushSender --realm Realm --actionName getAllTypes
```

1.128.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action PushSender --realm Realm --actionName getCreatableTypes
```

1.128.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action PushSender --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.128.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action PushSender --realm Realm --actionName nextdescendents
```

1.128.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query PushSender --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.128.1.8. read

Usage:

```
am> read PushSender --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.128.1.9. update

Usage:

```
am> update PushSender --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userMessage" : {
      "title" : "User Message",
      "description" : "The message to send to the user. {{user}} and {{issuer}} may be used as
wildcards.",
      "propertyOrder" : 200,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : ""
    },
    "mandatory" : {
      "title" : "Remove 'skip' option",
      "description" : "If checked, users will no longer be able to skip the module, and must interact
with it.",
      "propertyOrder" : 300,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "messageTimeout" : {
      "title" : "Message Timeout",
      "description" : "The duration (in ms) that the message will time out after.",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "messageTimeout", "userMessage", "mandatory" ]
}
```

1.129. PushUserDevices

1.129.1. Realm Operations

The Push devices service is responsible for exposing functions to change the collection of Push authentication devices. The supported methods are action, delete, query

Resource path: `/users/{user}/devices/2fa/push`

Resource version: `1.0`

1.129.1.1. check

Checks if the user's Authenticator Push module is 'skippable' and returns the result as a boolean

Usage:

```
am> action PushUserDevices --realm Realm --body body --user user --actionName check
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Push user device check action request schema",
  "type" : "object",
  "title" : "Push user device check action request schema"
}
```

--user

The Push devices service is responsible for exposing functions to change the collection of Push authentication devices. The supported methods are action, delete, query

1.129.1.2. delete

Delete Push user device

Usage:

```
am> delete PushUserDevices --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

The Push devices service is responsible for exposing functions to change the collection of Push authentication devices. The supported methods are action, delete, query

1.129.1.3. query

Query the user's device profile

Usage:

```
am> query PushUserDevices --realm Realm --filter filter --user user
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

--user

The Push devices service is responsible for exposing functions to change the collection of Push authentication devices. The supported methods are action, delete, query

1.129.1.4. reset

Sets the user's 'skippable' selection of Authenticator Push module to default (NOT_SET) and deletes their profile's attribute

Usage:

```
am> action PushUserDevices --realm Realm --body body --user user --actionName reset
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "Push user device reset action request schema",
  "type" : "object",
  "title" : "Push user device reset action request schema"
}
```

--user

The Push devices service is responsible for exposing functions to change the collection of Push authentication devices. The supported methods are action, delete, query

1.129.1.5. skip

Sets the user's ability to skip an Authenticator Push module

Usage:

```
am> action PushUserDevices --realm Realm --body body --user user --actionName skip
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "Push user device skip action request schema",
  "type" : "object",
  "title" : "Push user device skip action request schema",
  "properties" : {
    "value" : {
      "type" : "boolean",
      "title" : "Skip push module response value",
      "description" : "True if the push device is set to skipped"
    }
  },
  "required" : [ "value" ]
}
```

--user

The Push devices service is responsible for exposing functions to change the collection of Push authentication devices. The supported methods are action, delete, query

1.130. RESTSecurityTokenServices

1.130.1. Realm Operations

The REST STS endpoint is responsible for storing the configuration of instances of REST Security Token Services (STS). Available operations are create, read, update, delete, query, schema and template.

Resource path: [/realm-config/services/sts/rest-sts](#)

Resource version: [1.0](#)

1.130.1.1. create

Usage:

```
am> create RESTSecurityTokenServices --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "restStsSaml2" : {
      "type" : "object",
      "title" : "SAML2 Token",
      "propertyOrder" : 2,
      "properties" : {
        "saml2-encrypt-nameid" : {
          "title" : "Encrypt NameID",
          "description" : "Check this box if the assertion NameID should be encrypted. If this box is
checked, the Encrypt Assertion box cannot be checked.",
          "propertyOrder" : 2700,
          "required" : false,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "saml2-custom-conditions-provider-class-name" : {
          "title" : "Custom Conditions Provider Class Name",
          "description" : "If the Conditions of the issued SAML2 assertion need to be customized,
implement the <code>org.forgerock.openam.sts.tokengeneration.saml2.statements.ConditionsProvider</
code> interface, and specify the class name of the implementation here.",
          "propertyOrder" : 1600,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "saml2-sign-assertion" : {
          "title" : "Sign Assertion",
          "description" : "",
          "propertyOrder" : 2400,
          "required" : false,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "saml2-sp-acis-url" : {
          "title" : "Service Provider Assertion Consumer Service Url",
          "description" : "When issuing bearer assertions, the recipient attribute of the
SubjectConfirmation element must be set to the Service Provider Assertion Consumer Service Url. See
section 4.1.4.2 of Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0 for details.
Value required when issuing Bearer assertions.",
          "propertyOrder" : 1300,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "saml2-signature-key-password" : {
          "title" : "Signature Key Password",
          "description" : "",
          "propertyOrder" : 3400,
          "required" : false,
```



```

        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "saml2-name-id-format" : {
        "title" : "NameIdFormat",
        "description" : "The default value is <code>urn:oasis:names:tc:SAML:1.1:nameid-
format:unspecified</code><br><br>See section 8.3 of <a href=\"http://docs.oasis-open.org/security/
saml/v2.0/saml-core-2.0-os.pdf\" target=\"_blank\">Assertions and Protocols for the OASIS Security
Assertion Markup Language (SAML) V2.0</a> for details on possible values.",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-sp-entity-id" : {
        "title" : "Service Provider Entity Id",
        "description" : "Values will be used to populate the Audiences of the AudienceRestriction
element of the Conditions element. This value is required when issuing Bearer assertions. See section
4.1.4.2 of Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0 for details.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-encryption-algorithm" : {
        "title" : "Encryption Algorithm",
        "description" : "Algorithm used to encrypt generated assertions.",
        "propertyOrder" : 2800,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-encryption-key-alias" : {
        "title" : "Encryption Key Alias",
        "description" : "This alias corresponds to the SP's x509 Certificate identified by the SP
Entity ID for this rest-sts instance. Not necessary unless assertions are to be encrypted.",
        "propertyOrder" : 3200,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-token-lifetime-seconds" : {
        "title" : "Token Lifetime (Seconds)",
        "description" : "Set to over-ride the default of 600 (10 minutes).",
        "propertyOrder" : 1500,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "saml2-custom-subject-provider-class-name" : {
        "title" : "Customs Subject Provider Class Name",
        "description" : "If the Subject of the issued SAML2 assertion needs to be customized,
implement the <code>org.forgerock.openam.sts.tokengeneration.saml2.statements.SubjectProvider</code>
interface, and specify the class name of the implementation here.",
        "propertyOrder" : 1700,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    }

```

```

    },
    "saml2-custom-authz-decision-statements-provider-class-name" : {
      "title" : "Custom Authorization Decision Statements Class Name",
      "description" : "If the AuthorizationDecisionStatements
of the issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AuthzDecisionStatementsProvider</
code> interface, and specify the class name of the implementation here.",
      "propertyOrder" : 2000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "saml2-signature-key-alias" : {
      "title" : "Signature Key Alias",
      "description" : "Corresponds to the private key of the IdP. Will be used to sign assertions.
Value can remain unspecified unless assertions are signed.",
      "propertyOrder" : 3300,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "saml2-custom-authn-context-mapper-class-name" : {
      "title" : "Custom Authentication Context Class Name",
      "description" : "If the AuthnContext mapping implemented by the
<code>org.forgerock.openam.sts.rest.token.provider.saml.DefaultSaml2JsonTokenAuthnContextMapper</
code> class needs to be customized, implement the
<code>org.forgerock.openam.sts.rest.token.provider.saml.Saml2JsonTokenAuthnContextMapper</code>
interface, and specify the name of the implementation here.",
      "propertyOrder" : 2200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "saml2-keystore-filename" : {
      "title" : "KeystorePath",
      "description" : "Path to keystore<br><br>Provide either the full filesystem path to a
filesystem resident keystore, or a classpath-relative path to a keystore bundled in the OpenAM .war
file. This keystore contains the IdP public/private keys and SP public key for signed and/or
encrypted assertions. If assertions are neither signed nor encrypted, these values need not be
specified.",
      "propertyOrder" : 2900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "saml2-custom-attribute-mapper-class-name" : {
      "title" : "Custom Attribute Mapper Class Name",
      "description" : "If the class implementing attribute mapping for attributes
contained in the issued SAML2 assertion needs to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AttributeMapper</code> interface, and
specify the class name of the implementation here.",
      "propertyOrder" : 2100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "saml2-custom-authentication-statements-provider-class-name" : {
      "title" : "Custom AuthenticationStatements Class Name",

```

```

        "description" : "If the AuthenticationStatements of
the issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AuthenticationStatementsProvider</
code> interface, and specify the class name of the implementation here.",
        "propertyOrder" : 1800,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-custom-attribute-statements-provider-class-name" : {
        "title" : "Custom AttributeStatements Class Name",
        "description" : "If the AttributeStatements of the
issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AttributeStatementsProvider</code>
interface, and specify the class name of the implementation here.",
        "propertyOrder" : 1900,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-encrypt-attributes" : {
        "title" : "Encrypt Attributes",
        "description" : "Check this box if the assertion Attributes should be encrypted. If this box
is checked, the Encrypt Assertion box cannot be checked.",
        "propertyOrder" : 2600,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "saml2-encryption-algorithm-strength" : {
        "title" : "Encryption Algorithm Strength",
        "description" : "",
        "propertyOrder" : 2850,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "saml2-keystore-password" : {
        "title" : "Keystore Password",
        "description" : "",
        "propertyOrder" : 3000,
        "required" : false,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "saml2-attribute-map" : {
        "title" : "Attribute Mappings",
        "description" : "Contains the mapping of assertion attribute names (Map
keys) to local OpenAM attributes (Map values) in configured data stores. Format:
<code>assertion_attr_name=ldap_attr_name</code><br><br>The DefaultAttributeMapper looks at
profile attributes in configured data stores, or in Session properties. The keys will define
the name of the attributes included in the Assertion Attribute statements, and the data
pulled from the subject's directory entry or session state corresponding to the map value
will define the value corresponding to this attribute name. The keys can have the format
<code>[NameFormatURI]]SAML ATTRIBUTE NAME</code>. If the attribute value is enclosed in quotes,
that quoted value will be included in the attribute without mapping. Binary attributes should be
followed by ';binary'. <br>Examples: <ul><li>EmailAddress=mail</li><li>Address=postaladdress</
li><li>urn:oasis:names:tc:SAML:2.0:attrname-format:uri|urn:mace:dir:attribute-def:cn=cn</

```

```

<li><li>partnerID=\<staticPartnerIDValue\</li><li>urn:oasis:names:tc:SAML:2.0:attrname-format:uri|
nameID=\<staticNameIDValue\</li><li>photo=photo;binary</li><li>urn:oasis:names:tc:SAML:2.0:attrname-
format:uri|photo=photo;binary</li></ul>",
  "propertyOrder" : 2300,
  "required" : false,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"saml2-encrypt-assertion" : {
  "title" : "Encrypt Assertion",
  "description" : "Check this box if the entire assertion should be encrypted. If this box is
checked, the Encrypt NameID and Encrypt Attributes boxes cannot be checked.",
  "propertyOrder" : 2500,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"issuer-name" : {
  "title" : "The SAML2 Issuer Id",
  "description" : "The name of the issuer<br><br>This name will appear in some issued tokens -
e.g. in the <code>saml:Issuer</code> of issued SAML2 assertions.",
  "propertyOrder" : 1100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"restStsDeployment" : {
  "type" : "object",
  "title" : "Deployment",
  "propertyOrder" : 1,
  "properties" : {
    "deployment-tls-offload-engine-hosts" : {
      "title" : "Trusted Remote Hosts",
      "description" : "IP addresses of TLS-Offload Hosts<br><br>Token transformation which take
X509 Certificates as the input token require that the X509 Certificate be presented via two-way
TLS, so that the TLS handshake can validate client certificate ownership. If OpenAM is deployed in a
TLS-offloaded environment, in which the TLS-offloader must communicate the client certificate to the
rest-sts via an Http header, this certificate will only be accepted if the ip address(es) of the TLS-
offload engines are specified in this list. Specify 'any' if a client certificate can be presented in
the specified header by any rest-sts client.",
      "propertyOrder" : 1000,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "deployment-offloaded-two-way-tls-header-key" : {
      "title" : "Client Certificate Header Key",
      "description" : "TLS-offload host certificate header key<br><br>Token transformation
which take X509 Certificates as the input token require that the X509 Certificate be presented

```

via two-way TLS, so that the TLS handshake can validate client certificate ownership. A standard means of obtaining the client certificate presented via two-way TLS is via the `javax.servlet.request.X509Certificate` attribute in the `ServletRequest`. However, in TLS-offloaded deployments, the TLS-offloader must communicate the client certificate to its ultimate destination via an `Http` header. If this `rest-sts` instance is to support token transformations with X509 Certificate input, and OpenAM will be deployed in a TLS-offloaded context, then this value must be set to the header value which the TLS-offloading engine will use to set client certificates presented via the TLS handshake.",

```

        "propertyOrder" : 900,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "deployment-auth-target-mappings" : {
        "title" : "Authentication Target Mappings",
        "description" : "Configuration of consumption of OpenAM's
rest-authN. For each validated token type (other than OpenAM), the REST
authN elements which will validate token instances. <br>Entry format:
<code>TokenType;authIndexType;authIndexValue;context_key=context_value,context_key1=context_value1</
code>. <br>The <code>context_key=context_value</code> entries are optional.<br><br>Each deployed
STS is configured with the authentication targets for each input token type for each supported
token transformation. For example, if the transformation OPENIDCONNECT->SAML2 is supported, the
STS instance must be configured with information specifying which elements of the OpenAM restful
authentication context needs to be consumed to validate the OPENIDCONNECT token. The elements
of the configuration tuple are separated by '|'. <br>The first element is the input token type
in the token transform: i.e. X509, OPENIDCONNECT, USERNAME, or OPENAM. The second element is the
authentication target - i.e. either 'module' or 'service', and the third element is the name of
the authentication module or service. The fourth (optional) element provides the STS authentication
context information about the to-be-consumed authentication context. <br>When transforming OpenID
Connect Id tokens, the OpenID Connect authentication module must be consumed, and thus a deployed
rest-sts instance must be configured with the name of the header/cookie element where the OpenID
Connect Id token will be placed. For this example, the following string would define these
configurations: <code>OPENIDCONNECT|module|oidc|oidc_id_token_auth_target_header_key=oidc_id_token</
code>. In this case, 'oidc' is the name of the OpenID Connect authentication module created to
authenticate OpenID Connect tokens. <br>When transforming a X509 Certificate, the Certificate
module must be consumed, and the published rest-sts instance must be configured with the name of
the Certificate module (or the service containing the module), and the header name configured for
the Certificate module corresponding to where the Certificate module can expect to find the to-be-
validated Certificate. The following string would define these configurations: <code>X509|module|
cert_module|x509_token_auth_target_header_key=client_cert</code>. In this case 'cert_module' is the
name of the Certificate module, and client_cert is the header name where Certificate module has been
configured to find the client's Certificate.",
        "propertyOrder" : 800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"restStsOidc" : {
    "type" : "object",
    "title" : "OpenID Connect Token",
    "propertyOrder" : 3,
    "properties" : {
        "oidc-keystore-location" : {
            "title" : "KeyStore Location",

```

```

        "description" : "For RSA-signed tokens, the filesystem or classpath location of the KeyStore
        containing signing key entry<br><br>For RSA-signed tokens, the KeyStore location, password, signing-
        key alias, and signing key password must be specified. The client secret is not required for RSA-
        signed tokens.",
        "propertyOrder" : 3800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "oidc-public-key-reference-type" : {
        "title" : "Public Key Reference Type",
        "description" : "For tokens signed with RSA, how should corresponding public key be
        referenced in the issued jwt",
        "propertyOrder" : 3700,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "oidc-signature-key-alias" : {
        "title" : "KeyStore Signing Key Alias",
        "description" : "",
        "propertyOrder" : 4100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "oidc-custom-authn-context-mapper-class" : {
        "title" : "Custom Authn Context Mapper Class",
        "description" : "If issued OIDC tokens are to contain acr claims, implement the
        <code>org.forgerock.openam.sts.rest.token.provider.oidc.OpenIdConnectTokenAuthnContextMapper</code>
        interface, and specify the class name of the implementation here.",
        "propertyOrder" : 5000,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "oidc-token-lifetime-seconds" : {
        "title" : "Token Lifetime (Seconds)",
        "description" : "",
        "propertyOrder" : 3500,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "oidc-audience" : {
        "title" : "Issued Tokens Audience",
        "description" : "Contents will be set in the aud claim",
        "propertyOrder" : 4600,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "oidc-custom-claim-mapper-class" : {
        "title" : "Custom Claim Mapper Class",
        "description" : "If the class implementing attribute mapping for attributes
        contained in issued OpenID Connect tokens needs to be customized, implement the
    
```

```

<code>org.forgerock.openam.sts.tokengeneration.oidc.OpenIdConnectTokenClaimMapper</code> interface,
and specify the class name of the implementation here.",
    "propertyOrder" : 4900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "oidc-authorized-party" : {
    "title" : "Authorized Party",
    "description" : "",
    "propertyOrder" : 4700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "oidc-issuer" : {
    "title" : "The OpenID Connect Token Provider Issuer Id",
    "description" : "",
    "propertyOrder" : 3450,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "oidc-keystore-password" : {
    "title" : "KeyStore Password",
    "description" : "",
    "propertyOrder" : 3900,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "oidc-claim-map" : {
    "title" : "Claim Map",
    "description" : "Contains the mapping of OIDC token claim names (Map keys) to local
OpenAM attributes (Map values) in configured data stores. Format: <code>claim_name=attribute_name</code><br><br>The keys in the map will be claim entries in the issued OIDC token, and the value of
these claims will be the principal attribute state resulting from LDAP datastore lookup of the map
values. If no values are returned from the LDAP datastore lookup of the attribute corresponding to
the map value, no claim will be set in the issued OIDC token.",
    "propertyOrder" : 4800,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "oidc-signature-algorithm" : {
    "title" : "Token Signature Algorithm",
    "description" : "Algorithm used to sign issued OIDC tokens",
    "propertyOrder" : 3600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "oidc-custom-authn-method-references-mapper-class" : {

```

```

    "title" : "Custom Authn Methods References Mapper Class",
    "description" : "If issued OIDC tokens are to contain amr claims, implement the
<code>org.forgerock.openam.sts.rest.token.provider.oidc.OpenIdConnectTokenAuthMethodReferencesMapper</
code> interface, and specify the class name of the implementation here.",
    "propertyOrder" : 5100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "oidc-signature-key-password" : {
    "title" : "Signature Key Password",
    "description" : "",
    "propertyOrder" : 4200,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "oidc-client-secret" : {
    "title" : "Client Secret",
    "description" : "For HMAC-signed tokens, the client secret used as the HMAC key.<br><br>For
HMAC-signed tokens, the KeyStore location, password, signature key alias and password configurations
are not required.",
    "propertyOrder" : 4400,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }
}
},
"restStsGeneral" : {
  "type" : "object",
  "title" : "General",
  "propertyOrder" : 0,
  "properties" : {
    "persist-issued-tokens-in-cts" : {
      "title" : "Persist Issued Tokens in Core Token Store",
      "description" : "Necessary to support token validation and cancellation<br><br>Validation of
STS-issued tokens will involve determining whether the token has been issued, has not expired, and
has not been cancelled. Token cancellation involves removing the record of this token from the CTS.
Thus CTS persistence of STS-issued tokens is required to support these features.",
      "propertyOrder" : 100,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "custom-token-validators" : {
      "title" : "Custom Token Validators",
      "description" : "If validator of a custom token type is desired, specify
the name of the custom token here, followed by '|', followed by the class name of the
<code>org.forgerock.openam.sts.rest.token.validator.RestTokenTransformValidator</code> implementation
which will be invoked to validate the custom tokens.<br><br>Example: <code>MY_CUSTOM_INPUT_TOKEN|
org.mycompany.tokens.MyCustomTokenValidator</code> <br><br>Note that MY_CUSTOM_INPUT_TOKEN would then
be specified as the value corresponding to the token_type key in the input_token_state json object
specified in rest-sts token transformation invocations.",
      "propertyOrder" : 300,
      "required" : false,
      "items" : {

```



```

        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"custom-token-transforms" : {
    "title" : "Custom Token Transforms",
    "description" : "If either custom token validators or providers are specified, they must
also be specified in a custom rest-sts token transformation. These input or output tokens can be
specified in a transformation with standard, or other custom, tokens.<br><br>The format of these
token transformation definitions is the same as the standard token transformation definitions.
The first field defines the input token type, the second the output token type, and the third
field specifies whether the OpenAM session, produced as part of the validation of the input
token type, is invalidated following the production of the output token. <br><br>Example 1:<code>
MY_CUSTOM_INPUT_TOKEN|SAML2|true</code> <br>Example 1 specifies a MY_CUSTOM_INPUT_TOKEN as the
input token (requires the specification of a custom token validator) SAML2 as the produced token,
and that the interim OpenAM Session should be invalidated after the SAML2 token is produced.
<br><br>Example 2: <code>OPENIDCONNECT|MY_CUSTOM_OUTPUT_TOKEN|true</code> <br>Example 2 specifies
that an OPENIDCONNECT token should be authenticated to assert the identity of a token of type
MY_CUSTOM_OUTPUT_TOKEN (requires the specification of a custom token provider) and that the
interim OpenAM Session should be invalidated. <br><br>Example 3: <code>MY_CUSTOM_INPUT_TOKEN|
MY_CUSTOM_OUTPUT_TOKEN|false</code> <br>Example 3 specifies that a MY_CUSTOM_INPUT_TOKEN should be
transformed into a MY_CUSTOM_OUTPUT_TOKEN (requires the specification of both a custom provider and a
custom validator), and that the interim OpenAM session should not be invalidated.",
    "propertyOrder" : 500,
    "required" : false,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"supported-token-transforms" : {
    "title" : "Supported Token Transformations",
    "description" : "Entry format:<code>input_token_type;output_token_type;{true|false}</
code>, where true|false indicates whether the interim OpenAM session is invalidated following token
issuance.<br><br>Example: for the transform <code>USERNAME:SAML2</code>, it is likely that the
OpenAM session generated as part of validating the USERNAME token should be invalidated, and thus the
config entry would be <code>USERNAME;SAML2;true</code>. If this value is false, each USERNAME->SAML2
transformation will result in a 'left-over' OpenAM session. Note that currently, any transformation
which starts with an OPENAM session, e.g. <code>OPENAM;SAML2</code>, will not invalidate this OPENAM
session, as it was not created as part of the token transformation.",
    "propertyOrder" : 200,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"custom-token-providers" : {
    "title" : "Custom Token Providers",
    "description" : "If a rest-sts instance is to produce a custom token, specify
the name of the custom token here, followed by '|', followed by the class name of the
<code>org.forgerock.openam.sts.rest.token.provider.RestTokenProvider</code> implementation which will
be invoked to produce an instance of the custom token.<br><br>Example: <code>MY_CUSTOM_OUTPUT_TOKEN|
org.mycompany.tokens.MyCustomTokenProvider</code> <br>Note that MY_CUSTOM_OUTPUT_TOKEN would then
be specified as the value corresponding to the token_type key in the output_token_state json object
specified in rest-sts token transformation invocations.",

```

```
    "propertyOrder" : 400,  
    "required" : false,  
    "items" : {  
      "type" : "string"  
    },  
    "type" : "array",  
    "exampleValue" : ""  
  }  
}  
}  
}
```

1.130.1.2. delete

Usage:

```
am> delete RESTSecurityTokenServices --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.130.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RESTSecurityTokenServices --realm Realm --actionName getAllTypes
```

1.130.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RESTSecurityTokenServices --realm Realm --actionName getCreatableTypes
```

1.130.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RESTSecurityTokenServices --realm Realm --actionName nextdescendents
```

1.130.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query RESTSecurityTokenServices --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.130.1.7. read

Usage:

```
am> read RESTSecurityTokenServices --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.130.1.8. update

Usage:

```
am> update RESTSecurityTokenServices --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "restStsSaml2" : {
      "type" : "object",
      "title" : "SAML2 Token",
      "propertyOrder" : 2,
      "properties" : {
        "saml2-encrypt-nameid" : {
          "title" : "Encrypt NameID",
          "description" : "Check this box if the assertion NameID should be encrypted. If this box is
checked, the Encrypt Assertion box cannot be checked.",
```

```

    "propertyOrder" : 2700,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saml2-custom-conditions-provider-class-name" : {
    "title" : "Custom Conditions Provider Class Name",
    "description" : "If the Conditions of the issued SAML2 assertion need to be customized,
implement the <code>org.forgerock.openam.sts.tokengeneration.saml2.statements.ConditionsProvider</
code> interface, and specify the class name of the implementation here.",
    "propertyOrder" : 1600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-sign-assertion" : {
    "title" : "Sign Assertion",
    "description" : "",
    "propertyOrder" : 2400,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saml2-sp-acs-url" : {
    "title" : "Service Provider Assertion Consumer Service Url",
    "description" : "When issuing bearer assertions, the recipient attribute of the
SubjectConfirmation element must be set to the Service Provider Assertion Consumer Service Url. See
section 4.1.4.2 of Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0 for details.
Value required when issuing Bearer assertions.",
    "propertyOrder" : 1300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-signature-key-password" : {
    "title" : "Signature Key Password",
    "description" : "",
    "propertyOrder" : 3400,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "saml2-name-id-format" : {
    "title" : "NameIdFormat",
    "description" : "The default value is <code>urn:oasis:names:tc:SAML:1.1:nameid-
format:unspecified</code><br><br>See section 8.3 of <a href=\"http://docs.oasis-open.org/security/
saml/v2.0/saml-core-2.0-os.pdf\" target=\"_blank\">Assertions and Protocols for the OASIS Security
Assertion Markup Language (SAML) V2.0</a> for details on possible values.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-sp-entity-id" : {
    "title" : "Service Provider Entity Id",
    "description" : "Values will be used to populate the Audiences of the AudienceRestriction
element of the Conditions element. This value is required when issuing Bearer assertions. See section
4.1.4.2 of Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0 for details.",

```

```
"propertyOrder" : 1200,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"saml2-encryption-algorithm" : {
  "title" : "Encryption Algorithm",
  "description" : "Algorithm used to encrypt generated assertions.",
  "propertyOrder" : 2800,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"saml2-encryption-key-alias" : {
  "title" : "Encryption Key Alias",
  "description" : "This alias corresponds to the SP's x509 Certificate identified by the SP
Entity ID for this rest-sts instance. Not necessary unless assertions are to be encrypted.",
  "propertyOrder" : 3200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"saml2-token-lifetime-seconds" : {
  "title" : "Token Lifetime (Seconds)",
  "description" : "Set to over-ride the default of 600 (10 minutes).",
  "propertyOrder" : 1500,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"saml2-custom-subject-provider-class-name" : {
  "title" : "Customs Subject Provider Class Name",
  "description" : "If the Subject of the issued SAML2 assertion needs to be customized,
implement the <code>org.forgerock.openam.sts.tokengeneration.saml2.statements.SubjectProvider</code>
interface, and specify the class name of the implementation here.",
  "propertyOrder" : 1700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"saml2-custom-authz-decision-statements-provider-class-name" : {
  "title" : "Custom Authorization Decision Statements Class Name",
  "description" : "If the AuthorizationDecisionStatements
of the issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AuthzDecisionStatementsProvider</
code> interface, and specify the class name of the implementation here.",
  "propertyOrder" : 2000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"saml2-signature-key-alias" : {
  "title" : "Signature Key Alias",
  "description" : "Corresponds to the private key of the IdP. Will be used to sign assertions.
Value can remain unspecified unless assertions are signed.",
  "propertyOrder" : 3300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
```

```

    },
    "saml2-custom-authn-context-mapper-class-name" : {
        "title" : "Custom Authentication Context Class Name",
        "description" : "If the AuthnContext mapping implemented by the
<code>org.forgerock.openam.sts.rest.token.provider.saml.DefaultSaml2JsonTokenAuthnContextMapper</code>
class needs to be customized, implement the
<code>org.forgerock.openam.sts.rest.token.provider.saml.Saml2JsonTokenAuthnContextMapper</code>
interface, and specify the name of the implementation here.",
        "propertyOrder" : 2200,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-keystore-filename" : {
        "title" : "KeystorePath",
        "description" : "Path to keystore<br><br>Provide either the full filesystem path to a
filesystem resident keystore, or a classpath-relative path to a keystore bundled in the OpenAM .war
file. This keystore contains the IdP public/private keys and SP public key for signed and/or
encrypted assertions. If assertions are neither signed nor encrypted, these values need not be
specified.",
        "propertyOrder" : 2900,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-custom-attribute-mapper-class-name" : {
        "title" : "Custom Attribute Mapper Class Name",
        "description" : "If the class implementing attribute mapping for attributes
contained in the issued SAML2 assertion needs to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AttributeMapper</code> interface, and
specify the class name of the implementation here.",
        "propertyOrder" : 2100,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-custom-authentication-statements-provider-class-name" : {
        "title" : "Custom AuthenticationStatements Class Name",
        "description" : "If the AuthenticationStatements of
the issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AuthenticationStatementsProvider</code>
interface, and specify the class name of the implementation here.",
        "propertyOrder" : 1800,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-custom-attribute-statements-provider-class-name" : {
        "title" : "Custom AttributeStatements Class Name",
        "description" : "If the AttributeStatements of the
issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AttributeStatementsProvider</code>
interface, and specify the class name of the implementation here.",
        "propertyOrder" : 1900,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-encrypt-attributes" : {

```

```

    "title" : "Encrypt Attributes",
    "description" : "Check this box if the assertion Attributes should be encrypted. If this box
is checked, the Encrypt Assertion box cannot be checked.",
    "propertyOrder" : 2600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saml2-encryption-algorithm-strength" : {
    "title" : "Encryption Algorithm Strength",
    "description" : "",
    "propertyOrder" : 2850,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "saml2-keystore-password" : {
    "title" : "Keystore Password",
    "description" : "",
    "propertyOrder" : 3000,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "saml2-attribute-map" : {
    "title" : "Attribute Mappings",
    "description" : "Contains the mapping of assertion attribute names (Map
keys) to local OpenAM attributes (Map values) in configured data stores. Format:
<code>assertion_attr_name=ldap_attr_name</code><br><br>The DefaultAttributeMapper looks at
profile attributes in configured data stores, or in Session properties. The keys will define
the name of the attributes included in the Assertion Attribute statements, and the data
pulled from the subject's directory entry or session state corresponding to the map value
will define the value corresponding to this attribute name. The keys can have the format
<code>[NameFormatURI]SAML ATTRIBUTE NAME</code>. If the attribute value is enclosed in quotes,
that quoted value will be included in the attribute without mapping. Binary attributes should be
followed by ';binary'. <br>Examples: <ul><li>EmailAddress=mail</li><li>Address=postaladdress</
li><li>urn:oasis:names:tc:SAML:2.0:attrname-format:uri|urn:mace:dir:attribute-def:cn=cn</
li><li>partnerID=\"staticPartnerIDValue\"</li><li>urn:oasis:names:tc:SAML:2.0:attrname-format:uri|
nameID=\"staticNameIDValue\"</li><li>photo=photo;binary</li><li>urn:oasis:names:tc:SAML:2.0:attrname-
format:uri|photo=photo;binary</li></ul>",
    "propertyOrder" : 2300,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"saml2-encrypt-assertion" : {
  "title" : "Encrypt Assertion",
  "description" : "Check this box if the entire assertion should be encrypted. If this box is
checked, the Encrypt NameID and Encrypt Attributes boxes cannot be checked.",
  "propertyOrder" : 2500,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
}

```

```

    },
    "issuer-name" : {
      "title" : "The SAML2 Issuer Id",
      "description" : "The name of the issuer<br><br>This name will appear in some issued tokens -
e.g. in the <code>saml:Issuer</code> of issued SAML2 assertions.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"restStsDeployment" : {
  "type" : "object",
  "title" : "Deployment",
  "propertyOrder" : 1,
  "properties" : {
    "deployment-tls-offload-engine-hosts" : {
      "title" : "Trusted Remote Hosts",
      "description" : "IP addresses of TLS-Offload Hosts<br><br>Token transformation which take
X509 Certificates as the input token require that the X509 Certificate be presented via two-way
TLS, so that the TLS handshake can validate client certificate ownership. If OpenAM is deployed in a
TLS-offloaded environment, in which the TLS-offloader must communicate the client certificate to the
rest-sts via an Http header, this certificate will only be accepted if the ip address(es) of the TLS-
offload engines are specified in this list. Specify 'any' if a client certificate can be presented in
the specified header by any rest-sts client.",
      "propertyOrder" : 1000,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "deployment-offloaded-two-way-tls-header-key" : {
      "title" : "Client Certificate Header Key",
      "description" : "TLS-offload host certificate header key<br><br>Token transformation
which take X509 Certificates as the input token require that the X509 Certificate be presented
via two-way TLS, so that the TLS handshake can validate client certificate ownership. A
standard means of obtaining the client certificate presented via two-way TLS is via the
javax.servlet.request.X509Certificate attribute in the ServletRequest. However, in TLS-offloaded
deployments, the TLS-offloader must communicate the client certificate to its ultimate destination
via an Http header. If this rest-sts instance is to support token transformations with X509
Certificate input, and OpenAM will be deployed in a TLS-offloaded context, then this value must be
set to the header value which the TLS-offloading engine will use to set client certificates presented
via the TLS handshake.",
      "propertyOrder" : 900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "deployment-auth-target-mappings" : {
      "title" : "Authentication Target Mappings",
      "description" : "Configuration of consumption of OpenAM's
rest-authN. For each validated token type (other than OpenAM), the REST
authN elements which will validate token instances. <br>Entry format:
<code>TokenType;authIndexType;authIndexValue;context_key=context_value</
code>. <br>The <code>context_key=context_value</code> entries are optional.<br><br>Each deployed
STS is configured with the authentication targets for each input token type for each supported

```


token transformation. For example, if the transformation OPENIDCONNECT->SAML2 is supported, the STS instance must be configured with information specifying which elements of the OpenAM restful authentication context needs to be consumed to validate the OPENIDCONNECT token. The elements of the configuration tuple are separated by '|'.
The first element is the input token type in the token transform: i.e. X509, OPENIDCONNECT, USERNAME, or OPENAM. The second element is the authentication target - i.e. either 'module' or 'service', and the third element is the name of the authentication module or service. The fourth (optional) element provides the STS authentication context information about the to-be-consumed authentication context.
When transforming OpenID Connect Id tokens, the OpenID Connect authentication module must be consumed, and thus a deployed rest-sts instance must be configured with the name of the header/cookie element where the OpenID Connect Id token will be placed. For this example, the following string would define these configurations: `<code>OPENIDCONNECT|module|oidc|oidc_id_token_auth_target_header_key=oidc_id_token</code>`. In this case, 'oidc' is the name of the OpenID Connect authentication module created to authenticate OpenID Connect tokens.
When transforming a X509 Certificate, the Certificate module must be consumed, and the published rest-sts instance must be configured with the name of the Certificate module (or the service containing the module), and the header name configured for the Certificate module corresponding to where the Certificate module can expect to find the to-be-validated Certificate. The following string would define these configurations: `<code>X509|module|cert_module|x509_token_auth_target_header_key=client_cert</code>`. In this case 'cert_module' is the name of the Certificate module, and client_cert is the header name where Certificate module has been configured to find the client's Certificate.",

```

        "propertyOrder" : 800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"restStsOidc" : {
    "type" : "object",
    "title" : "OpenID Connect Token",
    "propertyOrder" : 3,
    "properties" : {
        "oidc-keystore-location" : {
            "title" : "KeyStore Location",
            "description" : "For RSA-signed tokens, the filesystem or classpath location of the KeyStore containing signing key entry<br><br>For RSA-signed tokens, the KeyStore location, password, signing-key alias, and signing key password must be specified. The client secret is not required for RSA-signed tokens.",
            "propertyOrder" : 3800,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "oidc-public-key-reference-type" : {
            "title" : "Public Key Reference Type",
            "description" : "For tokens signed with RSA, how should corresponding public key be referenced in the issued jwt",
            "propertyOrder" : 3700,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "oidc-signature-key-alias" : {
            "title" : "KeyStore Signing Key Alias",
            "description" : "",

```

```

        "propertyOrder" : 4100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "oidc-custom-authn-context-mapper-class" : {
        "title" : "Custom Authn Context Mapper Class",
        "description" : "If issued OIDC tokens are to contain acr claims, implement the
<code>org.forgerock.openam.sts.rest.token.provider.oidc.OpenIdConnectTokenAuthnContextMapper</code>
interface, and specify the class name of the implementation here.",
        "propertyOrder" : 5000,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "oidc-token-lifetime-seconds" : {
        "title" : "Token Lifetime (Seconds)",
        "description" : "",
        "propertyOrder" : 3500,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "oidc-audience" : {
        "title" : "Issued Tokens Audience",
        "description" : "Contents will be set in the aud claim",
        "propertyOrder" : 4600,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "oidc-custom-claim-mapper-class" : {
        "title" : "Custom Claim Mapper Class",
        "description" : "If the class implementing attribute mapping for attributes
contained in issued OpenID Connect tokens needs to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.oidc.OpenIdConnectTokenClaimMapper</code> interface,
and specify the class name of the implementation here.",
        "propertyOrder" : 4900,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "oidc-authorized-party" : {
        "title" : "Authorized Party",
        "description" : "",
        "propertyOrder" : 4700,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "oidc-issuer" : {
        "title" : "The OpenID Connect Token Provider Issuer Id",
        "description" : "",
        "propertyOrder" : 3450,
        "required" : true,
        "type" : "string",
    }

```

```

    "exampleValue" : ""
  },
  "oidc-keystore-password" : {
    "title" : "KeyStore Password",
    "description" : "",
    "propertyOrder" : 3900,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "oidc-claim-map" : {
    "title" : "Claim Map",
    "description" : "Contains the mapping of OIDC token claim names (Map keys) to local
OpenAM attributes (Map values) in configured data stores. Format: <code>claim_name=attribute_name</
code><br><br>The keys in the map will be claim entries in the issued OIDC token, and the value of
these claims will be the principal attribute state resulting from LDAP datastore lookup of the map
values. If no values are returned from the LDAP datastore lookup of the attribute corresponding to
the map value, no claim will be set in the issued OIDC token.",
    "propertyOrder" : 4800,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"oidc-signature-algorithm" : {
  "title" : "Token Signature Algorithm",
  "description" : "Algorithm used to sign issued OIDC tokens",
  "propertyOrder" : 3600,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"oidc-custom-authn-method-references-mapper-class" : {
  "title" : "Custom Authn Methods References Mapper Class",
  "description" : "If issued OIDC tokens are to contain amr claims, implement the
<code>org.forgerock.openam.sts.rest.token.provider.oidc.OpenIdConnectTokenAuthMethodReferencesMapper</
code> interface, and specify the class name of the implementation here.",
  "propertyOrder" : 5100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"oidc-signature-key-password" : {
  "title" : "Signature Key Password",
  "description" : "",
  "propertyOrder" : 4200,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"oidc-client-secret" : {
  "title" : "Client Secret",

```

```

    "description" : "For HMAC-signed tokens, the client secret used as the HMAC key.<br><br>For
HMAC-signed tokens, the KeyStore location, password, signature key alias and password configurations
are not required.",
    "propertyOrder" : 4400,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }
}
},
"restStsGeneral" : {
  "type" : "object",
  "title" : "General",
  "propertyOrder" : 0,
  "properties" : {
    "persist-issued-tokens-in-cts" : {
      "title" : "Persist Issued Tokens in Core Token Store",
      "description" : "Necessary to support token validation and cancellation<br><br>Validation of
STS-issued tokens will involve determining whether the token has been issued, has not expired, and
has not been cancelled. Token cancellation involves removing the record of this token from the CTS.
Thus CTS persistence of STS-issued tokens is required to support these features.",
      "propertyOrder" : 100,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "custom-token-validators" : {
      "title" : "Custom Token Validators",
      "description" : "If validator of a custom token type is desired, specify
the name of the custom token here, followed by '|', followed by the class name of the
<code>org.forgerock.openam.sts.rest.token.validator.RestTokenTransformValidator</code> implementation
which will be invoked to validate the custom tokens.<br><br>Example: <code>MY_CUSTOM_INPUT_TOKEN|
org.mycompany.tokens.MyCustomTokenValidator</code> <br>Note that MY_CUSTOM_INPUT_TOKEN would then
be specified as the value corresponding to the token_type key in the input_token_state json object
specified in rest-sts token transformation invocations.",
      "propertyOrder" : 300,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "custom-token-transforms" : {
      "title" : "Custom Token Transforms",
      "description" : "If either custom token validators or providers are specified, they must
also be specified in a custom rest-sts token transformation. These input or output tokens can be
specified in a transformation with standard, or other custom, tokens.<br><br>The format of these
token transformation definitions is the same as the standard token transformation definitions.
The first field defines the input token type, the second the output token type, and the third
field specifies whether the OpenAM session, produced as part of the validation of the input
token type, is invalidated following the production of the output token. <br><br>Example 1:<code>
MY_CUSTOM_INPUT_TOKEN|SAML2|true</code> <br>Example 1 specifies a MY_CUSTOM_INPUT_TOKEN as the
input token (requires the specification of a custom token validator) SAML2 as the produced token,
and that the interim OpenAM Session should be invalidated after the SAML2 token is produced.
<br><br>Example 2: <code>OPENIDCONNECT|MY_CUSTOM_OUTPUT_TOKEN|true</code> <br>Example 2 specifies
that an OPENIDCONNECT token should be authenticated to assert the identity of a token of type
MY_CUSTOM_OUTPUT_TOKEN (requires the specification of a custom token provider) and that the

```


1.131. RadiusClient

1.131.1. Global Operations

Resource path: `/global-config/services/RadiusServerService/radiusClient`

Resource version: `1.0`

1.131.1.1. create

Usage:

```
am> create RadiusClient --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "handlerClass" : {
      "title" : "Handler Class",
      "description" : "The fully qualified name of a class to handle incoming RADIUS Access-Requests for this client.<br><br>This class must implement the <code>com.sun.identity.authentication.modules.radius.server.spi.AccessRequestHandler</code> interface to handle incoming Access-Request packets and provide a suitable response. An instance of this class is created when configuration is first loaded to validate the class and then once for each new request. The configuration properties will only be passed for the request handling instances and not when validating the class.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "clientSecret" : {
      "title" : "Client Secret",
      "description" : "This secret shared between server and client for encryption of the user password.<br><br>This secret must be conveyed to the RADIUS client and entered into its configuration before the User-Password field of incoming Access-Request packets can be decrypted to validate the password for the represented by that packet. A default value is generated for you but you can enter a custom value if desired.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```

    },
    "handlerConfig" : {
      "title" : "Handler Class Configuration Properties",
      "description" : "Properties needed by the handler class for its configuration.<br><br>These
properties are provided to the handler via its <code>init</code> method prior to the call to handle
the request packet. If these values are changed the next handler instance created for an incoming
request will receive the updated values. Each entry assumes that the first '<code>=</code>' character
incurd separates a key from its value. All entries are placed in a properties file handed to each
handler instance.",
      "propertyOrder" : 900,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "clientIpAddress" : {
      "title" : "Client IP Address",
      "description" : "The IP Address of the client.<br><br><a href=\"http://tools.ietf.org/html/
rfc2865#section-5.4\" target=\"_blank\">Section 5.4 of the RADIUS Authentication Specification,
RFC 2865</a>, indicates that the source IP address of the Access-Request packet <em>MUST</em> be
used to identify a configured client and hence determine the shared secret to use for decrypting
the User-Password field.<p><p>This property should hold the source IP address of the client. This
should match the value obtained from Java's <code>InetSocketAddress.getAddress().toString</code>
function.<p><p>To verify the value, send an Access-Request packet to OpenAM's RADIUS port and watch
for a message stating: <code>\"No Defined RADIUS Client matches IP address '/127.0.0.1'. Dropping
request.\"</code>. The value used in this property should match the IP address returned in the single
quotes.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "clientPacketsLogged" : {
      "title" : "Log Packet Contents for this Client",
      "description" : "Indicates if full packet contents should be dumped to the log.<br><br>When
troubleshooting issues with RADIUS it is helpful to know what was received in a given packet.
Enabling this feature will cause packet contents to be logged in a human consumable format. The only
caveat is that the USER_PASSWORD field will be obfuscated by replacing with asterisks. This should
only be enabled for troubleshooting as it adds significant content to logs and slows processing.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}

```

1.131.1.2. delete

Usage:

```
am> delete RadiusClient --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.131.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RadiusClient --global --actionName getAllTypes
```

1.131.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RadiusClient --global --actionName getCreatableTypes
```

1.131.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RadiusClient --global --actionName nextdescendents
```

1.131.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query RadiusClient --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.131.1.7. read

Usage:

```
am> read RadiusClient --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.131.1.8. update

Usage:

```
am> update RadiusClient --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "handlerClass" : {
      "title" : "Handler Class",
      "description" : "The fully qualified name of a class to handle incoming
RADIUS Access-Requests for this client.<br><br>This class must implement the
<code>com.sun.identity.authentication.modules.radius.server.spi.AccessRequestHandler</code> interface
to handle incoming Access-Request packets and provide a suitable response. An instance of this class
is created when configuration is first loaded to validate the class and then once for each new
request. The configuration properties will only be passed for the request handling instances and not
when validating the class.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "clientSecret" : {
      "title" : "Client Secret",
      "description" : "This secret shared between server and client for encryption of the user
password.<br><br>This secret must be conveyed to the RADIUS client and entered into its configuration
before the User-Password field of incoming Access-Request packets can be decrypted to validate the
password for the represented by that packet. A default value is generated for you but you can enter a
custom value if desired.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "handlerConfig" : {
      "title" : "Handler Class Configuration Properties",
      "description" : "Properties needed by the handler class for its configuration.<br><br>These
properties are provided to the handler via its <code>init</code> method prior to the call to handle
the request packet. If these values are changed the next handler instance created for an incoming
request will receive the updated values. Each entry assumes that the first '<code>=</code>' character
```

```

incurred separates a key from its value. All entries are placed in a properties file handed to each
handler instance.",
  "propertyOrder" : 900,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"clientIpAddress" : {
  "title" : "Client IP Address",
  "description" : "The IP Address of the client.<br><br><a href=\"http://tools.ietf.org/html/
rfc2865#section-5.4\" target=\"_blank\">Section 5.4 of the RADIUS Authentication Specification,
RFC 2865</a>, indicates that the source IP address of the Access-Request packet <em>MUST</em> be
used to identify a configured client and hence determine the shared secret to use for decrypting
the User-Password field.<p><p>This property should hold the source IP address of the client. This
should match the value obtained from Java's <code>InetAddress.getAddress().toString()</code>
function.<p><p>To verify the value, send an Access-Request packet to OpenAM's RADIUS port and watch
for a message stating: <code>\"No Defined RADIUS Client matches IP address '/127.0.0.1'. Dropping
request.\"</code>. The value used in this property should match the IP address returned in the single
quotes.",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"clientPacketsLogged" : {
  "title" : "Log Packet Contents for this Client",
  "description" : "Indicates if full packet contents should be dumped to the log.<br><br>When
troubleshooting issues with RADIUS it is helpful to know what was received in a given packet.
Enabling this feature will cause packet contents to be logged in a human consumable format. The only
caveat is that the USER_PASSWORD field will be obfuscated by replacing with asterisks. This should
only be enabled for troubleshooting as it adds significant content to logs and slows processing.",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
}
}

```

1.132. RadiusModule

1.132.1. Realm Operations

Resource path: `/realm-config/authentication/modules/radius`

Resource version: `1.0`

1.132.1.1. create

Usage:

```
am> create RadiusModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "serverPortNumber" : {
      "title" : "Port Number",
      "description" : "Port number on which the RADIUS server is listening.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sharedSecret" : {
      "title" : "Shared Secret",
      "description" : "The secret shared between the RADIUS server and the authentication module.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "secondaryRadiusServers" : {
      "title" : "Secondary Radius Servers",
      "description" : "A list of secondary Radius servers that will be used for authentication, in case the primary servers are unavailable.<br><br>The module will use secondary servers for authentication if all primary servers are unavailable. A single entry must be in the format:<br><br><code>radius_server:port</code><br><br>Multiple entries allow associations between OpenAM servers and a Radius server. The format is:<br><br><code>local server name | radius_server:port</code><br><br><i>NB </i>The local server name is the full name of the server from the list of servers and sites.",
      "propertyOrder" : 200,
      "required" : true,
      "items" : {
        "type" : "string"
      }
    }
  }
}
```

```

    },
    "type" : "array",
    "exampleValue" : ""
  },
  "serverTimeout" : {
    "title" : "Timeout",
    "description" : "Amount of time in seconds to wait for the RADIUS server response.<br><br>This sets the <code>SO_TIMEOUT</code> timeout on the packet. ",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "primaryRadiusServers" : {
    "title" : "Primary Radius Servers",
    "description" : "A list of primary Radius servers that will be used for authentication<br><br>The module will use these servers in preference to the secondary servers. A single entry must be in the format:<br><br><code>radius_server:port</code><br><br>Multiple entries allow associations between OpenAM servers and a Radius server. The format is:<br><br><code>local server name | radius_server:port</code><br><br><i>NB </i>The local server name is the full name of the server from the list of servers and sites.",
    "propertyOrder" : 100,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "healthCheckInterval" : {
    "title" : "Health check interval",
    "description" : "The interval between checks to unavailable RADIUS servers, in minutes.<br><br>Determines how often OpenAM checks an offline server's status. The check will send an invalid authentication request to the RADIUS server. Offline servers will not be used until the healthcheck was successful. Primary servers that become available will be used in preference to secondary servers.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
}

```

1.132.1.2. delete

Usage:

```
am> delete RadiusModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.132.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RadiusModule --realm Realm --actionName getAllTypes
```

1.132.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RadiusModule --realm Realm --actionName getCreatableTypes
```

1.132.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RadiusModule --realm Realm --actionName nextdescendents
```

1.132.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query RadiusModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.132.1.7. read

Usage:

```
am> read RadiusModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.132.1.8. update

Usage:

```
am> update RadiusModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "serverPortNumber" : {
      "title" : "Port Number",
      "description" : "Port number on which the RADIUS server is listening.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "sharedSecret" : {
      "title" : "Shared Secret",
      "description" : "The secret shared between the RADIUS server and the authentication module.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "secondaryRadiusServers" : {
      "title" : "Secondary Radius Servers",
      "description" : "A list of secondary Radius servers that will be used for authentication, in case the primary servers are unavailable.<br><br>The module will use secondary servers for authentication if all primary servers are unavailable. A single entry must be in the format:<br><br><code>radius_server:port</code><br><br>Multiple entries allow associations between OpenAM servers and a Radius server. The format is:<br><br><code>local server name | radius_server:port</code><br><br><i>NB </i>The local server name is the full name of the server from the list of servers and sites.",
      "propertyOrder" : 200,
      "required" : true,
      "items" : {
```

```

    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"serverTimeout" : {
  "title" : "Timeout",
  "description" : "Amount of time in seconds to wait for the RADIUS server response.<br><br>This sets the <code>SO_TIMEOUT</code> timeout on the packet. ",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"primaryRadiusServers" : {
  "title" : "Primary Radius Servers",
  "description" : "A list of primary Radius servers that will be used for authentication<br><br>The module will use these servers in preference to the secondary servers. A single entry must be in the format:<br><br><code>radius_server:port</code><br><br>Multiple entries allow associations between OpenAM servers and a Radius server. The format is:<br><br><code>local server name | radius_server:port</code><br><br><i>NB </i>The local server name is the full name of the server from the list of servers and sites.",
  "propertyOrder" : 100,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"healthCheckInterval" : {
  "title" : "Health check interval",
  "description" : "The interval between checks to unavailable RADIUS servers, in minutes.<br><br>Determines how often OpenAM checks an offline server's status. The check will send an invalid authentication request to the RADIUS server. Offline servers will not be used until the healthcheck was successful. Primary servers that become available will be used in preference to secondary servers.",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}
}
}
}

```

1.132.2. Global Operations

Resource path: [/global-config/authentication/modules/radius](#)

Resource version: 1.0

1.132.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RadiusModule --global --actionName getAllTypes
```

1.132.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RadiusModule --global --actionName getCreatableTypes
```

1.132.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RadiusModule --global --actionName nextdescendents
```

1.132.2.4. read

Usage:

```
am> read RadiusModule --global
```

1.132.2.5. update

Usage:

```
am> update RadiusModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "serverTimeout" : {
          "title" : "Timeout",
          "description" : "Amount of time in seconds to wait for the RADIUS server
response.<br><br>This sets the <code>SO_TIMEOUT</code> timeout on the packet. ",
          "propertyOrder" : 500,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
      },
    },
  },
}
```



```

"primaryRadiusServers" : {
  "title" : "Primary Radius Servers",
  "description" : "A list of primary Radius servers that will be used for
authentication<br><br>The module will use these servers in preference to the secondary servers.
A single entry must be in the format:<br><br><code>radius_server:port</code><br><br>Multiple
entries allow associations between OpenAM servers and a Radius server. The format is:<br><br>
<code>local server name | radius_server:port</code><br><br><i>NB </i>The local server name is the
full name of the server from the list of servers and sites.",
  "propertyOrder" : 100,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"serverPortNumber" : {
  "title" : "Port Number",
  "description" : "Port number on which the RADIUS server is listening.",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"healthCheckInterval" : {
  "title" : "Health check interval",
  "description" : "The interval between checks to unavailable RADIUS servers, in minutes.
<br><br>Determines how often OpenAM checks an offline server's status. The check will send an invalid
authentication request to the RADIUS server. Offline servers will not be used until the healthcheck
was successful. Primary servers that become available will be used in preference to secondary
servers.",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default). ",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"secondaryRadiusServers" : {
  "title" : "Secondary Radius Servers",
  "description" : "A list of secondary Radius servers that will be used for authentication,
in case the primary servers are unavailable.<br><br>The module will use secondary servers for
authentication if all primary servers are unavailable. A single entry must be in the format:<br><br>
<code>radius_server:port</code><br><br>Multiple entries allow associations between OpenAM servers
and a Radius server. The format is:<br><br>
<code>local server name | radius_server:port</code><br>
<br><i>NB </i>The local server name is the full name of the server from the list of servers and
sites.",
  "propertyOrder" : 200,
  "required" : true,
  "items" : {
    "type" : "string"
  }
}
    
```

```
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sharedSecret" : {
    "title" : "Shared Secret",
    "description" : "The secret shared between the RADIUS server and the authentication
module.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
```

1.133. RadiusServer

1.133.1. Global Operations

Resource path: [/global-config/services/RadiusServerService](#)

Resource version: [1.0](#)

1.133.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RadiusServer --global --actionName getAllTypes
```

1.133.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RadiusServer --global --actionName getCreatableTypes
```

1.133.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RadiusServer --global --actionName nextdescendents
```

1.133.1.4. read

Usage:

```
am> read RadiusServer --global
```

1.133.1.5. update

Usage:

```
am> update RadiusServer --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "radiusThreadPoolMaxSize" : {
      "title" : "Thread Pool Max Size",
      "description" : "Maximum number of threads allowed in the pool. See also \"Thread Pool Core Size\"",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "radiusListenerEnabled" : {
      "title" : "Enabled",
      "description" : "Enables the OpenAM RADIUS server to listen for requests on the listener port and to handle the requests.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "radiusThreadPoolKeepaliveSeconds" : {
      "title" : "Thread Pool Keep-Alive Seconds",
      "description" : "If the pool currently has more than Thread Pool Core Size threads, excess threads will be terminated if they have been idle for more than the Keep-Alive Seconds. Specify a value from <code>1</code> to <code>3600</code>.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "radiusThreadPoolCoreSize" : {
```

```

    "title" : "Thread Pool Core Size",
    "description" : "When a RADIUS request is received and fewer than <code>corePoolSize</code> threads are running, a new thread is created to handle the request, even if other worker threads are idle. If there are more than \"Thread Pool Core Size\" but less than \"Thread Pool Max Size\" threads running, a new thread will be created only if the queue is full. By setting \"Thread Pool Core Size\" and \"Thread Pool Max Size\" to the same value, you create a fixed-size thread pool. Specify a value from <code>1</code> to <code>100</code>.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "radiusThreadPoolQueueSize" : {
    "title" : "Thread Pool Queue Size",
    "description" : "The number of requests that can be queued for the pool before further requests will be silently dropped. See also \"Thread Pool Core Size\" and \"Thread Pool Max Size\". Specify a value from <code>1</code> to <code>1000</code>.",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "radiusServerPort" : {
    "title" : "Listener Port",
    "description" : "The UDP port on which each OpenAM server will listen for RADIUS Access-Request packets<br><br>According to the RADIUS Authentication Specification, <a href=\"http://tools.ietf.org/html/rfc2865\" target=\"_blank\">RFC 2865</a>, the officially assigned port number for RADIUS is <code>1812</code>. Specify a value from <code>1024</code> to <code>65535</code>. All client requests are handled through the same port.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
}

```

1.134. Realms

1.134.1. Global Operations

The endpoint for Realm operations

Resource path: `/global-config/realms`

Resource version: `1.0`

1.134.1.1. create

Create a Realm

Usage:

```
am> create Realms --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Represents a Realm Resource",
  "type" : "object",
  "title" : "Realm",
  "properties" : {
    "name" : {
      "type" : "string",
      "title" : "Name",
      "description" : "The name of the Realm"
    },
    "active" : {
      "type" : "boolean",
      "title" : "Active",
      "description" : "True if the Realm is active"
    },
    "parentPath" : {
      "type" : "string",
      "title" : "Parent",
      "description" : "The path of the Realm's parent Realm"
    },
    "aliases" : {
      "type" : "array",
      "title" : "Aliases",
      "description" : "Aliases which can be used reference to the Realm",
      "items" : {
        "type" : "string"
      }
    }
  },
  "required" : [ "name", "active", "parentPath", "aliases" ]
}
```

1.134.1.2. delete

Delete a Realm

Usage:

```
am> delete Realms --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.134.1.3. query

Usage:

```
am> query Realms --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.134.1.4. read

Read a Realm

Usage:

```
am> read Realms --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.134.1.5. update

Update a Realm

Usage:

```
am> update Realms --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Represents a Realm Resource",
  "type" : "object",
  "title" : "Realm",
  "properties" : {
    "name" : {
      "type" : "string",
      "title" : "Name",
      "description" : "The name of the Realm"
```

```
},
"active" : {
  "type" : "boolean",
  "title" : "Active",
  "description" : "True if the Realm is active"
},
"parentPath" : {
  "type" : "string",
  "title" : "Parent",
  "description" : "The path of the Realm's parent Realm"
},
"aliases" : {
  "type" : "array",
  "title" : "Aliases",
  "description" : "Aliases which can be used reference to the Realm",
  "items" : {
    "type" : "string"
  }
}
},
"required" : [ "name", "active", "parentPath", "aliases" ]
}
```

1.135. Records

1.135.1. Realm Operations

Service for creating records.

Resource path: `/records`

Resource version: `1.0`

1.135.1.1. start

Starts recording.

Usage:

```
am> action Records --realm Realm --body body --actionName start
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "The properties of a Record, which can deserialized from json.",
  "type" : "object",
  "title" : "Record properties",
  "properties" : {
    "issueID" : {
```

```
"description" : "A case number is a good choice for the issueID value.",
"title" : "Issue ID",
"type" : "integer",
"format" : "int64"
},
"referenceID" : {
"issue." description" : "A second identifier to segregate multiple recording events for the same",
"title" : "Reference ID",
"type" : "string"
},
"description" : {
"description" : "A textual description of the recording event.",
"title" : "Description",
"type" : "string"
},
"threadDumpDelayInSeconds" : {
"description" : "Object used to specify an interval at which thread dumps are taken. The initial
thread dump is taken at the start of the recording event; subsequent thread dumps are taken at
multiples of the delay interval.",
"title" : "Thread dump delay in seconds",
"type" : "integer",
"format" : "int64"
},
"configExportPassword" : {
"description" : "A key required to import the exported configuration.",
"title" : "Config export password",
"type" : "string"
},
"debugLevel" : {
"description" : "The debug level to set for the recording event.",
"title" : "Debug level",
"type" : "string",
"enum" : [ "OFF", "ERROR", "WARNING", "MESSAGE", "ON" ]
},
"autoStopTimeInMS" : {
"description" : "Used to specify an event that automatically ends a recording period. For time-
based termination, specify a time object; for termination based on uncompressed file size, specify a
fileSize object. If you specify both time and fileSize objects, the event that occurs first causes
recording to stop.",
"title" : "Auto stop time in milliseconds",
"type" : "integer",
"format" : "int64"
},
"configExportSharePasswordEnabled" : {
"description" : "Whether to show the password value in the ssoadm start-recording, ssoadm get-
recording-status, ssoadm stop-recording output and in the info.json file.",
"title" : "Config export share password enabled",
"type" : "boolean"
},
"autoStopFileSizeInKB" : {
"description" : "Configures a recording period to terminate after the aggregate size of
uncompressed debug logs has reached this size.",
"title" : "Auto stop file size in KB",
"type" : "integer",
"format" : "int64"
},
"threadDumpEnabled" : {
"description" : "Whether to dump threads during the recording event.",
```



```
    "title" : "Thread dump enabled",
    "type" : "boolean"
  },
  "configExportEnabled" : {
    "description" : "Whether to export the OpenAM configuration upon completion of the recording
event.",
    "title" : "Config export enabled",
    "type" : "boolean"
  },
  "autoStopEnabled" : {
    "description" : "Whether auto stop is enabled.",
    "title" : "Auto stop enabled",
    "type" : "boolean"
  },
  "autoStopTimeEnabled" : {
    "description" : "Whether time is specified for the auto stop.",
    "title" : "Auto stop time enabled",
    "type" : "boolean"
  },
  "autoStopFileSizeEnabled" : {
    "description" : "Whether file size is enabled for the auto stop.",
    "title" : "Auto stop file size enabled",
    "type" : "boolean"
  },
  "zipEnabled" : {
    "description" : "Whether to compress the output directory into a zip file when recording has
stopped.",
    "title" : "Zip enabled",
    "type" : "boolean"
  }
}
```

1.135.1.2. status

Returns status of recording.

Usage:

```
am> action Records --realm Realm --actionName status
```

1.135.1.3. stop

Stops recording.

Usage:

```
am> action Records --realm Realm --actionName stop
```

1.136. RecoveryCodeCollectorDecision

1.136.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/RecoveryCodeCollectorDecisionNode`

Resource version: `1.0`

1.136.1.1. create

Usage:

```
am> create RecoveryCodeCollectorDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "recoveryCodeType" : {
      "title" : "Recovery Code Type",
      "description" : "Determines which type of recovery codes are going to be validated for the user.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "recoveryCodeType" ]
}
```

1.136.1.2. delete

Usage:

```
am> delete RecoveryCodeCollectorDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.136.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RecoveryCodeCollectorDecision --realm Realm --actionName getAllTypes
```

1.136.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RecoveryCodeCollectorDecision --realm Realm --actionName getCreatableTypes
```

1.136.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action RecoveryCodeCollectorDecision --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.136.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RecoveryCodeCollectorDecision --realm Realm --actionName nextdescendents
```

1.136.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query RecoveryCodeCollectorDecision --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.136.1.8. read

Usage:

```
am> read RecoveryCodeCollectorDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.136.1.9. update

Usage:

```
am> update RecoveryCodeCollectorDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "recoveryCodeType" : {
      "title" : "Recovery Code Type",
      "description" : "Determines which type of recovery codes are going to be validated for the user.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "recoveryCodeType" ]
}
```

1.137. RegisterLogoutWebhook

1.137.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/RegisterLogoutWebhookNode`

Resource version: `1.0`

1.137.1.1. create

Usage:

```
am> create RegisterLogoutWebhook --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "webhookName" : {
      "title" : "Webhook Name",
      "description" : "The name of the webhook stored using the webhook service.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "webhookName" ]
}
```

1.137.1.2. delete

Usage:

```
am> delete RegisterLogoutWebhook --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.137.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RegisterLogoutWebhook --realm Realm --actionName getAllTypes
```

1.137.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RegisterLogoutWebhook --realm Realm --actionName getCreatableTypes
```

1.137.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action RegisterLogoutWebhook --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.137.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RegisterLogoutWebhook --realm Realm --actionName nextdescendents
```

1.137.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query RegisterLogoutWebhook --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.137.1.8. read

Usage:

```
am> read RegisterLogoutWebhook --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.137.1.9. update

Usage:

```
am> update RegisterLogoutWebhook --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "webhookName" : {
      "title" : "Webhook Name",
      "description" : "The name of the webhook stored using the webhook service.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "webhookName" ]
}
```

1.138. RemoteConsentAgent

1.138.1. Realm Operations

Agents handler that is responsible for managing agents

Resource path: `/realm-config/agents/RemoteConsentAgent`

Resource version: `1.0`

1.138.1.1. create

Usage:

```
am> create RemoteConsentAgent --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "remoteConsentRequestSigningAlgorithm" : {
      "title" : "Consent request Signing Algorithm",
      "description" : "Signing algorithm to be used when signing the consent request JWT.",
      "propertyOrder" : 34500,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : true
        }
      }
    },
    "remoteConsentRequestEncryptionMethod" : {
      "title" : "Consent request Encryption Method",
      "description" : "Encryption method to be used when encrypting the consent request JWT.",
      "propertyOrder" : 34300,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
```



```

        "type" : "boolean",
        "required" : true
    },
    "value" : {
        "type" : "string",
        "required" : true
    }
}
},
"remoteConsentRequestEncryptionAlgorithm" : {
    "title" : "Consent request Encryption Algorithm",
    "description" : "Encryption algorithm to be used when encrypting the consent request JWT.",
    "propertyOrder" : 34200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : true
        }
    }
},
"agentgroup" : {
    "title" : "Group",
    "description" : "Add the agent to a group to allow inheritance of property values from the group. <br>Changing the group will update inherited property values. <br>Inherited property values are copied to the agent.",
    "propertyOrder" : 50,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
},
"remoteConsentResponseEncryptionAlgorithm" : {
    "title" : "Consent response encryption algorithm",
    "description" : "The encryption algorithm to be used by the provider when decrypting the remote consent response JWT received from the Remote Consent Service.",
    "propertyOrder" : 34500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
},
"requestTimeLimit" : {
    "title" : "Consent Request Time Limit",
    "description" : "The amount of seconds for which the consent request JWT sent to the Remote Consent Service should be considered valid.",
    "propertyOrder" : 35200,

```

```
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "integer",
    "required" : false
  }
}
},
"jwksCacheTimeout" : {
  "title" : "JWKS URI content cache timeout in ms",
  "description" : "To avoid loading the JWKS URI content for every operation, the JWKS content is
cached. This timeout defines the maximum amount of time the JWKS URI content can be cached before
being refreshed.",
  "propertyOrder" : 34900,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : true
    }
  }
}
},
"publicKeyLocation" : {
  "title" : "Public key selector",
  "description" : "",
  "propertyOrder" : 34700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
}
},
"jwkSet" : {
  "title" : "Json Web Key",
  "description" : "Raw JSON Web Key value containing the Remote Consent Service's public keys.",
  "propertyOrder" : 35100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
```

```

    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"userpassword" : {
  "title" : "Remote Consent Service secret",
  "description" : "Used when the Remote Consent Service authenticates to AM.",
  "propertyOrder" : 33000,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"jwkStoreCacheMissCacheTime" : {
  "title" : "JWKS URI content cache miss time",
  "description" : "To avoid loading the JWKS URI content for every operation, especially when the kid is not in the jwks content already cached, the JWKS content will be cached for a minimum period of time. This cache miss cache time defines the minimum amount of time the JWKS URI content is cached.",
  "propertyOrder" : 35000,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : true
    }
  }
}
},
"remoteConsentRequestEncryptionEnabled" : {
  "title" : "Enable consent request Encryption",
  "description" : "Enables encryption of the consent request JWT.",
  "propertyOrder" : 34100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
},
"remoteConsentResponseEncryptionMethod" : {
  "title" : "Consent response encryption method",
  "description" : "The encryption method to be used by the provider when decrypting the remote consent response JWT received from the Remote Consent Service.<br><br>AM supports the following token encryption algorithms: <ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC-HS256</code>,

```

```
<code>A192CBC-HS384</code>, and <code>A256CBC-HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 34600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"jwksUri" : {
  "title" : "Json Web Key URI",
  "description" : "The URI containing the public keys of the Remote Consent Service secret. The public keys are in the Json Web Key (jwk) format.",
  "propertyOrder" : 34800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"remoteConsentRedirectUrl" : {
  "title" : "Redirect URL",
  "description" : "The Remote Consent Service's URL to which the authorization server should redirect the user in order to obtain their consent.",
  "propertyOrder" : 34000,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"remoteConsentResponseSigningAlg" : {
  "title" : "Consent response signing algorithm",
  "description" : "The signing algorithm to be used by the provider when verifying the signature of the consent response JWT received from the Remote Consent Service.",
  "propertyOrder" : 34400,
  "type" : "object",
  "exampleValue" : "",
```

```
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "string",
    "required" : false
  }
}
}
```

1.138.1.2. delete

Usage:

```
am> delete RemoteConsentAgent --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.138.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RemoteConsentAgent --realm Realm --actionName getAllTypes
```

1.138.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RemoteConsentAgent --realm Realm --actionName getCreatableTypes
```

1.138.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RemoteConsentAgent --realm Realm --actionName nextdescendents
```

1.138.1.6. query

Querying the agents of a specific type

Usage:

```
am> query RemoteConsentAgent --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.138.1.7. read

Usage:

```
am> read RemoteConsentAgent --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.138.1.8. update

Usage:

```
am> update RemoteConsentAgent --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "remoteConsentRequestSigningAlgorithm" : {
      "title" : "Consent request Signing Algorithm",
      "description" : "Signing algorithm to be used when signing the consent request JWT.",
      "propertyOrder" : 34500,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
```

```

        "required" : true
    },
    "value" : {
        "type" : "string",
        "required" : true
    }
}
},
"remoteConsentRequestEncryptionMethod" : {
    "title" : "Consent request Encryption Method",
    "description" : "Encryption method to be used when encrypting the consent request JWT.",
    "propertyOrder" : 34300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : true
        }
    }
},
"remoteConsentRequestEncryptionAlgorithm" : {
    "title" : "Consent request Encryption Algorithm",
    "description" : "Encryption algorithm to be used when encrypting the consent request JWT.",
    "propertyOrder" : 34200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : true
        }
    }
},
"agentgroup" : {
    "title" : "Group",
    "description" : "Add the agent to a group to allow inheritance of property values from the group. <br>Changing the group will update inherited property values. <br>Inherited property values are copied to the agent.",
    "propertyOrder" : 50,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
},
"remoteConsentResponseEncryptionAlgorithm" : {
    "title" : "Consent response encryption algorithm",
    "description" : "The encryption algorithm to be used by the provider when decrypting the remote consent response JWT received from the Remote Consent Service.",
    "propertyOrder" : 34500,
    "type" : "object",
    "exampleValue" : "",

```

```
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "string",
    "required" : false
  }
}
},
"requestTimeLimit" : {
  "title" : "Consent Request Time Limit",
  "description" : "The amount of seconds for which the consent request JWT sent to the Remote
Consent Service should be considered valid.",
  "propertyOrder" : 35200,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : false
    }
  }
}
},
"jwksCacheTimeout" : {
  "title" : "JWKS URI content cache timeout in ms",
  "description" : "To avoid loading the JWKS URI content for every operation, the JWKS content is
cached. This timeout defines the maximum amount of time the JWKS URI content can be cached before
being refreshed.",
  "propertyOrder" : 34900,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : true
    }
  }
}
},
"publicKeyLocation" : {
  "title" : "Public key selector",
  "description" : "",
  "propertyOrder" : 34700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
```



```
    "value" : {
      "type" : "string",
      "required" : true
    }
  },
  "jwkSet" : {
    "title" : "Json Web Key",
    "description" : "Raw JSON Web Key value containing the Remote Consent Service's public keys.",
    "propertyOrder" : 35100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "userpassword" : {
    "title" : "Remote Consent Service secret",
    "description" : "Used when the Remote Consent Service authenticates to AM.",
    "propertyOrder" : 33000,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "jwkStoreCacheMissCacheTime" : {
    "title" : "JWKS URI content cache miss cache time",
    "description" : "To avoid loading the JWKS URI content for every operation, especially when the kid is not in the jwks content already cached, the JWKS content will be cached for a minimum period of time. This cache miss cache time defines the minimum amount of time the JWKS URI content is cached.",
    "propertyOrder" : 35000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : true
      }
    }
  },
  "remoteConsentRequestEncryptionEnabled" : {
    "title" : "Enable consent request Encryption",
    "description" : "Enables encryption of the consent request JWT.",
    "propertyOrder" : 34100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
```

```

    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"remoteConsentResponseEncryptionMethod" : {
  "title" : "Consent response encryption method",
  "description" : "The encryption method to be used by the provider when decrypting the remote consent response JWT received from the Remote Consent Service.<br><br>AM supports the following token encryption algorithms: <ul><li><code>A128GCM</code>, <code>A192GCM</code>, and <code>A256GCM</code> - AES in Galois Counter Mode (GCM) authenticated encryption mode.</li><li><code>A128CBC</code>, <code>A192CBC</code>-HS384</code>, and <code>A256CBC</code>-HS512</code> - AES encryption in CBC mode, with HMAC-SHA-2 for integrity.</li></ul>",
  "propertyOrder" : 34600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"jwksUri" : {
  "title" : "Json Web Key URI",
  "description" : "The URI containing the public keys of the Remote Consent Service secret. The public keys are in the Json Web Key (jwk) format.",
  "propertyOrder" : 34800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
},
"remoteConsentRedirectUrl" : {
  "title" : "Redirect URL",
  "description" : "The Remote Consent Service's URL to which the authorization server should redirect the user in order to obtain their consent.",
  "propertyOrder" : 34000,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {

```

```
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "string",
    "required" : false
  }
},
"remoteConsentResponseSigningAlg" : {
  "title" : "Consent response signing algorithm",
  "description" : "The signing algorithm to be used by the provider when verifying the signature
of the consent response JWT received from the Remote Consent Service.",
  "propertyOrder" : 34400,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
}
}
}
```

1.139. RemoteConsentService

1.139.1. Realm Operations

Resource path: `/realm-config/services/RemoteConsentService`

Resource version: `1.0`

1.139.1.1. create

Usage:

```
am> create RemoteConsentService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
```

```
"type" : "object",
"properties" : {
  "jwksUriAS" : {
    "title" : "Authorization Server jwk_uri",
    "description" : "The jwk_uri for retrieving the authorization server signing and encryption keys.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "signingKeyAlias" : {
    "title" : "Signing Key Alias",
    "description" : "The alias of the key in the default keystore to use for signing.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "jwkStoreCacheTimeout" : {
    "title" : "JWK Store Cache Timeout (in minutes)",
    "description" : "The cache timeout for the JWK store of the authorization server, in minutes.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "consentResponseTimeLimit" : {
    "title" : "Consent Response Time Limit (in minutes)",
    "description" : "The time limit set on the consent response JWT before it expires, in minutes.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "clientId" : {
    "title" : "Client Name",
    "description" : "The name used to identify this OAuth 2.0 remote consent service when referenced in other services.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "encryptionKeyAlias" : {
    "title" : "Encryption Key Alias",
    "description" : "The alias of the key in the default keystore to use for encryption.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "jwkStoreCacheMissCacheTime" : {
    "title" : "JWK Store Cache Miss Cache Time (in minutes)",
    "description" : "The length of time a cache miss is cached, in minutes.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
```

```
}  
}  
}
```

1.139.1.2. delete

Usage:

```
am> delete RemoteConsentService --realm Realm
```

1.139.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RemoteConsentService --realm Realm --actionName getAllTypes
```

1.139.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RemoteConsentService --realm Realm --actionName getCreatableTypes
```

1.139.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RemoteConsentService --realm Realm --actionName nextdescendents
```

1.139.1.6. read

Usage:

```
am> read RemoteConsentService --realm Realm
```

1.139.1.7. update

Usage:

```
am> update RemoteConsentService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "jwksUriAS" : {
      "title" : "Authorization Server jwk_uri",
      "description" : "The jwk_uri for retrieving the authorization server signing and encryption
keys.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "signingKeyAlias" : {
      "title" : "Signing Key Alias",
      "description" : "The alias of the key in the default keystore to use for signing.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "jwkStoreCacheTimeout" : {
      "title" : "JWK Store Cache Timeout (in minutes)",
      "description" : "The cache timeout for the JWK store of the authorization server, in minutes.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "consentResponseTimeLimit" : {
      "title" : "Consent Response Time Limit (in minutes)",
      "description" : "The time limit set on the consent response JWT before it expires, in minutes.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "clientId" : {
      "title" : "Client Name",
      "description" : "The name used to identify this OAuth 2.0 remote consent service when
referenced in other services.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "encryptionKeyAlias" : {
      "title" : "Encryption Key Alias",
      "description" : "The alias of the key in the default keystore to use for encryption.",
      "propertyOrder" : 300,
      "required" : true,

```

```
    "type" : "string",
    "exampleValue" : ""
  },
  "jwkStoreCacheMissCacheTime" : {
    "title" : "JWK Store Cache Miss Cache Time (in minutes)",
    "description" : "The length of time a cache miss is cached, in minutes.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
```

1.139.2. Global Operations

Resource path: `/global-config/services/RemoteConsentService`

Resource version: `1.0`

1.139.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RemoteConsentService --global --actionName getAllTypes
```

1.139.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RemoteConsentService --global --actionName getCreatableTypes
```

1.139.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RemoteConsentService --global --actionName nextdescendents
```

1.139.2.4. read

Usage:

```
am> read RemoteConsentService --global
```

1.139.2.5. update

Usage:

```
am> update RemoteConsentService --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "signingKeyAlias" : {
          "title" : "Signing Key Alias",
          "description" : "The alias of the key in the default keystore to use for signing.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "encryptionKeyAlias" : {
          "title" : "Encryption Key Alias",
          "description" : "The alias of the key in the default keystore to use for encryption.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "jwksUriAS" : {
          "title" : "Authorization Server jwk_uri",
          "description" : "The jwk_uri for retrieving the authorization server signing and encryption
keys.",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "clientId" : {
          "title" : "Client Name",
          "description" : "The name used to identify this OAuth 2.0 remote consent service when
referenced in other services.",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "jwkStoreCacheMissCacheTime" : {
          "title" : "JWK Store Cache Miss Cache Time (in minutes)",
```



```
    "description" : "The length of time a cache miss is cached, in minutes.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "jwkStoreCacheTimeout" : {
    "title" : "JWK Store Cache Timeout (in minutes)",
    "description" : "The cache timeout for the JWK store of the authorization server, in
minutes.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "consentResponseTimeLimit" : {
    "title" : "Consent Response Time Limit (in minutes)",
    "description" : "The time limit set on the consent response JWT before it expires, in
minutes.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
```

1.140. RemoveSessionProperties

1.140.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/RemoveSessionPropertiesNode`

Resource version: [1.0](#)

1.140.1.1. create

Usage:

```
am> create RemoveSessionProperties --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "propertyNames" : {
      "title" : "Property Names",
      "description" : "The names of session properties to remove that may have been contributed by nodes that executed earlier in the tree. If the properties do not exist, no error will be thrown. Names are case sensitive.",
      "propertyOrder" : 100,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  },
  "required" : [ "propertyNames" ]
}
```

1.140.1.2. delete

Usage:

```
am> delete RemoveSessionProperties --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.140.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RemoveSessionProperties --realm Realm --actionName getAllTypes
```

1.140.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RemoveSessionProperties --realm Realm --actionName getCreatableTypes
```

1.140.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action RemoveSessionProperties --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.140.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RemoveSessionProperties --realm Realm --actionName nextdescendents
```

1.140.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query RemoveSessionProperties --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.140.1.8. read

Usage:

```
am> read RemoveSessionProperties --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.140.1.9. update

Usage:

```
am> update RemoveSessionProperties --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "propertyNames" : {
      "title" : "Property Names",
      "description" : "The names of session properties to remove that may have been contributed by
Names are case sensitive.",
      "propertyOrder" : 100,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  },
  "required" : [ "propertyNames" ]
}
```

1.141. ResourceSets

1.141.1. Realm Operations

Resource set resource provider is responsible for managing Resource Sets belonging to a user. Available operations are update, query, read, revoke all action.

Resource path: </users/{user}/oauth2/resources/sets>

Resource version: [1.0](#)

1.141.1.1. query

Query the collection of the user's Resource Set.

Usage:

```
am> query ResourceSets --realm Realm --filter filter --user user
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

--user

Resource set resource provider is responsible for managing Resource Sets belonging to a user. Available operations are update, query, read, revoke all action.

1.141.1.2. read

Read Resource Set from the collection by id.

Usage:

```
am> read ResourceSets --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

Resource set resource provider is responsible for managing Resource Sets belonging to a user. Available operations are update, query, read, revoke all action.

1.141.1.3. update

Update a Resource Set record.

Usage:

```
am> update ResourceSets --realm Realm --id id --body body --user user
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Describes the structure of the OpenAM representation of a user's OAuth Resource Set. For further information see [insert link to the RSR standard], and documentation about UMA in OpenAM.",
  "type" : "object",
  "title" : "Resource Set resource schema",
  "properties" : {
    "scopes" : {
      "type" : "array",
      "title" : "Scopes",
      "description" : "List of Resource Set scopes.",
      "items" : {
        "type" : "string"
      }
    },
    "_id" : {
      "type" : "string",
      "title" : "Resource set id",
      "description" : "Unique identifier of the Resource Set."
    },
    "resourceServer" : {
      "type" : "string",
      "title" : "Resource server",
      "description" : "The resources server name."
    },
    "labels" : {
      "type" : "array",
      "title" : "Resource labels",
      "description" : "Labels of the resource.",
      "items" : {
        "type" : "string"
      }
    },
    "name" : {
      "type" : "string",
      "title" : "Resource name",
      "description" : "Name of the resource."
    },
    "icon_uri" : {
      "type" : "string",
      "title" : "Icon uri",
      "description" : "Resource icon uri."
    },
    "resourceOwnerId" : {
      "type" : "string",
      "title" : "Resource owner",
      "description" : "Name of the resource owner."
    },
    "type" : {
      "type" : "string",
      "title" : "Resource type",
      "description" : "Type of the resources."
    }
  }
}
```

```
}
```

--user

Resource set resource provider is responsible for managing Resource Sets belonging to a user. Available operations are update, query, read, revoke all action.

1.142. ResourceTypes

1.142.1. Realm Operations

The Resource Types resource is responsible for managing resource types, which define a template for the resources that Managing Policies policies apply to, and the actions associated with those resources. Available operations are Query, Read, Create, Update, Delete

Resource path: `/resourcetypes`

Resource version: `1.0`

1.142.1.1. create

Create new resource type

Usage:

```
am> create ResourceTypes --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Resource Types Resource schema",
  "type" : "object",
  "title" : "Resource Types Resource schema",
  "properties" : {
    "uuid" : {
      "title" : "UUID",
      "description" : "Unique identifier of the record",
      "type" : "string"
    },
    "name" : {
      "title" : "Name",
```

```

    "description" : "Resource type name",
    "type" : "string"
  },
  "description" : {
    "title" : "Description",
    "description" : "Resource type description",
    "type" : "string"
  },
  "patterns" : {
    "title" : "Patterns",
    "description" : "Resource type patterns",
    "type" : "array",
    "items" : {
      "type" : "string"
    }
  },
  "actions" : {
    "title" : "Actions",
    "description" : "Resource type actions",
    "type" : "object",
    "additionalProperties" : {
      "type" : "boolean"
    }
  },
  "createdBy" : {
    "title" : "Created by",
    "description" : "A string containing the universal identifier DN of the subject created the resource type",
    "type" : "string"
  },
  "creationDate" : {
    "title" : "Creation date",
    "description" : "An integer containing the creation date and time, in ISO 8601 format",
    "type" : "number"
  },
  "lastModifiedBy" : {
    "title" : "Last modifier",
    "description" : "A string containing the universal identifier DN of the subject that most recently updated the resource type. If the resource type has not been modified since it was created, this property will have the same value as createdBy",
    "type" : "string"
  },
  "lastModifiedDate" : {
    "title" : "Last modification date",
    "description" : "A string containing the last modified date and time, in ISO 8601 format. If the resource typ has not been modified since it was created, this property will have the same value as creationDate",
    "type" : "number"
  }
}
}

```

1.142.1.2. delete

Delete resource type

Usage:


```
am> delete ResourceTypes --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.142.1.3. query

Query the collection of resource types

Usage:

```
am> query ResourceTypes --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.142.1.4. read

Read from the resource types collection by unique identifier

Usage:

```
am> read ResourceTypes --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.142.1.5. update

Update an existing resource type

Usage:

```
am> update ResourceTypes --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema": "http://json-schema.org/draft-04/schema#",
  "description": "Resource Types Resource schema",
  "type": "object",
  "title": "Resource Types Resource schema",
  "properties": {
    "uuid": {
      "title": "UUID",
      "description": "Unique identifier of the record",
      "type": "string"
    },
    "name": {
      "title": "Name",
      "description": "Resource type name",
      "type": "string"
    },
    "description": {
      "title": "Description",
      "description": "Resource type description",
      "type": "string"
    },
    "patterns": {
      "title": "Patterns",
      "description": "Resource type patterns",
      "type": "array",
      "items": {
        "type": "string"
      }
    },
    "actions": {
      "title": "Actions",
      "description": "Resource type actions",
      "type": "object",
      "additionalProperties": {
        "type": "boolean"
      }
    },
    "createdBy": {
      "title": "Created by",
      "description": "A string containing the universal identifier DN of the subject created the resource type",
      "type": "string"
    },
    "creationDate": {
      "title": "Creation date",
      "description": "An integer containing the creation date and time, in ISO 8601 format",
      "type": "number"
    },
    "lastModifiedBy": {
      "title": "Last modifier",
      "description": "A string containing the universal identifier DN of the subject that most recently updated the resource type. If the resource type has not been modified since it was created, this property will have the same value as createdBy",
      "type": "string"
    }
  },
}
```

```
"lastModifiedDate" : {  
  "title" : "Last modification date",  
  "description" : "A string containing the last modified date and time, in ISO 8601 format. If the  
  resource typ has not been modified since it was created, this property will have the same value as  
  creationDate",  
  "type" : "number"  
}  
}  
}
```

1.143. RestApis

1.143.1. Global Operations

Resource path: `/global-config/services/rest`

Resource version: `1.0`

1.143.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RestApis --global --actionName getAllTypes
```

1.143.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RestApis --global --actionName getCreatableTypes
```

1.143.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RestApis --global --actionName nextdescendents
```

1.143.1.4. read

Usage:

```
am> read RestApis --global
```

1.143.1.5. update

Usage:

```
am> update RestApis --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "warningHeader" : {
      "title" : "Warning Header",
      "description" : "Whether to include a warning header in the response to a request which fails to include the <code>Accept-API-Version</code> header.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "descriptionsState" : {
      "title" : "API Descriptions",
      "description" : "Whether API Explorer and API Docs are enabled in OpenAM and how the documentation for them is generated. Dynamic generation includes descriptions from any custom services and authentication modules you may have added. Static generation only includes services and authentication modules that were present when OpenAM was built. Note that dynamic documentation generation may not work in some application containers.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "defaultProtocolVersion" : {
      "title" : "Default Protocol Version",
      "description" : "The API protocol version to use when a REST request does not specify an explicit version. Choose from:<br><br><ul><li><code>Oldest</code>. If an explicit version is not specified, the oldest protocol version is used.</li><li><code>Latest</code>. If an explicit version is not specified, the latest protocol version is used.</li><li><code>None</code>. If an explicit version is not specified, the request will not be handled and an error status is returned.</li></ul>",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "csrfFilterEnabled" : {
      "title" : "Enable CSRF Protection",
      "description" : "If enabled, all non-read/query requests will require the X-Requested-With header to be present.<br><br>Requiring a non-standard header ensures requests can only be made via
```

```
methods (XHR) that have stricter same-origin policy protections in Web browsers, preventing Cross-
Site Request Forgery (CSRF) attacks. Without this filter, cross-origin requests are prevented by the
use of the application/json Content-Type header, which is less robust.",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"defaultVersion" : {
  "title" : "Default Resource Version",
  "description" : "The API resource version to use when the REST request does not specify an
explicit version. Choose from:<br><br><ul><li><code>Latest</code>. If an explicit version is not
specified, the latest resource version of an API is used.</li><li><code>Oldest</code>. If an explicit
version is not specified, the oldest supported resource version of an API is used. Note that since
APIs may be deprecated and fall out of support, the oldest <i>supported</i> version may not be the
first version.</li><li><code>None</code>. If an explicit version is not specified, the request will
not be handled and an error status is returned.</li></ul>",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
}
```

1.144. RetryLimitDecision

1.144.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/RetryLimitDecisionNode`

Resource version: `1.0`

1.144.1.1. create

Usage:

```
am> create RetryLimitDecision --realm Realm --id id --body body
```

Parameters:

`--id`

The unique identifier for the resource.

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "retryLimit" : {
      "title" : "Retry Limit",
      "description" : "The number of times to allow a retry",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "retryLimit" ]
}
```

1.144.1.2. delete

Usage:

```
am> delete RetryLimitDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.144.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action RetryLimitDecision --realm Realm --actionName getAllTypes
```

1.144.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action RetryLimitDecision --realm Realm --actionName getCreatableTypes
```

1.144.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action RetryLimitDecision --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.144.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action RetryLimitDecision --realm Realm --actionName nextdescendents
```

1.144.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query RetryLimitDecision --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.144.1.8. read

Usage:

```
am> read RetryLimitDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.144.1.9. update

Usage:

```
am> update RetryLimitDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "retryLimit" : {
      "title" : "Retry Limit",
      "description" : "The number of times to allow a retry",
      "propertyOrder" : 100,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "required" : [ "retryLimit" ]
}
```

1.145. SOAPSecurityTokenServices

1.145.1. Realm Operations

The SOAP STS endpoint is responsible for storing the configuration of instances of REST Security Token Services (STS). Available operations are create, read, update, delete, query, schema and template.

Resource path: [/realm-config/services/sts/soap-sts](#)

Resource version: [1.0](#)

1.145.1.1. create

Usage:

```
am> create SOAPSecurityTokenServices --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "soapStsSaml2" : {
      "type" : "object",
      "title" : "SAML2 Token",
      "propertyOrder" : 3,
      "properties" : {
        "saml2-sp-entity-id" : {
          "title" : "Service Provider Entity Id",
          "description" : "Values will be used to populate the Audiences of the AudienceRestriction element of the Conditions element. This value is required when issuing Bearer assertions. See section 4.1.4.2 of Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0 for details.",
          "propertyOrder" : 2400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "saml2-encryption-algorithm" : {
          "title" : "Encryption Algorithm",
          "description" : "Algorithm used to encrypt generated assertions.",
          "propertyOrder" : 4000,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "saml2-encrypt-nameid" : {
          "title" : "Encrypt NameID",
          "description" : "Check this box if the assertion NameID should be encrypted. If this box is checked, the Encrypt Assertion box cannot be checked.",
          "propertyOrder" : 3900,
          "required" : false,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "saml2-encrypt-assertion" : {
          "title" : "Encrypt Assertion",
          "description" : "Check this box if the entire assertion should be encrypted. If this box is checked, the Encrypt NameID and Encrypt Attributes boxes cannot be checked.",
          "propertyOrder" : 3700,
          "required" : false,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "saml2-token-lifetime-seconds" : {
          "title" : "Token Lifetime (Seconds)",
          "description" : "",
          "propertyOrder" : 2700,
          "required" : false,
          "type" : "integer",
          "exampleValue" : ""
        },
        "saml2-attribute-map" : {
          "title" : "Attribute Mappings",
```

```

    "description" : "Contains the mapping of assertion attribute names (Map
keys) to local OpenAM attributes (Map values) in configured data stores.<br>Format:
<code>assertion_attr_name=ldap_attr_name</code><br><br>The DefaultAttributeMapper looks at
profile attributes in configured data stores, or in Session properties. The keys will define
the name of the attributes included in the Assertion Attribute statements, and the data
pulled from the subject's directory entry or session state corresponding to the map value
will define the value corresponding to this attribute name. The keys can have the format
<code>[NameFormatURI]|SAML ATTRIBUTE NAME.</code> If the attribute value is enclosed in quotes,
that quoted value will be included in the attribute without mapping. Binary attributes should
be followed by ';binary'.<br>Examples: <ul><li>EmailAddress=mail</li><li>Address=postaladdress</
li><li>urn:oasis:names:tc:SAML:2.0:attrname-format:uri|urn:mace:dir:attribute-def:cn=cn</
li><li>partnerID=\\\"staticPartnerIDValue\\\"</li><li>urn:oasis:names:tc:SAML:2.0:attrname-format:uri|
nameID=\\\"staticNameIDValue\\\"</li><li>photo=photo;binary</li><li>urn:oasis:names:tc:SAML:2.0:attrname-
format:uri|photo=photo;binary</li></ul>",
    "propertyOrder" : 3500,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "saml2-sign-assertion" : {
    "title" : "Sign Assertion",
    "description" : "",
    "propertyOrder" : 3600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saml2-custom-subject-provider-class-name" : {
    "title" : "Custom Subject Provider Class Name ",
    "description" : "If the Subject of the issued SAML2 assertion needs to be customized,
implement the org.forgerock.openam.sts.tokengeneration.saml2.statements.SubjectProvider interface,
and specify the class name of the implementation here.",
    "propertyOrder" : 2900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-custom-conditions-provider-class-name" : {
    "title" : "Custom Conditions Provider Class Name ",
    "description" : "If the Conditions of the issued SAML2 assertion need to be customized,
implement the org.forgerock.openam.sts.tokengeneration.saml2.statements.ConditionsProvider interface,
and specify the class name of the implementation here.",
    "propertyOrder" : 2800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-keystore-filename" : {
    "title" : "KeystorePath",
    "description" : "Path to keystore<br><br>Provide either the full filesystem path to a
filesystem resident keystore, or a classpath-relative path to a keystore bundled in the OpenAM .war
file. This keystore contains the IdP public/private keys and SP public key for signed and/or
encrypted assertions. If assertions are neither signed nor encrypted, these values need not be
specified.",

```

```

    "propertyOrder" : 4100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-signature-key-alias" : {
    "title" : "Signature Key Alias",
    "description" : "Corresponds to the private key of the IdP. Will be used to sign assertions.
Value can remain unspecified unless assertions are signed.",
    "propertyOrder" : 4500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-signature-key-password" : {
    "title" : "Signature Key Password",
    "description" : "",
    "propertyOrder" : 4600,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "saml2-custom-attribute-mapper-class-name" : {
    "title" : "Custom Attribute Mapper Class Name",
    "description" : "If the class implementing attribute mapping for attributes
contained in the issued SAML2 assertion needs to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AttributeMapper</code> interface, and
specify the class name of the implementation here.",
    "propertyOrder" : 3300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-custom-authn-context-mapper-class-name" : {
    "title" : "Custom Authentication Context Class Name",
    "description" : "If the AuthnContext mapping implemented by the
<code>org.forgerock.openam.sts.soap.token.provider.saml2.DefaultSaml2XmlTokenAuthnContextMapper</code>
class needs to be customized, implement the
<code>org.forgerock.openam.sts.soap.token.provider.saml2.Saml2XmlTokenAuthnContextMapper</code>
interface, and specify the name of the implementation here.",
    "propertyOrder" : 3400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-encryption-key-alias" : {
    "title" : "Encryption Key Alias",
    "description" : "This alias corresponds to the SP's x509 Certificate identified by the SP
Entity ID for this rest-sts instance. Not necessary unless assertions are to be encrypted.",
    "propertyOrder" : 4400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "issuer-name" : {
    "title" : "SAML2 issuer Id",
    "description" : "",
    "propertyOrder" : 2300,

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-custom-authz-decision-statements-provider-class-name" : {
    "title" : "Custom Authorization Decision Statements Class Name",
    "description" : "If the AuthorizationDecisionStatements
of the issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AuthzDecisionStatementsProvider</
code> interface, and specify the class name of the implementation here.",
    "propertyOrder" : 3200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-sp-accs-url" : {
    "title" : "Service Provider Assertion Consumer Service Url",
    "description" : "When issuing bearer assertions, the recipient attribute of the
SubjectConfirmation element must be set to the Service Provider Assertion Consumer Service Url. See
section 4.1.4.2 of Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0 for details.
Value required when issuing Bearer assertions.",
    "propertyOrder" : 2500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-encrypt-attributes" : {
    "title" : "Encrypt Attributes",
    "description" : "Check this box if the assertion Attributes should be encrypted. If this box
is checked, the Encrypt Assertion box cannot be checked.",
    "propertyOrder" : 3800,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saml2-name-id-format" : {
    "title" : "NameIdFormat",
    "description" : "",
    "propertyOrder" : 2600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-custom-authentication-statements-provider-class-name" : {
    "title" : "Custom AuthenticationStatements Class Name",
    "description" : "If the AuthenticationStatements of
the issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AuthenticationStatementsProvider</
code> interface, and specify the class name of the implementation here.",
    "propertyOrder" : 3000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-custom-attribute-statements-provider-class-name" : {
    "title" : "Custom AttributeStatements Class Name",
    "description" : "If the AttributeStatements of the
issued SAML2 assertion need to be customized, implement the

```

```

<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AttributeStatementsProvider</code>
interface, and specify the class name of the implementation here.",
    "propertyOrder" : 3100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-keystore-password" : {
    "title" : "Keystore Password",
    "description" : "",
    "propertyOrder" : 4200,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }
}
},
"soapStsOidc" : {
  "type" : "object",
  "title" : "OpenID Connect Token ",
  "propertyOrder" : 4,
  "properties" : {
    "oidc-client-secret" : {
      "title" : "Client Secret",
      "description" : "For HMAC-signed tokens, the client secret used as the HMAC key<br><br>For
HMAC-signed tokens, the KeyStore location, password, signature key alias and password configurations
are not required.",
      "propertyOrder" : 5700,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "oidc-custom-authn-context-mapper-class" : {
      "title" : "Custom Authn Context Mapper Class",
      "description" : "If issued OIDC tokens are to contain acr claims, implement the
<code>org.forgerock.openam.sts.rest.token.provider.oidc.OpenIdConnectTokenAuthnContextMapper</code>
interface, and specify the class name of the implementation here.",
      "propertyOrder" : 6300,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "oidc-signature-algorithm" : {
    "title" : "Token Signature Algorithm",
    "description" : "Algorithm used to sign issued OIDC tokens",
    "propertyOrder" : 4900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "oidc-custom-claim-mapper-class" : {
    "title" : "Custom Claim Mapper Class",
    "description" : "",
    "propertyOrder" : 6200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}

```

```

},
"oidc-keystore-password" : {
  "title" : "KeyStore Password",
  "description" : "",
  "propertyOrder" : 5200,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"oidc-authorized-party" : {
  "title" : "Authorized Party ",
  "description" : "Optional. Will be set in the azp claim",
  "propertyOrder" : 6000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"oidc-signature-key-alias" : {
  "title" : "KeyStore Signing Key Alias",
  "description" : "For RSA-signed tokens, corresponds to the private key of the OIDC OP. Will
be used to sign assertions.",
  "propertyOrder" : 5400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"oidc-public-key-reference-type" : {
  "title" : "Public Key Reference Type",
  "description" : "For tokens signed with RSA, how should corresponding public key be
referenced in the issued jwt",
  "propertyOrder" : 5000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"oidc-custom-authn-method-references-mapper-class" : {
  "title" : "Custom Authn Methods References Mapper Class",
  "description" : "If issued OIDC tokens are to contain amr claims, implement the
<code>org.forgerock.openam.sts.rest.token.provider.oidc.OpenIdConnectTokenAuthMethodReferencesMapper</
code> interface, and specify the class name of the implementation here.",
  "propertyOrder" : 6400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"oidc-claim-map" : {
  "title" : "Claim Map",
  "description" : "Contains the mapping of OIDC token claim names (Map keys) to local
OpenAM attributes (Map values) in configured data stores. Format: <code>claim_name=attribute_name</
code><br><br>The keys in the map will be claim entries in the issued OIDC token, and the value of
these claims will be the principal attribute state resulting from LDAP datastore lookup of the map
values. If no values are returned from the LDAP datastore lookup of the attribute corresponding to
the map value, no claim will be set in the issued OIDC token.",
  "propertyOrder" : 6100,
  "required" : false,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  }
}

```

```

    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"oidc-issuer" : {
  "title" : "OpenID Connect Token Provider ID",
  "description" : "",
  "propertyOrder" : 4700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"oidc-signature-key-password" : {
  "title" : "Signature Key Password",
  "description" : "",
  "propertyOrder" : 5500,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"oidc-audience" : {
  "title" : "Issued Tokens Audience",
  "description" : "Contents will be set in the aud claim",
  "propertyOrder" : 5900,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"oidc-keystore-location" : {
  "title" : "KeyStore Location",
  "description" : "For RSA-signed tokens, the filesystem or classpath location of the KeyStore
containing signing key entry<br><br>For RSA-signed tokens, the KeyStore location, password, signing-
key alias, and signing key password must be specified. The client secret is not required for RSA-
signed tokens.",
  "propertyOrder" : 5100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"oidc-token-lifetime-seconds" : {
  "title" : "Token Lifetime (Seconds)",
  "description" : "",
  "propertyOrder" : 4800,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
}
}
},
"soapStsSoap" : {
  "type" : "object",
  "title" : "Soap Keystore",
  "propertyOrder" : 2,
  "properties" : {

```

```

"soap-encryption-key-alias" : {
  "title" : "Decryption Key Alias",
  "description" : "Alias of key used by the STS to decrypt client messages in the asymmetric
binding, and to decrypt the client-generated symmetric key in the symmetric binding. Corresponds to
an STS PrivateKeyEntry.",
  "propertyOrder" : 2000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"soap-signature-key-password" : {
  "title" : "Signature Key Password",
  "description" : "",
  "propertyOrder" : 1800,
  "required" : false,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"soap-keystore-filename" : {
  "title" : "Soap Keystore Location",
  "description" : "The location of the keystore which contains the key state necessary for the
CXF and WSS4j runtime to enforce the SecurityPolicy bindings associated with this STS instance.",
  "propertyOrder" : 1400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"soap-keystore-password" : {
  "title" : "Keystore Password",
  "description" : "",
  "propertyOrder" : 1500,
  "required" : false,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"soap-encryption-key-password" : {
  "title" : "Decryption Key Password",
  "description" : "",
  "propertyOrder" : 2100,
  "required" : false,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"soap-signature-key-alias" : {
  "title" : "Signature Key Alias",
  "description" : "Alias of key used to sign messages from STS. Necessary for asymmetric
binding.",
  "propertyOrder" : 1700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"soapStsDeployment" : {
  "type" : "object",

```



```

"title" : "Deployment",
"propertyOrder" : 1,
"properties" : {
  "deployment-custom-wsdl-location" : {
    "title" : "Custom wsdl File",
    "description" : "The location (on soap-sts .war accessible filesystem or soap-sts .war
classpath) of the custom wsdl file.<br><br>If the signing and/or encryption of the request and/or
response messages specified in the SecurityPolicy bindings of standard soap-sts wsdl files must
be customized, specify the name of the customized wsdl file here. See documentation for additional
details.",
    "propertyOrder" : 800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "deployment-wsdl-location" : {
    "title" : "Wsdl File Referencing Security Policy Binding Selection",
    "description" : "Choose the SupportingToken type and corresponding SecurityPolicy binding
which will protect your sts instance. This choice will determine the SecurityPolicy bindings in
the wsdl file defining the WS-Trust API<br><br>Note that the SupportingToken type selected must
correspond to the Security Policy Validated Token selection. Note if a custom wsdl file is chose, the
user is responsible for providing a properly formatted wsdl file. See documentation for details.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "deployment-am-url" : {
    "title" : "OpenAM URL",
    "description" : "Set to URL of the OpenAM instance or site deployment.<br><br>The OpenAM
deployment will be consulted for published soap-sts instances, and to authenticate and issue
tokens.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "deployment-auth-target-mappings" : {
    "title" : "Authentication Target Mappings",
    "description" : "Configuration of consumption of OpenAM's rest-authN<br><br>Each deployed
STS is configured with the authentication targets for each input token type for each supported
token transformation. For example, if the transformation OPENIDCONNECT->SAML2 is supported, the
STS instance must be configured with information specifying which elements of the OpenAM restful
authentication context needs to be consumed to validate the OPENIDCONNECT token. The elements
of the configuration tuple are separated by '|'. <br><br>The first element is the input token type
in the token transform: i.e. X509, OPENIDCONNECT, USERNAME, or OPENAM. The second element is the
authentication target - i.e. either 'module' or 'service', and the third element is the name of
the authentication module or service. The fourth (optional) element provides the STS authentication
context information about the to-be-consumed authentication context. <br><br>When transforming OpenID
Connect Id tokens, the OpenID Connect authentication module must be consumed, and thus a deployed
rest-sts instance must be configured with the name of the header/cookie element where the OpenID
Connect Id token will be placed. For this example, the following string would define these
configurations: <code>OPENIDCONNECT|module|oidc|oidc_id_token_auth_target_header_key=oidc_id_token</
code>. In this case, 'oidc' is the name of the OpenID Connect authentication module created to
authenticate OpenID Connect tokens. <br><br>When transforming a X509 Certificate, the Certificate
module must be consumed, and the published rest-sts instance must be configured with the name of
the Certificate module (or the service containing the module), and the header name configured for
the Certificate module corresponding to where the Certificate module can expect to find the to-be-
validated Certificate. The following string would define these configurations: <code>X509|module|

```

```

cert_module|x509_token_auth_target_header_key=client_cert</code>. In this case 'cert_module' is the
name of the Certificate module, and client_cert is the header name where Certificate module has been
configured to find the client's Certificate.",
    "propertyOrder" : 500,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"deployment-custom-service-name" : {
    "title" : "Custom Service QName",
    "description" : "The name attribute of the wsdl:Service element referenced in the
Custom wsdl File, in QName format.<br><br>Example: <code>{http://docs.oasis-open.org/ws-sx/ws-
trust/200512/}service_name</code>",
    "propertyOrder" : 900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
},
"delegation-custom-token-handlers" : {
    "title" : "Custom Delegation Handlers ",
    "description" : "If delegation relationships are supported, the
class names soap-sts .war file classpath resident implementations of the
<code>org.apache.cxf.sts.token.delegation.TokenDelegationHandler</code> interface can be specified
here.<br><br>Custom TokenDelegationHandler implementations will be invoked to validate the
potentially custom token element included in the ActAs/OnBehalfOf element in the RequestSecurityToken
invocation. Note that a TokenDelegationHandler does not need to be supplied to validate username or
OpenAM session tokens. The validation of these tokens are supported out-of-the-box by selecting them
in the Delegated Token Types list.",
    "propertyOrder" : 1300,
    "required" : false,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"deployment-custom-service-port" : {
    "title" : "Custom Port QName",
    "description" : "The name attribute of the wsdl:Port element referenced in the
Custom wsdl File, in QName format.<br><br>Example: <code>{http://docs.oasis-open.org/ws-sx/ws-
trust/200512/}service_port_name</code>",
    "propertyOrder" : 1000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
},
"delegation-validated-token-types" : {
    "title" : "Delegated Token Types",
    "description" : "If delegation relationships are supported, out-of-the-box validation
support for the validation of username and OpenAM session tokens included as the ActAs/OnBehalfOf
element is configured here. If delegation relationships are supported, out-of-the-box validation
support for the validation of username and OpenAM session tokens included as the ActAs/OnBehalfOf
element is configured here.<br><br>If a value is selected in this list, then no Custom Delegation
Handlers must be specified. The true/false value indicates whether the interim OpenAM session,
created as part of delegated token validation, should be invalidated following token creation.",
    "propertyOrder" : 1200,

```

```

        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "delegation-relationship-supported" : {
        "title" : "Delegation Relationships Supported",
        "description" : "Check if the RST will include ActAs/OnBehalfOf token elements<br><br>If SAML2 assertions with SenderVouches SubjectConfirmation are to be issued, this box must be checked.",
        "propertyOrder" : 1100,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"soapStsGeneral" : {
    "type" : "object",
    "title" : "General",
    "propertyOrder" : 0,
    "properties" : {
        "issued-token-types" : {
            "title" : "Issued Tokens",
            "description" : "Determines which tokens this soap STS instance will issue",
            "propertyOrder" : 200,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "security-policy-validated-token-config" : {
            "title" : "Security Policy Validated Token",
            "description" : "Determines the SupportingToken type in the WS-SecurityPolicy bindings in the soap STS' wsdl, and whether the interim OpenAM session resulting from successful SupportingToken validation, should be invalidated following token issue.",
            "propertyOrder" : 300,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "persist-issued-tokens-in-cts" : {
            "title" : "Persist Issued Tokens in Core Token Store",
            "description" : "Necessary to support token validation and cancellation<br><br>Validation of STS-issued tokens will involve determining whether the token has been issued, has not expired, and has not been cancelled. Token cancellation involves removing the record of this token from the CTS. Thus CTS persistence of STS-issued tokens is required to support these features.",
            "propertyOrder" : 100,
            "required" : false,
            "type" : "boolean",
            "exampleValue" : ""
        }
    }
}
}

```

```
}  
}  
}
```

1.145.1.2. delete

Usage:

```
am> delete SOAPSecurityTokenServices --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.145.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SOAPSecurityTokenServices --realm Realm --actionName getAllTypes
```

1.145.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SOAPSecurityTokenServices --realm Realm --actionName getCreatableTypes
```

1.145.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SOAPSecurityTokenServices --realm Realm --actionName nextdescendents
```

1.145.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SOAPSecurityTokenServices --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.145.1.7. read

Usage:

```
am> read SOAPSecurityTokenServices --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.145.1.8. update

Usage:

```
am> update SOAPSecurityTokenServices --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "soapStsSaml2" : {
      "type" : "object",
      "title" : "SAML2 Token",
      "propertyOrder" : 3,
      "properties" : {
        "saml2-sp-entity-id" : {
          "title" : "Service Provider Entity Id",
          "description" : "Values will be used to populate the Audiences of the AudienceRestriction element of the Conditions element. This value is required when issuing Bearer assertions. See section 4.1.4.2 of Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0 for details.",
          "propertyOrder" : 2400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "saml2-encryption-algorithm" : {
          "title" : "Encryption Algorithm",
          "description" : "Algorithm used to encrypt generated assertions.",
          "propertyOrder" : 4000,

```

```

    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-encrypt-nameid" : {
    "title" : "Encrypt NameID",
    "description" : "Check this box if the assertion NameID should be encrypted. If this box is
checked, the Encrypt Assertion box cannot be checked.",
    "propertyOrder" : 3900,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saml2-encrypt-assertion" : {
    "title" : "Encrypt Assertion",
    "description" : "Check this box if the entire assertion should be encrypted. If this box is
checked, the Encrypt NameID and Encrypt Attributes boxes cannot be checked.",
    "propertyOrder" : 3700,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saml2-token-lifetime-seconds" : {
    "title" : "Token Lifetime (Seconds)",
    "description" : "",
    "propertyOrder" : 2700,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "saml2-attribute-map" : {
    "title" : "Attribute Mappings",
    "description" : "Contains the mapping of assertion attribute names (Map
keys) to local OpenAM attributes (Map values) in configured data stores.<br>Format:
<code>assertion_attr_name=ldap_attr_name</code><br><br>The DefaultAttributeMapper looks at
profile attributes in configured data stores, or in Session properties. The keys will define
the name of the attributes included in the Assertion Attribute statements, and the data
pulled from the subject's directory entry or session state corresponding to the map value
will define the value corresponding to this attribute name. The keys can have the format
<code>[NameFormatURI]SAML ATTRIBUTE NAME.</code> If the attribute value is enclosed in quotes,
that quoted value will be included in the attribute without mapping. Binary attributes should
be followed by '<code>binary'</code>.<br>Examples: <ul><li>EmailAddress=mail</li><li>Address=postaladdress</
li><li>urn:oasis:names:tc:SAML:2.0:attrname-format:uri|urn:mace:dir:attribute-def:cn=cn</
li><li>partnerID=\"staticPartnerIDValue\"</li><li>urn:oasis:names:tc:SAML:2.0:attrname-format:uri|
nameID=\"staticNameIDValue\"</li><li>photo=photo;binary</li><li>urn:oasis:names:tc:SAML:2.0:attrname-
format:uri|photo=photo;binary</li></ul>",
    "propertyOrder" : 3500,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "saml2-sign-assertion" : {
    "title" : "Sign Assertion",
    "description" : "",

```

```

    "propertyOrder" : 3600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saml2-custom-subject-provider-class-name" : {
    "title" : "Custom Subject Provider Class Name ",
    "description" : "If the Subject of the issued SAML2 assertion needs to be customized,
implement the org.forgerock.openam.sts.tokengeneration.saml2.statements.SubjectProvider interface,
and specify the class name of the implementation here.",
    "propertyOrder" : 2900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-custom-conditions-provider-class-name" : {
    "title" : "Custom Conditions Provider Class Name ",
    "description" : "If the Conditions of the issued SAML2 assertion need to be customized,
implement the org.forgerock.openam.sts.tokengeneration.saml2.statements.ConditionsProvider interface,
and specify the class name of the implementation here.",
    "propertyOrder" : 2800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-keystore-filename" : {
    "title" : "KeystorePath",
    "description" : "Path to keystore<br><br>Provide either the full filesystem path to a
filesystem resident keystore, or a classpath-relative path to a keystore bundled in the OpenAM .war
file. This keystore contains the IdP public/private keys and SP public key for signed and/or
encrypted assertions. If assertions are neither signed nor encrypted, these values need not be
specified.",
    "propertyOrder" : 4100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-signature-key-alias" : {
    "title" : "Signature Key Alias",
    "description" : "Corresponds to the private key of the IdP. Will be used to sign assertions.
Value can remain unspecified unless assertions are signed.",
    "propertyOrder" : 4500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saml2-signature-key-password" : {
    "title" : "Signature Key Password",
    "description" : "",
    "propertyOrder" : 4600,
    "required" : false,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "saml2-custom-attribute-mapper-class-name" : {
    "title" : "Custom Attribute Mapper Class Name",
    "description" : "If the class implementing attribute mapping for attributes
contained in the issued SAML2 assertion needs to be customized, implement the

```

```

<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AttributeMapper</code> interface, and
specify the class name of the implementation here.",
  "propertyOrder" : 3300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"saml2-custom-authn-context-mapper-class-name" : {
  "title" : "Custom Authentication Context Class Name",
  "description" : "If the AuthnContext mapping implemented by the
<code>org.forgerock.openam.sts.soap.token.provider.saml2.DefaultSaml2XmlTokenAuthnContextMapper</code>
class needs to be customized, implement the
<code>org.forgerock.openam.sts.soap.token.provider.saml2.Saml2XmlTokenAuthnContextMapper</code>
interface, and specify the name of the implementation here.",
  "propertyOrder" : 3400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"saml2-encryption-key-alias" : {
  "title" : "Encryption Key Alias",
  "description" : "This alias corresponds to the SP's x509 Certificate identified by the SP
Entity ID for this rest-sts instance. Not necessary unless assertions are to be encrypted.",
  "propertyOrder" : 4400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"issuer-name" : {
  "title" : "SAML2 issuer Id",
  "description" : "",
  "propertyOrder" : 2300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"saml2-custom-authz-decision-statements-provider-class-name" : {
  "title" : "Custom Authorization Decision Statements Class Name",
  "description" : "If the AuthorizationDecisionStatements
of the issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AuthzDecisionStatementsProvider</code>
interface, and specify the class name of the implementation here.",
  "propertyOrder" : 3200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"saml2-sp-acis-url" : {
  "title" : "Service Provider Assertion Consumer Service Url",
  "description" : "When issuing bearer assertions, the recipient attribute of the
SubjectConfirmation element must be set to the Service Provider Assertion Consumer Service Url. See
section 4.1.4.2 of Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0 for details.
Value required when issuing Bearer assertions.",
  "propertyOrder" : 2500,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"saml2-encrypt-attributes" : {

```



```

        "title" : "Encrypt Attributes",
        "description" : "Check this box if the assertion Attributes should be encrypted. If this box
is checked, the Encrypt Assertion box cannot be checked.",
        "propertyOrder" : 3800,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "saml2-name-id-format" : {
        "title" : "NameIdFormat",
        "description" : "",
        "propertyOrder" : 2600,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-custom-authentication-statements-provider-class-name" : {
        "title" : "Custom AuthenticationStatements Class Name",
        "description" : "If the AuthenticationStatements of
the issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AuthenticationStatementsProvider</
code> interface, and specify the class name of the implementation here.",
        "propertyOrder" : 3000,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-custom-attribute-statements-provider-class-name" : {
        "title" : "Custom AttributeStatements Class Name",
        "description" : "If the AttributeStatements of the
issued SAML2 assertion need to be customized, implement the
<code>org.forgerock.openam.sts.tokengeneration.saml2.statements.AttributeStatementsProvider</code>
interface, and specify the class name of the implementation here.",
        "propertyOrder" : 3100,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "saml2-keystore-password" : {
        "title" : "Keystore Password",
        "description" : "",
        "propertyOrder" : 4200,
        "required" : false,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    }
}
},
"soapStsOidc" : {
    "type" : "object",
    "title" : "OpenID Connect Token ",
    "propertyOrder" : 4,
    "properties" : {
        "oidc-client-secret" : {
            "title" : "Client Secret",
            "description" : "For HMAC-signed tokens, the client secret used as the HMAC key<br><br>For
HMAC-signed tokens, the KeyStore location, password, signature key alias and password configurations
are not required."
        }
    }
}

```

```
"propertyOrder" : 5700,
"required" : true,
"type" : "string",
"format" : "password",
"exampleValue" : ""
},
"oidc-custom-authn-context-mapper-class" : {
"title" : "Custom Authn Context Mapper Class",
"description" : "If issued OIDC tokens are to contain acr claims, implement the
<code>org.forgerock.openam.sts.rest.token.provider.oidc.OpenIdConnectTokenAuthnContextMapper</code>
interface, and specify the class name of the implementation here.",
"propertyOrder" : 6300,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"oidc-signature-algorithm" : {
"title" : "Token Signature Algorithm",
"description" : "Algorithm used to sign issued OIDC tokens",
"propertyOrder" : 4900,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"oidc-custom-claim-mapper-class" : {
"title" : "Custom Claim Mapper Class",
"description" : "",
"propertyOrder" : 6200,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"oidc-keystore-password" : {
"title" : "KeyStore Password",
"description" : "",
"propertyOrder" : 5200,
"required" : true,
"type" : "string",
"format" : "password",
"exampleValue" : ""
},
"oidc-authorized-party" : {
"title" : "Authorized Party ",
"description" : "Optional. Will be set in the azp claim",
"propertyOrder" : 6000,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"oidc-signature-key-alias" : {
"title" : "KeyStore Signing Key Alias",
"description" : "For RSA-signed tokens, corresponds to the private key of the OIDC OP. Will
be used to sign assertions.",
"propertyOrder" : 5400,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"oidc-public-key-reference-type" : {
```

```

    "title" : "Public Key Reference Type",
    "description" : "For tokens signed with RSA, how should corresponding public key be
referenced in the issued jwt",
    "propertyOrder" : 5000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "oidc-custom-authn-method-references-mapper-class" : {
    "title" : "Custom Authn Methods References Mapper Class",
    "description" : "If issued OIDC tokens are to contain amr claims, implement the
<code>org.forgerock.openam.sts.rest.token.provider.oidc.OpenIdConnectTokenAuthMethodReferencesMapper</
code> interface, and specify the class name of the implementation here.",
    "propertyOrder" : 6400,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "oidc-claim-map" : {
    "title" : "Claim Map",
    "description" : "Contains the mapping of OIDC token claim names (Map keys) to local
OpenAM attributes (Map values) in configured data stores. Format: <code>claim_name=attribute_name</
code><br><br>The keys in the map will be claim entries in the issued OIDC token, and the value of
these claims will be the principal attribute state resulting from LDAP datastore lookup of the map
values. If no values are returned from the LDAP datastore lookup of the attribute corresponding to
the map value, no claim will be set in the issued OIDC token.",
    "propertyOrder" : 6100,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "oidc-issuer" : {
    "title" : "OpenID Connect Token Provider ID",
    "description" : "",
    "propertyOrder" : 4700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "oidc-signature-key-password" : {
    "title" : "Signature Key Password",
    "description" : "",
    "propertyOrder" : 5500,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "oidc-audience" : {
    "title" : "Issued Tokens Audience",
    "description" : "Contents will be set in the aud claim",
    "propertyOrder" : 5900,
    "required" : true,
    "items" : {

```

```

        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"oidc-keystore-location" : {
    "title" : "KeyStore Location",
    "description" : "For RSA-signed tokens, the filesystem or classpath location of the KeyStore
containing signing key entry<br><br>For RSA-signed tokens, the KeyStore location, password, signing-
key alias, and signing key password must be specified. The client secret is not required for RSA-
signed tokens.",
    "propertyOrder" : 5100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"oidc-token-lifetime-seconds" : {
    "title" : "Token Lifetime (Seconds)",
    "description" : "",
    "propertyOrder" : 4800,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
}
}
},
"soapStsSoap" : {
    "type" : "object",
    "title" : "Soap Keystore",
    "propertyOrder" : 2,
    "properties" : {
        "soap-encryption-key-alias" : {
            "title" : "Decryption Key Alias",
            "description" : "Alias of key used by the STS to decrypt client messages in the asymmetric
binding, and to decrypt the client-generated symmetric key in the symmetric binding. Corresponds to
an STS PrivateKeyEntry.",
            "propertyOrder" : 2000,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "soap-signature-key-password" : {
            "title" : "Signature Key Password",
            "description" : "",
            "propertyOrder" : 1800,
            "required" : false,
            "type" : "string",
            "format" : "password",
            "exampleValue" : ""
        },
        "soap-keystore-filename" : {
            "title" : "Soap Keystore Location",
            "description" : "The location of the keystore which contains the key state necessary for the
CXF and WSS4j runtime to enforce the SecurityPolicy bindings associated with this STS instance.",
            "propertyOrder" : 1400,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        }
    }
},

```

```

"soap-keystore-password" : {
  "title" : "Keystore Password",
  "description" : "",
  "propertyOrder" : 1500,
  "required" : false,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"soap-encryption-key-password" : {
  "title" : "Decryption Key Password",
  "description" : "",
  "propertyOrder" : 2100,
  "required" : false,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"soap-signature-key-alias" : {
  "title" : "Signature Key Alias",
  "description" : "Alias of key used to sign messages from STS. Necessary for asymmetric
binding.",
  "propertyOrder" : 1700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"soapStsDeployment" : {
  "type" : "object",
  "title" : "Deployment",
  "propertyOrder" : 1,
  "properties" : {
    "deployment-custom-wsdl-location" : {
      "title" : "Custom wsdl File",
      "description" : "The location (on soap-sts .war accessible filesystem or soap-sts .war
classpath) of the custom wsdl file.<br><br>If the signing and/or encryption of the request and/or
response messages specified in the SecurityPolicy bindings of standard soap-sts wsdl files must
be customized, specify the name of the customized wsdl file here. See documentation for additional
details.",
      "propertyOrder" : 800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "deployment-wsdl-location" : {
      "title" : "Wsdl File Referencing Security Policy Binding Selection",
      "description" : "Choose the SupportingToken type and corresponding SecurityPolicy binding
which will protect your sts instance. This choice will determine the SecurityPolicy bindings in
the wsdl file defining the WS-Trust API<br><br>Note that the SupportingToken type selected must
correspond to the Security Policy Validated Token selection. Note if a custom wsdl file is chose, the
user is responsible for providing a properly formatted wsdl file. See documentation for details.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "deployment-am-url" : {

```

```

        "title" : "OpenAM URL",
        "description" : "Set to URL of the OpenAM instance or site deployment.<br><br>The OpenAM
deployment will be consulted for published soap-sts instances, and to authenticate and issue
tokens.",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "deployment-auth-target-mappings" : {
        "title" : "Authentication Target Mappings",
        "description" : "Configuration of consumption of OpenAM's rest-authN<br><br>Each deployed
STS is configured with the authentication targets for each input token type for each supported
token transformation. For example, if the transformation OPENIDCONNECT->SAML2 is supported, the
STS instance must be configured with information specifying which elements of the OpenAM restful
authentication context needs to be consumed to validate the OPENIDCONNECT token. The elements
of the configuration tuple are separated by '|'. <br>The first element is the input token type
in the token transform: i.e. X509, OPENIDCONNECT, USERNAME, or OPENAM. The second element is the
authentication target - i.e. either 'module' or 'service', and the third element is the name of
the authentication module or service. The fourth (optional) element provides the STS authentication
context information about the to-be-consumed authentication context. <br>When transforming OpenID
Connect Id tokens, the OpenID Connect authentication module must be consumed, and thus a deployed
rest-sts instance must be configured with the name of the header/cookie element where the OpenID
Connect Id token will be placed. For this example, the following string would define these
configurations: <code>OPENIDCONNECT|module|oidc|oidc_id_token_auth_target_header_key=oidc_id_token</
code>. In this case, 'oidc' is the name of the OpenID Connect authentication module created to
authenticate OpenID Connect tokens. <br>When transforming a X509 Certificate, the Certificate
module must be consumed, and the published rest-sts instance must be configured with the name of
the Certificate module (or the service containing the module), and the header name configured for
the Certificate module corresponding to where the Certificate module can expect to find the to-be-
validated Certificate. The following string would define these configurations: <code>X509|module|
cert_module|x509_token_auth_target_header_key=client_cert</code>. In this case 'cert_module' is the
name of the Certificate module, and client_cert is the header name where Certificate module has been
configured to find the client's Certificate.",
        "propertyOrder" : 500,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "deployment-custom-service-name" : {
        "title" : "Custom Service QName",
        "description" : "The name attribute of the wsdl:Service element referenced in the
Custom wsdl File, in QName format.<br><br>Example: <code>{http://docs.oasis-open.org/ws-sx/ws-
trust/200512/}service_name</code>",
        "propertyOrder" : 900,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "delegation-custom-token-handlers" : {
        "title" : "Custom Delegation Handlers ",
        "description" : "If delegation relationships are supported, the
class names soap-sts .war file classpath resident implementations of the
<code>org.apache.cxf.sts.token.delegation.TokenDelegationHandler</code> interface can be specified
here.<br><br>Custom TokenDelegationHandler implementations will be invoked to validate the
potentially custom token element included in the ActAs/OnBehalfOf element in the RequestSecurityToken
    
```

```

invocation. Note that a TokenDelegationHandler does not need to be supplied to validate username or
OpenAM session tokens. The validation of these tokens are supported out-of-the-box by selecting them
in the Delegated Token Types list.",
  "propertyOrder" : 1300,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"deployment-custom-service-port" : {
  "title" : "Custom Port QName",
  "description" : "The name attribute of the wsdl:Port element referenced in the
Custom wsdl File, in QName format.<br><br>Example: <code>{http://docs.oasis-open.org/ws-sx/ws-
trust/200512/}service_port_name</code>",
  "propertyOrder" : 1000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"delegation-validated-token-types" : {
  "title" : "Delegated Token Types",
  "description" : "If delegation relationships are supported, out-of-the-box validation
support for the validation of username and OpenAM session tokens included as the ActAs/OnBehalfOf
element is configured here. If delegation relationships are supported, out-of-the-box validation
support for the validation of username and OpenAM session tokens included as the ActAs/OnBehalfOf
element is configured here.<br><br>If a value is selected in this list, then no Custom Delegation
Handlers must be specified. The true/false value indicates whether the interim OpenAM session,
created as part of delegated token validation, should be invalidated following token creation.",
  "propertyOrder" : 1200,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"delegation-relationship-supported" : {
  "title" : "Delegation Relationships Supported",
  "description" : "Check if the RST will include ActAs/OnBehalfOf token elements<br><br>If
SAML2 assertions with SenderVouches SubjectConfirmation are to be issued, this box must be checked.",
  "propertyOrder" : 1100,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
}
}
},
"soapStsGeneral" : {
  "type" : "object",
  "title" : "General",
  "propertyOrder" : 0,
  "properties" : {
    "issued-token-types" : {
      "title" : "Issued Tokens",
      "description" : "Determines which tokens this soap STS instance will issue",
      "propertyOrder" : 200,
      "required" : true,

```

```

    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "security-policy-validated-token-config" : {
    "title" : "Security Policy Validated Token",
    "description" : "Determines the SupportingToken type in the WS-SecurityPolicy bindings in the soap STS' wsdl, and whether the interim OpenAM session resulting from successful SupportingToken validation, should be invalidated following token issue.",
    "propertyOrder" : 300,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "persist-issued-tokens-in-cts" : {
    "title" : "Persist Issued Tokens in Core Token Store",
    "description" : "Necessary to support token validation and cancellation<br><br>Validation of STS-issued tokens will involve determining whether the token has been issued, has not expired, and has not been cancelled. Token cancellation involves removing the record of this token from the CTS. Thus CTS persistence of STS-issued tokens is required to support these features.",
    "propertyOrder" : 100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
}
}
}
}

```

1.146. SaeModule

1.146.1. Realm Operations

Resource path: `/realm-config/authentication/modules/sae`

Resource version: `1.0`

1.146.1.1. create

Usage:

```
am> create SaeModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.146.1.2. delete

Usage:

```
am> delete SaeModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.146.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SaeModule --realm Realm --actionName getAllTypes
```

1.146.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SaeModule --realm Realm --actionName getCreatableTypes
```

1.146.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SaeModule --realm Realm --actionName nextdescendents
```

1.146.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SaeModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.146.1.7. read

Usage:

```
am> read SaeModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.146.1.8. update

Usage:

```
am> update SaeModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.146.2. Global Operations

Resource path: `/global-config/authentication/modules/sae`

Resource version: `1.0`

1.146.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SaeModule --global --actionName getAllTypes
```

1.146.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SaeModule --global --actionName getCreatableTypes
```

1.146.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SaeModule --global --actionName nextdescendents
```

1.146.2.4. read

Usage:

```
am> read SaeModule --global
```

1.146.2.5. update

Usage:

```
am> update SaeModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        }
      },
      "type" : "object",
      "title" : "Realm Defaults"
    }
  }
}
```

1.147. Saml2Entity

1.147.1. Realm Operations

Resource path: `/realm-config/federation/entityproviders/saml2`

Resource version: `1.0`

1.147.1.1. create

Usage:

```
am> create Saml2Entity --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "metadata" : {
      "title" : "Metadata",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "entityConfig" : {
      "title" : "Entity Configuration",
      "description" : "",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.147.1.2. delete

Usage:

```
am> delete Saml2Entity --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.147.1.3. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Saml2Entity --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.147.1.4. read

Usage:

```
am> read Saml2Entity --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.147.1.5. update

Usage:

```
am> update Saml2Entity --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "metadata" : {
      "title" : "Metadata",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "entityConfig" : {
      "title" : "Entity Configuration",
      "description" : "",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.148. Saml2Module

1.148.1. Realm Operations

Resource path: `/realm-config/authentication/modules/authSaml`

Resource version: `1.0`

1.148.1.1. create

Usage:

```
am> create Saml2Module --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authnContextDeclRef" : {
      "title" : "Authentication Context Declaration Reference",
```

```

    "description" : "(Optional) Use this parameter to specify authentication context declaration
references. Separate multiple values with pipe characters (|).",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "reqBinding" : {
    "title" : "Request Binding",
    "description" : "Use this parameter to indicate what binding the SP should use when
communicating with the IdP.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sloEnabled" : {
    "title" : "Single Logout Enabled",
    "description" : "Enable to attempt logout of the user's
IdP session at the point of session logout. Required the
<pre>org.forgerock.openam.authentication.modules.saml2.SAML2PostAuthenticationPlugin</pre> to be
active on the chain that includes this SAML2 module.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "entityName" : {
    "title" : "IdP Entity ID",
    "description" : "The entity name of the SAML2 IdP Service to use for this module (must be
configured).",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "metaAlias" : {
    "title" : "SP MetaAlias",
    "description" : "MetaAlias for Service Provider. The format of this parameter is <pre>/
realm_name/SP</pre>",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "isPassive" : {
    "title" : "Passive Authentication",
    "description" : "Use this parameter to indicate whether the identity provider should
authenticate passively (true) or not (false).",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "forceAuthn" : {
    "title" : "Force IdP Authentication",
    "description" : "Use this parameter to indicate whether the identity provider should force
authentication (true) or can reuse existing security contexts (false).",
    "propertyOrder" : 1100,

```



```
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"authComparison" : {
  "title" : "Comparison Type",
  "description" : "(Optional) Use this parameter to specify a comparison method to evaluate the
requested context classes or statements. OpenAM accepts the following values: <pre>better</pre>,
<pre>exact</pre>, <pre>maximum</pre>, and <pre>minimum</pre>.",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"nameIdFormat" : {
  "title" : "NameID Format",
  "description" : "(Optional) Use this parameter to specify a SAML Name
Identifier format identifier such as <pre>urn:oasis:names:tc:SAML:2.0:nameid-
format:persistent</pre> <pre>urn:oasis:names:tc:SAML:2.0:nameid-format:transient</pre>
<pre>urn:oasis:names:tc:SAML:2.0:nameid-format:unspecified</pre>",
  "propertyOrder" : 1300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"binding" : {
  "title" : "Response Binding",
  "description" : "Use this parameter to indicate what binding the IdP should use when
communicating with this SP.",
  "propertyOrder" : 1000,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"allowCreate" : {
  "title" : "Allow IdP to Create NameID",
  "description" : "Use this parameter to indicate whether the identity provider can create a new
identifier for the principal if none exists (true) or not (false).",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"loginChain" : {
  "title" : "Linking Authentication Chain",
  "description" : "The authentication chain that will be executed when a user is required to be
authenticated locally to match their user account with that of a remotely authenticated assertion.",
  "propertyOrder" : 500,
  "required" : true,
```

```
    "type" : "string",
    "exampleValue" : ""
  },
  "sloRelay" : {
    "title" : "Single Logout URL",
    "description" : "If Single Logout is enabled, this is the URL to which the user should be
forwarded after successful IdP logout. This must be a fully-qualified URL (start with http...), or
the redirect will not function.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authnContextClassRef" : {
    "title" : "Authentication Context Class Reference",
    "description" : "(Optional) Use this parameter to specify authentication context class
references. Separate multiple values with pipe characters (|).",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.148.1.2. delete

Usage:

```
am> delete Saml2Module --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.148.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Saml2Module --realm Realm --actionName getAllTypes
```

1.148.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Saml2Module --realm Realm --actionName getCreatableTypes
```

1.148.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Saml2Module --realm Realm --actionName nextdescendents
```

1.148.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Saml2Module --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.148.1.7. read

Usage:

```
am> read Saml2Module --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.148.1.8. update

Usage:

```
am> update Saml2Module --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "authContextDeclRef" : {
      "title" : "Authentication Context Declaration Reference",
      "description" : "(Optional) Use this parameter to specify authentication context declaration
references. Separate multiple values with pipe characters (|).",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "reqBinding" : {
      "title" : "Request Binding",
      "description" : "Use this parameter to indicate what binding the SP should use when
communicating with the IdP.",
      "propertyOrder" : 900,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sloEnabled" : {
      "title" : "Single Logout Enabled",
      "description" : "Enable to attempt logout of the user's
IdP session at the point of session logout. Required the
<pre>org.forgerock.openam.authentication.modules.saml2.SAML2PostAuthenticationPlugin</pre> to be
active on the chain that includes this SAML2 module.",
      "propertyOrder" : 1400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "entityName" : {
      "title" : "IdP Entity ID",
      "description" : "The entity name of the SAML2 IdP Service to use for this module (must be
configured).",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "metaAlias" : {
      "title" : "SP MetaAlias",
      "description" : "MetaAlias for Service Provider. The format of this parameter is <pre>/
realm_name/SP</pre>",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "isPassive" : {
      "title" : "Passive Authentication",
      "description" : "Use this parameter to indicate whether the identity provider should
authenticate passively (true) or not (false).",
      "propertyOrder" : 1200,

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "forceAuthn" : {
    "title" : "Force IdP Authentication",
    "description" : "Use this parameter to indicate whether the identity provider should force authentication (true) or can reuse existing security contexts (false).",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authComparison" : {
    "title" : "Comparison Type",
    "description" : "(Optional) Use this parameter to specify a comparison method to evaluate the requested context classes or statements. OpenAM accepts the following values: <pre>better</pre>, <pre>exact</pre>, <pre>maximum</pre>, and <pre>minimum</pre>.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "nameIdFormat" : {
    "title" : "NameID Format",
    "description" : "(Optional) Use this parameter to specify a SAML Name Identifier format identifier such as <pre>urn:oasis:names:tc:SAML:2.0:nameid-format:persistent</pre> <pre>urn:oasis:names:tc:SAML:2.0:nameid-format:transient</pre> <pre>urn:oasis:names:tc:SAML:2.0:nameid-format:unspecified</pre>",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "binding" : {
    "title" : "Response Binding",
    "description" : "Use this parameter to indicate what binding the IdP should use when communicating with this SP.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "allowCreate" : {
    "title" : "Allow IdP to Create NameID",
    "description" : "Use this parameter to indicate whether the identity provider can create a new identifier for the principal if none exists (true) or not (false).",
    "propertyOrder" : 400,
    "required" : true,

```

```
    "type" : "string",
    "exampleValue" : ""
  },
  "loginChain" : {
    "title" : "Linking Authentication Chain",
    "description" : "The authentication chain that will be executed when a user is required to be
authenticated locally to match their user account with that of a remotely authenticated assertion.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sloRelay" : {
    "title" : "Single Logout URL",
    "description" : "If Single Logout is enabled, this is the URL to which the user should be
forwarded after successful IdP logout. This must be a fully-qualified URL (start with http...), or
the redirect will not function.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authnContextClassRef" : {
    "title" : "Authentication Context Class Reference",
    "description" : "(Optional) Use this parameter to specify authentication context class
references. Separate multiple values with pipe characters (|).",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.148.2. Global Operations

Resource path: [/global-config/authentication/modules/authSaml](#)

Resource version: [1.0](#)

1.148.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Saml2Module --global --actionName getAllTypes
```

1.148.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Saml2Module --global --actionName getCreatableTypes
```

1.148.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Saml2Module --global --actionName nextdescendents
```

1.148.2.4. read

Usage:

```
am> read Saml2Module --global
```

1.148.2.5. update

Usage:

```
am> update Saml2Module --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "sloRelay" : {
          "title" : "Single Logout URL",
          "description" : "If Single Logout is enabled, this is the URL to which the user should be forwarded after successful IdP logout. This must be a fully-qualified URL (start with http...), or the redirect will not function.",
          "propertyOrder" : 1500,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "allowCreate" : {
          "title" : "Allow IdP to Create NameID",
          "description" : "Use this parameter to indicate whether the identity provider can create a new identifier for the principal if none exists (true) or not (false).",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      },
      "isPassive" : {
```

```

    "title" : "Passive Authentication",
    "description" : "Use this parameter to indicate whether the identity provider should
authenticate passively (true) or not (false).",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "metaAlias" : {
    "title" : "SP MetaAlias",
    "description" : "MetaAlias for Service Provider. The format of this parameter is <pre>/
realm_name/SP</pre>",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authnContextClassRef" : {
    "title" : "Authentication Context Class Reference",
    "description" : "(Optional) Use this parameter to specify authentication context class
references. Separate multiple values with pipe characters (|).",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authnContextDeclRef" : {
    "title" : "Authentication Context Declaration Reference",
    "description" : "(Optional) Use this parameter to specify authentication context declaration
references. Separate multiple values with pipe characters (|).",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "entityName" : {
    "title" : "IdP Entity ID",
    "description" : "The entity name of the SAML2 IdP Service to use for this module (must be
configured).",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "forceAuthn" : {
    "title" : "Force IdP Authentication",
    "description" : "Use this parameter to indicate whether the identity provider should force
authentication (true) or can reuse existing security contexts (false).",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 100,

```



```

    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "reqBinding" : {
    "title" : "Request Binding",
    "description" : "Use this parameter to indicate what binding the SP should use when
communicating with the IdP.",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sloEnabled" : {
    "title" : "Single Logout Enabled",
    "description" : "Enable to attempt logout of the
user's IdP session at the point of session logout. Required the
<pre>org.forgerock.openam.authentication.modules.saml2.SAML2PostAuthenticationPlugin</pre> to be
active on the chain that includes this SAML2 module.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authComparison" : {
    "title" : "Comparison Type",
    "description" : "(Optional) Use this parameter to specify a comparison method to evaluate
the requested context classes or statements. OpenAM accepts the following values: <pre>better</pre>,
<pre>exact</pre>, <pre>maximum</pre>, and <pre>minimum</pre>.",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "loginChain" : {
    "title" : "Linking Authentication Chain",
    "description" : "The authentication chain that will be executed when a user is required
to be authenticated locally to match their user account with that of a remotely authenticated
assertion.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "binding" : {
    "title" : "Response Binding",
    "description" : "Use this parameter to indicate what binding the IdP should use when
communicating with this SP.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "nameIdFormat" : {
    "title" : "NameID Format",
    "description" : "(Optional) Use this parameter to specify a SAML Name
Identifier format identifier such as <pre>urn:oasis:names:tc:SAML:2.0:nameid-
format:persistent</pre> <pre>urn:oasis:names:tc:SAML:2.0:nameid-format:transient</pre>
<pre>urn:oasis:names:tc:SAML:2.0:nameid-format:unspecified</pre>",

```

```
    "propertyOrder" : 1300,  
    "required" : true,  
    "type" : "string",  
    "exampleValue" : ""  
  }  
},  
"type" : "object",  
"title" : "Realm Defaults"  
}  
}
```

1.149. SamlV2ServiceConfiguration

1.149.1. Realm Operations

Resource path: `/realm-config/services/saml2`

Resource version: `1.0`

1.149.1.1. create

Usage:

```
am> create SamlV2ServiceConfiguration --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "metadataSigningKeyPass" : {
      "title" : "Metadata signing key password",
      "description" : "Specify the password used to retrieve the signing key from the keystore.",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "metadataSigningKey" : {
      "title" : "Metadata signing key alias",
      "description" : "Specify the private key alias to be used to sign the given entity's metadata when requesting signed metadata, either by using exportmetadata.jsp or the <code>ssoadm</code> command.",
      "propertyOrder" : 1400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.149.1.2. delete

Usage:

```
am> delete SamlV2ServiceConfiguration --realm Realm
```

1.149.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SamlV2ServiceConfiguration --realm Realm --actionName getAllTypes
```

1.149.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SamlV2ServiceConfiguration --realm Realm --actionName getCreatableTypes
```

1.149.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SamlV2ServiceConfiguration --realm Realm --actionName nextdescendents
```

1.149.1.6. read

Usage:

```
am> read SamlV2ServiceConfiguration --realm Realm
```

1.149.1.7. update

Usage:

```
am> update SamlV2ServiceConfiguration --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "metadataSigningKeyPass" : {
      "title" : "Metadata signing key password",
      "description" : "Specify the password used to retrieve the signing key from the keystore.",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "metadataSigningKey" : {
      "title" : "Metadata signing key alias",
      "description" : "Specify the private key alias to be used to sign the given entity's metadata when requesting signed metadata, either by using exportmetadata.jsp or the <code>ssoadm</code> command.",
      "propertyOrder" : 1400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.149.2. Global Operations

Resource path: [/global-config/services/saml2](#)

Resource version: [1.0](#)

1.149.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SamlV2ServiceConfiguration --global --actionName getAllTypes
```

1.149.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SamlV2ServiceConfiguration --global --actionName getCreatableTypes
```

1.149.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SamlV2ServiceConfiguration --global --actionName nextdescendents
```

1.149.2.4. read

Usage:

```
am> read SamlV2ServiceConfiguration --global
```

1.149.2.5. update

Usage:

```
am> update SamlV2ServiceConfiguration --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "idpDiscoveryCookieDomain" : {
      "title" : "Cookie domain for IdP Discovery Service",
      "description" : "Specifies the cookie domain for the IDP discovery service.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```
},
"xmlSigningClass" : {
  "title" : "XML Signing SPI implementation class",
  "description" : "Used by the SAML2 engine to <em>sign</em> documents.",
  "propertyOrder" : 900,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"idpDiscoveryUrlSchema" : {
  "title" : "URL scheme for IdP Discovery Service",
  "description" : "Specifies the URL scheme to use.",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"failOverEnabled" : {
  "title" : "Enable SAML v2.0 failover",
  "description" : "If enabled, OpenAM can failover SAML v2.0 requests to another instance.",
  "propertyOrder" : 1200,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"bufferLength" : {
  "title" : "Buffer length (in bytes) to decompress request",
  "description" : "Specify the size of the buffer used for decompressing requests, in bytes.",
  "propertyOrder" : 1300,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"nameIDInfoKeyAttribute" : {
  "title" : "Attribute name for Name ID information key",
  "description" : "User entry attribute to store the name identifier key.",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"cacheCleanupInterval" : {
  "title" : "Cache cleanup interval (in seconds)",
  "description" : "Time between cache cleanup operations, in seconds.",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"idpDiscoveryCookieType" : {
  "title" : "Cookie type for IdP Discovery Service",
  "description" : "Specifies the cookie type to use.",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"signingCertValidation" : {
  "title" : "XML Signing Certificate Validation",
```

```

        "description" : "If enabled, then validate certificates used to sign documents.",
        "propertyOrder" : 1000,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "encryptedKeyInKeyInfo" : {
        "title" : "Include xenc:EncryptedKey inside ds:KeyInfo Element",
        "description" : "Specify whether to include the <code>xenc:EncryptedKey</code> property inside
the <code>ds:KeyInfo</code> element.",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "nameIDInfoAttribute" : {
        "title" : "Attribute name for Name ID information",
        "description" : "User entry attribute to store name identifier information.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "caCertValidation" : {
        "title" : "CA Certificate Validation",
        "description" : "If enabled, then validate CA certificates.",
        "propertyOrder" : 1100,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "xmlEncryptionClass" : {
        "title" : "XML Encryption SPI implementation class",
        "description" : "Used by the SAML2 engine to <em>encrypt</em> and <em>decrypt</em> documents.",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "defaults" : {
        "properties" : {
            "metadataSigningKey" : {
                "title" : "Metadata signing key alias",
                "description" : "Specify the private key alias to be used to sign the given entity's
metadata when requesting signed metadata, either by using exportmetadata.jsp or the <code>ssoadm</
code> command.",
                "propertyOrder" : 1400,
                "required" : true,
                "type" : "string",
                "exampleValue" : ""
            },
            "metadataSigningKeyPass" : {
                "title" : "Metadata signing key password",
                "description" : "Specify the password used to retrieve the signing key from the keystore.",
                "propertyOrder" : 1500,
                "required" : true,
                "type" : "string",
                "format" : "password",
                "exampleValue" : ""
            }
        }
    }
}

```

```
    }  
  },  
  "type" : "object",  
  "title" : "Realm Defaults"  
} }  
}
```

1.150. SamlV2SoapBinding

1.150.1. Global Operations

Resource path: `/global-config/services/federation/saml2soapbinding`

Resource version: `1.0`

1.150.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SamlV2SoapBinding --global --actionName getAllTypes
```

1.150.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SamlV2SoapBinding --global --actionName getCreatableTypes
```

1.150.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SamlV2SoapBinding --global --actionName nextdescendents
```

1.150.1.4. read

Usage:

```
am> read SamlV2SoapBinding --global
```


1.150.1.5. update

Usage:

```
am> update SamlV2SoapBinding --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "requestHandlers" : {
      "title" : "Request Handler List",
      "description" : "List of handlers to deal with SAML v2.0 requests bound to SOAP. <p><p>The
      required format is: <code>key=<em>Meta Alias</em>|class=<em>Handler Class</em></code> <p><p>Set
      the <em>key</em> property for a request handler to the meta alias, and the <em>class</em>
      property to the name of the class that implements the handler.<p><p> For example: <code>key=/pdp|
      class=com.sun.identity.xacml.plugins.XACMLAuthzDecisionQueryHandler</code>",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.151. ScriptStore

1.151.1. Realm Operations

Resource path: `/realm-config/services/scripts`

Resource version: `1.0`

1.151.1.1. create

Usage:

```
am> create ScriptStore --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "createdBy" : {
      "title" : "Created by",
      "description" : "A string containing the universal identifier DN of the subject that created the script",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "context" : {
      "title" : "Script type",
      "description" : "The script type. Supported values are: POLICY_CONDITION : Policy Condition AUTHENTICATION_SERVER_SIDE : Server-side Authentication AUTHENTICATION_CLIENT_SIDE : Client-side Authentication - Note Client-side scripts must be written in JavaScript OIDC_CLAIMS : OIDC Claims",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "creationDate" : {
      "title" : "Creation date",
      "description" : "An integer containing the creation date and time, in ISO 8601 format",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "name" : {
      "title" : "Script name",
      "description" : "The name provided for the script",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "script" : {
      "title" : "Script",
      "description" : "The source code of the script. The source code is in UTF-8 format and encoded into Base64",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "lastModifiedDate" : {
```

```

    "title" : "Last modification date",
    "description" : "A string containing the last modified date and time, in ISO 8601 format. If
the script has not been modified since it was created, this property will have the same value as
creationDate",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "lastModifiedBy" : {
    "title" : "Last modifier",
    "description" : "A string containing the universal identifier DN of the subject that most
recently updated the script. If the script has not been modified since it was created, this property
will have the same value as createdBy",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "language" : {
    "title" : "Script language",
    "description" : "The language the script is written in - JAVASCRIPT or GROOVY",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "description" : {
    "title" : "Script description",
    "description" : "An optional text string to help identify the script",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}

```

1.151.1.2. delete

Usage:

```
am> delete ScriptStore --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.151.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ScriptStore --realm Realm --actionName getAllTypes
```

1.151.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ScriptStore --realm Realm --actionName getCreatableTypes
```

1.151.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ScriptStore --realm Realm --actionName nextdescendents
```

1.151.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ScriptStore --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.151.1.7. read

Usage:

```
am> read ScriptStore --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.151.1.8. update

Usage:

```
am> update ScriptStore --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "createdBy" : {
      "title" : "Created by",
      "description" : "A string containing the universal identifier DN of the subject that created the
script",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "context" : {
      "title" : "Script type",
      "description" : "The script type. Supported values are: POLICY_CONDITION : Policy Condition
AUTHENTICATION_SERVER_SIDE : Server-side Authentication AUTHENTICATION_CLIENT_SIDE : Client-side
Authentication - Note Client-side scripts must be written in JavaScript OIDC_CLAIMS : OIDC Claims",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "creationDate" : {
      "title" : "Creation date",
      "description" : "An integer containing the creation date and time, in ISO 8601 format",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "name" : {
      "title" : "Script name",
      "description" : "The name provided for the script",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "script" : {
      "title" : "Script",
      "description" : "The source code of the script. The source code is in UTF-8 format and encoded
into Base64",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```
    },
    "lastModifiedDate" : {
      "title" : "Last modification date",
      "description" : "A string containing the last modified date and time, in ISO 8601 format. If
the script has not been modified since it was created, this property will have the same value as
creationDate",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "lastModifiedBy" : {
      "title" : "Last modifier",
      "description" : "A string containing the universal identifier DN of the subject that most
recently updated the script. If the script has not been modified since it was created, this property
will have the same value as createdBy",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "language" : {
      "title" : "Script language",
      "description" : "The language the script is written in - JAVASCRIPT or GROOVY",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "description" : {
      "title" : "Script description",
      "description" : "An optional text string to help identify the script",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.152. ScriptTypes

1.152.1. Global Operations

Resource path: </global-config/services/scripting/contexts>

Resource version: 1.0

1.152.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ScriptTypes --global --actionName getAllTypes
```

1.152.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ScriptTypes --global --actionName getCreatableTypes
```

1.152.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ScriptTypes --global --actionName nextdescendents
```

1.152.1.4. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ScriptTypes --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.152.1.5. read

Usage:

```
am> read ScriptTypes --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.152.1.6. update

Usage:

```
am> update ScriptTypes --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaultScript" : {
      "title" : "Default Script",
      "description" : "The source code that is presented as the default when creating a new script of
this type.",
      "propertyOrder" : 1200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "languages" : {
      "title" : "Scripting languages",
      "description" : "The language the script is written in.<br><br>This is used to determine how to
validate the script, as well as which engine to run the script within.",
      "propertyOrder" : 1100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.153. ScriptedDecision

1.153.1. Realm Operations

Resource path: </realm-config/authentication/authenticationtrees/nodes/ScriptedDecisionNode>

Resource version: 1.0

1.153.1.1. create

Usage:


```
am> create ScriptedDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "outcomes" : {
      "title" : "Outcomes",
      "description" : "",
      "propertyOrder" : 200,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "script" : {
      "title" : "Script",
      "description" : "The script to evaluate.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "script", "outcomes" ]
}
```

1.153.1.2. delete

Usage:

```
am> delete ScriptedDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.153.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ScriptedDecision --realm Realm --actionName getAllTypes
```

1.153.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ScriptedDecision --realm Realm --actionName getCreatableTypes
```

1.153.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action ScriptedDecision --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.153.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ScriptedDecision --realm Realm --actionName nextdescendents
```

1.153.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ScriptedDecision --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.153.1.8. read

Usage:

```
am> read ScriptedDecision --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.153.1.9. update

Usage:

```
am> update ScriptedDecision --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "outcomes" : {
      "title" : "Outcomes",
      "description" : "",
      "propertyOrder" : 200,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "script" : {
      "title" : "Script",
      "description" : "The script to evaluate.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "script", "outcomes" ]
}
```

1.154. ScriptedModule

1.154.1. Realm Operations

Resource path: `/realm-config/authentication/modules/scripted`

Resource version: `1.0`

1.154.1.1. create

Usage:

```
am> create ScriptedModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with the authentication module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "clientScript" : {
      "title" : "Client-side Script",
      "description" : "The client-side script.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "clientScriptEnabled" : {
      "title" : "Client-side Script Enabled",
      "description" : "Enable this setting if the client-side script should be executed.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",

```

```
    "exampleValue" : ""
  },
  "serverScript" : {
    "title" : "Server-side Script",
    "description" : "The server-side script to execute.<br><br>This script will be run on the
server, subsequent to any client script having returned.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
```

1.154.1.2. delete

Usage:

```
am> delete ScriptedModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.154.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ScriptedModule --realm Realm --actionName getAllTypes
```

1.154.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ScriptedModule --realm Realm --actionName getCreatableTypes
```

1.154.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ScriptedModule --realm Realm --actionName nextdescendents
```

1.154.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ScriptedModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.154.1.7. read

Usage:

```
am> read ScriptedModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.154.1.8. update

Usage:

```
am> update ScriptedModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with the authentication module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 400,
      "required" : true,
    }
  }
}
```

```
    "type" : "integer",
    "exampleValue" : ""
  },
  "clientScript" : {
    "title" : "Client-side Script",
    "description" : "The client-side script.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientScriptEnabled" : {
    "title" : "Client-side Script Enabled",
    "description" : "Enable this setting if the client-side script should be executed.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "serverScript" : {
    "title" : "Server-side Script",
    "description" : "The server-side script to execute.<br><br>This script will be run on the
server, subsequent to any client script having returned.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.154.2. Global Operations

Resource path: `/global-config/authentication/modules/scripted`

Resource version: `1.0`

1.154.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ScriptedModule --global --actionName getAllTypes
```

1.154.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ScriptedModule --global --actionName getCreatableTypes
```

1.154.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ScriptedModule --global --actionName nextdescendents
```

1.154.2.4. read

Usage:

```
am> read ScriptedModule --global
```

1.154.2.5. update

Usage:

```
am> update ScriptedModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "clientScript" : {
          "title" : "Client-side Script",
          "description" : "The client-side script.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with the authentication
module.<br><br>Each authentication module has an authentication level that can be used to indicate
the level of security associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "serverScript" : {
          "title" : "Server-side Script",
          "description" : "The server-side script to execute.<br><br>This script will be run on the
server, subsequent to any client script having returned.",

```



```
    "propertyOrder" : 300,  
    "required" : true,  
    "type" : "string",  
    "exampleValue" : ""  
  },  
  "clientScriptEnabled" : {  
    "title" : "Client-side Script Enabled",  
    "description" : "Enable this setting if the client-side script should be executed.",  
    "propertyOrder" : 100,  
    "required" : true,  
    "type" : "boolean",  
    "exampleValue" : ""  
  }  
},  
"type" : "object",  
"title" : "Realm Defaults"  
}  
}
```

1.155. Scripting

1.155.1. Global Operations

Resource path: [/global-config/services/scripting](#)

Resource version: 1.0

1.155.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Scripting --global --actionName getAllTypes
```

1.155.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Scripting --global --actionName getCreatableTypes
```

1.155.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Scripting --global --actionName nextdescendents
```

1.155.1.4. read

Usage:

```
am> read Scripting --global
```

1.155.1.5. update

Usage:

```
am> update Scripting --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaultContext" : {
      "title" : "Default Script Type",
      "description" : "The default script context type when creating a new script.",
      "propertyOrder" : 900,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.156. ScriptingEngineConfiguration

1.156.1. Global Operations

Resource path: </global-config/services/scripting/contexts/{contexts}/engineConfiguration>

Resource version: 1.0

1.156.1.1. create

Usage:

```
am> create ScriptingEngineConfiguration --global --contexts contexts --body body
```

Parameters:

--contexts

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "useSecurityManager" : {
      "title" : "Use system SecurityManager",
      "description" : "Indicates whether the system SecurityManager should also be consulted when checking access to Java classes.<br><br>If enabled, then the checkPackageAccess method will be called for each Java class accessed. If no SecurityManager is configured, then this has no effect.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "queueSize" : {
      "title" : "Thread pool queue size",
      "description" : "Size of queue to use for buffering script execution request when core pool is at capacity.<br><br>Use -1 for an unbounded queue (this disables the maximum pool size setting). For short, CPU-bound scripts, consider a small pool size and larger queue length. For I/O-bound scripts (e.g., REST calls) consider a larger maximum pool size and a smaller queue. Not hot-swappable: restart server for changes to take effect.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "idleTimeout" : {
      "title" : "Thread idle timeout (seconds)",
      "description" : "Length of time (in seconds) to wait before terminating threads.<br><br>Length of time (in seconds) to wait before terminating threads that were started when the queue reached capacity. Only applies to threads beyond the core pool size (up to the maximum size).",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "serverTimeout" : {
      "title" : "Server-side Script Timeout",
      "description" : "The maximum execution time any individual script should take on the server (in seconds).<br><br>Server-side scripts will be forcibly stopped after this amount of execution time.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "maxThreads" : {
      "title" : "Maximum thread pool size",
```

```

    "description" : "The maximum size of the thread pool from which scripts will operate.<br><br>New threads will be created up to this size once the task queue reaches capacity. Has no effect if the queue is unbounded.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "coreThreads" : {
    "title" : "Core thread pool size",
    "description" : "The core size of the thread pool from which scripts will operate.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "blackList" : {
    "title" : "Java class blacklist",
    "description" : "List of patterns of Java classes that must not be accessed by a script.<br><br>This blacklist is applied after the whitelist to apply additional restrictions. For instance you may whitelist java.lang.* and then blacklist java.lang.System and java.lang.Runtime. It is recommended to always prefer specific whitelists where possible.",
    "propertyOrder" : 700,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "whiteList" : {
    "title" : "Java class whitelist",
    "description" : "List of patterns of allowed Java classes that may be loaded/accessed by scripts.<br><br>Each Java class accessed by a script must match at least one of these patterns. Use '*' as a wildcard, e.g. <code>java.lang.*</code>",
    "propertyOrder" : 600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
}

```

1.156.1.2. delete

Usage:

```
am> delete ScriptingEngineConfiguration --global --contexts contexts
```

Parameters:

--contexts

1.156.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ScriptingEngineConfiguration --global --contexts contexts --actionName getAllTypes
```

Parameters:

--contexts

1.156.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ScriptingEngineConfiguration --global --contexts contexts --actionName getCreatableTypes
```

Parameters:

--contexts

1.156.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ScriptingEngineConfiguration --global --contexts contexts --actionName nextdescendents
```

Parameters:

--contexts

1.156.1.6. read

Usage:

```
am> read ScriptingEngineConfiguration --global --contexts contexts
```

Parameters:

--contexts

1.156.1.7. update

Usage:

```
am> update ScriptingEngineConfiguration --global --contexts contexts --body body
```

Parameters:

--contexts

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "useSecurityManager" : {
      "title" : "Use system SecurityManager",
      "description" : "Indicates whether the system SecurityManager should also be consulted when checking access to Java classes.<br><br>If enabled, then the checkPackageAccess method will be called for each Java class accessed. If no SecurityManager is configured, then this has no effect.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "queueSize" : {
      "title" : "Thread pool queue size",
      "description" : "Size of queue to use for buffering script execution request when core pool is at capacity.<br><br>Use -1 for an unbounded queue (this disables the maximum pool size setting). For short, CPU-bound scripts, consider a small pool size and larger queue length. For I/O-bound scripts (e.g., REST calls) consider a larger maximum pool size and a smaller queue. Not hot-swappable: restart server for changes to take effect.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "idleTimeout" : {
      "title" : "Thread idle timeout (seconds)",
      "description" : "Length of time (in seconds) to wait before terminating threads.<br><br>Length of time (in seconds) to wait before terminating threads that were started when the queue reached capacity. Only applies to threads beyond the core pool size (up to the maximum size).",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "serverTimeout" : {
      "title" : "Server-side Script Timeout",
      "description" : "The maximum execution time any individual script should take on the server (in seconds).<br><br>Server-side scripts will be forcibly stopped after this amount of execution time.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
}
```

```

"maxThreads" : {
  "title" : "Maximum thread pool size",
  "description" : "The maximum size of the thread pool from which scripts will operate.<br><br>New threads will be created up to this size once the task queue reaches capacity. Has no effect if the queue is unbounded.",
  "propertyOrder" : 300,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"coreThreads" : {
  "title" : "Core thread pool size",
  "description" : "The core size of the thread pool from which scripts will operate.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"blackList" : {
  "title" : "Java class blacklist",
  "description" : "List of patterns of Java classes that must not be accessed by a script.<br><br>This blacklist is applied after the whitelist to apply additional restrictions. For instance you may whitelist java.lang.* and then blacklist java.lang.System and java.lang.Runtime. It is recommended to always prefer specific whitelists where possible.",
  "propertyOrder" : 700,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"whiteList" : {
  "title" : "Java class whitelist",
  "description" : "List of patterns of allowed Java classes that may be loaded/accessed by scripts.<br><br>Each Java class accessed by a script must match at least one of these patterns. Use '*' as a wildcard, e.g. <code>java.lang.*</code>",
  "propertyOrder" : 600,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
}
}

```

1.157. Scripts

1.157.1. Realm Operations

The script resources service is responsible for managing scripts used for client-side and server-side scripted authentication, custom policy conditions, and handling OpenID Connect claims. Scripts

are represented in JSON and take the following form. Scripts are built from standard JSON objects and values (strings, numbers, objects, sets, arrays, true, false, and null). Each script has a system-generated universally unique identifier (UUID), which must be used when modifying existing scripts. Renaming a script will not affect the UUID

Resource path: `/scripts`

Resource version: `1.1`

1.157.1.1. create

Create a script in a realm. The value for script must be in UTF-8 format and then encoded into Base64.

Usage:

```
am> create Scripts --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description": "Script resource endpoint json schema",
  "type": "object",
  "title": "Script resource schema",
  "properties": {
    "_id": {
      "title": "Script unique ID",
      "description": "A unique ID for a script configuration, provided by the server",
      "type": "string"
    },
    "name": {
      "title": "Script name",
      "description": "The name provided for the script",
      "type": "string"
    },
    "description": {
      "title": "Script description",
      "description": "An optional text string to help identify the script",
      "type": "string"
    },
    "script": {
      "title": "Script",
      "description": "The source code of the script. The source code is in UTF-8 format and encoded into Base64",
      "type": "string"
    }
  }
}
```



```

},
"language" : {
  "title" : "Script language",
  "description" : "The language the script is written in - JAVASCRIPT or GROOVY",
  "type" : "string"
},
"context" : {
  "title" : "Script type",
  "description" : "The script type. Supported values are: POLICY_CONDITION : Policy Condition
AUTHENTICATION_SERVER_SIDE : Server-side Authentication AUTHENTICATION_CLIENT_SIDE : Client-side
Authentication - Note Client-side scripts must be written in JavaScript OIDC_CLAIMS : OIDC Claims",
  "type" : "string"
},
"createdBy" : {
  "title" : "Created by",
  "description" : "A string containing the universal identifier DN of the subject that created the
script",
  "type" : "string"
},
"creationDate" : {
  "title" : "Creation date",
  "description" : "An integer containing the creation date and time, in ISO 8601 format",
  "type" : "number"
},
"lastModifiedBy" : {
  "title" : "Last modifier",
  "description" : "A string containing the universal identifier DN of the subject that most
recently updated the script. If the script has not been modified since it was created, this property
will have the same value as createdBy",
  "type" : "string"
},
"lastModifiedDate" : {
  "title" : "Last modification date",
  "description" : "A string containing the last modified date and time, in ISO 8601 format. If
the script has not been modified since it was created, this property will have the same value as
creationDate",
  "type" : "number"
}
},
"required" : [ "name", "description", "script", "language", "context" ]
}

```

1.157.1.2. delete

Delete an individual script in a realm specified by the UUID parameter

Usage:

```
am> delete Scripts --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.157.1.3. query

List all the scripts in a realm, as well as any global scripts

Usage:

```
am> query Scripts --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.157.1.4. read

Read an individual script in a realm by specifying the UUID parameter

Usage:

```
am> read Scripts --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.157.1.5. update

Update an individual script in a realm specified by the UUID parameter

Usage:

```
am> update Scripts --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "Script resource endpoint json schema",
  "type" : "object",
  "title" : "Script resource schema",
  "properties" : {
    "_id" : {
      "title" : "Script unique ID",
      "description" : "A unique ID for a script configuration, provided by the server",
      "type" : "string"
    }
  }
}
```

```

    },
    "name" : {
        "title" : "Script name",
        "description" : "The name provided for the script",
        "type" : "string"
    },
    "description" : {
        "title" : "Script description",
        "description" : "An optional text string to help identify the script",
        "type" : "string"
    },
    "script" : {
        "title" : "Script",
        "description" : "The source code of the script. The source code is in UTF-8 format and encoded
into Base64",
        "type" : "string"
    },
    "language" : {
        "title" : "Script language",
        "description" : "The language the script is written in - JAVASCRIPT or GROOVY",
        "type" : "string"
    },
    "context" : {
        "title" : "Script type",
        "description" : "The script type. Supported values are: POLICY_CONDITION : Policy Condition
AUTHENTICATION_SERVER_SIDE : Server-side Authentication AUTHENTICATION_CLIENT_SIDE : Client-side
Authentication - Note Client-side scripts must be written in JavaScript OIDC_CLAIMS : OIDC Claims",
        "type" : "string"
    },
    "createdBy" : {
        "title" : "Created by",
        "description" : "A string containing the universal identifier DN of the subject that created the
script",
        "type" : "string"
    },
    "creationDate" : {
        "title" : "Creation date",
        "description" : "An integer containing the creation date and time, in ISO 8601 format",
        "type" : "number"
    },
    "lastModifiedBy" : {
        "title" : "Last modifier",
        "description" : "A string containing the universal identifier DN of the subject that most
recently updated the script. If the script has not been modified since it was created, this property
will have the same value as createdBy",
        "type" : "string"
    },
    "lastModifiedDate" : {
        "title" : "Last modification date",
        "description" : "A string containing the last modified date and time, in ISO 8601 format. If
the script has not been modified since it was created, this property will have the same value as
creationDate",
        "type" : "number"
    }
}
"required" : [ "name", "description", "script", "language", "context" ]
}

```

1.157.1.6. validate

Validate a script. Include a JSON representation of the script and the script language, JAVASCRIPT or GROOVY, in the POST data. The value for script must be in UTF-8 format and then encoded into Base64

Usage:

```
am> action Scripts --realm Realm --body body --actionName validate
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description": "Validate action request schema",
  "type": "object",
  "title": "Validate request schema",
  "properties": {
    "script": {
      "title": "Script",
      "description": "The source code of the script. The source code is in UTF-8 format and encoded into Base64",
      "type": "string"
    },
    "language": {
      "title": "Script language",
      "description": "The language the script is written in - JAVASCRIPT or GROOVY",
      "type": "string"
    }
  },
  "required": [ "script", "language" ]
}
```

1.158. SdkProperties

1.158.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/{serverName}/properties/sdk`

Resource version: `1.0`

1.158.1.1. read

Usage:

```
am> read SdkProperties --global --serverName serverName
```

Parameters:

--serverName

An object of property key-value pairs

1.158.1.2. update

Usage:

```
am> update SdkProperties --global --serverName serverName --body body
```

Parameters:

--serverName

An object of property key-value pairs

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.header.datastore" : {
      "title" : "Data Store",
      "type" : "object",
      "propertyOrder" : 0,
      "properties" : {
        "com.sun.identity.sm.enableDataStoreNotification" : {
          "title" : "Enable Datastore Notification",
          "type" : "object",
          "propertyOrder" : 0,
          "description" : "Specifies if backend datastore notification is enabled. If
this value is set to 'false', then in-memory notification is enabled. (property name:
com.sun.identity.sm.enableDataStoreNotification)",
          "properties" : {
            "value" : {
              "type" : "boolean",
              "required" : false
            },
            "inherited" : {
              "type" : "boolean",
              "required" : true
            }
          }
        },
        "com.sun.identity.sm.notification.threadpool.size" : {
          "title" : "Notification Pool Size",
          "type" : "object",
          "propertyOrder" : 1,
          "description" : "Specifies the size of the sm notification thread pool (total number of
threads). (property name: com.sun.identity.sm.notification.threadpool.size)",
          "properties" : {
            "value" : {
```

```

        "type" : "integer",
        "required" : false
    },
    "inherited" : {
        "type" : "boolean",
        "required" : true
    }
}
}
},
"amconfig.header.eventservice" : {
    "title" : "Event Service",
    "type" : "object",
    "propertyOrder" : 1,
    "properties" : {
        "com.iplanet.am.event.connection.num.retries" : {
            "title" : "Number of retries for Event Service connections",
            "type" : "object",
            "propertyOrder" : 0,
            "description" : "Specifies the number of attempts made to successfully re-establish the
Event Service connections. (property name: com.iplanet.am.event.connection.num.retries)",
            "properties" : {
                "value" : {
                    "type" : "integer",
                    "required" : false
                },
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                }
            }
        },
        "com.iplanet.am.event.connection.delay.between.retries" : {
            "title" : "Delay between Event Service connection retries",
            "type" : "object",
            "propertyOrder" : 1,
            "description" : "Specifies the delay in milliseconds between retries to re-establish the
Event Service connections. (property name: com.iplanet.am.event.connection.delay.between.retries)",
            "properties" : {
                "value" : {
                    "type" : "integer",
                    "required" : false
                },
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                }
            }
        }
    }
},
"com.iplanet.am.event.connection.ldap.error.codes.retries" : {
    "title" : "Error codes for Event Service connection retries",
    "type" : "object",
    "propertyOrder" : 2,
    "description" : "This secifies the LDAP exception error codes for which
retries to re-establish Event Service connections will trigger. (property name:
com.iplanet.am.event.connection.ldap.error.codes.retries)",
    "properties" : {
        "value" : {

```

```

        "type" : "string",
        "required" : false
    },
    "inherited" : {
        "type" : "boolean",
        "required" : true
    }
}
},
"com.sun.am.event.connection.disable.list" : {
    "title" : "Disabled Event Service Connection",
    "type" : "object",
    "propertyOrder" : 3,
    "description" : "Specifies which event connection (persistent search) to be disabled. There
are three valid values - aci, sm and um (case insensitive). Multiple values should be separated with
\\,\\. (property name: com.sun.am.event.connection.disable.list)",
    "properties" : {
        "value" : {
            "type" : "string",
            "required" : false
        },
        "inherited" : {
            "type" : "boolean",
            "required" : true
        }
    }
}
}
},
"amconfig.header.ldapconnection" : {
    "title" : "LDAP Connection",
    "type" : "object",
    "propertyOrder" : 2,
    "properties" : {
        "com.iplanet.am.ldap.connection.num.retries" : {
            "title" : "Number of retries for LDAP Connection",
            "type" : "object",
            "propertyOrder" : 0,
            "description" : "Specifies the number of attempts made to successfully re-establish LDAP
Connection. (property name: com.iplanet.am.ldap.connection.num.retries)",
            "properties" : {
                "value" : {
                    "type" : "integer",
                    "required" : false
                },
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                }
            }
        }
    }
},
"com.iplanet.am.ldap.connection.delay.between.retries" : {
    "title" : "Delay between LDAP connection retries",
    "type" : "object",
    "propertyOrder" : 1,
    "description" : "Specifies the delay in milliseconds between retries to re-establish the
LDAP connections. (property name: com.iplanet.am.ldap.connection.delay.between.retries)",
    "properties" : {
        "value" : {

```

```

        "type" : "integer",
        "required" : false
    },
    "inherited" : {
        "type" : "boolean",
        "required" : true
    }
}
},
"com.iplanet.am.ldap.connection.ldap.error.codes.retries" : {
    "title" : "Error codes for LDAP connection retries",
    "type" : "object",
    "propertyOrder" : 2,
    "description" : "This secifies the LDAP exception error codes for
which retries to re-establish LDAP connections will trigger. (property name:
com.iplanet.am.ldap.connection.ldap.error.codes.retries)",
    "properties" : {
        "value" : {
            "type" : "string",
            "required" : false
        },
        "inherited" : {
            "type" : "boolean",
            "required" : true
        }
    }
}
}
},
"amconfig.header.cachingreplica" : {
    "title" : "Caching and Replica",
    "type" : "object",
    "propertyOrder" : 3,
    "properties" : {
        "com.iplanet.am.sdk.cache.maxSize" : {
            "title" : "SDK Caching Max. Size",
            "type" : "object",
            "propertyOrder" : 0,
            "description" : "Specifies the size of the cache when SDK caching is enabled. The size
should be an integer greater than 0, or default size (10000) will be used. Changing this value will
reset (clear) the contents of the cache. (property name: com.iplanet.am.sdk.cache.maxSize)",
            "properties" : {
                "value" : {
                    "type" : "integer",
                    "required" : false
                },
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                }
            }
        }
    }
}
},
"amconfig.header.sdktimetoliveconfig" : {
    "title" : "Time To Live Configuration",
    "type" : "object",
    "propertyOrder" : 4,
    "properties" : {

```



```

"com.iplanet.am.sdk.cache.entry.expire.enabled" : {
  "title" : "Cache Entry Expiration Enabled",
  "type" : "object",
  "propertyOrder" : 0,
  "description" : "If this property is set, the cache entries will expire
based on the time specified in User Entry Expiration Time property. (property name:
com.iplanet.am.sdk.cache.entry.expire.enabled)",
  "properties" : {
    "value" : {
      "type" : "boolean",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"com.iplanet.am.sdk.cache.entry.user.expire.time" : {
  "title" : "User Entry Expiration Time",
  "type" : "object",
  "propertyOrder" : 1,
  "description" : "This property specifies time in minutes for which the user entries remain
valid in cache after their last modification. After this specified period of time elapses (after the
last modification/read from the directory), the data for the entry that is cached will expire. At
that instant new requests for data for these user entries will result in reading from the Directory.
(property name: com.iplanet.am.sdk.cache.entry.user.expire.time)",
  "properties" : {
    "value" : {
      "type" : "integer",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"com.iplanet.am.sdk.cache.entry.default.expire.time" : {
  "title" : "Default Entry Expiration Time",
  "type" : "object",
  "propertyOrder" : 2,
  "description" : "This property specifies time in minutes for which the non-user entries
remain valid in cache after their last modification. After this specified period of time elapses
(after the last modification/read from the directory), the data for the entry that is cached will
expire. At that instant new requests for data for these non-user entries will result in reading from
the Directory. (property name: com.iplanet.am.sdk.cache.entry.default.expire.time)",
  "properties" : {
    "value" : {
      "type" : "integer",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
}

```

```
}  
}  
}
```

1.159. SecurID

1.159.1. Realm Operations

Resource path: `/realm-config/authentication/modules/securid`

Resource version: `1.0`

1.159.1.1. create

Usage:

```
am> create SecurID --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "type" : "object",  
  "properties" : {  
    "authenticationLevel" : {  
      "title" : "Authentication Level",  
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",  
      "propertyOrder" : null,  
      "required" : true,  
      "type" : "integer",  
      "exampleValue" : ""  
    },  
    "serverConfigPath" : {  
      "title" : "ACE/Server Configuration Path",  
      "description" : "The path to the ACE/Server configuration files",  
      "propertyOrder" : null,  
      "required" : true,  
      "type" : "string",  
      "exampleValue" : ""  
    }  
  }  
}
```

1.159.1.2. delete

Usage:

```
am> delete SecurID --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.159.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SecurID --realm Realm --actionName getAllTypes
```

1.159.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SecurID --realm Realm --actionName getCreatableTypes
```

1.159.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SecurID --realm Realm --actionName nextdescendents
```

1.159.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SecurID --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.159.1.7. read

Usage:

```
am> read SecurID --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.159.1.8. update

Usage:

```
am> update SecurID --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
      "propertyOrder" : null,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "serverConfigPath" : {
      "title" : "ACE/Server Configuration Path",
      "description" : "The path to the ACE/Server configuration files",
      "propertyOrder" : null,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.159.2. Global Operations

Resource path: `/global-config/authentication/modules/securid`

Resource version: `1.0`

1.159.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SecurID --global --actionName getAllTypes
```

1.159.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SecurID --global --actionName getCreatableTypes
```

1.159.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SecurID --global --actionName nextdescendents
```

1.159.2.4. read

Usage:

```
am> read SecurID --global
```

1.159.2.5. update

Usage:

```
am> update SecurID --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "serverConfigPath" : {
          "title" : "ACE/Server Configuration Path",
          "description" : "The path to the ACE/Server configuration files",
          "propertyOrder" : null,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
          "propertyOrder" : null,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        }
      }
    },
    "type" : "object",
    "title" : "Realm Defaults"
  }
}

```

1.160. SecurityProperties

1.160.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/{serverName}/properties/security`

Resource version: `1.0`

1.160.1.1. read

Usage:

```
am> read SecurityProperties --gGlobal --serverName serverName
```

Parameters:

--serverName

An object of property key-value pairs

1.160.1.2. update

Usage:

```
am> update SecurityProperties --global --serverName serverName --body body
```

Parameters:

--serverName

An object of property key-value pairs

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.header.encryption" : {
      "title" : "Encryption",
      "type" : "object",
      "propertyOrder" : 0,
      "properties" : {
        "am.encryption.pwd" : {
          "title" : "Password Encryption Key",
          "type" : "object",
          "propertyOrder" : 0,
          "description" : "The encryption key value for decrypting passwords stored in the Service Management System configuration. (property name: am.encryption.pwd)",
          "properties" : {
            "value" : {
              "type" : "string",
              "required" : false
            },
            "inherited" : {
              "type" : "boolean",
              "required" : true
            }
          }
        },
        "com.iplanet.security.encryptor" : {
          "title" : "Encryption class",
          "type" : "object",
          "propertyOrder" : 1,
          "description" : "The default encryption class. (property name: com.iplanet.security.encryptor)",
          "properties" : {
            "value" : {
              "type" : "string",
              "required" : false
            },
            "inherited" : {
              "type" : "boolean",
              "required" : true
            }
          }
        }
      }
    }
  }
},
```

```

"com.iplanet.security.SecureRandomFactoryImpl" : {
  "title" : "Secure Random Factory Class",
  "type" : "object",
  "propertyOrder" : 2,
  "description" : "This property is used for specifying SecureRandomFactory class. Available
values for this property are com.iplanet.am.util.JSSSecureRandomFactoryImpl that is using JSS
and com.iplanet.am.util.SecureRandomFactoryImpl that is using pure Java only. (property name:
com.iplanet.security.SecureRandomFactoryImpl)",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"amconfig.header.validation" : {
  "title" : "Validation",
  "type" : "object",
  "propertyOrder" : 1,
  "properties" : {
    "com.iplanet.services.comm.server.pllrequest.maxContentLength" : {
      "title" : "Platform Low Level Comm. Max. Content Length",
      "type" : "object",
      "propertyOrder" : 0,
      "description" : "Maximum content-length for an HttpRequest. (property name:
com.iplanet.services.comm.server.pllrequest.maxContentLength)",
      "properties" : {
        "value" : {
          "type" : "integer",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
},
"com.iplanet.am.clientIPCheckEnabled" : {
  "title" : "Client IP Address Check",
  "type" : "object",
  "propertyOrder" : 1,
  "description" : "Specifies whether or not the IP address of the client is checked in all
single sign on token creations or validations. (property name: com.iplanet.am.clientIPCheckEnabled)",
  "properties" : {
    "value" : {
      "type" : "boolean",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}

```



```
    }
  },
  "amconfig.header.cookie" : {
    "title" : "Cookie",
    "type" : "object",
    "propertyOrder" : 2,
    "properties" : {
      "com.iplanet.am.cookie.name" : {
        "title" : "Cookie Name",
        "type" : "object",
        "propertyOrder" : 0,
        "description" : "The cookie name used by Authentication Service to set the valid session handler ID. This name is used to retrieve the valid session information. (property name: com.iplanet.am.cookie.name)",
        "properties" : {
          "value" : {
            "type" : "string",
            "required" : false
          },
          "inherited" : {
            "type" : "boolean",
            "required" : true
          }
        }
      },
      "com.iplanet.am.cookie.secure" : {
        "title" : "Secure Cookie",
        "type" : "object",
        "propertyOrder" : 1,
        "description" : "Specifies whether to set cookie in a secure mode in which the browser will only return the cookie when a secure protocol such as HTTP(s) is used. (property name: com.iplanet.am.cookie.secure)",
        "properties" : {
          "value" : {
            "type" : "boolean",
            "required" : false
          },
          "inherited" : {
            "type" : "boolean",
            "required" : true
          }
        }
      },
      "com.iplanet.am.cookie.encode" : {
        "title" : "Encode Cookie Value",
        "type" : "object",
        "propertyOrder" : 2,
        "description" : "Specifies whether to URL encode the cookie value. (property name: com.iplanet.am.cookie.encode)",
        "properties" : {
          "value" : {
            "type" : "boolean",
            "required" : false
          },
          "inherited" : {
            "type" : "boolean",
            "required" : true
          }
        }
      }
    }
  }
}
```

```

    }
  }
},
"amconfig.header.securitykey" : {
  "title" : "Key Store",
  "type" : "object",
  "propertyOrder" : 3,
  "properties" : {
    "com.sun.identity.saml.xmlsig.keystore" : {
      "title" : "Keystore File",
      "type" : "object",
      "propertyOrder" : 0,
      "description" : "Specifies the location of the keystore file. (property name:
com.sun.identity.saml.xmlsig.keystore)",
      "properties" : {
        "value" : {
          "type" : "string",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
},
"com.sun.identity.saml.xmlsig.storetype" : {
  "title" : "Keystore Type",
  "type" : "object",
  "propertyOrder" : 1,
  "description" : "Specifies the keystore type. (property name:
com.sun.identity.saml.xmlsig.storetype)",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"com.sun.identity.saml.xmlsig.storepass" : {
  "title" : "Keystore Password File",
  "type" : "object",
  "propertyOrder" : 2,
  "description" : "Specifies the location of the file that contains the password used to
access the keystore file. (property name: com.sun.identity.saml.xmlsig.storepass)",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
}

```

```

    },
    "com.sun.identity.saml.xmlsig.keypass" : {
      "title" : "Private Key Password File",
      "type" : "object",
      "propertyOrder" : 3,
      "description" : "Specifies the location of the file that contains the
password used to protect the private key of a generated key pair. (property name:
com.sun.identity.saml.xmlsig.keypass)",
      "properties" : {
        "value" : {
          "type" : "string",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    },
    "com.sun.identity.saml.xmlsig.certalias" : {
      "title" : "Certificate Alias",
      "type" : "object",
      "propertyOrder" : 4,
      "description" : "(property name: com.sun.identity.saml.xmlsig.certalias)",
      "properties" : {
        "value" : {
          "type" : "string",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  },
  "amconfig.header.crlcache" : {
    "title" : "Certificate Revocation List Caching",
    "type" : "object",
    "propertyOrder" : 4,
    "properties" : {
      "com.sun.identity.crl.cache.directory.host" : {
        "title" : "LDAP server host name",
        "type" : "object",
        "propertyOrder" : 0,
        "description" : "",
        "properties" : {
          "value" : {
            "type" : "string",
            "required" : false
          },
          "inherited" : {
            "type" : "boolean",
            "required" : true
          }
        }
      }
    }
  },
  "com.sun.identity.crl.cache.directory.port" : {

```

```
"title" : "LDAP server port number",
"type" : "object",
"propertyOrder" : 1,
"description" : "",
"properties" : {
  "value" : {
    "type" : "integer",
    "required" : false
  },
  "inherited" : {
    "type" : "boolean",
    "required" : true
  }
}
},
"com.sun.identity.crl.cache.directory.ssl" : {
  "title" : "SSL/TLS Enabled",
  "type" : "object",
  "propertyOrder" : 2,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "boolean",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"com.sun.identity.crl.cache.directory.user" : {
  "title" : "LDAP server bind user name",
  "type" : "object",
  "propertyOrder" : 3,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"com.sun.identity.crl.cache.directory.password" : {
  "title" : "LDAP server bind password",
  "type" : "object",
  "propertyOrder" : 4,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false,
      "format" : "password"
    },
    "inherited" : {
```

```

      "type" : "boolean",
      "required" : true
    }
  }
},
"com.sun.identity.crl.cache.directory.searchlocs" : {
  "title" : "LDAP search base DN",
  "type" : "object",
  "propertyOrder" : 5,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"com.sun.identity.crl.cache.directory.searchattr" : {
  "title" : "Search Attributes",
  "type" : "object",
  "propertyOrder" : 6,
  "description" : "Any DN component of issuer's subjectDN can be used to retrieve CRL from
local LDAP server. It is single value string, like, \"cn\". All Root CA need to use the same search
attribute.",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
}
},
"amconfig.header.ocsp.check" : {
  "title" : "Online Certificate Status Protocol Check",
  "type" : "object",
  "propertyOrder" : 5,
  "properties" : {
    "com.sun.identity.authentication.ocspCheck" : {
      "title" : "Check Enabled",
      "type" : "object",
      "propertyOrder" : 0,
      "description" : "",
      "properties" : {
        "value" : {
          "type" : "boolean",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
}

```

```

    }
  },
  "com.sun.identity.authentication.ocsp.responder.url" : {
    "title" : "Responder URL",
    "type" : "object",
    "propertyOrder" : 1,
    "description" : "",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "com.sun.identity.authentication.ocsp.responder.nickname" : {
    "title" : "Certificate Nickname",
    "type" : "object",
    "propertyOrder" : 2,
    "description" : "",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
},
"amconfig.header.deserialisationwhitelist" : {
  "title" : "Object Deserialisation Class Whitelist",
  "type" : "object",
  "propertyOrder" : 6,
  "properties" : {
    "openam.deserialisation.classes.whitelist" : {
      "title" : "Whitelist",
      "type" : "object",
      "propertyOrder" : 0,
      "description" : "The list of classes that are considered valid when OpenAM performs
Object deserialisation operations. The defaults should work for most installations. (property name:
openam.deserialisation.classes.whitelist)",
      "properties" : {
        "value" : {
          "type" : "string",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
}

```

```
}  
  }  
} }  
}
```

1.161. SecurityTokenServices

1.161.1. Realm Operations

Security Token Services configuration

Resource path: `/realm-config/services/sts`

Resource version: `1.0`

1.161.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SecurityTokenServices --realm Realm --actionName getAllTypes
```

1.161.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SecurityTokenServices --realm Realm --actionName getCreatableTypes
```

1.161.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SecurityTokenServices --realm Realm --actionName nextdescendents
```

1.162. ServerInformation

1.162.1. Realm Operations

Provides information about the server.

Resource path: `/serverinfo`

Resource version: `1.1`

1.162.1.1. read

Read the server information.

Usage:

```
am> read ServerInformation --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.163. ServerVersion

1.163.1. Realm Operations

Server Version schema

Resource path: `/serverinfo/version`

Resource version: `1.0`

1.163.1.1. read

It returns information about OpenAM such as: version, revision and date

Usage:

```
am> read ServerVersion --realm Realm
```

1.164. Servers

1.164.1. Global Operations

Servers resource provider is responsible for managing Servers and their configuration for an OpenAM instance.

Resource path: `/global-config/servers`

Resource version: `1.0`

1.164.1.1. clone

Clone the specified Server, keeping it's settings but using a different URL.

Usage:

```
am> action Servers --global --body body --actionName clone
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Container for required data to clone a Server.",
  "type" : "object",
  "title" : "Clone Server Request schema",
  "properties" : {
    "clonedUrl" : {
      "type" : "string",
      "title" : "Cloned Server URL",
      "description" : "The new URL of the cloned server. Must be unique."
    }
  }
}
```

1.164.1.2. create

Create a Server.

Usage:

```
am> create Servers --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Describes the data that a Server Resource could contain.",
  "type" : "object",
  "title" : "Server resource schema",
  "properties" : {
    "_id" : {
      "type" : "string",
      "title" : "Server id",
      "description" : "Unique identifier of the Server."
    },
    "siteName" : {
      "type" : "string",
      "title" : "Site name",
      "description" : "The Server's name."
    },
    "url" : {
      "type" : "string",
      "title" : "Url",
      "description" : "The URL of the Server."
    }
  }
}
```

1.164.1.3. delete

Delete a Server.

Usage:

```
am> delete Servers --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.164.1.4. query

Query the collection of the Servers.

Usage:

```
am> query Servers --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.164.1.5. read

Read a Server.

Usage:

```
am> read Servers --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.165. Services

1.165.1. Realm Operations

The collection of services available on a realm.

Resource path: [/realm-config/services](#)

Resource version: [1.0](#)

1.165.1.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Services --realm Realm --actionName getAllTypes
```

1.165.1.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Services --realm Realm --actionName getCreatableTypes
```

1.165.1.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Services --realm Realm --actionName nextdescendents
```

1.165.1.4. query

Find services provisioned for the realm - query for a particular service by identifier, or request all services using `_queryFilter=true`

Usage:

```
am> query Services --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [_id]

1.165.2. Global Operations

Global and default configuration for services

Resource path: [/global-config/services](#)

Resource version: [1.0](#)

1.165.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Services --global --actionName getAllTypes
```

1.165.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Services --global --actionName getCreatableTypes
```

1.165.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Services --global --actionName nextdescendents
```

1.166. Session

1.166.1. Realm Operations

Resource path: `/realm-config/services/session`

Resource version: `1.0`

1.166.1.1. create

Usage:

```
am> create Session --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "dynamic" : {
      "properties" : {
        "maxCachingTime" : {
          "title" : "Maximum Caching Time",
          "description" : "Maximum time before OpenAM refreshes a session that has been cached, in
minutes.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "maxIdleTime" : {
          "title" : "Maximum Idle Time",
          "description" : "Maximum time a stateful session can remain idle before OpenAM requires the
user to authenticate again, in minutes.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "maxSessionTime" : {
          "title" : "Maximum Session Time",
          "description" : "Maximum time a session can remain valid before OpenAM requires the user to
authenticate again, in minutes.",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "quotaLimit" : {
```

```
        "title" : "Active User Sessions",
        "description" : "Maximum number of concurrent stateful sessions OpenAM allows a user to
have.",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    }
},
"type" : "object",
"title" : "Dynamic Attributes"
}
}
```

1.166.1.2. delete

Usage:

```
am> delete Session --realm Realm
```

1.166.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Session --realm Realm --actionName getAllTypes
```

1.166.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Session --realm Realm --actionName getCreatableTypes
```

1.166.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Session --realm Realm --actionName nextdescendents
```

1.166.1.6. read

Usage:

```
am> read Session --realm Realm
```

1.166.1.7. update

Usage:

```
am> update Session --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "dynamic" : {
      "properties" : {
        "maxCachingTime" : {
          "title" : "Maximum Caching Time",
          "description" : "Maximum time before OpenAM refreshes a session that has been cached, in
minutes.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "maxIdleTime" : {
          "title" : "Maximum Idle Time",
          "description" : "Maximum time a stateful session can remain idle before OpenAM requires the
user to authenticate again, in minutes.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "maxSessionTime" : {
          "title" : "Maximum Session Time",
          "description" : "Maximum time a session can remain valid before OpenAM requires the user to
authenticate again, in minutes.",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "quotaLimit" : {
          "title" : "Active User Sessions",
          "description" : "Maximum number of concurrent stateful sessions OpenAM allows a user to
have.",
          "propertyOrder" : 800,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        }
      }
    },
    "type" : "object",
    "title" : "Dynamic Attributes"
  }
}
```

```
}  
}
```

1.166.2. Global Operations

Resource path: `/global-config/services/session`

Resource version: `1.0`

1.166.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Session --global --actionName getAllTypes
```

1.166.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Session --global --actionName getCreatableTypes
```

1.166.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Session --global --actionName nextdescendents
```

1.166.2.4. read

Usage:

```
am> read Session --global
```

1.166.2.5. update

Usage:

```
am> update Session --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "stateless" : {
      "type" : "object",
      "title" : "Client-based Sessions",
      "propertyOrder" : 4,
      "properties" : {
        "statelessSigningRsaCertAlias" : {
          "title" : "Signing RSA/ECDSA Certificate Alias",
          "description" : "Specify the alias of a certificate containing a public/private key pair that AM uses when performing RSA or ECDSA signing on the session JWT. Specify a signing certificate alias when using a \"Signing Algorithm Type\" of <code>RS256</code>, <code>ES256</code>, <code>ES384</code>, or <code>ES512</code>.<br><br>The certificate is retrieved from the keystore specified by the <code>com.sun.identity.saml.xmlsig.keystore</code> property.",
          "propertyOrder" : 2100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "openam-session-stateless-enable-session-blacklisting" : {
          "title" : "Enable Session Blacklisting",
          "description" : "Blacklists client-based sessions that log out.<br><br>We recommend enabling this setting if the maximum session time is high. Blacklist state is stored in the Core Token Service (CTS) token store until the session expires, in order to ensure that sessions cannot continue to be used. Requires a server restart for changes to take effect.",
          "propertyOrder" : 2600,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "openam-session-stateless-blacklist-cache-size" : {
          "title" : "Session Blacklist Cache Size",
          "description" : "Number of blacklisted sessions to cache in memory to speed up blacklist checks and reduce load on the CTS. The cache size should be approximately the number of logouts expected in the maximum session time.",
          "propertyOrder" : 2700,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "openam-session-stateless-blacklist-purge-delay" : {
          "title" : "Blacklist Purge Delay (minutes)",
          "description" : "When added to the maximum session time, specifies the amount of time that AM tracks logged out sessions.<br><br>Increase the blacklist purge delay if you expect system clock skews in a deployment of AM servers to be greater than one minute. There is no need to increase the blacklist purge delay for servers running a clock synchronization protocol, such as Network Time Protocol.",
          "propertyOrder" : 2900,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "statelessSigningType" : {
          "title" : "Signing Algorithm Type",

```

```

        "description" : "Specifies the algorithm that AM uses to sign the JSON Web Token (JWT) containing the session content. Signing the JWT enables tampering detection.<br><br>AM supports the following signing algorithms: <ul><li><strong>HS256</strong>. HMAC using SHA-256.</li><li><strong>HS384</strong>. HMAC using SHA-384.</li><li><strong>HS512</strong>. HMAC using SHA-512.</li><li><strong>RS256</strong>. RSASSA-PKCS1-v1_5 using SHA-256.</li><li><strong>ES256</strong>. ECDSA using SHA-256 and NIST standard P-256 elliptic curve.</li><li><strong>ES384</strong>. ECDSA using SHA-384 and NIST standard P-384 elliptic curve.</li><li><strong>ES512</strong>. ECDSA using SHA-512 and NIST standard P-521 elliptic curve.</li></ul>",
        "propertyOrder" : 1900,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "statelessSigningHmacSecret" : {
        "title" : "Signing HMAC Shared Secret",
        "description" : "Specifies the shared secret that AM uses when performing HMAC signing on the session JWT.<p><p>Specify a shared secret when using a \"Signing Algorithm Type\" of <code>HS256</code>, <code>HS384</code>, or <code>HS512</code>.",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "statelessEncryptionRsaCertAlias" : {
        "title" : "Encryption RSA Certificate Alias",
        "description" : "Specifies the alias of a certificate containing a public/private key pair that AM uses when encrypting a JWT. Specify an encryption certificate alias when using an Encryption Algorithm Type of <code>RSA</code>.<br><br>The certificate is retrieved from the keystore referenced by the <code>com.sun.identity.saml.xmlsig.keystore</code> property.",
        "propertyOrder" : 2300,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "statelessEncryptionAesKey" : {
        "title" : "Encryption Symmetric AES Key",
        "description" : "AES key for use with Direct or AES KeyWrap encryption modes.<br><br>The symmetric AES key is a base64-encoded random key.<p><p>For direct encryption with <code>AES-GCM</code> or for <code>AES-KeyWrap</code> with any content encryption method, this should be 128, 192, or 256 bits.<p><p>For direct encryption with <code>AES-CBC-HMAC</code>, the key should be double those sizes (one half for the AES key, the other have for the HMAC key).<p><p>AES key sizes greater than 128 bits require installation of the JCE Unlimited Strength policy files in your JRE.",
        "propertyOrder" : 2400,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "statelessEncryptionType" : {
        "title" : "Encryption Algorithm",
        "description" : "Specifies the algorithm that AM uses to encrypt the JSON Web Token (JWT) containing the session content.<br><br>AM supports the following encryption algorithms:<ul><li><strong>NONE</strong>. No encryption is selected.</li><li><strong>RSA</strong>. Session content is encrypted with AES using a unique key. The key is then encrypted with an RSA public key and appended to the JWT.<p><p>AM supports the following padding modes, which you can set using the <code>org.forgerock.openam.session.stateless.rsa.padding</code> advanced property:<ul><li><code>RSA1_5</code>. RSA with PKCS#1 v1.5 padding.</li><li><code>RSA-OAEP</code>. RSA with optimal asymmetric encryption padding (OAEP) and SHA-1.</li><li><code>RSA-
    
```

```

OAEP-256</code>. RSA with OAEP padding and SHA-256.</li></ul></li><li><strong>AES KeyWrapping</strong>. Session content is encrypted with AES using a unique key and is then wrapped using AES KeyWrap and the master key. This provides additional security, compared to RSA, at the cost of 128 or 256 bits (or 32 bytes) depending on the size of the master key. This method provides authenticated encryption, which removes the need for a separate signature and decreases the byte size of the JWT. See <a href="https://tools.ietf.org/html/rfc3394" target="_blank">RFC 3394</a>.</li><li><strong>Direct AES Encryption</strong>. Session content is encrypted with direct AES encryption with a symmetric key. This method provides authenticated encryption, which removes the need for a separate signature and decreases the byte size of the JWT. </li></ul><p><strong>Important</strong>: To prevent users from accidentally disabling all authentication support, which can be accomplished by disabling signing and not using an authenticated encryption mode, you must set the <code>org.forgerock.openam.session.stateless.signing.allownone</code> system property to <code>>true</code> to turn off signing completely."</p>
    "propertyOrder" : 2200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "openam-session-stateless-blacklist-poll-interval" : {
    "title" : "Blacklist Poll Interval (seconds)",
    "description" : "Specifies the interval at which AM polls the Core Token Service to update the list of logged out sessions, in seconds.<br><br>The longer the polling interval, the more time a malicious user has to connect to other AM servers in a deployment and make use of a stolen session cookie. Shortening the polling interval improves the security for logged out sessions, but might incur a minimal decrease in overall AM performance due to increased network activity. Set to <code>0</code> to disable this feature completely."</p>
    "propertyOrder" : 2800,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "statelessCompressionType" : {
    "title" : "Compression Algorithm",
    "description" : "If enabled the session state is compressed before signing and encryption.<br><br><strong>WARNING</strong>: Enabling compression may compromise encryption. This may leak information about the content of the session state if encryption is enabled."</p>
    "propertyOrder" : 2500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"quotas" : {
  "type" : "object",
  "title" : "Session Quotas",
  "propertyOrder" : 3,
  "properties" : {
    "denyLoginWhenRepoDown" : {
      "title" : "Deny user login when session repository is down",
      "description" : "This property only takes effect when the session quota constraint is enabled, and the session data store is unavailable."</p>
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "iplanet-am-session-enable-session-constraint" : {
      "title" : "Enable Quota Constraints",

```

```

        "description" : "If on, then OpenAM allows you to set quota constraints on stateful
sessions.",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "quotaConstraintMaxWaitTime" : {
        "title" : "Read Timeout for Quota Constraint",
        "description" : "Maximum wait time after which OpenAM considers a search for live session
count as having failed if quota constraints are enabled, in milliseconds.",
        "propertyOrder" : 900,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "behaviourWhenQuotaExhausted" : {
        "title" : "Resulting behavior if session quota exhausted",
        "description" : "Specify the action to take if a session quota is
exhausted:<ul><li><strong>Deny Access</strong>. New session creation requests will be denied.</
li><li><strong>Destroy Next Expiring</strong>. The session that would expire next will be destroyed.</
li><li><strong>Destroy Oldest</strong>. The oldest session will be destroyed.</li><li><strong>Destroy
All</strong>. All previous sessions will be destroyed.</li></ul>",
        "propertyOrder" : 1000,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"notifications" : {
    "type" : "object",
    "title" : "Session Property Change Notifications",
    "propertyOrder" : 2,
    "properties" : {
        "notificationPropertyList" : {
            "title" : "Notification Properties",
            "description" : "Lists session properties for which OpenAM can send notifications upon
modification. Session notification applies to stateful sessions only.",
            "propertyOrder" : 1200,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "propertyChangeNotifications" : {
            "title" : "Enable Property Change Notifications",
            "description" : "If on, then OpenAM notifies other applications participating in SSO when a
session property in the Notification Properties list changes on a stateful session.",
            "propertyOrder" : 600,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}
},
"general" : {

```

```

    "type" : "object",
    "title" : "General",
    "propertyOrder" : 0,
    "properties" : {
      "dnRestrictionOnly" : {
        "title" : "DN Restriction Only Enabled",
        "description" : "If enabled, OpenAM will not perform DNS lookups when checking restrictions
in cookie hijacking mode.",
        "propertyOrder" : 1300,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "latestAccessTimeUpdateFrequency" : {
        "title" : "Latest Access Time Update Frequency",
        "description" : "Defaults to <code>60</code> seconds. At most, AM updates a session's
latest access time this often.<br><br>Subsequent touches to the session that occur within the
specified number of seconds after an update will not cause additional updates to the session's
access time.<p><p>Refreshing a session returns the idle time as the number of seconds since an
update has occurred, which will be between <code>0</code> and the specified Latest Access Time Update
Frequency.",
        "propertyOrder" : null,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      },
      "timeoutHandlers" : {
        "title" : "Session Timeout Handler implementations",
        "description" : "Lists plugin classes implementing session timeout handlers. Specify the
fully qualified name.",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
          "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
      }
    }
  },
  "iplanet-am-session-constraint-resulting-behavior" : {
    "title" : "Resulting behavior if session quota exhausted",
    "description" : "Specify the action to take if a session quota is exhausted:<ul><li><strong>Deny
Access</strong>. New session creation requests will be denied.</li><li><strong>Destroy Next
Expiring</strong>. The session that would expire next will be destroyed.</li><li><strong>Destroy
Oldest</strong>. The oldest session will be destroyed.</li><li><strong>Destroy All</strong>. All
previous sessions will be destroyed.</li></ul>",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "search" : {
    "type" : "object",
    "title" : "Session Search",
    "propertyOrder" : 1,
    "properties" : {
      "maxSessionListSize" : {
        "title" : "Maximum Number of Search Results",

```

```

        "description" : "Maximum number of results from a session search. Do not set this attribute
to a large value, for example more than 1000, unless sufficient system resources are allocated.",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "sessionListRetrievalTimeout" : {
        "title" : "Timeout for Search",
        "description" : "Time after which OpenAM sees an incomplete search as having failed, in
seconds.",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    }
},
    "dynamic" : {
        "properties" : {
            "maxCachingTime" : {
                "title" : "Maximum Caching Time",
                "description" : "Maximum time before OpenAM refreshes a session that has been cached, in
minutes.",
                "propertyOrder" : 300,
                "required" : true,
                "type" : "integer",
                "exampleValue" : ""
            },
            "maxSessionTime" : {
                "title" : "Maximum Session Time",
                "description" : "Maximum time a session can remain valid before OpenAM requires the user to
authenticate again, in minutes.",
                "propertyOrder" : 100,
                "required" : true,
                "type" : "integer",
                "exampleValue" : ""
            },
            "maxIdleTime" : {
                "title" : "Maximum Idle Time",
                "description" : "Maximum time a stateful session can remain idle before OpenAM requires the
user to authenticate again, in minutes.",
                "propertyOrder" : 200,
                "required" : true,
                "type" : "integer",
                "exampleValue" : ""
            },
            "quotaLimit" : {
                "title" : "Active User Sessions",
                "description" : "Maximum number of concurrent stateful sessions OpenAM allows a user to
have.",
                "propertyOrder" : 800,
                "required" : true,
                "type" : "integer",
                "exampleValue" : ""
            }
        }
    },
    "type" : "object",
    "title" : "Dynamic Attributes"

```

```
}  
}  
}
```

1.167. SessionProperties

1.167.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/{serverName}/properties/session`

Resource version: `1.0`

1.167.1.1. read

Usage:

```
am> read SessionProperties --global --serverName serverName
```

Parameters:

--serverName

An object of property key-value pairs

1.167.1.2. update

Usage:

```
am> update SessionProperties --global --serverName serverName --body body
```

Parameters:

--serverName

An object of property key-value pairs

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "type" : "object",  
  "properties" : {  
    "amconfig.header.sessionthresholds" : {  
      "title" : "Session Limits",  
      "type" : "object",  
      "propertyOrder" : 0,  
    },  
  },  
}
```

```

        "properties" : {
            "org.forgerock.openam.session.service.access.persistence.caching.maxsize" : {
                "title" : "Maximum Session Cache Size",
                "type" : "object",
                "propertyOrder" : 0,
                "description" : "The maximum number of sessions to cache in the per-server internal session
                cache. (property name: org.forgerock.openam.session.service.access.persistence.caching.maxsize)",
                "properties" : {
                    "value" : {
                        "type" : "integer",
                        "required" : false
                    },
                    "inherited" : {
                        "type" : "boolean",
                        "required" : true
                    }
                }
            },
            "com.iplanet.am.session.invalidsessionmaxtime" : {
                "title" : "Invalidate Session Max Time",
                "type" : "object",
                "propertyOrder" : 1,
                "description" : "Duration in minutes after which the invalid session will be removed
                from the session table if it is created and the user does not login. This value should always
                be greater than the timeout value in the Authentication module properties file. (property name:
                com.iplanet.am.session.invalidsessionmaxtime)",
                "properties" : {
                    "value" : {
                        "type" : "integer",
                        "required" : false
                    },
                    "inherited" : {
                        "type" : "boolean",
                        "required" : true
                    }
                }
            }
        }
    },
    "amconfig.header.sessionlogging" : {
        "title" : "Statistics",
        "type" : "object",
        "propertyOrder" : 1,
        "properties" : {
            "com.iplanet.am.stats.interval" : {
                "title" : "Logging Interval (in seconds)",
                "type" : "object",
                "propertyOrder" : 0,
                "description" : "Number of seconds to elapse between statistics logging. The interval
                should be at least 5 seconds to avoid CPU saturation. An interval value less than 5 seconds will be
                interpreted as 5 seconds. (property name: com.iplanet.am.stats.interval)",
                "properties" : {
                    "value" : {
                        "type" : "integer",
                        "required" : false
                    },
                    "inherited" : {
                        "type" : "boolean",
                        "required" : true
                    }
                }
            }
        }
    }
}

```



```

    }
  },
  "com.iplanet.services.stats.state" : {
    "title" : "State",
    "type" : "object",
    "propertyOrder" : 1,
    "description" : "Statistics state 'file' will write to a file under the
specified directory, and 'console' will write into webserver log files. (property name:
com.iplanet.services.stats.state)",
    "properties" : {
      "value" : {
        "enum" : [ "off", "file", "console" ],
        "options" : {
          "enum_titles" : [ "Off", "File", "Console" ]
        },
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "com.iplanet.services.stats.directory" : {
    "title" : "Directory",
    "type" : "object",
    "propertyOrder" : 2,
    "description" : "Directory where the statistic files will be created. Use forward slashes
\"/\" to separate directories, not backslash \"\\\". Spaces in the file name are allowed for Windows.
(property name: com.iplanet.services.stats.directory)",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "com.sun.am.session.enableHostLookUp" : {
    "title" : "Enable Host Lookup",
    "type" : "object",
    "propertyOrder" : 3,
    "description" : "Enables or disables host lookup during session logging. (property name:
com.sun.am.session.enableHostLookUp)",
    "properties" : {
      "value" : {
        "type" : "boolean",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
}

```

```

    }
  },
  "amconfig.header.sessionnotification" : {
    "title" : "Notification",
    "type" : "object",
    "propertyOrder" : 2,
    "properties" : {
      "com.iplanet.am.notification.threadpool.size" : {
        "title" : "Notification Pool Size",
        "type" : "object",
        "propertyOrder" : 0,
        "description" : "Specifies the size of the notification thread pool (total number of
threads). (property name: com.iplanet.am.notification.threadpool.size)",
        "properties" : {
          "value" : {
            "type" : "integer",
            "required" : false
          },
          "inherited" : {
            "type" : "boolean",
            "required" : true
          }
        }
      },
      "com.iplanet.am.notification.threadpool.threshold" : {
        "title" : "Notification Thread Pool Threshold",
        "type" : "object",
        "propertyOrder" : 1,
        "description" : "Specifies the maximum task queue length for serving notification threads.
(property name: com.iplanet.am.notification.threadpool.threshold)",
        "properties" : {
          "value" : {
            "type" : "integer",
            "required" : false
          },
          "inherited" : {
            "type" : "boolean",
            "required" : true
          }
        }
      }
    }
  },
  "amconfig.header.sessionvalidation" : {
    "title" : "Validation",
    "type" : "object",
    "propertyOrder" : 3,
    "properties" : {
      "com.sun.am.session.caseInsensitiveDN" : {
        "title" : "Case Insensitive client DN comparison",
        "type" : "object",
        "propertyOrder" : 0,
        "description" : "Specifies if client distinguished name comparison is case insensitive/
sensitive. (property name: com.sun.am.session.caseInsensitiveDN)",
        "properties" : {
          "value" : {
            "type" : "boolean",
            "required" : false
          }
        }
      }
    }
  }
}

```

```
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
}
}
}
```

1.168. SessionPropertyWhiteList

1.168.1. Realm Operations

Resource path: `/realm-config/services/amSessionPropertyWhiteList`

Resource version: `1.0`

1.168.1.1. create

Usage:

```
am> create SessionPropertyWhiteList --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "sessionPropertyWhitelist" : {
      "title" : "Whitelisted Session Property Names",
      "description" : "A list of properties that users may read, edit the value of, or delete from their session.<p><p> Adding properties to sessions can impact OpenAM's performance. Because there is no size constraint limiting the set of properties that you can add to sessions, and no limit on the number of session properties you can add, keep in mind that adding session properties can increase the load on an OpenAM deployment in the following areas: <ul><li>OpenAM server memory</li><li>OpenDJ storage</li><li>OpenDJ replication</li></ul><p>Protected attributes will NOT be allowed to be set, edited or deleted, even if they are included in this whitelist.",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.168.1.2. delete

Usage:

```
am> delete SessionPropertyWhitelist --realm Realm
```

1.168.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SessionPropertyWhitelist --realm Realm --actionName getAllTypes
```

1.168.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SessionPropertyWhitelist --realm Realm --actionName getCreatableTypes
```

1.168.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SessionPropertyWhiteList --realm Realm --actionName nextdescendents
```

1.168.1.6. read

Usage:

```
am> read SessionPropertyWhiteList --realm Realm
```

1.168.1.7. update

Usage:

```
am> update SessionPropertyWhiteList --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "sessionPropertyWhitelist" : {
      "title" : "Whitelisted Session Property Names",
      "description" : "A list of properties that users may read, edit the value of, or delete from their session.<p><p> Adding properties to sessions can impact OpenAM's performance. Because there is no size constraint limiting the set of properties that you can add to sessions, and no limit on the number of session properties you can add, keep in mind that adding session properties can increase the load on an OpenAM deployment in the following areas: <ul><li>OpenAM server memory</li><li>OpenDJ storage</li><li>OpenDJ replication</li></ul><p>Protected attributes will NOT be allowed to be set, edited or deleted, even if they are included in this whitelist.",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.168.2. Global Operations

Resource path: </global-config/services/amSessionPropertyWhitelist>

Resource version: 1.0

1.168.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SessionPropertyWhiteList --global --actionName getAllTypes
```

1.168.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SessionPropertyWhiteList --global --actionName getCreatableTypes
```

1.168.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SessionPropertyWhiteList --global --actionName nextdescendents
```

1.168.2.4. read

Usage:

```
am> read SessionPropertyWhiteList --global
```

1.168.2.5. update

Usage:

```
am> update SessionPropertyWhiteList --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "sessionPropertyWhitelist" : {
          "title" : "Whitelisted Session Property Names",
          "description" : "A list of properties that users may read, edit the value of, or delete from their session.<p><p> Adding properties to sessions can impact OpenAM's performance. Because there is no size constraint limiting the set of properties that you can add to sessions, and no limit on the number of session properties you can add, keep in mind that adding session properties can increase the load on an OpenAM deployment in the following areas: <ul><li>OpenAM server memory</li><li>OpenDJ storage</li><li>OpenDJ replication</li></ul><p>Protected attributes will NOT be allowed to be set, edited or deleted, even if they are included in this whitelist.",
          "propertyOrder" : 100,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      },
      "type" : "object",
      "title" : "Realm Defaults"
    }
  }
}
```

1.169. SessionUserService

1.169.1. Realm Operations

Resource path: `/users/{user}/services/session`

Resource version: `1.0`

1.169.1.1. create

Usage:

```
am> create SessionUserService --realm Realm --body body
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "iplanet-am-session-max-idle-time" : {
      "title" : "Maximum Idle Time",
      "description" : "Maximum time a stateful session can remain idle before OpenAM requires the user
to authenticate again, in minutes.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "iplanet-am-session-max-caching-time" : {
      "title" : "Maximum Caching Time",
      "description" : "Maximum time before OpenAM refreshes a session that has been cached, in
minutes.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "iplanet-am-session-quota-limit" : {
      "title" : "Active User Sessions",
      "description" : "Maximum number of concurrent stateful sessions OpenAM allows a user to have.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "iplanet-am-session-max-session-time" : {
      "title" : "Maximum Session Time",
      "description" : "Maximum time a session can remain valid before OpenAM requires the user to
authenticate again, in minutes.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.169.1.2. delete

Usage:

```
am> delete SessionUserService --realm Realm
```

1.169.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SessionUserService --realm Realm --user user --actionName getAllTypes
```


Parameters:

--user

1.169.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SessionUserService --realm Realm --user user --actionName getCreatableTypes
```

Parameters:

--user

1.169.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SessionUserService --realm Realm --user user --actionName nextdescendents
```

Parameters:

--user

1.169.1.6. read

Usage:

```
am> read SessionUserService --realm Realm
```

1.169.1.7. unassignServices

action.unassignServices.description

Usage:

```
am> action SessionUserService --realm Realm --body body --user user --actionName unassignServices
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "i18n:api-descriptor/UserServicesResource#schema.description",
  "type" : "object",
  "title" : "i18n:api-descriptor/UserServicesResource#schema.title",
  "properties" : {
    "serviceNames" : {
      "type" : "array",
      "title" : "i18n:api-descriptor/UserServicesResource#schema.servicename.title",
      "description" : "i18n:api-descriptor/UserServicesResource#schema.servicename.description",
      "items" : {
        "type" : "string"
      }
    }
  }
}
```

--user

1.169.1.8. update

Usage:

```
am> update SessionUserService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "iplanet-am-session-max-idle-time" : {
      "title" : "Maximum Idle Time",
      "description" : "Maximum time a stateful session can remain idle before OpenAM requires the user to authenticate again, in minutes.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "iplanet-am-session-max-caching-time" : {
      "title" : "Maximum Caching Time",
      "description" : "Maximum time before OpenAM refreshes a session that has been cached, in minutes.",
      "propertyOrder" : 300,
      "required" : true,

```

```
    "type" : "integer",
    "exampleValue" : ""
  },
  "iplanet-am-session-quota-limit" : {
    "title" : "Active User Sessions",
    "description" : "Maximum number of concurrent stateful sessions OpenAM allows a user to have.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "iplanet-am-session-max-session-time" : {
    "title" : "Maximum Session Time",
    "description" : "Maximum time a session can remain valid before OpenAM requires the user to
authenticate again, in minutes.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
```

1.170. Sessions

1.170.1. Realm Operations

Represents Sessions that can queried via a REST interface.

Resource path: `/sessions`

Resource version: `3.1`

1.170.1.1. getSessionInfo

It reads and returns the information about the requested session.

Usage:

```
am> action Sessions --realm Realm --body body --actionName getSessionInfo
```

Parameters:

`--body`

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Action request",
  "title" : "Action request",
  "type" : "object",
  "properties" : {
    "tokenId" : {
      "title" : "The tokenId",
      "description" : "The tokenId of the user you requests information for",
      "type" : "string"
    }
  },
  "required" : [ "tokenId" ]
}
```

1.170.1.2. getSessionProperties

It reads and returns all of the whitelisted properties for the requested session.

Usage:

```
am> action Sessions --realm Realm --body body --actionName getSessionProperties
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Action request",
  "title" : "Action request",
  "type" : "object",
  "properties" : {
    "tokenId" : {
      "title" : "The tokenId",
      "description" : "The tokenId of the user you requests information for",
      "type" : "string"
    }
  },
  "required" : [ "tokenId" ]
}
```

1.170.1.3. logout

It does logout from OpenAM

Usage:

```
am> action Sessions --realm Realm --body body --actionName logout
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Action request",
  "title" : "Action request",
  "type" : "object",
  "properties" : {
    "tokenId" : {
      "title" : "The tokenId",
      "description" : "The tokenId of the user you requests information for",
      "type" : "string"
    }
  },
  "required" : [ "tokenId" ]
}
```

1.170.1.4. logoutByHandle

It logs out sessions based on the provided session handles.

Usage:

```
am> action Sessions --realm Realm --body body --actionName logoutByHandle
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Logout By Handle request",
  "type" : "object",
  "title" : "Logout By Handle request",
  "properties" : {
    "sessionHandles" : {
      "title" : "Session handles",
      "description" : "The array of session handles that needs to be invalidated.",
      "type" : "array",
      "items" : {
        "type" : "string"
      }
    }
  },
  "required" : [ "sessionHandles" ]
}
```

1.170.1.5. query

It queries all sessions using the provided query filter.

Usage:

```
am> query Sessions --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [username, realm]

1.170.1.6. refresh

Suggests to OpenAM that it should refresh this session (update it's latest access time and reset its idleTime to 0). This will only be obeyed if the time between the session's previous latest access time and now is greater than the value configured for the server's Latest Access Time Update Frequency setting, which defaults to 60 seconds.

Usage:

```
am> action Sessions --realm Realm --body body --actionName refresh
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Action request",
  "title" : "Action request",
  "type" : "object",
  "properties" : {
    "tokenId" : {
      "title" : "The tokenId",
      "description" : "The tokenId of the user you requests information for",
      "type" : "string"
    }
  },
  "required" : [ "tokenId" ]
}
```

1.170.1.7. updateSessionProperties

It updates and returns all of the whitelisted properties for the requested session.

Usage:

```
am> action Sessions --realm Realm --body body --actionName updateSessionProperties
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Action request",
  "title" : "Action request",
  "type" : "object",
  "properties" : {
    "tokenId" : {
      "title" : "The tokenId",
      "description" : "The tokenId of the user you requests information for",
      "type" : "string"
    }
  },
  "required" : [ "tokenId" ]
}
```

1.170.1.8. validate

It checks that the specified SSO Token Id is valid or not. If there is any problem getting or validating the token which causes an exception the json response will be false. In addition if the token is expired then the json response will be set to false. Otherwise it will be set to true.

Usage:

```
am> action Sessions --realm Realm --body body --actionName validate
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Action request",
  "title" : "Action request",
  "type" : "object",
  "properties" : {
    "tokenId" : {
      "title" : "The tokenId",
      "description" : "The tokenId of the user you requests information for",
      "type" : "string"
    }
  },
  "required" : [ "tokenId" ]
}
```

1.171. SetPersistentCookie

1.171.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/SetPersistentCookieNode`

Resource version: `1.0`

1.171.1.1. create

Usage:

```
am> create SetPersistentCookie --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "hmacSigningKey" : {
      "title" : "HMAC Signing Key",
      "description" : "Base64-encoded 256-bit key to use for HMAC signing of the cookie.",
      "propertyOrder" : 500,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "maxLife" : {
      "title" : "Max Life",
      "description" : "The maximum length of time the persistent cookie is valid for, in hours.",
      "propertyOrder" : 200,
      "type" : "integer",
      "exampleValue" : ""
    },
    "useSecureCookie" : {
      "title" : "Use Secure Cookie",
      "description" : "Sets the persistent cookie as \"Secure\".",
      "propertyOrder" : 300,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "useHttpOnlyCookie" : {
      "title" : "Use HTTP Only Cookie",
      "description" : "Sets the persistent cookie as \"HttpOnly\".",
      "propertyOrder" : 400,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "persistentCookieName" : {
      "title" : "Persistent Cookie Name",
      "description" : "Sets the name of the persistent cookie.",

```



```
    "propertyOrder" : 600,  
    "type" : "string",  
    "exampleValue" : ""  
  },  
  "idleTimeout" : {  
    "title" : "Idle Timeout",  
    "description" : "The maximum idle time between requests before the cookie is invalidated, in  
hours.",  
    "propertyOrder" : 100,  
    "type" : "integer",  
    "exampleValue" : ""  
  }  
},  
"required" : [ "persistentCookieName", "hmacSigningKey", "maxLife", "idleTimeout",  
"useSecureCookie", "useHttpOnlyCookie" ]  
}
```

1.171.1.2. delete

Usage:

```
am> delete SetPersistentCookie --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.171.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SetPersistentCookie --realm Realm --actionName getAllTypes
```

1.171.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SetPersistentCookie --realm Realm --actionName getCreatableTypes
```

1.171.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action SetPersistentCookie --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.171.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SetPersistentCookie --realm Realm --actionName nextdescendents
```

1.171.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SetPersistentCookie --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.171.1.8. read

Usage:

```
am> read SetPersistentCookie --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.171.1.9. update

Usage:

```
am> update SetPersistentCookie --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "hmacSigningKey" : {
      "title" : "HMAC Signing Key",
      "description" : "Base64-encoded 256-bit key to use for HMAC signing of the cookie.",
      "propertyOrder" : 500,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "maxLife" : {
      "title" : "Max Life",
      "description" : "The maximum length of time the persistent cookie is valid for, in hours.",
      "propertyOrder" : 200,
      "type" : "integer",
      "exampleValue" : ""
    },
    "useSecureCookie" : {
      "title" : "Use Secure Cookie",
      "description" : "Sets the persistent cookie as \"Secure\".",
      "propertyOrder" : 300,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "useHttpOnlyCookie" : {
      "title" : "Use HTTP Only Cookie",
      "description" : "Sets the persistent cookie as \"HttpOnly\".",
      "propertyOrder" : 400,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "persistentCookieName" : {
      "title" : "Persistent Cookie Name",
      "description" : "Sets the name of the persistent cookie.",
      "propertyOrder" : 600,
      "type" : "string",
      "exampleValue" : ""
    },
    "idleTimeout" : {
      "title" : "Idle Timeout",
      "description" : "The maximum idle time between requests before the cookie is invalidated, in hours.",
      "propertyOrder" : 100,

```

```
    "type" : "integer",
    "exampleValue" : ""
  }
},
"required" : [ "persistentCookieName", "hmacSigningKey", "maxLife", "idleTimeout",
"useSecureCookie", "useHttpOnlyCookie" ]
}
```

1.172. SetSessionProperties

1.172.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/SetSessionPropertiesNode`

Resource version: `1.0`

1.172.1.1. create

Usage:

```
am> create SetSessionProperties --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "properties" : {
      "title" : "Properties",
      "description" : "The properties to set on the user's session if/when it is created.",
      "propertyOrder" : 100,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : ""
    }
  },
  "required" : [ "properties" ]
}
```

1.172.1.2. delete

Usage:

```
am> delete SetSessionProperties --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.172.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SetSessionProperties --realm Realm --actionName getAllTypes
```

1.172.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SetSessionProperties --realm Realm --actionName getCreatableTypes
```

1.172.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action SetSessionProperties --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.172.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SetSessionProperties --realm Realm --actionName nextdescendents
```

1.172.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SetSessionProperties --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.172.1.8. read

Usage:

```
am> read SetSessionProperties --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.172.1.9. update

Usage:

```
am> update SetSessionProperties --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "properties" : {
      "title" : "Properties",
      "description" : "The properties to set on the user's session if/when it is created.",
      "propertyOrder" : 100,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : ""
    }
  },
  "required" : [ "properties" ]
}
```

1.173. SharedAgents

1.173.1. Realm Operations

Agents handler that is responsible for managing agents

Resource path: `/realm-config/agents/SharedAgent`

Resource version: `1.0`

1.173.1.1. create

Usage:

```
am> create SharedAgents --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "agentProfilesAllowedToRead" : {
      "title" : "Agent Profiles allowed to Read.",
      "description" : ""
    }
  }
}
```

```

"propertyOrder" : 22600,
"items" : {
  "type" : "string"
},
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "array",
    "required" : true
  }
}
},
"userpassword" : {
  "title" : "Password",
  "description" : "",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"cdssoRootUrl" : {
  "title" : "Agent Root URL for CDSSO",
  "description" : "The agent root URL for CDSSO. The valid value is in the following format:
<br>protocol://hostname:port/<br> The protocol represents the protocol used, such as http or https.
The hostname represents the host name of the machine on which the agent resides. The port represents
the port number on which the agent is installed. The slash following the port number is required.",
  "propertyOrder" : 22700,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : true
    }
  }
}
},
"status" : {
  "title" : "Status",
  "description" : "Status of the agent configuration.",
  "propertyOrder" : 200,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}

```



```
    },  
    "value" : {  
      "type" : "string",  
      "required" : true  
    }  
  }  
}  
}
```

1.173.1.2. delete

Usage:

```
am> delete SharedAgents --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.173.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SharedAgents --realm Realm --actionName getAllTypes
```

1.173.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SharedAgents --realm Realm --actionName getCreatableTypes
```

1.173.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SharedAgents --realm Realm --actionName nextdescendents
```

1.173.1.6. query

Querying the agents of a specific type

Usage:

```
am> query SharedAgents --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.173.1.7. read

Usage:

```
am> read SharedAgents --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.173.1.8. update

Usage:

```
am> update SharedAgents --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "agentProfilesAllowedToRead" : {
      "title" : "Agent Profiles allowed to Read.",
      "description" : "",
      "propertyOrder" : 22600,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
}
```

```

    },
    "value" : {
      "type" : "array",
      "required" : true
    }
  }
},
"userpassword" : {
  "title" : "Password",
  "description" : "",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"cdssoRootUrl" : {
  "title" : "Agent Root URL for CDSSO",
  "description" : "The agent root URL for CDSSO. The valid value is in the following format:
<br>protocol://hostname:port/<br> The protocol represents the protocol used, such as http or https.
The hostname represents the host name of the machine on which the agent resides. The port represents
the port number on which the agent is installed. The slash following the port number is required.",
  "propertyOrder" : 22700,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : true
    }
  }
},
"status" : {
  "title" : "Status",
  "description" : "Status of the agent configuration.",
  "propertyOrder" : 200,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : true
    }
  }
}
}
}
}

```

1.174. Sites

1.174.1. Global Operations

This version 1.0 sites service represents a Sites resource with CQ operations on the users collection and CRUDPA operations available for the site item. Items can have server version 1.0 subresources.

Resource path: `/global-config/sites`

Resource version: `1.0`

1.174.1.1. create

Create new site entry

Usage:

```
am> create Sites --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Site schema.",
  "type" : "object",
  "title" : "Site schema",
  "properties" : {
    "_id" : {
      "type" : "string",
      "title" : "Name",
      "description" : "Site name."
    },
    "id" : {
      "type" : "string",
      "title" : "Site id",
      "description" : "Site's unique identifier.",
      "javaName" : "siteId"
    },
    "url" : {
      "type" : "string",
      "title" : "Primary URL",
      "description" : "Site primary URL."
    },
    "secondaryURLs" : {
      "type" : "array",
      "title" : "Secondary URLs",

```

```
"description" : "Secondary URLs for this site.",
"items" : {
  "type" : "string"
}
},
"servers" : {
  "type" : "array",
  "title" : "Assigned Servers",
  "description" : "Servers assigned to this site.",
  "items" : {
    "type" : "object",
    "properties" : {
      "id" : {
        "type" : "string",
        "title" : "Server id",
        "description" : "Server's unique identifier for the site."
      },
      "url" : {
        "type" : "string",
        "title" : "Server URL",
        "description" : "Server URL of the site"
      }
    }
  }
}
}
```

1.174.1.2. delete

Delete site entry

Usage:

```
am> delete Sites --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.174.1.3. query

Query the collection of site entries

Usage:

```
am> query Sites --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [_id, url]

1.174.1.4. read

Read a site entry

Usage:

```
am> read Sites --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.174.1.5. schema

Sites schema action that returns the sites schema json

Usage:

```
am> action Sites --global --actionName schema
```

1.174.1.6. template

Sites template action that returns a template json object for site insert

Usage:

```
am> action Sites --global --actionName template
```

1.174.1.7. update

Update a site entry

Usage:

```
am> update Sites --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Site schema.",
  "type" : "object",
  "title" : "Site schema",
  "properties" : {
```

```
"_id" : {
  "type" : "string",
  "title" : "Name",
  "description" : "Site name."
},
"id" : {
  "type" : "string",
  "title" : "Site id",
  "description" : "Site's unique identifier.",
  "javaName" : "siteId"
},
"url" : {
  "type" : "string",
  "title" : "Primary URL",
  "description" : "Site primary URL."
},
"secondaryURLs" : {
  "type" : "array",
  "title" : "Secondary URLs",
  "description" : "Secondary URLs for this site.",
  "items" : {
    "type" : "string"
  }
},
"servers" : {
  "type" : "array",
  "title" : "Assigned Servers",
  "description" : "Servers assigned to this site.",
  "items" : {
    "type" : "object",
    "properties" : {
      "id" : {
        "type" : "string",
        "title" : "Server id",
        "description" : "Server's unique identifier for the site."
      },
      "url" : {
        "type" : "string",
        "title" : "Server URL",
        "description" : "Server URL of the site"
      }
    }
  }
}
}
```

1.175. SoapSTSAgentGroups

1.175.1. Realm Operations

Agent Groups handler that is responsible for managing agent groups

Resource path: </realm-config/agents/groups/SoapSTSAgent>

Resource version: 1.0

1.175.1.1. create

Usage:

```
am> create SoapSTSAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "publishServicePollInterval" : {
      "title" : "Poll Interval",
      "description" : "Interval, in seconds, to poll the sts publish service for newly-published SOAP
STS instances.",
      "propertyOrder" : 26300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.175.1.2. delete

Usage:

```
am> delete SoapSTSAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.175.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SoapSTSAgentGroups --realm Realm --actionName getAllTypes
```


1.175.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SoapSTSAgentGroups --realm Realm --actionName getCreatableTypes
```

1.175.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SoapSTSAgentGroups --realm Realm --actionName nextdescendents
```

1.175.1.6. query

Querying the agent groups of a specific type

Usage:

```
am> query SoapSTSAgentGroups --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.175.1.7. read

Usage:

```
am> read SoapSTSAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.175.1.8. update

Usage:

```
am> update SoapSTSAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "publishServicePollInterval" : {
      "title" : "Poll Interval",
      "description" : "Interval, in seconds, to poll the sts publish service for newly-published SOAP
STS instances.",
      "propertyOrder" : 26300,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.176. SoapStsAgents

1.176.1. Realm Operations

Agents handler that is responsible for managing agents

Resource path: `/realm-config/agents/SoapSTSAgent`

Resource version: `1.0`

1.176.1.1. create

Usage:

```
am> create SoapStsAgents --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "agentgroup" : {
      "title" : "Group",
      "description" : "Add the agent to a group to allow inheritance of property values from the
group. <br>Changing the group will update inherited property values. <br>Inherited property values
are copied to the agent.",
      "propertyOrder" : 50,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "publishServicePollInterval" : {
      "title" : "Poll Interval",
      "description" : "Interval, in seconds, to poll the sts publish service for newly-published SOAP
STS instances.",
      "propertyOrder" : 26300,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : true
        }
      }
    }
  },
  "userpassword" : {
    "title" : "Password",
    "description" : "",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }
}
}
```

1.176.1.2. delete

Usage:

```
am> delete SoapStsAgents --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.176.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SoapStsAgents --realm Realm --actionName getAllTypes
```

1.176.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SoapStsAgents --realm Realm --actionName getCreatableTypes
```

1.176.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SoapStsAgents --realm Realm --actionName nextdescendents
```

1.176.1.6. query

Querying the agents of a specific type

Usage:

```
am> query SoapStsAgents --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.176.1.7. read

Usage:

```
am> read SoapStsAgents --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.176.1.8. update

Usage:

```
am> update SoapStsAgents --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "agentgroup" : {
      "title" : "Group",
      "description" : "Add the agent to a group to allow inheritance of property values from the group. <br>Changing the group will update inherited property values. <br>Inherited property values are copied to the agent.",
      "propertyOrder" : 50,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "publishServicePollInterval" : {
      "title" : "Poll Interval",
      "description" : "Interval, in seconds, to poll the sts publish service for newly-published SOAP STS instances.",
      "propertyOrder" : 26300,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : true
        }
      }
    },
    "userpassword" : {
      "title" : "Password",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    }
  }
}
```

```
}
```

1.177. SocialAuthInstagramModule

1.177.1. Realm Operations

Resource path: `/realm-config/authentication/modules/authSocialInstagram`

Resource version: `1.0`

1.177.1.1. create

Usage:

```
am> create SocialAuthInstagramModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type": "object",
  "properties": {
    "core": {
      "type": "object",
      "title": "Core",
      "propertyOrder": 0,
      "properties": {
        "clientSecret": {
          "title": "Client Secret",
          "description": "OAuth client_secret parameter<br><br>For more information on the OAuth client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
          "propertyOrder": 500,
          "required": true,
          "type": "string",
          "format": "password",
          "exampleValue": ""
        },
        "subjectProperty": {
          "title": "Subject Property",
          "description": "Property used to identify which attribute an auth server identifies a user by.",
          "propertyOrder": 1100,
          "required": true,

```

```

        "type" : "string",
        "exampleValue" : ""
    },
    "provider" : {
        "title" : "Social Provider",
        "description" : "Social Provider for which this module is being setup.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "logoutBehaviour" : {
        "title" : "Logout Options",
        "description" : "Specify logout behavior.<br><br>The following options are available
for logging out of the OAuth 2.0 Provider when the user logs out of AM:<br><br><ul><li>prompt:
Ask the user whether to log out from the OAuth 2.0 Provider</li><li>logout: Log out from
the OAuth 2.0 Provider without asking the user</li><li>donotlogout: Do not log out the
user from the OAuth 2.0 Provider</li></ul><br><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
        "propertyOrder" : 2155,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "usesBasicAuth" : {
        "title" : "Use Basic Auth",
        "description" : "When enabled, the client will use basic auth for authenticating with the
social auth provider. Enabled by default.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "logoutServiceUrl" : {
        "title" : "OAuth 2.0 Provider Logout Service",
        "description" : "The URL of the Identity Provider's
logout service.<br><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
        "propertyOrder" : 2150,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "clientId" : {
        "title" : "Client Id",
        "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "tokenEndpoint" : {
        "title" : "Access Token Endpoint URL",

```

```

    "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
    access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
    tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
    authentication module has an authentication level that can be used to indicate the level of security
    associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "authorizeEndpoint" : {
    "title" : "Authentication Endpoint URL",
    "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth
    authentication provided by the OAuth Identity Provider",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL<br><br>This URL endpoint provides user profile
    information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return
    JSON objects in response",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "scope" : {
    "title" : "Scope",
    "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth
    2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the
    client application requires. The list depends on the permissions that the resource owner grants to
    the client application.<br><br>Some authorization servers use non-standard separators for scopes.
    For example, Facebook takes a comma-separated list.<br><br>",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "ssoProxyUrl" : {
    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
    changed from the default, if an external server is performing the GET to POST proxying. The default
    is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 1300,
    "required" : true,

```



```

    "type" : "string",
    "exampleValue" : ""
  },
  "scopeDelimiter" : {
    "title" : "Scope Delimiter",
    "description" : "Delimiter used to separate scope values. Default value is space.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"accountProvisioning" : {
  "type" : "object",
  "title" : "Account Provisioning",
  "propertyOrder" : 1,
  "properties" : {
    "enableRegistrationService" : {
      "title" : "Use IDM as Registration Service",
      "description" : "Whether to use IDM as an external Registration Service to complete
registration for new users.<br><br>IDM is called and passed these parameters:<br><br/>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</li>
<li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
      "propertyOrder" : 1350,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "attributeMapperConfiguration" : {
      "title" : "Attribute Mapper Configuration",
      "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</code>",
      "propertyOrder" : 1800,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  },
  "anonymousUserName" : {
    "title" : "Anonymous User",
    "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that
will represent the anonymous user. This user account must already exist in the realm.",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saveAttributesInSession" : {
    "title" : "Save attributes in the session",
    "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
    "propertyOrder" : 2400,
    "required" : true,

```

```

        "type" : "boolean",
        "exampleValue" : ""
    },
    "accountMapperConfiguration" : {
        "title" : "Account Mapper Configuration",
        "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute configuration that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
        "propertyOrder" : 1600,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "attributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom attribute mapper can be provided.<br><br>A custom attribute mapper must implement the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.<br><br>Provided implementations are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</code> separated values.",
        "propertyOrder" : 1700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This class is used by the module to find the account from the attributes mapped by the Account Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.<br><br>String constructor parameters can be provided by appending <code>|</code> separated values.",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br><br>If not selected the users authenticated will be mapped by the parameters configured in the account mapper.<br><br><i>NB </i><br><i>If <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}

```

```
    },
    "accountMapperClass" : {
      "title" : "Account Mapper",
      "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br><br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
      "propertyOrder" : 1500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "createAccount" : {
      "title" : "Create account if it does not exist",
      "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
      "propertyOrder" : 1360,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
```

1.177.1.2. delete

Usage:

```
am> delete SocialAuthInstagramModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.177.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthInstagramModule --realm Realm --actionName getAllTypes
```

1.177.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthInstagramModule --realm Realm --actionName getCreatableTypes
```

1.177.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthInstagramModule --realm Realm --actionName nextdescendents
```

1.177.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SocialAuthInstagramModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.177.1.7. read

Usage:

```
am> read SocialAuthInstagramModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.177.1.8. update

Usage:

```
am> update SocialAuthInstagramModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "core" : {
      "type" : "object",
      "title" : "Core",
      "propertyOrder" : 0,
      "properties" : {
        "clientSecret" : {
          "title" : "Client Secret",
          "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
          "propertyOrder" : 500,
          "required" : true,
          "type" : "string",
          "format" : "password",
          "exampleValue" : ""
        },
        "subjectProperty" : {
          "title" : "Subject Property",
          "description" : "Property used to identify which attribute an auth server identifies a user
by.",
          "propertyOrder" : 1100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "provider" : {
          "title" : "Social Provider",
          "description" : "Social Provider for which this module is being setup.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "logoutBehaviour" : {
          "title" : "Logout Options",
          "description" : "Specify logout behavior.<br><br>The following options are available
for logging out of the OAuth 2.0 Provider when the user logs out of AM:<br><ul><li>prompt:
Ask the user whether to log out from the OAuth 2.0 Provider</li><li>logout: Log out from
the OAuth 2.0 Provider without asking the user</li><li>donotlogout: Do not log out the
user from the OAuth 2.0 Provider</li></ul><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    }
  }
}
```

```

        "propertyOrder" : 2155,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "usesBasicAuth" : {
        "title" : "Use Basic Auth",
        "description" : "When enabled, the client will use basic auth for authenticating with the
social auth provider. Enabled by default.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "logoutServiceUrl" : {
        "title" : "OAuth 2.0 Provider Logout Service",
        "description" : "The URL of the Identity Provider's
logout service.<br><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
        "propertyOrder" : 2150,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "clientId" : {
        "title" : "Client Id",
        "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "tokenEndpoint" : {
        "title" : "Access Token Endpoint URL",
        "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=
\"http://tools.ietf.org/html/rfc6749#section-3.2\" target=
\"_blank\">RFC 6749</a>, section 3.2",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "authenticationLevel" : {
        "title" : "Authentication Level",
        "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "authorizeEndpoint" : {
        "title" : "Authentication Endpoint URL",

```

```

    "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL<br><br>This URL endpoint provides user profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return JSON objects in response",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "scope" : {
    "title" : "Scope",
    "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the client application requires. The list depends on the permissions that the resource owner grants to the client application.<br><br>Some authorization servers use non-standard separators for scopes. For example, Facebook takes a comma-separated list.<br><br>",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "ssoProxyUrl" : {
    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be changed from the default, if an external server is performing the GET to POST proxying. The default is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "scopeDelimiter" : {
    "title" : "Scope Delimiter",
    "description" : "Delimiter used to separate scope values. Default value is space.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"accountProvisioning" : {
  "type" : "object",
  "title" : "Account Provisioning",
  "propertyOrder" : 1,
  "properties" : {
    "enableRegistrationService" : {
      "title" : "Use IDM as Registration Service",

```

```

    "description" : "Whether to use IDM as an external Registration Service to complete
    registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
    <ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
    li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
    authentication after registration in IDM is complete.</li></ul>",
    "propertyOrder" : 1350,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "attributeMapperConfiguration" : {
    "title" : "Attribute Mapper Configuration",
    "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
    configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
    local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
    code>",
    "propertyOrder" : 1800,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "anonymousUserName" : {
    "title" : "Anonymous User",
    "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that
    will represent the anonymous user. This user account must already exist in the realm.",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saveAttributesInSession" : {
    "title" : "Save attributes in the session",
    "description" : "If this option is enabled, the attributes configured in the attribute
    mapper will be saved into the OpenAM session",
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "accountMapperConfiguration" : {
    "title" : "Account Mapper Configuration",
    "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
    configuration that will be used to map the account of the user authenticated in the OAuth 2.0
    Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
    code>",
    "propertyOrder" : 1600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "attributeMappingClasses" : {
    "title" : "Attribute Mapper",

```



```

        "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "accountMapperClass" : {
        "title" : "Account Mapper",
        "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "createAccount" : {
        "title" : "Create account if it does not exist",

```

```
"description" : "If the OAuth2 account does not exist in the local OpenAM data store, an  
account will be created dynamically.<br><br>If this is enabled, the account mapper could create  
the account dynamically if there is no account mapped. Before creating the account, a dialog  
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt  
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3  
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM  
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in  
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see  
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>\",  
  "propertyOrder" : 1360,  
  "required" : true,  
  "type" : "boolean",  
  "exampleValue" : ""  
},  
},  
},  
}
```

1.177.2. Global Operations

Resource path: `/global-config/authentication/modules/authSocialInstagram`

Resource version: `1.0`

1.177.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthInstagramModule --global --actionName getAllTypes
```

1.177.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthInstagramModule --global --actionName getCreatableTypes
```

1.177.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthInstagramModule --global --actionName nextdescendents
```

1.177.2.4. read

Usage:

```
am> read SocialAuthInstagramModule --global
```

1.177.2.5. update

Usage:

```
am> update SocialAuthInstagramModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "accountProvisioning" : {
          "type" : "object",
          "title" : "Account Provisioning",
          "propertyOrder" : 1,
          "properties" : {
            "saveAttributesInSession" : {
              "title" : "Save attributes in the session",
              "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
              "propertyOrder" : 2400,
              "required" : true,
              "type" : "boolean",
              "exampleValue" : ""
            },
            "accountProviderClass" : {
              "title" : "Account Provider",
              "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br></code>String constructor parameters can be provided by appending <code>|</code> separated
values.",
              "propertyOrder" : 1400,
              "required" : true,
              "type" : "string",
              "exampleValue" : ""
            },
            "accountMapperConfiguration" : {
              "title" : "Account Mapper Configuration",
              "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
              "propertyOrder" : 1600,
```

```

        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "createAccount" : {
        "title" : "Create account if it does not exist",
        "description" : "If the OAuth2 account does not exist in the local OpenAM data store,
an account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
        "propertyOrder" : 1360,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
mapped by the parameters configured in the account mapper.<br><br><i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "attributeMapperConfiguration" : {
        "title" : "Attribute Mapper Configuration",
        "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    },
    "accountMapperClass" : {
        "title" : "Account Mapper",
        "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
    
```

```

using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</code> separated values.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "anonymousUserName" : {
    "title" : "Anonymous User",
    "description" : "Username of the OpenAM anonymous user<br><br>The username of the user
that will represent the anonymous user. This user account must already exist in the realm.",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "attributeMappingClasses" : {
    "title" : "Attribute Mapper",
    "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</li>
<li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</code> separated values.",
    "propertyOrder" : 1700,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "enableRegistrationService" : {
    "title" : "Use IDM as Registration Service",
    "description" : "Whether to use IDM as an external Registration Service to
complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</li>
<li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
    "propertyOrder" : 1350,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
}
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "logoutServiceUrl" : {
      "title" : "OAuth 2.0 Provider Logout Service",
      "description" : "The URL of the Identity Provider's
logout service.<br><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the

```

```

<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
    "propertyOrder" : 2150,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "usesBasicAuth" : {
    "title" : "Use Basic Auth",
    "description" : "When enabled, the client will use basic auth for authenticating with
the social auth provider. Enabled by default.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "authorizeEndpoint" : {
    "title" : "Authentication Endpoint URL",
    "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for
OAuth authentication provided by the OAuth Identity Provider",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "subjectProperty" : {
    "title" : "Subject Property",
    "description" : "Property used to identify which attribute an auth server identifies a
user by.",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientId" : {
    "title" : "Client Id",
    "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "ssoProxyUrl" : {
    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL<br><br>This URL endpoint provides user
profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should
return JSON objects in response",

```

```

        "propertyOrder" : 800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "scopeDelimiter" : {
        "title" : "Scope Delimiter",
        "description" : "Delimiter used to separate scope values. Default value is space.",
        "propertyOrder" : 1000,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "logoutBehaviour" : {
        "title" : "Logout Options",
        "description" : "Specify logout behavior.<br><br>The following options are
available for logging out of the OAuth 2.0 Provider when the user logs out of AM:<br>
<ul><li>prompt: Ask the user whether to log out from the OAuth 2.0 Provider</li><li>logout:
Log out from the OAuth 2.0 Provider without asking the user</li><li>donotlogout: Do not log
out the user from the OAuth 2.0 Provider</li></ul><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
        "propertyOrder" : 2155,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "tokenEndpoint" : {
        "title" : "Access Token Endpoint URL",
        "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "scope" : {
        "title" : "Scope",
        "description" : "OAuth scope; list of user profile properties<br><br>According to the
OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that
the client application requires. The list depends on the permissions that the resource owner grants
to the client application.<br><br>Some authorization servers use non-standard separators for
scopes. For example, Facebook takes a comma-separated list.<br><br>",
        "propertyOrder" : 900,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "authenticationLevel" : {
        "title" : "Authentication Level",
        "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
        "propertyOrder" : 100,

```

```

        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "clientSecret" : {
        "title" : "Client Secret",
        "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "provider" : {
        "title" : "Social Provider",
        "description" : "Social Provider for which this module is being setup.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
}
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}

```

1.178. SocialAuthOAuth2Module

1.178.1. Realm Operations

Resource path: `/realm-config/authentication/modules/authSocialOAuth2`

Resource version: `1.0`

1.178.1.1. create

Usage:

```
am> create SocialAuthOAuth2Module --realm Realm --id id --body body
```

Parameters:

`--id`

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "core" : {
      "type" : "object",
      "title" : "Core",
      "propertyOrder" : 0,
      "properties" : {
        "mixUpMitigation" : {
          "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
          "description" : "Enables OAuth 2.0 mix-up mitigation<br><br>The authorization
server must support the <a href=\"https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
mitigation-01#section-3.1\">OAuth 2.0 Mix-Up Mitigation draft</a>, otherwise OpenAM will fail to
validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make
sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
          "propertyOrder" : 2600,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "usesBasicAuth" : {
          "title" : "Use Basic Auth",
          "description" : "When enabled, the client will use basic auth for authenticating with the
social auth provider. Enabled by default.",
          "propertyOrder" : 1200,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "authorizeEndpoint" : {
          "title" : "Authentication Endpoint URL",
          "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth
authentication provided by the OAuth Identity Provider",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "string",
          "exampleValue" : "https://accounts.google.com/o/oauth2/v2/auth"
        },
        "scopeDelimiter" : {
          "title" : "Scope Delimiter",
          "description" : "Delimiter used to separate scope values. Default value is space.",
          "propertyOrder" : 1000,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "tokenEndpoint" : {
          "title" : "Access Token Endpoint URL",
          "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
          "propertyOrder" : 700,
          "required" : true,
          "type" : "string",
          "exampleValue" : "https://www.googleapis.com/oauth2/v4/token"
        }
      }
    }
  }
}
```

```

},
"scope" : {
  "title" : "Scope",
  "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth
2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the
client application requires. The list depends on the permissions that the resource owner grants to
the client application.<br><br>Some authorization servers use non-standard separators for scopes.
For example, Facebook takes a comma-separated list.<br><br>",
  "propertyOrder" : 900,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : "profile email"
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"ssoProxyUrl" : {
  "title" : "Proxy URL",
  "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
  "propertyOrder" : 1300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"provider" : {
  "title" : "Social Provider",
  "description" : "Social Provider for which this module is being setup.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : "Google"
},
"userInfoEndpoint" : {
  "title" : "User Profile Service URL",
  "description" : "User profile information URL<br><br>This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider<br><br><i>This URL should return
JSON objects in response",
  "propertyOrder" : 800,
  "required" : true,
  "type" : "string",
  "exampleValue" : "https://www.googleapis.com/oauth2/v3/userinfo"
},
"logoutServiceUrl" : {
  "title" : "OAuth 2.0 Provider Logout Service",
  "description" : "The URL of the Identity Provider's
logout service.<br><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the

```

```

<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
  "propertyOrder" : 2150,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
  "clientId" : {
    "title" : "Client Id",
    "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "subjectProperty" : {
    "title" : "Subject Property",
    "description" : "Property used to identify which attribute an auth server identifies a user
by.",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : "sub"
  },
  "issuerName" : {
    "title" : "Token Issuer",
    "description" : "Required when the 'openid' scope is included. Value must match the iss
field in issued ID Token<br>/>e.g. accounts.google.com<br><br>The issuer value MUST be provided when
OAuth 2.0 Mix-Up Mitigation is enabled.",
    "propertyOrder" : 2500,
    "required" : true,
    "type" : "string",
    "exampleValue" : "https://accounts.google.com"
  },
  "logoutBehaviour" : {
    "title" : "Logout Options",
    "description" : "Specify logout behavior.<br><br>The following options are available
for logging out of the OAuth 2.0 Provider when the user logs out of AM:<br></ul><li>prompt:
Ask the user whether to log out from the OAuth 2.0 Provider</li><li>logout: Log out from
the OAuth 2.0 Provider without asking the user</li><li>donotlogout: Do not log out the
user from the OAuth 2.0 Provider</li></ul><br>/>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
    "propertyOrder" : 2155,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=
\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
  }
}

```

```

        "format" : "password",
        "exampleValue" : ""
    }
}
},
"accountProvisioning" : {
    "type" : "object",
    "title" : "Account Provisioning",
    "propertyOrder" : 1,
    "properties" : {
        "accountMapperConfiguration" : {
            "title" : "Account Mapper Configuration",
            "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute configuration that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
            "propertyOrder" : 1600,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : "sub=uid"
        },
        "attributeMapperConfiguration" : {
            "title" : "Attribute Mapper Configuration",
            "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</code>",
            "propertyOrder" : 1800,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : "given_name=givenName family_name=sn name=cn email=mail sub=uid"
        },
        "anonymousUserName" : {
            "title" : "Anonymous User",
            "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that will represent the anonymous user. This user account must already exist in the realm.",
            "propertyOrder" : 2100,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "saveAttributesInSession" : {
            "title" : "Save attributes in the session",
            "description" : "If this option is enabled, the attributes configured in the attribute mapper will be saved into the OpenAM session",
            "propertyOrder" : 2400,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "enableRegistrationService" : {
            "title" : "Use IDM as Registration Service",

```

```

        "description" : "Whether to use IDM as an external Registration Service to complete
        registration for new users.<br><br>IDM is called and passed these parameters:<br><br/>
        <ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
        li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
        authentication after registration in IDM is complete.</li></ul>",
        "propertyOrder" : 1350,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "attributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute
        mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
        attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
        <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
        interface.<br>Provided implementations
        are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
        li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
        using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
        code> separated values.",
        "propertyOrder" : 1700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" :
        "org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper|uid|google-"
    },
    "promptPasswordFlag" : {
        "title" : "Prompt for password setting and activation code",
        "description" : "Users must set a password and complete the activation flow during dynamic
        profile creation.<br><br>If this is enabled, the user must set a password before the system creates
        an account dynamically and an activation code will be sent to the user's email address. The account
        will be created only if the password and activation code are properly set. <br />If this is disabled,
        the account will be created transparently without prompting the user.",
        "propertyOrder" : 1905,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This
        class is used by the module to find the account from the attributes mapped by the Account
        Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
        interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
        values.",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
        users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
        anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
    
```

```

mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"createAccount" : {
    "title" : "Create account if it does not exist",
    "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
    "propertyOrder" : 1360,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"accountMapperClass" : {
    "title" : "Account Mapper",
    "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" :
"org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper*|google-"
}
},
"emailSettings" : {
    "type" : "object",
    "title" : "Email",
    "propertyOrder" : 2,
    "properties" : {
        "emailGateway" : {
            "title" : "Mail Server Gateway implementation class",
            "description" : "The class used by the module to send email.<br><br>This class is used by
the module to send email. A custom implementation can be provided.<br><br>The custom implementation
must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
            "propertyOrder" : 1915,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "smtpPassword" : {
            "title" : "SMTP User Password",

```

```
"description" : "The Password of the SMTP User Name",
"propertyOrder" : 1935,
"required" : true,
"type" : "string",
"format" : "password",
"exampleValue" : ""
},
"smtpHost" : {
  "title" : "SMTP host",
  "description" : "The mail host that will be used by the Email Gateway implementation",
  "propertyOrder" : 1920,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"smtpPort" : {
  "title" : "SMTP port",
  "description" : "The TCP port that will be used by the SMTP gateway",
  "propertyOrder" : 1925,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"smtpSslEnabled" : {
  "title" : "SMTP SSL Enabled",
  "description" : "Tick this option if the SMTP Server provides SSL",
  "propertyOrder" : 1940,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"smtpUsername" : {
  "title" : "SMTP User Name",
  "description" : "If the SMTP Service requires authentication, configure the user name here",
  "propertyOrder" : 1930,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"emailAttribute" : {
  "title" : "Email attribute in the Response",
  "description" : "Attribute from the response used to send activation code emails.<br><br>The attribute in the response from the profile service of the Provider that contains the email address of the authenticated user. This address will be used to send an email with an activation code when the accounts are allowed to be created dynamically.",
  "propertyOrder" : 1910,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"smtpFromAddress" : {
  "title" : "SMTP From address",
  "description" : "The email address on behalf of whom the messages will be sent",
  "propertyOrder" : 1945,
  "required" : true,
  "type" : "string",
  "exampleValue" : "info@forgerock.com"
}
}
```

```
}  
}  
}
```

1.178.1.2. delete

Usage:

```
am> delete SocialAuth0Auth2Module --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.178.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuth0Auth2Module --realm Realm --actionName getAllTypes
```

1.178.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuth0Auth2Module --realm Realm --actionName getCreatableTypes
```

1.178.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuth0Auth2Module --realm Realm --actionName nextdescendents
```

1.178.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SocialAuth0Auth2Module --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.178.1.7. read

Usage:

```
am> read SocialAuthOAuth2Module --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.178.1.8. update

Usage:

```
am> update SocialAuthOAuth2Module --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "core" : {
      "type" : "object",
      "title" : "Core",
      "propertyOrder" : 0,
      "properties" : {
        "mixUpMitigation" : {
          "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
          "description" : "Enables OAuth 2.0 mix-up mitigation<br><br>The authorization
server must support the <a href=\"https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
mitigation-01#section-3.1\">OAuth 2.0 Mix-Up Mitigation draft</a>, otherwise OpenAM will fail to
validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make
sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
          "propertyOrder" : 2600,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "usesBasicAuth" : {
          "title" : "Use Basic Auth",
```

```

        "description" : "When enabled, the client will use basic auth for authenticating with the
social auth provider. Enabled by default.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "authorizeEndpoint" : {
        "title" : "Authentication Endpoint URL",
        "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth
authentication provided by the OAuth Identity Provider",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "string",
        "exampleValue" : "https://accounts.google.com/o/oauth2/v2/auth"
    },
    "scopeDelimiter" : {
        "title" : "Scope Delimiter",
        "description" : "Delimiter used to separate scope values. Default value is space.",
        "propertyOrder" : 1000,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "tokenEndpoint" : {
        "title" : "Access Token Endpoint URL",
        "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "string",
        "exampleValue" : "https://www.googleapis.com/oauth2/v4/token"
    },
    "scope" : {
        "title" : "Scope",
        "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth
2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the
client application requires. The list depends on the permissions that the resource owner grants to
the client application.<br><br>Some authorization servers use non-standard separators for scopes.
For example, Facebook takes a comma-separated list.<br><br>",
        "propertyOrder" : 900,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : "profile email"
    },
    "authenticationLevel" : {
        "title" : "Authentication Level",
        "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    },

```

```

"ssoProxyUrl" : {
  "title" : "Proxy URL",
  "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
  "propertyOrder" : 1300,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"provider" : {
  "title" : "Social Provider",
  "description" : "Social Provider for which this module is being setup.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : "Google"
},
"userInfoEndpoint" : {
  "title" : "User Profile Service URL",
  "description" : "User profile information URL<br><br>This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return
JSON objects in response",
  "propertyOrder" : 800,
  "required" : true,
  "type" : "string",
  "exampleValue" : "https://www.googleapis.com/oauth2/v3/userinfo"
},
"logoutServiceUrl" : {
  "title" : "OAuth 2.0 Provider Logout Service",
  "description" : "The URL of the Identity Provider's
logout service.<br><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
  "propertyOrder" : 2150,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"clientId" : {
  "title" : "Client Id",
  "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"subjectProperty" : {
  "title" : "Subject Property",
  "description" : "Property used to identify which attribute an auth server identifies a user
by.",
  "propertyOrder" : 1100,
  "required" : true,
  "type" : "string",
  "exampleValue" : "sub"
},

```

```

"issuerName" : {
  "title" : "Token Issuer",
  "description" : "Required when the 'openid' scope is included. Value must match the iss
field in issued ID Token<br/>e.g. accounts.google.com<br><br>The issuer value MUST be provided when
OAuth 2.0 Mix-Up Mitigation is enabled.",
  "propertyOrder" : 2500,
  "required" : true,
  "type" : "string",
  "exampleValue" : "https://accounts.google.com"
},
"logoutBehaviour" : {
  "title" : "Logout Options",
  "description" : "Specify logout behavior.<br><br>The following options are available
for logging out of the OAuth 2.0 Provider when the user logs out of AM:<br><br><ul><li>prompt:
Ask the user whether to log out from the OAuth 2.0 Provider</li><li>logout: Log out from
the OAuth 2.0 Provider without asking the user</li><li>donotlogout: Do not log out the
user from the OAuth 2.0 Provider</li></ul><br><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
  "propertyOrder" : 2155,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"clientSecret" : {
  "title" : "Client Secret",
  "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
}
}
},
"accountProvisioning" : {
  "type" : "object",
  "title" : "Account Provisioning",
  "propertyOrder" : 1,
  "properties" : {
    "accountMapperConfiguration" : {
      "title" : "Account Mapper Configuration",
      "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
      "propertyOrder" : 1600,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : "sub=uid"
    },
    "attributeMapperConfiguration" : {
      "title" : "Attribute Mapper Configuration",

```

```

    "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
    "propertyOrder" : 1800,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : "given_name=givenName family_name=sn name=cn email=mail sub=uid"
},
"anonymousUserName" : {
    "title" : "Anonymous User",
    "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that
will represent the anonymous user. This user account must already exist in the realm.",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"saveAttributesInSession" : {
    "title" : "Save attributes in the session",
    "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"enableRegistrationService" : {
    "title" : "Use IDM as Registration Service",
    "description" : "Whether to use IDM as an external Registration Service to complete
registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
    "propertyOrder" : 1350,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"attributeMappingClasses" : {
    "title" : "Attribute Mapper",
    "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br><br>Provided implementations
are:<ul><li><code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li><code>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</code> (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1700,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",

```

```

        "exampleValue" :
"org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper|uid|google-"
    },
    "promptPasswordFlag" : {
        "title" : "Prompt for password setting and activation code",
        "description" : "Users must set a password and complete the activation flow during dynamic
profile creation.<br><br>If this is enabled, the user must set a password before the system creates
an account dynamically and an activation code will be sent to the user's email address. The account
will be created only if the password and activation code are properly set. <br />If this is disabled,
the account will be created transparently without prompting the user.",
        "propertyOrder" : 1905,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "createAccount" : {
        "title" : "Create account if it does not exist",
        "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
        "propertyOrder" : 1360,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "accountMapperClass" : {
        "title" : "Account Mapper",
        "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
    
```

```

received from the OAuth Identity Provider into OpenAM.<br/><br/>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br/>Provided implementations
are:<ul><li><code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li><code>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</code> (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" :
"org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper|*|google-"
  }
}
},
"emailSettings" : {
  "type" : "object",
  "title" : "Email",
  "propertyOrder" : 2,
  "properties" : {
    "emailGateway" : {
      "title" : "Mail Server Gateway implementation class",
      "description" : "The class used by the module to send email.<br><br>This class is used by
the module to send email. A custom implementation can be provided.<br><br>The custom implementation
must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
      "propertyOrder" : 1915,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpPassword" : {
      "title" : "SMTP User Password",
      "description" : "The Password of the SMTP User Name",
      "propertyOrder" : 1935,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "smtpHost" : {
      "title" : "SMTP host",
      "description" : "The mail host that will be used by the Email Gateway implementation",
      "propertyOrder" : 1920,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpPort" : {
      "title" : "SMTP port",
      "description" : "The TCP port that will be used by the SMTP gateway",
      "propertyOrder" : 1925,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpSslEnabled" : {
      "title" : "SMTP SSL Enabled",
      "description" : "Tick this option if the SMTP Server provides SSL",
      "propertyOrder" : 1940,

```


Usage:

```
am> action SocialAuth0Auth2Module --global --actionName getCreatableTypes
```

1.178.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuth0Auth2Module --global --actionName nextdescendents
```

1.178.2.4. read

Usage:

```
am> read SocialAuth0Auth2Module --global
```

1.178.2.5. update

Usage:

```
am> update SocialAuth0Auth2Module --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "emailSettings" : {
          "type" : "object",
          "title" : "Email",
          "propertyOrder" : 2,
          "properties" : {
            "smtpUsername" : {
              "title" : "SMTP User Name",
              "description" : "If the SMTP Service requires authentication, configure the user name
here",
              "propertyOrder" : 1930,
              "required" : true,
              "type" : "string",
              "exampleValue" : ""
            },
            "emailGateway" : {
              "title" : "Mail Server Gateway implementation class",
              "description" : "The class used by the module to send
email.<br><br>This class is used by the module to send email. A custom
```

```

implementation can be provided.<br/><br/>The custom implementation must implement the
<code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>,
    "propertyOrder" : 1915,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"smtpPassword" : {
    "title" : "SMTP User Password",
    "description" : "The Password of the SMTP User Name",
    "propertyOrder" : 1935,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
},
"emailAttribute" : {
    "title" : "Email attribute in the Response",
    "description" : "Attribute from the response used to send activation code
emails.<br><br>The attribute in the response from the profile service of the Provider that contains
the email address of the authenticated user. This address will be used to send an email with an
activation code when the accounts are allowed to be created dynamically.",
    "propertyOrder" : 1910,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"smtpPort" : {
    "title" : "SMTP port",
    "description" : "The TCP port that will be used by the SMTP gateway",
    "propertyOrder" : 1925,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"smtpSslEnabled" : {
    "title" : "SMTP SSL Enabled",
    "description" : "Tick this option if the SMTP Server provides SSL",
    "propertyOrder" : 1940,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"smtpHost" : {
    "title" : "SMTP host",
    "description" : "The mail host that will be used by the Email Gateway implementation",
    "propertyOrder" : 1920,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"smtpFromAddress" : {
    "title" : "SMTP From address",
    "description" : "The email address on behalf of whom the messages will be sent",
    "propertyOrder" : 1945,
    "required" : true,
    "type" : "string",
    "exampleValue" : "info@forgerock.com"
}
}

```

```

    }
  },
  "core" : {
    "type" : "object",
    "title" : "Core",
    "propertyOrder" : 0,
    "properties" : {
      "authorizeEndpoint" : {
        "title" : "Authentication Endpoint URL",
        "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for
        OAuth authentication provided by the OAuth Identity Provider",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "string",
        "exampleValue" : "https://accounts.google.com/o/oauth2/v2/auth"
      },
      "tokenEndpoint" : {
        "title" : "Access Token Endpoint URL",
        "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
        access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
        tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "string",
        "exampleValue" : "https://www.googleapis.com/oauth2/v4/token"
      },
      "usesBasicAuth" : {
        "title" : "Use Basic Auth",
        "description" : "When enabled, the client will use basic auth for authenticating with
        the social auth provider. Enabled by default.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "provider" : {
        "title" : "Social Provider",
        "description" : "Social Provider for which this module is being setup.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : "Google"
      },
      "mixUpMitigation" : {
        "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
        "description" : "Enables OAuth 2.0 mix-up mitigation<br><br>The authorization
        server must support the <a href=\"https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
        mitigation-01#section-3.1\">OAuth 2.0 Mix-Up Mitigation draft</a>, otherwise OpenAM will fail to
        validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make
        sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
        "propertyOrder" : 2600,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "logoutServiceUrl" : {
        "title" : "OAuth 2.0 Provider Logout Service",
        "description" : "The URL of the Identity Provider's
        logout service.<br><br>To enable IdP logout, you must also add
    
```

```

<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
    "propertyOrder" : 2150,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "scope" : {
    "title" : "Scope",
    "description" : "OAuth scope; list of user profile properties<br><br>According to the
OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that
the client application requires. The list depends on the permissions that the resource owner grants
to the client application.<br><br>Some authorization servers use non-standard separators for
scopes. For example, Facebook takes a comma-separated list.<br><br>",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : "profile email"
  },
  "logoutBehaviour" : {
    "title" : "Logout Options",
    "description" : "Specify logout behavior.<br><br>The following options are
available for logging out of the OAuth 2.0 Provider when the user logs out of AM:<br>
<ul><li>prompt: Ask the user whether to log out from the OAuth 2.0 Provider</li><li>logout:
Log out from the OAuth 2.0 Provider without asking the user</li><li>donotlogout: Do not log
out the user from the OAuth 2.0 Provider</li></ul><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
    "propertyOrder" : 2155,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
},

```

```

        "issuerName" : {
            "title" : "Token Issuer",
            "description" : "Required when the 'openid' scope is included. Value must match the iss
field in issued ID Token<br/>e.g. accounts.google.com<br/><br/>The issuer value MUST be provided when
OAuth 2.0 Mix-Up Mitigation is enabled.",
            "propertyOrder" : 2500,
            "required" : true,
            "type" : "string",
            "exampleValue" : "https://accounts.google.com"
        },
        "scopeDelimiter" : {
            "title" : "Scope Delimiter",
            "description" : "Delimiter used to separate scope values. Default value is space.",
            "propertyOrder" : 1000,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "subjectProperty" : {
            "title" : "Subject Property",
            "description" : "Property used to identify which attribute an auth server identifies a
user by.",
            "propertyOrder" : 1100,
            "required" : true,
            "type" : "string",
            "exampleValue" : "sub"
        },
        "clientId" : {
            "title" : "Client Id",
            "description" : "OAuth client_id parameter<br/><br/>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
            "propertyOrder" : 400,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "userInfoEndpoint" : {
            "title" : "User Profile Service URL",
            "description" : "User profile information URL<br/><br/>This URL endpoint provides user
profile information and is provided by the OAuth Identity Provider<br/><br/><i>NB </i>This URL should
return JSON objects in response",
            "propertyOrder" : 800,
            "required" : true,
            "type" : "string",
            "exampleValue" : "https://www.googleapis.com/oauth2/v3/userinfo"
        },
        "ssoProxyUrl" : {
            "title" : "Proxy URL",
            "description" : "The URL to the OpenAM OAuth proxy JSP<br/><br/>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>openam/oauth2c/OAuthProxy.jsp</code>",
            "propertyOrder" : 1300,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
},

```

```

"accountProvisioning" : {
  "type" : "object",
  "title" : "Account Provisioning",
  "propertyOrder" : 1,
  "properties" : {
    "promptPasswordFlag" : {
      "title" : "Prompt for password setting and activation code",
      "description" : "Users must set a password and complete the activation flow during
dynamic profile creation.<br><br>If this is enabled, the user must set a password before the system
creates an account dynamically and an activation code will be sent to the user's email address. The
account will be created only if the password and activation code are properly set. <br />If this is
disabled, the account will be created transparently without prompting the user.",
      "propertyOrder" : 1905,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "enableRegistrationService" : {
      "title" : "Use IDM as Registration Service",
      "description" : "Whether to use IDM as an external Registration Service to
complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
      "propertyOrder" : 1350,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "anonymousUserName" : {
      "title" : "Anonymous User",
      "description" : "Username of the OpenAM anonymous user<br><br>The username of the user
that will represent the anonymous user. This user account must already exist in the realm.",
      "propertyOrder" : 2100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "accountMapperConfiguration" : {
      "title" : "Account Mapper Configuration",
      "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
      "propertyOrder" : 1600,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : "sub=uid"
    },
    "saveAttributesInSession" : {
      "title" : "Save attributes in the session",
      "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
      "propertyOrder" : 2400,
      "required" : true,
      "type" : "boolean",

```

```

        "exampleValue" : ""
    },
    "attributeMapperConfiguration" : {
        "title" : "Attribute Mapper Configuration",
        "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data store in the OpenAM.<br/><br/>Example: <code>OAuth2.0_attribute=local_attribute</code>",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : "given_name=givenName family_name=sn name=cn email=mail sub=uid"
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This class is used by the module to find the account from the attributes mapped by the Account Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.<br/>String constructor parameters can be provided by appending <code>|</code> separated values.",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "CreateAccount" : {
        "title" : "Create account if it does not exist",
        "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an account will be created dynamically.<br><br>If this is enabled, the account mapper could create the account dynamically if there is no account mapped. Before creating the account, a dialog prompting for a password and asking for an activation code can be shown if the parameter \"Prompt for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3 alternative options exist:<br/><br/><ol><li>The accounts need to have a user profile in the OpenAM User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
        "propertyOrder" : 1360,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br/>If not selected the users authenticated will be mapped by the parameters configured in the account mapper.<br/><br/><i>NB </i>If <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "attributeMappingClasses" : {
        "title" : "Attribute Mapper",

```


1.179.1.1. create

Usage:

```
am> create SocialAuthOpenIDModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "accountProvisioning" : {
      "type" : "object",
      "title" : "Account Provisioning",
      "propertyOrder" : 2,
      "properties" : {
        "accountMapperConfiguration" : {
          "title" : "Account Mapper Configuration",
          "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute configuration that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
          "propertyOrder" : 1600,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : "sub=uid"
        },
        "mapToAnonymousUser" : {
          "title" : "Map to anonymous user",
          "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br>If not selected the users authenticated will be mapped by the parameters configured in the account mapper.<br><br><i>If <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
          "propertyOrder" : 2000,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "accountProviderClass" : {
          "title" : "Account Provider",
          "description" : "Name of the class implementing the account provider.<br><br>This class is used by the module to find the account from the attributes mapped by the Account Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.<br><br>String constructor parameters can be provided by appending <code>|</code> separated values.",
          "propertyOrder" : 1400,

```

```

        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "enableRegistrationService" : {
        "title" : "Use IDM as Registration Service",
        "description" : "Whether to use IDM as an external Registration Service to complete
registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
        "propertyOrder" : 1350,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "promptPasswordFlag" : {
        "title" : "Prompt for password setting and activation code",
        "description" : "Users must set a password and complete the activation flow during dynamic
profile creation.<br><br>If this is enabled, the user must set a password before the system creates
an account dynamically and an activation code will be sent to the user's email address. The account
will be created only if the password and activation code are properly set. <br />If this is disabled,
the account will be created transparently without prompting the user.",
        "propertyOrder" : 1905,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "attributeMapperConfiguration" : {
        "title" : "Attribute Mapper Configuration",
        "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : "given_name=givenName family_name=sn name=cn email=mail sub=uid"
    },
    },
    "accountMapperClass" : {
        "title" : "Account Mapper",
        "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br><br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1500,
        "required" : true,
        "type" : "string",
        "exampleValue" :
"org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper|*|google-"
    },
    },

```

```

"saveAttributesInSession" : {
  "title" : "Save attributes in the session",
  "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
  "propertyOrder" : 2400,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"createAccount" : {
  "title" : "Create account if it does not exist",
  "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
  "propertyOrder" : 1360,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"attributeMappingClasses" : {
  "title" : "Attribute Mapper",
  "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
  "propertyOrder" : 1700,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" :
"org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper|uid|google-"
},
"anonymousUserName" : {
  "title" : "Anonymous User",
  "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that
will represent the anonymous user. This user account must already exist in the realm.",
  "propertyOrder" : 2100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"emailSettings" : {
  "type" : "object",
  "title" : "Email",

```

```
"propertyOrder" : 3,
"properties" : {
  "smtpSslEnabled" : {
    "title" : "SMTP SSL Enabled",
    "description" : "Tick this option if the SMTP Server provides SSL",
    "propertyOrder" : 1940,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "smtpHost" : {
    "title" : "SMTP host",
    "description" : "The mail host that will be used by the Email Gateway implementation",
    "propertyOrder" : 1920,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpFromAddress" : {
    "title" : "SMTP From address",
    "description" : "The email address on behalf of whom the messages will be sent",
    "propertyOrder" : 1945,
    "required" : true,
    "type" : "string",
    "exampleValue" : "info@forgerock.com"
  },
  "smtpUsername" : {
    "title" : "SMTP User Name",
    "description" : "If the SMTP Service requires authentication, configure the user name here",
    "propertyOrder" : 1930,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpPort" : {
    "title" : "SMTP port",
    "description" : "The TCP port that will be used by the SMTP gateway",
    "propertyOrder" : 1925,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpPassword" : {
    "title" : "SMTP User Password",
    "description" : "The Password of the SMTP User Name",
    "propertyOrder" : 1935,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "emailGateway" : {
    "title" : "Mail Server Gateway implementation class",
    "description" : "The class used by the module to send email.<br><br>This class is used by the module to send email. A custom implementation can be provided.<br><br>The custom implementation must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
    "propertyOrder" : 1915,
    "required" : true,
    "type" : "string",
```

```

    "exampleValue" : ""
  },
  "emailAttribute" : {
    "title" : "Email attribute in the Response",
    "description" : "Attribute from the response used to send activation code emails.<br><br>The
attribute in the response from the profile service of the Provider that contains the email address of
the authenticated user. This address will be used to send an email with an activation code when the
accounts are allowed to be created dynamically.",
    "propertyOrder" : 1910,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "tokenEndpoint" : {
      "title" : "Access Token Endpoint URL",
      "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : "https://www.googleapis.com/oauth2/v4/token"
    },
    "subjectProperty" : {
      "title" : "Subject Property",
      "description" : "Property used to identify which attribute an auth server identifies a user
by.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : "sub"
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "userInfoEndpoint" : {
      "title" : "User Profile Service URL",
      "description" : "User profile information URL<br><br>This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return
JSON objects in response",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : "https://www.googleapis.com/oauth2/v3/userinfo"
    }
  }
},

```

```

"authorizeEndpoint" : {
  "title" : "Authentication Endpoint URL",
  "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth
authentication provided by the OAuth Identity Provider",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "string",
  "exampleValue" : "https://accounts.google.com/o/oauth2/v2/auth"
},
"logoutServiceUrl" : {
  "title" : "OAuth 2.0 Provider Logout Service",
  "description" : "The URL of the Identity Provider's
logout service.<br><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
  "propertyOrder" : 2150,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"clientId" : {
  "title" : "Client Id",
  "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"usesBasicAuth" : {
  "title" : "Use Basic Auth",
  "description" : "When enabled, the client will use basic auth for authenticating with the
social auth provider. Enabled by default.",
  "propertyOrder" : 1200,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"logoutBehaviour" : {
  "title" : "Logout Options",
  "description" : "Specify logout behavior.<br><br>The following options are available
for logging out of the OAuth 2.0 Provider when the user logs out of AM:<br><ul><li>prompt:
Ask the user whether to log out from the OAuth 2.0 Provider</li><li>logout: Log out from
the OAuth 2.0 Provider without asking the user</li><li>donotlogout: Do not log out the
user from the OAuth 2.0 Provider</li></ul><br><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
  "propertyOrder" : 2155,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"issuerName" : {
  "title" : "Token Issuer",

```

```

    "description" : "Required when the 'openid' scope is included. Value must match the iss field in issued ID Token<br/>e.g. accounts.google.com<br/><br/>The issuer value MUST be provided when OAuth 2.0 Mix-Up Mitigation is enabled.",
    "propertyOrder" : 2700,
    "required" : true,
    "type" : "string",
    "exampleValue" : "https://accounts.google.com"
  },
  "scopeDelimiter" : {
    "title" : "Scope Delimiter",
    "description" : "Delimiter used to separate scope values. Default value is space.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter<br/><br/>For more information on the OAuth client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "mixUpMitigation" : {
    "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
    "description" : "Enables OAuth 2.0 mix-up mitigation<br/><br/>The authorization server must support the <a href=\"https://tools.ietf.org/html/draft-ietf-oauth-mix-up-mitigation-01#section-3.1\">OAuth 2.0 Mix-Up Mitigation draft</a>, otherwise OpenAM will fail to validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
    "propertyOrder" : 2800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ssoProxyUrl" : {
    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br/><br/>This URL should only be changed from the default, if an external server is performing the GET to POST proxying. The default is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "scope" : {
    "title" : "Scope",
    "description" : "OAuth scope; list of user profile properties<br/><br/>According to the OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the client application requires. The list depends on the permissions that the resource owner grants to the client application.<br/><br/>Some authorization servers use non-standard separators for scopes. For example, Facebook takes a comma-separated list.<br/><br/>/",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {

```


--id

The unique identifier for the resource.

1.179.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthOpenIDModule --realm Realm --actionName getAllTypes
```

1.179.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthOpenIDModule --realm Realm --actionName getCreatableTypes
```

1.179.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthOpenIDModule --realm Realm --actionName nextdescendents
```

1.179.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SocialAuthOpenIDModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.179.1.7. read

Usage:

```
am> read SocialAuthOpenIDModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.179.1.8. update

Usage:

```
am> update SocialAuthOpenIDModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "accountProvisioning" : {
      "type" : "object",
      "title" : "Account Provisioning",
      "propertyOrder" : 2,
      "properties" : {
        "accountMapperConfiguration" : {
          "title" : "Account Mapper Configuration",
          "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute configuration that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
          "propertyOrder" : 1600,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : "sub=uid"
        },
        "mapToAnonymousUser" : {
          "title" : "Map to anonymous user",
          "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br>If not selected the users authenticated will be mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
          "propertyOrder" : 2000,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        }
      },
      "accountProviderClass" : {
        "title" : "Account Provider",
```

```

    "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "enableRegistrationService" : {
    "title" : "Use IDM as Registration Service",
    "description" : "Whether to use IDM as an external Registration Service to complete
registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
    "propertyOrder" : 1350,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "promptPasswordFlag" : {
    "title" : "Prompt for password setting and activation code",
    "description" : "Users must set a password and complete the activation flow during dynamic
profile creation.<br><br>If this is enabled, the user must set a password before the system creates
an account dynamically and an activation code will be sent to the user's email address. The account
will be created only if the password and activation code are properly set. <br />If this is disabled,
the account will be created transparently without prompting the user.",
    "propertyOrder" : 1905,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "attributeMapperConfiguration" : {
    "title" : "Attribute Mapper Configuration",
    "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
    "propertyOrder" : 1800,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : "given_name=givenName family_name=sn name=cn email=mail sub=uid"
  },
  "accountMapperClass" : {
    "title" : "Account Mapper",
    "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",

```

```

        "propertyOrder" : 1500,
        "required" : true,
        "type" : "string",
        "exampleValue" :
"org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper|*|google-"
    },
    "saveAttributesInSession" : {
        "title" : "Save attributes in the session",
        "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
        "propertyOrder" : 2400,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "createAccount" : {
        "title" : "Create account if it does not exist",
        "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
        "propertyOrder" : 1360,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    },
    "attributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" :
"org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper|uid|google-"
    },
    "anonymousUserName" : {
        "title" : "Anonymous User",
        "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that
will represent the anonymous user. This user account must already exist in the realm.",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }

```

```
    }
  },
  "emailSettings" : {
    "type" : "object",
    "title" : "Email",
    "propertyOrder" : 3,
    "properties" : {
      "smtpSslEnabled" : {
        "title" : "SMTP SSL Enabled",
        "description" : "Tick this option if the SMTP Server provides SSL",
        "propertyOrder" : 1940,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "smtpHost" : {
        "title" : "SMTP host",
        "description" : "The mail host that will be used by the Email Gateway implementation",
        "propertyOrder" : 1920,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "smtpFromAddress" : {
        "title" : "SMTP From address",
        "description" : "The email address on behalf of whom the messages will be sent",
        "propertyOrder" : 1945,
        "required" : true,
        "type" : "string",
        "exampleValue" : "info@forgerock.com"
      },
      "smtpUsername" : {
        "title" : "SMTP User Name",
        "description" : "If the SMTP Service requires authentication, configure the user name here",
        "propertyOrder" : 1930,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "smtpPort" : {
        "title" : "SMTP port",
        "description" : "The TCP port that will be used by the SMTP gateway",
        "propertyOrder" : 1925,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      },
      "smtpPassword" : {
        "title" : "SMTP User Password",
        "description" : "The Password of the SMTP User Name",
        "propertyOrder" : 1935,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
      },
      "emailGateway" : {
        "title" : "Mail Server Gateway implementation class",
```

```

    "description" : "The class used by the module to send email.<br><br>This class is used by
the module to send email. A custom implementation can be provided.<br><br>The custom implementation
must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
    "propertyOrder" : 1915,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "emailAttribute" : {
    "title" : "Email attribute in the Response",
    "description" : "Attribute from the response used to send activation code emails.<br><br>The
attribute in the response from the profile service of the Provider that contains the email address of
the authenticated user. This address will be used to send an email with an activation code when the
accounts are allowed to be created dynamically.",
    "propertyOrder" : 1910,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "tokenEndpoint" : {
      "title" : "Access Token Endpoint URL",
      "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : "https://www.googleapis.com/oauth2/v4/token"
    },
    "subjectProperty" : {
      "title" : "Subject Property",
      "description" : "Property used to identify which attribute an auth server identifies a user
by.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : "sub"
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",

```

```

        "description" : "User profile information URL<br><br>This URL endpoint provides user profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return JSON objects in response",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "string",
        "exampleValue" : "https://www.googleapis.com/oauth2/v3/userinfo"
    },
    "authorizeEndpoint" : {
        "title" : "Authentication Endpoint URL",
        "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "string",
        "exampleValue" : "https://accounts.google.com/o/oauth2/v2/auth"
    },
    "logoutServiceUrl" : {
        "title" : "OAuth 2.0 Provider Logout Service",
        "description" : "The URL of the Identity Provider's logout service.<br><br>To enable IdP logout, you must also add <code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the <em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post Authentication Processing.",
        "propertyOrder" : 2150,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "clientId" : {
        "title" : "Client Id",
        "description" : "OAuth client_id parameter<br><br>For more information on the OAuth client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "usesBasicAuth" : {
        "title" : "Use Basic Auth",
        "description" : "When enabled, the client will use basic auth for authenticating with the social auth provider. Enabled by default.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "logoutBehaviour" : {
        "title" : "Logout Options",
        "description" : "Specify logout behavior.<br><br>The following options are available for logging out of the OAuth 2.0 Provider when the user logs out of AM:<br><br><ul><li>prompt: Ask the user whether to log out from the OAuth 2.0 Provider</li><li>logout: Log out from the OAuth 2.0 Provider without asking the user</li><li>donotlogout: Do not log out the user from the OAuth 2.0 Provider</li></ul><br><br>To enable IdP logout, you must also add <code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the <em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post Authentication Processing.",
        "propertyOrder" : 2155,
    }

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "issuerName" : {
    "title" : "Token Issuer",
    "description" : "Required when the 'openid' scope is included. Value must match the iss
field in issued ID Token<br/>e.g. accounts.google.com<br/><br/>The issuer value MUST be provided when
OAuth 2.0 Mix-Up Mitigation is enabled.",
    "propertyOrder" : 2700,
    "required" : true,
    "type" : "string",
    "exampleValue" : "https://accounts.google.com"
  },
  "scopeDelimiter" : {
    "title" : "Scope Delimiter",
    "description" : "Delimiter used to separate scope values. Default value is space.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter<br/><br/>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "mixUpMitigation" : {
    "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
    "description" : "Enables OAuth 2.0 mix-up mitigation<br/><br/>The authorization
server must support the <a href=\"https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
mitigation-01#section-3.1\">OAuth 2.0 Mix-Up Mitigation draft</a>, otherwise OpenAM will fail to
validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make
sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
    "propertyOrder" : 2800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ssoProxyUrl" : {
    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br/><br/>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "scope" : {
    "title" : "Scope",
    "description" : "OAuth scope; list of user profile properties<br/><br/>According to the OAuth
2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the

```


client application requires. The list depends on the permissions that the resource owner grants to the client application.

 Some authorization servers use non-standard separators for scopes. For example, Facebook takes a comma-separated list.


```
"propertyOrder" : 900,
"required" : true,
"items" : {
  "type" : "string"
},
"type" : "array",
"exampleValue" : "profile email openid"
},
"provider" : {
  "title" : "Social Provider",
  "description" : "Social Provider for which this module is being setup.",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : "Google"
}
},
"openId" : {
  "type" : "object",
  "title" : "OpenID Connect",
  "propertyOrder" : 1,
  "properties" : {
    "cryptoContextValue" : {
      "title" : "OpenID Connect validation configuration value",
      "description" : "Required when the 'openid' scope is included. The discovery url, or jwk url, or the client_secret, corresponding to the selection above.<br/><br/>If discovery or jwk url entered, entry must be in valid url format, <br/>e.g. https://accounts.google.com/.well-known/openid-configuration<br/><i>NB </i>If client_secret entered, entry is ignored and the value of the Client Secret is used.",
      "propertyOrder" : 2600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "cryptoContextType" : {
      "title" : "OpenID Connect validation configuration type",
      "description" : "Required when the 'openid' scope is included. Please select either 1. the issuer discovery url, 2. the issuer jwk url, or 3. the client_secret.",
      "propertyOrder" : 2500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
}
```

1.179.2. Global Operations

Resource path: </global-config/authentication/modules/authSocialOpenID>

Resource version: 1.0

1.179.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthOpenIDModule --global --actionName getAllTypes
```

1.179.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthOpenIDModule --global --actionName getCreatableTypes
```

1.179.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthOpenIDModule --global --actionName nextdescendents
```

1.179.2.4. read

Usage:

```
am> read SocialAuthOpenIDModule --global
```

1.179.2.5. update

Usage:

```
am> update SocialAuthOpenIDModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "core" : {
```

```

"type" : "object",
"title" : "Core",
"propertyOrder" : 0,
"properties" : {
  "usesBasicAuth" : {
    "title" : "Use Basic Auth",
    "description" : "When enabled, the client will use basic auth for authenticating with
the social auth provider. Enabled by default.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "logoutServiceUrl" : {
    "title" : "OAuth 2.0 Provider Logout Service",
    "description" : "The URL of the Identity Provider's
logout service.<br><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
    "propertyOrder" : 2150,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "logoutBehaviour" : {
    "title" : "Logout Options",
    "description" : "Specify logout behavior.<br><br>The following options are
available for logging out of the OAuth 2.0 Provider when the user logs out of AM:<br>
<ul><li>prompt: Ask the user whether to log out from the OAuth 2.0 Provider</li><li>logout:
Log out from the OAuth 2.0 Provider without asking the user</li><li>doNotLogout: Do not log
out the user from the OAuth 2.0 Provider</li></ul><br>To enable IdP logout, you must also add
<code>org.forgerock.openam.authentication.modules.oauth2.OAuth2PostAuthnPlugin</code> to the
<em>Authentication Post Processing Classes</em> setting. Navigate to Authentication > Settings > Post
Authentication Processing.",
    "propertyOrder" : 2155,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "mixUpMitigation" : {
    "title" : "OAuth 2.0 Mix-Up Mitigation enabled",
    "description" : "Enables OAuth 2.0 mix-up mitigation<br><br>The authorization
server must support the <a href=\"https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
mitigation-01#section-3.1\">OAuth 2.0 Mix-Up Mitigation draft</a>, otherwise OpenAM will fail to
validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make
sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
    "propertyOrder" : 2800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL<br><br>This URL endpoint provides user
profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should
return JSON objects in response",
    "propertyOrder" : 800,
    "required" : true,

```

```

    "type" : "string",
    "exampleValue" : "https://www.googleapis.com/oauth2/v3/userinfo"
  },
  "authorizeEndpoint" : {
    "title" : "Authentication Endpoint URL",
    "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for
OAuth authentication provided by the OAuth Identity Provider",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : "https://accounts.google.com/o/oauth2/v2/auth"
  },
  "subjectProperty" : {
    "title" : "Subject Property",
    "description" : "Property used to identify which attribute an auth server identifies a
user by.",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : "sub"
  },
  "scopeDelimiter" : {
    "title" : "Scope Delimiter",
    "description" : "Delimiter used to separate scope values. Default value is space.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "provider" : {
    "title" : "Social Provider",
    "description" : "Social Provider for which this module is being setup.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : "Google"
  },
  "ssoProxyUrl" : {
    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenEndpoint" : {
    "title" : "Access Token Endpoint URL",
    "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : "https://www.googleapis.com/oauth2/v4/token"
  },
  "clientSecret" : {
    "title" : "Client Secret",

```

```

    "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "issuerName" : {
    "title" : "Token Issuer",
    "description" : "Required when the 'openid' scope is included. Value must match the iss
field in issued ID Token<br>e.g. accounts.google.com<br><br>The issuer value MUST be provided when
OAuth 2.0 Mix-Up Mitigation is enabled.",
    "propertyOrder" : 2700,
    "required" : true,
    "type" : "string",
    "exampleValue" : "https://accounts.google.com"
  },
  "clientId" : {
    "title" : "Client Id",
    "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "scope" : {
    "title" : "Scope",
    "description" : "OAuth scope; list of user profile properties<br><br>According to the
OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that
the client application requires. The list depends on the permissions that the resource owner grants
to the client application.<br><br> Some authorization servers use non-standard separators for
scopes. For example, Facebook takes a comma-separated list.<br><br>",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : "profile email openid"
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
},
"emailSettings" : {
  "type" : "object",
  "title" : "Email",

```

```

"propertyOrder" : 3,
"properties" : {
  "smtpFromAddress" : {
    "title" : "SMTP From address",
    "description" : "The email address on behalf of whom the messages will be sent",
    "propertyOrder" : 1945,
    "required" : true,
    "type" : "string",
    "exampleValue" : "info@forgerock.com"
  },
  "smtpSslEnabled" : {
    "title" : "SMTP SSL Enabled",
    "description" : "Tick this option if the SMTP Server provides SSL",
    "propertyOrder" : 1940,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "emailAttribute" : {
    "title" : "Email attribute in the Response",
    "description" : "Attribute from the response used to send activation code
emails.<br><br>The attribute in the response from the profile service of the Provider that contains
the email address of the authenticated user. This address will be used to send an email with an
activation code when the accounts are allowed to be created dynamically.",
    "propertyOrder" : 1910,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "emailGateway" : {
    "title" : "Mail Server Gateway implementation class",
    "description" : "The class used by the module to send
email.<br><br>This class is used by the module to send email. A custom
implementation can be provided.<br><br>The custom implementation must implement the
<code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
    "propertyOrder" : 1915,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpPassword" : {
    "title" : "SMTP User Password",
    "description" : "The Password of the SMTP User Name",
    "propertyOrder" : 1935,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "smtpHost" : {
    "title" : "SMTP host",
    "description" : "The mail host that will be used by the Email Gateway implementation",
    "propertyOrder" : 1920,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpUsername" : {
    "title" : "SMTP User Name",

```

```

    "description" : "If the SMTP Service requires authentication, configure the user name
here",
    "propertyOrder" : 1930,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpPort" : {
    "title" : "SMTP port",
    "description" : "The TCP port that will be used by the SMTP gateway",
    "propertyOrder" : 1925,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"accountProvisioning" : {
  "type" : "object",
  "title" : "Account Provisioning",
  "propertyOrder" : 2,
  "properties" : {
    "enableRegistrationService" : {
      "title" : "Use IDM as Registration Service",
      "description" : "Whether to use IDM as an external Registration Service to
complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
      "propertyOrder" : 1350,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "saveAttributesInSession" : {
      "title" : "Save attributes in the session",
      "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
      "propertyOrder" : 2400,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "accountProviderClass" : {
      "title" : "Account Provider",
      "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br></String constructor parameters can be provided by appending <code>|</code> separated
values.",
      "propertyOrder" : 1400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "accountMapperClass" : {
      "title" : "Account Mapper",
      "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information

```

```

received from the OAuth Identity Provider into OpenAM.<br/><br/>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br/>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" :
"org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper|*|google-"
  },
  "createAccount" : {
    "title" : "Create account if it does not exist",
    "description" : "If the OAuth2 account does not exist in the local OpenAM data store,
an account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
    "propertyOrder" : 1360,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "mapToAnonymousUser" : {
    "title" : "Map to anonymous user",
    "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "attributeMappingClasses" : {
    "title" : "Attribute Mapper",
    "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1700,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",

```



```

        "exampleValue" :
"org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper|uid|google-"
    },
    "promptPasswordFlag" : {
        "title" : "Prompt for password setting and activation code",
        "description" : "Users must set a password and complete the activation flow during
dynamic profile creation.<br><br>If this is enabled, the user must set a password before the system
creates an account dynamically and an activation code will be sent to the user's email address. The
account will be created only if the password and activation code are properly set. <br />If this is
disabled, the account will be created transparently without prompting the user.",
        "propertyOrder" : 1905,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "attributeMapperConfiguration" : {
        "title" : "Attribute Mapper Configuration",
        "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : "given_name=givenName family_name=sn name=cn email=mail sub=uid"
    },
    "accountMapperConfiguration" : {
        "title" : "Account Mapper Configuration",
        "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
        "propertyOrder" : 1600,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : "sub=uid"
    },
    "anonymousUserName" : {
        "title" : "Anonymous User",
        "description" : "Username of the OpenAM anonymous user<br><br>The username of the user
that will represent the anonymous user. This user account must already exist in the realm.",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"openId" : {
    "type" : "object",
    "title" : "OpenID Connect",
    "propertyOrder" : 1,
    "properties" : {

```


--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "accountProvisioning" : {
      "type" : "object",
      "title" : "Account Provisioning",
      "propertyOrder" : 1,
      "properties" : {
        "mapToAnonymousUser" : {
          "title" : "Map to anonymous user",
          "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br>If not selected the users authenticated will be mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
          "propertyOrder" : 2000,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "enableRegistrationService" : {
          "title" : "Use IDM as Registration Service",
          "description" : "Whether to use IDM as an external Registration Service to complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br><ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume authentication after registration in IDM is complete.</li></ul>",
          "propertyOrder" : 1350,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "accountMapperClass" : {
          "title" : "Account Mapper",
          "description" : "Name of the class implementing the attribute mapping for the account search.<br><br>This class is used by the module to map from the account information received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.<br>Provided implementations are:<ul><li><code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</li><li><code>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</li></ul>String constructor parameters can be provided by appending <code>|</code> separated values.",
          "propertyOrder" : 1500,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      },
        "anonymousUserName" : {
          "title" : "Anonymous User",
          "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that will represent the anonymous user. This user account must already exist in the realm.",
          "propertyOrder" : 2100,
          "required" : true,
          "type" : "string",

```

```

        "exampleValue" : ""
    },
    "attributeMapperConfiguration" : {
        "title" : "Attribute Mapper Configuration",
        "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</code>",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "createAccount" : {
        "title" : "Create account if it does not exist",
        "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an account will be created dynamically.<br><br>If this is enabled, the account mapper could create the account dynamically if there is no account mapped. Before creating the account, a dialog prompting for a password and asking for an activation code can be shown if the parameter \"Prompt for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3 alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
        "propertyOrder" : 1360,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "attributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom attribute mapper can be provided.<br><br>A custom attribute mapper must implement the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.<br>Provided implementations are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</code> separated values.",
        "propertyOrder" : 1700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This class is used by the module to find the account from the attributes mapped by the Account Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.<br>String constructor parameters can be provided by appending <code>|</code> separated values.",
        "propertyOrder" : 1400,
    }
}

```

```

        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "accountMapperConfiguration" : {
        "title" : "Account Mapper Configuration",
        "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
        "propertyOrder" : 1600,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "saveAttributesInSession" : {
        "title" : "Save attributes in the session",
        "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
        "propertyOrder" : 2400,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"core" : {
    "type" : "object",
    "title" : "Core",
    "propertyOrder" : 0,
    "properties" : {
        "subjectProperty" : {
            "title" : "Subject Property",
            "description" : "Property used to identify which attribute an auth server identifies a user
by.",
            "propertyOrder" : 1100,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "authorizeEndpoint" : {
            "title" : "Authentication Endpoint URL",
            "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth
authentication provided by the OAuth Identity Provider",
            "propertyOrder" : 600,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "provider" : {
            "title" : "Social Provider",
            "description" : "Social Provider for which this module is being setup.",
            "propertyOrder" : 200,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}

```

```
    },
    "userInfoEndpoint" : {
      "title" : "User Profile Service URL",
      "description" : "User profile information URL<br><br>This URL endpoint provides user profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return JSON objects in response",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "tokenEndpoint" : {
      "title" : "Access Token Endpoint URL",
      "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "clientSecret" : {
      "title" : "Client Secret",
      "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "requestTokenEndpoint" : {
      "title" : "Request Token Endpoint URL",
      "description" : "OAuth request token endpoint URL<br><br>This is the URL endpoint for OAuth request token provided by the OAuth Identity Provider",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "clientId" : {
      "title" : "Client Id",
      "description" : "OAuth client_id parameter<br><br>For more information on the OAuth client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
```

```
    "exampleValue" : ""
  },
  "usesBasicAuth" : {
    "title" : "Use Basic Auth",
    "description" : "When enabled, the client will use basic auth for authenticating with the
social auth provider. Enabled by default.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ssoProxyUrl" : {
    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}
```

1.180.1.2. delete

Usage:

```
am> delete SocialAuthTwitterModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.180.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthTwitterModule --realm Realm --actionName getAllTypes
```

1.180.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthTwitterModule --realm Realm --actionName getCreatableTypes
```

1.180.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthTwitterModule --realm Realm --actionName nextdescendents
```

1.180.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SocialAuthTwitterModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.180.1.7. read

Usage:

```
am> read SocialAuthTwitterModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.180.1.8. update

Usage:

```
am> update SocialAuthTwitterModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "accountProvisioning" : {
      "type" : "object",
      "title" : "Account Provisioning",
      "propertyOrder" : 1,
      "properties" : {
        "mapToAnonymousUser" : {
          "title" : "Map to anonymous user",
          "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br>If not selected the users authenticated will be mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
          "propertyOrder" : 2000,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "enableRegistrationService" : {
          "title" : "Use IDM as Registration Service",
          "description" : "Whether to use IDM as an external Registration Service to complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br><ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume authentication after registration in IDM is complete.</li></ul>",
          "propertyOrder" : 1350,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "accountMapperClass" : {
          "title" : "Account Mapper",
          "description" : "Name of the class implementing the attribute mapping for the account search.<br><br>This class is used by the module to map from the account information received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.<br>Provided implementations are:<ul><li><code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</li><li><code>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</li></ul>String constructor parameters can be provided by appending <code>|</code> separated values.",
          "propertyOrder" : 1500,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      },
      "anonymousUserName" : {
        "title" : "Anonymous User",
        "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that will represent the anonymous user. This user account must already exist in the realm.",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "string",

```

```

        "exampleValue" : ""
    },
    "attributeMapperConfiguration" : {
        "title" : "Attribute Mapper Configuration",
        "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</code>",
        "propertyOrder" : 1800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "createAccount" : {
        "title" : "Create account if it does not exist",
        "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an account will be created dynamically.<br><br>If this is enabled, the account mapper could create the account dynamically if there is no account mapped. Before creating the account, a dialog prompting for a password and asking for an activation code can be shown if the parameter \"Prompt for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3 alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
        "propertyOrder" : 1360,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "attributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom attribute mapper can be provided.<br><br>A custom attribute mapper must implement the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.<br>Provided implementations are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</code> separated values.",
        "propertyOrder" : 1700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This class is used by the module to find the account from the attributes mapped by the Account Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.<br>String constructor parameters can be provided by appending <code>|</code> separated values.",
        "propertyOrder" : 1400,
    }
}

```

```

        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "accountMapperConfiguration" : {
        "title" : "Account Mapper Configuration",
        "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
        "propertyOrder" : 1600,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "saveAttributesInSession" : {
        "title" : "Save attributes in the session",
        "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
        "propertyOrder" : 2400,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"core" : {
    "type" : "object",
    "title" : "Core",
    "propertyOrder" : 0,
    "properties" : {
        "subjectProperty" : {
            "title" : "Subject Property",
            "description" : "Property used to identify which attribute an auth server identifies a user
by.",
            "propertyOrder" : 1100,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "authorizeEndpoint" : {
            "title" : "Authentication Endpoint URL",
            "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth
authentication provided by the OAuth Identity Provider",
            "propertyOrder" : 600,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "provider" : {
            "title" : "Social Provider",
            "description" : "Social Provider for which this module is being setup.",
            "propertyOrder" : 200,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}

```

```
},
"userInfoEndpoint" : {
  "title" : "User Profile Service URL",
  "description" : "User profile information URL<br><br>This URL endpoint provides user profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return JSON objects in response",
  "propertyOrder" : 800,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"tokenEndpoint" : {
  "title" : "Access Token Endpoint URL",
  "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"clientSecret" : {
  "title" : "Client Secret",
  "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"requestTokenEndpoint" : {
  "title" : "Request Token Endpoint URL",
  "description" : "OAuth request token endpoint URL<br><br>This is the URL endpoint for OAuth request token provided by the OAuth Identity Provider",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"clientId" : {
  "title" : "Client Id",
  "description" : "OAuth client_id parameter<br><br>For more information on the OAuth client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
```

```
    "exampleValue" : ""
  },
  "usesBasicAuth" : {
    "title" : "Use Basic Auth",
    "description" : "When enabled, the client will use basic auth for authenticating with the
social auth provider. Enabled by default.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ssoProxyUrl" : {
    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
}
```

1.180.2. Global Operations

Resource path: `/global-config/authentication/modules/authSocialTwitter`

Resource version: `1.0`

1.180.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthTwitterModule --global --actionName getAllTypes
```

1.180.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthTwitterModule --global --actionName getCreatableTypes
```

1.180.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthTwitterModule --global --actionName nextdescendents
```

1.180.2.4. read

Usage:

```
am> read SocialAuthTwitterModule --global
```

1.180.2.5. update

Usage:

```
am> update SocialAuthTwitterModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "core" : {
          "type" : "object",
          "title" : "Core",
          "propertyOrder" : 0,
          "properties" : {
            "subjectProperty" : {
              "title" : "Subject Property",
              "description" : "Property used to identify which attribute an auth server identifies a
user by.",
              "propertyOrder" : 1100,
              "required" : true,
              "type" : "string",
              "exampleValue" : ""
            },
            "requestTokenEndpoint" : {
              "title" : "Request Token Endpoint URL",
              "description" : "OAuth request token endpoint URL<br><br>This is the URL endpoint for
OAuth request token provided by the OAuth Identity Provider",
              "propertyOrder" : 600,
              "required" : true,
              "type" : "string",
              "exampleValue" : ""
            },
            "ssoProxyUrl" : {
              "title" : "Proxy URL",
              "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",

```

```

    "propertyOrder" : 1300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenEndpoint" : {
    "title" : "Access Token Endpoint URL",
    "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "usesBasicAuth" : {
    "title" : "Use Basic Auth",
    "description" : "When enabled, the client will use basic auth for authenticating with
the social auth provider. Enabled by default.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL<br><br>This URL endpoint provides user
profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should
return JSON objects in response",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "clientId" : {
    "title" : "Client Id",

```

```

        "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
        client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
        \"_blank\">RFC 6749</a>, section 2.3.1",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "authorizeEndpoint" : {
        "title" : "Authentication Endpoint URL",
        "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for
        OAuth authentication provided by the OAuth Identity Provider",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "provider" : {
        "title" : "Social Provider",
        "description" : "Social Provider for which this module is being setup.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"accountProvisioning" : {
    "type" : "object",
    "title" : "Account Provisioning",
    "propertyOrder" : 1,
    "properties" : {
        "mapToAnonymousUser" : {
            "title" : "Map to anonymous user",
            "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
            users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
            anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
            mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
            it does not exist</i> is enabled, that parameter takes precedence.",
            "propertyOrder" : 2000,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "accountMapperClass" : {
            "title" : "Account Mapper",
            "description" : "Name of the class implementing the attribute mapping for the
            account search.<br><br>This class is used by the module to map from the account information
            received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
            the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
            interface.<br><br>Provided implementations
            are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
            li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
            using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
            code> separated values.",
            "propertyOrder" : 1500,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}

```



```

    },
    "anonymousUserName" : {
      "title" : "Anonymous User",
      "description" : "Username of the OpenAM anonymous user<br><br>The username of the user
that will represent the anonymous user. This user account must already exist in the realm.",
      "propertyOrder" : 2100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "createAccount" : {
      "title" : "Create account if it does not exist",
      "description" : "If the OAuth2 account does not exist in the local OpenAM data store,
an account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
      "propertyOrder" : 1360,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    },
    "attributeMappingClasses" : {
      "title" : "Attribute Mapper",
      "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br><br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
      "propertyOrder" : 1700,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    },
    "accountMapperConfiguration" : {
      "title" : "Account Mapper Configuration",
      "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
      "propertyOrder" : 1600,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    },
  },

```

```

        "attributeMapperConfiguration" : {
            "title" : "Attribute Mapper Configuration",
            "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
            "propertyOrder" : 1800,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "accountProviderClass" : {
            "title" : "Account Provider",
            "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
            "propertyOrder" : 1400,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "enableRegistrationService" : {
            "title" : "Use IDM as Registration Service",
            "description" : "Whether to use IDM as an external Registration Service to
complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
            "propertyOrder" : 1350,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "saveAttributesInSession" : {
            "title" : "Save attributes in the session",
            "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
            "propertyOrder" : 2400,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        }
    }
}
    },
    "type" : "object",
    "title" : "Realm Defaults"
}
}
}

```

1.181. SocialAuthVKontakteModule

1.181.1. Realm Operations

Resource path: `/realm-config/authentication/modules/authSocialVk`

Resource version: `1.0`

1.181.1.1. create

Usage:

```
am> create SocialAuthVKontakteModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "emailSettings" : {
      "type" : "object",
      "title" : "Email",
      "propertyOrder" : 2,
      "properties" : {
        "smtpFromAddress" : {
          "title" : "SMTP From address",
          "description" : "The email address on behalf of whom the messages will be sent",
          "propertyOrder" : 1645,
          "required" : true,
          "type" : "string",
          "exampleValue" : "info@forgerock.com"
        },
        "smtpUsername" : {
          "title" : "SMTP User Name",
          "description" : "If the SMTP Service requires authentication, configure the user name here",
          "propertyOrder" : 1630,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "smtpPort" : {
      "title" : "SMTP port",
      "description" : "The TCP port that will be used by the SMTP gateway",
      "propertyOrder" : 1625,
      "required" : true,
    }
  }
}
```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "emailAttribute" : {
    "title" : "Email attribute in the Response",
    "description" : "Attribute from the response used to send activation code emails.<br><br>The attribute in the response from the profile service of the Provider that contains the email address of the authenticated user. This address will be used to send an email with an activation code when the accounts are allowed to be created dynamically.",
    "propertyOrder" : 1610,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpSslEnabled" : {
    "title" : "SMTP SSL Enabled",
    "description" : "Tick this option if the SMTP Server provides SSL",
    "propertyOrder" : 1640,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "smtpHost" : {
    "title" : "SMTP host",
    "description" : "The mail host that will be used by the Email Gateway implementation",
    "propertyOrder" : 1620,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "emailGateway" : {
    "title" : "Mail Server Gateway implementation class",
    "description" : "The class used by the module to send email.<br><br>This class is used by the module to send email. A custom implementation can be provided.<br><br>The custom implementation must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
    "propertyOrder" : 1615,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpPassword" : {
    "title" : "SMTP User Password",
    "description" : "The Password of the SMTP User Name",
    "propertyOrder" : 1635,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }
}
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "provider" : {
      "title" : "Social Provider",
      "description" : "Social Provider for which this module is being setup.",

```

```

        "propertyOrder" : 100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "authorizeEndpoint" : {
        "title" : "Authentication Endpoint URL",
        "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "tokenEndpoint" : {
        "title" : "Access Token Endpoint URL",
        "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "scope" : {
        "title" : "Scope",
        "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the client application requires. The list depends on the permissions that the resource owner grants to the client application.<br><br>Some authorization servers use non-standard separators for scopes. For example, Facebook takes a comma-separated list.<br><br>",
        "propertyOrder" : 800,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "apiVersion" : {
        "title" : "API Version",
        "description" : "Specifies the version of the auth server API",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "clientSecret" : {
        "title" : "Client Secret",
        "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
        "propertyOrder" : 300,
        "required" : true,
        "type" : "string",
        "format" : "password",
        "exampleValue" : ""
    },
    "userInfoEndpoint" : {

```

```

    "title" : "User Profile Service URL",
    "description" : "User profile information URL<br><br>This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return
JSON objects in response",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientId" : {
    "title" : "Client Id",
    "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "ssoProxyUrl" : {
    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "forgerock-am-auth-socialauthvk-auth-level" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "subjectProperty" : {
    "title" : "Subject Property",
    "description" : "Property used to identify which attribute an auth server identifies a user
by.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"accountProvisioning" : {
  "type" : "object",
  "title" : "Account Provisioning",
  "propertyOrder" : 1,
  "properties" : {
    "attributeMappingClasses" : {
      "title" : "Attribute Mapper",
      "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom

```

attribute mapper can be provided.

A custom attribute mapper must implement the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.
Provided implementations are:<code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</code>/li><code>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</code> (can only be used when using the openid scope)String constructor parameters can be provided by appending <code>|</code> separated values.",

```

    "propertyOrder" : 1400,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "promptPasswordFlag" : {
    "title" : "Prompt for password setting and activation code",
    "description" : "Users must set a password and complete the activation flow during dynamic profile creation.<br><br>If this is enabled, the user must set a password before the system creates an account dynamically and an activation code will be sent to the user's email address. The account will be created only if the password and activation code are properly set. <br />If this is disabled, the account will be created transparently without prompting the user.",
    "propertyOrder" : 1605,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saveAttributesInSession" : {
    "title" : "Save attributes in the session",
    "description" : "If this option is enabled, the attributes configured in the attribute mapper will be saved into the OpenAM session",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "accountMapperConfiguration" : {
    "title" : "Account Mapper Configuration",
    "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute configuration that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "anonymousUserName" : {
    "title" : "Anonymous User",
    "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that will represent the anonymous user. This user account must already exist in the realm.",
    "propertyOrder" : 1800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
},

```

```

"accountProviderClass" : {
  "title" : "Account Provider",
  "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
  "propertyOrder" : 1100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"createAccount" : {
  "title" : "Create account if it does not exist",
  "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
  "propertyOrder" : 1160,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"attributeMapperConfiguration" : {
  "title" : "Attribute Mapper Configuration",
  "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
  "propertyOrder" : 1500,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"accountMapperClass" : {
  "title" : "Account Mapper",
  "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
  "propertyOrder" : 1200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"enableRegistrationService" : {

```



```
        "title" : "Use IDM as Registration Service",
        "description" : "Whether to use IDM as an external Registration Service to complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br/><ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume authentication after registration in IDM is complete.</li></ul>",
        "propertyOrder" : 1150,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br>If not selected the users authenticated will be mapped by the parameters configured in the account mapper.<br><br><i>NB</i> <i>If</i> <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
        "propertyOrder" : 1700,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
}
```

1.181.1.2. delete

Usage:

```
am> delete SocialAuthVKontakteModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.181.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthVKontakteModule --realm Realm --actionName getAllTypes
```

1.181.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthVKontakteModule --realm Realm --actionName getCreatableTypes
```

1.181.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthVKontakteModule --realm Realm --actionName nextdescendents
```

1.181.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SocialAuthVKontakteModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.181.1.7. read

Usage:

```
am> read SocialAuthVKontakteModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.181.1.8. update

Usage:

```
am> update SocialAuthVKontakteModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "emailSettings" : {
      "type" : "object",
      "title" : "Email",
      "propertyOrder" : 2,
      "properties" : {
        "smtpFromAddress" : {
          "title" : "SMTP From address",
          "description" : "The email address on behalf of whom the messages will be sent",
          "propertyOrder" : 1645,
          "required" : true,
          "type" : "string",
          "exampleValue" : "info@forgerock.com"
        },
        "smtpUsername" : {
          "title" : "SMTP User Name",
          "description" : "If the SMTP Service requires authentication, configure the user name here",
          "propertyOrder" : 1630,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "smtpPort" : {
          "title" : "SMTP port",
          "description" : "The TCP port that will be used by the SMTP gateway",
          "propertyOrder" : 1625,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "emailAttribute" : {
          "title" : "Email attribute in the Response",
          "description" : "Attribute from the response used to send activation code emails.<br><br>The attribute in the response from the profile service of the Provider that contains the email address of the authenticated user. This address will be used to send an email with an activation code when the accounts are allowed to be created dynamically.",
          "propertyOrder" : 1610,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "smtpSslEnabled" : {
          "title" : "SMTP SSL Enabled",
          "description" : "Tick this option if the SMTP Server provides SSL",
          "propertyOrder" : 1640,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "smtpHost" : {
          "title" : "SMTP host",
          "description" : "The mail host that will be used by the Email Gateway implementation",
          "propertyOrder" : 1620,
```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "emailGateway" : {
    "title" : "Mail Server Gateway implementation class",
    "description" : "The class used by the module to send email.<br><br>This class is used by
the module to send email. A custom implementation can be provided.<br><br>The custom implementation
must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
    "propertyOrder" : 1615,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpPassword" : {
    "title" : "SMTP User Password",
    "description" : "The Password of the SMTP User Name",
    "propertyOrder" : 1635,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  }
}
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "provider" : {
      "title" : "Social Provider",
      "description" : "Social Provider for which this module is being setup.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authorizeEndpoint" : {
      "title" : "Authentication Endpoint URL",
      "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth
authentication provided by the OAuth Identity Provider",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "tokenEndpoint" : {
      "title" : "Access Token Endpoint URL",
      "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\\"http://
tools.ietf.org/html/rfc6749#section-3.2\\" target=\\"_blank\\">RFC 6749</a>, section 3.2",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "scope" : {
      "title" : "Scope",

```

```

    "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth
2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the
client application requires. The list depends on the permissions that the resource owner grants to
the client application.<br><br>Some authorization servers use non-standard separators for scopes.
For example, Facebook takes a comma-separated list.<br><br>",
    "propertyOrder" : 800,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "apiVersion" : {
    "title" : "API Version",
    "description" : "Specifies the version of the auth server API",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL<br><br>This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return
JSON objects in response",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientId" : {
    "title" : "Client Id",
    "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "ssoProxyUrl" : {
    "title" : "Proxy URL",
    "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
    "propertyOrder" : 900,
    "required" : true,

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "forgerock-am-auth-socialauthvk-auth-level" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "subjectProperty" : {
    "title" : "Subject Property",
    "description" : "Property used to identify which attribute an auth server identifies a user by.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"accountProvisioning" : {
  "type" : "object",
  "title" : "Account Provisioning",
  "propertyOrder" : 1,
  "properties" : {
    "attributeMappingClasses" : {
      "title" : "Attribute Mapper",
      "description" : "Name of the class that implements the attribute mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom attribute mapper can be provided.<br><br>A custom attribute mapper must implement the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.<br><br>Provided implementations are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</code> separated values.",
      "propertyOrder" : 1400,
      "required" : true,
      "items" : {
        "type" : "string"
      },
    },
    "type" : "array",
    "exampleValue" : ""
  },
},
"promptPasswordFlag" : {
  "title" : "Prompt for password setting and activation code",
  "description" : "Users must set a password and complete the activation flow during dynamic profile creation.<br><br>If this is enabled, the user must set a password before the system creates an account dynamically and an activation code will be sent to the user's email address. The account will be created only if the password and activation code are properly set. <br />If this is disabled, the account will be created transparently without prompting the user.",
  "propertyOrder" : 1605,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
}

```

```

    },
    "saveAttributesInSession" : {
      "title" : "Save attributes in the session",
      "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
      "propertyOrder" : 2000,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    },
    "accountMapperConfiguration" : {
      "title" : "Account Mapper Configuration",
      "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
      "propertyOrder" : 1300,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    },
    "anonymousUserName" : {
      "title" : "Anonymous User",
      "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that
will represent the anonymous user. This user account must already exist in the realm.",
      "propertyOrder" : 1800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "accountProviderClass" : {
      "title" : "Account Provider",
      "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "createAccount" : {
      "title" : "Create account if it does not exist",
      "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
      "propertyOrder" : 1160,
      "required" : true,
      "type" : "boolean",

```

```

        "exampleValue" : ""
    },
    "attributeMapperConfiguration" : {
        "title" : "Attribute Mapper Configuration",
        "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</code>",
        "propertyOrder" : 1500,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "accountMapperClass" : {
        "title" : "Account Mapper",
        "description" : "Name of the class implementing the attribute mapping for the account search.<br><br>This class is used by the module to map from the account information received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.<br>Provided implementations are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</code> separated values.",
        "propertyOrder" : 1200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "enableRegistrationService" : {
        "title" : "Use IDM as Registration Service",
        "description" : "Whether to use IDM as an external Registration Service to complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br><ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume authentication after registration in IDM is complete.</li></ul>",
        "propertyOrder" : 1150,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the anonymous user configured in the next parameter.<br>If not selected the users authenticated will be mapped by the parameters configured in the account mapper.<br><br><i>NB</i> If <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
        "propertyOrder" : 1700,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
    }
}
}
}
}

```



```
}
```

1.181.2. Global Operations

Resource path: `/global-config/authentication/modules/authSocialVK`

Resource version: `1.0`

1.181.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthVKontakteModule --global --actionName getAllTypes
```

1.181.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthVKontakteModule --global --actionName getCreatableTypes
```

1.181.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthVKontakteModule --global --actionName nextdescendents
```

1.181.2.4. read

Usage:

```
am> read SocialAuthVKontakteModule --global
```

1.181.2.5. update

Usage:

```
am> update SocialAuthVKontakteModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "emailSettings" : {
          "type" : "object",
          "title" : "Email",
          "propertyOrder" : 2,
          "properties" : {
            "smtpUsername" : {
              "title" : "SMTP User Name",
              "description" : "If the SMTP Service requires authentication, configure the user name
here",
              "propertyOrder" : 1630,
              "required" : true,
              "type" : "string",
              "exampleValue" : ""
            },
            "smtpPassword" : {
              "title" : "SMTP User Password",
              "description" : "The Password of the SMTP User Name",
              "propertyOrder" : 1635,
              "required" : true,
              "type" : "string",
              "format" : "password",
              "exampleValue" : ""
            },
            "smtpPort" : {
              "title" : "SMTP port",
              "description" : "The TCP port that will be used by the SMTP gateway",
              "propertyOrder" : 1625,
              "required" : true,
              "type" : "string",
              "exampleValue" : ""
            },
            "smtpSslEnabled" : {
              "title" : "SMTP SSL Enabled",
              "description" : "Tick this option if the SMTP Server provides SSL",
              "propertyOrder" : 1640,
              "required" : true,
              "type" : "boolean",
              "exampleValue" : ""
            },
            "smtpHost" : {
              "title" : "SMTP host",
              "description" : "The mail host that will be used by the Email Gateway implementation",
              "propertyOrder" : 1620,
              "required" : true,
              "type" : "string",
              "exampleValue" : ""
            },
            "emailGateway" : {
              "title" : "Mail Server Gateway implementation class",
```

```

    "description" : "The class used by the module to send
email.<br><br>This class is used by the module to send email. A custom
implementation can be provided.<br/><br/>The custom implementation must implement the
<code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
    "propertyOrder" : 1615,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpFromAddress" : {
    "title" : "SMTP From address",
    "description" : "The email address on behalf of whom the messages will be sent",
    "propertyOrder" : 1645,
    "required" : true,
    "type" : "string",
    "exampleValue" : "info@forgerock.com"
  },
  "emailAttribute" : {
    "title" : "Email attribute in the Response",
    "description" : "Attribute from the response used to send activation code
emails.<br><br>The attribute in the response from the profile service of the Provider that contains
the email address of the authenticated user. This address will be used to send an email with an
activation code when the accounts are allowed to be created dynamically.",
    "propertyOrder" : 1610,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"accountProvisioning" : {
  "type" : "object",
  "title" : "Account Provisioning",
  "propertyOrder" : 1,
  "properties" : {
    "attributeMappingClasses" : {
      "title" : "Attribute Mapper",
      "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br/><br/>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br/>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
      "propertyOrder" : 1400,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "accountMapperConfiguration" : {
      "title" : "Account Mapper Configuration",
      "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0

```

```

Provider to the local data store in the OpenAM. Example: <code>0Auth2.0_attribute=local_attribute</code>",
    "propertyOrder" : 1300,
    "required" : true,
    "items" : {
        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"saveAttributesInSession" : {
    "title" : "Save attributes in the session",
    "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"createAccount" : {
    "title" : "Create account if it does not exist",
    "description" : "If the OAuth2 account does not exist in the local OpenAM data store,
an account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
    "propertyOrder" : 1160,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"enableRegistrationService" : {
    "title" : "Use IDM as Registration Service",
    "description" : "Whether to use IDM as an external Registration Service to
complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
    "propertyOrder" : 1150,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"mapToAnonymousUser" : {
    "title" : "Map to anonymous user",
    "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
    "propertyOrder" : 1700,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
}

```

```

        "anonymousUserName" : {
            "title" : "Anonymous User",
            "description" : "Username of the OpenAM anonymous user<br><br>The username of the user
that will represent the anonymous user. This user account must already exist in the realm.",
            "propertyOrder" : 1800,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "attributeMapperConfiguration" : {
            "title" : "Attribute Mapper Configuration",
            "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
            "propertyOrder" : 1500,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "accountProviderClass" : {
            "title" : "Account Provider",
            "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br><br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
            "propertyOrder" : 1100,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "accountMapperClass" : {
            "title" : "Account Mapper",
            "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br><br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
            "propertyOrder" : 1200,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "promptPasswordFlag" : {
            "title" : "Prompt for password setting and activation code",
            "description" : "Users must set a password and complete the activation flow during
dynamic profile creation.<br><br>If this is enabled, the user must set a password before the system
creates an account dynamically and an activation code will be sent to the user's email address. The
account will be created only if the password and activation code are properly set. <br />If this is
disabled, the account will be created transparently without prompting the user.",
            "propertyOrder" : 1605,
    
```

```

        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"core" : {
    "type" : "object",
    "title" : "Core",
    "propertyOrder" : 0,
    "properties" : {
        "ssoProxyUrl" : {
            "title" : "Proxy URL",
            "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
            "propertyOrder" : 900,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "tokenEndpoint" : {
            "title" : "Access Token Endpoint URL",
            "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
            "propertyOrder" : 600,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "userInfoEndpoint" : {
            "title" : "User Profile Service URL",
            "description" : "User profile information URL<br><br>This URL endpoint provides user
profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should
return JSON objects in response",
            "propertyOrder" : 700,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "forgerock-am-auth-socialauthvk-auth-level" : {
            "title" : "Authentication Level",
            "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
            "propertyOrder" : 400,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "scope" : {
            "title" : "Scope",
            "description" : "OAuth scope; list of user profile properties<br><br>According to the
OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that
the client application requires. The list depends on the permissions that the resource owner grants
to the client application.<br><br>Some authorization servers use non-standard separators for
scopes. For example, Facebook takes a comma-separated list.<br><br></a>",
            "propertyOrder" : 800,

```

```

    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "subjectProperty" : {
    "title" : "Subject Property",
    "description" : "Property used to identify which attribute an auth server identifies a
user by.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "provider" : {
    "title" : "Social Provider",
    "description" : "Social Provider for which this module is being setup.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "authorizeEndpoint" : {
    "title" : "Authentication Endpoint URL",
    "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for
OAuth authentication provided by the OAuth Identity Provider",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "apiVersion" : {
    "title" : "API Version",
    "description" : "Specifies the version of the auth server API",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientId" : {
    "title" : "Client Id",
    "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 200,
    "required" : true,

```

```
        "type" : "string",
        "exampleValue" : ""
      }
    }
  },
  "type" : "object",
  "title" : "Realm Defaults"
}
}
```

1.182. SocialAuthWeChatMobileModule

1.182.1. Realm Operations

Resource path: `/realm-config/authentication/modules/authSocialWeChatMobile`

Resource version: `1.0`

1.182.1.1. create

Usage:

```
am> create SocialAuthWeChatMobileModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "accountProvisioning" : {
      "type" : "object",
```



```

"title" : "Account Provisioning",
"propertyOrder" : 1,
"properties" : {
  "saveAttributesInSession" : {
    "title" : "Save attributes in the session",
    "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "anonymousUserName" : {
    "title" : "Anonymous User",
    "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that
will represent the anonymous user. This user account must already exist in the realm.",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "createAccount" : {
    "title" : "Create account if it does not exist",
    "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
    "propertyOrder" : 1360,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "attributeMappingClasses" : {
    "title" : "Attribute Mapper",
    "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br><br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1700,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "accountMapperClass" : {
    "title" : "Account Mapper",

```

```

        "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "enableRegistrationService" : {
        "title" : "Use IDM as Registration Service",
        "description" : "Whether to use IDM as an external Registration Service to complete
registration for new users.<br><br>IDM is called and passed these parameters:<br><br/>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
        "propertyOrder" : 1350,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "accountMapperConfiguration" : {
        "title" : "Account Mapper Configuration",
        "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
        "propertyOrder" : 1600,
        "required" : true,
        "items" : {

```

```

    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"promptPasswordFlag" : {
  "title" : "Prompt for password setting and activation code",
  "description" : "Users must set a password and complete the activation flow during dynamic
profile creation.<br><br>If this is enabled, the user must set a password before the system creates
an account dynamically and an activation code will be sent to the user's email address. The account
will be created only if the password and activation code are properly set. <br />If this is disabled,
the account will be created transparently without prompting the user.",
  "propertyOrder" : 1905,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"attributeMapperConfiguration" : {
  "title" : "Attribute Mapper Configuration",
  "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
  "propertyOrder" : 1800,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
}
},
"emailSettings" : {
  "type" : "object",
  "title" : "Email",
  "propertyOrder" : 2,
  "properties" : {
    "emailAttribute" : {
      "title" : "Email attribute in the Response",
      "description" : "Attribute from the response used to send activation code emails.<br><br>The
attribute in the response from the profile service of the Provider that contains the email address of
the authenticated user. This address will be used to send an email with an activation code when the
accounts are allowed to be created dynamically.",
      "propertyOrder" : 1910,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpFromAddress" : {
      "title" : "SMTP From address",
      "description" : "The email address on behalf of whom the messages will be sent",
      "propertyOrder" : 1945,
      "required" : true,
      "type" : "string",
      "exampleValue" : "info@forgerock.com"
    },
    "emailGateway" : {
      "title" : "Mail Server Gateway implementation class",

```

```

    "description" : "The class used by the module to send email.<br><br>This class is used by
the module to send email. A custom implementation can be provided.<br><br>The custom implementation
must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
    "propertyOrder" : 1915,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpSslEnabled" : {
    "title" : "SMTP SSL Enabled",
    "description" : "Tick this option if the SMTP Server provides SSL",
    "propertyOrder" : 1940,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "smtpPort" : {
    "title" : "SMTP port",
    "description" : "The TCP port that will be used by the SMTP gateway",
    "propertyOrder" : 1925,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpUsername" : {
    "title" : "SMTP User Name",
    "description" : "If the SMTP Service requires authentication, configure the user name here",
    "propertyOrder" : 1930,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "smtpPassword" : {
    "title" : "SMTP User Password",
    "description" : "The Password of the SMTP User Name",
    "propertyOrder" : 1935,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "smtpHost" : {
    "title" : "SMTP host",
    "description" : "The mail host that will be used by the Email Gateway implementation",
    "propertyOrder" : 1920,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "provider" : {
      "title" : "Social Provider",
      "description" : "Social Provider for which this module is being setup.",

```

```
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "ssoProxyUrl" : {
        "title" : "Proxy URL",
        "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be changed from the default, if an external server is performing the GET to POST proxying. The default is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
        "propertyOrder" : 1300,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "userInfoEndpoint" : {
        "title" : "User Profile Service URL",
        "description" : "User profile information URL<br><br>This URL endpoint provides user profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return JSON objects in response",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "subjectProperty" : {
        "title" : "Subject Property",
        "description" : "Property used to identify which attribute an auth server identifies a user by.",
        "propertyOrder" : 1100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "scope" : {
        "title" : "Scope",
        "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the client application requires. The list depends on the permissions that the resource owner grants to the client application.<br><br>Some authorization servers use non-standard separators for scopes. For example, Facebook takes a comma-separated list.<br><br>",
        "propertyOrder" : 900,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
}
}
}
```

1.182.1.2. delete

Usage:

```
am> delete SocialAuthWeChatMobileModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.182.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthWeChatMobileModule --realm Realm --actionName getAllTypes
```

1.182.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthWeChatMobileModule --realm Realm --actionName getCreatableTypes
```

1.182.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthWeChatMobileModule --realm Realm --actionName nextdescendents
```

1.182.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SocialAuthWeChatMobileModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.182.1.7. read

Usage:

```
am> read SocialAuthWeChatMobileModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.182.1.8. update

Usage:

```
am> update SocialAuthWeChatMobileModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "accountProvisioning" : {
      "type" : "object",
      "title" : "Account Provisioning",
      "propertyOrder" : 1,
      "properties" : {
        "saveAttributesInSession" : {
          "title" : "Save attributes in the session",
          "description" : "If this option is enabled, the attributes configured in the attribute mapper will be saved into the OpenAM session",
          "propertyOrder" : 2400,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        }
      },
      "anonymousUserName" : {
        "title" : "Anonymous User",
```

```

        "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that
will represent the anonymous user. This user account must already exist in the realm.",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "createAccount" : {
        "title" : "Create account if it does not exist",
        "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
        "propertyOrder" : 1360,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "attributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "accountMapperClass" : {
        "title" : "Account Mapper",
        "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "enableRegistrationService" : {

```



```

        "title" : "Use IDM as Registration Service",
        "description" : "Whether to use IDM as an external Registration Service to complete
registration for new users.<br><br>IDM is called and passed these parameters:<br><br/>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
        "propertyOrder" : 1350,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
        "propertyOrder" : 2000,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "accountMapperConfiguration" : {
        "title" : "Account Mapper Configuration",
        "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
        "propertyOrder" : 1600,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "promptPasswordFlag" : {
        "title" : "Prompt for password setting and activation code",
        "description" : "Users must set a password and complete the activation flow during dynamic
profile creation.<br><br>If this is enabled, the user must set a password before the system creates
an account dynamically and an activation code will be sent to the user's email address. The account
will be created only if the password and activation code are properly set. <br />If this is disabled,
the account will be created transparently without prompting the user.",
        "propertyOrder" : 1905,
        "required" : true,
        "type" : "boolean",
    }
}

```

```

    "exampleValue" : ""
  },
  "attributeMapperConfiguration" : {
    "title" : "Attribute Mapper Configuration",
    "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data store in the OpenAM.<br/><br/>Example: <code>OAuth2.0_attribute=local_attribute</code>",
    "propertyOrder" : 1800,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
},
"emailSettings" : {
  "type" : "object",
  "title" : "Email",
  "propertyOrder" : 2,
  "properties" : {
    "emailAttribute" : {
      "title" : "Email attribute in the Response",
      "description" : "Attribute from the response used to send activation code emails.<br><br>The attribute in the response from the profile service of the Provider that contains the email address of the authenticated user. This address will be used to send an email with an activation code when the accounts are allowed to be created dynamically.",
      "propertyOrder" : 1910,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpFromAddress" : {
      "title" : "SMTP From address",
      "description" : "The email address on behalf of whom the messages will be sent",
      "propertyOrder" : 1945,
      "required" : true,
      "type" : "string",
      "exampleValue" : "info@forgerock.com"
    },
    "emailGateway" : {
      "title" : "Mail Server Gateway implementation class",
      "description" : "The class used by the module to send email.<br><br>This class is used by the module to send email. A custom implementation can be provided.<br/><br/>The custom implementation must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
      "propertyOrder" : 1915,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpSslEnabled" : {
      "title" : "SMTP SSL Enabled",
      "description" : "Tick this option if the SMTP Server provides SSL",
      "propertyOrder" : 1940,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}

```

```

    },
    "smtpPort" : {
      "title" : "SMTP port",
      "description" : "The TCP port that will be used by the SMTP gateway",
      "propertyOrder" : 1925,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpUsername" : {
      "title" : "SMTP User Name",
      "description" : "If the SMTP Service requires authentication, configure the user name here",
      "propertyOrder" : 1930,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpPassword" : {
      "title" : "SMTP User Password",
      "description" : "The Password of the SMTP User Name",
      "propertyOrder" : 1935,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "smtpHost" : {
      "title" : "SMTP host",
      "description" : "The mail host that will be used by the Email Gateway implementation",
      "propertyOrder" : 1920,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "provider" : {
      "title" : "Social Provider",
      "description" : "Social Provider for which this module is being setup.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "ssoProxyUrl" : {
      "title" : "Proxy URL",
      "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
      "propertyOrder" : 1300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},

```

```

    "userInfoEndpoint" : {
      "title" : "User Profile Service URL",
      "description" : "User profile information URL<br><br>This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return
JSON objects in response",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "subjectProperty" : {
      "title" : "Subject Property",
      "description" : "Property used to identify which attribute an auth server identifies a user
by.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "scope" : {
      "title" : "Scope",
      "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth
2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the
client application requires. The list depends on the permissions that the resource owner grants to
the client application.<br><br>Some authorization servers use non-standard separators for scopes.
For example, Facebook takes a comma-separated list.<br><br>",
      "propertyOrder" : 900,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
}
}
}
}
}

```

1.182.2. Global Operations

Resource path: [/global-config/authentication/modules/authSocialWeChatMobile](#)

Resource version: 1.0

1.182.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthWeChatMobileModule --global --actionName getAllTypes
```

1.182.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthWeChatMobileModule --global --actionName getCreatableTypes
```

1.182.2.3. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthWeChatMobileModule --global --actionName nextdescendants
```

1.182.2.4. read

Usage:

```
am> read SocialAuthWeChatMobileModule --global
```

1.182.2.5. update

Usage:

```
am> update SocialAuthWeChatMobileModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "accountProvisioning" : {
          "type" : "object",
          "title" : "Account Provisioning",
          "propertyOrder" : 1,
          "properties" : {
            "attributeMapperConfiguration" : {
              "title" : "Attribute Mapper Configuration",
              "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</code>",
              "propertyOrder" : 1800,
              "required" : true,
              "items" : {
```

```

        "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
},
"accountMapperClass" : {
    "title" : "Account Mapper",
    "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"promptPasswordFlag" : {
    "title" : "Prompt for password setting and activation code",
    "description" : "Users must set a password and complete the activation flow during
dynamic profile creation.<br><br>If this is enabled, the user must set a password before the system
creates an account dynamically and an activation code will be sent to the user's email address. The
account will be created only if the password and activation code are properly set. <br />If this is
disabled, the account will be created transparently without prompting the user.",
    "propertyOrder" : 1905,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
},
"anonymousUserName" : {
    "title" : "Anonymous User",
    "description" : "Username of the OpenAM anonymous user<br><br>The username of the user
that will represent the anonymous user. This user account must already exist in the realm.",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"accountProviderClass" : {
    "title" : "Account Provider",
    "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
    "propertyOrder" : 1400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"createAccount" : {
    "title" : "Create account if it does not exist",
    "description" : "If the OAuth2 account does not exist in the local OpenAM data store,
an account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
    
```

prompting for a password and asking for an activation code can be shown if the parameter \"Prompt for password setting and activation code\" is enabled.

If this flag is not enabled, 3 alternative options exist:

The accounts need to have a user profile in the OpenAM User Data StoreThe user does not have a user profile and the \"Ignore Profile\" is set in the Authentication Service of the realm.The account is mapped to an anonymous account (see parameter \"Map to anonymous user\" and \"Anonymous User\")

```

    "propertyOrder" : 1360,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "mapToAnonymousUser" : {
    "title" : "Map to anonymous user",
    "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saveAttributesInSession" : {
    "title" : "Save attributes in the session",
    "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "accountMapperConfiguration" : {
    "title" : "Account Mapper Configuration",
    "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
    "propertyOrder" : 1600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "attributeMappingClasses" : {
    "title" : "Attribute Mapper",
    "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1700,
    "required" : true,

```

```

    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "enableRegistrationService" : {
    "title" : "Use IDM as Registration Service",
    "description" : "Whether to use IDM as an external Registration Service to
complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
    "propertyOrder" : 1350,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "subjectProperty" : {
      "title" : "Subject Property",
      "description" : "Property used to identify which attribute an auth server identifies a
user by.",
      "propertyOrder" : 1100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "userInfoEndpoint" : {
      "title" : "User Profile Service URL",
      "description" : "User profile information URL<br><br>This URL endpoint provides user
profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should
return JSON objects in response",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "scope" : {
      "title" : "Scope",
      "description" : "OAuth scope; list of user profile properties<br><br>According to the
OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that
the client application requires. The list depends on the permissions that the resource owner grants
to the client application.<br><br>Some authorization servers use non-standard separators for
scopes. For example, Facebook takes a comma-separated list.<br><br>",
      "propertyOrder" : 900,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
},

```



```

    "ssoProxyUrl" : {
      "title" : "Proxy URL",
      "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
      "propertyOrder" : 1300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "provider" : {
      "title" : "Social Provider",
      "description" : "Social Provider for which this module is being setup.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"emailSettings" : {
  "type" : "object",
  "title" : "Email",
  "propertyOrder" : 2,
  "properties" : {
    "smtpPassword" : {
      "title" : "SMTP User Password",
      "description" : "The Password of the SMTP User Name",
      "propertyOrder" : 1935,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "emailGateway" : {
      "title" : "Mail Server Gateway implementation class",
      "description" : "The class used by the module to send
email.<br><br>This class is used by the module to send email. A custom
implementation can be provided.<br><br>The custom implementation must implement the
<code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
      "propertyOrder" : 1915,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpPort" : {
      "title" : "SMTP port",
      "description" : "The TCP port that will be used by the SMTP gateway",
      "propertyOrder" : 1925,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "smtpFromAddress" : {
      "title" : "SMTP From address",
      "description" : "The email address on behalf of whom the messages will be sent",
      "propertyOrder" : 1945,
      "required" : true,
      "type" : "string",

```

```

        "exampleValue" : "info@forgerock.com"
    },
    "smtpHost" : {
        "title" : "SMTP host",
        "description" : "The mail host that will be used by the Email Gateway implementation",
        "propertyOrder" : 1920,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "smtpSslEnabled" : {
        "title" : "SMTP SSL Enabled",
        "description" : "Tick this option if the SMTP Server provides SSL",
        "propertyOrder" : 1940,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "smtpUsername" : {
        "title" : "SMTP User Name",
        "description" : "If the SMTP Service requires authentication, configure the user name
here",
        "propertyOrder" : 1930,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "emailAttribute" : {
        "title" : "Email attribute in the Response",
        "description" : "Attribute from the response used to send activation code
emails.<br><br>The attribute in the response from the profile service of the Provider that contains
the email address of the authenticated user. This address will be used to send an email with an
activation code when the accounts are allowed to be created dynamically.",
        "propertyOrder" : 1910,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
    }
},
"authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
}
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}

```

1.183. SocialAuthWeChatModule

1.183.1. Realm Operations

Resource path: `/realm-config/authentication/modules/authSocialWeChat`

Resource version: `1.0`

1.183.1.1. create

Usage:

```
am> create SocialAuthWeChatModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "emailSettings" : {
      "type" : "object",
      "title" : "Email",
      "propertyOrder" : 2,
      "properties" : {
        "smtpPort" : {
          "title" : "SMTP port",
          "description" : "The TCP port that will be used by the SMTP gateway",
          "propertyOrder" : 1925,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "emailAttribute" : {
          "title" : "Email attribute in the Response",
          "description" : "Attribute from the response used to send activation code emails.<br><br>The attribute in the response from the profile service of the Provider that contains the email address of the authenticated user. This address will be used to send an email with an activation code when the accounts are allowed to be created dynamically.",
          "propertyOrder" : 1910,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "emailGateway" : {
          "title" : "Mail Server Gateway implementation class",
```

```
"description" : "The class used by the module to send email.<br><br>This class is used by  
the module to send email. A custom implementation can be provided.<br><br>The custom implementation  
must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",  
  "propertyOrder" : 1915,  
  "required" : true,  
  "type" : "string",  
  "exampleValue" : ""  
},  
"smtpPassword" : {  
  "title" : "SMTP User Password",  
  "description" : "The Password of the SMTP User Name",  
  "propertyOrder" : 1935,  
  "required" : true,  
  "type" : "string",  
  "format" : "password",  
  "exampleValue" : ""  
},  
"smtpUsername" : {  
  "title" : "SMTP User Name",  
  "description" : "If the SMTP Service requires authentication, configure the user name here",  
  "propertyOrder" : 1930,  
  "required" : true,  
  "type" : "string",  
  "exampleValue" : ""  
},  
"smtpFromAddress" : {  
  "title" : "SMTP From address",  
  "description" : "The email address on behalf of whom the messages will be sent",  
  "propertyOrder" : 1945,  
  "required" : true,  
  "type" : "string",  
  "exampleValue" : "info@forgerock.com"  
},  
"smtpSslEnabled" : {  
  "title" : "SMTP SSL Enabled",  
  "description" : "Tick this option if the SMTP Server provides SSL",  
  "propertyOrder" : 1940,  
  "required" : true,  
  "type" : "boolean",  
  "exampleValue" : ""  
},  
"smtpHost" : {  
  "title" : "SMTP host",  
  "description" : "The mail host that will be used by the Email Gateway implementation",  
  "propertyOrder" : 1920,  
  "required" : true,  
  "type" : "string",  
  "exampleValue" : ""  
}  
}  
},  
"accountProvisioning" : {  
  "type" : "object",  
  "title" : "Account Provisioning",  
  "propertyOrder" : 1,  
  "properties" : {  
    "attributeMapperConfiguration" : {  
      "title" : "Attribute Mapper Configuration",
```

```

    "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
    "propertyOrder" : 1800,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "accountMapperClass" : {
    "title" : "Account Mapper",
    "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br><br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saveAttributesInSession" : {
    "title" : "Save attributes in the session",
    "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "createAccount" : {
    "title" : "Create account if it does not exist",
    "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
    "propertyOrder" : 1360,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "accountMapperConfiguration" : {
    "title" : "Account Mapper Configuration",
    "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",

```

```

        "propertyOrder" : 1600,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "anonymousUserName" : {
        "title" : "Anonymous User",
        "description" : "Username of the OpenAM anonymous user<br><br>The username of the user that
will represent the anonymous user. This user account must already exist in the realm.",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "promptPasswordFlag" : {
        "title" : "Prompt for password setting and activation code",
        "description" : "Users must set a password and complete the activation flow during dynamic
profile creation.<br><br>If this is enabled, the user must set a password before the system creates
an account dynamically and an activation code will be sent to the user's email address. The account
will be created only if the password and activation code are properly set. <br />If this is disabled,
the account will be created transparently without prompting the user.",
        "propertyOrder" : 1905,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "attributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "enableRegistrationService" : {
        "title" : "Use IDM as Registration Service",
        "description" : "Whether to use IDM as an external Registration Service to complete
registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
        "propertyOrder" : 1350,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }

```

```

    },
    "accountProviderClass" : {
      "title" : "Account Provider",
      "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br></>String constructor parameters can be provided by appending <code>|</code> separated
values.",
      "propertyOrder" : 1400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
      "title" : "Map to anonymous user",
      "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
      "propertyOrder" : 2000,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "clientId" : {
      "title" : "Client Id",
      "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
\"_blank\">RFC 6749</a>, section 2.3.1",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "ssoProxyUrl" : {
      "title" : "Proxy URL",
      "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
changed from the default, if an external server is performing the GET to POST proxying. The default
is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
      "propertyOrder" : 1300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "userInfoEndpoint" : {
      "title" : "User Profile Service URL",
      "description" : "User profile information URL<br><br>This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return
JSON objects in response",
      "propertyOrder" : 800,
      "required" : true,

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "scopeDelimiter" : {
    "title" : "Scope Delimiter",
    "description" : "Delimiter used to separate scope values. Default value is space.",
    "propertyOrder" : 1000,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authorizeEndpoint" : {
    "title" : "Authentication Endpoint URL",
    "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
    "propertyOrder" : 600,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "subjectProperty" : {
    "title" : "Subject Property",
    "description" : "Property used to identify which attribute an auth server identifies a user by.",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "scope" : {
    "title" : "Scope",
    "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the client application requires. The list depends on the permissions that the resource owner grants to the client application.<br><br>Some authorization servers use non-standard separators for scopes. For example, Facebook takes a comma-separated list.<br><br>",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "usesBasicAuth" : {
    "title" : "Use Basic Auth",
    "description" : "When enabled, the client will use basic auth for authenticating with the social auth provider. Enabled by default.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 500,

```



```

    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "provider" : {
    "title" : "Social Provider",
    "description" : "Social Provider for which this module is being setup.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenEndpoint" : {
    "title" : "Access Token Endpoint URL",
    "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}
}
}
}

```

1.183.1.2. delete

Usage:

```
am> delete SocialAuthWeChatModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.183.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthWeChatModule --realm Realm --actionName getAllTypes
```

1.183.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthWeChatModule --realm Realm --actionName getCreatableTypes
```

1.183.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthWeChatModule --realm Realm --actionName nextdescendents
```

1.183.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SocialAuthWeChatModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.183.1.7. read

Usage:

```
am> read SocialAuthWeChatModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.183.1.8. update

Usage:

```
am> update SocialAuthWeChatModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "emailSettings" : {
      "type" : "object",
      "title" : "Email",
      "propertyOrder" : 2,
      "properties" : {
        "smtpPort" : {
          "title" : "SMTP port",
          "description" : "The TCP port that will be used by the SMTP gateway",
          "propertyOrder" : 1925,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "emailAttribute" : {
          "title" : "Email attribute in the Response",
          "description" : "Attribute from the response used to send activation code emails.<br><br>The attribute in the response from the profile service of the Provider that contains the email address of the authenticated user. This address will be used to send an email with an activation code when the accounts are allowed to be created dynamically.",
          "propertyOrder" : 1910,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "emailGateway" : {
          "title" : "Mail Server Gateway implementation class",
          "description" : "The class used by the module to send email.<br><br>This class is used by the module to send email. A custom implementation can be provided.<br><br>The custom implementation must implement the <code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
          "propertyOrder" : 1915,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "smtpPassword" : {
          "title" : "SMTP User Password",
          "description" : "The Password of the SMTP User Name",
          "propertyOrder" : 1935,
          "required" : true,
          "type" : "string",
          "format" : "password",
          "exampleValue" : ""
        }
      }
    }
  }
},
```

```

"smtpUsername" : {
  "title" : "SMTP User Name",
  "description" : "If the SMTP Service requires authentication, configure the user name here",
  "propertyOrder" : 1930,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"smtpFromAddress" : {
  "title" : "SMTP From address",
  "description" : "The email address on behalf of whom the messages will be sent",
  "propertyOrder" : 1945,
  "required" : true,
  "type" : "string",
  "exampleValue" : "info@forgerock.com"
},
"smtpSslEnabled" : {
  "title" : "SMTP SSL Enabled",
  "description" : "Tick this option if the SMTP Server provides SSL",
  "propertyOrder" : 1940,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"smtpHost" : {
  "title" : "SMTP host",
  "description" : "The mail host that will be used by the Email Gateway implementation",
  "propertyOrder" : 1920,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
},
"accountProvisioning" : {
  "type" : "object",
  "title" : "Account Provisioning",
  "propertyOrder" : 1,
  "properties" : {
    "attributeMapperConfiguration" : {
      "title" : "Attribute Mapper Configuration",
      "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</code>",
      "propertyOrder" : 1800,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "accountMapperClass" : {
      "title" : "Account Mapper",
      "description" : "Name of the class implementing the attribute mapping for the account search.<br><br>This class is used by the module to map from the account information received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>"
    }
  }
}

```

```

interface.<br/>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
    "propertyOrder" : 1500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "saveAttributesInSession" : {
    "title" : "Save attributes in the session",
    "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "createAccount" : {
    "title" : "Create account if it does not exist",
    "description" : "If the OAuth2 account does not exist in the local OpenAM data store, an
account will be created dynamically.<br/><br/>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br/><br/><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
    "propertyOrder" : 1360,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "accountMapperConfiguration" : {
    "title" : "Account Mapper Configuration",
    "description" : "Mapping of OAuth account to local OpenAM account<br/><br/>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
    "propertyOrder" : 1600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "anonymousUserName" : {
    "title" : "Anonymous User",
    "description" : "Username of the OpenAM anonymous user<br/><br/>The username of the user that
will represent the anonymous user. This user account must already exist in the realm.",
    "propertyOrder" : 2100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "promptPasswordFlag" : {

```

```

        "title" : "Prompt for password setting and activation code",
        "description" : "Users must set a password and complete the activation flow during dynamic
profile creation.<br><br>If this is enabled, the user must set a password before the system creates
an account dynamically and an activation code will be sent to the user's email address. The account
will be created only if the password and activation code are properly set. <br />If this is disabled,
the account will be created transparently without prompting the user.",
        "propertyOrder" : 1905,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "attributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br><br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "enableRegistrationService" : {
        "title" : "Use IDM as Registration Service",
        "description" : "Whether to use IDM as an external Registration Service to complete
registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
        "propertyOrder" : 1350,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br><br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "mapToAnonymousUser" : {
        "title" : "Map to anonymous user",
        "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
    
```

```

mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if it does not exist</i> is enabled, that parameter takes precedence.",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"core" : {
  "type" : "object",
  "title" : "Core",
  "propertyOrder" : 0,
  "properties" : {
    "clientId" : {
      "title" : "Client Id",
      "description" : "OAuth client_id parameter<br><br>For more information on the OAuth client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=\"_blank\">RFC 6749</a>, section 2.3.1",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "ssoProxyUrl" : {
      "title" : "Proxy URL",
      "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be changed from the default, if an external server is performing the GET to POST proxying. The default is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
      "propertyOrder" : 1300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "userInfoEndpoint" : {
      "title" : "User Profile Service URL",
      "description" : "User profile information URL<br><br>This URL endpoint provides user profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should return JSON objects in response",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "scopeDelimiter" : {
      "title" : "Scope Delimiter",
      "description" : "Delimiter used to separate scope values. Default value is space.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authorizeEndpoint" : {
      "title" : "Authentication Endpoint URL",
      "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "string",

```

```

    "exampleValue" : ""
  },
  "subjectProperty" : {
    "title" : "Subject Property",
    "description" : "Property used to identify which attribute an auth server identifies a user
by.",
    "propertyOrder" : 1100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "scope" : {
    "title" : "Scope",
    "description" : "OAuth scope; list of user profile properties<br><br>According to the OAuth
2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the
client application requires. The list depends on the permissions that the resource owner grants to
the client application.<br><br>Some authorization servers use non-standard separators for scopes.
For example, Facebook takes a comma-separated list.<br><br>",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "usesBasicAuth" : {
    "title" : "Use Basic Auth",
    "description" : "When enabled, the client will use basic auth for authenticating with the
social auth provider. Enabled by default.",
    "propertyOrder" : 1200,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "provider" : {
    "title" : "Social Provider",
    "description" : "Social Provider for which this module is being setup.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenEndpoint" : {
    "title" : "Access Token Endpoint URL",
    "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",

```



```
        "propertyOrder" : 700,  
        "required" : true,  
        "type" : "string",  
        "exampleValue" : ""  
    }  
},  
"authenticationLevel" : {  
    "title" : "Authentication Level",  
    "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default).",  
    "propertyOrder" : 100,  
    "required" : true,  
    "type" : "integer",  
    "exampleValue" : ""  
}  
}
```

1.183.2. Global Operations

Resource path: `/global-config/authentication/modules/authSocialWeChat`

Resource version: `1.0`

1.183.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthWeChatModule --global --actionName getAllTypes
```

1.183.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthWeChatModule --global --actionName getCreatableTypes
```

1.183.2.3. nextDescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthWeChatModule --global --actionName nextDescendants
```

1.183.2.4. read

Usage:

```
am> read SocialAuthWeChatModule --global
```

1.183.2.5. update

Usage:

```
am> update SocialAuthWeChatModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "emailSettings" : {
          "type" : "object",
          "title" : "Email",
          "propertyOrder" : 2,
          "properties" : {
            "emailGateway" : {
              "title" : "Mail Server Gateway implementation class",
              "description" : "The class used by the module to send
email.<br><br>This class is used by the module to send email. A custom
implementation can be provided.<br><br>The custom implementation must implement the
<code>org.forgerock.openam.authentication.modules.oauth2.EmailGateway</code>",
              "propertyOrder" : 1915,
              "required" : true,
              "type" : "string",
              "exampleValue" : ""
            },
            "smtpFromAddress" : {
              "title" : "SMTP From address",
              "description" : "The email address on behalf of whom the messages will be sent",
              "propertyOrder" : 1945,
              "required" : true,
              "type" : "string",
              "exampleValue" : "info@forgerock.com"
            },
            "smtpUsername" : {
              "title" : "SMTP User Name",
              "description" : "If the SMTP Service requires authentication, configure the user name
here",
              "propertyOrder" : 1930,
              "required" : true,
              "type" : "string",
              "exampleValue" : ""
            }
          }
        }
      }
    }
  }
}
```

```

        "emailAttribute" : {
            "title" : "Email attribute in the Response",
            "description" : "Attribute from the response used to send activation code
emails.<br><br>The attribute in the response from the profile service of the Provider that contains
the email address of the authenticated user. This address will be used to send an email with an
activation code when the accounts are allowed to be created dynamically.",
            "propertyOrder" : 1910,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "smtpPassword" : {
            "title" : "SMTP User Password",
            "description" : "The Password of the SMTP User Name",
            "propertyOrder" : 1935,
            "required" : true,
            "type" : "string",
            "format" : "password",
            "exampleValue" : ""
        },
        "smtpSslEnabled" : {
            "title" : "SMTP SSL Enabled",
            "description" : "Tick this option if the SMTP Server provides SSL",
            "propertyOrder" : 1940,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "smtpPort" : {
            "title" : "SMTP port",
            "description" : "The TCP port that will be used by the SMTP gateway",
            "propertyOrder" : 1925,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "smtpHost" : {
            "title" : "SMTP host",
            "description" : "The mail host that will be used by the Email Gateway implementation",
            "propertyOrder" : 1920,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
},
"accountProvisioning" : {
    "type" : "object",
    "title" : "Account Provisioning",
    "propertyOrder" : 1,
    "properties" : {
        "enableRegistrationService" : {
            "title" : "Use IDM as Registration Service",
            "description" : "Whether to use IDM as an external Registration Service to
complete registration for new users.<br><br>IDM is called and passed these parameters:<br><br>
<ul><li><code>clientToken</code>: Signed, encrypted JWT of the OAuth 2.0 authentication state.</
li><li><code>returnParams</code>: Encoded URL parameters, required to be returned to AM to resume
authentication after registration in IDM is complete.</li></ul>",
            "propertyOrder" : 1350,

```

```

    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "attributeMapperConfiguration" : {
    "title" : "Attribute Mapper Configuration",
    "description" : "Mapping of OAuth attributes to local OpenAM attributes<br><br>Attribute
configuration that will be used to map the user info obtained from the OAuth 2.0 Provider to the
local user data store in the OpenAM.<br><br>Example: <code>OAuth2.0_attribute=local_attribute</
code>",
    "propertyOrder" : 1800,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "mapToAnonymousUser" : {
    "title" : "Map to anonymous user",
    "description" : "Enabled anonymous user access to OpenAM for OAuth authenticated
users<br><br>If selected, the authenticated users in the OAuth 2.0 Provider will be mapped to the
anonymous user configured in the next parameter.<br>If not selected the users authenticated will be
mapped by the parameters configured in the account mapper.<br><br><i>NB </i>If <i>Create account if
it does not exist</i> is enabled, that parameter takes precedence.",
    "propertyOrder" : 2000,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "createAccount" : {
    "title" : "Create account if it does not exist",
    "description" : "If the OAuth2 account does not exist in the local OpenAM data store,
an account will be created dynamically.<br><br>If this is enabled, the account mapper could create
the account dynamically if there is no account mapped. Before creating the account, a dialog
prompting for a password and asking for an activation code can be shown if the parameter \"Prompt
for password setting and activation code\" is enabled.<br /><br />If this flag is not enabled, 3
alternative options exist:<br><br><ol><li>The accounts need to have a user profile in the OpenAM
User Data Store</li><li>The user does not have a user profile and the \"Ignore Profile\" is set in
the Authentication Service of the realm.</li><li>The account is mapped to an anonymous account (see
parameter \"Map to anonymous user\" and \"Anonymous User\")</li></ol>",
    "propertyOrder" : 1360,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "promptPasswordFlag" : {
    "title" : "Prompt for password setting and activation code",
    "description" : "Users must set a password and complete the activation flow during
dynamic profile creation.<br><br>If this is enabled, the user must set a password before the system
creates an account dynamically and an activation code will be sent to the user's email address. The
account will be created only if the password and activation code are properly set. <br />If this is
disabled, the account will be created transparently without prompting the user.",
    "propertyOrder" : 1905,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "saveAttributesInSession" : {

```

```

        "title" : "Save attributes in the session",
        "description" : "If this option is enabled, the attributes configured in the attribute
mapper will be saved into the OpenAM session",
        "propertyOrder" : 2400,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "accountMapperClass" : {
        "title" : "Account Mapper",
        "description" : "Name of the class implementing the attribute mapping for the
account search.<br><br>This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM.<br><br>The class must implement
the <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1500,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "anonymousUserName" : {
        "title" : "Anonymous User",
        "description" : "Username of the OpenAM anonymous user<br><br>The username of the user
that will represent the anonymous user. This user account must already exist in the realm.",
        "propertyOrder" : 2100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "attributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute
mapping<br><br>This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided.<br><br>A custom attribute mapper must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code>
interface.<br>Provided implementations
are:<ul><li>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper</
li><li>org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when
using the openid scope)</li></ul>String constructor parameters can be provided by appending <code>|</
code> separated values.",
        "propertyOrder" : 1700,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "accountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider.<br><br>This
class is used by the module to find the account from the attributes mapped by the Account
Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code>
interface.<br>String constructor parameters can be provided by appending <code>|</code> separated
values.",
    }

```

```

        "propertyOrder" : 1400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "accountMapperConfiguration" : {
        "title" : "Account Mapper Configuration",
        "description" : "Mapping of OAuth account to local OpenAM account<br><br>Attribute
configuration that will be used to map the account of the user authenticated in the OAuth 2.0
Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</
code>",
        "propertyOrder" : 1600,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"core" : {
    "type" : "object",
    "title" : "Core",
    "propertyOrder" : 0,
    "properties" : {
        "subjectProperty" : {
            "title" : "Subject Property",
            "description" : "Property used to identify which attribute an auth server identifies a
user by.",
            "propertyOrder" : 1100,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "clientSecret" : {
            "title" : "Client Secret",
            "description" : "OAuth client_secret parameter<br><br>For more information on the OAuth
client_secret parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\"
target=\"_blank\">RFC 6749</a>, section 2.3.1",
            "propertyOrder" : 500,
            "required" : true,
            "type" : "string",
            "format" : "password",
            "exampleValue" : ""
        },
        "usesBasicAuth" : {
            "title" : "Use Basic Auth",
            "description" : "When enabled, the client will use basic auth for authenticating with
the social auth provider. Enabled by default.",
            "propertyOrder" : 1200,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "ssoProxyUrl" : {
            "title" : "Proxy URL",

```

```

        "description" : "The URL to the OpenAM OAuth proxy JSP<br><br>This URL should only be
        changed from the default, if an external server is performing the GET to POST proxying. The default
        is <code>/openam/oauth2c/OAuthProxy.jsp</code>",
        "propertyOrder" : 1300,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "clientId" : {
        "title" : "Client Id",
        "description" : "OAuth client_id parameter<br><br>For more information on the OAuth
        client_id parameter refer to the <a href=\"http://tools.ietf.org/html/rfc6749#section-2.3.1\" target=
        \"_blank\">RFC 6749</a>, section 2.3.1",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "scope" : {
        "title" : "Scope",
        "description" : "OAuth scope; list of user profile properties<br><br>According to the
        OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that
        the client application requires. The list depends on the permissions that the resource owner grants
        to the client application.<br><br>Some authorization servers use non-standard separators for
        scopes. For example, Facebook takes a comma-separated list.<br><br>",
        "propertyOrder" : 900,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "authorizeEndpoint" : {
        "title" : "Authentication Endpoint URL",
        "description" : "OAuth authentication endpoint URL<br><br>This is the URL endpoint for
        OAuth authentication provided by the OAuth Identity Provider",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "provider" : {
        "title" : "Social Provider",
        "description" : "Social Provider for which this module is being setup.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "userInfoEndpoint" : {
        "title" : "User Profile Service URL",
        "description" : "User profile information URL<br><br>This URL endpoint provides user
        profile information and is provided by the OAuth Identity Provider<br><br><i>NB </i>This URL should
        return JSON objects in response",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }

```

```
    },
    "scopeDelimiter" : {
      "title" : "Scope Delimiter",
      "description" : "Delimiter used to separate scope values. Default value is space.",
      "propertyOrder" : 1000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "tokenEndpoint" : {
      "title" : "Access Token Endpoint URL",
      "description" : "OAuth access token endpoint URL<br><br>This is the URL endpoint for
access token retrieval provided by the OAuth Identity Provider. Refer to the <a href=\"http://
tools.ietf.org/html/rfc6749#section-3.2\" target=\"_blank\">RFC 6749</a>, section 3.2",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}
```

1.184. SocialAuthentication

1.184.1. Realm Operations

Resource path: `/realm-config/services/socialauthentication`

Resource version: `1.0`

1.184.1.1. create

Usage:

```
am> create SocialAuthentication --realm Realm --body body
```


Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationChains" : {
      "title" : "Authentication Chains",
      "description" : "The name of the authentication chains that are the entry points to being
authenticated by each respective social authentication provider. The key should correspond to a
key used to define a Display Name above.<br><br>For example:<table><tr><th>Key</th><th>Value</th></
tr><tr><td>google</td><td>socialAuthChainGoogle</td></tr></table>",
      "propertyOrder" : 200,
      "required" : true,
      "patternProperties" : {
        ".*" : { }
      },
      "type" : "object",
      "exampleValue" : ""
    },
    "icons" : {
      "title" : "Icons",
      "description" : "Either a full URL or a path relative to the base of the site/server where the
image can be found. The image will be used on the login page to link to the authentication chain
defined above. The key should correspond to a key used to define a Display Name above.<br><br>For
example:<table><tr><th>Key</th><th>Value</th></tr><tr><td>google</td><td>/images/google-sign-in.png</
td></tr></table>",
      "propertyOrder" : 300,
      "required" : true,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : ""
    },
    "enabledKeys" : {
      "title" : "Enabled Implementations",
      "description" : "Provide a key that has been used to define the settings above to enable that
set of settings.<br><br>For example: google",
      "propertyOrder" : 400,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "displayNames" : {
      "title" : "Display Names",
      "description" : "The display names for the implementations - this will be used to provide a name
for the icon displayed on the login page. The key should be used across all the settings on this page
to join them together.<br><br>For example:<table><tr><th>Key</th><th>Value</th></tr><tr><td>google</
td><td>Google</td></tr></table>",
      "propertyOrder" : 100,

```

```
"required" : true,  
"patternProperties" : {  
  ".*" : {  
    "type" : "string"  
  }  
},  
"type" : "object",  
"exampleValue" : ""  
}  
}
```

1.184.1.2. delete

Usage:

```
am> delete SocialAuthentication --realm Realm
```

1.184.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthentication --realm Realm --actionName getAllTypes
```

1.184.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthentication --realm Realm --actionName getCreatableTypes
```

1.184.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthentication --realm Realm --actionName nextdescendents
```

1.184.1.6. read

Usage:

```
am> read SocialAuthentication --realm Realm
```

1.184.1.7. update

Usage:

```
am> update SocialAuthentication --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationChains" : {
      "title" : "Authentication Chains",
      "description" : "The name of the authentication chains that are the entry points to being authenticated by each respective social authentication provider. The key should correspond to a key used to define a Display Name above.<br><br>For example:<table><tr><th>Key</th><th>Value</th></tr><tr><td>google</td><td>socialAuthChainGoogle</td></tr></table>",
      "propertyOrder" : 200,
      "required" : true,
      "patternProperties" : {
        ".*" : { }
      },
      "type" : "object",
      "exampleValue" : ""
    },
    "icons" : {
      "title" : "Icons",
      "description" : "Either a full URL or a path relative to the base of the site/server where the image can be found. The image will be used on the login page to link to the authentication chain defined above. The key should correspond to a key used to define a Display Name above.<br><br>For example:<table><tr><th>Key</th><th>Value</th></tr><tr><td>google</td><td>/images/google-sign-in.png</td></tr></table>",
      "propertyOrder" : 300,
      "required" : true,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : ""
    },
    "enabledKeys" : {
      "title" : "Enabled Implementations",
      "description" : "Provide a key that has been used to define the settings above to enable that set of settings.<br><br>For example: google",
      "propertyOrder" : 400,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

```
    },
    "displayNames" : {
      "title" : "Display Names",
      "description" : "The display names for the implementations - this will be used to provide a name
for the icon displayed on the login page. The key should be used across all the settings on this page
to join them together.<br><br>For example:<table><tr><th>Key</th><th>Value</th></tr><tr><td>google/<
td><td>Google</td></tr></table>",
      "propertyOrder" : 100,
      "required" : true,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : ""
    }
  }
}
```

1.184.2. Global Operations

Resource path: [/global-config/services/socialauthentication](#)

Resource version: [1.0](#)

1.184.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialAuthentication --global --actionName getAllTypes
```

1.184.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialAuthentication --global --actionName getCreatableTypes
```

1.184.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialAuthentication --global --actionName nextdescendents
```

1.184.2.4. read

Usage:

```
am> read SocialAuthentication --global
```

1.184.2.5. update

Usage:

```
am> update SocialAuthentication --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "displayNames" : {
          "title" : "Display Names",
          "description" : "The display names for the implementations - this will be used to provide
a name for the icon displayed on the login page. The key should be used across all the settings
on this page to join them together.<br><br>For example:<table><tr><th>Key</th><th>Value</th></
tr><tr><td>google</td><td>Google</td></tr></table>",
          "propertyOrder" : 100,
          "required" : true,
          "patternProperties" : {
            ".*" : {
              "type" : "string"
            }
          }
        },
        "type" : "object",
        "exampleValue" : ""
      }
    },
    "authenticationChains" : {
      "title" : "Authentication Chains",
      "description" : "The name of the authentication chains that are the entry points to being
authenticated by each respective social authentication provider. The key should correspond to a
key used to define a Display Name above.<br><br>For example:<table><tr><th>Key</th><th>Value</th></
tr><tr><td>google</td><td>socialAuthChainGoogle</td></tr></table>",
      "propertyOrder" : 200,
      "required" : true,
      "patternProperties" : {
        ".*" : { }
      }
    },
    "type" : "object",
    "exampleValue" : ""
  }
},
"icons" : {
```

```

    "title" : "Icons",
    "description" : "Either a full URL or a path relative to the base of the site/server where
the image can be found. The image will be used on the login page to link to the authentication chain
defined above. The key should correspond to a key used to define a Display Name above.<br><br>For
example:<table><tr><th>Key</th><th>Value</th></tr><tr><td>google</td><td>/images/google-sign-in.png/<
td></tr></table>",
    "propertyOrder" : 300,
    "required" : true,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "enabledKeys" : {
    "title" : "Enabled Implementations",
    "description" : "Provide a key that has been used to define the settings above to enable
that set of settings.<br><br>For example: google",
    "propertyOrder" : 400,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}
}
}

```

1.185. SocialFacebook

1.185.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/SocialFacebookNode`

Resource version: `1.0`

1.185.1.1. create

Usage:

```
am> create SocialFacebook --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authorizeEndpoint" : {
      "title" : "Authentication Endpoint URL",
      "description" : "OAuth authentication endpoint URL <p> This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
      "propertyOrder" : 300,
      "type" : "string",
      "exampleValue" : ""
    },
    "cfgMixUpMitigation" : {
      "title" : "OAuth 2.0 Mix-Up Mitigation Enabled",
      "description" : "Enables OAuth 2.0 mix-up mitigation The authorization server must support the OAuth 2.0 Mix-Up Mitigation draft (https://tools.ietf.org/html/draft-ietf-oauth-mix-up-mitigation-01#section-3.1), otherwise OpenAM will fail to validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
      "propertyOrder" : 1700,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "scopeString" : {
      "title" : "OAuth Scope",
      "description" : "List of user profile properties<p>According to the OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the client application requires. The list depends on the permissions that the resource owner grants to the client application. Some authorization servers use non-standard separators for scopes.",
      "propertyOrder" : 600,
      "type" : "string",
      "exampleValue" : ""
    },
    "redirectURI" : {
      "title" : "Redirect URL",
      "description" : "",
      "propertyOrder" : 700,
      "type" : "string",
      "exampleValue" : ""
    },
    "basicAuth" : {
      "title" : "Use Basic Auth",
      "description" : "When enabled, the client will use basic auth for authenticating with the social auth provider. Enabled by default.",
      "propertyOrder" : 1000,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "cfgAttributeMappingClasses" : {
      "title" : "Attribute Mapper",
      "description" : "Name of the class that implements the attribute mapping This class maps the OAuth properties into OpenAM properties. A custom
```

attribute mapper can be provided. A custom attribute mapper must implement the `org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper` interface. Provided implementations are: `org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper` `org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper` (can only be used when using the openid scope)",

```

    "propertyOrder" : 1300,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "cfgAccountMapperClass" : {
    "title" : "Account Mapper",
    "description" : "Name of the class implementing the attribute mapping for the
account search. This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM. The class must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.
Provided implementations are:
<code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper
org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</code>(can only be used when
using the openid scope) String constructor parameters can be provided by appending | separated
values.",
    "propertyOrder" : 1200,
    "type" : "string",
    "exampleValue" : ""
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL <p> This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider NB This URL should return JSON objects in
response",
    "propertyOrder" : 500,
    "type" : "string",
    "exampleValue" : ""
  },
  "cfgAttributeMappingConfiguration" : {
    "title" : "Attribute Mapper Configuration",
    "description" : "Mapping of OAuth attributes to local OpenAM attributes Attribute configuration
that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data
store in the OpenAM. Example: OAuth2.0_attribute=local_attribute",
    "propertyOrder" : 1500,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter <p>For more information on the OAuth client_id
parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
    "propertyOrder" : 200,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
}

```



```

"provider" : {
  "title" : "Social Provider",
  "description" : "Social Provider for which this module is being setup.",
  "propertyOrder" : 800,
  "type" : "string",
  "exampleValue" : ""
},
"clientId" : {
  "title" : "Client ID",
  "description" : "OAuth client_id parameter<p> For more information on the OAuth client_id parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
  "propertyOrder" : 100,
  "type" : "string",
  "exampleValue" : ""
},
"tokenEndpoint" : {
  "title" : "Access Token Endpoint URL",
  "description" : "OAuth access token endpoint URL This is the URL endpoint for access token retrieval provided by the OAuth Identity Provider.Refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-3.2), section 3.2",
  "propertyOrder" : 400,
  "type" : "string",
  "exampleValue" : ""
},
"cfgAccountMapperConfiguration" : {
  "title" : "Account Mapper Configuration",
  "description" : "Mapping of OAuth account to local OpenAM account Attribute configuration that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
  "propertyOrder" : 1400,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  },
  "type" : "object",
  "exampleValue" : ""
},
"cfgAccountProviderClass" : {
  "title" : "Account Provider",
  "description" : "Name of the class implementing the account provider. This class is used by the module to find the account from the attributes mapped by the Account Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface. String constructor parameters can be provided by appending | separated values.",
  "propertyOrder" : 1100,
  "type" : "string",
  "exampleValue" : ""
},
"authenticationIdKey" : {
  "title" : "Auth ID Key",
  "description" : "",
  "propertyOrder" : 900,
  "type" : "string",
  "exampleValue" : ""
},
"issuer" : {
  "title" : "Token Issuer",

```

```

    "description" : "Required when the 'openid' scope is included. Value must match the iss field
in issued ID Token e.g. accounts.google.com The issuer value MUST be provided when OAuth 2.0 Mix-Up
Mitigation is enabled.",
    "propertyOrder" : 1800,
    "type" : "string",
    "exampleValue" : ""
  },
  "saveUserAttributesToSession" : {
    "title" : "Save Attributes in the Session",
    "description" : "If this option is enabled, the attributes configured in the attribute mapper
will be saved into the OpenAM session",
    "propertyOrder" : 1600,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"required" : [ "userInfoEndpoint", "cfgAccountProviderClass", "provider", "scopeString",
"issuer", "cfgAccountMapperConfiguration", "clientId", "cfgAttributeMappingConfiguration",
"cfgAccountMapperClass", "basicAuth", "clientSecret", "saveUserAttributesToSession",
"authenticationIdKey", "authorizeEndpoint", "tokenEndpoint", "cfgMixUpMitigation", "redirectURI",
"cfgAttributeMappingClasses" ]
}

```

1.185.1.2. delete

Usage:

```
am> delete SocialFacebook --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.185.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialFacebook --realm Realm --actionName getAllTypes
```

1.185.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialFacebook --realm Realm --actionName getCreatableTypes
```

1.185.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action SocialFacebook --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.185.1.6. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialFacebook --realm Realm --actionName nextdescendants
```

1.185.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SocialFacebook --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.185.1.8. read

Usage:

```
am> read SocialFacebook --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.185.1.9. update

Usage:

```
am> update SocialFacebook --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authorizeEndpoint" : {
      "title" : "Authentication Endpoint URL",
      "description" : "OAuth authentication endpoint URL <p> This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
      "propertyOrder" : 300,
      "type" : "string",
      "exampleValue" : ""
    },
    "cfgMixUpMitigation" : {
      "title" : "OAuth 2.0 Mix-Up Mitigation Enabled",
      "description" : "Enables OAuth 2.0 mix-up mitigation The authorization server must support the OAuth 2.0 Mix-Up Mitigation draft (https://tools.ietf.org/html/draft-ietf-oauth-mix-up-mitigation-01#section-3.1), otherwise OpenAM will fail to validate responses from the authorization server. If only the OAuth 2.0 protocol is utilized, make sure that the accepted issuer value is set in the \"Token Issuer\" setting.",
      "propertyOrder" : 1700,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "scopeString" : {
      "title" : "OAuth Scope",
      "description" : "List of user profile properties<p>According to the OAuth 2.0 Authorization Framework, scope is a space-separated list of user profile attributes that the client application requires. The list depends on the permissions that the resource owner grants to the client application. Some authorization servers use non-standard separators for scopes.",
      "propertyOrder" : 600,
      "type" : "string",
      "exampleValue" : ""
    },
    "redirectURI" : {
      "title" : "Redirect URL",
      "description" : "",
      "propertyOrder" : 700,
      "type" : "string",
      "exampleValue" : ""
    },
    "basicAuth" : {
      "title" : "Use Basic Auth",
```

```

        "description" : "When enabled, the client will use basic auth for authenticating with the social
        auth provider. Enabled by default.",
        "propertyOrder" : 1000,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "cfgAttributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute
        mapping This class maps the OAuth properties into OpenAM properties. A custom
        attribute mapper can be provided. A custom attribute mapper must implement the
        org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper interface. Provided
        implementations are: org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper
        org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the
        openid scope)",
        "propertyOrder" : 1300,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "cfgAccountMapperClass" : {
        "title" : "Account Mapper",
        "description" : "Name of the class implementing the attribute mapping for the
        account search. This class is used by the module to map from the account information
        received from the OAuth Identity Provider into OpenAM. The class must implement the
        <code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.
        Provided implementations are:
        <code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper
        org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</code>(can only be used when
        using the openid scope) String constructor parameters can be provided by appending | separated
        values.",
        "propertyOrder" : 1200,
        "type" : "string",
        "exampleValue" : ""
    },
    "userInfoEndpoint" : {
        "title" : "User Profile Service URL",
        "description" : "User profile information URL <p> This URL endpoint provides user profile
        information and is provided by the OAuth Identity Provider NB This URL should return JSON objects in
        response",
        "propertyOrder" : 500,
        "type" : "string",
        "exampleValue" : ""
    },
    "cfgAttributeMappingConfiguration" : {
        "title" : "Attribute Mapper Configuration",
        "description" : "Mapping of OAuth attributes to local OpenAM attributes Attribute configuration
        that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data
        store in the OpenAM. Example: OAuth2.0_attribute=local_attribute",
        "propertyOrder" : 1500,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    }

```

```
},
"clientSecret" : {
  "title" : "Client Secret",
  "description" : "OAuth client_secret parameter <p>For more information on the OAuth client_id parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
  "propertyOrder" : 200,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"provider" : {
  "title" : "Social Provider",
  "description" : "Social Provider for which this module is being setup.",
  "propertyOrder" : 800,
  "type" : "string",
  "exampleValue" : ""
},
"clientId" : {
  "title" : "Client ID",
  "description" : "OAuth client_id parameter<p> For more information on the OAuth client_id parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
  "propertyOrder" : 100,
  "type" : "string",
  "exampleValue" : ""
},
"tokenEndpoint" : {
  "title" : "Access Token Endpoint URL",
  "description" : "OAuth access token endpoint URL This is the URL endpoint for access token retrieval provided by the OAuth Identity Provider.Refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-3.2), section 3.2",
  "propertyOrder" : 400,
  "type" : "string",
  "exampleValue" : ""
},
"cfgAccountMapperConfiguration" : {
  "title" : "Account Mapper Configuration",
  "description" : "Mapping of OAuth account to local OpenAM account Attribute configuration that will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
  "propertyOrder" : 1400,
  "patternProperties" : {
    ".*" : {
      "type" : "string"
    }
  }
},
"cfgAccountProviderClass" : {
  "title" : "Account Provider",
  "description" : "Name of the class implementing the account provider. This class is used by the module to find the account from the attributes mapped by the Account Mapper <code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface. String constructor parameters can be provided by appending | separated values.",
  "propertyOrder" : 1100,
  "type" : "string",
  "exampleValue" : ""
},
"authenticationIdKey" : {
```

```

    "title" : "Auth ID Key",
    "description" : "",
    "propertyOrder" : 900,
    "type" : "string",
    "exampleValue" : ""
  },
  "issuer" : {
    "title" : "Token Issuer",
    "description" : "Required when the 'openid' scope is included. Value must match the iss field
in issued ID Token e.g. accounts.google.com The issuer value MUST be provided when OAuth 2.0 Mix-Up
Mitigation is enabled.",
    "propertyOrder" : 1800,
    "type" : "string",
    "exampleValue" : ""
  },
  "saveUserAttributesToSession" : {
    "title" : "Save Attributes in the Session",
    "description" : "If this option is enabled, the attributes configured in the attribute mapper
will be saved into the OpenAM session",
    "propertyOrder" : 1600,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"required" : [ "userInfoEndpoint", "cfgAccountProviderClass", "provider", "scopeString",
"issuer", "cfgAccountMapperConfiguration", "clientId", "cfgAttributeMappingConfiguration",
"cfgAccountMapperClass", "basicAuth", "clientSecret", "saveUserAttributesToSession",
"authenticationIdKey", "authorizeEndpoint", "tokenEndpoint", "cfgMixUpMitigation", "redirectURI",
"cfgAttributeMappingClasses" ]
}

```

1.186. SocialGoogle

1.186.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/SocialGoogleNode`

Resource version: [1.0](#)

1.186.1.1. create

Usage:

```
am> create SocialGoogle --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "cfgAccountMapperClass" : {
      "title" : "Account Mapper",
      "description" : "Name of the class implementing the attribute mapping for the
account search. This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM. The class must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.
Provided implementations are:
<code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper
org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</code>(can only be used when
using the openid scope) String constructor parameters can be provided by appending | separated
values.",
      "propertyOrder" : 1200,
      "type" : "string",
      "exampleValue" : ""
    },
    "clientId" : {
      "title" : "Client ID",
      "description" : "OAuth client_id parameter<p> For more information on the OAuth client_id
parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    },
    "cfgAccountMapperConfiguration" : {
      "title" : "Account Mapper Configuration",
      "description" : "Mapping of OAuth account to local OpenAM account Attribute configuration that
will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data
store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
      "propertyOrder" : 1400,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "scopeString" : {
    "title" : "OAuth Scope",
    "description" : "List of user profile properties<p>According to the OAuth 2.0 Authorization
Framework, scope is a space-separated list of user profile attributes that the client application
requires. The list depends on the permissions that the resource owner grants to the client
application. Some authorization servers use non-standard separators for scopes.",
    "propertyOrder" : 600,
    "type" : "string",
    "exampleValue" : ""
  },
  "tokenEndpoint" : {
    "title" : "Access Token Endpoint URL",
    "description" : "OAuth access token endpoint URL This is the URL endpoint for access token
retrieval provided by the OAuth Identity Provider. Refer to the RFC 6749 (http://tools.ietf.org/html/
rfc6749#section-3.2), section 3.2",

```



```

    "propertyOrder" : 400,
    "type" : "string",
    "exampleValue" : ""
  },
  "authorizeEndpoint" : {
    "title" : "Authentication Endpoint URL",
    "description" : "OAuth authentication endpoint URL <p> This is the URL endpoint for OAuth authentication provided by the OAuth Identity Provider",
    "propertyOrder" : 300,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientSecret" : {
    "title" : "Client Secret",
    "description" : "OAuth client_secret parameter <p>For more information on the OAuth client_id parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
    "propertyOrder" : 200,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "provider" : {
    "title" : "Social Provider",
    "description" : "Social Provider for which this module is being setup.",
    "propertyOrder" : 800,
    "type" : "string",
    "exampleValue" : ""
  },
  "userInfoEndpoint" : {
    "title" : "User Profile Service URL",
    "description" : "User profile information URL <p> This URL endpoint provides user profile information and is provided by the OAuth Identity Provider NB This URL should return JSON objects in response",
    "propertyOrder" : 500,
    "type" : "string",
    "exampleValue" : ""
  },
  "saveUserAttributesToSession" : {
    "title" : "Save Attributes in the Session",
    "description" : "If this option is enabled, the attributes configured in the attribute mapper will be saved into the OpenAM session",
    "propertyOrder" : 1600,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "issuer" : {
    "title" : "Token Issuer",
    "description" : "Required when the 'openid' scope is included. Value must match the iss field in issued ID Token e.g. accounts.google.com The issuer value MUST be provided when OAuth 2.0 Mix-Up Mitigation is enabled.",
    "propertyOrder" : 1800,
    "type" : "string",
    "exampleValue" : ""
  },
  "basicAuth" : {
    "title" : "Use Basic Auth",
    "description" : "When enabled, the client will use basic auth for authenticating with the social auth provider. Enabled by default.",
    "propertyOrder" : 1000,

```

```

        "type" : "boolean",
        "exampleValue" : ""
    },
    "redirectURI" : {
        "title" : "Redirect URL",
        "description" : "",
        "propertyOrder" : 700,
        "type" : "string",
        "exampleValue" : ""
    },
    "authenticationIdKey" : {
        "title" : "Auth ID Key",
        "description" : "",
        "propertyOrder" : 900,
        "type" : "string",
        "exampleValue" : ""
    },
    "cfgAccountProviderClass" : {
        "title" : "Account Provider",
        "description" : "Name of the class implementing the account provider. This class is
used by the module to find the account from the attributes mapped by the Account Mapper
<code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.
String constructor parameters can be provided by appending | separated values.",
        "propertyOrder" : 1100,
        "type" : "string",
        "exampleValue" : ""
    },
    "cfgAttributeMappingClasses" : {
        "title" : "Attribute Mapper",
        "description" : "Name of the class that implements the attribute
mapping This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided. A custom attribute mapper must implement the
org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper interface. Provided
implementations are: org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper
org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the
openid scope)",
        "propertyOrder" : 1300,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "cfgMixUpMitigation" : {
        "title" : "OAuth 2.0 Mix-Up Mitigation Enabled",
        "description" : "Enables OAuth 2.0 mix-up mitigation The authorization server must support
the OAuth 2.0 Mix-Up Mitigation draft (https://tools.ietf.org/html/draft-ietf-oauth-mix-up-mitigation-01#section-3.1), otherwise OpenAM will fail to validate responses from the authorization
server. If only the OAuth 2.0 protocol is utilized, make sure that the accepted issuer value is set
in the \"Token Issuer\" setting.",
        "propertyOrder" : 1700,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "cfgAttributeMappingConfiguration" : {
        "title" : "Attribute Mapper Configuration",
        "description" : "Mapping of OAuth attributes to local OpenAM attributes Attribute configuration
that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data
store in the OpenAM. Example: OAuth2.0_attribute=local_attribute",

```

```
    "propertyOrder" : 1500,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  }
},
"required" : [ "redirectURI", "authenticationIdKey", "cfgAccountMapperConfiguration",
"tokenEndpoint", "issuer", "scopeString", "saveUserAttributesToSession", "clientId",
"cfgAttributeMappingClasses", "cfgAccountMapperClass", "cfgAccountProviderClass",
"authorizeEndpoint", "clientSecret", "cfgAttributeMappingConfiguration", "provider",
"userInfoEndpoint", "cfgMixUpMitigation", "basicAuth" ]
}
```

1.186.1.2. delete

Usage:

```
am> delete SocialGoogle --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.186.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialGoogle --realm Realm --actionName getAllTypes
```

1.186.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialGoogle --realm Realm --actionName getCreatableTypes
```

1.186.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action SocialGoogle --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.186.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialGoogle --realm Realm --actionName nextdescendents
```

1.186.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SocialGoogle --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.186.1.8. read

Usage:

```
am> read SocialGoogle --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.186.1.9. update

Usage:

```
am> update SocialGoogle --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "cfgAccountMapperClass" : {
      "title" : "Account Mapper",
      "description" : "Name of the class implementing the attribute mapping for the
account search. This class is used by the module to map from the account information
received from the OAuth Identity Provider into OpenAM. The class must implement the
<code>org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper</code> interface.
Provided implementations are:
<code>org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper
org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper</code>(can only be used when
using the openid scope) String constructor parameters can be provided by appending | separated
values.",
      "propertyOrder" : 1200,
      "type" : "string",
      "exampleValue" : ""
    },
    "clientId" : {
      "title" : "Client ID",
      "description" : "OAuth client_id parameter<p> For more information on the OAuth client_id
parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    },
    "cfgAccountMapperConfiguration" : {
      "title" : "Account Mapper Configuration",
      "description" : "Mapping of OAuth account to local OpenAM account Attribute configuration that
will be used to map the account of the user authenticated in the OAuth 2.0 Provider to the local data
store in the OpenAM. Example: <code>OAuth2.0_attribute=local_attribute</code>",
      "propertyOrder" : 1400,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      }
    },
    "scopeString" : {
      "title" : "OAuth Scope",
      "description" : "List of user profile properties<p>According to the OAuth 2.0 Authorization
Framework, scope is a space-separated list of user profile attributes that the client application
requires. The list depends on the permissions that the resource owner grants to the client
application. Some authorization servers use non-standard separators for scopes.",
      "propertyOrder" : 600,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```
},
"tokenEndpoint" : {
  "title" : "Access Token Endpoint URL",
  "description" : "OAuth access token endpoint URL This is the URL endpoint for access token
retrieval provided by the OAuth Identity Provider.Refer to the RFC 6749 (http://tools.ietf.org/html/
rfc6749#section-3.2), section 3.2",
  "propertyOrder" : 400,
  "type" : "string",
  "exampleValue" : ""
},
"authorizeEndpoint" : {
  "title" : "Authentication Endpoint URL",
  "description" : "OAuth authentication endpoint URL <p> This is the URL endpoint for OAuth
authentication provided by the OAuth Identity Provider",
  "propertyOrder" : 300,
  "type" : "string",
  "exampleValue" : ""
},
"clientSecret" : {
  "title" : "Client Secret",
  "description" : "OAuth client_secret parameter <p>For more information on the OAuth client_id
parameter refer to the RFC 6749 (http://tools.ietf.org/html/rfc6749#section-2.3.1), section 2.3.1",
  "propertyOrder" : 200,
  "type" : "string",
  "format" : "password",
  "exampleValue" : ""
},
"provider" : {
  "title" : "Social Provider",
  "description" : "Social Provider for which this module is being setup.",
  "propertyOrder" : 800,
  "type" : "string",
  "exampleValue" : ""
},
"userInfoEndpoint" : {
  "title" : "User Profile Service URL",
  "description" : "User profile information URL <p> This URL endpoint provides user profile
information and is provided by the OAuth Identity Provider NB This URL should return JSON objects in
response",
  "propertyOrder" : 500,
  "type" : "string",
  "exampleValue" : ""
},
"saveUserAttributesToSession" : {
  "title" : "Save Attributes in the Session",
  "description" : "If this option is enabled, the attributes configured in the attribute mapper
will be saved into the OpenAM session",
  "propertyOrder" : 1600,
  "type" : "boolean",
  "exampleValue" : ""
},
"issuer" : {
  "title" : "Token Issuer",
  "description" : "Required when the 'openid' scope is included. Value must match the iss field
in issued ID Token e.g. accounts.google.com The issuer value MUST be provided when OAuth 2.0 Mix-Up
Mitigation is enabled.",
  "propertyOrder" : 1800,
  "type" : "string",
  "exampleValue" : ""
}
```

```
    },
    "basicAuth" : {
      "title" : "Use Basic Auth",
      "description" : "When enabled, the client will use basic auth for authenticating with the social
auth provider. Enabled by default.",
      "propertyOrder" : 1000,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "redirectURI" : {
      "title" : "Redirect URL",
      "description" : "",
      "propertyOrder" : 700,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationIdKey" : {
      "title" : "Auth ID Key",
      "description" : "",
      "propertyOrder" : 900,
      "type" : "string",
      "exampleValue" : ""
    },
    "cfgAccountProviderClass" : {
      "title" : "Account Provider",
      "description" : "Name of the class implementing the account provider. This class is
used by the module to find the account from the attributes mapped by the Account Mapper
<code>org.forgerock.openam.authentication.modules.common.mapping.AccountProvider</code> interface.
String constructor parameters can be provided by appending | separated values.",
      "propertyOrder" : 1100,
      "type" : "string",
      "exampleValue" : ""
    },
    "cfgAttributeMappingClasses" : {
      "title" : "Attribute Mapper",
      "description" : "Name of the class that implements the attribute
mapping This class maps the OAuth properties into OpenAM properties. A custom
attribute mapper can be provided. A custom attribute mapper must implement the
org.forgerock.openam.authentication.modules.common.mapping.AttributeMapper interface. Provided
implementations are: org.forgerock.openam.authentication.modules.common.mapping.JsonAttributeMapper
org.forgerock.openam.authentication.modules.oidc.JwtAttributeMapper (can only be used when using the
openid scope)",
      "propertyOrder" : 1300,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "cfgMixUpMitigation" : {
      "title" : "OAuth 2.0 Mix-Up Mitigation Enabled",
      "description" : "Enables OAuth 2.0 mix-up mitigation The authorization server must support
the OAuth 2.0 Mix-Up Mitigation draft (https://tools.ietf.org/html/draft-ietf-oauth-mix-up-
mitigation-01#section-3.1), otherwise OpenAM will fail to validate responses from the authorization
server. If only the OAuth 2.0 protocol is utilized, make sure that the accepted issuer value is set
in the \"Token Issuer\" setting.",
      "propertyOrder" : 1700,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}
```

```

    },
    "cfgAttributeMappingConfiguration" : {
      "title" : "Attribute Mapper Configuration",
      "description" : "Mapping of OAuth attributes to local OpenAM attributes Attribute configuration
that will be used to map the user info obtained from the OAuth 2.0 Provider to the local user data
store in the OpenAM. Example: OAuth2.0_attribute=local_attribute",
      "propertyOrder" : 1500,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      }
    },
    "type" : "object",
    "exampleValue" : ""
  }
},
"required" : [ "redirectURI", "authenticationIdKey", "cfgAccountMapperConfiguration",
"tokenEndpoint", "issuer", "scopeString", "saveUserAttributesToSession", "clientId",
"cfgAttributeMappingClasses", "cfgAccountMapperClass", "cfgAccountProviderClass",
"authorizeEndpoint", "clientSecret", "cfgAttributeMappingConfiguration", "provider",
"userInfoEndpoint", "cfgMixUpMitigation", "basicAuth" ]
}

```

1.187. SocialIgnoreProfile

1.187.1. Realm Operations

Resource path: [/realm-config/authentication/authenticationtrees/nodes/SocialOAuthIgnoreProfileNode](#)

Resource version: 1.0

1.187.1.1. create

Usage:

```
am> create SocialIgnoreProfile --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "required" : [ ]
}

```


1.187.1.2. delete

Usage:

```
am> delete SocialIgnoreProfile --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.187.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SocialIgnoreProfile --realm Realm --actionName getAllTypes
```

1.187.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SocialIgnoreProfile --realm Realm --actionName getCreatableTypes
```

1.187.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action SocialIgnoreProfile --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.187.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SocialIgnoreProfile --realm Realm --actionName nextdescendents
```

1.187.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SocialIgnoreProfile --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.187.1.8. read

Usage:

```
am> read SocialIgnoreProfile --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.187.1.9. update

Usage:

```
am> update SocialIgnoreProfile --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "required" : [ ]
}
```

1.188. SoftwarePublisher

1.188.1. Realm Operations

Agents handler that is responsible for managing agents

Resource path: `/realm-config/agents/SoftwarePublisher`

Resource version: `1.0`

1.188.1.1. create

Usage:

```
am> create SoftwarePublisher --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userpassword" : {
      "title" : "Software publisher secret",
      "description" : "Software publisher secret. Used when software statement signatures are HMAC based.",
      "propertyOrder" : 33000,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "agentgroup" : {
      "title" : "Group",
      "description" : "Add the agent to a group to allow inheritance of property values from the group. <br>Changing the group will update inherited property values. <br>Inherited property values are copied to the agent.",
      "propertyOrder" : 50,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "issuer" : {
      "title" : "Software publisher issuer",
      "description" : "Identifier for the software publisher, generally represented as a URL.",
      "propertyOrder" : 33001,
      "type" : "object",
```

```
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "string",
    "required" : true
  }
}
},
"jwkSet" : {
  "title" : "Json Web Key",
  "description" : "Raw JSON Web Key value containing the Software Publisher's public keys.",
  "propertyOrder" : 35100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
}
},
"softwareStatementSigningAlgorithm" : {
  "title" : "Software statement signing Algorithm",
  "description" : "Signing algorithm to be used when verifying software statement signatures.",
  "propertyOrder" : 34500,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
}
},
"jwksUri" : {
  "title" : "Json Web Key URI",
  "description" : "The URI that contains the Software Publisher's public keys in Json Web Key format.",
  "propertyOrder" : 34800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
```

```
        "type" : "string",
        "required" : false
    }
}
},
"jwksCacheTimeout" : {
    "title" : "JWKS URI content cache timeout in ms",
    "description" : "To avoid loading the JWKS URI content for every operation, the JWKS content is
cached. This timeout defines the maximum amount of time the JWKS URI content can be cached before
being refreshed.",
    "propertyOrder" : 34900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
}
},
"publicKeyLocation" : {
    "title" : "Public key selector",
    "description" : "Select how the Software Publisher's public keys should be retrieved by the
provider when validating software statement signatures.",
    "propertyOrder" : 34700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
}
},
"jwkStoreCacheMissCacheTime" : {
    "title" : "JWKS URI content cache miss cache time",
    "description" : "To avoid loading the JWKS URI content for every operation, especially when
the kid is not in the jwks content already cached, the JWKS content will be cached for a minimum
period of time. This cache miss cache time defines the minimum amount of time the JWKS URI content is
cached.",
    "propertyOrder" : 35000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
}
```

```
}  
  }  
} }
```

1.188.1.2. delete

Usage:

```
am> delete SoftwarePublisher --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.188.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SoftwarePublisher --realm Realm --actionName getAllTypes
```

1.188.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SoftwarePublisher --realm Realm --actionName getCreatableTypes
```

1.188.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SoftwarePublisher --realm Realm --actionName nextdescendents
```

1.188.1.6. query

Querying the agents of a specific type

Usage:

```
am> query SoftwarePublisher --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.188.1.7. read

Usage:

```
am> read SoftwarePublisher --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.188.1.8. update

Usage:

```
am> update SoftwarePublisher --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userpassword" : {
      "title" : "Software publisher secret",
      "description" : "Software publisher secret. Used when software statement signatures are HMAC based.",
      "propertyOrder" : 33000,
      "required" : true,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "agentgroup" : {
      "title" : "Group",
      "description" : "Add the agent to a group to allow inheritance of property values from the group. <br>Changing the group will update inherited property values. <br>Inherited property values are copied to the agent.",
      "propertyOrder" : 50,
      "required" : false,
```

```
    "type" : "string",
    "exampleValue" : ""
  },
  "issuer" : {
    "title" : "Software publisher issuer",
    "description" : "Identifier for the software publisher, generally represented as a URL.",
    "propertyOrder" : 33001,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  }
},
"jwkSet" : {
  "title" : "Json Web Key",
  "description" : "Raw JSON Web Key value containing the Software Publisher's public keys.",
  "propertyOrder" : 35100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"softwareStatementSigningAlgorithm" : {
  "title" : "Software statement signing Algorithm",
  "description" : "Signing algorithm to be used when verifying software statement signatures.",
  "propertyOrder" : 34500,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"jwksUri" : {
  "title" : "Json Web Key URI",
  "description" : "The URI that contains the Software Publisher's public keys in Json Web Key format.",
  "propertyOrder" : 34800,
```



```
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "string",
    "required" : false
  }
}
},
"jwksCacheTimeout" : {
  "title" : "JWKS URI content cache timeout in ms",
  "description" : "To avoid loading the JWKS URI content for every operation, the JWKS content is
cached. This timeout defines the maximum amount of time the JWKS URI content can be cached before
being refreshed.",
  "propertyOrder" : 34900,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : false
    }
  }
}
},
"publicKeyLocation" : {
  "title" : "Public key selector",
  "description" : "Select how the Software Publisher's public keys should be retrieved by the
provider when validating software statement signatures.",
  "propertyOrder" : 34700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
}
},
"jwkStoreCacheMissCacheTime" : {
  "title" : "JWKS URI content cache miss cache time",
  "description" : "To avoid loading the JWKS URI content for every operation, especially when
the kid is not in the jwks content already cached, the JWKS content will be cached for a minimum
period of time. This cache miss cache time defines the minimum amount of time the JWKS URI content is
cached.",
  "propertyOrder" : 35000,
  "type" : "object",
  "exampleValue" : "",
```

```
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "integer",
    "required" : false
  }
}
}
```

1.189. Splunk

1.189.1. Realm Operations

Resource path: `/realm-config/services/audit/Splunk`

Resource version: `1.0`

1.189.1.1. create

Usage:

```
am> create Splunk --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandlerPlugin" : {
      "type" : "object",
      "title" : "Audit Event Handler Factory",
      "propertyOrder" : 1,
      "properties" : {
        "handlerFactory" : {
          "title" : "Factory Class Name",
          "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
```

```

        "propertyOrder" : null,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"commonHandler" : {
    "type" : "object",
    "title" : "General Handler Configuration",
    "propertyOrder" : 0,
    "properties" : {
        "topics" : {
            "title" : "Topics",
            "description" : "List of topics handled by an audit event handler.",
            "propertyOrder" : 200,
            "required" : true,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "enabled" : {
            "title" : "Enabled",
            "description" : "Enables or disables an audit event handler.",
            "propertyOrder" : 100,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        }
    }
}
},
"splunkBuffering" : {
    "type" : "object",
    "title" : "Buffering",
    "propertyOrder" : 3,
    "properties" : {
        "writeInterval" : {
            "title" : "Write interval (in milliseconds)",
            "description" : "Interval at which buffered events are written to Splunk.",
            "propertyOrder" : 800,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        },
        "maxEvents" : {
            "title" : "Queue Capacity",
            "description" : "Maximum number of audit evens in the batch queue; additional events are
dropped.",
            "propertyOrder" : 700,
            "required" : true,
            "type" : "integer",
            "exampleValue" : ""
        }
    },
    "batchSize" : {
        "title" : "Batch Size",
        "description" : "Maximum number of events that can be buffered (default: 10000).",
        "propertyOrder" : 600,

```


--id

The unique identifier for the resource.

1.189.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Splunk --realm Realm --actionName getAllTypes
```

1.189.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Splunk --realm Realm --actionName getCreatableTypes
```

1.189.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Splunk --realm Realm --actionName nextdescendents
```

1.189.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Splunk --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.189.1.7. read

Usage:

```
am> read Splunk --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.189.1.8. update

Usage:

```
am> update Splunk --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandlerPlugin" : {
      "type" : "object",
      "title" : "Audit Event Handler Factory",
      "propertyOrder" : 1,
      "properties" : {
        "handlerFactory" : {
          "title" : "Factory Class Name",
          "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
          "propertyOrder" : null,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 200,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      }
    }
  }
}
```

```

    "enabled" : {
      "title" : "Enabled",
      "description" : "Enables or disables an audit event handler.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    }
  },
  "splunkBuffering" : {
    "type" : "object",
    "title" : "Buffering",
    "propertyOrder" : 3,
    "properties" : {
      "writeInterval" : {
        "title" : "Write interval (in milliseconds)",
        "description" : "Interval at which buffered events are written to Splunk.",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      },
      "maxEvents" : {
        "title" : "Queue Capacity",
        "description" : "Maximum number of audit evens in the batch queue; additional events are
dropped.",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      },
      "batchSize" : {
        "title" : "Batch Size",
        "description" : "Maximum number of events that can be buffered (default: 10000).",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      }
    }
  },
  "splunkConfig" : {
    "type" : "object",
    "title" : "Splunk Configuration",
    "propertyOrder" : 2,
    "properties" : {
      "sslEnabled" : {
        "title" : "SSL Enabled",
        "description" : "Use HTTPS protocol for communication with Splunk.",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "host" : {
        "title" : "Server Hostname",
        "description" : "Host name or IP address of Splunk server.",
        "propertyOrder" : 300,

```

```
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authzToken" : {
    "title" : "Authorization Token",
    "description" : "Authorization token used to connect to Splunk HTTP Event Collector
endpoint.",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "port" : {
    "title" : "Server Port",
    "description" : "Port number of Splunk server.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
}
```

1.189.2. Global Operations

Resource path: `/global-config/services/audit/Splunk`

Resource version: `1.0`

1.189.2.1. create

Usage:

```
am> create Splunk --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
```



```

"propertyOrder" : 0,
"properties" : {
  "enabled" : {
    "title" : "Enabled",
    "description" : "Enables or disables an audit event handler.",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "topics" : {
    "title" : "Topics",
    "description" : "List of topics handled by an audit event handler.",
    "propertyOrder" : 200,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"splunkBuffering" : {
  "type" : "object",
  "title" : "Buffering",
  "propertyOrder" : 3,
  "properties" : {
    "writeInterval" : {
      "title" : "Write interval (in milliseconds)",
      "description" : "Interval at which buffered events are written to Splunk.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "maxEvents" : {
      "title" : "Queue Capacity",
      "description" : "Maximum number of audit evens in the batch queue; additional events are
dropped.",
      "propertyOrder" : 700,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "batchSize" : {
      "title" : "Batch Size",
      "description" : "Maximum number of events that can be buffered (default: 10000).",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,

```

```
"properties" : {
  "handlerFactory" : {
    "title" : "Factory Class Name",
    "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"splunkConfig" : {
  "type" : "object",
  "title" : "Splunk Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "port" : {
      "title" : "Server Port",
      "description" : "Port number of Splunk server.",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "host" : {
      "title" : "Server Hostname",
      "description" : "Host name or IP address of Splunk server.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sslEnabled" : {
      "title" : "SSL Enabled",
      "description" : "Use HTTPS protocol for communication with Splunk.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "authzToken" : {
      "title" : "Authorization Token",
      "description" : "Authorization token used to connect to Splunk HTTP Event Collector
endpoint.",
      "propertyOrder" : null,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
```

1.189.2.2. delete

Usage:

```
am> delete Splunk --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.189.2.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Splunk --global --actionName getAllTypes
```

1.189.2.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Splunk --global --actionName getCreatableTypes
```

1.189.2.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Splunk --global --actionName nextdescendents
```

1.189.2.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Splunk --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.189.2.7. read

Usage:

```
am> read Splunk --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.189.2.8. update

Usage:

```
am> update Splunk --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 200,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      }
    }
  }
}
```

```

    }
  },
  "splunkBuffering" : {
    "type" : "object",
    "title" : "Buffering",
    "propertyOrder" : 3,
    "properties" : {
      "writeInterval" : {
        "title" : "Write interval (in milliseconds)",
        "description" : "Interval at which buffered events are written to Splunk.",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      },
      "maxEvents" : {
        "title" : "Queue Capacity",
        "description" : "Maximum number of audit events in the batch queue; additional events are
dropped.",
        "propertyOrder" : 700,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      },
      "batchSize" : {
        "title" : "Batch Size",
        "description" : "Maximum number of events that can be buffered (default: 10000).",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
      }
    }
  },
  "commonHandlerPlugin" : {
    "type" : "object",
    "title" : "Audit Event Handler Factory",
    "propertyOrder" : 1,
    "properties" : {
      "handlerFactory" : {
        "title" : "Factory Class Name",
        "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
        "propertyOrder" : null,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      }
    }
  },
  "splunkConfig" : {
    "type" : "object",
    "title" : "Splunk Configuration",
    "propertyOrder" : 2,
    "properties" : {
      "port" : {
        "title" : "Server Port",
        "description" : "Port number of Splunk server.",

```

```
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "host" : {
    "title" : "Server Hostname",
    "description" : "Host name or IP address of Splunk server.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sslEnabled" : {
    "title" : "SSL Enabled",
    "description" : "Use HTTPS protocol for communication with Splunk.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "authzToken" : {
    "title" : "Authorization Token",
    "description" : "Authorization token used to connect to Splunk HTTP Event Collector
endpoint.",
    "propertyOrder" : null,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.190. SubjectAttributes

1.190.1. Realm Operations

Service for querying subject attributes stored in OpenAM. When you define a policy subject condition, the condition can depend on values of subject attributes stored in a user's profile. The list of possible subject attributes that you can use depends on the LDAP User Attributes configured for the Identity data store where OpenAM looks up the user's profile

Resource path: [/subjectattributes](#)

Resource version: [1.0](#)

1.190.1.1. query

Query the list of subject attributes stored in OpenAM

Usage:

```
am> query SubjectAttributes --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.191. SubjectTypes

1.191.1. Realm Operations

Service for querying and reading the subject types stored in OpenAM. Subject condition types describe the JSON representation of subject conditions that you can use in policy definitions

Resource path: [/subjecttypes](#)

Resource version: [1.0](#)

1.191.1.1. query

Query the list of subject condition types

Usage:

```
am> query SubjectTypes --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

1.191.1.2. read

Read an individual subject condition type by providing the unique identifier title

Usage:

```
am> read SubjectTypes --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.192. SuccessURL

1.192.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/SetSuccessUrlNode`

Resource version: `1.0`

1.192.1.1. create

Usage:

```
am> create SuccessURL --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "successUrl" : {
      "title" : "Success URL",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "successUrl" ]
}
```

1.192.1.2. delete

Usage:

```
am> delete SuccessURL --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.192.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SuccessURL --realm Realm --actionName getAllTypes
```

1.192.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SuccessURL --realm Realm --actionName getCreatableTypes
```

1.192.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action SuccessURL --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.192.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SuccessURL --realm Realm --actionName nextdescendents
```

1.192.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SuccessURL --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.192.1.8. read

Usage:

```
am> read SuccessURL --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.192.1.9. update

Usage:

```
am> update SuccessURL --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "successUrl" : {
      "title" : "Success URL",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "successUrl" ]
}
```

1.193. SunDSWithOpenAMSchema

1.193.1. Realm Operations

Resource path: `/realm-config/services/id-repositories/LDAPv3ForAMDS`

Resource version: `1.0`

1.193.1.1. create

Usage:

```
am> create SunDSWithOpenAMSchema --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "roleconfig" : {
      "type" : "object",
      "title" : "Role Configuration",
      "propertyOrder" : 6,
      "properties" : {
        "sun-idrepo-ldapv3-config-nsrole" : {
          "title" : "Attribute Name for Filtered Role Membership",
          "description" : "",
          "propertyOrder" : 4700,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-role-objectclass" : {
          "title" : "LDAP Roles Object Class",
          "description" : "",
          "propertyOrder" : 4100,
          "required" : false,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-nsrolefilter" : {
          "title" : "Attribute Name of Filtered Role Filter",
          "description" : "",
          "propertyOrder" : 4900,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        }
      },
      "sun-idrepo-ldapv3-config-filterroles-search-attribute" : {
```

```
"title" : "LDAP Filter Roles Search Attribute",
"description" : "",
"propertyOrder" : 4300,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-filterrole-attributes" : {
"title" : "LDAP Filter Roles Attributes",
"description" : "",
"propertyOrder" : 4600,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-roles-search-filter" : {
"title" : "LDAP Roles Search Filter",
"description" : "",
"propertyOrder" : 4000,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-filterroles-search-filter" : {
"title" : "LDAP Filter Roles Search Filter",
"description" : "",
"propertyOrder" : 4400,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-role-attributes" : {
"title" : "LDAP Roles Attributes",
"description" : "",
"propertyOrder" : 4200,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-filterrole-objectclass" : {
"title" : "LDAP Filter Roles Object Class",
"description" : "",
"propertyOrder" : 4500,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-roles-search-attribute" : {
"title" : "LDAP Roles Search Attribute",
"description" : "",
```

```

    "propertyOrder" : 3900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-nsroledn" : {
    "title" : "Attribute Name of Role Membership.",
    "description" : "",
    "propertyOrder" : 4800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"ldapsettings" : {
  "type" : "object",
  "title" : "Server Settings",
  "propertyOrder" : 0,
  "properties" : {
    "openam-idrepo-ldapv3-behera-support-enabled" : {
      "title" : "Behera Support Enabled",
      "description" : "When enabled, Behera draft control will be used in the outgoing requests
for operations that may modify password value. This will allow OpenAM to display password policy
related error messages when password policies are not met.",
      "propertyOrder" : 6100,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-authpw" : {
      "title" : "LDAP Bind Password",
      "description" : "",
      "propertyOrder" : 800,
      "required" : false,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-authid" : {
      "title" : "LDAP Bind DN",
      "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
      "propertyOrder" : 700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-search-scope" : {
      "title" : "LDAPv3 Plug-in Search Scope",
      "description" : "",
      "propertyOrder" : 2000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
      "title" : "LDAP Connection Pool Maximum Size",
      "description" : "",

```

```

        "propertyOrder" : 1200,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-organization_name" : {
        "title" : "LDAP Organization DN",
        "description" : "",
        "propertyOrder" : 900,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-max-result" : {
        "title" : "Maximum Results Returned from Search",
        "description" : "",
        "propertyOrder" : 1500,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-interval" : {
        "title" : "LDAP Connection Heartbeat Interval",
        "description" : "Specifies how often should OpenAM send a heartbeat request to the
        directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
        request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
        error) then it may take up to the interval period before the problem is detected. Use along with the
        Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
        disabling heartbeat requests.",
        "propertyOrder" : 1300,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-connection-mode" : {
        "title" : "LDAP Connection Mode",
        "description" : "Defines which protocol/operation is used to establish the connection to
        the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
        passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
        connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
        using StartTLS extended operation.",
        "propertyOrder" : 1000,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-ldap-server" : {
        "title" : "LDAP Server",
        "description" : "Format: LDAP server host name:port | server_ID | site_ID",
        "propertyOrder" : 600,
        "required" : true,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-time-limit" : {
        "title" : "Search Timeout",
    }

```

```

        "description" : "In seconds.",
        "propertyOrder" : 1600,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-timeunit" : {
        "title" : "LDAP Connection Heartbeat Time Unit",
        "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
it may take up to the interval period before the problem is detected. Use along with the Heartbeat
Interval parameter to define the exact interval.",
        "propertyOrder" : 1400,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"groupconfig" : {
    "type" : "object",
    "title" : "Group Configuration",
    "propertyOrder" : 5,
    "properties" : {
        "sun-idrepo-ldapv3-config-memberurl" : {
            "title" : "Attribute Name of Group Member URL",
            "description" : "",
            "propertyOrder" : 3700,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-group-container-value" : {
            "title" : "LDAP Groups Container Value",
            "description" : "",
            "propertyOrder" : 3200,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-group-attributes" : {
            "title" : "LDAP Groups Attributes",
            "description" : "",
            "propertyOrder" : 3400,
            "required" : false,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-memberof" : {
            "title" : "Attribute Name for Group Membership",
            "description" : "",
            "propertyOrder" : 3500,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}

```

```

    },
    "sun-idrepo-ldapv3-config-groups-search-filter" : {
      "title" : "LDAP Groups Search Filter",
      "description" : "",
      "propertyOrder" : 3000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "sun-idrepo-ldapv3-config-group-objectclass" : {
      "title" : "LDAP Groups Object Class",
      "description" : "",
      "propertyOrder" : 3300,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    },
    "sun-idrepo-ldapv3-config-groups-search-attribute" : {
      "title" : "LDAP Groups Search Attribute",
      "description" : "",
      "propertyOrder" : 2900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "sun-idrepo-ldapv3-config-unique-member" : {
      "title" : "Attribute Name of Unique Member",
      "description" : "",
      "propertyOrder" : 3600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "sun-idrepo-ldapv3-config-group-container-name" : {
      "title" : "LDAP Groups Container Naming Attribute",
      "description" : "",
      "propertyOrder" : 3100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"userconfig" : {
  "type" : "object",
  "title" : "User Configuration",
  "propertyOrder" : 3,
  "properties" : {
    "sun-idrepo-ldapv3-config-people-container-value" : {
      "title" : "LDAP People Container Value",
      "description" : "",
      "propertyOrder" : 5100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},

```



```
"sun-idrepo-ldapv3-config-user-attributes" : {
  "title" : "LDAP User Attributes",
  "description" : "",
  "propertyOrder" : 2400,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-inactive" : {
  "title" : "User Status Inactive Value",
  "description" : "",
  "propertyOrder" : 2800,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-attr" : {
  "title" : "Knowledge Based Authentication Attribute Name",
  "description" : "",
  "propertyOrder" : 5300,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-attempts-attr" : {
  "title" : "Knowledge Based Authentication Attempts Attribute Name",
  "description" : "",
  "propertyOrder" : 5410,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-people-container-name" : {
  "title" : "LDAP People Container Naming Attribute",
  "description" : "",
  "propertyOrder" : 5000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-user-objectclass" : {
  "title" : "LDAP User Object Class",
  "description" : "",
  "propertyOrder" : 2300,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-index-attr" : {
  "title" : "Knowledge Based Authentication Active Index",
```

```
"description" : "",
"propertyOrder" : 5400,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-users-search-attribute" : {
  "title" : "LDAP Users Search Attribute",
  "description" : "",
  "propertyOrder" : 2100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
  "title" : "Create User Attribute Mapping",
  "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
  "propertyOrder" : 2500,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-isactive" : {
  "title" : "Attribute Name of User Status",
  "description" : "",
  "propertyOrder" : 2600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-active" : {
  "title" : "User Status Active Value",
  "description" : "",
  "propertyOrder" : 2700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-users-search-filter" : {
  "title" : "LDAP Users Search Filter",
  "description" : "",
  "propertyOrder" : 2200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"cachecontrol" : {
  "type" : "object",
  "title" : "Cache Control",
  "propertyOrder" : 9,
  "properties" : {
    "sun-idrepo-ldapv3-dncache-enabled" : {
      "title" : "DN Cache",
```

```

    "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
    "propertyOrder" : 5900,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-dncache-size" : {
    "title" : "DN Cache Size",
    "description" : "In DN items, only used when DN Cache is enabled.",
    "propertyOrder" : 6000,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  }
}
},
"persistentsearch" : {
  "type" : "object",
  "title" : "Persistent Search Controls",
  "propertyOrder" : 7,
  "properties" : {
    "sun-idrepo-ldapv3-config-psearch-scope" : {
      "title" : "Persistent Search Scope",
      "description" : "",
      "propertyOrder" : 5700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-psearchbase" : {
      "title" : "Persistent Search Base DN",
      "description" : "",
      "propertyOrder" : 5500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-psearch-filter" : {
      "title" : "Persistent Search Filter",
      "description" : "",
      "propertyOrder" : 5600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
},
"authentication" : {
  "type" : "object",
  "title" : "Authentication Configuration",
  "propertyOrder" : 4,
  "properties" : {
    "sun-idrepo-ldapv3-config-auth-naming-attr" : {
      "title" : "Authentication Naming Attribute",
      "description" : "",

```

```
        "propertyOrder" : 5200,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"pluginconfig" : {
    "type" : "object",
    "title" : "Plug-in Configuration",
    "propertyOrder" : 2,
    "properties" : {
        "sunIdRepoAttributeMapping" : {
            "title" : "Attribute Name Mapping",
            "description" : "",
            "propertyOrder" : 1800,
            "required" : false,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "sunIdRepoSupportedOperations" : {
            "title" : "LDAPv3 Plug-in Supported Types and Operations",
            "description" : "",
            "propertyOrder" : 1900,
            "required" : false,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "sunIdRepoClass" : {
            "title" : "LDAPv3 Repository Plug-in Class Name",
            "description" : "",
            "propertyOrder" : 1700,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
},
"errorhandling" : {
    "type" : "object",
    "title" : "Error Handling Configuration",
    "propertyOrder" : 8,
    "properties" : {
        "com.iplanet.am.ldap.connection.delay.between.retries" : {
            "title" : "The Delay Time Between Retries",
            "description" : "In milliseconds.",
            "propertyOrder" : 5800,
            "required" : false,
            "type" : "integer",
            "exampleValue" : ""
        }
    }
}
}
```

```
}  
}
```

1.193.1.2. delete

Usage:

```
am> delete SunDSWithOpenAMSchema --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.193.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SunDSWithOpenAMSchema --realm Realm --actionName getAllTypes
```

1.193.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SunDSWithOpenAMSchema --realm Realm --actionName getCreatableTypes
```

1.193.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SunDSWithOpenAMSchema --realm Realm --actionName nextdescendents
```

1.193.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SunDSWithOpenAMSchema --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.193.1.7. read

Usage:

```
am> read SunDSWithOpenAMSchema --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.193.1.8. update

Usage:

```
am> update SunDSWithOpenAMSchema --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "roleconfig" : {
      "type" : "object",
      "title" : "Role Configuration",
      "propertyOrder" : 6,
      "properties" : {
        "sun-idrepo-ldapv3-config-nsrole" : {
          "title" : "Attribute Name for Filtered Role Membership",
          "description" : "",
          "propertyOrder" : 4700,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-role-objectclass" : {
          "title" : "LDAP Roles Object Class",
          "description" : "",
          "propertyOrder" : 4100,
          "required" : false,
          "items" : {
```

```

    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-nsrolefilter" : {
  "title" : "Attribute Name of Filtered Role Filter",
  "description" : "",
  "propertyOrder" : 4900,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-filterroles-search-attribute" : {
  "title" : "LDAP Filter Roles Search Attribute",
  "description" : "",
  "propertyOrder" : 4300,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-filterrole-attributes" : {
  "title" : "LDAP Filter Roles Attributes",
  "description" : "",
  "propertyOrder" : 4600,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-roles-search-filter" : {
  "title" : "LDAP Roles Search Filter",
  "description" : "",
  "propertyOrder" : 4000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-filterroles-search-filter" : {
  "title" : "LDAP Filter Roles Search Filter",
  "description" : "",
  "propertyOrder" : 4400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-role-attributes" : {
  "title" : "LDAP Roles Attributes",
  "description" : "",
  "propertyOrder" : 4200,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},

```

```

"sun-idrepo-ldapv3-config-filterrole-objectclass" : {
  "title" : "LDAP Filter Roles Object Class",
  "description" : "",
  "propertyOrder" : 4500,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-roles-search-attribute" : {
  "title" : "LDAP Roles Search Attribute",
  "description" : "",
  "propertyOrder" : 3900,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-nsroledn" : {
  "title" : "Attribute Name of Role Membership.",
  "description" : "",
  "propertyOrder" : 4800,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"ldapsettings" : {
  "type" : "object",
  "title" : "Server Settings",
  "propertyOrder" : 0,
  "properties" : {
    "openam-idrepo-ldapv3-behera-support-enabled" : {
      "title" : "Behera Support Enabled",
      "description" : "When enabled, Behera draft control will be used in the outgoing requests
for operations that may modify password value. This will allow OpenAM to display password policy
related error messages when password policies are not met.",
      "propertyOrder" : 6100,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-authpw" : {
      "title" : "LDAP Bind Password",
      "description" : "",
      "propertyOrder" : 800,
      "required" : false,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-authid" : {
      "title" : "LDAP Bind DN",
      "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
      "propertyOrder" : 700,
      "required" : false,

```



```

    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-search-scope" : {
    "title" : "LDAPv3 Plug-in Search Scope",
    "description" : "",
    "propertyOrder" : 2000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
    "title" : "LDAP Connection Pool Maximum Size",
    "description" : "",
    "propertyOrder" : 1200,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-organization_name" : {
    "title" : "LDAP Organization DN",
    "description" : "",
    "propertyOrder" : 900,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-max-result" : {
    "title" : "Maximum Results Returned from Search",
    "description" : "",
    "propertyOrder" : 1500,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-heartbeat-interval" : {
    "title" : "LDAP Connection Heartbeat Interval",
    "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
error) then it may take up to the interval period before the problem is detected. Use along with the
Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
disabling heartbeat requests.",
    "propertyOrder" : 1300,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection-mode" : {
    "title" : "LDAP Connection Mode",
    "description" : "Defines which protocol/operation is used to establish the connection to
the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
    "propertyOrder" : 1000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}

```

```

},
"sun-idrepo-ldapv3-config-ldap-server" : {
  "title" : "LDAP Server",
  "description" : "Format: LDAP server host name:port | server_ID | site_ID",
  "propertyOrder" : 600,
  "required" : true,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-time-limit" : {
  "title" : "Search Timeout",
  "description" : "In seconds.",
  "propertyOrder" : 1600,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"openam-idrepo-ldapv3-heartbeat-timeunit" : {
  "title" : "LDAP Connection Heartbeat Time Unit",
  "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
it may take up to the interval period before the problem is detected. Use along with the Heartbeat
Interval parameter to define the exact interval.",
  "propertyOrder" : 1400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"groupconfig" : {
  "type" : "object",
  "title" : "Group Configuration",
  "propertyOrder" : 5,
  "properties" : {
    "sun-idrepo-ldapv3-config-memberurl" : {
      "title" : "Attribute Name of Group Member URL",
      "description" : "",
      "propertyOrder" : 3700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-container-value" : {
      "title" : "LDAP Groups Container Value",
      "description" : "",
      "propertyOrder" : 3200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-attributes" : {
      "title" : "LDAP Groups Attributes",
      "description" : "",
      "propertyOrder" : 3400,

```

```
"required" : false,
"items" : {
  "type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-memberof" : {
  "title" : "Attribute Name for Group Membership",
  "description" : "",
  "propertyOrder" : 3500,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-groups-search-filter" : {
  "title" : "LDAP Groups Search Filter",
  "description" : "",
  "propertyOrder" : 3000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-objectclass" : {
  "title" : "LDAP Groups Object Class",
  "description" : "",
  "propertyOrder" : 3300,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-groups-search-attribute" : {
  "title" : "LDAP Groups Search Attribute",
  "description" : "",
  "propertyOrder" : 2900,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-unique-member" : {
  "title" : "Attribute Name of Unique Member",
  "description" : "",
  "propertyOrder" : 3600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-group-container-name" : {
  "title" : "LDAP Groups Container Naming Attribute",
  "description" : "",
  "propertyOrder" : 3100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
```

```
},
"userconfig" : {
  "type" : "object",
  "title" : "User Configuration",
  "propertyOrder" : 3,
  "properties" : {
    "sun-idrepo-ldapv3-config-people-container-value" : {
      "title" : "LDAP People Container Value",
      "description" : "",
      "propertyOrder" : 5100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-user-attributes" : {
      "title" : "LDAP User Attributes",
      "description" : "",
      "propertyOrder" : 2400,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-inactive" : {
      "title" : "User Status Inactive Value",
      "description" : "",
      "propertyOrder" : 2800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-auth-kba-attr" : {
      "title" : "Knowledge Based Authentication Attribute Name",
      "description" : "",
      "propertyOrder" : 5300,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-auth-kba-attempts-attr" : {
      "title" : "Knowledge Based Authentication Attempts Attribute Name",
      "description" : "",
      "propertyOrder" : 5410,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-people-container-name" : {
      "title" : "LDAP People Container Naming Attribute",
      "description" : "",
      "propertyOrder" : 5000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```
},
"sun-idrepo-ldapv3-config-user-objectclass" : {
  "title" : "LDAP User Object Class",
  "description" : "",
  "propertyOrder" : 2300,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-index-attr" : {
  "title" : "Knowledge Based Authentication Active Index",
  "description" : "",
  "propertyOrder" : 5400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-users-search-attribute" : {
  "title" : "LDAP Users Search Attribute",
  "description" : "",
  "propertyOrder" : 2100,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
  "title" : "Create User Attribute Mapping",
  "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
  "propertyOrder" : 2500,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-isactive" : {
  "title" : "Attribute Name of User Status",
  "description" : "",
  "propertyOrder" : 2600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-active" : {
  "title" : "User Status Active Value",
  "description" : "",
  "propertyOrder" : 2700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-users-search-filter" : {
  "title" : "LDAP Users Search Filter",
  "description" : "",
  "propertyOrder" : 2200,
```

```

        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    }
},
"cachecontrol" : {
    "type" : "object",
    "title" : "Cache Control",
    "propertyOrder" : 9,
    "properties" : {
        "sun-idrepo-ldapv3-dncache-enabled" : {
            "title" : "DN Cache",
            "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
            "propertyOrder" : 5900,
            "required" : false,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-dncache-size" : {
            "title" : "DN Cache Size",
            "description" : "In DN items, only used when DN Cache is enabled.",
            "propertyOrder" : 6000,
            "required" : false,
            "type" : "integer",
            "exampleValue" : ""
        }
    }
},
"persistentsearch" : {
    "type" : "object",
    "title" : "Persistent Search Controls",
    "propertyOrder" : 7,
    "properties" : {
        "sun-idrepo-ldapv3-config-psearch-scope" : {
            "title" : "Persistent Search Scope",
            "description" : "",
            "propertyOrder" : 5700,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-psearchbase" : {
            "title" : "Persistent Search Base DN",
            "description" : "",
            "propertyOrder" : 5500,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-psearch-filter" : {
            "title" : "Persistent Search Filter",
            "description" : "",
            "propertyOrder" : 5600,
            "required" : false,

```

```
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"authentication" : {
    "type" : "object",
    "title" : "Authentication Configuration",
    "propertyOrder" : 4,
    "properties" : {
        "sun-idrepo-ldapv3-config-auth-naming-attr" : {
            "title" : "Authentication Naming Attribute",
            "description" : "",
            "propertyOrder" : 5200,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        }
    }
},
"pluginconfig" : {
    "type" : "object",
    "title" : "Plug-in Configuration",
    "propertyOrder" : 2,
    "properties" : {
        "sunIdRepoAttributeMapping" : {
            "title" : "Attribute Name Mapping",
            "description" : "",
            "propertyOrder" : 1800,
            "required" : false,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "sunIdRepoSupportedOperations" : {
            "title" : "LDAPv3 Plug-in Supported Types and Operations",
            "description" : "",
            "propertyOrder" : 1900,
            "required" : false,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "sunIdRepoClass" : {
            "title" : "LDAPv3 Repository Plug-in Class Name",
            "description" : "",
            "propertyOrder" : 1700,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
},
"errorhandling" : {
    "type" : "object",
```

```
"title" : "Error Handling Configuration",
"propertyOrder" : 8,
"properties" : {
  "com.iplanet.am.ldap.connection.delay.between.retries" : {
    "title" : "The Delay Time Between Retries",
    "description" : "In milliseconds.",
    "propertyOrder" : 5800,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  }
}
}
```

1.194. SupportedIds

1.194.1. Global Operations

Resource path: `/global-config/services/id-repositories/SupportedIdentities`

Resource version: `1.0`

1.194.1.1. create

Usage:

```
am> create SupportedIds --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object"
}
```

1.194.1.2. delete

Usage:


```
am> delete SupportedIds --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.194.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action SupportedIds --global --actionName getAllTypes
```

1.194.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action SupportedIds --global --actionName getCreatableTypes
```

1.194.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action SupportedIds --global --actionName nextdescendents
```

1.194.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query SupportedIds --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.194.1.7. read

Usage:

```
am> read SupportedIds --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.194.1.8. update

Usage:

```
am> update SupportedIds --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object"
}
```

1.195. Syslog

1.195.1. Realm Operations

Resource path: [/realm-config/services/audit/Syslog](#)

Resource version: [1.0](#)

1.195.1.1. create

Usage:

```
am> create Syslog --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 2300,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 2200,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        }
      }
    },
    "sysLogConfig" : {
      "type" : "object",
      "title" : "Syslog Configuration",
      "propertyOrder" : 2,
      "properties" : {
        "transportProtocol" : {
          "title" : "Transport Protocol",
          "description" : "",
          "propertyOrder" : 2600,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "connectTimeout" : {
          "title" : "Connection timeout",
          "description" : "Timeout for connecting to syslog server, in seconds.",
          "propertyOrder" : 2700,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "facility" : {
          "title" : "Facility",
          "description" : "Syslog facility value to apply to all events.",
          "propertyOrder" : 2800,
          "required" : true,

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "port" : {
    "title" : "Server port",
    "description" : "Port number of receiving syslog server.",
    "propertyOrder" : 2500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "host" : {
    "title" : "Server hostname",
    "description" : "Host name or IP address of receiving syslog server.",
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"sysLogBuffering" : {
  "type" : "object",
  "title" : "Buffering",
  "propertyOrder" : 3,
  "properties" : {
    "bufferingEnabled" : {
      "title" : "Buffering Enabled",
      "description" : "Enables or disables audit event buffering.",
      "propertyOrder" : 2900,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "bufferingMaxSize" : {
      "title" : "Buffer Size",
      "description" : "Maximum number of events that can be buffered (default/minimum: 5000)",
      "propertyOrder" : 2950,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory responsible for creating the Audit Event Handler. The class must implement org.forgerock.openam.audit.AuditEventHandlerFactory.",
      "propertyOrder" : 3000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}

```

```
}  
  }  
} }
```

1.195.1.2. delete

Usage:

```
am> delete Syslog --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.195.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Syslog --realm Realm --actionName getAllTypes
```

1.195.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Syslog --realm Realm --actionName getCreatableTypes
```

1.195.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Syslog --realm Realm --actionName nextdescendents
```

1.195.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Syslog --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.195.1.7. read

Usage:

```
am> read Syslog --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.195.1.8. update

Usage:

```
am> update Syslog --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 2300,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
```

```
        "propertyOrder" : 2200,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"sysLogConfig" : {
    "type" : "object",
    "title" : "Syslog Configuration",
    "propertyOrder" : 2,
    "properties" : {
        "transportProtocol" : {
            "title" : "Transport Protocol",
            "description" : "",
            "propertyOrder" : 2600,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "connectTimeout" : {
            "title" : "Connection timeout",
            "description" : "Timeout for connecting to syslog server, in seconds.",
            "propertyOrder" : 2700,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "facility" : {
            "title" : "Facility",
            "description" : "Syslog facility value to apply to all events.",
            "propertyOrder" : 2800,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "port" : {
            "title" : "Server port",
            "description" : "Port number of receiving syslog server.",
            "propertyOrder" : 2500,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        },
        "host" : {
            "title" : "Server hostname",
            "description" : "Host name or IP address of receiving syslog server.",
            "propertyOrder" : 2400,
            "required" : true,
            "type" : "string",
            "exampleValue" : ""
        }
    }
}
},
"sysLogBuffering" : {
    "type" : "object",
    "title" : "Buffering",
    "propertyOrder" : 3,
    "properties" : {
```

```
"bufferingEnabled" : {
  "title" : "Buffering Enabled",
  "description" : "Enables or disables audit event buffering.",
  "propertyOrder" : 2900,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"bufferingMaxSize" : {
  "title" : "Buffer Size",
  "description" : "Maximum number of events that can be buffered (default/minimum: 5000)",
  "propertyOrder" : 2950,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 3000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
```

1.195.2. Global Operations

Resource path: `/global-config/services/audit/Syslog`

Resource version: `1.0`

1.195.2.1. create

Usage:

```
am> create Syslog --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 2200,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "topics" : {
          "title" : "Topics",
          "description" : "List of topics handled by an audit event handler.",
          "propertyOrder" : 2300,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      }
    },
    "sysLogBuffering" : {
      "type" : "object",
      "title" : "Buffering",
      "propertyOrder" : 3,
      "properties" : {
        "bufferingEnabled" : {
          "title" : "Buffering Enabled",
          "description" : "Enables or disables audit event buffering.",
          "propertyOrder" : 2900,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "bufferingMaxSize" : {
          "title" : "Buffer Size",
          "description" : "Maximum number of events that can be buffered (default/minimum: 5000)",
          "propertyOrder" : 2950,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    }
  }
}
```

```
},
"sysLogConfig" : {
  "type" : "object",
  "title" : "Syslog Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "facility" : {
      "title" : "Facility",
      "description" : "Syslog facility value to apply to all events.",
      "propertyOrder" : 2800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "transportProtocol" : {
      "title" : "Transport Protocol",
      "description" : "",
      "propertyOrder" : 2600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "host" : {
      "title" : "Server hostname",
      "description" : "Host name or IP address of receiving syslog server.",
      "propertyOrder" : 2400,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "connectTimeout" : {
      "title" : "Connection timeout",
      "description" : "Timeout for connecting to syslog server, in seconds.",
      "propertyOrder" : 2700,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "port" : {
      "title" : "Server port",
      "description" : "Port number of receiving syslog server.",
      "propertyOrder" : 2500,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory responsible for creating the Audit Event Handler. The class must implement <code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 3000,

```

```
    "required" : true,  
    "type" : "string",  
    "exampleValue" : ""  
  }  
}  
}  
}
```

1.195.2.2. delete

Usage:

```
am> delete Syslog --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.195.2.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action Syslog --global --actionName getAllTypes
```

1.195.2.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action Syslog --global --actionName getCreatableTypes
```

1.195.2.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action Syslog --global --actionName nextdescendents
```

1.195.2.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query Syslog --global --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.195.2.7. read

Usage:

```
am> read Syslog --global --id id
```

Parameters:

--id

The unique identifier for the resource.

1.195.2.8. update

Usage:

```
am> update Syslog --global --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "commonHandler" : {
      "type" : "object",
      "title" : "General Handler Configuration",
      "propertyOrder" : 0,
      "properties" : {
        "enabled" : {
          "title" : "Enabled",
          "description" : "Enables or disables an audit event handler.",
          "propertyOrder" : 2200,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "topics" : {
```

```
    "title" : "Topics",
    "description" : "List of topics handled by an audit event handler.",
    "propertyOrder" : 2300,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
},
"sysLogBuffering" : {
  "type" : "object",
  "title" : "Buffering",
  "propertyOrder" : 3,
  "properties" : {
    "bufferingEnabled" : {
      "title" : "Buffering Enabled",
      "description" : "Enables or disables audit event buffering.",
      "propertyOrder" : 2900,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "bufferingMaxSize" : {
      "title" : "Buffer Size",
      "description" : "Maximum number of events that can be buffered (default/minimum: 5000)",
      "propertyOrder" : 2950,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"sysLogConfig" : {
  "type" : "object",
  "title" : "Syslog Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "facility" : {
      "title" : "Facility",
      "description" : "Syslog facility value to apply to all events.",
      "propertyOrder" : 2800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "transportProtocol" : {
      "title" : "Transport Protocol",
      "description" : "",
      "propertyOrder" : 2600,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "host" : {
      "title" : "Server hostname",
      "description" : "Host name or IP address of receiving syslog server.",
```

```
    "propertyOrder" : 2400,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "connectTimeout" : {
    "title" : "Connection timeout",
    "description" : "Timeout for connecting to syslog server, in seconds.",
    "propertyOrder" : 2700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "port" : {
    "title" : "Server port",
    "description" : "Port number of receiving syslog server.",
    "propertyOrder" : 2500,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"commonHandlerPlugin" : {
  "type" : "object",
  "title" : "Audit Event Handler Factory",
  "propertyOrder" : 1,
  "properties" : {
    "handlerFactory" : {
      "title" : "Factory Class Name",
      "description" : "The fully qualified class name of the factory
responsible for creating the Audit Event Handler. The class must implement
<code>org.forgerock.openam.audit.AuditEventHandlerFactory</code>.",
      "propertyOrder" : 3000,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
}
}
```

1.196. TimerStart

1.196.1. Realm Operations

Resource path: </realm-config/authentication/authenticationtrees/nodes/TimerStartNode>

Resource version: 1.0

1.196.1.1. create

Usage:

```
am> create TimerStart --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "startTimeProperty" : {
      "title" : "Start Time Property",
      "description" : "Identifier of property into which start time should be stored by this node.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "startTimeProperty" ]
}
```

1.196.1.2. delete

Usage:

```
am> delete TimerStart --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.196.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action TimerStart --realm Realm --actionName getAllTypes
```

1.196.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action TimerStart --realm Realm --actionName getCreatableTypes
```

1.196.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action TimerStart --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.196.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action TimerStart --realm Realm --actionName nextdescendents
```

1.196.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query TimerStart --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.196.1.8. read

Usage:

```
am> read TimerStart --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.196.1.9. update

Usage:

```
am> update TimerStart --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "startTimeProperty" : {
      "title" : "Start Time Property",
      "description" : "Identifier of property into which start time should be stored by this node.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "startTimeProperty" ]
}
```

1.197. TimerStop

1.197.1. Realm Operations

Resource path: [/realm-config/authentication/authenticationtrees/nodes/TimerStopNode](#)

Resource version: 1.0

1.197.1.1. create

Usage:

```
am> create TimerStop --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "metricKey" : {
      "title" : "Metric Key",
      "description" : "Identifier of metric to update when this node is processed.",
      "propertyOrder" : 200,
      "type" : "string",
      "exampleValue" : ""
    },
    "startTimeProperty" : {
      "title" : "Start Time Property",
      "description" : "Identifier of property in which start time should have been stored by a \"Timer
Start\" node.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "metricKey", "startTimeProperty" ]
}
```

1.197.1.2. delete

Usage:

```
am> delete TimerStop --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.197.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action TimerStop --realm Realm --actionName getAllTypes
```

1.197.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action TimerStop --realm Realm --actionName getCreatableTypes
```

1.197.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action TimerStop --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
  configuration schema."
}
```

1.197.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action TimerStop --realm Realm --actionName nextdescendents
```

1.197.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query TimerStop --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.197.1.8. read

Usage:

```
am> read TimerStop --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.197.1.9. update

Usage:

```
am> update TimerStop --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "metricKey" : {
      "title" : "Metric Key",
      "description" : "Identifier of metric to update when this node is processed.",
      "propertyOrder" : 200,
      "type" : "string",
      "exampleValue" : ""
    },
    "startTimeProperty" : {
      "title" : "Start Time Property",
      "description" : "Identifier of property in which start time should have been stored by a \"Timer
Start\" node.",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "metricKey", "startTimeProperty" ]
}
```

1.198. TivoliDirectoryServer

1.198.1. Realm Operations

Resource path: `/realm-config/services/id-repositories/LDAPv3ForTivoli`

Resource version: `1.0`

1.198.1.1. create

Usage:

```
am> create TivoliDirectoryServer --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userconfig" : {
      "type" : "object",
      "title" : "User Configuration",
      "propertyOrder" : 3,
      "properties" : {
        "sun-idrepo-ldapv3-config-users-search-filter" : {
          "title" : "LDAP Users Search Filter",
          "description" : "",
          "propertyOrder" : 2200,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-auth-kba-attempts-attr" : {
          "title" : "Knowledge Based Authentication Attempts Attribute Name",
          "description" : "",
          "propertyOrder" : 5340,
          "required" : false,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-inactive" : {
          "title" : "User Status Inactive Value",
          "description" : "",
          "propertyOrder" : 2800,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-active" : {
```

```
"title" : "User Status Active Value",
"description" : "",
"propertyOrder" : 2700,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-people-container-name" : {
"title" : "LDAP People Container Naming Attribute",
"description" : "",
"propertyOrder" : 5000,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
},
"sun-idrepo-ldapv3-config-user-objectclass" : {
"title" : "LDAP User Object Class",
"description" : "",
"propertyOrder" : 2300,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
},
"sun-idrepo-ldapv3-config-people-container-value" : {
"title" : "LDAP People Container Value",
"description" : "",
"propertyOrder" : 5100,
"required" : false,
"type" : "string",
"exampleValue" : ""
},
},
"sun-idrepo-ldapv3-config-auth-kba-index-attr" : {
"title" : "Knowledge Based Authentication Active Index",
"description" : "",
"propertyOrder" : 5400,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
},
"sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
"title" : "Create User Attribute Mapping",
"description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
"propertyOrder" : 2500,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
},
"sun-idrepo-ldapv3-config-auth-kba-attr" : {
"title" : "Knowledge Based Authentication Attribute Name",
"description" : "",
```

```

    "propertyOrder" : 5300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-user-attributes" : {
    "title" : "LDAP User Attributes",
    "description" : "",
    "propertyOrder" : 2400,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-isactive" : {
    "title" : "Attribute Name of User Status",
    "description" : "",
    "propertyOrder" : 2600,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-users-search-attribute" : {
    "title" : "LDAP Users Search Attribute",
    "description" : "",
    "propertyOrder" : 2100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"pluginconfig" : {
  "type" : "object",
  "title" : "Plug-in Configuration",
  "propertyOrder" : 2,
  "properties" : {
    "sunIdRepoSupportedOperations" : {
      "title" : "LDAPv3 Plug-in Supported Types and Operations",
      "description" : "",
      "propertyOrder" : 1900,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sunIdRepoClass" : {
      "title" : "LDAPv3 Repository Plug-in Class Name",
      "description" : "",
      "propertyOrder" : 1700,
      "required" : true,
      "type" : "string",

```

```
    "exampleValue" : ""
  },
  "sunIdRepoAttributeMapping" : {
    "title" : "Attribute Name Mapping",
    "description" : "",
    "propertyOrder" : 1800,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
},
"groupconfig" : {
  "type" : "object",
  "title" : "Group Configuration",
  "propertyOrder" : 5,
  "properties" : {
    "sun-idrepo-ldapv3-config-group-container-value" : {
      "title" : "LDAP Groups Container Value",
      "description" : "",
      "propertyOrder" : 3200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-container-name" : {
      "title" : "LDAP Groups Container Naming Attribute",
      "description" : "",
      "propertyOrder" : 3100,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-unique-member" : {
      "title" : "Attribute Name of Unique Member",
      "description" : "",
      "propertyOrder" : 3600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-groups-search-attribute" : {
      "title" : "LDAP Groups Search Attribute",
      "description" : "",
      "propertyOrder" : 2900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-memberof" : {
      "title" : "Attribute Name for Group Membership",
      "description" : "",
      "propertyOrder" : 3500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```



```

    },
    "sun-idrepo-ldapv3-config-dftgroupmember" : {
      "title" : "Default Group Member's User DN",
      "description" : "User automatically added when group is created.",
      "propertyOrder" : 3800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
  },
  "sun-idrepo-ldapv3-config-group-attributes" : {
    "title" : "LDAP Groups Attributes",
    "description" : "",
    "propertyOrder" : 3400,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-group-objectclass" : {
    "title" : "LDAP Groups Object Class",
    "description" : "",
    "propertyOrder" : 3300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-groups-search-filter" : {
    "title" : "LDAP Groups Search Filter",
    "description" : "",
    "propertyOrder" : 3000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"ldapsettings" : {
  "type" : "object",
  "title" : "Server Settings",
  "propertyOrder" : 0,
  "properties" : {
    "sun-idrepo-ldapv3-config-organization_name" : {
      "title" : "LDAP Organization DN",
      "description" : "",
      "propertyOrder" : 900,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
  },
  "sun-idrepo-ldapv3-config-authpw" : {
    "title" : "LDAP Bind Password",
    "description" : "",
    "propertyOrder" : 800,
    "required" : false,
  }
}

```

```

    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-ldap-server" : {
    "title" : "LDAP Server",
    "description" : "Format: LDAP server host name:port | server_ID | site_ID",
    "propertyOrder" : 600,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-search-scope" : {
    "title" : "LDAPv3 Plug-in Search Scope",
    "description" : "",
    "propertyOrder" : 2000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-behera-support-enabled" : {
    "title" : "Behera Support Enabled",
    "description" : "When enabled, Behera draft control will be used in the outgoing requests
for operations that may modify password value. This will allow OpenAM to display password policy
related error messages when password policies are not met.",
    "propertyOrder" : 6100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-time-limit" : {
    "title" : "Search Timeout",
    "description" : "In seconds.",
    "propertyOrder" : 1600,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-max-result" : {
    "title" : "Maximum Results Returned from Search",
    "description" : "",
    "propertyOrder" : 1500,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
    "title" : "LDAP Connection Pool Maximum Size",
    "description" : "",
    "propertyOrder" : 1200,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "openam-idrepo-ldapv3-heartbeat-timeunit" : {
    "title" : "LDAP Connection Heartbeat Time Unit",

```

```

      "description" : "Defines the time unit corresponding to the Heartbeat Interval
      setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
      to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
      it may take up to the interval period before the problem is detected. Use along with the Heartbeat
      Interval parameter to define the exact interval.",
      "propertyOrder" : 1400,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-authid" : {
      "title" : "LDAP Bind DN",
      "description" : "A user or admin with sufficient access rights to perform the supported
      operations.",
      "propertyOrder" : 700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-connection-mode" : {
      "title" : "LDAP Connection Mode",
      "description" : "Defines which protocol/operation is used to establish the connection to
      the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b> and
      passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
      connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
      using StartTLS extended operation.",
      "propertyOrder" : 1000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-interval" : {
      "title" : "LDAP Connection Heartbeat Interval",
      "description" : "Specifies how often should OpenAM send a heartbeat request to the
      directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
      request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
      error) then it may take up to the interval period before the problem is detected. Use along with the
      Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
      disabling heartbeat requests.",
      "propertyOrder" : 1300,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
},
"persistentsearch" : {
  "type" : "object",
  "title" : "Persistent Search Controls",
  "propertyOrder" : 7,
  "properties" : {
    "sun-idrepo-ldapv3-config-psearchbase" : {
      "title" : "Persistent Search Base DN",
      "description" : "",
      "propertyOrder" : 5500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},

```

```

"sun-idrepo-ldapv3-config-psearch-scope" : {
  "title" : "Persistent Search Scope",
  "description" : "",
  "propertyOrder" : 5700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-psearch-filter" : {
  "title" : "Persistent Search Filter",
  "description" : "",
  "propertyOrder" : 5600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
}
},
"authentication" : {
  "type" : "object",
  "title" : "Authentication Configuration",
  "propertyOrder" : 4,
  "properties" : {
    "sun-idrepo-ldapv3-config-auth-naming-attr" : {
      "title" : "Authentication Naming Attribute",
      "description" : "",
      "propertyOrder" : 5200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
},
"errorhandling" : {
  "type" : "object",
  "title" : "Error Handling Configuration",
  "propertyOrder" : 8,
  "properties" : {
    "com.iplanet.am.ldap.connection.delay.between.retries" : {
      "title" : "The Delay Time Between Retries",
      "description" : "In milliseconds.",
      "propertyOrder" : 5800,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
},
"cachecontrol" : {
  "type" : "object",
  "title" : "Cache Control",
  "propertyOrder" : 9,
  "properties" : {
    "sun-idrepo-ldapv3-dncache-size" : {
      "title" : "DN Cache Size",
      "description" : "In DN items, only used when DN Cache is enabled.",
      "propertyOrder" : 6000,
      "required" : false,
      "type" : "integer",

```

```
        "exampleValue" : ""
      },
      "sun-idrepo-ldapv3-dncache-enabled" : {
        "title" : "DN Cache",
        "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
        "propertyOrder" : 5900,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
      }
    }
  }
}
```

1.198.1.2. delete

Usage:

```
am> delete TivoliDirectoryServer --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.198.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action TivoliDirectoryServer --realm Realm --actionName getAllTypes
```

1.198.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action TivoliDirectoryServer --realm Realm --actionName getCreatableTypes
```

1.198.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action TivoliDirectoryServer --realm Realm --actionName nextdescendents
```

1.198.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query TivoliDirectoryServer --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.198.1.7. read

Usage:

```
am> read TivoliDirectoryServer --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.198.1.8. update

Usage:

```
am> update TivoliDirectoryServer --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "userconfig" : {
      "type" : "object",
      "title" : "User Configuration",
      "propertyOrder" : 3,
      "properties" : {
```

```
"sun-idrepo-ldapv3-config-users-search-filter" : {
  "title" : "LDAP Users Search Filter",
  "description" : "",
  "propertyOrder" : 2200,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-attempts-attr" : {
  "title" : "Knowledge Based Authentication Attempts Attribute Name",
  "description" : "",
  "propertyOrder" : 5340,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-inactive" : {
  "title" : "User Status Inactive Value",
  "description" : "",
  "propertyOrder" : 2800,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-active" : {
  "title" : "User Status Active Value",
  "description" : "",
  "propertyOrder" : 2700,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-people-container-name" : {
  "title" : "LDAP People Container Naming Attribute",
  "description" : "",
  "propertyOrder" : 5000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-user-objectclass" : {
  "title" : "LDAP User Object Class",
  "description" : "",
  "propertyOrder" : 2300,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-people-container-value" : {
  "title" : "LDAP People Container Value",
  "description" : "",
  "propertyOrder" : 5100,
  "required" : false,
```

```
"type" : "string",
"exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-index-attr" : {
  "title" : "Knowledge Based Authentication Active Index",
  "description" : "",
  "propertyOrder" : 5400,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-createuser-attr-mapping" : {
  "title" : "Create User Attribute Mapping",
  "description" : "Format: attribute name or TargetAttributeName=SourceAttributeName",
  "propertyOrder" : 2500,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-auth-kba-attr" : {
  "title" : "Knowledge Based Authentication Attribute Name",
  "description" : "",
  "propertyOrder" : 5300,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-user-attributes" : {
  "title" : "LDAP User Attributes",
  "description" : "",
  "propertyOrder" : 2400,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-isactive" : {
  "title" : "Attribute Name of User Status",
  "description" : "",
  "propertyOrder" : 2600,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"sun-idrepo-ldapv3-config-users-search-attribute" : {
  "title" : "LDAP Users Search Attribute",
  "description" : "",
  "propertyOrder" : 2100,
```



```

        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"pluginconfig" : {
    "type" : "object",
    "title" : "Plug-in Configuration",
    "propertyOrder" : 2,
    "properties" : {
        "sunIdRepoSupportedOperations" : {
            "title" : "LDAPv3 Plug-in Supported Types and Operations",
            "description" : "",
            "propertyOrder" : 1900,
            "required" : false,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
    },
    "sunIdRepoClass" : {
        "title" : "LDAPv3 Repository Plug-in Class Name",
        "description" : "",
        "propertyOrder" : 1700,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "sunIdRepoAttributeMapping" : {
        "title" : "Attribute Name Mapping",
        "description" : "",
        "propertyOrder" : 1800,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"groupconfig" : {
    "type" : "object",
    "title" : "Group Configuration",
    "propertyOrder" : 5,
    "properties" : {
        "sun-idrepo-ldapv3-config-group-container-value" : {
            "title" : "LDAP Groups Container Value",
            "description" : "",
            "propertyOrder" : 3200,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "sun-idrepo-ldapv3-config-group-container-name" : {
            "title" : "LDAP Groups Container Naming Attribute",
            "description" : "",

```

```

        "propertyOrder" : 3100,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-uniquemember" : {
        "title" : "Attribute Name of Unique Member",
        "description" : "",
        "propertyOrder" : 3600,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-groups-search-attribute" : {
        "title" : "LDAP Groups Search Attribute",
        "description" : "",
        "propertyOrder" : 2900,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-memberof" : {
        "title" : "Attribute Name for Group Membership",
        "description" : "",
        "propertyOrder" : 3500,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-dftgroupmember" : {
        "title" : "Default Group Member's User DN",
        "description" : "User automatically added when group is created.",
        "propertyOrder" : 3800,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-attributes" : {
        "title" : "LDAP Groups Attributes",
        "description" : "",
        "propertyOrder" : 3400,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-group-objectclass" : {
        "title" : "LDAP Groups Object Class",
        "description" : "",
        "propertyOrder" : 3300,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
}

```

```

"sun-idrepo-ldapv3-config-groups-search-filter" : {
  "title" : "LDAP Groups Search Filter",
  "description" : "",
  "propertyOrder" : 3000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
}
},
"ldapsettings" : {
  "type" : "object",
  "title" : "Server Settings",
  "propertyOrder" : 0,
  "properties" : {
    "sun-idrepo-ldapv3-config-organization_name" : {
      "title" : "LDAP Organization DN",
      "description" : "",
      "propertyOrder" : 900,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-authpw" : {
      "title" : "LDAP Bind Password",
      "description" : "",
      "propertyOrder" : 800,
      "required" : false,
      "type" : "string",
      "format" : "password",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-ldap-server" : {
      "title" : "LDAP Server",
      "description" : "Format: LDAP server host name:port | server_ID | site_ID",
      "propertyOrder" : 600,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-search-scope" : {
      "title" : "LDAPv3 Plug-in Search Scope",
      "description" : "",
      "propertyOrder" : 2000,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-behera-support-enabled" : {
      "title" : "Behera Support Enabled",
      "description" : "When enabled, Behera draft control will be used in the outgoing requests for operations that may modify password value. This will allow OpenAM to display password policy related error messages when password policies are not met.",
      "propertyOrder" : 6100,
      "required" : false,
      "type" : "boolean",

```

```

        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-time-limit" : {
        "title" : "Search Timeout",
        "description" : "In seconds.",
        "propertyOrder" : 1600,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-max-result" : {
        "title" : "Maximum Results Returned from Search",
        "description" : "",
        "propertyOrder" : 1500,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-connection_pool_max_size" : {
        "title" : "LDAP Connection Pool Maximum Size",
        "description" : "",
        "propertyOrder" : 1200,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "openam-idrepo-ldapv3-heartbeat-timeunit" : {
        "title" : "LDAP Connection Heartbeat Time Unit",
        "description" : "Defines the time unit corresponding to the Heartbeat Interval
setting.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search request
to the configured directory. If a connection becomes unresponsive (e.g. due to a network error) then
it may take up to the interval period before the problem is detected. Use along with the Heartbeat
Interval parameter to define the exact interval.",
        "propertyOrder" : 1400,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-authid" : {
        "title" : "LDAP Bind DN",
        "description" : "A user or admin with sufficient access rights to perform the supported
operations.",
        "propertyOrder" : 700,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "sun-idrepo-ldapv3-config-connection-mode" : {
        "title" : "LDAP Connection Mode",
        "description" : "Defines which protocol/operation is used to establish the connection to
the LDAP Directory Server.<br><br>If 'LDAP' is selected, the connection <b>won't be secured</b>
and passwords are transferred in <b>cleartext</b> over the network.<br> If 'LDAPS' is selected, the
connection is secured via SSL or TLS. <br> If 'StartTLS' is selected, the connection is secured by
using StartTLS extended operation.",
        "propertyOrder" : 1000,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    },

```

```

    "openam-idrepo-ldapv3-heartbeat-interval" : {
      "title" : "LDAP Connection Heartbeat Interval",
      "description" : "Specifies how often should OpenAM send a heartbeat request to the
directory.<br><br>This setting controls how often OpenAM <b>should</b> send a heartbeat search
request to the configured directory. If a connection becomes unresponsive (e.g. due to a network
error) then it may take up to the interval period before the problem is detected. Use along with the
Heartbeat Time Unit parameter to define the exact interval. Zero or negative value will result in
disabling heartbeat requests.",
      "propertyOrder" : 1300,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    }
  },
  "persistentsearch" : {
    "type" : "object",
    "title" : "Persistent Search Controls",
    "propertyOrder" : 7,
    "properties" : {
      "sun-idrepo-ldapv3-config-psearchbase" : {
        "title" : "Persistent Search Base DN",
        "description" : "",
        "propertyOrder" : 5500,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
      },
      "sun-idrepo-ldapv3-config-psearch-scope" : {
        "title" : "Persistent Search Scope",
        "description" : "",
        "propertyOrder" : 5700,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
      },
      "sun-idrepo-ldapv3-config-psearch-filter" : {
        "title" : "Persistent Search Filter",
        "description" : "",
        "propertyOrder" : 5600,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
      }
    }
  },
  "authentication" : {
    "type" : "object",
    "title" : "Authentication Configuration",
    "propertyOrder" : 4,
    "properties" : {
      "sun-idrepo-ldapv3-config-auth-naming-attr" : {
        "title" : "Authentication Naming Attribute",
        "description" : "",
        "propertyOrder" : 5200,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
      }
    }
  }
}

```

```
    }
  },
  "errorhandling" : {
    "type" : "object",
    "title" : "Error Handling Configuration",
    "propertyOrder" : 8,
    "properties" : {
      "com.iplanet.am.ldap.connection.delay.between.retries" : {
        "title" : "The Delay Time Between Retries",
        "description" : "In milliseconds.",
        "propertyOrder" : 5800,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
      }
    }
  },
  "cachecontrol" : {
    "type" : "object",
    "title" : "Cache Control",
    "propertyOrder" : 9,
    "properties" : {
      "sun-idrepo-ldapv3-dncache-size" : {
        "title" : "DN Cache Size",
        "description" : "In DN items, only used when DN Cache is enabled.",
        "propertyOrder" : 6000,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
      },
      "sun-idrepo-ldapv3-dncache-enabled" : {
        "title" : "DN Cache",
        "description" : "Used to enable/disable the DN Cache within the OpenAM repository
implementation.<br><br>The DN Cache is used to cache DN lookups which tend to happen in bursts during
authentication. The DN Cache can become out of date when a user is moved or renamed in the underlying
LDAP store and this is not reflected in a persistent search result. Enable when the underlying LDAP
store supports persistent search and move/rename (mod_dn) results are available.",
        "propertyOrder" : 5900,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
      }
    }
  }
}
```

1.199. TransactionAuthentication

1.199.1. Realm Operations

Resource path: </realm-config/services/transaction>

Resource version: 1.0

1.199.1.1. create

Usage:

```
am> create TransactionAuthentication --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "timeToLive" : {
      "title" : "Time to Live",
      "description" : "The number of seconds within which the transaction must be completed.",
      "propertyOrder" : 0,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.199.1.2. delete

Usage:

```
am> delete TransactionAuthentication --realm Realm
```

1.199.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action TransactionAuthentication --realm Realm --actionName getAllTypes
```

1.199.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action TransactionAuthentication --realm Realm --actionName getCreatableTypes
```

1.199.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action TransactionAuthentication --realm Realm --actionName nextdescendents
```

1.199.1.6. read

Usage:

```
am> read TransactionAuthentication --realm Realm
```

1.199.1.7. update

Usage:

```
am> update TransactionAuthentication --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "timeToLive" : {
      "title" : "Time to Live",
      "description" : "The number of seconds within which the transaction must be completed.",
      "propertyOrder" : 0,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.199.2. Global Operations

Resource path: </global-config/services/transaction>

Resource version: 1.0

1.199.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action TransactionAuthentication --global --actionName getAllTypes
```

1.199.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action TransactionAuthentication --global --actionName getCreatableTypes
```

1.199.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action TransactionAuthentication --global --actionName nextdescendents
```

1.199.2.4. read

Usage:

```
am> read TransactionAuthentication --global
```

1.199.2.5. update

Usage:

```
am> update TransactionAuthentication --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "timeToLive" : {
          "title" : "Time to Live",
          "description" : "The number of seconds within which the transaction must be completed.",
          "propertyOrder" : 0,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      },
      "type" : "object",
      "title" : "Realm Defaults"
    }
  }
}
```

1.200. TrustedUserDevices

1.200.1. Realm Operations

Trusted devices service is responsible for querying and deleting trusted devices.

Resource path: `/users/{user}/devices/trusted`

Resource version: `1.0`

1.200.1.1. delete

Delete trusted user device

Usage:

```
am> delete TrustedUserDevices --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

Trusted devices service is responsible for querying and deleting trusted devices.

1.200.1.2. query

Query trusted user devices

Usage:

```
am> query TrustedUserDevices --realm Realm --filter filter --user user
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

--user

Trusted devices service is responsible for querying and deleting trusted devices.

1.201. UmaDataStoreProperties

1.201.1. Global Operations

An object of property key-value pairs

Resource path: `/global-config/servers/{serverName}/properties/uma`

Resource version: `1.0`

1.201.1.1. read

Usage:

```
am> read UmaDataStoreProperties --global --serverName serverName
```

Parameters:

--serverName

An object of property key-value pairs

1.201.1.2. update

Usage:

```
am> update UmaDataStoreProperties --global --serverName serverName --body body
```

Parameters:

--serverName

An object of property key-value pairs

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amconfig.org.forgerock.services.resourcesets.store.common.section" : {
      "title" : "Resource Sets Store",
      "type" : "object",
      "propertyOrder" : 0,
      "properties" : {
        "org.forgerock.services.resourcesets.store.location" : {
          "title" : "Store Mode",
          "type" : "object",
          "propertyOrder" : 0,
          "description" : "",
          "properties" : {
            "value" : {
              "enum" : [ "default", "external" ],
              "options" : {
                "enum_titles" : [ "Default Token Store", "External Token Store" ]
              },
              "type" : "string",
              "required" : false
            },
            "inherited" : {
              "type" : "boolean",
              "required" : true
            }
          }
        },
        "org.forgerock.services.resourcesets.store.root.suffix" : {
          "title" : "Root Suffix",
          "type" : "object",
          "propertyOrder" : 1,
          "description" : "",
          "properties" : {
            "value" : {
              "type" : "string",
              "required" : false
            },
            "inherited" : {
              "type" : "boolean",
              "required" : true
            }
          }
        },
        "org.forgerock.services.resourcesets.store.max.connections" : {
          "title" : "Max Connections",
          "type" : "object",
          "propertyOrder" : 2,
          "description" : "",
          "properties" : {
            "value" : {
```

```

        "type" : "string",
        "required" : false
    },
    "inherited" : {
        "type" : "boolean",
        "required" : true
    }
}
}
},
"amconfig.org.forgerock.services.resourcesets.store.external.section" : {
    "title" : "External Resource Sets Store Configuration",
    "type" : "object",
    "propertyOrder" : 1,
    "properties" : {
        "org.forgerock.services.resourcesets.store.ssl.enabled" : {
            "title" : "SSL/TLS Enabled",
            "type" : "object",
            "propertyOrder" : 0,
            "description" : "",
            "properties" : {
                "value" : {
                    "type" : "boolean",
                    "required" : false
                },
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                }
            }
        },
        "org.forgerock.services.resourcesets.store.directory.name" : {
            "title" : "Connection String(s)",
            "type" : "object",
            "propertyOrder" : 1,
            "description" : "An ordered list of connection strings for LDAP directories. Each connection
string is composed as follows: <code>HOST:PORT[|SERVERID[|SITEID]]</code>, where server and site
IDs are optional parameters that will prioritize that connection to use from the specified nodes.
Multiple connection strings should be comma-separated, e.g. <code>host1:389,host2:50389|server1|
site1,host3:50389</code>.",
            "properties" : {
                "value" : {
                    "type" : "string",
                    "required" : false
                },
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                }
            }
        },
        "org.forgerock.services.resourcesets.store.loginid" : {
            "title" : "Login Id",
            "type" : "object",
            "propertyOrder" : 2,
            "description" : "",
            "properties" : {
                "value" : {

```

```

    "type" : "string",
    "required" : false
  },
  "inherited" : {
    "type" : "boolean",
    "required" : true
  }
},
"org.forgerock.services.resourcesets.store.password" : {
  "title" : "Password",
  "type" : "object",
  "propertyOrder" : 3,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false,
      "format" : "password"
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"org.forgerock.services.resourcesets.store.heartbeat" : {
  "title" : "Heartbeat",
  "type" : "object",
  "propertyOrder" : 4,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "integer",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"amconfig.org.forgerock.services.umaaudit.store.common.section" : {
  "title" : "UMA Audit Store",
  "type" : "object",
  "propertyOrder" : 2,
  "properties" : {
    "org.forgerock.services.umaaudit.store.location" : {
      "title" : "Store Mode",
      "type" : "object",
      "propertyOrder" : 0,
      "description" : "",
      "properties" : {
        "value" : {
          "enum" : [ "default", "external" ],
          "options" : {
            "enum_titles" : [ "Default Token Store", "External Token Store" ]
          }
        }
      }
    }
  }
}

```

```
    },
    "type" : "string",
    "required" : false
  },
  "inherited" : {
    "type" : "boolean",
    "required" : true
  }
}
},
"org.forgerock.services.umaudit.store.root.suffix" : {
  "title" : "Root Suffix",
  "type" : "object",
  "propertyOrder" : 1,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
},
"org.forgerock.services.umaudit.store.max.connections" : {
  "title" : "Max Connections",
  "type" : "object",
  "propertyOrder" : 2,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
}
},
"amconfig.org.forgerock.services.umaudit.store.external.section" : {
  "title" : "External UMA Audit Store Configuration",
  "type" : "object",
  "propertyOrder" : 3,
  "properties" : {
    "org.forgerock.services.umaudit.store.ssl.enabled" : {
      "title" : "SSL/TLS Enabled",
      "type" : "object",
      "propertyOrder" : 0,
      "description" : "",
      "properties" : {
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    }
  }
},
```

```

    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  },
  "org.forgerock.services.umaaudit.store.directory.name" : {
    "title" : "Connection String(s)",
    "type" : "object",
    "propertyOrder" : 1,
    "description" : "An ordered list of connection strings for LDAP directories. Each connection string is composed as follows: <code>HOST:PORT[|SERVERID[|SITEID]]</code>, where server and site IDs are optional parameters that will prioritize that connection to use from the specified nodes. Multiple connection strings should be comma-separated, e.g. <code>host1:389,host2:50389|server1|site1,host3:50389</code>.",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "org.forgerock.services.umaaudit.store.loginid" : {
    "title" : "Login Id",
    "type" : "object",
    "propertyOrder" : 2,
    "description" : "",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },
  "org.forgerock.services.umaaudit.store.password" : {
    "title" : "Password",
    "type" : "object",
    "propertyOrder" : 3,
    "description" : "",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false,
        "format" : "password"
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
},

```



```
"org.forgerock.services.umaudit.store.heartbeat" : {
  "title" : "Heartbeat",
  "type" : "object",
  "propertyOrder" : 4,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "integer",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
},
"amconfig.org.forgerock.services.uma.pendingrequests.store.common.section" : {
  "title" : "Pending Requests Store",
  "type" : "object",
  "propertyOrder" : 4,
  "properties" : {
    "org.forgerock.services.uma.pendingrequests.store.location" : {
      "title" : "Store Mode",
      "type" : "object",
      "propertyOrder" : 0,
      "description" : "",
      "properties" : {
        "value" : {
          "enum" : [ "default", "external" ],
          "options" : {
            "enum_titles" : [ "Default Token Store", "External Token Store" ]
          },
          "type" : "string",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  },
  "org.forgerock.services.uma.pendingrequests.store.root.suffix" : {
    "title" : "Root Suffix",
    "type" : "object",
    "propertyOrder" : 1,
    "description" : "",
    "properties" : {
      "value" : {
        "type" : "string",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
},
},
```

```

"org.forgerock.services.uma.pendingrequests.store.max.connections" : {
  "title" : "Max Connections",
  "type" : "object",
  "propertyOrder" : 2,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
},
"amconfig.org.forgerock.services.uma.pendingrequests.store.external.section" : {
  "title" : "External Pending Requests Store Configuration",
  "type" : "object",
  "propertyOrder" : 5,
  "properties" : {
    "org.forgerock.services.uma.pendingrequests.store.ssl.enabled" : {
      "title" : "SSL/TLS Enabled",
      "type" : "object",
      "propertyOrder" : 0,
      "description" : "",
      "properties" : {
        "value" : {
          "type" : "boolean",
          "required" : false
        },
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
},
"org.forgerock.services.uma.pendingrequests.store.directory.name" : {
  "title" : "Connection String(s)",
  "type" : "object",
  "propertyOrder" : 1,
  "description" : "An ordered list of connection strings for LDAP directories. Each connection
string is composed as follows: <code>HOST:PORT[|SERVERID[|SITEID]]</code>, where server and site
IDs are optional parameters that will prioritize that connection to use from the specified nodes.
Multiple connection strings should be comma-separated, e.g. <code>host1:389,host2:50389|server1|
sitel,host3:50389</code>.",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
},

```

```

"org.forgerock.services.uma.pendingrequests.store.loginid" : {
  "title" : "Login Id",
  "type" : "object",
  "propertyOrder" : 2,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"org.forgerock.services.uma.pendingrequests.store.password" : {
  "title" : "Password",
  "type" : "object",
  "propertyOrder" : 3,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "string",
      "required" : false,
      "format" : "password"
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"org.forgerock.services.uma.pendingrequests.store.heartbeat" : {
  "title" : "Heartbeat",
  "type" : "object",
  "propertyOrder" : 4,
  "description" : "",
  "properties" : {
    "value" : {
      "type" : "integer",
      "required" : false
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
"amconfig.org.forgerock.services.uma.labels.store.common.section" : {
  "title" : "UMA Resource Set Labels Store",
  "type" : "object",
  "propertyOrder" : 6,
  "properties" : {
    "org.forgerock.services.uma.labels.store.location" : {
      "title" : "Store Mode",
      "type" : "object",

```

```

        "propertyOrder" : 0,
        "description" : "",
        "properties" : {
            "value" : {
                "enum" : [ "default", "external" ],
                "options" : {
                    "enum_titles" : [ "Default Token Store", "External Token Store" ]
                },
                "type" : "string",
                "required" : false
            },
            "inherited" : {
                "type" : "boolean",
                "required" : true
            }
        }
    },
    "org.forgerock.services.uma.labels.store.root.suffix" : {
        "title" : "Root Suffix",
        "type" : "object",
        "propertyOrder" : 1,
        "description" : "",
        "properties" : {
            "value" : {
                "type" : "string",
                "required" : false
            },
            "inherited" : {
                "type" : "boolean",
                "required" : true
            }
        }
    },
    "org.forgerock.services.uma.labels.store.max.connections" : {
        "title" : "Max Connections",
        "type" : "object",
        "propertyOrder" : 2,
        "description" : "",
        "properties" : {
            "value" : {
                "type" : "string",
                "required" : false
            },
            "inherited" : {
                "type" : "boolean",
                "required" : true
            }
        }
    }
}
},
"amconfig.org.forgerock.services.uma.labels.store.external.section" : {
    "title" : "External Resource Set Labels Store Configuration",
    "type" : "object",
    "propertyOrder" : 7,
    "properties" : {
        "org.forgerock.services.uma.labels.store.ssl.enabled" : {
            "title" : "SSL/TLS Enabled",
            "type" : "object",

```

```

        "propertyOrder" : 0,
        "description" : "",
        "properties" : {
            "value" : {
                "type" : "boolean",
                "required" : false
            },
            "inherited" : {
                "type" : "boolean",
                "required" : true
            }
        }
    },
    "org.forgerock.services.uma.labels.store.directory.name" : {
        "title" : "Connection String(s)",
        "type" : "object",
        "propertyOrder" : 1,
        "description" : "An ordered list of connection strings for LDAP directories. Each connection string is composed as follows: <code>HOST:PORT[|SERVERID[|SITEID]]</code>, where server and site IDs are optional parameters that will prioritize that connection to use from the specified nodes. Multiple connection strings should be comma-separated, e.g. <code>host1:389,host2:50389|server1|site1,host3:50389</code>.",
        "properties" : {
            "value" : {
                "type" : "string",
                "required" : false
            },
            "inherited" : {
                "type" : "boolean",
                "required" : true
            }
        }
    },
    "org.forgerock.services.uma.labels.store.loginid" : {
        "title" : "Login Id",
        "type" : "object",
        "propertyOrder" : 2,
        "description" : "",
        "properties" : {
            "value" : {
                "type" : "string",
                "required" : false
            },
            "inherited" : {
                "type" : "boolean",
                "required" : true
            }
        }
    },
    "org.forgerock.services.uma.labels.store.password" : {
        "title" : "Password",
        "type" : "object",
        "propertyOrder" : 3,
        "description" : "",
        "properties" : {
            "value" : {
                "type" : "string",
                "required" : false,
                "format" : "password"
            }
        }
    }
}

```

```
    },
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  },
  "org.forgerock.services.uma.labels.store.heartbeat" : {
    "title" : "Heartbeat",
    "type" : "object",
    "propertyOrder" : 4,
    "description" : "",
    "properties" : {
      "value" : {
        "type" : "integer",
        "required" : false
      },
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
}
}
```

1.202. UmaPolicies

1.202.1. Realm Operations

Provides create, delete and query operations for UMA Policies

Resource path: `/users/{user}/uma/policies`

Resource version: `1.0`

1.202.1.1. create

Creates an UMA Policy

Usage:

```
am> create UmaPolicies --realm Realm --id id --body body --user user
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "A policy defining who can access a particular resource set",
  "type" : "object",
  "title" : "UMA Policy",
  "properties" : {
    "policyId" : {
      "type" : "string",
      "title" : "Policy ID",
      "description" : "The ID must correspond with an existing resource set ID"
    },
    "permissions" : {
      "type" : "array",
      "title" : "Permissions",
      "description" : "A list of subjects and the scopes they are allowed access to",
      "items" : {
        "type" : "object",
        "properties" : {
          "subject" : {
            "type" : "string",
            "title" : "Subject",
            "description" : "The username of the subject"
          },
          "scopes" : {
            "type" : "array",
            "title" : "Scopes",
            "description" : "The scopes that the user is allowed access to",
            "items" : {
              "type" : "string"
            }
          }
        }
      }
    }
  }
}
```

--user

Provides create, delete and query operations for UMA Policies

1.202.1.2. delete

Deletes an UMA Policy

Usage:

```
am> delete UmaPolicies --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

Provides create, delete and query operations for UMA Policies

1.202.1.3. query

Queries an UMA Policy

Usage:

```
am> query UmaPolicies --realm Realm --filter filter --user user
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

--user

Provides create, delete and query operations for UMA Policies

1.202.1.4. read

Reads an UMA Policy

Usage:

```
am> read UmaPolicies --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

Provides create, delete and query operations for UMA Policies

1.202.1.5. update

Updates an UMA Policy

Usage:

```
am> update UmaPolicies --realm Realm --id id --body body --user user
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "A policy defining who can access a particular resource set",
  "type" : "object",
  "title" : "UMA Policy",
  "properties" : {
    "policyId" : {
      "type" : "string",
      "title" : "Policy ID",
      "description" : "The ID must correspond with an existing resource set ID"
    },
    "permissions" : {
      "type" : "array",
      "title" : "Permissions",
      "description" : "A list of subjects and the scopes they are allowed access to",
      "items" : {
        "type" : "object",
        "properties" : {
          "subject" : {
            "type" : "string",
            "title" : "Subject",
            "description" : "The username of the subject"
          },
          "scopes" : {
            "type" : "array",
            "title" : "Scopes",
            "description" : "The scopes that the user is allowed access to",
            "items" : {
              "type" : "string"
            }
          }
        }
      }
    }
  }
}
```

--user

Provides create, delete and query operations for UMA Policies

1.203. UmaProvider

1.203.1. Realm Operations

Resource path: `/realm-config/services/uma`

Resource version: `1.0`

1.203.1.1. create

Usage:

```
am> create UmaProvider --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "emailRequestingPartyOnPendingRequestApproval" : {
      "title" : "Email Requesting Party on Pending Request approval",
      "description" : "Specifies whether to send an email to the Requesting Party when a Pending Request is approved by the Resource Owner.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "deletePoliciesOnDeleteRS" : {
      "title" : "Delete user policies when Resource Server is removed",
      "description" : "Delete all user policies that relate to a Resource Server when removing the OAuth2 agent entry or removing the <code>uma_protection</code> scope from the OAuth2 agent.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "resharingMode" : {
      "title" : "Re-Sharing Mode",
      "description" : "Specifies whether re-sharing is off or on implicitly for all users, allowing all users to re-share resource sets that have been shared with them.",
      "propertyOrder" : 800,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "grantRptConditions" : {
      "title" : "Grant RPTs...",
      "description" : "In UMA, scope comes from both the permission ticket and from the token request. An RPT is always granted when all scope matches, and is never granted when no scope matches. You can configure when RPTs are granted for partial match conditions here. For more information, see the UMA Grant Type specification section on Authorization Assessment and Results Determination.",
      "propertyOrder" : 900,
      "required" : true,
      "items" : {
```

```

    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"userProfileLocaleAttribute" : {
  "title" : "User profile preferred Locale attribute",
  "description" : "User profile attribute storing the user's preferred locale.",
  "propertyOrder" : 700,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
},
"deleteResourceSetsOnDeleteRS" : {
  "title" : "Delete resource sets when Resource Server is removed",
  "description" : "Delete all resource sets that relate to a Resource Server when removing the
OAuth2 agent entry or removing the <code>uma_protection</code> scope from the OAuth2 agent.",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
},
"pendingRequestsEnabled" : {
  "title" : "Pending Requests Enabled",
  "description" : "Specifies whether to use the Pending Requests subsystem that notifies the
resource owner that an attempt to access a resource was made.",
  "propertyOrder" : 450,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
},
"emailResourceOwnerOnPendingRequestCreation" : {
  "title" : "Email Resource Owner on Pending Request creation",
  "description" : "Specifies whether to send an email to the Resource Owner when a Pending Request
is created when a Requesting Party requests authorization to a resource.",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
},
"permissionTicketLifetime" : {
  "title" : "Permission Ticket Lifetime (seconds)",
  "description" : "The maximum life of a permission ticket before it expires, in seconds.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
}
}
}
}

```

1.203.1.2. delete

Usage:

```
am> delete UmaProvider --realm Realm
```

1.203.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action UmaProvider --realm Realm --actionName getAllTypes
```

1.203.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action UmaProvider --realm Realm --actionName getCreatableTypes
```

1.203.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action UmaProvider --realm Realm --actionName nextdescendents
```

1.203.1.6. read

Usage:

```
am> read UmaProvider --realm Realm
```

1.203.1.7. update

Usage:

```
am> update UmaProvider --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "emailRequestingPartyOnPendingRequestApproval" : {
      "title" : "Email Requesting Party on Pending Request approval",
      "description" : "Specifies whether to send an email to the Requesting Party when a Pending Request is approved by the Resource Owner.",
      "propertyOrder" : 600,
      "required" : true,
      "type" : "boolean",
```

```
    "exampleValue" : ""
  },
  "deletePoliciesOnDeleteRS" : {
    "title" : "Delete user policies when Resource Server is removed",
    "description" : "Delete all user policies that relate to a Resource Server when removing the
OAuth2 agent entry or removing the <code>uma_protection</code> scope from the OAuth2 agent.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "resharingMode" : {
    "title" : "Re-Sharing Mode",
    "description" : "Specifies whether re-sharing is off or on implicitly for all users, allowing
all users to re-share resource sets that have been shared with them.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "grantRptConditions" : {
    "title" : "Grant RPTs...",
    "description" : "In UMA, scope comes from both the permission ticket and from the token request.
An RPT is always granted when all scope matches, and is never granted when no scope matches. You can
configure when RPTs are granted for partial match conditions here. For more information, see the UMA
Grant Type specification section on Authorization Assessment and Results Determination.",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "userProfileLocaleAttribute" : {
    "title" : "User profile preferred Locale attribute",
    "description" : "User profile attribute storing the user's preferred locale.",
    "propertyOrder" : 700,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "deleteResourceSetsOnDeleteRS" : {
    "title" : "Delete resource sets when Resource Server is removed",
    "description" : "Delete all resource sets that relate to a Resource Server when removing the
OAuth2 agent entry or removing the <code>uma_protection</code> scope from the OAuth2 agent.",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "pendingRequestsEnabled" : {
    "title" : "Pending Requests Enabled",
    "description" : "Specifies whether to use the Pending Requests subsystem that notifies the
resource owner that an attempt to access a resource was made.",
    "propertyOrder" : 450,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
```

```
    },
    "emailResourceOwnerOnPendingRequestCreation" : {
      "title" : "Email Resource Owner on Pending Request creation",
      "description" : "Specifies whether to send an email to the Resource Owner when a Pending Request is created when a Requesting Party requests authorization to a resource.",
      "propertyOrder" : 500,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    },
    "permissionTicketLifetime" : {
      "title" : "Permission Ticket Lifetime (seconds)",
      "description" : "The maximum life of a permission ticket before it expires, in seconds.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    }
  }
}
```

1.203.2. Global Operations

Resource path: `/global-config/services/uma`

Resource version: `1.0`

1.203.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action UmaProvider --global --actionName getAllTypes
```

1.203.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action UmaProvider --global --actionName getCreatableTypes
```

1.203.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action UmaProvider --global --actionName nextdescendents
```

1.203.2.4. read

Usage:

```
am> read UmaProvider --global
```

1.203.2.5. update

Usage:

```
am> update UmaProvider --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "emailRequestingPartyOnPendingRequestApproval" : {
          "title" : "Email Requesting Party on Pending Request approval",
          "description" : "Specifies whether to send an email to the Requesting Party when a Pending
Request is approved by the Resource Owner.",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "pendingRequestsEnabled" : {
          "title" : "Pending Requests Enabled",
          "description" : "Specifies whether to use the Pending Requests subsystem that notifies the
resource owner that an attempt to access a resource was made.",
          "propertyOrder" : 450,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "deleteResourceSetsOnDeleteRS" : {
          "title" : "Delete resource sets when Resource Server is removed",
          "description" : "Delete all resource sets that relate to a Resource Server when removing the
OAuth2 agent entry or removing the <code>uma_protection</code> scope from the OAuth2 agent.",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "userProfileLocaleAttribute" : {
          "title" : "User profile preferred Locale attribute",
          "description" : "User profile attribute storing the user's preferred locale.",
          "propertyOrder" : 700,
          "required" : true,
          "type" : "string",

```

```

    "exampleValue" : ""
  },
  "resharingMode" : {
    "title" : "Re-Sharing Mode",
    "description" : "Specifies whether re-sharing is off or on implicitly for all users,
allowing all users to re-share resource sets that have been shared with them.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "permissionTicketLifetime" : {
    "title" : "Permission Ticket Lifetime (seconds)",
    "description" : "The maximum life of a permission ticket before it expires, in seconds.",
    "propertyOrder" : 200,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "grantRptConditions" : {
    "title" : "Grant RPTs...",
    "description" : "In UMA, scope comes from both the permission ticket and from the token
request. An RPT is always granted when all scope matches, and is never granted when no scope matches.
You can configure when RPTs are granted for partial match conditions here. For more information, see
the UMA Grant Type specification section on Authorization Assessment and Results Determination.",
    "propertyOrder" : 900,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "emailResourceOwnerOnPendingRequestCreation" : {
    "title" : "Email Resource Owner on Pending Request creation",
    "description" : "Specifies whether to send an email to the Resource Owner when a Pending
Request is created when a Requesting Party requests authorization to a resource.",
    "propertyOrder" : 500,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "deletePoliciesOnDeleteRS" : {
    "title" : "Delete user policies when Resource Server is removed",
    "description" : "Delete all user policies that relate to a Resource Server when removing the
OAuth2 agent entry or removing the <code>uma_protection</code> scope from the OAuth2 agent.",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}

```


1.204. UmaResourceSetLabels

1.204.1. Realm Operations

Provides create, delete and query operations for UMA resource set labels

Resource path: `/users/{user}/oauth2/resources/labels`

Resource version: `1.0`

1.204.1.1. create

Creates a UMA Resource Set Label

Usage:

```
am> create UmaResourceSetLabels --realm Realm --id id --body body --user user
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "Represents a UMA Resource Set Label",
  "id" : "urn:jsonschema:org:forgerock:openam:oauth2:resources:labels:ResourceSetLabel",
  "type" : "object",
  "title" : "UMA Resource Set Label",
  "properties" : {
    "id" : {
      "type" : "string",
      "description" : "The unique identifier of the resource set label",
      "title" : "Id"
    },
    "name" : {
      "type" : "string",
      "description" : "The displayed text of the label",
      "title" : "Name"
    },
    "type" : {
      "type" : "string",
      "description" : "The type of the label e.g. 'System'",
      "title" : "Type",
      "enum" : [ "STAR", "USER", "SYSTEM" ]
    },
    "resourceSetIds" : {
      "type" : "array",
      "items" : {
        "type" : "string"
      }
    }
  }
}
```

--user

Provides create, delete and query operations for UMA resource set labels

1.204.1.2. delete

Deletes a UMA Resource Set Label

Usage:

```
am> delete UmaResourceSetLabels --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

Provides create, delete and query operations for UMA resource set labels

1.204.1.3. query

Queries the collection of UMA labels

Usage:

```
am> query UmaResourceSetLabels --realm Realm --filter filter --user user
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

--user

Provides create, delete and query operations for UMA resource set labels

1.205. UmaUserAuditHistory

1.205.1. Realm Operations

Provides access to UMA auditing history for a user

Resource path: `/users/{user}/uma/auditHistory`

Resource version: `1.0`

1.205.1.1. getHistory

Returns the audit history of a user

Usage:

```
am> action UmaUserAuditHistory --realm Realm --user user --actionName getHistory
```

Parameters:

--user

Provides access to UMA auditing history for a user

1.205.1.2. query

Queries the collection of auditing history

Usage:

```
am> query UmaUserAuditHistory --realm Realm --filter filter --user user
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

--user

Provides access to UMA auditing history for a user

1.206. User

1.206.1. Realm Operations

Resource path: [/realm-config/services/user](#)

Resource version: 1.0

1.206.1.1. create

Usage:

```
am> create User --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "dynamic" : {
      "properties" : {
        "adminDNStartingView" : {
          "title" : "Administrator DN Starting View",
          "description" : "Specifies the DN for the initial screen when the OpenAM administrator
successfully logs in to the OpenAM console.",
          "propertyOrder" : 200,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "defaultUserStatus" : {
          "title" : "Default User Status",
          "description" : "Inactive users cannot authenticate, though OpenAM stores their profiles.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "string",

```

```
        "exampleValue" : ""
      },
      "preferredTimezone" : {
        "title" : "User Preferred Timezone",
        "description" : "Time zone for accessing OpenAM console.",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
      }
    },
    "type" : "object",
    "title" : "Dynamic Attributes"
  }
}
```

1.206.1.2. delete

Usage:

```
am> delete User --realm Realm
```

1.206.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action User --realm Realm --actionName getAllTypes
```

1.206.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action User --realm Realm --actionName getCreatableTypes
```

1.206.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action User --realm Realm --actionName nextdescendents
```

1.206.1.6. read

Usage:

```
am> read User --realm Realm
```

1.206.1.7. update

Usage:

```
am> update User --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "dynamic" : {
      "properties" : {
        "adminDNStartingView" : {
          "title" : "Administrator DN Starting View",
          "description" : "Specifies the DN for the initial screen when the OpenAM administrator
successfully logs in to the OpenAM console.",
          "propertyOrder" : 200,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "defaultUserStatus" : {
          "title" : "Default User Status",
          "description" : "Inactive users cannot authenticate, though OpenAM stores their profiles.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "preferredTimezone" : {
          "title" : "User Preferred Timezone",
          "description" : "Time zone for accessing OpenAM console.",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    },
    "type" : "object",
    "title" : "Dynamic Attributes"
  }
}
```

1.206.2. Global Operations

Resource path: `/global-config/services/user`

Resource version: `1.0`

1.206.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action User --global --actionName getAllTypes
```

1.206.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action User --global --actionName getCreatableTypes
```

1.206.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action User --global --actionName nextdescendents
```

1.206.2.4. read

Usage:

```
am> read User --global
```

1.206.2.5. update

Usage:

```
am> update User --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
```

```

"dynamic" : {
  "properties" : {
    "preferredTimezone" : {
      "title" : "User Preferred Timezone",
      "description" : "Time zone for accessing OpenAM console.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "adminDNStartingView" : {
      "title" : "Administrator DN Starting View",
      "description" : "Specifies the DN for the initial screen when the OpenAM administrator
successfully logs in to the OpenAM console.",
      "propertyOrder" : 200,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "defaultUserStatus" : {
      "title" : "Default User Status",
      "description" : "Inactive users cannot authenticate, though OpenAM stores their profiles.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
"type" : "object",
"title" : "Dynamic Attributes"
}
}
}

```

1.207. UserGroups

1.207.1. Realm Operations

The User Groups resource allows an admin to query which groups a particular user belongs to. The only supported method is query

Resource path: `/users/{user}/groups`

Resource version: `1.0`

1.207.1.1. query

Query the user's groups

Usage:

```
am> query UserGroups --realm Realm --filter filter --user user
```


Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

--user

The User Groups resource allows an admin to query which groups a particular user belongs to. The only supported method is query

1.207.1.2. updateMemberships

Usage:

```
am> action UserGroups --realm Realm --body body --user user --actionName updateMemberships
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "",
  "title" : "User groups schema",
  "type" : "object",
  "properties" : {
    "groups" : {
      "type" : "array",
      "title" : "Name",
      "description" : "The name of the group",
      "items" : {
        "type" : "string"
      }
    }
  }
}
```

--user

The User Groups resource allows an admin to query which groups a particular user belongs to. The only supported method is query

1.208. UserPolicies

1.208.1. Realm Operations

The User Policy resource endpoint is responsible for managing a user's policies. The available operations are create, read, update, delete, query. Policies are realm specific, hence the URI for the

policies API can contain a realm component. If the realm is not specified in the URI, the top level realm is used.

Resource path: `/users/{user}/policies`

Resource version: `1.0`

1.208.1.1. create

Create new policy

Usage:

```
am> create UserPolicies --realm Realm --id id --body body --user user
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema": "http://json-schema.org/draft-04/schema#",
  "description": "Json schema for the policy resource",
  "title": "Policy Resource Schema",
  "type": "object",
  "properties": {
    "name": {
      "title": "Name",
      "description": "String matching the name of the application",
      "type": "string"
    },
    "active": {
      "title": "Active flag",
      "description": "Boolean indicating whether OpenAM considers the policy active for evaluation purposes, defaults to false",
      "type": "boolean"
    },
    "description": {
      "title": "Description",
      "description": "String describing the policy",
      "type": "string"
    },
    "applicationName": {
      "title": "Application name",
      "description": "String containing the application name, such as \"iPlanetAMWebAgentService\", or \"mypolicyset\"",
      "type": "string"
    },
    "actionValues": {
      "title": "Action values",
```

```

        "description" : "Set of string action names, each set to a boolean indicating whether the action
        is allowed. Chosen from the available actions provided by the associated Managing Resource Types
        resource type",
        "type" : "object",
        "additionalProperties" : {
            "type" : "boolean"
        }
    },
    "resources" : {
        "title" : "Resources",
        "description" : "List of the resource name pattern strings to which the policy applies. Must
        conform to the pattern templates provided by the associated Managing Resource Types resource type",
        "type" : "array",
        "items" : {
            "type" : "string"
        }
    },
    "subject" : {
        "title" : "Subject",
        "description" : "Specifies the subject conditions to which the policy applies, where subjects
        can be combined by using the built-in types \"AND\", \"OR\", and \"NOT\", and where subject
        implementations are pluggable",
        "type" : "object"
    },
    "condition" : {
        "title" : "Condition",
        "description" : "Specifies environment conditions, where conditions can be combined by using the
        built-in types \"AND\", \"OR\", and \"NOT\", and where condition implementations are pluggable",
        "type" : "object",
        "properties" : {
            "type" : {
                "type" : "string"
            }
        },
        "conditions" : {
            "type" : "array",
            "title" : "Condition",
            "description" : "Specifies environment conditions, where conditions can be combined by using
            the built-in types \"AND\", \"OR\", and \"NOT\", and where condition implementations are pluggable",
            "items" : {
                "type" : "object"
            }
        }
    }
},
"resourceTypeUuid" : {
    "title" : "Resource Type UUID",
    "description" : "The UUIDs of the resource type associated with the policy",
    "type" : "string"
},
"resourceAttributes" : {
    "title" : "Resource Attributes",
    "description" : "List of attributes to return with decisions. These attributes are known as
    response attributes",
    "type" : "array",
    "items" : {
        "type" : "object"
    }
},
"lastModifiedBy" : {

```

```
    "title" : "Last Modified By",
    "description" : "A string containing the universal identifier DN of the subject that most
recently updated the policy",
    "type" : "string"
  },
  "lastModifiedDate" : {
    "title" : "Last Modified date",
    "description" : "An integer containing the last modified date and time, in number of seconds",
    "type" : "string"
  },
  "createdBy" : {
    "title" : "Created By",
    "description" : "A string containing the universal identifier DN of the subject that created the
policy",
    "type" : "string"
  },
  "creationDate" : {
    "title" : "Creation Date",
    "description" : "An integer containing the creation date and time, in number of seconds",
    "type" : "string"
  }
}
```

--user

The User Policy resource endpoint is responsible for managing a user's policies. The available operations are create, read, update, delete, query. Policies are realm specific, hence the URI for the policies API can contain a realm component. If the realm is not specified in the URI, the top level realm is used.

1.208.1.2. delete

Delete policy

Usage:

```
am> delete UserPolicies --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

The User Policy resource endpoint is responsible for managing a user's policies. The available operations are create, read, update, delete, query. Policies are realm specific, hence the URI for the policies API can contain a realm component. If the realm is not specified in the URI, the top level realm is used.

1.208.1.3. query

Query the stored policies

Usage:

```
am> query UserPolicies --realm Realm --filter filter --user user
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all. Fields that can be queried: [*]

--user

The User Policy resource endpoint is responsible for managing a user's policies. The available operations are create, read, update, delete, query. Policies are realm specific, hence the URI for the policies API can contain a realm component. If the realm is not specified in the URI, the top level realm is used.

1.208.1.4. read

Read policy

Usage:

```
am> read UserPolicies --realm Realm --id id --user user
```

Parameters:

--id

The unique identifier for the resource.

--user

The User Policy resource endpoint is responsible for managing a user's policies. The available operations are create, read, update, delete, query. Policies are realm specific, hence the URI for the policies API can contain a realm component. If the realm is not specified in the URI, the top level realm is used.

1.208.1.5. update

Update an existing policy

Usage:

```
am> update UserPolicies --realm Realm --id id --body body --user user
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "Json schema for the policy resource",
  "title" : "Policy Resource Schema",
  "type" : "object",
  "properties" : {
    "name" : {
      "title" : "Name",
      "description" : "String matching the name of the application",
      "type" : "string"
    },
    "active" : {
      "title" : "Active flag",
      "description" : "Boolean indicating whether OpenAM considers the policy active for evaluation purposes, defaults to false",
      "type" : "boolean"
    },
    "description" : {
      "title" : "Description",
      "description" : "String describing the policy",
      "type" : "string"
    },
    "applicationName" : {
      "title" : "Application name",
      "description" : "String containing the application name, such as \"iPlanetAMWebAgentService\", or \"mypolicyset\"",
      "type" : "string"
    },
    "actionValues" : {
      "title" : "Action values",
      "description" : "Set of string action names, each set to a boolean indicating whether the action is allowed. Chosen from the available actions provided by the associated Managing Resource Types resource type",
      "type" : "object",
      "additionalProperties" : {
        "type" : "boolean"
      }
    },
    "resources" : {
      "title" : "Resources",
      "description" : "List of the resource name pattern strings to which the policy applies. Must conform to the pattern templates provided by the associated Managing Resource Types resource type",
      "type" : "array",
      "items" : {
        "type" : "string"
      }
    },
    "subject" : {
      "title" : "Subject",
```

```

    "description" : "Specifies the subject conditions to which the policy applies, where subjects
can be combined by using the built-in types \"AND\", \"OR\", and \"NOT\", and where subject
implementations are pluggable",
    "type" : "object"
  },
  "condition" : {
    "title" : "Condition",
    "description" : "Specifies environment conditions, where conditions can be combined by using the
built-in types \"AND\", \"OR\", and \"NOT\", and where condition implementations are pluggable",
    "type" : "object",
    "properties" : {
      "type" : {
        "type" : "string"
      },
      "conditions" : {
        "type" : "array",
        "title" : "Condition",
        "description" : "Specifies environment conditions, where conditions can be combined by using
the built-in types \"AND\", \"OR\", and \"NOT\", and where condition implementations are pluggable",
        "items" : {
          "type" : "object"
        }
      }
    }
  },
  "resourceTypeUuid" : {
    "title" : "Resource Type UUID",
    "description" : "The UUIDs of the resource type associated with the policy",
    "type" : "string"
  },
  "resourceAttributes" : {
    "title" : "Resource Attributes",
    "description" : "List of attributes to return with decisions. These attributes are known as
response attributes",
    "type" : "array",
    "items" : {
      "type" : "object"
    }
  },
  "lastModifiedBy" : {
    "title" : "Last Modified By",
    "description" : "A string containing the universal identifier DN of the subject that most
recently updated the policy",
    "type" : "string"
  },
  "lastModifiedDate" : {
    "title" : "Last Modified date",
    "description" : "An integer containing the last modified date and time, in number of seconds",
    "type" : "string"
  },
  "createdBy" : {
    "title" : "Created By",
    "description" : "A string containing the universal identifier DN of the subject that created the
policy",
    "type" : "string"
  },
  "creationDate" : {
    "title" : "Creation Date",
    "description" : "An integer containing the creation date and time, in number of seconds",

```

```
    "type" : "string"
  }
}
```

--user

The User Policy resource endpoint is responsible for managing a user's policies. The available operations are create, read, update, delete, query. Policies are realm specific, hence the URI for the policies API can contain a realm component. If the realm is not specified in the URI, the top level realm is used.

1.209. UserRegistration

1.209.1. Realm Operations

Self Service endpoint for registering a new user

Resource path: `/selfservice/userRegistration`

Resource version: `1.0`

1.209.1.1. read

Initialise the user registration process. A set of requirements will be returned that will need to be fulfilled and sent to the submitRequirements action.

Usage:

```
am> read UserRegistration --realm Realm
```

1.209.1.2. submitRequirements

Submit some fulfilled requirements. Returns either a completion status, or a token along with some more requirements. If requirements are returned, they should be submitted with the token as a fresh request to this action.

Usage:

```
am> action UserRegistration --realm Realm --body body --actionName submitRequirements
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:


```
{
  "$schema" : "http://json-schema.org/draft-04/schema#",
  "description" : "The structure of a request to the submitRequirements action.",
  "type" : "object",
  "title" : "Submit requirements structure",
  "properties" : {
    "token" : {
      "type" : "string",
      "title" : "Token",
      "description" : "The token returned from the previous submitRequirements request."
    },
    "input" : {
      "type" : "object",
      "title" : "Input",
      "description" : "The input as collected from the new user. This object must conform to the JSON Schema of the requirements property from the last response.",
      "patternProperties" : {
        ".*" : {
          "type" : "any",
          "title" : "Input Property",
          "description" : "Valid content according to the received JSON Schema."
        }
      }
    }
  }
},
"required" : [ "input" ]
}
```

1.210. UserSelfService

1.210.1. Realm Operations

Resource path: `/realm-config/services/selfService`

Resource version: `1.0`

1.210.1.1. create

Usage:

```
am> create UserSelfService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
```

```

"forgottenPassword" : {
  "type" : "object",
  "title" : "Forgotten Password",
  "propertyOrder" : 2,
  "properties" : {
    "forgottenPasswordKbaEnabled" : {
      "title" : "Security Questions",
      "description" : "If enabled, users must answer their security questions during the forgotten
password process.",
      "propertyOrder" : 200,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "forgottenPasswordEmailSubject" : {
      "title" : "Outgoing Email Subject",
      "description" : "Customize the forgotten password email subject text. Format is
<code>locale|subject text</code>.",
      "propertyOrder" : 220,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "numberOfAllowedAttempts" : {
      "title" : "Lock Out After number of attempts",
      "description" : "Can be set to 1 or more attempts for a user to correctly answer all their
security questions. After the number of configured attempts the user has not correctly answered them
the password reset feature will be disabled.",
      "propertyOrder" : 202,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "forgottenPasswordCaptchaEnabled" : {
      "title" : "Captcha",
      "description" : "If enabled, users must pass a Google reCAPTCHA challenge during password
reset to mitigate against software bots.",
      "propertyOrder" : 180,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "numberOfAttemptsEnforced" : {
      "title" : "Enforce password reset lockout",
      "description" : "If enabled, users will be prevented from resetting their password after the
configured number of failed attempts.",
      "propertyOrder" : 201,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "forgottenPasswordTokenTTL" : {
      "title" : "Token Lifetime (seconds)",
      "description" : "Maximum lifetime for the token allowing forgotten password reset, in
seconds.<p><p>Specify a value from <code>0</code> to <code>2147483647</code>.",
      "propertyOrder" : 210,

```

```

        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "forgottenPasswordEmailVerificationEnabled" : {
        "title" : "Email Verification",
        "description" : "If enabled, users who reset passwords must perform email address
verification.",
        "propertyOrder" : 190,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "forgottenPasswordEnabled" : {
        "title" : "Forgotten Password",
        "description" : "If enabled, users can reset their forgotten password.",
        "propertyOrder" : 170,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "forgottenPasswordEmailBody" : {
        "title" : "Outgoing Email Body",
        "description" : "Customize the forgotten password email body text. Format is <code>locale|
body text</code>.",
        "propertyOrder" : 230,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"generalConfig" : {
    "type" : "object",
    "title" : "General Configuration",
    "propertyOrder" : 0,
    "properties" : {
        "captchaSiteKey" : {
            "title" : "Google reCAPTCHA Site Key",
            "description" : "Google reCAPTCHA plugin site key.",
            "propertyOrder" : 20,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "captchaSecretKey" : {
            "title" : "Google reCAPTCHA Secret Key",
            "description" : "Google reCAPTCHA plugin secret key.",
            "propertyOrder" : 30,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "minimumAnswersToVerify" : {
            "title" : "Minimum Answers to Verify",

```

```

    "description" : "Specifies the minimum number of KBA questions that users need to answer
to be granted the privilege to carry out an action, such as registering for an account, resetting a
password, or retrieving a username. Specify a value from <code>0</code> to <code>50</code>.",
    "propertyOrder" : 70,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "encryptionKeyPairAlias" : {
    "title" : "Encryption Key Pair Alias",
    "description" : "An encryption key alias in the OpenAM server's JCEKS keystore. Used to
encrypt the JWT token that OpenAM uses to track end users during User Self-Service operations.",
    "propertyOrder" : 0,
    "required" : true,
    "type" : "string",
    "exampleValue" : "selfserviceentctest"
  },
  "minimumAnswersToDefine" : {
    "title" : "Minimum Answers to Define",
    "description" : "Specifies the minimum number of KBA answers that users must define.",
    "propertyOrder" : 60,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "signingSecretKeyAlias" : {
    "title" : "Signing Secret Key Alias",
    "description" : "A signing secret key alias in the OpenAM server's JCEKS keystore. Used to
sign the JWT token that OpenAM uses to track end users during User Self-Service operations.",
    "propertyOrder" : 10,
    "required" : true,
    "type" : "string",
    "exampleValue" : "selfservicesigntest"
  },
  "kbaQuestions" : {
    "title" : "Security Questions",
    "description" : "Specifies the default set of knowledge-based authentication (KBA) security
questions. The security questions can be set for the User Self-Registration, forgotten password
reset, and forgotten username services, respectively.<p><p>Format is <code>unique key|locale|
question</code>.",
    "propertyOrder" : 50,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "captchaVerificationUrl" : {
    "title" : "Google Re-captcha Verification URL",
    "description" : "Google reCAPTCHA plugin verification URL.",
    "propertyOrder" : 40,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "validQueryAttributes" : {
    "title" : "Valid Query Attributes",

```

```

    "description" : "Specifies the valid query attributes used to search for the user. This is a
list of attributes used to identify your account for forgotten password and forgotten username.",
    "propertyOrder" : 80,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
},
"forgottenUsername" : {
  "type" : "object",
  "title" : "Forgotten Username",
  "propertyOrder" : 3,
  "properties" : {
    "forgottenUsernameEnabled" : {
      "title" : "Forgotten Username",
      "description" : "If enabled, users can retrieve their forgotten username.",
      "propertyOrder" : 240,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "forgottenUsernameTokenTTL" : {
      "title" : "Token LifeTime (seconds)",
      "description" : "Maximum lifetime for the token allowing forgotten username, in seconds.",
      "propertyOrder" : 290,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "forgottenUsernameEmailUsernameEnabled" : {
      "title" : "Email Username",
      "description" : "If enabled, users receive their forgotten username by email.",
      "propertyOrder" : 270,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "forgottenUsernameEmailBody" : {
      "title" : "Outgoing Email Body",
      "description" : "Customizes the forgotten username email body text. Format is <code>locale|
body text</code>.",
      "propertyOrder" : 310,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "forgottenUsernameShowUsernameEnabled" : {
      "title" : "Show Username",
      "description" : "If enabled, users see their forgotten username on the browser page.",
      "propertyOrder" : 280,
      "required" : false,
      "type" : "boolean",

```

```

    "exampleValue" : ""
  },
  "forgottenUsernameCaptchaEnabled" : {
    "title" : "Captcha",
    "description" : "If enabled, users must pass a Google reCAPTCHA challenge during the
forgotten username retrieval process to mitigate against software bots.",
    "propertyOrder" : 250,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "forgottenUsernameEmailSubject" : {
    "title" : "Outgoing Email Subject",
    "description" : "Customizes the forgotten username email subject text. Format is
<code>locale|subject text</code>.",
    "propertyOrder" : 300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "forgottenUsernameKbaEnabled" : {
    "title" : "Security Questions",
    "description" : "If enabled, users must answer their security questions during the forgotten
username process.",
    "propertyOrder" : 260,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"advancedConfig" : {
  "type" : "object",
  "title" : "Advanced Configuration",
  "propertyOrder" : 5,
  "properties" : {
    "forgottenUsernameServiceConfigClass" : {
      "title" : "Forgotten Username Service Config Provider Class",
      "description" : "Specifies the provider class to configure any custom plugins.",
      "propertyOrder" : 370,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "userRegistrationConfirmationUrl" : {
      "title" : "User Registration Confirmation Email URL",
      "description" : "Specifies the confirmation URL that the user receives during the self-
registration process. The <code>${realm}</code> string is replaced with the current realm.",
      "propertyOrder" : 330,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "forgottenPasswordServiceConfigClass" : {
      "title" : "Forgotten Password Service Config Provider Class",
      "description" : "Specifies the provider class to configure any custom plugins.",

```

```

    "propertyOrder" : 360,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "userRegistrationServiceConfigClass" : {
    "title" : "User Registration Service Config Provider Class",
    "description" : "Specifies the provider class to configure any custom plugins.",
    "propertyOrder" : 350,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "forgottenPasswordConfirmationUrl" : {
    "title" : "Forgotten Password Confirmation Email URL",
    "description" : "Specifies the confirmation URL that the user receives after confirming
their identity during the forgotten password process. The <code>${realm}</code> string is replaced
with the current realm.",
    "propertyOrder" : 340,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"profileManagement" : {
  "type" : "object",
  "title" : "Profile Management",
  "propertyOrder" : 4,
  "properties" : {
    "profileProtectedUserAttributes" : {
      "title" : "Protected Update Attributes",
      "description" : "Specifies a profile's protected user attributes, which causes re-
authentication when the user attempts to modify these attributes.",
      "propertyOrder" : 320,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
},
"userRegistration" : {
  "type" : "object",
  "title" : "User Registration",
  "propertyOrder" : 1,
  "properties" : {
    "userRegistrationEmailVerificationEnabled" : {
      "title" : "Email Verification",
      "description" : "If enabled, users who self-register must perform email address
verification.",
      "propertyOrder" : 110,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    }
  },
  "userRegistrationEmailSubject" : {

```

```

    "title" : "Outgoing Email Subject",
    "description" : "Customize the User Self-Registration verification email subject text.
Format is <code>locale|subject text</code>.",
    "propertyOrder" : 140,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "userRegisteredDestination" : {
    "title" : "Destination After Successful Self-Registration",
    "description" : "Specifies the action to be taken after a user successfully registers
a new account. Choose from:<ul><li><code>default</code>. User is sent to a success page without
being logged in.</li><li><code>login</code>. User is sent to the login page to authenticate.</
li><li><code>autologin</code>. User is automatically logged in and sent to the appropriate page.</
li></ul>",
    "propertyOrder" : 161,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userRegistrationKbaEnabled" : {
    "title" : "Security Questions",
    "description" : "If enabled, users must set up their security questions during the self-
registration process.",
    "propertyOrder" : 120,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userRegistrationValidUserAttributes" : {
    "title" : "Valid Creation Attributes",
    "description" : "Specifies a whitelist of user attributes that can be set during user
creation.",
    "propertyOrder" : 160,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "userRegistrationTokenTTL" : {
    "title" : "Token Lifetime (seconds)",
    "description" : "Maximum lifetime of the token allowing User Self-Registration, in
seconds.",
    "propertyOrder" : 130,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "userRegistrationEmailBody" : {
    "title" : "Outgoing Email Body",
    "description" : "Customize the User Self-Registration verification email body text. Format
is: <code>locale|body text</code>.",
    "propertyOrder" : 150,
    "required" : false,

```



```
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "userRegistrationEnabled" : {
    "title" : "User Registration",
    "description" : "If enabled, new users can sign up for an account.",
    "propertyOrder" : 90,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userRegistrationCaptchaEnabled" : {
    "title" : "Captcha",
    "description" : "If enabled, users must pass a Google reCAPTCHA challenge during user self-
registration to mitigate against software bots.",
    "propertyOrder" : 100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userRegistrationEmailVerificationFirstEnabled" : {
    "title" : "Verify Email before User Detail",
    "description" : "If enabled, email address verification will be performed first before user
details screen is displayed. This will take effect only if Verify Email is enabled.",
    "propertyOrder" : 110,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
}
}
```

1.210.1.2. delete

Usage:

```
am> delete UserSelfService --realm Realm
```

1.210.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action UserSelfService --realm Realm --actionName getAllTypes
```

1.210.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action UserSelfService --realm Realm --actionName getCreatableTypes
```

1.210.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action UserSelfService --realm Realm --actionName nextdescendents
```

1.210.1.6. read

Usage:

```
am> read UserSelfService --realm Realm
```

1.210.1.7. update

Usage:

```
am> update UserSelfService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "forgottenPassword" : {
      "type" : "object",
      "title" : "Forgotten Password",
      "propertyOrder" : 2,
      "properties" : {
        "forgottenPasswordKbaEnabled" : {
          "title" : "Security Questions",
          "description" : "If enabled, users must answer their security questions during the forgotten
password process.",
          "propertyOrder" : 200,
          "required" : false,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "forgottenPasswordEmailSubject" : {
          "title" : "Outgoing Email Subject",
```

```

    "description" : "Customize the forgotten password email subject text. Format is
<code>locale|subject text</code>.",
    "propertyOrder" : 220,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "numberOfAllowedAttempts" : {
    "title" : "Lock Out After number of attempts",
    "description" : "Can be set to 1 or more attempts for a user to correctly answer all their
security questions. After the number of configured attempts the user has not correctly answered them
the password reset feature will be disabled.",
    "propertyOrder" : 202,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "forgottenPasswordCaptchaEnabled" : {
    "title" : "Captcha",
    "description" : "If enabled, users must pass a Google reCAPTCHA challenge during password
reset to mitigate against software bots.",
    "propertyOrder" : 180,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "numberOfAttemptsEnforced" : {
    "title" : "Enforce password reset lockout",
    "description" : "If enabled, users will be prevented from resetting their password after the
configured number of failed attempts.",
    "propertyOrder" : 201,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "forgottenPasswordTokenTTL" : {
    "title" : "Token Lifetime (seconds)",
    "description" : "Maximum lifetime for the token allowing forgotten password reset, in
seconds.<p><p>Specify a value from <code>0</code> to <code>2147483647</code>.",
    "propertyOrder" : 210,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "forgottenPasswordEmailVerificationEnabled" : {
    "title" : "Email Verification",
    "description" : "If enabled, users who reset passwords must perform email address
verification.",
    "propertyOrder" : 190,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "forgottenPasswordEnabled" : {
    "title" : "Forgotten Password",
    "description" : "If enabled, users can reset their forgotten password.",

```

```

    "propertyOrder" : 170,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "forgottenPasswordEmailBody" : {
    "title" : "Outgoing Email Body",
    "description" : "Customize the forgotten password email body text. Format is <code>locale|
body text</code>.",
    "propertyOrder" : 230,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
},
"generalConfig" : {
  "type" : "object",
  "title" : "General Configuration",
  "propertyOrder" : 0,
  "properties" : {
    "captchaSiteKey" : {
      "title" : "Google reCAPTCHA Site Key",
      "description" : "Google reCAPTCHA plugin site key.",
      "propertyOrder" : 20,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "captchaSecretKey" : {
      "title" : "Google reCAPTCHA Secret Key",
      "description" : "Google reCAPTCHA plugin secret key.",
      "propertyOrder" : 30,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "minimumAnswersToVerify" : {
      "title" : "Minimum Answers to Verify",
      "description" : "Specifies the minimum number of KBA questions that users need to answer
to be granted the privilege to carry out an action, such as registering for an account, resetting a
password, or retrieving a username. Specify a value from <code>0</code> to <code>50</code>.",
      "propertyOrder" : 70,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "encryptionKeyPairAlias" : {
      "title" : "Encryption Key Pair Alias",
      "description" : "An encryption key alias in the OpenAM server's JCEKS keystore. Used to
encrypt the JWT token that OpenAM uses to track end users during User Self-Service operations.",
      "propertyOrder" : 0,
      "required" : true,
      "type" : "string",
      "exampleValue" : "selfserviceentest"
    }
  }
},

```

```

"minimumAnswersToDefine" : {
  "title" : "Minimum Answers to Define",
  "description" : "Specifies the minimum number of KBA answers that users must define.",
  "propertyOrder" : 60,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"signingSecretKeyAlias" : {
  "title" : "Signing Secret Key Alias",
  "description" : "A signing secret key alias in the OpenAM server's JCEKS keystore. Used to
sign the JWT token that OpenAM uses to track end users during User Self-Service operations.",
  "propertyOrder" : 10,
  "required" : true,
  "type" : "string",
  "exampleValue" : "selfservicesigntest"
},
"kbaQuestions" : {
  "title" : "Security Questions",
  "description" : "Specifies the default set of knowledge-based authentication (KBA) security
questions. The security questions can be set for the User Self-Registration, forgotten password
reset, and forgotten username services, respectively.<p><p>Format is <code>unique key|locale|
question</code>.",
  "propertyOrder" : 50,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"captchaVerificationUrl" : {
  "title" : "Google Re-captcha Verification URL",
  "description" : "Google reCAPTCHA plugin verification URL.",
  "propertyOrder" : 40,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"validQueryAttributes" : {
  "title" : "Valid Query Attributes",
  "description" : "Specifies the valid query attributes used to search for the user. This is a
list of attributes used to identify your account for forgotten password and forgotten username.",
  "propertyOrder" : 80,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
}
},
"forgottenUsername" : {
  "type" : "object",
  "title" : "Forgotten Username",
  "propertyOrder" : 3,
  "properties" : {
    "forgottenUsernameEnabled" : {

```

```
"title" : "Forgotten Username",
"description" : "If enabled, users can retrieve their forgotten username.",
"propertyOrder" : 240,
"required" : true,
"type" : "boolean",
"exampleValue" : ""
},
"forgottenUsernameTokenTTL" : {
"title" : "Token LifeTime (seconds)",
"description" : "Maximum lifetime for the token allowing forgotten username, in seconds.",
"propertyOrder" : 290,
"required" : false,
"type" : "integer",
"exampleValue" : ""
},
"forgottenUsernameEmailUsernameEnabled" : {
"title" : "Email Username",
"description" : "If enabled, users receive their forgotten username by email.",
"propertyOrder" : 270,
"required" : false,
"type" : "boolean",
"exampleValue" : ""
},
"forgottenUsernameEmailBody" : {
"title" : "Outgoing Email Body",
"description" : "Customizes the forgotten username email body text. Format is <code>locale|
body text</code>.",
"propertyOrder" : 310,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"forgottenUsernameShowUsernameEnabled" : {
"title" : "Show Username",
"description" : "If enabled, users see their forgotten username on the browser page.",
"propertyOrder" : 280,
"required" : false,
"type" : "boolean",
"exampleValue" : ""
},
"forgottenUsernameCaptchaEnabled" : {
"title" : "Captcha",
"description" : "If enabled, users must pass a Google reCAPTCHA challenge during the
forgotten username retrieval process to mitigate against software bots.",
"propertyOrder" : 250,
"required" : false,
"type" : "boolean",
"exampleValue" : ""
},
"forgottenUsernameEmailSubject" : {
"title" : "Outgoing Email Subject",
"description" : "Customizes the forgotten username email subject text. Format is
<code>locale|subject text</code>.",
"propertyOrder" : 300,
"required" : false,
"items" : {
```

```

    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"forgottenUsernameKbaEnabled" : {
  "title" : "Security Questions",
  "description" : "If enabled, users must answer their security questions during the forgotten
username process.",
  "propertyOrder" : 260,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
}
},
"advancedConfig" : {
  "type" : "object",
  "title" : "Advanced Configuration",
  "propertyOrder" : 5,
  "properties" : {
    "forgottenUsernameServiceConfigClass" : {
      "title" : "Forgotten Username Service Config Provider Class",
      "description" : "Specifies the provider class to configure any custom plugins.",
      "propertyOrder" : 370,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "userRegistrationConfirmationUrl" : {
      "title" : "User Registration Confirmation Email URL",
      "description" : "Specifies the confirmation URL that the user receives during the self-
registration process. The <code>${realm}</code> string is replaced with the current realm.",
      "propertyOrder" : 330,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "forgottenPasswordServiceConfigClass" : {
      "title" : "Forgotten Password Service Config Provider Class",
      "description" : "Specifies the provider class to configure any custom plugins.",
      "propertyOrder" : 360,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "userRegistrationServiceConfigClass" : {
      "title" : "User Registration Service Config Provider Class",
      "description" : "Specifies the provider class to configure any custom plugins.",
      "propertyOrder" : 350,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "forgottenPasswordConfirmationUrl" : {
      "title" : "Forgotten Password Confirmation Email URL",
      "description" : "Specifies the confirmation URL that the user receives after confirming
their identity during the forgotten password process. The <code>${realm}</code> string is replaced
with the current realm.",

```

```

    "propertyOrder" : 340,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
},
"profileManagement" : {
  "type" : "object",
  "title" : "Profile Management",
  "propertyOrder" : 4,
  "properties" : {
    "profileProtectedUserAttributes" : {
      "title" : "Protected Update Attributes",
      "description" : "Specifies a profile's protected user attributes, which causes re-
authentication when the user attempts to modify these attributes.",
      "propertyOrder" : 320,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
},
"userRegistration" : {
  "type" : "object",
  "title" : "User Registration",
  "propertyOrder" : 1,
  "properties" : {
    "userRegistrationEmailVerificationEnabled" : {
      "title" : "Email Verification",
      "description" : "If enabled, users who self-register must perform email address
verification.",
      "propertyOrder" : 110,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "userRegistrationEmailSubject" : {
      "title" : "Outgoing Email Subject",
      "description" : "Customize the User Self-Registration verification email subject text.
Format is <code>locale|subject text</code>.",
      "propertyOrder" : 140,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "userRegisteredDestination" : {
      "title" : "Destination After Successful Self-Registration",
      "description" : "Specifies the action to be taken after a user successfully registers
a new account. Choose from:<ul><li><code>default</code>. User is sent to a success page without
being logged in.</li><li><code>login</code>. User is sent to the login page to authenticate.</
li><li><code>autologin</code>. User is automatically logged in and sent to the appropriate page.</
li></ul>",

```



```
    "propertyOrder" : 161,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "userRegistrationKbaEnabled" : {
    "title" : "Security Questions",
    "description" : "If enabled, users must set up their security questions during the self-
registration process.",
    "propertyOrder" : 120,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userRegistrationValidUserAttributes" : {
    "title" : "Valid Creation Attributes",
    "description" : "Specifies a whitelist of user attributes that can be set during user
creation.",
    "propertyOrder" : 160,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "userRegistrationTokenTTL" : {
    "title" : "Token Lifetime (seconds)",
    "description" : "Maximum lifetime of the token allowing User Self-Registration, in
seconds.",
    "propertyOrder" : 130,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "userRegistrationEmailBody" : {
    "title" : "Outgoing Email Body",
    "description" : "Customize the User Self-Registration verification email body text. Format
is: <code>locale|body text</code>.",
    "propertyOrder" : 150,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "userRegistrationEnabled" : {
    "title" : "User Registration",
    "description" : "If enabled, new users can sign up for an account.",
    "propertyOrder" : 90,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userRegistrationCaptchaEnabled" : {
    "title" : "Captcha",
    "description" : "If enabled, users must pass a Google reCAPTCHA challenge during user self-
registration to mitigate against software bots.",
```

```
    "propertyOrder" : 100,  
    "required" : false,  
    "type" : "boolean",  
    "exampleValue" : ""  
  },  
  "userRegistrationEmailVerificationFirstEnabled" : {  
    "title" : "Verify Email before User Detail",  
    "description" : "If enabled, email address verification will be performed first before user  
details screen is displayed. This will take effect only if Verify Email is enabled.",  
    "propertyOrder" : 110,  
    "required" : false,  
    "type" : "boolean",  
    "exampleValue" : ""  
  }  
}  
}  
}
```

1.210.2. Global Operations

Resource path: `/global-config/services/selfService`

Resource version: `1.0`

1.210.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action UserSelfService --global --actionName getAllTypes
```

1.210.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action UserSelfService --global --actionName getCreatableTypes
```

1.210.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action UserSelfService --global --actionName nextdescendents
```

1.210.2.4. read

Usage:

```
am> read UserSelfService --global
```

1.210.2.5. update

Usage:

```
am> update UserSelfService --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "userRegistration" : {
          "type" : "object",
          "title" : "User Registration",
          "propertyOrder" : 1,
          "properties" : {
            "userRegistrationValidUserAttributes" : {
              "title" : "Valid Creation Attributes",
              "description" : "Specifies a whitelist of user attributes that can be set during user
creation.",
              "propertyOrder" : 160,
              "required" : false,
              "items" : {
                "type" : "string"
              },
              "type" : "array",
              "exampleValue" : ""
            },
            "userRegistrationEmailVerificationFirstEnabled" : {
              "title" : "Verify Email before User Detail",
              "description" : "If enabled, email address verification will be performed first before
user details screen is displayed. This will take effect only if Verify Email is enabled.",
              "propertyOrder" : 110,
              "required" : false,
              "type" : "boolean",
              "exampleValue" : ""
            }
          },
          "userRegistrationTokenTTL" : {
            "title" : "Token Lifetime (seconds)",
            "description" : "Maximum lifetime of the token allowing User Self-Registration, in
seconds.",
            "propertyOrder" : 130,
            "required" : false,
            "type" : "integer",
```

```

    "exampleValue" : ""
  },
  "userRegistrationEnabled" : {
    "title" : "User Registration",
    "description" : "If enabled, new users can sign up for an account.",
    "propertyOrder" : 90,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userRegistrationEmailVerificationEnabled" : {
    "title" : "Email Verification",
    "description" : "If enabled, users who self-register must perform email address
verification.",
    "propertyOrder" : 110,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userRegistrationEmailSubject" : {
    "title" : "Outgoing Email Subject",
    "description" : "Customize the User Self-Registration verification email subject text.
Format is <code>locale|subject text</code>.",
    "propertyOrder" : 140,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "userRegistrationCaptchaEnabled" : {
    "title" : "Captcha",
    "description" : "If enabled, users must pass a Google reCAPTCHA challenge during user
self-registration to mitigate against software bots.",
    "propertyOrder" : 100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userRegistrationKbaEnabled" : {
    "title" : "Security Questions",
    "description" : "If enabled, users must set up their security questions during the self-
registration process.",
    "propertyOrder" : 120,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "userRegisteredDestination" : {
    "title" : "Destination After Successful Self-Registration",
    "description" : "Specifies the action to be taken after a user successfully registers
a new account. Choose from:<ul><li><code>default</code>. User is sent to a success page without
being logged in.</li><li><code>login</code>. User is sent to the login page to authenticate.</
li><li><code>autologin</code>. User is automatically logged in and sent to the appropriate page.</
li></ul>",
    "propertyOrder" : 161,
    "required" : true,
    "type" : "string",

```

```

        "exampleValue" : ""
    },
    "userRegistrationEmailBody" : {
        "title" : "Outgoing Email Body",
        "description" : "Customize the User Self-Registration verification email body text.
Format is: <code>locale|body text</code>.",
        "propertyOrder" : 150,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
}
},
"forgottenUsername" : {
    "type" : "object",
    "title" : "Forgotten Username",
    "propertyOrder" : 3,
    "properties" : {
        "forgottenUsernameTokenTTL" : {
            "title" : "Token LifeTime (seconds)",
            "description" : "Maximum lifetime for the token allowing forgotten username, in
seconds.",
            "propertyOrder" : 290,
            "required" : false,
            "type" : "integer",
            "exampleValue" : ""
        },
        "forgottenUsernameEmailSubject" : {
            "title" : "Outgoing Email Subject",
            "description" : "Customizes the forgotten username email subject text. Format is
<code>locale|subject text</code>.",
            "propertyOrder" : 300,
            "required" : false,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        },
        "forgottenUsernameEnabled" : {
            "title" : "Forgotten Username",
            "description" : "If enabled, users can retrieve their forgotten username.",
            "propertyOrder" : 240,
            "required" : true,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "forgottenUsernameEmailUsernameEnabled" : {
            "title" : "Email Username",
            "description" : "If enabled, users receive their forgotten username by email.",
            "propertyOrder" : 270,
            "required" : false,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "forgottenUsernameEmailBody" : {

```

```

        "title" : "Outgoing Email Body",
        "description" : "Customizes the forgotten username email body text. Format is
<code>locale|body text</code>.",
        "propertyOrder" : 310,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "forgottenUsernameKbaEnabled" : {
        "title" : "Security Questions",
        "description" : "If enabled, users must answer their security questions during the
forgotten username process.",
        "propertyOrder" : 260,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "forgottenUsernameCaptchaEnabled" : {
        "title" : "Captcha",
        "description" : "If enabled, users must pass a Google reCAPTCHA challenge during the
forgotten username retrieval process to mitigate against software bots.",
        "propertyOrder" : 250,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "forgottenUsernameShowUsernameEnabled" : {
        "title" : "Show Username",
        "description" : "If enabled, users see their forgotten username on the browser page.",
        "propertyOrder" : 280,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    }
}
},
"generalConfig" : {
    "type" : "object",
    "title" : "General Configuration",
    "propertyOrder" : 0,
    "properties" : {
        "minimumAnswersToVerify" : {
            "title" : "Minimum Answers to Verify",
            "description" : "Specifies the minimum number of KBA questions that users need to answer
to be granted the privilege to carry out an action, such as registering for an account, resetting a
password, or retrieving a username. Specify a value from <code>0</code> to <code>50</code>.",
            "propertyOrder" : 70,
            "required" : false,
            "type" : "integer",
            "exampleValue" : ""
        },
        "signingSecretKeyAlias" : {
            "title" : "Signing Secret Key Alias",
            "description" : "A signing secret key alias in the OpenAM server's JCEKS keystore. Used
to sign the JWT token that OpenAM uses to track end users during User Self-Service operations.",
            "propertyOrder" : 10,

```

```

    "required" : true,
    "type" : "string",
    "exampleValue" : "selfservicesigntest"
  },
  "minimumAnswersToDefine" : {
    "title" : "Minimum Answers to Define",
    "description" : "Specifies the minimum number of KBA answers that users must define.",
    "propertyOrder" : 60,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "captchaVerificationUrl" : {
    "title" : "Google Re-captcha Verification URL",
    "description" : "Google reCAPTCHA plugin verification URL.",
    "propertyOrder" : 40,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "captchaSecretKey" : {
    "title" : "Google reCAPTCHA Secret Key",
    "description" : "Google reCAPTCHA plugin secret key.",
    "propertyOrder" : 30,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "encryptionKeyPairAlias" : {
    "title" : "Encryption Key Pair Alias",
    "description" : "An encryption key alias in the OpenAM server's JCEKS keystore. Used to
encrypt the JWT token that OpenAM uses to track end users during User Self-Service operations.",
    "propertyOrder" : 0,
    "required" : true,
    "type" : "string",
    "exampleValue" : "selfserviceenctest"
  },
  "validQueryAttributes" : {
    "title" : "Valid Query Attributes",
    "description" : "Specifies the valid query attributes used to search for the user.
This is a list of attributes used to identify your account for forgotten password and forgotten
username.",
    "propertyOrder" : 80,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "captchaSiteKey" : {
    "title" : "Google reCAPTCHA Site Key",
    "description" : "Google reCAPTCHA plugin site key.",
    "propertyOrder" : 20,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "kbaQuestions" : {

```

```

        "title" : "Security Questions",
        "description" : "Specifies the default set of knowledge-based authentication (KBA)
security questions. The security questions can be set for the User Self-Registration, forgotten
password reset, and forgotten username services, respectively.<p><p>Format is <code>unique key|
locale|question</code>.",
        "propertyOrder" : 50,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    }
},
"advancedConfig" : {
    "type" : "object",
    "title" : "Advanced Configuration",
    "propertyOrder" : 5,
    "properties" : {
        "forgottenPasswordServiceConfigClass" : {
            "title" : "Forgotten Password Service Config Provider Class",
            "description" : "Specifies the provider class to configure any custom plugins.",
            "propertyOrder" : 360,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "forgottenPasswordConfirmationUrl" : {
            "title" : "Forgotten Password Confirmation Email URL",
            "description" : "Specifies the confirmation URL that the user receives after confirming
their identity during the forgotten password process. The <code>${realm}</code> string is replaced
with the current realm.",
            "propertyOrder" : 340,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "userRegistrationServiceConfigClass" : {
            "title" : "User Registration Service Config Provider Class",
            "description" : "Specifies the provider class to configure any custom plugins.",
            "propertyOrder" : 350,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "userRegistrationConfirmationUrl" : {
            "title" : "User Registration Confirmation Email URL",
            "description" : "Specifies the confirmation URL that the user receives during the self-
registration process. The <code>${realm}</code> string is replaced with the current realm.",
            "propertyOrder" : 330,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "forgottenUsernameServiceConfigClass" : {
            "title" : "Forgotten Username Service Config Provider Class",
            "description" : "Specifies the provider class to configure any custom plugins.",
            "propertyOrder" : 370,

```



```

    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
},
"forgottenPassword" : {
  "type" : "object",
  "title" : "Forgotten Password",
  "propertyOrder" : 2,
  "properties" : {
    "forgottenPasswordCaptchaEnabled" : {
      "title" : "Captcha",
      "description" : "If enabled, users must pass a Google reCAPTCHA challenge during
password reset to mitigate against software bots.",
      "propertyOrder" : 180,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "forgottenPasswordEmailBody" : {
      "title" : "Outgoing Email Body",
      "description" : "Customize the forgotten password email body text. Format is
<code>locale|body text</code>.",
      "propertyOrder" : 230,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "forgottenPasswordTokenTTL" : {
      "title" : "Token Lifetime (seconds)",
      "description" : "Maximum lifetime for the token allowing forgotten password reset, in
seconds.<p><p>Specify a value from <code>0</code> to <code>2147483647</code>.",
      "propertyOrder" : 210,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "forgottenPasswordEnabled" : {
      "title" : "Forgotten Password",
      "description" : "If enabled, users can reset their forgotten password.",
      "propertyOrder" : 170,
      "required" : true,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "numberOfAttemptsEnforced" : {
      "title" : "Enforce password reset lockout",
      "description" : "If enabled, users will be prevented from resetting their password after
the configured number of failed attempts.",
      "propertyOrder" : 201,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "forgottenPasswordEmailSubject" : {

```

```

        "title" : "Outgoing Email Subject",
        "description" : "Customize the forgotten password email subject text. Format is
<code>locale|subject text</code>.",
        "propertyOrder" : 220,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "forgottenPasswordKbaEnabled" : {
        "title" : "Security Questions",
        "description" : "If enabled, users must answer their security questions during the
forgotten password process.",
        "propertyOrder" : 200,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "forgottenPasswordEmailVerificationEnabled" : {
        "title" : "Email Verification",
        "description" : "If enabled, users who reset passwords must perform email address
verification.",
        "propertyOrder" : 190,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "numberOfAllowedAttempts" : {
        "title" : "Lock Out After number of attempts",
        "description" : "Can be set to 1 or more attempts for a user to correctly answer all
their security questions. After the number of configured attempts the user has not correctly answered
them the password reset feature will be disabled.",
        "propertyOrder" : 202,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    }
}
},
"profileManagement" : {
    "type" : "object",
    "title" : "Profile Management",
    "propertyOrder" : 4,
    "properties" : {
        "profileProtectedUserAttributes" : {
            "title" : "Protected Update Attributes",
            "description" : "Specifies a profile's protected user attributes, which causes re-
authentication when the user attempts to modify these attributes.",
            "propertyOrder" : 320,
            "required" : false,
            "items" : {
                "type" : "string"
            },
            "type" : "array",
            "exampleValue" : ""
        }
    }
}
}

```

```
    },  
    "type" : "object",  
    "title" : "Realm Defaults"  
  }  
}
```

1.211. UserServices

1.211.1. Realm Operations

Resource path: `/users/{user}/services`

Resource version: `1.0`

1.211.1.1. create

Usage:

```
am> create UserServices --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "type" : "object"  
}
```

1.211.1.2. delete

Usage:

```
am> delete UserServices --realm Realm
```

1.211.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action UserServices --realm Realm --user user --actionName getAllTypes
```

Parameters:

--user

1.211.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action UserServices --realm Realm --user user --actionName getCreatableTypes
```

Parameters:

--user

1.211.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action UserServices --realm Realm --user user --actionName nextdescendents
```

Parameters:

--user

1.211.1.6. read

Usage:

```
am> read UserServices --realm Realm
```

1.211.1.7. unassignServices

action.unassignServices.description

Usage:

```
am> action UserServices --realm Realm --body body --user user --actionName unassignServices
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "description" : "i18n:api-descriptor/UserServicesResource#schema.description",
  "type" : "object",
  "title" : "i18n:api-descriptor/UserServicesResource#schema.title",
  "properties" : {
    "serviceNames" : {
      "type" : "array",
      "title" : "i18n:api-descriptor/UserServicesResource#schema.servicename.title",
      "description" : "i18n:api-descriptor/UserServicesResource#schema.servicename.description",
      "items" : {
        "type" : "string"
      }
    }
  }
}
```

--user

1.211.1.8. update

Usage:

```
am> update UserServices --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object"
}
```

1.212. UsernameCollector

1.212.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/UsernameCollectorNode`

Resource version: `1.0`

1.212.1.1. create

Usage:

```
am> create UsernameCollector --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "required" : [ ]
}
```

1.212.1.2. delete

Usage:

```
am> delete UsernameCollector --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.212.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action UsernameCollector --realm Realm --actionName getAllTypes
```

1.212.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action UsernameCollector --realm Realm --actionName getCreatableTypes
```

1.212.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action UsernameCollector --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "title" : "Some configuration of the node. This does not need to be complete against the
configuration schema."
}
```

1.212.1.6. nextdescendants

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action UsernameCollector --realm Realm --actionName nextdescendants
```

1.212.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query UsernameCollector --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.212.1.8. read

Usage:

```
am> read UsernameCollector --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.212.1.9. update

Usage:

```
am> update UsernameCollector --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "required" : [ ]
}
```

1.213. ValidationService

1.213.1. Realm Operations

Resource path: [/realm-config/services/validation](#)

Resource version: [1.0](#)

1.213.1.1. create

Usage:

```
am> create ValidationService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "validGotoDestinations" : {
      "title" : "Valid goto URL Resources",
      "description" : "List of valid goto URL resources.<br><br>OpenAM's default behavior after login or logout is to redirect the user to the URL specified in the <code>goto</code> or <code>gotoOnFail</code> query string parameters supplied to the authentication interface during login or logout. <p><p>To enhance security, a list of valid URL resources can be specified here so OpenAM can validate the <code>goto</code> and <code>gotoOnFail</code> URL against them. <p><p>OpenAM will only redirect a user after login or logout if the URL matches any of the resources specified in this property. If the URL does not match, the user is redirected to either the user profile page or administration console after login, or the logged out page after logout. If this property is not set, it is assumed that all redirect URLs are valid.<p><p>The resources defined here can have the <code>*</code> wildcard defined, which matches all characters except <code>?</code>. Example values for this setting:<ul><li><code>http://app.example.com:80/*</code></li><li><code>http://app.example.com:80/*?*</code></li></ul>",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.213.1.2. delete

Usage:

```
am> delete ValidationService --realm Realm
```

1.213.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ValidationService --realm Realm --actionName getAllTypes
```

1.213.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ValidationService --realm Realm --actionName getCreatableTypes
```

1.213.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ValidationService --realm Realm --actionName nextdescendents
```

1.213.1.6. read

Usage:

```
am> read ValidationService --realm Realm
```

1.213.1.7. update

Usage:

```
am> update ValidationService --realm Realm --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "validGotoDestinations" : {
      "title" : "Valid goto URL Resources",
      "description" : "List of valid goto URL resources.<br><br>OpenAM's default behavior after login or logout is to redirect the user to the URL specified in the <code>goto</code> or <code>gotoOnFail</code> query string parameters supplied to the authentication interface during login or logout. <p><p>To enhance security, a list of valid URL resources can be specified here so OpenAM can validate the <code>goto</code> and <code>gotoOnFail</code> URL against them. <p><p>OpenAM will only redirect a user after login or logout if the URL matches any of the resources specified in this property. If the URL does not match, the user is redirected to either the user profile page or administration console after login, or the logged out page after logout. If this property is not set, it is assumed that all redirect URLs are valid.<p><p>The resources defined here can have the <code>*</code> wildcard defined, which matches all characters except <code>?</code>. Example values for this setting:<ul><li><code>http://app.example.com:80/*</code></li><li><code>http://app.example.com:80/*?*</code></li></ul>",
      "propertyOrder" : 100,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    }
  }
}
```

1.213.2. Global Operations

Resource path: `/global-config/services/validation`

Resource version: `1.0`

1.213.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ValidationService --global --actionName getAllTypes
```

1.213.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ValidationService --global --actionName getCreatableTypes
```

1.213.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ValidationService --global --actionName nextdescendents
```

1.213.2.4. read

Usage:

```
am> read ValidationService --global
```

1.213.2.5. update

Usage:

```
am> update ValidationService --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "validGotoDestinations" : {
          "title" : "Valid goto URL Resources",
          "description" : "List of valid goto URL resources.<br><br>OpenAM's default behavior after login or logout is to redirect the user to the URL specified in the <code>goto</code> or <code>gotoOnFail</code> query string parameters supplied to the authentication interface during login or logout. <p><p>To enhance security, a list of valid URL resources can be specified here so OpenAM can validate the <code>goto</code> and <code>gotoOnFail</code> URL against them. <p><p>OpenAM will only redirect a user after login or logout if the URL matches any of the resources specified in this property. If the URL does not match, the user is redirected to either the user profile page or administration console after login, or the logged out page after logout. If this property is not set, it is assumed that all redirect URLs are valid.<p><p>The resources defined here can have the <code>*</code> wildcard defined, which matches all characters except <code>?</code>. Example values for this setting:<ul><li><code>http://app.example.com:80/*</code></li><li><code>http://app.example.com:80/*?*</code></li></ul>",
          "propertyOrder" : 100,
          "required" : true,
          "items" : {
            "type" : "string"
          },
          "type" : "array",
          "exampleValue" : ""
        }
      },
      "type" : "object",
      "title" : "Realm Defaults"
    }
  }
}

```

1.214. WebAgentGroups

1.214.1. Realm Operations

Agent Groups handler that is responsible for managing agent groups

Resource path: [/realm-config/agents/groups/WebAgent](#)

Resource version: **1.0**

1.214.1.1. create

Usage:

```
am> create WebAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "amServicesWebAgent" : {
      "type" : "object",
      "title" : "AM Services",
      "propertyOrder" : 3,
      "properties" : {
        "policyEvaluationApplication" : {
          "title" : "Application",
          "description" : "Which application contains the policies to evaluate with (property name: org.forgerock.openam.agents.config.policy.evaluation.application) <br>Hot-swap: Yes",
          "propertyOrder" : 31400,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "fetchPoliciesFromRootResource" : {
          "title" : "Fetch Policies from Root Resource",
          "description" : "Agent caches policy decision of the resource and all resources from the root of the resource down. (property name: com.sun.identity.agents.config.fetch.from.root.resource) <br>Hot-swap: No",
          "propertyOrder" : 31000,
          "required" : false,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "userIdParameter" : {
          "title" : "User ID Parameter",
          "description" : "Agent sets value of User Id to REMOTE_USER server variable. (property name: com.sun.identity.agents.config.userid.param) <br>Hot-swap: Yes",
          "propertyOrder" : 30800,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "policyClockSkew" : {
          "title" : "Policy Clock Skew",
          "description" : "Time in seconds used adjust time difference between Agent machine and AM. Clock skew in seconds = AgentTime - AMServerTime. (property name: com.sun.identity.agents.config.policy.clock.skew) <br>Hot-swap: No",
          "propertyOrder" : 31200,
          "required" : false,
          "type" : "integer",
          "exampleValue" : ""
        },
        "policyEvaluationRealm" : {
          "title" : "Realm",
          "description" : "Which realm to start evaluating from (property name: org.forgerock.openam.agents.config.policy.evaluation.realm) <br>Hot-swap: Yes",
          "propertyOrder" : 31300,

```

```
"required" : false,
"type" : "string",
"exampleValue" : ""
},
"agentConnectionTimeout" : {
"title" : "Agent Connection Timeout",
"description" : "Timeout period in seconds for an agent connection with AM auth server.
(property name: com.sun.identity.agents.config.auth.connection.timeout) <br>Hot-swap: Yes",
"propertyOrder" : 30000,
"required" : false,
"type" : "integer",
"exampleValue" : ""
},
"policyCachePollingInterval" : {
"title" : "Policy Cache Polling Period",
"description" : "Polling interval in minutes to refresh agent's policy cache. (property
name: com.sun.identity.agents.config.policy.cache.polling.interval) <br>Hot-swap: No",
"propertyOrder" : 30600,
"required" : false,
"type" : "integer",
"exampleValue" : ""
},
"retrieveClientHostname" : {
"title" : "Retrieve Client Hostname",
"description" : "Gets the client's hostname through DNS reverse lookup for use in policy
evaluation. (property name: com.sun.identity.agents.config.get.client.host.name) <br>Hot-swap: Yes",
"propertyOrder" : 31100,
"required" : false,
"type" : "boolean",
"exampleValue" : ""
},
"logoutResetCookies" : {
"title" : "Logout Cookies List for Reset",
"description" : "Any cookies to be reset upon logout in the same format as cookie reset
list. (property name: com.sun.identity.agents.config.logout.cookie.reset) <br>Hot-swap: Yes <br>
Cookie1 <br> Cookie2=value;Domain=subdomain.domain.com",
"propertyOrder" : 30400,
"required" : false,
"items" : {
"type" : "string"
},
"type" : "array",
"exampleValue" : ""
},
"ssoCachePollingInterval" : {
"title" : "SSO Cache Polling Period",
"description" : "Polling interval in minutes to refresh agent's sso cache. (property name:
com.sun.identity.agents.config.sso.cache.polling.interval) <br>Hot-swap: No",
"propertyOrder" : 30700,
"required" : false,
"type" : "integer",
"exampleValue" : ""
},
"userIdParameterType" : {
"title" : "User ID Parameter Type",
"description" : "User ID can be fetched from either SESSION and LDAP attributes. (property
name: com.sun.identity.agents.config.userid.param.type) <br>Hot-swap: Yes",
"propertyOrder" : 30900,
"required" : false,
```

```

        "type" : "string",
        "exampleValue" : ""
    },
    "primaryServerPollingPeriod" : {
        "title" : "Polling Period for Primary Server",
        "description" : "Interval in minutes, agent polls to check the primary server is up and
running. (property name: com.sun.identity.agents.config.poll.primary.server) <br>Hot-swap: No",
        "propertyOrder" : 30100,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    },
    "applicationLogoutUrls" : {
        "title" : "Logout URL List",
        "description" : "List of application logout URLs. User gets logged out from AM session
when these urls accessed. (property name: com.sun.identity.agents.config.agent.logout.url). If this
property is used, user should specify a value for the below Logout Redirect URL property.<br>Hot-
swap: Yes <br> Example: <br> http://myagent.mydomain.com/logout.html",
        "propertyOrder" : 30300,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    },
    "amLoginUrl" : {
        "title" : "AM Login URL",
        "description" : "AM login page URL. (property name:
com.sun.identity.agents.config.login.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Login",
        "propertyOrder" : 29900,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    },
    "amLogoutUrl" : {
        "title" : "AM Logout URL",
        "description" : "AM logout page URL. (property name:
com.sun.identity.agents.config.logout.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Logout",
        "propertyOrder" : 30200,
        "required" : false,
        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    },
    "logoutRedirectUrl" : {
        "title" : "Logout Redirect URL",
        "description" : "User gets redirected to this url after logout. (property name:
com.sun.identity.agents.config.logout.redirect.url). This property should be specified along with the
above Logout URL List.<br>Hot-swap: Yes",
        "propertyOrder" : 30500,
        "required" : false,
    }
}

```

```

        "type" : "string",
        "exampleValue" : ""
    }
},
"globalWebAgentConfig" : {
    "type" : "object",
    "title" : "Global",
    "propertyOrder" : 0,
    "properties" : {
        "fqdnMapping" : {
            "title" : "FQDN Virtual Host Map",
            "description" : "Maps virtual, invalid, or partial hostnames, and IP addresses to the FQDN
to access protected resources. (property name: com.sun.identity.agents.config.fqdn.mapping) <br>Hot-
swap: Yes <br> Examples: <br> To map the partial hostname myserver to myserver.mydomain.com: enter
myserver in the Map Key field and myserver.mydomain.com in the Corresponding Map Value field. To map
a virtual server rst.hostname.com that points to the actual server abc.hostname.com: enter valid1
in the Map Key field and rst.hostname.com in the Corresponding Map Value field.",
            "propertyOrder" : 27500,
            "required" : false,
            "patternProperties" : {
                ".*" : {
                    "type" : "string"
                }
            },
            "type" : "object",
            "exampleValue" : ""
        },
        "localAuditLogRotation" : {
            "title" : "Rotate Local Audit Log",
            "description" : "Flag to indicate that audit log files should be rotated when reaching a
certain size. (property name: com.sun.identity.agents.config.local.log.rotate) <br>Hot-swap: Yes",
            "propertyOrder" : 27100,
            "required" : false,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "fqdnDefault" : {
            "title" : "FQDN Default",
            "description" : "Fully qualified hostname that the users should use in order to access
resources. (property name: com.sun.identity.agents.config.fqdn.default) <br>Hot-swap: Yes",
            "propertyOrder" : 27400,
            "required" : false,
            "type" : "string",
            "exampleValue" : ""
        },
        "agentConfigChangeNotificationsEnabled" : {
            "title" : "Agent Configuration Change Notification",
            "description" : "Enable agent to receive notification messages from AM server for
configuration changes. (property name: com.sun.identity.agents.config.change.notification.enable)
<br>Hot-swap: Yes",
            "propertyOrder" : 25300,
            "required" : false,
            "type" : "boolean",
            "exampleValue" : ""
        },
        "debugLogRotation" : {
            "title" : "Agent Debug File Rotation",

```



```

        "description" : "Debug file gets rotated based on the size specified. (property name:
com.sun.identity.agents.config.debug.file.rotate) <br>Hot-swap: Yes",
        "propertyOrder" : 26500,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "agentUriPrefix" : {
        "title" : "Agent Deployment URI Prefix",
        "description" : "(property name: com.sun.identity.agents.config.agenturi.prefix)<br>Hot-
swap: Yes",
        "propertyOrder" : 25800,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "agentNotificationUrl" : {
        "title" : "Agent Notification URL",
        "description" : "(Not used in Agent 5 onwards) <br>URL used by agent to register
notification listeners. (property name: com.sun.identity.client.notification.url) <br>Hot-swap: No",
        "propertyOrder" : 25700,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "debugRotationSize" : {
        "title" : "Agent Debug File Size",
        "description" : "Agent debug file size in bytes. (property name:
com.sun.identity.agents.config.debug.file.size) <br>Hot-swap: Yes",
        "propertyOrder" : 26600,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "accessDeniedUrl" : {
        "title" : "Resources Access Denied URL",
        "description" : "The URL of the customized access denied page. (property name:
com.sun.identity.agents.config.access.denied.url) <br>Hot-swap: Yes",
        "propertyOrder" : 26300,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "status" : {
        "title" : "Status",
        "description" : "Status of the agent configuration.",
        "propertyOrder" : 25100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "configurationPollingInterval" : {
        "title" : "Configuration Reload Interval",
        "description" : "Interval in minutes to fetch agent configuration from AM. (property name:
com.sun.identity.agents.config.polling.interval) <br>Hot-swap: No",
        "propertyOrder" : 25900,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    }

```

```
    },
    "auditAccessType" : {
      "title" : "Audit Access Types",
      "description" : "Types of messages to log based on user URL access attempts. (property name:
com.sun.identity.agents.config.audit.accesstype) <br>Hot-swap: Yes",
      "propertyOrder" : 26700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "websocketConnectionIntervalInMinutes" : {
      "title" : "Web Socket Connection Interval",
      "description" : "Interval in minutes by which agents reopen their web socket connection to
ensure a fair distribution of connections across AM servers. (Agent 5 only).",
      "propertyOrder" : 25400,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    "cdssoRootUrl" : {
      "title" : "Agent Root URL for CDSO",
      "description" : "The agent root URL for CDSO. The valid value is in the following format:
<br>protocol://hostname:port/<br> The protocol represents the protocol used, such as http or https.
The hostname represents the host name of the machine on which the agent resides. The port represents
the port number on which the agent is installed. The slash following the port number is required.",
      "propertyOrder" : 26100,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "auditLogLocation" : {
      "title" : "Audit Log Location",
      "description" : "Specifies where audit messages should be logged. (property name:
com.sun.identity.agents.config.log.disposition) <br>Hot-swap: Yes",
      "propertyOrder" : 26800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "ssoOnlyMode" : {
      "title" : "SSO Only Mode",
      "description" : "Agent will just enforce authentication (SSO), but no authorization for
policies. (property name: com.sun.identity.agents.config.sso.only) <br>Hot-swap: Yes",
      "propertyOrder" : 26200,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "jwtName" : {
      "title" : "JWT Cookie Name",
      "description" : "The name used by the agent to set the OIDC JWT on the user's browser.
(Agent 5 only).",
      "propertyOrder" : 25500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

```

    },
    "localAuditRotationSize" : {
      "title" : "Local Audit Log Rotation Size",
      "description" : "Size limit in bytes when a local audit log file is rotated to a new file.
(property name: com.sun.identity.agents.config.local.log.size) <br>Hot-swap: Yes",
      "propertyOrder" : 27200,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    },
    "configurationCleanupInterval" : {
      "title" : "Configuration Cleanup Interval",
      "description" : "Interval in minutes to cleanup old agent configuration entries. (property
name: com.sun.identity.agents.config.cleanup.interval) <br>Hot-swap: No",
      "propertyOrder" : 26000,
      "required" : false,
      "type" : "integer",
      "exampleValue" : ""
    },
    },
    "remoteLogFilename" : {
      "title" : "Remote Log Filename",
      "description" : "(Not used in Agent 5 onwards) <br>Name of file stored on AM server that
contains agent audit messages. (property name: com.sun.identity.agents.config.remote.logfile)
<br>Hot-swap: No",
      "propertyOrder" : 26900,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "notificationsEnabled" : {
      "title" : "Enable Notifications",
      "description" : "The notifications help in maintaining agent's sso, policy and configuration
caches. (property name: com.sun.identity.agents.config.notification.enable) <br>Hot-swap: No",
      "propertyOrder" : 25600,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    },
    "agentDebugLevel" : {
      "title" : "Agent Debug Level",
      "description" : "Agent debug level. (property name:
com.sun.identity.agents.config.debug.level) <br>Hot-swap: Yes",
      "propertyOrder" : 26400,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    },
    "fqdnCheck" : {
      "title" : "FQDN Check",
      "description" : "Enables checking of fqdn default value and fqdn map values. (property name:
com.sun.identity.agents.config.fqdn.check.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 27300,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    },
    "remoteLogSendInterval" : {
      "title" : "Remote Audit Log Interval",

```

```

    "description" : "Periodic interval in minutes in which audit log messages are sent to remote
log file. (property name: com.sun.identity.agents.config.remote.log.interval) <br>Hot-swap: No",
    "propertyOrder" : 27000,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  }
},
"advancedWebAgentConfig" : {
  "type" : "object",
  "title" : "Advanced",
  "propertyOrder" : 5,
  "properties" : {
    "clientIpHeader" : {
      "title" : "Client IP Address Header",
      "description" : "HTTP header name that holds the IP address of the client. (property name:
com.sun.identity.agents.config.client.ip.header) <br>Hot-swap: Yes",
      "propertyOrder" : 32800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "useLtpaToken" : {
      "title" : "Use LTPA token",
      "description" : "Set to true if agent needs to use LTPA Token. (property name:
com.sun.identity.agents.config.domino.ltpa.enable)",
      "propertyOrder" : 34700,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "changeProtocolToHttps" : {
      "title" : "Change URL Protocol to https",
      "description" : "If true, avoids IE6 security pop-ups. (property name:
com.sun.identity.agents.config.iis.owa.enable.change.protocol)",
      "propertyOrder" : 34200,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "overrideRequestHost" : {
      "title" : "Override Request URL Host",
      "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the host with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.host) <br>Hot-swap: Yes",
      "propertyOrder" : 33200,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "overrideRequestPort" : {
      "title" : "Override Request URL Port",
      "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the port with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.port) <br>Hot-swap: Yes",
      "propertyOrder" : 33300,

```

```

    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ltpaTokenOrganizationName" : {
    "title" : "LTPA Token Organization Name",
    "description" : "The organization name to which the LTPA token belongs. (property name:
com.sun.identity.agents.config.domino.ltpa.org.name)",
    "propertyOrder" : 35000,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "loadBalanced" : {
    "title" : "Load Balancer Setup",
    "description" : "Set to true if a load balancer is used for AM services. (property name:
com.sun.identity.agents.config.load.balancer.enable) <br>Hot-swap: No",
    "propertyOrder" : 33000,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "overrideNotificationUrl" : {
    "title" : "Override Notification URL",
    "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the URL with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.notification.url) <br>Hot-swap: Yes",
    "propertyOrder" : 33400,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "filterConfiguredWithOwa" : {
    "title" : "Filter configured with OWA",
    "description" : "Set to true if the IIS agent filter is configured for OWA. (property name:
com.sun.identity.agents.config.iis.owa.enable)",
    "propertyOrder" : 34100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "ltpaTokenConfigurationname" : {
    "title" : "LTPA Token Configuration Name",
    "description" : "The configuration name that the agent uses in order to employ the LTPA
token mechanism. (property name: com.sun.identity.agents.config.domino.ltpa.config.name)",
    "propertyOrder" : 34900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "idleSessionTimeoutUrl" : {
    "title" : "Idle Session Timeout Page URL",
    "description" : "URL of the local idle session timeout page. (property name:
com.sun.identity.agents.config.iis.owa.enable.session.timeout.url)",
    "propertyOrder" : 34300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }

```

```

    },
    "overrideProxyHostAndPort" : {
        "title" : "Override Proxy Server's Host and Port",
        "description" : "(property name: com.sun.identity.agents.config.proxy.override.host.port)
<br>Hot-swap: No",
        "propertyOrder" : 33700,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "postDataCachePeriod" : {
        "title" : "POST Data Entries Cache Period",
        "description" : "POST cache entry lifetime in minutes. (property name:
com.sun.identity.agents.config.postcache.entry.lifetime) <br>Hot-swap: Yes",
        "propertyOrder" : 33600,
        "required" : false,
        "type" : "integer",
        "exampleValue" : ""
    },
    "overrideRequestProtocol" : {
        "title" : "Override Request URL Protocol",
        "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the protocol with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.protocol) <br>Hot-swap: Yes",
        "propertyOrder" : 33100,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "checkUserInDomino" : {
        "title" : "Check User in Domino Database",
        "description" : "If true, agent checks user existence in Domino name database. (property
name: com.sun.identity.agents.config.domino.check.name.database)",
        "propertyOrder" : 34600,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "authenticationType" : {
        "title" : "Authentication Type",
        "description" : "(property name: com.sun.identity.agents.config.iis.auth.type)",
        "propertyOrder" : 33800,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "clientHostnameHeader" : {
        "title" : "Client Hostname Header",
        "description" : "HTTP header name that holds the Hostname of the client. (property name:
com.sun.identity.agents.config.client.hostname.header) <br>Hot-swap: Yes",
        "propertyOrder" : 32900,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "logonAndImpersonation" : {
        "title" : "Logon and Impersonation",
    }

```

```

        "description" : "Set to true if agent should do Windows Logon and User Impersonation.
(property name: com.sun.identity.agents.config.iis.logonuser)",
        "propertyOrder" : 34500,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "filterPriority" : {
        "title" : "Filter Priority",
        "description" : "The loading priority of filter. (property name:
com.sun.identity.agents.config.iis.filter.priority)",
        "propertyOrder" : 34000,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "ltpaTokenCookieName" : {
        "title" : "LTPA Token Cookie Name",
        "description" : "The name of the cookie that contains the LTPA token. (property name:
com.sun.identity.agents.config.domino.ltpa.cookie.name)",
        "propertyOrder" : 34800,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "showPasswordInHeader" : {
        "title" : "Show Password in HTTP Header",
        "description" : "Set to true if encrypted password should be set in HTTP header
AUTH_PASSWORD. (property name: com.sun.identity.agents.config.iis.password.header)",
        "propertyOrder" : 34400,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "postDataPreservation" : {
        "title" : "POST Data Preservation",
        "description" : "Enables POST data preservation. (property name:
com.sun.identity.agents.config.postdata.preserve.enable) <br> Note that this feature is not supported
in all the web agents. Please refer individual agents documentation for more details. <br>Hot-swap:
Yes",
        "propertyOrder" : 33500,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "replayPasswordKey" : {
        "title" : "Replay Password Key",
        "description" : "DES key for decrypting the basic authentication password in the session.
(property name: com.sun.identity.agents.config.replaypasswd.key)",
        "propertyOrder" : 33900,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "customProperties" : {
        "title" : "Custom Properties",
        "description" : "Additional properties that allow users to augment the set of properties
supported by agent. (property name: com.sun.identity.agents.config.freeformproperties) <br>Hot-
swap: Yes <br> Examples: <br> customproperty=custom-value1 <br> customlist[0]=customlist-
    
```

```

value-0 <br> customlist[1]=customlist-value-1 <br> custommap[key1]=custommap-value-1 <br>
  custommap[key2]=custommap-value-2",
  "propertyOrder" : 35100,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
}
},
"miscWebAgentConfig" : {
  "type" : "object",
  "title" : "Miscellaneous",
  "propertyOrder" : 4,
  "properties" : {
    "gotoParameterName" : {
      "title" : "Goto Parameter Name",
      "description" : "Property used only when CDSSO is enabled. Default value
should be changed only when the login URL has a landing page specified <br> Example :
com.sun.identity.agents.config.cdssso.cdcservlet.url = http://host:port/opensso/cdcservlet?
goto=http://agent:port/landing.jsp <br> The parameter is used by the Agent to append the original
request URL to this cdcservlet URL. This parameter is consumed by the landing page to redirect to
the original URL. (property name: com.sun.identity.agents.config.redirect.param) <br>Hot-swap: Yes
<br> Example: com.sun.identity.agents.config.redirect.param = goto2<br> The complete URL sent for
authentication will be <br> http://host:port/opensso/cdcservlet?goto=http://agent:port/landing.jsp?
goto2=http://agent.port/original.jsp",
      "propertyOrder" : 32600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "ignoreServerCheck" : {
      "title" : "Ignore Server Check",
      "description" : "Agent uses this value to check AM is up before doing a 302 redirect.
(property name: com.sun.identity.agents.config.ignore.server.check) <br>Hot-swap: Yes",
      "propertyOrder" : 32300,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "profileAttributesCookiePrefix" : {
      "title" : "Profile Attributes Cookie Prefix",
      "description" : "Sets cookie prefix in the attributes headers. (property name:
com.sun.identity.agents.config.profile.attribute.cookie.prefix) <br>Hot-swap: Yes",
      "propertyOrder" : 31800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "ignorePreferredNamingUrl" : {
      "title" : "Ignore Preferred Naming URL in Naming Request",
      "description" : "Agent uses this value to send preferred naming url in the naming request.
(property name: com.sun.identity.agents.config.ignore.preferred.naming.url) <br>Hot-swap: Yes",
      "propertyOrder" : 32200,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}

```



```
    },
    "agentLocale" : {
      "title" : "Agent Locale",
      "description" : "The default locale for the product. (property name:
com.sun.identity.agents.config.locale) <br>Hot-swap: No",
      "propertyOrder" : 31500,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "caseInsensitiveUrlComparison" : {
      "title" : "URL Comparison Case Sensitivity Check",
      "description" : "Enforces case insensitivity in both policy and not enforced url evaluation.
(property name: com.sun.identity.agents.config.url.comparison.case.ignore) <br>Hot-swap: Yes",
      "propertyOrder" : 32000,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "encodeProfileAttributes" : {
      "title" : "Native Encoding of Profile Attributes",
      "description" : "Agent encodes the ldap header values in the default encoding of OS locale.
If false, UTF-8 gets used. (property name: com.sun.identity.agents.config.convert.mbyte.enable)
<br>Hot-swap: Yes",
      "propertyOrder" : 32500,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "anonymousUserId" : {
      "title" : "Anonymous User Default Value",
      "description" : "User id of unauthenticated users. (property name:
com.sun.identity.agents.config.anonymous.user.id) <br>Hot-swap: Yes",
      "propertyOrder" : 32700,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "ignorePathInfo" : {
      "title" : "Ignore Path Info in Request URL",
      "description" : "The path info will be stripped from the request URL while doing Not
Enforced List check and url policy evaluation if the value is set to true. (property name:
com.sun.identity.agents.config.ignore.path.info) <br>Hot-swap: Yes",
      "propertyOrder" : 32400,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "encodeSpecialCharsInCookies" : {
      "title" : "Encode special chars in Cookies",
      "description" : "Encode special chars in cookie by URL encoding. Useful when profile,
session and response attributes contain special chars and attributes fetch mode is set to
HTTP_COOKIE. (property name: com.sun.identity.agents.config.encode.cookie.special.chars.enable)
<br>Hot-swap: Yes",
      "propertyOrder" : 31700,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
  },
},
```

```

"encodeUrlSpecialCharacters" : {
  "title" : "Encode URL's Special Characters",
  "description" : "Encodes the url which has special characters before doing policy
evaluation. (property name: com.sun.identity.agents.config.encode.url.special.chars.enable) <br>Hot-
swap: Yes",
  "propertyOrder" : 32100,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"profileAttributesCookieMaxAge" : {
  "title" : "Profile Attributes Cookie Maxage",
  "description" : "Maxage of attributes cookie headers. (property name:
com.sun.identity.agents.config.profile.attribute.cookie.maxage) <br>Hot-swap: Yes",
  "propertyOrder" : 31900,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"anonymousUserEnabled" : {
  "title" : "Anonymous User",
  "description" : "Enable/Disable REMOTE_USER processing for anonymous users. (property name:
com.sun.identity.agents.config.anonymous.user.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 31600,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
}
}
},
"applicationWebAgentConfig" : {
  "type" : "object",
  "title" : "Application",
  "propertyOrder" : 1,
  "properties" : {
    "notEnforcedIps" : {
      "title" : "Not Enforced Client IP List",
      "description" : "No authentication and authorization are required for the requests coming
from these client IP addresses. (property name: com.sun.identity.agents.config.notenforced.ip)
<br>Hot-swap: Yes <br> Examples: <br> 192.18.145.* <br> 192.18.146.123",
      "propertyOrder" : 28000,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "invertNotEnforcedUrls" : {
      "title" : "Invert Not Enforced URLs",
      "description" : "Only not enforced list of urls will be enforced. (property name:
com.sun.identity.agents.config.notenforced.url.invert) <br>Hot-swap: Yes",
      "propertyOrder" : 27800,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "clientIpValidation" : {
      "title" : "Client IP Validation",

```

```

        "description" : "This validates if the subsequent browser requests come from
the same ip address that the SSO token is initially issued against. (property name:
com.sun.identity.agents.config.client.ip.validation.enable) <br>Hot-swap: Yes",
        "propertyOrder" : 28100,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "sessionAttributeMap" : {
        "title" : "Session Attribute Map",
        "description" : "Maps the session attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.session.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of session attribute UserToken under name CUSTOM-userid: enter UserToken in Map
Key field, and enter CUSTOM-userid in Corresponding Map Value field.",
        "propertyOrder" : 28700,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "continuousSecurityHeaders" : {
        "title" : "Continuous Security Headers",
        "description" : "The name of the headers in the user's original request, that will be sent
as part of the payload during policy evaluation, which can then be accessed via the 'environment'
variable in a policy script. The 'key' is the name of the header to be sent, and the 'value' is the
name which it will appear as in the policy evaluation script.It is possible to map multiple headers
to the same name (they will simply appear as an array in the evaluation script). If the header
doesn't exist, then the empty string will be sent.",
        "propertyOrder" : 29000,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "responseAttributeFetchMode" : {
        "title" : "Response Attribute Fetch Mode",
        "description" : "(property name:
com.sun.identity.agents.config.response.attribute.fetch.mode) <br>Hot-swap: Yes",
        "propertyOrder" : 28400,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "notEnforcedUrls" : {
        "title" : "Not Enforced URLs",
        "description" : "List of urls for which no authentication required. (property name:
com.sun.identity.agents.config.notenforced.url) <br>Hot-swap: Yes <br> Example: <br> http://
myagent.mydomain.com/*.gif",
        "propertyOrder" : 27700,
        "required" : false,
    
```

```

        "items" : {
            "type" : "string"
        },
        "type" : "array",
        "exampleValue" : ""
    },
    "fetchAttributesForNotEnforcedUrls" : {
        "title" : "Fetch Attributes for Not Enforced URLs",
        "description" : "Agent fetches profile attributes for not enforced urls by doing policy
evaluation. (property name: com.sun.identity.agents.config.notenforced.url.attributes.enable)
<br>Hot-swap: Yes",
        "propertyOrder" : 27900,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "profileAttributeMap" : {
        "title" : "Profile Attribute Map",
        "description" : "Maps the profile attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.profile.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of profile attribute cn under name CUSTOM-Common-Name: enter cn in Map Key field,
and enter CUSTOM-Common-Name in Corresponding Map Value field. <br> To populate the value of profile
attribute mail under name CUSTOM-Email: enter mail in Map Key field, and enter CUSTOM-Email in
Corresponding Map Value field.",
        "propertyOrder" : 28300,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "responseAttributeMap" : {
        "title" : "Response Attribute Map",
        "description" : "Maps the policy response attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.response.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of response attribute uid under name CUSTOM-USER-NAME: enter uid in Map Key field,
and enter CUSTOM-USER-NAME in Corresponding Map Value field.",
        "propertyOrder" : 28500,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "profileAttributeFetchMode" : {
        "title" : "Profile Attribute Fetch Mode",
        "description" : "(property name:
com.sun.identity.agents.config.profile.attribute.fetch.mode) <br>Hot-swap: Yes",
        "propertyOrder" : 28200,
        "required" : false,
        "type" : "string",
    }

```

```

        "exampleValue" : ""
    },
    "sessionAttributeFetchMode" : {
        "title" : "Session Attribute Fetch Mode",
        "description" : "(property name:
com.sun.identity.agents.config.session.attribute.fetch.mode) <br>Hot-swap: Yes",
        "propertyOrder" : 28600,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "continuousSecurityCookies" : {
        "title" : "Continuous Security Cookies",
        "description" : "The name of the cookies to be sent as part of the payload during policy
evaluation, which can be accessed via the 'environment' variable in a policy script. The 'key' is
the name of the cookie to be sent, and the 'value' is the name which it will appear as in the policy
evaluation script. It is possible to map multiple cookies to the same name (they will simply appear
as an array in the evaluation script). If the cookie doesn't exist, then the empty string will be
sent.",
        "propertyOrder" : 28900,
        "required" : false,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : ""
    },
    "ignorePathInfoForNotEnforcedUrls" : {
        "title" : "Ignore Path Info for Not Enforced URLs",
        "description" : "Indicate whether the path info and query should be
stripped from the request URL before being compared with the URLs of the not
enforced list when those URLs have a wildcard '*' character. (property name:
com.sun.identity.agents.config.ignore.path.info.for.not.enforced.list) <br>Hot-swap: Yes",
        "propertyOrder" : 27600,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "attributeMultiValueSeparator" : {
        "title" : "Attribute Multi Value Separator",
        "description" : "Specifies separator for multiple values. Applies to all
types of attributes i.e. profile, session and response attributes. (property name:
com.sun.identity.agents.config.attribute.multi.value.separator) <br>Hot-swap: Yes",
        "propertyOrder" : 28800,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    }
}
},
"ssoWebAgentConfig" : {
    "type" : "object",
    "title" : "SSO",
    "propertyOrder" : 2,
    "properties" : {
        "cookieResetList" : {
            "title" : "Cookies Reset Name List",

```

```

    "description" : "List of cookies in the format: name[=value][;Domain=value]. (property name:
com.sun.identity.agents.config.cookie.reset) <br>Hot-swap: Yes <br> Examples: <br> Cookie1 <br>
Cookie2=value;Domain=subdomain.domain.com",
    "propertyOrder" : 29800,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "cookieResetEnabled" : {
    "title" : "Cookie Reset",
    "description" : "Agent reset cookies in the response before redirecting to authentication.
(property name: com.sun.identity.agents.config.cookie.reset.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 29700,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cdssoRedirectUri" : {
    "title" : "CDSSO Redirect URI",
    "description" : "An intermediate URI that is used by the Agent for processing CDSSO
requests. (property name: com.sun.identity.agents.config.cdsso.redirect.uri) <br>Hot-swap: Yes",
    "propertyOrder" : 29300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "cookieName" : {
    "title" : "Cookie Name",
    "description" : "Name of the SSO Token cookie used between the AM server and the Agent.
(property name: com.sun.identity.agents.config.cookie.name)<br>Hot-swap: No",
    "propertyOrder" : 29100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "secureCookies" : {
    "title" : "Cookie Security",
    "description" : "Agent sends secure cookies if communication is secure. (property name:
com.sun.identity.agents.config.cookie.secure) <br>Hot-swap: No",
    "propertyOrder" : 29200,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cdssoUrls" : {
    "title" : "CDSSO Servlet URL",
    "description" : "List of URLs of the available CDSSO controllers that may be used by the
Agent for CDSSO processing. (property name: com.sun.identity.agents.config.cdsso.cdcervlet.url)
<br>Hot-swap: Yes <br> Example: <br> http://host:port/opensso/cdcervlet",
    "propertyOrder" : 29500,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}

```

```
    },  
    "cdsso" : {  
      "title" : "Cross Domain SSO",  
      "description" : "Enables Cross-Domain Single Sign On. (property name:  
com.sun.identity.agents.config.cdsso.enable) <br>Hot-swap: Yes",  
      "propertyOrder" : 29400,  
      "required" : false,  
      "type" : "boolean",  
      "exampleValue" : ""  
    },  
    "cdssoCookieDomain" : {  
      "title" : "Cookies Domain List",  
      "description" : "List of domains in which cookies have to be set in CDSSO. (property name:  
com.sun.identity.agents.config.cdsso.cookie.domain) <br>Hot-swap: Yes <br> Example: <br> .sun.com",  
      "propertyOrder" : 29600,  
      "required" : false,  
      "items" : {  
        "type" : "string"  
      },  
      "type" : "array",  
      "exampleValue" : ""  
    }  
  }  
}  
}
```

1.214.1.2. delete

Usage:

```
am> delete WebAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.214.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action WebAgentGroups --realm Realm --actionName getAllTypes
```

1.214.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action WebAgentGroups --realm Realm --actionName getCreatableTypes
```

1.214.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action WebAgentGroups --realm Realm --actionName nextdescendents
```

1.214.1.6. query

Querying the agent groups of a specific type

Usage:

```
am> query WebAgentGroups --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.214.1.7. read

Usage:

```
am> read WebAgentGroups --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.214.1.8. update

Usage:

```
am> update WebAgentGroups --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```

{
  "type" : "object",
  "properties" : {
    "amServicesWebAgent" : {
      "type" : "object",
      "title" : "AM Services",
      "propertyOrder" : 3,
      "properties" : {
        "policyEvaluationApplication" : {
          "title" : "Application",
          "description" : "Which application contains the policies to evaluate with (property name:
org.forgerock.openam.agents.config.policy.evaluation.application) <br>Hot-swap: Yes",
          "propertyOrder" : 31400,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "fetchPoliciesFromRootResource" : {
          "title" : "Fetch Policies from Root Resource",
          "description" : "Agent caches policy decision of the resource and all resources from the
root of the resource down. (property name: com.sun.identity.agents.config.fetch.from.root.resource)
<br>Hot-swap: No",
          "propertyOrder" : 31000,
          "required" : false,
          "type" : "boolean",
          "exampleValue" : ""
        },
        "userIdParameter" : {
          "title" : "User ID Parameter",
          "description" : "Agent sets value of User Id to REMOTE_USER server variable. (property name:
com.sun.identity.agents.config.userid.param) <br>Hot-swap: Yes",
          "propertyOrder" : 30800,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        },
        "policyClockSkew" : {
          "title" : "Policy Clock Skew",
          "description" : "Time in seconds used adjust time difference between Agent
machine and AM. Clock skew in seconds = AgentTime - AMServerTime. (property name:
com.sun.identity.agents.config.policy.clock.skew) <br>Hot-swap: No",
          "propertyOrder" : 31200,
          "required" : false,
          "type" : "integer",
          "exampleValue" : ""
        },
        "policyEvaluationRealm" : {
          "title" : "Realm",
          "description" : "Which realm to start evaluating from (property name:
org.forgerock.openam.agents.config.policy.evaluation.realm) <br>Hot-swap: Yes",
          "propertyOrder" : 31300,
          "required" : false,
          "type" : "string",
          "exampleValue" : ""
        }
      }
    }
  }
}

```

```

"agentConnectionTimeout" : {
  "title" : "Agent Connection Timeout",
  "description" : "Timeout period in seconds for an agent connection with AM auth server.
(property name: com.sun.identity.agents.config.auth.connection.timeout) <br>Hot-swap: Yes",
  "propertyOrder" : 30000,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"policyCachePollingInterval" : {
  "title" : "Policy Cache Polling Period",
  "description" : "Polling interval in minutes to refresh agent's policy cache. (property
name: com.sun.identity.agents.config.policy.cache.polling.interval) <br>Hot-swap: No",
  "propertyOrder" : 30600,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"retrieveClientHostname" : {
  "title" : "Retrieve Client Hostname",
  "description" : "Gets the client's hostname through DNS reverse lookup for use in policy
evaluation. (property name: com.sun.identity.agents.config.get.client.host.name) <br>Hot-swap: Yes",
  "propertyOrder" : 31100,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"logoutResetCookies" : {
  "title" : "Logout Cookies List for Reset",
  "description" : "Any cookies to be reset upon logout in the same format as cookie reset
list. (property name: com.sun.identity.agents.config.logout.cookie.reset) <br>Hot-swap: Yes <br>
Cookie1 <br> Cookie2=value;Domain=subdomain.domain.com",
  "propertyOrder" : 30400,
  "required" : false,
  "items" : {
    "type" : "string"
  },
  "type" : "array",
  "exampleValue" : ""
},
"ssoCachePollingInterval" : {
  "title" : "SSO Cache Polling Period",
  "description" : "Polling interval in minutes to refresh agent's sso cache. (property name:
com.sun.identity.agents.config.sso.cache.polling.interval) <br>Hot-swap: No",
  "propertyOrder" : 30700,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"userIdParameterType" : {
  "title" : "User ID Parameter Type",
  "description" : "User ID can be fetched from either SESSION and LDAP attributes. (property
name: com.sun.identity.agents.config.userid.param.type) <br>Hot-swap: Yes",
  "propertyOrder" : 30900,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"primaryServerPollingPeriod" : {

```

```

    "title" : "Polling Period for Primary Server",
    "description" : "Interval in minutes, agent polls to check the primary server is up and
running. (property name: com.sun.identity.agents.config.poll.primary.server) <br>Hot-swap: No",
    "propertyOrder" : 30100,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "applicationLogoutUrls" : {
    "title" : "Logout URL List",
    "description" : "List of application logout URLs. User gets logged out from AM session
when these urls accessed. (property name: com.sun.identity.agents.config.agent.logout.url). If this
property is used, user should specify a value for the below Logout Redirect URL property.<br>Hot-
swap: Yes <br> Example: <br> http://myagent.mydomain.com/logout.html",
    "propertyOrder" : 30300,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "amLoginUrl" : {
    "title" : "AM Login URL",
    "description" : "AM login page URL. (property name:
com.sun.identity.agents.config.login.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Login",
    "propertyOrder" : 29900,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "amLogoutUrl" : {
    "title" : "AM Logout URL",
    "description" : "AM logout page URL. (property name:
com.sun.identity.agents.config.logout.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Logout",
    "propertyOrder" : 30200,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "logoutRedirectUrl" : {
    "title" : "Logout Redirect URL",
    "description" : "User gets redirected to this url after logout. (property name:
com.sun.identity.agents.config.logout.redirect.url). This property should be specified along with the
above Logout URL List.<br>Hot-swap: Yes",
    "propertyOrder" : 30500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}

```

```

    },
    "globalWebAgentConfig" : {
      "type" : "object",
      "title" : "Global",
      "propertyOrder" : 0,
      "properties" : {
        "fqdnMapping" : {
          "title" : "FQDN Virtual Host Map",
          "description" : "Maps virtual, invalid, or partial hostnames, and IP addresses to the FQDN
to access protected resources. (property name: com.sun.identity.agents.config.fqdn.mapping) <br>Hot-
swap: Yes <br> Examples: <br> To map the partial hostname myserver to myserver.mydomain.com: enter
myserver in the Map Key field and myserver.mydomain.com in the Corresponding Map Value field. To map
a virtual server rst.hostname.com that points to the actual server abc.hostname.com: enter valid1 in
the Map Key field and rst.hostname.com in the Corresponding Map Value field.",
          "propertyOrder" : 27500,
          "required" : false,
          "patternProperties" : {
            ".*" : {
              "type" : "string"
            }
          }
        },
        "type" : "object",
        "exampleValue" : ""
      }
    },
    "localAuditLogRotation" : {
      "title" : "Rotate Local Audit Log",
      "description" : "Flag to indicate that audit log files should be rotated when reaching a
certain size. (property name: com.sun.identity.agents.config.local.log.rotate) <br>Hot-swap: Yes",
      "propertyOrder" : 27100,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "fqdnDefault" : {
      "title" : "FQDN Default",
      "description" : "Fully qualified hostname that the users should use in order to access
resources. (property name: com.sun.identity.agents.config.fqdn.default) <br>Hot-swap: Yes",
      "propertyOrder" : 27400,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "agentConfigChangeNotificationsEnabled" : {
      "title" : "Agent Configuration Change Notification",
      "description" : "Enable agent to receive notification messages from AM server for
configuration changes. (property name: com.sun.identity.agents.config.change.notification.enable)
<br>Hot-swap: Yes",
      "propertyOrder" : 25300,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "debugLogRotation" : {
      "title" : "Agent Debug File Rotation",
      "description" : "Debug file gets rotated based on the size specified. (property name:
com.sun.identity.agents.config.debug.file.rotate) <br>Hot-swap: Yes",
      "propertyOrder" : 26500,
      "required" : false,
      "type" : "boolean",

```

```

    "exampleValue" : ""
  },
  "agentUriPrefix" : {
    "title" : "Agent Deployment URI Prefix",
    "description" : "(property name: com.sun.identity.agents.config.agenturi.prefix)<br>Hot-
swap: Yes",
    "propertyOrder" : 25800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "agentNotificationUrl" : {
    "title" : "Agent Notification URL",
    "description" : "(Not used in Agent 5 onwards) <br>URL used by agent to register
notification listeners. (property name: com.sun.identity.client.notification.url) <br>Hot-swap: No",
    "propertyOrder" : 25700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "debugRotationSize" : {
    "title" : "Agent Debug File Size",
    "description" : "Agent debug file size in bytes. (property name:
com.sun.identity.agents.config.debug.file.size) <br>Hot-swap: Yes",
    "propertyOrder" : 26600,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "accessDeniedUrl" : {
    "title" : "Resources Access Denied URL",
    "description" : "The URL of the customized access denied page. (property name:
com.sun.identity.agents.config.access.denied.url) <br>Hot-swap: Yes",
    "propertyOrder" : 26300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "status" : {
    "title" : "Status",
    "description" : "Status of the agent configuration.",
    "propertyOrder" : 25100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "configurationPollingInterval" : {
    "title" : "Configuration Reload Interval",
    "description" : "Interval in minutes to fetch agent configuration from AM. (property name:
com.sun.identity.agents.config.polling.interval) <br>Hot-swap: No",
    "propertyOrder" : 25900,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "auditAccessType" : {
    "title" : "Audit Access Types",
    "description" : "Types of messages to log based on user URL access attempts. (property name:
com.sun.identity.agents.config.audit.accesstype) <br>Hot-swap: Yes",

```

```

    "propertyOrder" : 26700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "websocketConnectionIntervalInMinutes" : {
    "title" : "Web Socket Connection Interval",
    "description" : "Interval in minutes by which agents reopen their web socket connection to
ensure a fair distribution of connections across AM servers. (Agent 5 only).",
    "propertyOrder" : 25400,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "cdssoRootUrl" : {
    "title" : "Agent Root URL for CDSSO",
    "description" : "The agent root URL for CDSSO. The valid value is in the following format:
<br>protocol://hostname:port/<br> The protocol represents the protocol used, such as http or https.
The hostname represents the host name of the machine on which the agent resides. The port represents
the port number on which the agent is installed. The slash following the port number is required.",
    "propertyOrder" : 26100,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "auditLogLocation" : {
    "title" : "Audit Log Location",
    "description" : "Specifies where audit messages should be logged. (property name:
com.sun.identity.agents.config.log.disposition) <br>Hot-swap: Yes",
    "propertyOrder" : 26800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "ssoOnlyMode" : {
    "title" : "SSO Only Mode",
    "description" : "Agent will just enforce authentication (SSO), but no authorization for
policies. (property name: com.sun.identity.agents.config.sso.only) <br>Hot-swap: Yes",
    "propertyOrder" : 26200,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "jwtName" : {
    "title" : "JWT Cookie Name",
    "description" : "The name used by the agent to set the OIDC JWT on the user's browser.
(Agent 5 only).",
    "propertyOrder" : 25500,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "localAuditRotationSize" : {
    "title" : "Local Audit Log Rotation Size",
    "description" : "Size limit in bytes when a local audit log file is rotated to a new file.
(property name: com.sun.identity.agents.config.local.log.size) <br>Hot-swap: Yes",

```

```
"propertyOrder" : 27200,
"required" : false,
"type" : "integer",
"exampleValue" : ""
},
"configurationCleanupInterval" : {
  "title" : "Configuration Cleanup Interval",
  "description" : "Interval in minutes to cleanup old agent configuration entries. (property
name: com.sun.identity.agents.config.cleanup.interval) <br>Hot-swap: No",
  "propertyOrder" : 26000,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
},
"remoteLogFilename" : {
  "title" : "Remote Log Filename",
  "description" : "(Not used in Agent 5 onwards) <br>Name of file stored on AM server that
contains agent audit messages. (property name: com.sun.identity.agents.config.remote.logfile)
<br>Hot-swap: No",
  "propertyOrder" : 26900,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"notificationsEnabled" : {
  "title" : "Enable Notifications",
  "description" : "The notifications help in maintaining agent's sso, policy and configuration
caches. (property name: com.sun.identity.agents.config.notification.enable) <br>Hot-swap: No",
  "propertyOrder" : 25600,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"agentDebugLevel" : {
  "title" : "Agent Debug Level",
  "description" : "Agent debug level. (property name:
com.sun.identity.agents.config.debug.level) <br>Hot-swap: Yes",
  "propertyOrder" : 26400,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"fqdnCheck" : {
  "title" : "FQDN Check",
  "description" : "Enables checking of fqdn default value and fqdn map values. (property name:
com.sun.identity.agents.config.fqdn.check.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 27300,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"remoteLogSendInterval" : {
  "title" : "Remote Audit Log Interval",
  "description" : "Periodic interval in minutes in which audit log messages are sent to remote
log file. (property name: com.sun.identity.agents.config.remote.log.interval) <br>Hot-swap: No",
  "propertyOrder" : 27000,
  "required" : false,
  "type" : "integer",
  "exampleValue" : ""
}
```

```

    }
  },
  "advancedWebAgentConfig" : {
    "type" : "object",
    "title" : "Advanced",
    "propertyOrder" : 5,
    "properties" : {
      "clientIpHeader" : {
        "title" : "Client IP Address Header",
        "description" : "HTTP header name that holds the IP address of the client. (property name:
com.sun.identity.agents.config.client.ip.header) <br>Hot-swap: Yes",
        "propertyOrder" : 32800,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
      },
      "useLtpaToken" : {
        "title" : "Use LTPA token",
        "description" : "Set to true if agent needs to use LTPA Token. (property name:
com.sun.identity.agents.config.domino.ltpa.enable)",
        "propertyOrder" : 34700,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "changeProtocolToHttps" : {
        "title" : "Change URL Protocol to https",
        "description" : "If true, avoids IE6 security pop-ups. (property name:
com.sun.identity.agents.config.iis.owa.enable.change.protocol)",
        "propertyOrder" : 34200,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "overrideRequestHost" : {
        "title" : "Override Request URL Host",
        "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the host with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.host) <br>Hot-swap: Yes",
        "propertyOrder" : 33200,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "overrideRequestPort" : {
        "title" : "Override Request URL Port",
        "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the port with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.port) <br>Hot-swap: Yes",
        "propertyOrder" : 33300,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
      },
      "ltpaTokenOrganizationName" : {
        "title" : "LTPA Token Organization Name",

```



```

        "description" : "The organization name to which the LTPA token belongs. (property name:
com.sun.identity.agents.config.domino.ltpa.org.name)",
        "propertyOrder" : 35000,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "loadBalanced" : {
        "title" : "Load Balancer Setup",
        "description" : "Set to true if a load balancer is used for AM services. (property name:
com.sun.identity.agents.config.load.balancer.enable) <br>Hot-swap: No",
        "propertyOrder" : 33000,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "overrideNotificationUrl" : {
        "title" : "Override Notification URL",
        "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the URL with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.notification.url) <br>Hot-swap: Yes",
        "propertyOrder" : 33400,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "filterConfiguredWithOwa" : {
        "title" : "Filter configured with OWA",
        "description" : "Set to true if the IIS agent filter is configured for OWA. (property name:
com.sun.identity.agents.config.iis.owa.enable)",
        "propertyOrder" : 34100,
        "required" : false,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "ltpaTokenConfigurationName" : {
        "title" : "LTPA Token Configuration Name",
        "description" : "The configuration name that the agent uses in order to employ the LTPA
token mechanism. (property name: com.sun.identity.agents.config.domino.ltpa.config.name)",
        "propertyOrder" : 34900,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "idleSessionTimeoutUrl" : {
        "title" : "Idle Session Timeout Page URL",
        "description" : "URL of the local idle session timeout page. (property name:
com.sun.identity.agents.config.iis.owa.enable.session.timeout.url)",
        "propertyOrder" : 34300,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "overrideProxyHostAndPort" : {
        "title" : "Override Proxy Server's Host and Port",
        "description" : "(property name: com.sun.identity.agents.config.proxy.override.host.port)
<br>Hot-swap: No",
        "propertyOrder" : 33700,
    }

```

```

    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "postDataCachePeriod" : {
    "title" : "POST Data Entries Cache Period",
    "description" : "POST cache entry lifetime in minutes. (property name:
com.sun.identity.agents.config.postcache.entry.lifetime) <br>Hot-swap: Yes",
    "propertyOrder" : 33600,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "overrideRequestProtocol" : {
    "title" : "Override Request URL Protocol",
    "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the protocol with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.protocol) <br>Hot-swap: Yes",
    "propertyOrder" : 33100,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "checkUserInDomino" : {
    "title" : "Check User in Domino Database",
    "description" : "If true, agent checks user existence in Domino name database. (property
name: com.sun.identity.agents.config.domino.check.name.database)",
    "propertyOrder" : 34600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "authenticationType" : {
    "title" : "Authentication Type",
    "description" : "(property name: com.sun.identity.agents.config.iis.auth.type)",
    "propertyOrder" : 33800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "clientHostnameHeader" : {
    "title" : "Client Hostname Header",
    "description" : "HTTP header name that holds the Hostname of the client. (property name:
com.sun.identity.agents.config.client.hostname.header) <br>Hot-swap: Yes",
    "propertyOrder" : 32900,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "logonAndImpersonation" : {
    "title" : "Logon and Impersonation",
    "description" : "Set to true if agent should do Windows Logon and User Impersonation.
(property name: com.sun.identity.agents.config.iis.logonuser)",
    "propertyOrder" : 34500,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
},

```

```

"filterPriority" : {
  "title" : "Filter Priority",
  "description" : "The loading priority of filter. (property name:
com.sun.identity.agents.config.iis.filter.priority)",
  "propertyOrder" : 34000,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"ltpaTokenCookieName" : {
  "title" : "LTPA Token Cookie Name",
  "description" : "The name of the cookie that contains the LTPA token. (property name:
com.sun.identity.agents.config.domino.ltpa.cookie.name)",
  "propertyOrder" : 34800,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"showPasswordInHeader" : {
  "title" : "Show Password in HTTP Header",
  "description" : "Set to true if encrypted password should be set in HTTP header
AUTH_PASSWORD. (property name: com.sun.identity.agents.config.iis.password.header)",
  "propertyOrder" : 34400,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"postDataPreservation" : {
  "title" : "POST Data Preservation",
  "description" : "Enables POST data preservation. (property name:
com.sun.identity.agents.config.postdata.preserve.enable) <br> Note that this feature is not supported
in all the web agents. Please refer individual agents documentation for more details. <br>Hot-swap:
Yes",
  "propertyOrder" : 33500,
  "required" : false,
  "type" : "boolean",
  "exampleValue" : ""
},
"replayPasswordKey" : {
  "title" : "Replay Password Key",
  "description" : "DES key for decrypting the basic authentication password in the session.
(property name: com.sun.identity.agents.config.replaypasswd.key)",
  "propertyOrder" : 33900,
  "required" : false,
  "type" : "string",
  "exampleValue" : ""
},
"customProperties" : {
  "title" : "Custom Properties",
  "description" : "Additional properties that allow users to augment the set of properties
supported by agent. (property name: com.sun.identity.agents.config.freeformproperties) <br>Hot-
swap: Yes <br> Examples: <br> customproperty=custom-value1 <br> customlist[0]=customlist-
value-0 <br> customlist[1]=customlist-value-1 <br> custommap[key1]=custommap-value-1 <br>
custommap[key2]=custommap-value-2",
  "propertyOrder" : 35100,
  "required" : false,
  "items" : {
    "type" : "string"
  }
},

```

```

    "type" : "array",
    "exampleValue" : ""
  }
},
"miscWebAgentConfig" : {
  "type" : "object",
  "title" : "Miscellaneous",
  "propertyOrder" : 4,
  "properties" : {
    "gotoParameterName" : {
      "title" : "Goto Parameter Name",
      "description" : "Property used only when CDSSO is enabled. Default value
should be changed only when the login URL has a landing page specified <br> Example :
com.sun.identity.agents.config.cdssso.cdcservlet.url = http://host:port/opensso/cdcservlet?
goto=http://agent:port/landing.jsp <br> The parameter is used by the Agent to append the original
request URL to this cdcservlet URL. This parameter is consumed by the landing page to redirect to
the original URL. (property name: com.sun.identity.agents.config.redirect.param) <br>Hot-swap: Yes
<br> Example: com.sun.identity.agents.config.redirect.param = goto2<br> The complete URL sent for
authentication will be <br> http://host:port/opensso/cdcservlet?goto=http://agent:port/landing.jsp?
goto2=http://agent.port/original.jsp",
      "propertyOrder" : 32600,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "ignoreServerCheck" : {
      "title" : "Ignore Server Check",
      "description" : "Agent uses this value to check AM is up before doing a 302 redirect.
(property name: com.sun.identity.agents.config.ignore.server.check) <br>Hot-swap: Yes",
      "propertyOrder" : 32300,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "profileAttributesCookiePrefix" : {
      "title" : "Profile Attributes Cookie Prefix",
      "description" : "Sets cookie prefix in the attributes headers. (property name:
com.sun.identity.agents.config.profile.attribute.cookie.prefix) <br>Hot-swap: Yes",
      "propertyOrder" : 31800,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "ignorePreferredNamingUrl" : {
      "title" : "Ignore Preferred Naming URL in Naming Request",
      "description" : "Agent uses this value to send preferred naming url in the naming request.
(property name: com.sun.identity.agents.config.ignore.preferred.naming.url) <br>Hot-swap: Yes",
      "propertyOrder" : 32200,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "agentLocale" : {
      "title" : "Agent Locale",
      "description" : "The default locale for the product. (property name:
com.sun.identity.agents.config.locale) <br>Hot-swap: No",
      "propertyOrder" : 31500,
      "required" : false,

```

```

    "type" : "string",
    "exampleValue" : ""
  },
  "caseInsensitiveUrlComparison" : {
    "title" : "URL Comparison Case Sensitivity Check",
    "description" : "Enforces case insensitivity in both policy and not enforced url evaluation.
(property name: com.sun.identity.agents.config.url.comparison.case.ignore) <br>Hot-swap: Yes",
    "propertyOrder" : 32000,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "encodeProfileAttributes" : {
    "title" : "Native Encoding of Profile Attributes",
    "description" : "Agent encodes the ldap header values in the default encoding of OS locale.
If false, UTF-8 gets used. (property name: com.sun.identity.agents.config.convert.mbyte.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 32500,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "anonymousUserId" : {
    "title" : "Anonymous User Default Value",
    "description" : "User id of unauthenticated users. (property name:
com.sun.identity.agents.config.anonymous.user.id) <br>Hot-swap: Yes",
    "propertyOrder" : 32700,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "ignorePathInfo" : {
    "title" : "Ignore Path Info in Request URL",
    "description" : "The path info will be stripped from the request URL while doing Not
Enforced List check and url policy evaluation if the value is set to true. (property name:
com.sun.identity.agents.config.ignore.path.info) <br>Hot-swap: Yes",
    "propertyOrder" : 32400,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "encodeSpecialCharsInCookies" : {
    "title" : "Encode special chars in Cookies",
    "description" : "Encode special chars in cookie by URL encoding. Useful when profile,
session and response attributes contain special chars and attributes fetch mode is set to
HTTP_COOKIE. (property name: com.sun.identity.agents.config.encode.cookie.special.chars.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 31700,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "encodeUrlSpecialCharacters" : {
    "title" : "Encode URL's Special Characters",
    "description" : "Encodes the url which has special characters before doing policy
evaluation. (property name: com.sun.identity.agents.config.encode.url.special.chars.enable) <br>Hot-
swap: Yes",
    "propertyOrder" : 32100,
    "required" : false,

```

```

    "type" : "boolean",
    "exampleValue" : ""
  },
  "profileAttributesCookieMaxAge" : {
    "title" : "Profile Attributes Cookie Maxage",
    "description" : "Maxage of attributes cookie headers. (property name:
com.sun.identity.agents.config.profile.attribute.cookie.maxage) <br>Hot-swap: Yes",
    "propertyOrder" : 31900,
    "required" : false,
    "type" : "integer",
    "exampleValue" : ""
  },
  "anonymousUserEnabled" : {
    "title" : "Anonymous User",
    "description" : "Enable/Disable REMOTE_USER processing for anonymous users. (property name:
com.sun.identity.agents.config.anonymous.user.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 31600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  }
}
},
"applicationWebAgentConfig" : {
  "type" : "object",
  "title" : "Application",
  "propertyOrder" : 1,
  "properties" : {
    "notEnforcedIps" : {
      "title" : "Not Enforced Client IP List",
      "description" : "No authentication and authorization are required for the requests coming
from these client IP addresses. (property name: com.sun.identity.agents.config.notenforced.ip)
<br>Hot-swap: Yes <br> Examples: <br> 192.18.145.* <br> 192.18.146.123",
      "propertyOrder" : 28000,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "invertNotEnforcedUrls" : {
      "title" : "Invert Not Enforced URLs",
      "description" : "Only not enforced list of urls will be enforced. (property name:
com.sun.identity.agents.config.notenforced.url.invert) <br>Hot-swap: Yes",
      "propertyOrder" : 27800,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "clientIpValidation" : {
      "title" : "Client IP Validation",
      "description" : "This validates if the subsequent browser requests come from
the same ip address that the SSO token is initially issued against. (property name:
com.sun.identity.agents.config.client.ip.validation.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 28100,
      "required" : false,
      "type" : "boolean",
      "exampleValue" : ""
    }
  }
}

```

```

    },
    "sessionAttributeMap" : {
      "title" : "Session Attribute Map",
      "description" : "Maps the session attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.session.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of session attribute UserToken under name CUSTOM-userid: enter UserToken in Map
Key field, and enter CUSTOM-userid in Corresponding Map Value field.",
      "propertyOrder" : 28700,
      "required" : false,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : ""
    },
    "continuousSecurityHeaders" : {
      "title" : "Continuous Security Headers",
      "description" : "The name of the headers in the user's original request, that will be sent
as part of the payload during policy evaluation, which can then be accessed via the 'environment'
variable in a policy script. The 'key' is the name of the header to be sent, and the 'value' is the
name which it will appear as in the policy evaluation script.It is possible to map multiple headers
to the same name (they will simply appear as an array in the evaluation script). If the header
doesn't exist, then the empty string will be sent.",
      "propertyOrder" : 29000,
      "required" : false,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      },
      "type" : "object",
      "exampleValue" : ""
    },
    "responseAttributeFetchMode" : {
      "title" : "Response Attribute Fetch Mode",
      "description" : "(property name:
com.sun.identity.agents.config.response.attribute.fetch.mode) <br>Hot-swap: Yes",
      "propertyOrder" : 28400,
      "required" : false,
      "type" : "string",
      "exampleValue" : ""
    },
    "notEnforcedUrls" : {
      "title" : "Not Enforced URLs",
      "description" : "List of urls for which no authentication required. (property name:
com.sun.identity.agents.config.notenforced.url) <br>Hot-swap: Yes <br> Example: <br> http://
myagent.mydomain.com/*.gif",
      "propertyOrder" : 27700,
      "required" : false,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "fetchAttributesForNotEnforcedUrls" : {

```

```

    "title" : "Fetch Attributes for Not Enforced URLs",
    "description" : "Agent fetches profile attributes for not enforced urls by doing policy
evaluation. (property name: com.sun.identity.agents.config.notenforced.url.attributes.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 27900,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "profileAttributeMap" : {
    "title" : "Profile Attribute Map",
    "description" : "Maps the profile attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.profile.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of profile attribute cn under name CUSTOM-Common-Name: enter cn in Map Key field,
and enter CUSTOM-Common-Name in Corresponding Map Value field. <br> To populate the value of profile
attribute mail under name CUSTOM-Email: enter mail in Map Key field, and enter CUSTOM-Email in
Corresponding Map Value field.",
    "propertyOrder" : 28300,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "responseAttributeMap" : {
    "title" : "Response Attribute Map",
    "description" : "Maps the policy response attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.response.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of response attribute uid under name CUSTOM-USER-NAME: enter uid in Map Key field,
and enter CUSTOM-USER-NAME in Corresponding Map Value field.",
    "propertyOrder" : 28500,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "profileAttributeFetchMode" : {
    "title" : "Profile Attribute Fetch Mode",
    "description" : "(property name:
com.sun.identity.agents.config.profile.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 28200,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "sessionAttributeFetchMode" : {
    "title" : "Session Attribute Fetch Mode",
    "description" : "(property name:
com.sun.identity.agents.config.session.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 28600,

```



```

    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "continuousSecurityCookies" : {
    "title" : "Continuous Security Cookies",
    "description" : "The name of the cookies to be sent as part of the payload during policy
evaluation, which can be accessed via the 'environment' variable in a policy script. The 'key' is
the name of the cookie to be sent, and the 'value' is the name which it will appear as in the policy
evaluation script. It is possible to map multiple cookies to the same name (they will simply appear
as an array in the evaluation script). If the cookie doesn't exist, then the empty string will be
sent.",
    "propertyOrder" : 28900,
    "required" : false,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : ""
  },
  "ignorePathInfoForNotEnforcedUrls" : {
    "title" : "Ignore Path Info for Not Enforced URLs",
    "description" : "Indicate whether the path info and query should be
stripped from the request URL before being compared with the URLs of the not
enforced list when those URLs have a wildcard '*' character. (property name:
com.sun.identity.agents.config.ignore.path.info.for.not.enforced.list) <br>Hot-swap: Yes",
    "propertyOrder" : 27600,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "attributeMultiValueSeparator" : {
    "title" : "Attribute Multi Value Separator",
    "description" : "Specifies separator for multiple values. Applies to all
types of attributes i.e. profile, session and response attributes. (property name:
com.sun.identity.agents.config.attribute.multi.value.separator) <br>Hot-swap: Yes",
    "propertyOrder" : 28800,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  }
}
},
"ssoWebAgentConfig" : {
  "type" : "object",
  "title" : "SSO",
  "propertyOrder" : 2,
  "properties" : {
    "cookieResetList" : {
      "title" : "Cookies Reset Name List",
      "description" : "List of cookies in the format: name[=value][;Domain=value]. (property name:
com.sun.identity.agents.config.cookie.reset) <br>Hot-swap: Yes <br> Examples: <br> Cookie1 <br>
Cookie2=value;Domain=subdomain.domain.com",
      "propertyOrder" : 29800,
      "required" : false,
      "items" : {
        "type" : "string"
      }
    }
  }
}

```

```

    },
    "type" : "array",
    "exampleValue" : ""
  },
  "cookieResetEnabled" : {
    "title" : "Cookie Reset",
    "description" : "Agent reset cookies in the response before redirecting to authentication.
(property name: com.sun.identity.agents.config.cookie.reset.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 29700,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cdssoRedirectUri" : {
    "title" : "CDSSO Redirect URI",
    "description" : "An intermediate URI that is used by the Agent for processing CDSSO
requests. (property name: com.sun.identity.agents.config.cdsso.redirect.uri) <br>Hot-swap: Yes",
    "propertyOrder" : 29300,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "cookieName" : {
    "title" : "Cookie Name",
    "description" : "Name of the SSO Token cookie used between the AM server and the Agent.
(property name: com.sun.identity.agents.config.cookie.name)<br>Hot-swap: No",
    "propertyOrder" : 29100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "secureCookies" : {
    "title" : "Cookie Security",
    "description" : "Agent sends secure cookies if communication is secure. (property name:
com.sun.identity.agents.config.cookie.secure) <br>Hot-swap: No",
    "propertyOrder" : 29200,
    "required" : false,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cdssoUrls" : {
    "title" : "CDSSO Servlet URL",
    "description" : "List of URLs of the available CDSSO controllers that may be used by the
Agent for CDSSO processing. (property name: com.sun.identity.agents.config.cdsso.cdcervlet.url)
<br>Hot-swap: Yes <br> Example: <br> http://host:port/opensso/cdcervlet",
    "propertyOrder" : 29500,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "cdsso" : {
    "title" : "Cross Domain SSO",
    "description" : "Enables Cross-Domain Single Sign On. (property name:
com.sun.identity.agents.config.cdsso.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 29400,
    "required" : false,

```

```
    "type" : "boolean",
    "exampleValue" : ""
  },
  "cdssoCookieDomain" : {
    "title" : "Cookies Domain List",
    "description" : "List of domains in which cookies have to be set in CDSSO. (property name:
com.sun.identity.agents.config.cdsso.cookie.domain) <br>Hot-swap: Yes <br> Example: <br> .sun.com",
    "propertyOrder" : 29600,
    "required" : false,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  }
}
}
```

1.215. WebAgents

1.215.1. Realm Operations

Agents handler that is responsible for managing agents

Resource path: `/realm-config/agents/WebAgent`

Resource version: `1.0`

1.215.1.1. create

Usage:

```
am> create WebAgents --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "applicationWebAgentConfig" : {
      "type" : "object",
      "title" : "Application",

```

```

"propertyOrder" : 1,
"properties" : {
  "responseAttributeMap" : {
    "title" : "Response Attribute Map",
    "description" : "Maps the policy response attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.response.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of response attribute uid under name CUSTOM-USER-NAME: enter uid in Map Key field,
and enter CUSTOM-USER-NAME in Corresponding Map Value field.",
    "propertyOrder" : 28500,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "notEnforcedUrls" : {
    "title" : "Not Enforced URLs",
    "description" : "List of urls for which no authentication required. (property name:
com.sun.identity.agents.config.notenforced.url) <br>Hot-swap: Yes <br> Example: <br> http://
myagent.mydomain.com/*.gif",
    "propertyOrder" : 27700,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "continuousSecurityHeaders" : {
    "title" : "Continuous Security Headers",
    "description" : "The name of the headers in the user's original request, that will be sent
as part of the payload during policy evaluation, which can then be accessed via the 'environment'
variable in a policy script. The 'key' is the name of the header to be sent, and the 'value' is the
name which it will appear as in the policy evaluation script.It is possible to map multiple headers
to the same name (they will simply appear as an array in the evaluation script). If the header
doesn't exist, then the empty string will be sent.",
    "propertyOrder" : 29000,

```

```

        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "object",
                "required" : false
            }
        }
    },
    "invertNotEnforcedUrls" : {
        "title" : "Invert Not Enforced URLs",
        "description" : "Only not enforced list of urls will be enforced. (property name: com.sun.identity.agents.config.notenforced.url.invert) <br>Hot-swap: Yes",
        "propertyOrder" : 27800,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "attributeMultiValueSeparator" : {
        "title" : "Attribute Multi Value Separator",
        "description" : "Specifies separator for multiple values. Applies to all types of attributes i.e. profile, session and response attributes. (property name: com.sun.identity.agents.config.attribute.multi.value.separator) <br>Hot-swap: Yes",
        "propertyOrder" : 28800,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "profileAttributeFetchMode" : {
        "title" : "Profile Attribute Fetch Mode",
        "description" : "(property name: com.sun.identity.agents.config.profile.attribute.fetch.mode) <br>Hot-swap: Yes",

```

```

    "propertyOrder" : 28200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "sessionAttributeMap" : {
    "title" : "Session Attribute Map",
    "description" : "Maps the session attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.session.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of session attribute UserToken under name CUSTOM-userid: enter UserToken in Map
Key field, and enter CUSTOM-userid in Corresponding Map Value field.",
    "propertyOrder" : 28700,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "notEnforcedIps" : {
    "title" : "Not Enforced Client IP List",
    "description" : "No authentication and authorization are required for the requests coming
from these client IP addresses. (property name: com.sun.identity.agents.config.notenforced.ip)
<br>Hot-swap: Yes <br> Examples: <br> 192.18.145.* <br> 192.18.146.123",
    "propertyOrder" : 28000,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  }
}

```

```

    }
  },
  "fetchAttributesForNotEnforcedUrls" : {
    "title" : "Fetch Attributes for Not Enforced URLs",
    "description" : "Agent fetches profile attributes for not enforced urls by doing policy
evaluation. (property name: com.sun.identity.agents.config.notenforced.url.attributes.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 27900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "ignorePathInfoForNotEnforcedUrls" : {
    "title" : "Ignore Path Info for Not Enforced URLs",
    "description" : "Indicate whether the path info and query should be
stripped from the request URL before being compared with the URLs of the not
enforced list when those URLs have a wildcard '*' character. (property name:
com.sun.identity.agents.config.ignore.path.info.for.not.enforced.list) <br>Hot-swap: Yes",
    "propertyOrder" : 27600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "clientIpValidation" : {
    "title" : "Client IP Validation",
    "description" : "This validates if the subsequent browser requests come from
the same ip address that the SSO token is initially issued against. (property name:
com.sun.identity.agents.config.client.ip.validation.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 28100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  }
}

```

```

    }
  },
  "profileAttributeMap" : {
    "title" : "Profile Attribute Map",
    "description" : "Maps the profile attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.profile.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of profile attribute cn under name CUSTOM-Common-Name: enter cn in Map Key field,
and enter CUSTOM-Common-Name in Corresponding Map Value field. <br> To populate the value of profile
attribute mail under name CUSTOM-Email: enter mail in Map Key field, and enter CUSTOM-Email in
Corresponding Map Value field.",
    "propertyOrder" : 28300,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "continuousSecurityCookies" : {
    "title" : "Continuous Security Cookies",
    "description" : "The name of the cookies to be sent as part of the payload during policy
evaluation, which can be accessed via the 'environment' variable in a policy script. The 'key' is
the name of the cookie to be sent, and the 'value' is the name which it will appear as in the policy
evaluation script. It is possible to map multiple cookies to the same name (they will simply appear
as an array in the evaluation script). If the cookie doesn't exist, then the empty string will be
sent.",
    "propertyOrder" : 28900,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "sessionAttributeFetchMode" : {
    "title" : "Session Attribute Fetch Mode",

```



```

    "description" : "(property name:
com.sun.identity.agents.config.session.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 28600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "responseAttributeFetchMode" : {
    "title" : "Response Attribute Fetch Mode",
    "description" : "(property name:
com.sun.identity.agents.config.response.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 28400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  }
},
"globalWebAgentConfig" : {
  "type" : "object",
  "title" : "Global",
  "propertyOrder" : 0,
  "properties" : {
    "configurationCleanupInterval" : {
      "title" : "Configuration Cleanup Interval",
      "description" : "Interval in minutes to cleanup old agent configuration entries. (property
name: com.sun.identity.agents.config.cleanup.interval) <br>Hot-swap: No",
      "propertyOrder" : 26000,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : false
        }
      }
    }
  }
},

```

```

"agentNotificationUrl" : {
  "title" : "Agent Notification URL",
  "description" : "(Not used in Agent 5 onwards) <br>URL used by agent to register
notification listeners. (property name: com.sun.identity.client.notification.url) <br>Hot-swap: No",
  "propertyOrder" : 25700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"configurationPollingInterval" : {
  "title" : "Configuration Reload Interval",
  "description" : "Interval in minutes to fetch agent configuration from AM. (property name:
com.sun.identity.agents.config.polling.interval) <br>Hot-swap: No",
  "propertyOrder" : 25900,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : false
    }
  }
},
"accessDeniedUrl" : {
  "title" : "Resources Access Denied URL",
  "description" : "The URL of the customized access denied page. (property name:
com.sun.identity.agents.config.access.denied.url) <br>Hot-swap: Yes",
  "propertyOrder" : 26300,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"remoteLogFilename" : {
  "title" : "Remote Log Filename",
  "description" : "(Not used in Agent 5 onwards) <br>Name of file stored on AM server that
contains agent audit messages. (property name: com.sun.identity.agents.config.remote.logfile)
<br>Hot-swap: No",

```

```

        "propertyOrder" : 26900,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "jwtName" : {
        "title" : "JWT Cookie Name",
        "description" : "The name used by the agent to set the OIDC JWT on the user's browser.
    (Agent 5 only).",
        "propertyOrder" : 25500,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "fqdnCheck" : {
        "title" : "FQDN Check",
        "description" : "Enables checking of fqdn default value and fqdn map values. (property name:
    com.sun.identity.agents.config.fqdn.check.enable) <br>Hot-swap: Yes",
        "propertyOrder" : 27300,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "agentUriPrefix" : {
        "title" : "Agent Deployment URI Prefix",
        "description" : "(property name: com.sun.identity.agents.config.agenturi.prefix)<br>Hot-
    swap: Yes",
        "propertyOrder" : 25800,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {

```

```

        "type" : "boolean",
        "required" : true
    },
    "value" : {
        "type" : "string",
        "required" : false
    }
},
"repositoryLocation" : {
    "title" : "Location of Agent Configuration Repository",
    "description" : "Indicates agent's configuration located either on agent's host or centrally
on AM server.",
    "propertyOrder" : 25200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
},
"ssoOnlyMode" : {
    "title" : "SSO Only Mode",
    "description" : "Agent will just enforce authentication (SSO), but no authorization for
policies. (property name: com.sun.identity.agents.config.sso.only) <br>Hot-swap: Yes",
    "propertyOrder" : 26200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
},
"remoteLogSendInterval" : {
    "title" : "Remote Audit Log Interval",
    "description" : "Periodic interval in minutes in which audit log messages are sent to remote
log file. (property name: com.sun.identity.agents.config.remote.log.interval) <br>Hot-swap: No",
    "propertyOrder" : 27000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
},
"status" : {
    "title" : "Status",
    "description" : "Status of the agent configuration.",
    "propertyOrder" : 25100,
    "type" : "object",

```

```

        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : true
            }
        }
    },
    "agentgroup" : {
        "title" : "Group",
        "description" : "Add the agent to a group to allow inheritance of property values from the
group. <br>Changing the group will update inherited property values. <br>Inherited property values
are copied to the agent.",
        "propertyOrder" : 100,
        "required" : false,
        "type" : "string",
        "exampleValue" : ""
    },
    "agentDebugLevel" : {
        "title" : "Agent Debug Level",
        "description" : "Agent debug level. (property name:
com.sun.identity.agents.config.debug.level) <br>Hot-swap: Yes",
        "propertyOrder" : 26400,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "debugLogRotation" : {
        "title" : "Agent Debug File Rotation",
        "description" : "Debug file gets rotated based on the size specified. (property name:
com.sun.identity.agents.config.debug.file.rotate) <br>Hot-swap: Yes",
        "propertyOrder" : 26500,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "userpassword" : {

```

```

    "title" : "Password",
    "description" : "",
    "propertyOrder" : 25000,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "agentConfigChangeNotificationsEnabled" : {
    "title" : "Agent Configuration Change Notification",
    "description" : "Enable agent to receive notification messages from AM server for
configuration changes. (property name: com.sun.identity.agents.config.change.notification.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 25300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "localAuditRotationSize" : {
    "title" : "Local Audit Log Rotation Size",
    "description" : "Size limit in bytes when a local audit log file is rotated to a new file.
(property name: com.sun.identity.agents.config.local.log.size) <br>Hot-swap: Yes",
    "propertyOrder" : 27200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "cdssoRootUrl" : {
    "title" : "Agent Root URL for CDSSO",
    "description" : "The agent root URL for CDSSO. The valid value is in the following format:
<br>protocol://hostname:port/<br> The protocol represents the protocol used, such as http or https.
The hostname represents the host name of the machine on which the agent resides. The port represents
the port number on which the agent is installed. The slash following the port number is required.",
    "propertyOrder" : 26100,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {

```

```

        "type" : "boolean",
        "required" : true
    },
    "value" : {
        "type" : "array",
        "required" : false
    }
}
},
"fqdnDefault" : {
    "title" : "FQDN Default",
    "description" : "Fully qualified hostname that the users should use in order to access
resources. (property name: com.sun.identity.agents.config.fqdn.default) <br>Hot-swap: Yes",
    "propertyOrder" : 27400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
}
},
"auditLogLocation" : {
    "title" : "Audit Log Location",
    "description" : "Specifies where audit messages should be logged. (property name:
com.sun.identity.agents.config.log.disposition) <br>Hot-swap: Yes",
    "propertyOrder" : 26800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
}
},
"notificationsEnabled" : {
    "title" : "Enable Notifications",
    "description" : "The notifications help in maintaining agent's sso, policy and configuration
caches. (property name: com.sun.identity.agents.config.notification.enable) <br>Hot-swap: No",
    "propertyOrder" : 25600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",

```

```

        "required" : false
    }
}
},
"auditAccessType" : {
    "title" : "Audit Access Types",
    "description" : "Types of messages to log based on user URL access attempts. (property name:
com.sun.identity.agents.config.audit.accesstype) <br>Hot-swap: Yes",
    "propertyOrder" : 26700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
}
},
"websocketConnectionIntervalInMinutes" : {
    "title" : "Web Socket Connection Interval",
    "description" : "Interval in minutes by which agents reopen their web socket connection to
ensure a fair distribution of connections across AM servers. (Agent 5 only).",
    "propertyOrder" : 25400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
}
},
"localAuditLogRotation" : {
    "title" : "Rotate Local Audit Log",
    "description" : "Flag to indicate that audit log files should be rotated when reaching a
certain size. (property name: com.sun.identity.agents.config.local.log.rotate) <br>Hot-swap: Yes",
    "propertyOrder" : 27100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
}
},
"fqdnMapping" : {

```



```

    "title" : "FQDN Virtual Host Map",
    "description" : "Maps virtual, invalid, or partial hostnames, and IP addresses to the FQDN
to access protected resources. (property name: com.sun.identity.agents.config.fqdn.mapping) <br>Hot-
swap: Yes <br> Examples: <br> To map the partial hostname myserver to myserver.mydomain.com: enter
myserver in the Map Key field and myserver.mydomain.com in the Corresponding Map Value field. To map
a virtual server rst.hostname.com that points to the actual server abc.hostname.com: enter valid1
in the Map Key field and rst.hostname.com in the Corresponding Map Value field.",
    "propertyOrder" : 27500,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "debugRotationSize" : {
    "title" : "Agent Debug File Size",
    "description" : "Agent debug file size in bytes. (property name:
com.sun.identity.agents.config.debug.file.size) <br>Hot-swap: Yes",
    "propertyOrder" : 26600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  }
}
},
"advancedWebAgentConfig" : {
  "type" : "object",
  "title" : "Advanced",
  "propertyOrder" : 5,
  "properties" : {
    "changeProtocolToHttps" : {
      "title" : "Change URL Protocol to https",
      "description" : "If true, avoids IE6 security pop-ups. (property name:
com.sun.identity.agents.config.iis.owa.enable.change.protocol)",
      "propertyOrder" : 34200,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {

```

```

    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"authenticationType" : {
  "title" : "Authentication Type",
  "description" : "(property name: com.sun.identity.agents.config.iis.auth.type)",
  "propertyOrder" : 33800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"ltpaTokenConfigurationname" : {
  "title" : "LTPA Token Configuration Name",
  "description" : "The configuration name that the agent uses in order to employ the LTPA
token mechanism. (property name: com.sun.identity.agents.config.domino.ltpa.config.name)",
  "propertyOrder" : 34900,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"overrideNotificationUrl" : {
  "title" : "Override Notification URL",
  "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the URL with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.notification.url) <br>Hot-swap: Yes",
  "propertyOrder" : 33400,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},

```

```

        "value" : {
          "type" : "boolean",
          "required" : false
        }
      },
      "clientIpHeader" : {
        "title" : "Client IP Address Header",
        "description" : "HTTP header name that holds the IP address of the client. (property name: com.sun.identity.agents.config.client.ip.header) <br>Hot-swap: Yes",
        "propertyOrder" : 32800,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
          "inherited" : {
            "type" : "boolean",
            "required" : true
          },
          "value" : {
            "type" : "string",
            "required" : false
          }
        }
      },
      "customProperties" : {
        "title" : "Custom Properties",
        "description" : "Additional properties that allow users to augment the set of properties supported by agent. (property name: com.sun.identity.agents.config.freeformproperties) <br>Hot-swap: Yes <br> Examples: <br> customproperty=custom-value1 <br> customlist[0]=customlist-value-0 <br> customlist[1]=customlist-value-1 <br> custommap[key1]=custommap-value-1 <br> custommap[key2]=custommap-value-2",
        "propertyOrder" : 35100,
        "items" : {
          "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
          "inherited" : {
            "type" : "boolean",
            "required" : true
          },
          "value" : {
            "type" : "array",
            "required" : false
          }
        }
      },
      "idleSessionTimeoutUrl" : {
        "title" : "Idle Session Timeout Page URL",
        "description" : "URL of the local idle session timeout page. (property name: com.sun.identity.agents.config.iis.owa.enable.session.timeout.url)",
        "propertyOrder" : 34300,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
          "inherited" : {
            "type" : "boolean",
            "required" : true
          }
        }
      }
    }
  }

```

```

    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  },
  "filterConfiguredWithOwa" : {
    "title" : "Filter configured with OWA",
    "description" : "Set to true if the IIS agent filter is configured for OWA. (property name: com.sun.identity.agents.config.iis.owa.enable)",
    "propertyOrder" : 34100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "postDataCachePeriod" : {
    "title" : "POST Data Entries Cache Period",
    "description" : "POST cache entry lifetime in minutes. (property name: com.sun.identity.agents.config.postcache.entry.lifetime) <br>Hot-swap: Yes",
    "propertyOrder" : 33600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "checkUserInDomino" : {
    "title" : "Check User in Domino Database",
    "description" : "If true, agent checks user existence in Domino name database. (property name: com.sun.identity.agents.config.domino.check.name.database)",
    "propertyOrder" : 34600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  }
}

```

```

    }
  },
  "logonAndImpersonation" : {
    "title" : "Logon and Impersonation",
    "description" : "Set to true if agent should do Windows Logon and User Impersonation.
(property name: com.sun.identity.agents.config.iis.logonuser)",
    "propertyOrder" : 34500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "showPasswordInHeader" : {
    "title" : "Show Password in HTTP Header",
    "description" : "Set to true if encrypted password should be set in HTTP header
AUTH_PASSWORD. (property name: com.sun.identity.agents.config.iis.password.header)",
    "propertyOrder" : 34400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "overrideProxyHostAndPort" : {
    "title" : "Override Proxy Server's Host and Port",
    "description" : "(property name: com.sun.identity.agents.config.proxy.override.host.port)
<br>Hot-swap: No",
    "propertyOrder" : 33700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "overrideRequestProtocol" : {
    "title" : "Override Request URL Protocol",

```

```
"description" : "Set to true if the agent is sitting behind a ssl/tls  
off-loader, load balancer, or proxy to override the protocol with the value from  
the property com.sun.identity.agents.config.agenturi.prefix. (property name:  
com.sun.identity.agents.config.override.protocol) <br>Hot-swap: Yes",  
  "propertyOrder" : 33100,  
  "type" : "object",  
  "exampleValue" : "",  
  "properties" : {  
    "inherited" : {  
      "type" : "boolean",  
      "required" : true  
    },  
    "value" : {  
      "type" : "boolean",  
      "required" : false  
    }  
  }  
},  
  "ltpaTokenOrganizationName" : {  
    "title" : "LTPA Token Organization Name",  
    "description" : "The organization name to which the LTPA token belongs. (property name:  
com.sun.identity.agents.config.domino.ltpa.org.name)",  
    "propertyOrder" : 35000,  
    "type" : "object",  
    "exampleValue" : "",  
    "properties" : {  
      "inherited" : {  
        "type" : "boolean",  
        "required" : true  
      },  
      "value" : {  
        "type" : "string",  
        "required" : false  
      }  
    }  
  },  
  "ltpaTokenCookieName" : {  
    "title" : "LTPA Token Cookie Name",  
    "description" : "The name of the cookie that contains the LTPA token. (property name:  
com.sun.identity.agents.config.domino.ltpa.cookie.name)",  
    "propertyOrder" : 34800,  
    "type" : "object",  
    "exampleValue" : "",  
    "properties" : {  
      "inherited" : {  
        "type" : "boolean",  
        "required" : true  
      },  
      "value" : {  
        "type" : "string",  
        "required" : false  
      }  
    }  
  },  
  "filterPriority" : {  
    "title" : "Filter Priority",  
    "description" : "The loading priority of filter. (property name:  
com.sun.identity.agents.config.iis.filter.priority)",  
    "propertyOrder" : 34000,
```

```

    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "postDataPreservation" : {
    "title" : "POST Data Preservation",
    "description" : "Enables POST data preservation. (property name:
com.sun.identity.agents.config.postdata.preserve.enable) <br> Note that this feature is not supported
in all the web agents. Please refer individual agents documentation for more details. <br>Hot-swap:
Yes",
    "propertyOrder" : 33500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "replayPasswordKey" : {
    "title" : "Replay Password Key",
    "description" : "DES key for decrypting the basic authentication password in the session.
(property name: com.sun.identity.agents.config.replaypasswd.key)",
    "propertyOrder" : 33900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "clientHostnameHeader" : {
    "title" : "Client Hostname Header",
    "description" : "HTTP header name that holds the Hostname of the client. (property name:
com.sun.identity.agents.config.client.hostname.header) <br>Hot-swap: Yes",
    "propertyOrder" : 32900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {

```

```

    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"overrideRequestPort" : {
  "title" : "Override Request URL Port",
  "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the port with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.port) <br>Hot-swap: Yes",
  "propertyOrder" : 33300,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"loadBalanced" : {
  "title" : "Load Balancer Setup",
  "description" : "Set to true if a load balancer is used for AM services. (property name:
com.sun.identity.agents.config.load.balancer.enable) <br>Hot-swap: No",
  "propertyOrder" : 33000,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"useLtpaToken" : {
  "title" : "Use LTPA token",
  "description" : "Set to true if agent needs to use LTPA Token. (property name:
com.sun.identity.agents.config.domino.ltpa.enable)",
  "propertyOrder" : 34700,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}

```



```

    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"overrideRequestHost" : {
  "title" : "Override Request URL Host",
  "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the host with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.host) <br>Hot-swap: Yes",
  "propertyOrder" : 33200,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
}
}
},
"amServicesWebAgent" : {
  "type" : "object",
  "title" : "AM Services",
  "propertyOrder" : 3,
  "properties" : {
    "policyClockSkew" : {
      "title" : "Policy Clock Skew",
      "description" : "Time in seconds used adjust time difference between Agent
machine and AM. Clock skew in seconds = AgentTime - AMServerTime. (property name:
com.sun.identity.agents.config.policy.clock.skew) <br>Hot-swap: No",
      "propertyOrder" : 31200,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : false
        }
      }
    }
  }
}
},
"userIdParameterType" : {
  "title" : "User ID Parameter Type",
  "description" : "User ID can be fetched from either SESSION and LDAP attributes. (property
name: com.sun.identity.agents.config.userid.param.type) <br>Hot-swap: Yes",
  "propertyOrder" : 30900,
  "type" : "object",

```

```

    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "fetchPoliciesFromRootResource" : {
    "title" : "Fetch Policies from Root Resource",
    "description" : "Agent caches policy decision of the resource and all resources from the
root of the resource down. (property name: com.sun.identity.agents.config.fetch.from.root.resource)
<br>Hot-swap: No",
    "propertyOrder" : 31000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "policyEvaluationRealm" : {
    "title" : "Realm",
    "description" : "Which realm to start evaluating from (property name:
org.forgerock.openam.agents.config.policy.evaluation.realm) <br>Hot-swap: Yes",
    "propertyOrder" : 31300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "ssoCachePollingInterval" : {
    "title" : "SSO Cache Polling Period",
    "description" : "Polling interval in minutes to refresh agent's sso cache. (property name:
com.sun.identity.agents.config.sso.cache.polling.interval) <br>Hot-swap: No",
    "propertyOrder" : 30700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",

```

```

        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "retrieveClientHostname" : {
    "title" : "Retrieve Client Hostname",
    "description" : "Gets the client's hostname through DNS reverse lookup for use in policy
evaluation. (property name: com.sun.identity.agents.config.get.client.host.name) <br>Hot-swap: Yes",
    "propertyOrder" : 31100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "logoutRedirectUrl" : {
    "title" : "Logout Redirect URL",
    "description" : "User gets redirected to this url after logout. (property name:
com.sun.identity.agents.config.logout.redirect.url). This property should be specified along with the
above Logout URL List.<br>Hot-swap: Yes",
    "propertyOrder" : 30500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "policyCachePollingInterval" : {
    "title" : "Policy Cache Polling Period",
    "description" : "Polling interval in minutes to refresh agent's policy cache. (property
name: com.sun.identity.agents.config.policy.cache.polling.interval) <br>Hot-swap: No",
    "propertyOrder" : 30600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",

```

```

    "required" : false
  }
}
},
"amLoginUrl" : {
  "title" : "AM Login URL",
  "description" : "AM login page URL. (property name:
com.sun.identity.agents.config.login.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Login",
  "propertyOrder" : 29900,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"agentConnectionTimeout" : {
  "title" : "Agent Connection Timeout",
  "description" : "Timeout period in seconds for an agent connection with AM auth server.
(property name: com.sun.identity.agents.config.auth.connection.timeout) <br>Hot-swap: Yes",
  "propertyOrder" : 30000,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : false
    }
  }
},
"logoutResetCookies" : {
  "title" : "Logout Cookies List for Reset",
  "description" : "Any cookies to be reset upon logout in the same format as cookie reset
list. (property name: com.sun.identity.agents.config.logout.cookie.reset) <br>Hot-swap: Yes <br>
Cookie1 <br> Cookie2=value;Domain=subdomain.domain.com",
  "propertyOrder" : 30400,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
}
}
}

```

```

    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  },
  "policyEvaluationApplication" : {
    "title" : "Application",
    "description" : "Which application contains the policies to evaluate with (property name: org.forgerock.openam.agents.config.policy.evaluation.application) <br>Hot-swap: Yes",
    "propertyOrder" : 31400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "userIdParameter" : {
    "title" : "User ID Parameter",
    "description" : "Agent sets value of User Id to REMOTE_USER server variable. (property name: com.sun.identity.agents.config.userid.param) <br>Hot-swap: Yes",
    "propertyOrder" : 30800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "applicationLogoutUrls" : {
    "title" : "Logout URL List",
    "description" : "List of application logout URLs. User gets logged out from AM session when these urls accessed. (property name: com.sun.identity.agents.config.agent.logout.url). If this property is used, user should specify a value for the below Logout Redirect URL property.<br>Hot-swap: Yes <br> Example: <br> http://myagent.mydomain.com/logout.html",
    "propertyOrder" : 30300,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  }
}

```

```

    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  },
  "amLogoutUrl" : {
    "title" : "AM Logout URL",
    "description" : "AM logout page URL. (property name:
com.sun.identity.agents.config.logout.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Logout",
    "propertyOrder" : 30200,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "primaryServerPollingPeriod" : {
    "title" : "Polling Period for Primary Server",
    "description" : "Interval in minutes, agent polls to check the primary server is up and
running. (property name: com.sun.identity.agents.config.poll.primary.server) <br>Hot-swap: No",
    "propertyOrder" : 30100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  }
}
},
"ssoWebAgentConfig" : {
  "type" : "object",
  "title" : "SSO",
  "propertyOrder" : 2,
  "properties" : {
    "cdssoRedirectUri" : {
      "title" : "CDSSO Redirect URI",
      "description" : "An intermediate URI that is used by the Agent for processing CDSSO
requests. (property name: com.sun.identity.agents.config.cdsso.redirect.uri) <br>Hot-swap: Yes",
      "propertyOrder" : 29300,

```

```

    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "cdssoUrls" : {
    "title" : "CDSSO Servlet URL",
    "description" : "List of URLs of the available CDSSO controllers that may be used by the
Agent for CDSSO processing. (property name: com.sun.identity.agents.config.cdsso.cdcervlet.url)
<br>Hot-swap: Yes <br> Example: <br> http://host:port/opensso/cdcervlet",
    "propertyOrder" : 29500,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "secureCookies" : {
    "title" : "Cookie Security",
    "description" : "Agent sends secure cookies if communication is secure. (property name:
com.sun.identity.agents.config.cookie.secure) <br>Hot-swap: No",
    "propertyOrder" : 29200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "cookieName" : {
    "title" : "Cookie Name",
    "description" : "Name of the SSO Token cookie used between the AM server and the Agent.
(property name: com.sun.identity.agents.config.cookie.name)<br>Hot-swap: No",
    "propertyOrder" : 29100,
    "type" : "object",

```

```

        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "cdssoCookieDomain" : {
        "title" : "Cookies Domain List",
        "description" : "List of domains in which cookies have to be set in CDSSO. (property name: com.sun.identity.agents.config.cdsso.cookie.domain) <br>Hot-swap: Yes <br> Example: <br> .sun.com",
        "propertyOrder" : 29600,
        "items" : {
            "type" : "string"
        },
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "array",
                "required" : false
            }
        }
    },
    "cookieResetEnabled" : {
        "title" : "Cookie Reset",
        "description" : "Agent reset cookies in the response before redirecting to authentication. (property name: com.sun.identity.agents.config.cookie.reset.enable) <br>Hot-swap: Yes",
        "propertyOrder" : 29700,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "cookieResetList" : {
        "title" : "Cookies Reset Name List",
        "description" : "List of cookies in the format: name[=value][;Domain=value]. (property name: com.sun.identity.agents.config.cookie.reset) <br>Hot-swap: Yes <br> Examples: <br> Cookie1 <br> Cookie2=value;Domain=subdomain.domain.com",
        "propertyOrder" : 29800,
        "items" : {
            "type" : "string"
        }
    }
}

```



```

    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "cdsso" : {
    "title" : "Cross Domain SSO",
    "description" : "Enables Cross-Domain Single Sign On. (property name:
com.sun.identity.agents.config.cdsso.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 29400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  }
},
"miscWebAgentConfig" : {
  "type" : "object",
  "title" : "Miscellaneous",
  "propertyOrder" : 4,
  "properties" : {
    "anonymousUserId" : {
      "title" : "Anonymous User Default Value",
      "description" : "User id of unauthenticated users. (property name:
com.sun.identity.agents.config.anonymous.user.id) <br>Hot-swap: Yes",
      "propertyOrder" : 32700,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    }
  }
},
"encodeUrlSpecialCharacters" : {
  "title" : "Encode URL's Special Characters",

```

```

    "description" : "Encodes the url which has special characters before doing policy
evaluation. (property name: com.sun.identity.agents.config.encode.url.special.chars.enable) <br>Hot-
swap: Yes",
    "propertyOrder" : 32100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "agentLocale" : {
    "title" : "Agent Locale",
    "description" : "The default locale for the product. (property name:
com.sun.identity.agents.config.locale) <br>Hot-swap: No",
    "propertyOrder" : 31500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "ignorePathInfo" : {
    "title" : "Ignore Path Info in Request URL",
    "description" : "The path info will be stripped from the request URL while doing Not
Enforced List check and url policy evaluation if the value is set to true. (property name:
com.sun.identity.agents.config.ignore.path.info) <br>Hot-swap: Yes",
    "propertyOrder" : 32400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "profileAttributesCookieMaxAge" : {
    "title" : "Profile Attributes Cookie Maxage",
    "description" : "Maxage of attributes cookie headers. (property name:
com.sun.identity.agents.config.profile.attribute.cookie.maxage) <br>Hot-swap: Yes",
    "propertyOrder" : 31900,

```

```

        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "integer",
                "required" : false
            }
        }
    },
    "anonymousUserEnabled" : {
        "title" : "Anonymous User",
        "description" : "Enable/Disable REMOTE_USER processing for anonymous users. (property name: com.sun.identity.agents.config.anonymous.user.enable) <br>Hot-swap: Yes",
        "propertyOrder" : 31600,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "encodeSpecialCharsInCookies" : {
        "title" : "Encode special chars in Cookies",
        "description" : "Encode special chars in cookie by URL encoding. Useful when profile, session and response attributes contain special chars and attributes fetch mode is set to HTTP_COOKIE. (property name: com.sun.identity.agents.config.encode.cookie.special.chars.enable) <br>Hot-swap: Yes",
        "propertyOrder" : 31700,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "ignorePreferredNamingUrl" : {
        "title" : "Ignore Preferred Naming URL in Naming Request",
        "description" : "Agent uses this value to send preferred naming url in the naming request. (property name: com.sun.identity.agents.config.ignore.preferred.naming.url) <br>Hot-swap: Yes",
        "propertyOrder" : 32200,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
    
```

```

        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    },
    "profileAttributesCookiePrefix" : {
        "title" : "Profile Attributes Cookie Prefix",
        "description" : "Sets cookie prefix in the attributes headers. (property name: com.sun.identity.agents.config.profile.attribute.cookie.prefix) <br>Hot-swap: Yes",
        "propertyOrder" : 31800,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "encodeProfileAttributes" : {
        "title" : "Native Encoding of Profile Attributes",
        "description" : "Agent encodes the ldap header values in the default encoding of OS locale. If false, UTF-8 gets used. (property name: com.sun.identity.agents.config.convert.mbyte.enable) <br>Hot-swap: Yes",
        "propertyOrder" : 32500,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "ignoreServerCheck" : {
        "title" : "Ignore Server Check",
        "description" : "Agent uses this value to check AM is up before doing a 302 redirect. (property name: com.sun.identity.agents.config.ignore.server.check) <br>Hot-swap: Yes",
        "propertyOrder" : 32300,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            }
        }
    },

```

```
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    },
    "caseInsensitiveUrlComparison" : {
        "title" : "URL Comparison Case Sensitivity Check",
        "description" : "Enforces case insensitivity in both policy and not enforced url evaluation.
(property name: com.sun.identity.agents.config.url.comparison.case.ignore) <br>Hot-swap: Yes",
        "propertyOrder" : 32000,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "gotoParameterName" : {
        "title" : "Goto Parameter Name",
        "description" : "Property used only when CDSSO is enabled. Default value
should be changed only when the login URL has a landing page specified <br> Example :
com.sun.identity.agents.config.cdssso.cdcservlet.url = http://host:port/opensso/cdcservlet?
goto=http://agent:port/landing.jsp <br> The parameter is used by the Agent to append the original
request URL to this cdcservlet URL. This parameter is consumed by the landing page to redirect to
the original URL. (property name: com.sun.identity.agents.config.redirect.param) <br>Hot-swap: Yes
<br> Example: com.sun.identity.agents.config.redirect.param = goto2<br> The complete URL sent for
authentication will be <br> http://host:port/opensso/cdcservlet?goto=http://agent:port/landing.jsp?
goto2=http://agent.port/original.jsp",
        "propertyOrder" : 32600,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    }
}
}
```

1.215.1.2. delete

Usage:

```
am> delete WebAgents --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.215.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action WebAgents --realm Realm --actionName getAllTypes
```

1.215.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action WebAgents --realm Realm --actionName getCreatableTypes
```

1.215.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action WebAgents --realm Realm --actionName nextdescendents
```

1.215.1.6. query

Querying the agents of a specific type

Usage:

```
am> query WebAgents --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.215.1.7. read

Usage:

```
am> read WebAgents --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.215.1.8. update

Usage:

```
am> update WebAgents --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "applicationWebAgentConfig" : {
      "type" : "object",
      "title" : "Application",
      "propertyOrder" : 1,
      "properties" : {
        "responseAttributeMap" : {
          "title" : "Response Attribute Map",
          "description" : "Maps the policy response attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.response.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of response attribute uid under name CUSTOM-USER-NAME: enter uid in Map Key field,
and enter CUSTOM-USER-NAME in Corresponding Map Value field.",
          "propertyOrder" : 28500,
          "patternProperties" : {
            ".*" : {
              "type" : "string"
            }
          },
          "type" : "object",
          "exampleValue" : "",
          "properties" : {
            "inherited" : {
              "type" : "boolean",
              "required" : true
            },
            "value" : {
              "type" : "object",

```

```

        "required" : false
    }
}
},
"notEnforcedUrls" : {
    "title" : "Not Enforced URLs",
    "description" : "List of urls for which no authentication required. (property name:
com.sun.identity.agents.config.notenforced.url) <br>Hot-swap: Yes <br> Example: <br> http://
myagent.mydomain.com/*.gif",
    "propertyOrder" : 27700,
    "items" : {
        "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "array",
            "required" : false
        }
    }
},
"continuousSecurityHeaders" : {
    "title" : "Continuous Security Headers",
    "description" : "The name of the headers in the user's original request, that will be sent
as part of the payload during policy evaluation, which can then be accessed via the 'environment'
variable in a policy script. The 'key' is the name of the header to be sent, and the 'value' is the
name which it will appear as in the policy evaluation script.It is possible to map multiple headers
to the same name (they will simply appear as an array in the evaluation script). If the header
doesn't exist, then the empty string will be sent.",
    "propertyOrder" : 29000,
    "patternProperties" : {
        ".*" : {
            "type" : "string"
        }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "object",
            "required" : false
        }
    }
},
"invertNotEnforcedUrls" : {
    "title" : "Invert Not Enforced URLs",
    "description" : "Only not enforced list of urls will be enforced. (property name:
com.sun.identity.agents.config.notenforced.url.invert) <br>Hot-swap: Yes",
    "propertyOrder" : 27800,
    "type" : "object",

```



```

        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "attributeMultiValueSeparator" : {
        "title" : "Attribute Multi Value Separator",
        "description" : "Specifies separator for multiple values. Applies to all
types of attributes i.e. profile, session and response attributes. (property name:
com.sun.identity.agents.config.attribute.multi.value.separator) <br>Hot-swap: Yes",
        "propertyOrder" : 28800,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "profileAttributeFetchMode" : {
        "title" : "Profile Attribute Fetch Mode",
        "description" : "(property name:
com.sun.identity.agents.config.profile.attribute.fetch.mode) <br>Hot-swap: Yes",
        "propertyOrder" : 28200,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "string",
                "required" : false
            }
        }
    },
    "sessionAttributeMap" : {
        "title" : "Session Attribute Map",
        "description" : "Maps the session attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.session.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of session attribute UserToken under name CUSTOM-userid: enter UserToken in Map
Key field, and enter CUSTOM-userid in Corresponding Map Value field.",
        "propertyOrder" : 28700,
        "patternProperties" : {
            ".*" : {

```

```

        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "notEnforcedIps" : {
    "title" : "Not Enforced Client IP List",
    "description" : "No authentication and authorization are required for the requests coming
from these client IP addresses. (property name: com.sun.identity.agents.config.notenforced.ip)
<br>Hot-swap: Yes <br> Examples: <br> 192.18.145.* <br> 192.18.146.123",
    "propertyOrder" : 28000,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "fetchAttributesForNotEnforcedUrls" : {
    "title" : "Fetch Attributes for Not Enforced URLs",
    "description" : "Agent fetches profile attributes for not enforced urls by doing policy
evaluation. (property name: com.sun.identity.agents.config.notenforced.url.attributes.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 27900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "ignorePathInfoForNotEnforcedUrls" : {
    "title" : "Ignore Path Info for Not Enforced URLs",

```

```

      "description" : "Indicate whether the path info and query should be
stripped from the request URL before being compared with the URLs of the not
enforced list when those URLs have a wildcard '*' character. (property name:
com.sun.identity.agents.config.ignore.path.info.for.not.enforced.list) <br>Hot-swap: Yes",
      "propertyOrder" : 27600,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    },
    "clientIpValidation" : {
      "title" : "Client IP Validation",
      "description" : "This validates if the subsequent browser requests come from
the same ip address that the SSO token is initially issued against. (property name:
com.sun.identity.agents.config.client.ip.validation.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 28100,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    },
    "profileAttributeMap" : {
      "title" : "Profile Attribute Map",
      "description" : "Maps the profile attributes to be populated
under specific names for the currently authenticated user. (property name:
com.sun.identity.agents.config.profile.attribute.mapping) <br>Hot-swap: Yes <br> Example: <br> To
populate the value of profile attribute cn under name CUSTOM-Common-Name: enter cn in Map Key field,
and enter CUSTOM-Common-Name in Corresponding Map Value field. <br> To populate the value of profile
attribute mail under name CUSTOM-Email: enter mail in Map Key field, and enter CUSTOM-Email in
Corresponding Map Value field.",
      "propertyOrder" : 28300,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      }
    }
  },

```

```

    "value" : {
      "type" : "object",
      "required" : false
    }
  },
  "continuousSecurityCookies" : {
    "title" : "Continuous Security Cookies",
    "description" : "The name of the cookies to be sent as part of the payload during policy
evaluation, which can be accessed via the 'environment' variable in a policy script. The 'key' is
the name of the cookie to be sent, and the 'value' is the name which it will appear as in the policy
evaluation script. It is possible to map multiple cookies to the same name (they will simply appear
as an array in the evaluation script). If the cookie doesn't exist, then the empty string will be
sent.",
    "propertyOrder" : 28900,
    "patternProperties" : {
      ".*" : {
        "type" : "string"
      }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "object",
        "required" : false
      }
    }
  },
  "sessionAttributeFetchMode" : {
    "title" : "Session Attribute Fetch Mode",
    "description" : "(property name:
com.sun.identity.agents.config.session.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 28600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "responseAttributeFetchMode" : {
    "title" : "Response Attribute Fetch Mode",
    "description" : "(property name:
com.sun.identity.agents.config.response.attribute.fetch.mode) <br>Hot-swap: Yes",
    "propertyOrder" : 28400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {

```

```

        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "string",
            "required" : false
        }
    }
}
},
"globalWebAgentConfig" : {
    "type" : "object",
    "title" : "Global",
    "propertyOrder" : 0,
    "properties" : {
        "configurationCleanupInterval" : {
            "title" : "Configuration Cleanup Interval",
            "description" : "Interval in minutes to cleanup old agent configuration entries. (property name: com.sun.identity.agents.config.cleanup.interval) <br>Hot-swap: No",
            "propertyOrder" : 26000,
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                },
                "value" : {
                    "type" : "integer",
                    "required" : false
                }
            }
        },
        "agentNotificationUrl" : {
            "title" : "Agent Notification URL",
            "description" : "(Not used in Agent 5 onwards) <br>URL used by agent to register notification listeners. (property name: com.sun.identity.client.notification.url) <br>Hot-swap: No",
            "propertyOrder" : 25700,
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                },
                "value" : {
                    "type" : "string",
                    "required" : false
                }
            }
        },
        "configurationPollingInterval" : {
            "title" : "Configuration Reload Interval",
            "description" : "Interval in minutes to fetch agent configuration from AM. (property name: com.sun.identity.agents.config.polling.interval) <br>Hot-swap: No",
            "propertyOrder" : 25900,
            "type" : "object",

```

```

    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "accessDeniedUrl" : {
    "title" : "Resources Access Denied URL",
    "description" : "The URL of the customized access denied page. (property name:
com.sun.identity.agents.config.access.denied.url) <br>Hot-swap: Yes",
    "propertyOrder" : 26300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "remoteLogFilename" : {
    "title" : "Remote Log Filename",
    "description" : "(Not used in Agent 5 onwards) <br>Name of file stored on AM server that
contains agent audit messages. (property name: com.sun.identity.agents.config.remote.logfile)
<br>Hot-swap: No",
    "propertyOrder" : 26900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "jwtName" : {
    "title" : "JWT Cookie Name",
    "description" : "The name used by the agent to set the OIDC JWT on the user's browser.
(Agent 5 only).",
    "propertyOrder" : 25500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",

```

```

        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "fqdnCheck" : {
    "title" : "FQDN Check",
    "description" : "Enables checking of fqdn default value and fqdn map values. (property name: com.sun.identity.agents.config.fqdn.check.enable) <br>Hot-swap: Yes",
    "propertyOrder" : 27300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "agentUriPrefix" : {
    "title" : "Agent Deployment URI Prefix",
    "description" : "(property name: com.sun.identity.agents.config.agenturi.prefix)<br>Hot-swap: Yes",
    "propertyOrder" : 25800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "repositoryLocation" : {
    "title" : "Location of Agent Configuration Repository",
    "description" : "Indicates agent's configuration located either on agent's host or centrally on AM server.",
    "propertyOrder" : 25200,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "ssoOnlyMode" : {
    "title" : "SSO Only Mode",
    "description" : "Agent will just enforce authentication (SSO), but no authorization for policies. (property name: com.sun.identity.agents.config.sso.only) <br>Hot-swap: Yes",
    "propertyOrder" : 26200,
    "type" : "object",

```

```

    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "remoteLogSendInterval" : {
    "title" : "Remote Audit Log Interval",
    "description" : "Periodic interval in minutes in which audit log messages are sent to remote
log file. (property name: com.sun.identity.agents.config.remote.log.interval) <br>Hot-swap: No",
    "propertyOrder" : 27000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "status" : {
    "title" : "Status",
    "description" : "Status of the agent configuration.",
    "propertyOrder" : 25100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : true
      }
    }
  },
  "agentgroup" : {
    "title" : "Group",
    "description" : "Add the agent to a group to allow inheritance of property values from the
group. <br>Changing the group will update inherited property values. <br>Inherited property values
are copied to the agent.",
    "propertyOrder" : 100,
    "required" : false,
    "type" : "string",
    "exampleValue" : ""
  },
  "agentDebugLevel" : {
    "title" : "Agent Debug Level",

```



```

    "description" : "Agent debug level. (property name:
com.sun.identity.agents.config.debug.level) <br>Hot-swap: Yes",
    "propertyOrder" : 26400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "debugLogRotation" : {
    "title" : "Agent Debug File Rotation",
    "description" : "Debug file gets rotated based on the size specified. (property name:
com.sun.identity.agents.config.debug.file.rotate) <br>Hot-swap: Yes",
    "propertyOrder" : 26500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "userpassword" : {
    "title" : "Password",
    "description" : "",
    "propertyOrder" : 25000,
    "required" : true,
    "type" : "string",
    "format" : "password",
    "exampleValue" : ""
  },
  "agentConfigChangeNotificationsEnabled" : {
    "title" : "Agent Configuration Change Notification",
    "description" : "Enable agent to receive notification messages from AM server for
configuration changes. (property name: com.sun.identity.agents.config.change.notification.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 25300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  }
}

```

```

    }
  },
  "localAuditRotationSize" : {
    "title" : "Local Audit Log Rotation Size",
    "description" : "Size limit in bytes when a local audit log file is rotated to a new file.
(property name: com.sun.identity.agents.config.local.log.size) <br>Hot-swap: Yes",
    "propertyOrder" : 27200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  },
  "cdssoRootUrl" : {
    "title" : "Agent Root URL for CDSSO",
    "description" : "The agent root URL for CDSSO. The valid value is in the following format:
<br>protocol://hostname:port/<br>The protocol represents the protocol used, such as http or https.
The hostname represents the host name of the machine on which the agent resides. The port represents
the port number on which the agent is installed. The slash following the port number is required.",
    "propertyOrder" : 26100,
    "items" : {
      "type" : "string"
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    }
  },
  "fqdnDefault" : {
    "title" : "FQDN Default",
    "description" : "Fully qualified hostname that the users should use in order to access
resources. (property name: com.sun.identity.agents.config.fqdn.default) <br>Hot-swap: Yes",
    "propertyOrder" : 27400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  }
}

```

```
    }
  },
  "auditLogLocation" : {
    "title" : "Audit Log Location",
    "description" : "Specifies where audit messages should be logged. (property name:
com.sun.identity.agents.config.log.disposition) <br>Hot-swap: Yes",
    "propertyOrder" : 26800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "notificationsEnabled" : {
    "title" : "Enable Notifications",
    "description" : "The notifications help in maintaining agent's sso, policy and configuration
caches. (property name: com.sun.identity.agents.config.notification.enable) <br>Hot-swap: No",
    "propertyOrder" : 25600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "auditAccessType" : {
    "title" : "Audit Access Types",
    "description" : "Types of messages to log based on user URL access attempts. (property name:
com.sun.identity.agents.config.audit.accesstype) <br>Hot-swap: Yes",
    "propertyOrder" : 26700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "websocketConnectionIntervalInMinutes" : {
    "title" : "Web Socket Connection Interval",
```

```

        "description" : "Interval in minutes by which agents reopen their web socket connection to
        ensure a fair distribution of connections across AM servers. (Agent 5 only).",
        "propertyOrder" : 25400,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "integer",
                "required" : false
            }
        }
    },
    "localAuditLogRotation" : {
        "title" : "Rotate Local Audit Log",
        "description" : "Flag to indicate that audit log files should be rotated when reaching a
        certain size. (property name: com.sun.identity.agents.config.local.log.rotate) <br>Hot-swap: Yes",
        "propertyOrder" : 27100,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "fqdnMapping" : {
        "title" : "FQDN Virtual Host Map",
        "description" : "Maps virtual, invalid, or partial hostnames, and IP addresses to the FQDN
        to access protected resources. (property name: com.sun.identity.agents.config.fqdn.mapping) <br>Hot-
        swap: Yes <br> Examples: <br> To map the partial hostname myserver to myserver.mydomain.com: enter
        myserver in the Map Key field and myserver.mydomain.com in the Corresponding Map Value field. To map
        a virtual server rst.hostname.com that points to the actual server abc.hostname.com: enter valid1
        in the Map Key field and rst.hostname.com in the Corresponding Map Value field.",
        "propertyOrder" : 27500,
        "patternProperties" : {
            ".*" : {
                "type" : "string"
            }
        }
    },
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "object",
            "required" : false
        }
    }
}

```

```

    }
  },
  "debugRotationSize" : {
    "title" : "Agent Debug File Size",
    "description" : "Agent debug file size in bytes. (property name:
com.sun.identity.agents.config.debug.file.size) <br>Hot-swap: Yes",
    "propertyOrder" : 26600,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "integer",
        "required" : false
      }
    }
  }
}
},
"advancedWebAgentConfig" : {
  "type" : "object",
  "title" : "Advanced",
  "propertyOrder" : 5,
  "properties" : {
    "changeProtocolToHttps" : {
      "title" : "Change URL Protocol to https",
      "description" : "If true, avoids IE6 security pop-ups. (property name:
com.sun.identity.agents.config.iis.owa.enable.change.protocol)",
      "propertyOrder" : 34200,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    }
  }
},
"authenticationType" : {
  "title" : "Authentication Type",
  "description" : "(property name: com.sun.identity.agents.config.iis.auth.type)",
  "propertyOrder" : 33800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
}
}

```

```

    }
  },
  "ltpaTokenConfigurationName" : {
    "title" : "LTPA Token Configuration Name",
    "description" : "The configuration name that the agent uses in order to employ the LTPA
token mechanism. (property name: com.sun.identity.agents.config.domino.ltpa.config.name)",
    "propertyOrder" : 34900,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "overrideNotificationUrl" : {
    "title" : "Override Notification URL",
    "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the URL with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.notification.url) <br>Hot-swap: Yes",
    "propertyOrder" : 33400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "clientIpHeader" : {
    "title" : "Client IP Address Header",
    "description" : "HTTP header name that holds the IP address of the client. (property name:
com.sun.identity.agents.config.client.ip.header) <br>Hot-swap: Yes",
    "propertyOrder" : 32800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  }
},

```

```
"customProperties" : {
  "title" : "Custom Properties",
  "description" : "Additional properties that allow users to augment the set of properties
supported by agent. (property name: com.sun.identity.agents.config.freeformproperties) <br>Hot-
swap: Yes <br> Examples: <br> customproperty=custom-value1 <br> customlist[0]=customlist-
value-0 <br> customlist[1]=customlist-value-1 <br> custommap[key1]=custommap-value-1 <br>
custommap[key2]=custommap-value-2",
  "propertyOrder" : 35100,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"idleSessionTimeoutUrl" : {
  "title" : "Idle Session Timeout Page URL",
  "description" : "URL of the local idle session timeout page. (property name:
com.sun.identity.agents.config.iis.owa.enable.session.timeout.url)",
  "propertyOrder" : 34300,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"filterConfiguredWithOwa" : {
  "title" : "Filter configured with OWA",
  "description" : "Set to true if the IIS agent filter is configured for OWA. (property name:
com.sun.identity.agents.config.iis.owa.enable)",
  "propertyOrder" : 34100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
}
```

```

    },
    "postDataCachePeriod" : {
        "title" : "POST Data Entries Cache Period",
        "description" : "POST cache entry lifetime in minutes. (property name:
com.sun.identity.agents.config.postcache.entry.lifetime) <br>Hot-swap: Yes",
        "propertyOrder" : 33600,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "integer",
                "required" : false
            }
        }
    },
    "checkUserInDomino" : {
        "title" : "Check User in Domino Database",
        "description" : "If true, agent checks user existence in Domino name database. (property
name: com.sun.identity.agents.config.domino.check.name.database)",
        "propertyOrder" : 34600,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "logonAndImpersonation" : {
        "title" : "Logon and Impersonation",
        "description" : "Set to true if agent should do Windows Logon and User Impersonation.
(property name: com.sun.identity.agents.config.iis.logonuser)",
        "propertyOrder" : 34500,
        "type" : "object",
        "exampleValue" : "",
        "properties" : {
            "inherited" : {
                "type" : "boolean",
                "required" : true
            },
            "value" : {
                "type" : "boolean",
                "required" : false
            }
        }
    },
    "showPasswordInHeader" : {
        "title" : "Show Password in HTTP Header",
        "description" : "Set to true if encrypted password should be set in HTTP header
AUTH_PASSWORD. (property name: com.sun.identity.agents.config.iis.password.header)",
    }

```



```

    "propertyOrder" : 34400,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "overrideProxyHostAndPort" : {
    "title" : "Override Proxy Server's Host and Port",
    "description" : "(property name: com.sun.identity.agents.config.proxy.override.host.port)
<br>Hot-swap: No",
    "propertyOrder" : 33700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "overrideRequestProtocol" : {
    "title" : "Override Request URL Protocol",
    "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the protocol with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.protocol) <br>Hot-swap: Yes",
    "propertyOrder" : 33100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "ltpaTokenOrganizationName" : {
    "title" : "LTPA Token Organization Name",
    "description" : "The organization name to which the LTPA token belongs. (property name:
com.sun.identity.agents.config.domino.ltpa.org.name)",
    "propertyOrder" : 35000,
    "type" : "object",
    "exampleValue" : "",

```

```

    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "ltpaTokenCookieName" : {
    "title" : "LTPA Token Cookie Name",
    "description" : "The name of the cookie that contains the LTPA token. (property name: com.sun.identity.agents.config.domino.ltpa.cookie.name)",
    "propertyOrder" : 34800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "filterPriority" : {
    "title" : "Filter Priority",
    "description" : "The loading priority of filter. (property name: com.sun.identity.agents.config.iis.filter.priority)",
    "propertyOrder" : 34000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  },
  "postDataPreservation" : {
    "title" : "POST Data Preservation",
    "description" : "Enables POST data preservation. (property name: com.sun.identity.agents.config.postdata.preserve.enable) <br> Note that this feature is not supported in all the web agents. Please refer individual agents documentation for more details. <br>Hot-swap: Yes",
    "propertyOrder" : 33500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",

```

```

        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    },
    "replayPasswordKey" : {
      "title" : "Replay Password Key",
      "description" : "DES key for decrypting the basic authentication password in the session.
(property name: com.sun.identity.agents.config.replaypasswd.key)",
      "propertyOrder" : 33900,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "clientHostnameHeader" : {
      "title" : "Client Hostname Header",
      "description" : "HTTP header name that holds the Hostname of the client. (property name:
com.sun.identity.agents.config.client.hostname.header) <br>Hot-swap: Yes",
      "propertyOrder" : 32900,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "overrideRequestPort" : {
      "title" : "Override Request URL Port",
      "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the port with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.port) <br>Hot-swap: Yes",
      "propertyOrder" : 33300,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {

```

```

        "type" : "boolean",
        "required" : false
    }
}
},
"loadBalanced" : {
    "title" : "Load Balancer Setup",
    "description" : "Set to true if a load balancer is used for AM services. (property name:
com.sun.identity.agents.config.load.balancer.enable) <br>Hot-swap: No",
    "propertyOrder" : 33000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
}
},
"useLtpaToken" : {
    "title" : "Use LTPA token",
    "description" : "Set to true if agent needs to use LTPA Token. (property name:
com.sun.identity.agents.config.domino.ltpa.enable)",
    "propertyOrder" : 34700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
}
},
"overrideRequestHost" : {
    "title" : "Override Request URL Host",
    "description" : "Set to true if the agent is sitting behind a ssl/tls
off-loader, load balancer, or proxy to override the host with the value from
the property com.sun.identity.agents.config.agenturi.prefix. (property name:
com.sun.identity.agents.config.override.host) <br>Hot-swap: Yes",
    "propertyOrder" : 33200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "boolean",
            "required" : false
        }
    }
}
}

```

```

    }
  }
},
"amServicesWebAgent" : {
  "type" : "object",
  "title" : "AM Services",
  "propertyOrder" : 3,
  "properties" : {
    "policyClockSkew" : {
      "title" : "Policy Clock Skew",
      "description" : "Time in seconds used adjust time difference between Agent
machine and AM. Clock skew in seconds = AgentTime - AMServerTime. (property name:
com.sun.identity.agents.config.policy.clock.skew) <br>Hot-swap: No",
      "propertyOrder" : 31200,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : false
        }
      }
    },
    "userIdParameterType" : {
      "title" : "User ID Parameter Type",
      "description" : "User ID can be fetched from either SESSION and LDAP attributes. (property
name: com.sun.identity.agents.config.userid.param.type) <br>Hot-swap: Yes",
      "propertyOrder" : 30900,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "fetchPoliciesFromRootResource" : {
      "title" : "Fetch Policies from Root Resource",
      "description" : "Agent caches policy decision of the resource and all resources from the
root of the resource down. (property name: com.sun.identity.agents.config.fetch.from.root.resource)
<br>Hot-swap: No",
      "propertyOrder" : 31000,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
},

```

```
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      },
    },
    "policyEvaluationRealm" : {
      "title" : "Realm",
      "description" : "Which realm to start evaluating from (property name:
org.forgerock.openam.agents.config.policy.evaluation.realm) <br>Hot-swap: Yes",
      "propertyOrder" : 31300,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "ssoCachePollingInterval" : {
      "title" : "SSO Cache Polling Period",
      "description" : "Polling interval in minutes to refresh agent's sso cache. (property name:
com.sun.identity.agents.config.sso.cache.polling.interval) <br>Hot-swap: No",
      "propertyOrder" : 30700,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : false
        }
      }
    },
    "retrieveClientHostname" : {
      "title" : "Retrieve Client Hostname",
      "description" : "Gets the client's hostname through DNS reverse lookup for use in policy
evaluation. (property name: com.sun.identity.agents.config.get.client.host.name) <br>Hot-swap: Yes",
      "propertyOrder" : 31100,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    }
  }
}
```

```

    },
    "logoutRedirectUrl" : {
      "title" : "Logout Redirect URL",
      "description" : "User gets redirected to this url after logout. (property name:
com.sun.identity.agents.config.logout.redirect.url). This property should be specified along with the
above Logout URL List.<br>Hot-swap: Yes",
      "propertyOrder" : 30500,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "policyCachePollingInterval" : {
      "title" : "Policy Cache Polling Period",
      "description" : "Polling interval in minutes to refresh agent's policy cache. (property
name: com.sun.identity.agents.config.policy.cache.polling.interval) <br>Hot-swap: No",
      "propertyOrder" : 30600,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : false
        }
      }
    },
    "amLoginUrl" : {
      "title" : "AM Login URL",
      "description" : "AM login page URL. (property name:
com.sun.identity.agents.config.login.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Login",
      "propertyOrder" : 29900,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "array",
          "required" : false
        }
      }
    }
  }
}

```

```

    },
    "agentConnectionTimeout" : {
      "title" : "Agent Connection Timeout",
      "description" : "Timeout period in seconds for an agent connection with AM auth server.
(property name: com.sun.identity.agents.config.auth.connection.timeout) <br>Hot-swap: Yes",
      "propertyOrder" : 30000,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "integer",
          "required" : false
        }
      }
    },
    "logoutResetCookies" : {
      "title" : "Logout Cookies List for Reset",
      "description" : "Any cookies to be reset upon logout in the same format as cookie reset
list. (property name: com.sun.identity.agents.config.logout.cookie.reset) <br>Hot-swap: Yes <br>
Cookie1 <br> Cookie2=value;Domain=subdomain.domain.com",
      "propertyOrder" : 30400,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "array",
          "required" : false
        }
      }
    },
    "policyEvaluationApplication" : {
      "title" : "Application",
      "description" : "Which application contains the policies to evaluate with (property name:
org.forgerock.openam.agents.config.policy.evaluation.application) <br>Hot-swap: Yes",
      "propertyOrder" : 31400,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    }
  },
}

```



```

"userIdParameter" : {
  "title" : "User ID Parameter",
  "description" : "Agent sets value of User Id to REMOTE_USER server variable. (property name:
com.sun.identity.agents.config.userid.param) <br>Hot-swap: Yes",
  "propertyOrder" : 30800,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"applicationLogoutUrls" : {
  "title" : "Logout URL List",
  "description" : "List of application logout URLs. User gets logged out from AM session
when these urls accessed. (property name: com.sun.identity.agents.config.agent.logout.url). If this
property is used, user should specify a value for the below Logout Redirect URL property.<br>Hot-
swap: Yes <br> Example: <br> http://myagent.mydomain.com/logout.html",
  "propertyOrder" : 30300,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"amLogoutUrl" : {
  "title" : "AM Logout URL",
  "description" : "AM logout page URL. (property name:
com.sun.identity.agents.config.logout.url) <br>Hot-swap: Yes <br> Example: <br> http://host:port/
opensso/UI/Logout",
  "propertyOrder" : 30200,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",

```

```

        "required" : false
    }
},
"primaryServerPollingPeriod" : {
    "title" : "Polling Period for Primary Server",
    "description" : "Interval in minutes, agent polls to check the primary server is up and
running. (property name: com.sun.identity.agents.config.poll.primary.server) <br>Hot-swap: No",
    "propertyOrder" : 30100,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
        "inherited" : {
            "type" : "boolean",
            "required" : true
        },
        "value" : {
            "type" : "integer",
            "required" : false
        }
    }
},
},
"ssoWebAgentConfig" : {
    "type" : "object",
    "title" : "SSO",
    "propertyOrder" : 2,
    "properties" : {
        "cdssoRedirectUri" : {
            "title" : "CDSSO Redirect URI",
            "description" : "An intermediate URI that is used by the Agent for processing CDSSO
requests. (property name: com.sun.identity.agents.config.cdsso.redirect.uri) <br>Hot-swap: Yes",
            "propertyOrder" : 29300,
            "type" : "object",
            "exampleValue" : "",
            "properties" : {
                "inherited" : {
                    "type" : "boolean",
                    "required" : true
                },
                "value" : {
                    "type" : "string",
                    "required" : false
                }
            }
        },
        "cdssoUrls" : {
            "title" : "CDSSO Servlet URL",
            "description" : "List of URLs of the available CDSSO controllers that may be used by the
Agent for CDSSO processing. (property name: com.sun.identity.agents.config.cdsso.cdcervlet.url)
<br>Hot-swap: Yes <br> Example: <br> http://host:port/opensso/cdcervlet",
            "propertyOrder" : 29500,
            "items" : {
                "type" : "string"
            },
            "type" : "object",
            "exampleValue" : "",
            "properties" : {

```

```

    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "array",
      "required" : false
    }
  }
},
"secureCookies" : {
  "title" : "Cookie Security",
  "description" : "Agent sends secure cookies if communication is secure. (property name:
com.sun.identity.agents.config.cookie.secure) <br>Hot-swap: No",
  "propertyOrder" : 29200,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"cookieName" : {
  "title" : "Cookie Name",
  "description" : "Name of the SSO Token cookie used between the AM server and the Agent.
(property name: com.sun.identity.agents.config.cookie.name)<br>Hot-swap: No",
  "propertyOrder" : 29100,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"cdssoCookieDomain" : {
  "title" : "Cookies Domain List",
  "description" : "List of domains in which cookies have to be set in CDSSO. (property name:
com.sun.identity.agents.config.cdsso.cookie.domain) <br>Hot-swap: Yes <br> Example: <br> .sun.com",
  "propertyOrder" : 29600,
  "items" : {
    "type" : "string"
  },
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",

```

```

        "required" : true
      },
      "value" : {
        "type" : "array",
        "required" : false
      }
    },
    "cookieResetEnabled" : {
      "title" : "Cookie Reset",
      "description" : "Agent reset cookies in the response before redirecting to authentication.
(property name: com.sun.identity.agents.config.cookie.reset.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 29700,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    },
    "cookieResetList" : {
      "title" : "Cookies Reset Name List",
      "description" : "List of cookies in the format: name[=value][;Domain=value]. (property name:
com.sun.identity.agents.config.cookie.reset) <br>Hot-swap: Yes <br> Examples: <br> Cookie1 <br>
Cookie2=value;Domain=subdomain.domain.com",
      "propertyOrder" : 29800,
      "items" : {
        "type" : "string"
      },
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "array",
          "required" : false
        }
      }
    },
    "cdsso" : {
      "title" : "Cross Domain SSO",
      "description" : "Enables Cross-Domain Single Sign On. (property name:
com.sun.identity.agents.config.cdsso.enable) <br>Hot-swap: Yes",
      "propertyOrder" : 29400,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        }
      }
    }
  }
}

```

```

    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"miscWebAgentConfig" : {
  "type" : "object",
  "title" : "Miscellaneous",
  "propertyOrder" : 4,
  "properties" : {
    "anonymousUserId" : {
      "title" : "Anonymous User Default Value",
      "description" : "User id of unauthenticated users. (property name:
com.sun.identity.agents.config.anonymous.user.id) <br>Hot-swap: Yes",
      "propertyOrder" : 32700,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "string",
          "required" : false
        }
      }
    },
    "encodeUrlSpecialCharacters" : {
      "title" : "Encode URL's Special Characters",
      "description" : "Encodes the url which has special characters before doing policy
evaluation. (property name: com.sun.identity.agents.config.encode.url.special.chars.enable) <br>Hot-
swap: Yes",
      "propertyOrder" : 32100,
      "type" : "object",
      "exampleValue" : "",
      "properties" : {
        "inherited" : {
          "type" : "boolean",
          "required" : true
        },
        "value" : {
          "type" : "boolean",
          "required" : false
        }
      }
    }
  }
},
"agentLocale" : {
  "title" : "Agent Locale",
  "description" : "The default locale for the product. (property name:
com.sun.identity.agents.config.locale) <br>Hot-swap: No",
  "propertyOrder" : 31500,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {

```

```
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "string",
      "required" : false
    }
  }
},
"ignorePathInfo" : {
  "title" : "Ignore Path Info in Request URL",
  "description" : "The path info will be stripped from the request URL while doing Not
Enforced List check and url policy evaluation if the value is set to true. (property name:
com.sun.identity.agents.config.ignore.path.info) <br>Hot-swap: Yes",
  "propertyOrder" : 32400,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "boolean",
      "required" : false
    }
  }
},
"profileAttributesCookieMaxAge" : {
  "title" : "Profile Attributes Cookie Maxage",
  "description" : "Maxage of attributes cookie headers. (property name:
com.sun.identity.agents.config.profile.attribute.cookie.maxage) <br>Hot-swap: Yes",
  "propertyOrder" : 31900,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    },
    "value" : {
      "type" : "integer",
      "required" : false
    }
  }
},
"anonymousUserEnabled" : {
  "title" : "Anonymous User",
  "description" : "Enable/Disable REMOTE_USER processing for anonymous users. (property name:
com.sun.identity.agents.config.anonymous.user.enable) <br>Hot-swap: Yes",
  "propertyOrder" : 31600,
  "type" : "object",
  "exampleValue" : "",
  "properties" : {
    "inherited" : {
      "type" : "boolean",
      "required" : true
    }
  }
},
```

```

    "value" : {
      "type" : "boolean",
      "required" : false
    }
  },
  "encodeSpecialCharsInCookies" : {
    "title" : "Encode special chars in Cookies",
    "description" : "Encode special chars in cookie by URL encoding. Useful when profile,
session and response attributes contain special chars and attributes fetch mode is set to
HTTP_COOKIE. (property name: com.sun.identity.agents.config.encode.cookie.special.chars.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 31700,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "ignorePreferredNamingUrl" : {
    "title" : "Ignore Preferred Naming URL in Naming Request",
    "description" : "Agent uses this value to send preferred naming url in the naming request.
(property name: com.sun.identity.agents.config.ignore.preferred.naming.url) <br>Hot-swap: Yes",
    "propertyOrder" : 32200,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "profileAttributesCookiePrefix" : {
    "title" : "Profile Attributes Cookie Prefix",
    "description" : "Sets cookie prefix in the attributes headers. (property name:
com.sun.identity.agents.config.profile.attribute.cookie.prefix) <br>Hot-swap: Yes",
    "propertyOrder" : 31800,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "string",
        "required" : false
      }
    }
  }
}

```

```

    }
  },
  "encodeProfileAttributes" : {
    "title" : "Native Encoding of Profile Attributes",
    "description" : "Agent encodes the ldap header values in the default encoding of OS locale.
If false, UTF-8 gets used. (property name: com.sun.identity.agents.config.convert.mbyte.enable)
<br>Hot-swap: Yes",
    "propertyOrder" : 32500,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "ignoreServerCheck" : {
    "title" : "Ignore Server Check",
    "description" : "Agent uses this value to check AM is up before doing a 302 redirect.
(property name: com.sun.identity.agents.config.ignore.server.check) <br>Hot-swap: Yes",
    "propertyOrder" : 32300,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "caseInsensitiveUrlComparison" : {
    "title" : "URL Comparison Case Sensitivity Check",
    "description" : "Enforces case insensitivity in both policy and not enforced url evaluation.
(property name: com.sun.identity.agents.config.url.comparison.case.ignore) <br>Hot-swap: Yes",
    "propertyOrder" : 32000,
    "type" : "object",
    "exampleValue" : "",
    "properties" : {
      "inherited" : {
        "type" : "boolean",
        "required" : true
      },
      "value" : {
        "type" : "boolean",
        "required" : false
      }
    }
  },
  "gotoParameterName" : {

```



```
"title" : "Goto Parameter Name",
"description" : "Property used only when CDSSO is enabled. Default value
should be changed only when the login URL has a landing page specified <br> Example :
com.sun.identity.agents.config.cdssso.cdcservlet.url = http://host:port/opensso/cdcservlet?
goto=http://agent:port/landing.jsp <br> The parameter is used by the Agent to append the original
request URL to this cdcservlet URL. This parameter is consumed by the landing page to redirect to
the original URL. (property name: com.sun.identity.agents.config.redirect.param) <br>Hot-swap: Yes
<br> Example: com.sun.identity.agents.config.redirect.param = goto2<br> The complete URL sent for
authentication will be <br> http://host:port/opensso/cdcservlet?goto=http://agent:port/landing.jsp?
goto2=http://agent.port/original.jsp",
"propertyOrder" : 32600,
"type" : "object",
"exampleValue" : "",
"properties" : {
  "inherited" : {
    "type" : "boolean",
    "required" : true
  },
  "value" : {
    "type" : "string",
    "required" : false
  }
}
}
```

1.216. WebhookService

1.216.1. Realm Operations

Resource path: `/realm-config/webhooks`

Resource version: `1.0`

1.216.1.1. create

Usage:

```
am> create WebhookService --realm Realm --id id --body body
```

Parameters:

`--id`

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "url" : {
      "title" : "Url",
      "description" : "The webhook url that is used to create the http call for this webhook.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "body" : {
      "title" : "Body",
      "description" : "The webhook body to be sent in the http request.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "headers" : {
      "title" : "Headers",
      "description" : "The webhook headers added to the http request.",
      "propertyOrder" : 300,
      "required" : true,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      }
    },
    "type" : "object",
    "exampleValue" : ""
  }
}
```

1.216.1.2. delete

Usage:

```
am> delete WebhookService --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.216.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action WebhookService --realm Realm --actionName getAllTypes
```

1.216.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action WebhookService --realm Realm --actionName getCreatableTypes
```

1.216.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action WebhookService --realm Realm --actionName nextdescendents
```

1.216.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query WebhookService --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.216.1.7. read

Usage:

```
am> read WebhookService --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.216.1.8. update

Usage:

```
am> update WebhookService --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "url" : {
      "title" : "Url",
      "description" : "The webhook url that is used to create the http call for this webhook.",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "body" : {
      "title" : "Body",
      "description" : "The webhook body to be sent in the http request.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "headers" : {
      "title" : "Headers",
      "description" : "The webhook headers added to the http request.",
      "propertyOrder" : 300,
      "required" : true,
      "patternProperties" : {
        ".*" : {
          "type" : "string"
        }
      }
    },
    "type" : "object",
    "exampleValue" : ""
  }
}
```

1.216.2. Global Operations

Resource path: `/global-config/webhooks`

Resource version: `1.0`

1.216.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action WebhookService --global --actionName getAllTypes
```

1.216.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action WebhookService --global --actionName getCreatableTypes
```

1.216.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action WebhookService --global --actionName nextdescendents
```

1.216.2.4. read

Usage:

```
am> read WebhookService --global
```

1.216.2.5. update

Usage:

```
am> update WebhookService --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "type" : "object"  
}
```

1.217. WindowsDesktopSsoModule

1.217.1. Realm Operations

Resource path: `/realm-config/authentication/modules/windowsdesktopsso`

Resource version: `1.0`

1.217.1.1. create

Usage:

```
am> create WindowsDesktopSsoModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "trustedKerberosRealms" : {
      "title" : "Trusted Kerberos realms",
      "description" : "List of trusted Kerberos realms for User Kerberos tickets.<br><br>If realms are configured, then Kerberos tickets are only accepted if the realm part of the UserPrincipalName of the Users Kerberos ticket matches a realm from the list.",
      "propertyOrder" : 700,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "kerberosRealm" : {
      "title" : "Kerberos Realm",
      "description" : "The name of the Kerberos (Active Directory) realm used for authentication",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "lookupUserInRealm" : {
      "title" : "Search for the user in the realm",
      "description" : "Validate that the user has a matched user profile configured in the data store.<br><br>If this option is enabled, the module validates whether the account corresponds to a user profile in the Data Store for the realm. The attributes to perform the search are configured
```

```

under <i>Access Control > Realm Name > Authentication > All Core settings > Alias Search Attribute
Name</i>.",
  "propertyOrder" : 800,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"kerberosServerName" : {
  "title" : "Kerberos Server Name",
  "description" : "The hostname/IP address of the Kerberos (Active Directory) server.",
  "propertyOrder" : 400,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"returnPrincipalWithDomainName" : {
  "title" : "Return Principal with Domain Name",
  "description" : "Returns the fully qualified name of the authenticated user rather than just the
username.",
  "propertyOrder" : 500,
  "required" : true,
  "type" : "boolean",
  "exampleValue" : ""
},
"principalName" : {
  "title" : "Service Principal",
  "description" : "The name of the Kerberos principal used during authentication<br><br>This
principal must match the name used in the keytab file created from the Active Directory server.<br>
>The format of the field is as follows:<br><br><code>HTTP/openam.forgerock.com@AD_DOMAIN.COM</
code>",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
},
"authenticationLevel" : {
  "title" : "Authentication Level",
  "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
  "propertyOrder" : 600,
  "required" : true,
  "type" : "integer",
  "exampleValue" : ""
},
"keytabFileName" : {
  "title" : "Keytab File Name",
  "description" : "The path of the AD keytab file<br><br>This is the absolute pathname of the AD
keytab file. The keytab file is generated by the Active Directory server.",
  "propertyOrder" : 200,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
}
}
}

```

1.217.1.2. delete

Usage:

```
am> delete WindowsDesktopSsoModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.217.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action WindowsDesktopSsoModule --realm Realm --actionName getAllTypes
```

1.217.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action WindowsDesktopSsoModule --realm Realm --actionName getCreatableTypes
```

1.217.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action WindowsDesktopSsoModule --realm Realm --actionName nextdescendents
```

1.217.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query WindowsDesktopSsoModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.217.1.7. read

Usage:

```
am> read WindowsDesktopSsoModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.217.1.8. update

Usage:

```
am> update WindowsDesktopSsoModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "trustedKerberosRealms" : {
      "title" : "Trusted Kerberos realms",
      "description" : "List of trusted Kerberos realms for User Kerberos tickets.<br><br>If realms are configured, then Kerberos tickets are only accepted if the realm part of the UserPrincipalName of the Users Kerberos ticket matches a realm from the list.",
      "propertyOrder" : 700,
      "required" : true,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "kerberosRealm" : {
      "title" : "Kerberos Realm",
      "description" : "The name of the Kerberos (Active Directory) realm used for authentication",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "lookupUserInRealm" : {
      "title" : "Search for the user in the realm",
```

```

        "description" : "Validate that the user has a matched user profile configured in the data
store.<br><br>If this option is enabled, the module validates whether the account corresponds to a
user profile in the Data Store for the realm. The attributes to perform the search are configured
under <i>Access Control > Realm Name > Authentication > All Core settings > Alias Search Attribute
Name</i>.",
        "propertyOrder" : 800,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "kerberosServerName" : {
        "title" : "Kerberos Server Name",
        "description" : "The hostname/IP address of the Kerberos (Active Directory) server.",
        "propertyOrder" : 400,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "returnPrincipalWithDomainName" : {
        "title" : "Return Principal with Domain Name",
        "description" : "Returns the fully qualified name of the authenticated user rather than just the
username.",
        "propertyOrder" : 500,
        "required" : true,
        "type" : "boolean",
        "exampleValue" : ""
    },
    "principalName" : {
        "title" : "Service Principal",
        "description" : "The name of the Kerberos principal used during authentication<br><br>This
principal must match the name used in the keytab file created from the Active Directory server.<br>
>The format of the field is as follows:<br><br><code>HTTP/openam.forgerock.com@AD_DOMAIN.COM</
code>",
        "propertyOrder" : 100,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    },
    "authenticationLevel" : {
        "title" : "Authentication Level",
        "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
        "propertyOrder" : 600,
        "required" : true,
        "type" : "integer",
        "exampleValue" : ""
    },
    "keytabFileName" : {
        "title" : "Keytab File Name",
        "description" : "The path of the AD keytab file<br><br>This is the absolute pathname of the AD
keytab file. The keytab file is generated by the Active Directory server.",
        "propertyOrder" : 200,
        "required" : true,
        "type" : "string",
        "exampleValue" : ""
    }
}

```

```
}
```

1.217.2. Global Operations

Resource path: `/global-config/authentication/modules/windowsdesktopsso`

Resource version: `1.0`

1.217.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action WindowsDesktopSsoModule --global --actionName getAllTypes
```

1.217.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action WindowsDesktopSsoModule --global --actionName getCreatableTypes
```

1.217.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action WindowsDesktopSsoModule --global --actionName nextdescendents
```

1.217.2.4. read

Usage:

```
am> read WindowsDesktopSsoModule --global
```

1.217.2.5. update

Usage:

```
am> update WindowsDesktopSsoModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "keytabFileName" : {
          "title" : "Keytab File Name",
          "description" : "The path of the AD keytab file<br><br>This is the absolute pathname of the
AD keytab file. The keytab file is generated by the Active Directory server.",
          "propertyOrder" : 200,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "kerberosServerName" : {
          "title" : "Kerberos Server Name",
          "description" : "The hostname/IP address of the Kerberos (Active Directory) server.",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "principalName" : {
          "title" : "Service Principal",
          "description" : "The name of the Kerberos principal used during authentication<br><br>This
principal must match the name used in the keytab file created from the Active Directory server.<br>
>The format of the field is as follows:<br><br><code>HTTP/openam.forgerock.com@AD_DOMAIN.COM</
code>",
          "propertyOrder" : 100,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each
authentication module has an authentication level that can be used to indicate the level of security
associated with the module; 0 is the lowest (and the default).",
          "propertyOrder" : 600,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "returnPrincipalWithDomainName" : {
          "title" : "Return Principal with Domain Name",
          "description" : "Returns the fully qualified name of the authenticated user rather than just
the username.",
          "propertyOrder" : 500,
          "required" : true,
          "type" : "boolean",

```

```

    "exampleValue" : ""
  },
  "trustedKerberosRealms" : {
    "title" : "Trusted Kerberos realms",
    "description" : "List of trusted Kerberos realms for User Kerberos tickets.<br><br>If realms
are configured, then Kerberos tickets are only accepted if the realm part of the UserPrincipalName of
the Users Kerberos ticket matches a realm from the list.",
    "propertyOrder" : 700,
    "required" : true,
    "items" : {
      "type" : "string"
    },
    "type" : "array",
    "exampleValue" : ""
  },
  "lookupUserInRealm" : {
    "title" : "Search for the user in the realm",
    "description" : "Validate that the user has a matched user profile configured in the data
store.<br><br>If this option is enabled, the module validates whether the account corresponds to a
user profile in the Data Store for the realm. The attributes to perform the search are configured
under <i>Access Control > Realm Name > Authentication > All Core settings > Alias Search Attribute
Name</i>.",
    "propertyOrder" : 800,
    "required" : true,
    "type" : "boolean",
    "exampleValue" : ""
  },
  "kerberosRealm" : {
    "title" : "Kerberos Realm",
    "description" : "The name of the Kerberos (Active Directory) realm used for authentication",
    "propertyOrder" : 300,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
},
"type" : "object",
"title" : "Realm Defaults"
}
}
}

```

1.218. WindowsNtModule

1.218.1. Realm Operations

Resource path: `/realm-config/authentication/modules/windowsnt`

Resource version: `1.0`

1.218.1.1. create

Usage:

```
am> create WindowsNtModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationHost" : {
      "title" : "Authentication Host",
      "description" : "The name of the Windows NT Domain Controller.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sambaConfigurationFileName" : {
      "title" : "Samba Configuration File Name",
      "description" : "The path to the Samba configuration file.<br><br>The Windows NT authentication module uses the <code>smbclient</code> command to validate the user credentials against the Windows domain controller. <br><br>For example: <code>/opt/openam/smb.conf</code><br><br><i>NB </i>The <code>smbclient</code> command must be available in the <code>PATH</code> environmental variable associated with OpenAM.",
      "propertyOrder" : 300,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "authenticationLevel" : {
      "title" : "Authentication Level",
      "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
      "propertyOrder" : 400,
      "required" : true,
      "type" : "integer",
      "exampleValue" : ""
    },
    "authenticationDomain" : {
      "title" : "Authentication Domain",
      "description" : "The name of the Windows Domain used for authentication",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.218.1.2. delete

Usage:

```
am> delete WindowsNtModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.218.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action WindowsNtModule --realm Realm --actionName getAllTypes
```

1.218.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action WindowsNtModule --realm Realm --actionName getCreatableTypes
```

1.218.1.5. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action WindowsNtModule --realm Realm --actionName nextdescendents
```

1.218.1.6. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query WindowsNtModule --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.218.1.7. read

Usage:

```
am> read WindowsNtModule --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.218.1.8. update

Usage:

```
am> update WindowsNtModule --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "authenticationHost" : {
      "title" : "Authentication Host",
      "description" : "The name of the Windows NT Domain Controller.",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "sambaConfigurationFileName" : {
      "title" : "Samba Configuration File Name",
      "description" : "The path to the Samba configuration file.<br><br>The Windows NT authentication module uses the <code>smbclient</code> command to validate the user credentials against the Windows domain controller. <br><br>For example: <code>/opt/openam/smb.conf</code><br><br><i>NB </i>The <code>smbclient</code> command must be available in the <code>PATH</code> environmental variable associated with OpenAM.",
      "propertyOrder" : 300,

```



```
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  },
  "authenticationLevel" : {
    "title" : "Authentication Level",
    "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
    "propertyOrder" : 400,
    "required" : true,
    "type" : "integer",
    "exampleValue" : ""
  },
  "authenticationDomain" : {
    "title" : "Authentication Domain",
    "description" : "The name of the Windows Domain used for authentication",
    "propertyOrder" : 100,
    "required" : true,
    "type" : "string",
    "exampleValue" : ""
  }
}
}
```

1.218.2. Global Operations

Resource path: `/global-config/authentication/modules/windowsnt`

Resource version: `1.0`

1.218.2.1. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action WindowsNtModule --global --actionName getAllTypes
```

1.218.2.2. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action WindowsNtModule --global --actionName getCreatableTypes
```

1.218.2.3. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action WindowsNtModule --global --actionName nextdescendents
```

1.218.2.4. read

Usage:

```
am> read WindowsNtModule --global
```

1.218.2.5. update

Usage:

```
am> update WindowsNtModule --global --body body
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "defaults" : {
      "properties" : {
        "authenticationLevel" : {
          "title" : "Authentication Level",
          "description" : "The authentication level associated with this module.<br><br>Each authentication module has an authentication level that can be used to indicate the level of security associated with the module; 0 is the lowest (and the default). ",
          "propertyOrder" : 400,
          "required" : true,
          "type" : "integer",
          "exampleValue" : ""
        },
        "sambaConfigurationFileName" : {
          "title" : "Samba Configuration File Name",
          "description" : "The path to the Samba configuration file.<br><br>The Windows NT authentication module uses the <code>smbclient</code> command to validate the user credentials against the Windows domain controller. <br><br>For example: <code>/opt/openam/smb.conf</code><br><br><i>NB </i>The <code>smbclient</code> command must be available in the <code>PATH</code> environmental variable associated with OpenAM.",
          "propertyOrder" : 300,
          "required" : true,
          "type" : "string",
          "exampleValue" : ""
        },
        "authenticationHost" : {
          "title" : "Authentication Host",
```

```
"description" : "The name of the Windows NT Domain Controller.",
"propertyOrder" : 200,
"required" : true,
"type" : "string",
"exampleValue" : ""
},
"authenticationDomain" : {
  "title" : "Authentication Domain",
  "description" : "The name of the Windows Domain used for authentication",
  "propertyOrder" : 100,
  "required" : true,
  "type" : "string",
  "exampleValue" : ""
}
},
"type" : "object",
"title" : "Realm Defaults"
}
}
```

1.219. WsEntity

1.219.1. Realm Operations

Resource path: `/realm-config/federation/entityproviders/ws`

Resource version: `1.0`

1.219.1.1. create

Usage:

```
am> create WsEntity --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "entityConfig" : {
      "title" : "Entity Configuration",
      "description" : "",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "metadata" : {
      "title" : "Metadata",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.219.1.2. delete

Usage:

```
am> delete WsEntity --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.219.1.3. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query WsEntity --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.219.1.4. read

Usage:

```
am> read WsEntity --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.219.1.5. update

Usage:

```
am> update WsEntity --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "entityConfig" : {
      "title" : "Entity Configuration",
      "description" : "",
      "propertyOrder" : 200,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    },
    "metadata" : {
      "title" : "Metadata",
      "description" : "",
      "propertyOrder" : 100,
      "required" : true,
      "type" : "string",
      "exampleValue" : ""
    }
  }
}
```

1.220. ZeroPageLoginCollector

1.220.1. Realm Operations

Resource path: `/realm-config/authentication/authenticationtrees/nodes/ZeroPageLoginNode`

Resource version: `1.0`

1.220.1.1. create

Usage:

```
am> create ZeroPageLoginCollector --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:

```
{
  "type" : "object",
  "properties" : {
    "allowWithoutReferer" : {
      "title" : "Allow Without Referer",
      "description" : "",
      "propertyOrder" : 300,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "referrerWhiteList" : {
      "title" : "Referer Whitelist",
      "description" : "",
      "propertyOrder" : 400,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "usernameHeader" : {
      "title" : "Username Header Name",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    },
    "passwordHeader" : {
      "title" : "Password Header Name",
      "description" : "",
      "propertyOrder" : 200,
      "type" : "string",
      "exampleValue" : ""
    }
  }
},
```

```
"required" : [ "passwordHeader", "referrerWhiteList", "allowWithoutReferer", "usernameHeader" ]  
}
```

1.220.1.2. delete

Usage:

```
am> delete ZeroPageLoginCollector --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.220.1.3. getAllTypes

Obtain the collection of all secondary configuration types related to the resource.

Usage:

```
am> action ZeroPageLoginCollector --realm Realm --actionName getAllTypes
```

1.220.1.4. getCreatableTypes

Obtain the collection of secondary configuration types that have yet to be added to the resource.

Usage:

```
am> action ZeroPageLoginCollector --realm Realm --actionName getCreatableTypes
```

1.220.1.5. listOutcomes

List the available outcomes for the node type.

Usage:

```
am> action ZeroPageLoginCollector --realm Realm --body body --actionName listOutcomes
```

Parameters:

--body

The resource in JSON format, described by the following JSON schema:

```
{  
  "type" : "object",  
  "title" : "Some configuration of the node. This does not need to be complete against the  
  configuration schema."  
}
```

1.220.1.6. nextdescendents

Obtain the collection of secondary configuration instances that have been added to the resource.

Usage:

```
am> action ZeroPageLoginCollector --realm Realm --actionName nextdescendents
```

1.220.1.7. query

Get the full list of instances of this collection. This query only supports `_queryFilter=true` filter.

Usage:

```
am> query ZeroPageLoginCollector --realm Realm --filter filter
```

Parameters:

--filter

A CREST formatted query filter, where "true" will query all.

1.220.1.8. read

Usage:

```
am> read ZeroPageLoginCollector --realm Realm --id id
```

Parameters:

--id

The unique identifier for the resource.

1.220.1.9. update

Usage:

```
am> update ZeroPageLoginCollector --realm Realm --id id --body body
```

Parameters:

--id

The unique identifier for the resource.

--body

The resource in JSON format, described by the following JSON schema:


```

{
  "type" : "object",
  "properties" : {
    "allowWithoutReferer" : {
      "title" : "Allow Without Referer",
      "description" : "",
      "propertyOrder" : 300,
      "type" : "boolean",
      "exampleValue" : ""
    },
    "referrerWhiteList" : {
      "title" : "Referer Whitelist",
      "description" : "",
      "propertyOrder" : 400,
      "items" : {
        "type" : "string"
      },
      "type" : "array",
      "exampleValue" : ""
    },
    "usernameHeader" : {
      "title" : "Username Header Name",
      "description" : "",
      "propertyOrder" : 100,
      "type" : "string",
      "exampleValue" : ""
    },
    "passwordHeader" : {
      "title" : "Password Header Name",
      "description" : "",
      "propertyOrder" : 200,
      "type" : "string",
      "exampleValue" : ""
    }
  },
  "required" : [ "passwordHeader", "referrerWhiteList", "allowWithoutReferer", "usernameHeader" ]
}

```

Appendix A. Getting Support

For more information or resources about OpenAM and ForgeRock Support, see the following sections:

A.1. Accessing Documentation Online

ForgeRock publishes comprehensive documentation online:

- The ForgeRock Knowledge Base offers a large and increasing number of up-to-date, practical articles that help you deploy and manage ForgeRock software.

While many articles are visible to community members, ForgeRock customers have access to much more, including advanced information for customers using ForgeRock software in a mission-critical capacity.

- ForgeRock product documentation, such as this document, aims to be technically accurate and complete with respect to the software documented. It is visible to everyone and covers all product features and examples of how to use them.

A.2. Using the ForgeRock.org Site

The [ForgeRock.org](https://forgerock.org) site has links to source code for ForgeRock open source software, as well as links to the ForgeRock forums and technical blogs.

If you are a *ForgeRock customer*, raise a support ticket instead of using the forums. ForgeRock support professionals will get in touch to help you.

A.3. Getting Support and Contacting ForgeRock

ForgeRock provides support services, professional services, training through ForgeRock University, and partner services to assist you in setting up and maintaining your deployments. For a general overview of these services, see <https://www.forgerock.com>.

ForgeRock has staff members around the globe who support our international customers and partners. For details on ForgeRock's support offering, including support plans and service level agreements (SLAs), visit <https://www.forgerock.com/support>.