

PingGateway

July 7, 2025



PINGGATEWAY
Version: 2025.6

Copyright

All product technical documentation is
Ping Identity Corporation
1001 17th Street, Suite 100
Denver, CO 80202
U.S.A.

Refer to <https://docs.pingidentity.com> for the most current product documentation.

Trademark

Ping Identity, the Ping Identity logo, PingAccess, PingFederate, PingID, PingDirectory, PingDataGovernance, PingIntelligence, and PingOne are registered trademarks of Ping Identity Corporation ("Ping Identity"). All other trademarks or registered trademarks are the property of their respective owners.

Disclaimer

The information provided in Ping Identity product documentation is provided "as is" without warranty of any kind. Ping Identity disclaims all warranties, either express or implied, including the warranties of merchantability and fitness for a particular purpose. In no event shall Ping Identity or its suppliers be liable for any damages whatsoever including direct, indirect, incidental, consequential, loss of business profits or special damages, even if Ping Identity or its suppliers have been advised of the possibility of such damages. Some states do not allow the exclusion or limitation of liability for consequential or incidental damages so the foregoing limitation may not apply.

Table of Contents

PingGateway	10
Introduction to PingGateway.	13
PingGateway as a reverse proxy	15
PingGateway as a forward proxy.	16
PingGateway as a microgateway.	17
Object model	18
Sessions	19
API descriptors	22
Get started	25
Download PingGateway.	27
Prepare the network	27
Start and stop PingGateway	28
Use the sample application.	29
Protect an application with PingGateway.	31
Next steps.	33
Install	36
Prepare to install.	38
Download PingGateway.	44
Start and stop PingGateway	44
Set up environment variables and system properties	47
Encrypt and share JWT sessions	49
Prepare for load balancing and failover.	61
Secure connections	63
FIPS 140-3 compliance	79
Configure	81
Configuration files and routes	83
Routes and common REST	87
Decorators	89
Operating modes	95
Configuration templates	98
Extend	113
Upgrade.	140
Plan the upgrade.	142
Upgrade.	142
Migrate from web container mode to standalone mode	146
Deploy with Docker	147
Build and run a Docker image	149

Add configuration to a Docker image	152
Gateway guide	154
Authentication	158
Single sign-on	159
Use the default journey	160
Use a specific journey	163
Cross-domain single sign-on	164
Password replay with AM	170
Password replay from a database	179
Password replay from a file	184
Session cache eviction	188
Policy enforcement	189
Enforce AM policy decisions.	193
Decisions in the same domain	193
Require authentication to a realm	196
Decisions in different domains	199
Decisions with claimsSubject	202
Notifications and the policy cache	204
Harden authorization	205
Step up the authentication level	205
Authorize a single transaction.	207
OAuth 2.0	211
Validate access tokens with introspection	214
Script required scopes	219
Validate stateless access tokens	222
With JwkSetSecretStore	223
Signed tokens with KeyStoreSecretStore	227
Encrypted tokens with KeyStoreSecretStore	234
Mutual TLS.	238
mTLS with client certificates.	239
mTLS with trusted headers	251
OAuth 2.0 context for authentication	257
Cache access tokens	261
Client credentials grant	265
Resource owner password credentials grant	270
OpenID Connect	276
AM as OIDC provider.	277
Multiple OIDC providers	282
Discovery and dynamic registration	285
ID token validation	291
Pass data along the chain.	293

SAML.	322
AM as IdP	
Unsigned/unencrypted assertions	325
Signed/encrypted assertions	330
SamlFederationHandler (deprecated)	
About SP-initiated SSO with the SamlFederationHandler	334
About IdP-initiated SSO	335
Unsigned/unencrypted assertions	336
Signed/encrypted assertions	342
SAML 2.0 and multiple applications	346
Additional topics	
Non-transient NameID format	349
Example Fedlet files.	350
Token transformation.	371
OIDC ID tokens to SAML assertions	372
OAuth 2.0 token exchange	380
Not-enforced URIs	387
POST data preservation.	393
CSRF protection	399
Throttling	403
URI fragments in redirect.	414
JWT validation	418
WebSocket traffic	422
UMA support	426
Protect PingAM.	438
PingGateway as a microgateway.	443
PingOne.	445
PingOne as OIDC provider	448
PingOne as SAML IdP	452
PingOne Authorize integration.	456
PingOne Protect integration	465
PingOne Advanced Identity Cloud.	475
Overview	480
OAuth 2.0	481
OpenID Connect	485
Cross-domain single sign-on	488
Password replay	492
Policy enforcement	504
Proxy Connect	509
Pass runtime data downstream in a JWT	517
Secure the OAuth 2.0 access token endpoint	523
Studio	527
Start with Studio	529
Upgrade from an earlier version of Studio	530

Create and edit routes with Structured Editor (deprecated)	530
Create and edit routes with Freeform Designer	533
Edit and import routes	535
Restrict access to Studio	536
Example routes created with Structured Editor (deprecated)	539
Example routes created with Freeform Designer	552
Summary of tasks, route status, and icons	562
Maintenance	564
Audit the deployment	566
Monitor services	594
Manage sessions	603
Manage logs	603
Tune performance	612
Rotate keys	618
Secure and harden.	628
Troubleshoot	630
Security	635
Access	637
Threats	640
Operating systems.	642
Network connections	644
Keys and secrets	645
Audits and logs	649
Reference	649
Required configuration	654
AdminHttpApplication (admin.json)	654
GatewayHttpApplication (config.json)	674
Heap objects	680
Configuration settings	681
System properties	681
Handlers	682
Chain	683
ClientHandler	684
DispatchHandler	695
ForgeRockClientHandler.	697
IdentityAssertionHandler	697
JwkSetHandler	703
PingOneProtectThreatLevelRoutingHandler	707
ResourceHandler	709
ReverseProxyHandler	711
Route.	722
Router	727

SamlFederationHandler (deprecated)	730
ScriptableHandler	734
SequenceHandler.	735
StaticResponseHandler	736
Filters	739
AllowOnlyFilter	741
AmSessionIdleTimeoutFilter	747
AssignmentFilter	753
AuthorizationCodeOAuth2ClientFilter	755
CapturedUserPasswordFilter	767
CertificateThumbprintFilter	768
ChainOfFilters.	770
CircuitBreakerFilter	771
ClientCredentialsOAuth2ClientFilter	774
ClientSecretBasicAuthenticationFilter	775
ClientSecretPostAuthenticationFilter	776
ConditionEnforcementFilter.	777
ConditionalFilter	778
CookieFilter	779
CorsFilter	781
CrossDomainSingleSignOnFilter	784
CsrfFilter	791
DataPreservationFilter.	793
DateHeaderFilter	794
EncryptedPrivateKeyJwtClientAuthenticationFilter	795
EntityExtractFilter	798
FapiInteractionIdFilter	800
FileAttributesFilter	801
ForwardedRequestFilter.	803
FragmentFilter	805
GrantSwapJwtAssertionOAuth2ClientFilter	807
HeaderFilter.	812
HttpBasicAuthFilter	816
HttpBasicAuthenticationClientFilter	818
IdTokenValidationFilter	824
JwtBuilderFilter	828
JwtValidationFilter	832
LocationHeaderFilter.	836
OAuth2ResourceServerFilter	837
OAuth2TokenExchangeFilter	842
PasswordReplayFilter	845
PingOneApiAccessManagementFilter	848
PingOneProtectEvaluationFilter	850
PingOneProtectFeedbackFailureFilter	854

PingOneProtectFeedbackSuccessFilter	855
PolicyEnforcementFilter	856
PrivateKeyJwtClientAuthenticationFilter.	865
ResourceOwnerOAuth2ClientFilter	867
SamlFederationFilter.	869
ScriptableFilter	876
SessionInfoFilter	877
SetCookieUpdateFilter.	879
SingleSignOnFilter	881
SqlAttributesFilter	885
StaticRequestFilter	887
SwitchFilter	891
ThrottlingFilter	893
TokenTransformationFilter	895
TransactionIdOutboundFilter.	897
UmaFilter	897
UriPathRewriteFilter	898
UserProfileFilter	904
Decorators	907
BaseUriDecorator	907
CaptureDecorator	909
TimerDecorator.	916
TracingDecorator.	919
Audit framework	920
AuditService.	921
CsvAuditEventHandler.	925
JdbcAuditEventHandler	929
JmsAuditEventHandler.	936
JsonAuditEventHandler	940
JsonStdoutAuditEventHandler	944
NoOpAuditService	946
SyslogAuditEventHandler	947
Monitoring	951
Monitoring types	951
Metrics at the Prometheus Scrape Endpoint	952
Metrics at the Common REST Monitoring Endpoint (deprecated)	960
Throttling policies	962
DefaultRateThrottlingPolicy.	962
MappedThrottlingPolicy	963
ScriptableThrottlingPolicy.	967
Miscellaneous configuration objects	970
AmService	971
ClientRegistration	981
ClientTlsOptions	985

Delegate	988
InMemorySessionManager	989
Issuer.	991
IssuerRepository (deprecated)	996
JdbcDataSource.	997
JwtSession (deprecated)	999
JwtSessionManager	1004
KerberosIdentityAssertionPlugin.	1008
KeyManager (deprecated).	1012
KeyStore (deprecated)	1014
PingOneService	1015
ProxyOptions	1016
RequestResourceUriProvider	1018
ScheduledExecutorService	1019
ScriptableIdentityAssertionPlugin	1021
ScriptableResourceUriProvider	1023
ServerTlsOptions	1024
TemporaryStorage	1029
TrustAllManager	1030
UmaService	1030
Property value substitution.	1034
Configuration Tokens	1035
Token Resolution	1036
JSON Evaluation.	1038
Transformations	1039
Expressions	1045
Functions	1055
Patterns	1072
Scripts	1072
Route properties	1081
Contexts.	1086
AttributesContext	1090
AuthRedirectContext.	1091
CapturedUserPasswordContext	1092
CdSsoContext	1092
CdSsoFailureContext.	1093
ClientContext	1093
FileAttributesContext	1095
IdentityRequestJwtContext	1095
IdpSelectionLoginContext.	1096
JwtBuilderContext	1096
JwtValidationContext.	1096
JwtValidationErrorContext.	1097
OAuth2Context	1098

OAuth2FailureContext	1098
OAuth2TokenExchangeContext	1099
PingOneProtectDeviceProfileContext	1100
PingOneProtectEvaluationContext	1101
PolicyDecisionContext	1101
SessionContext	1103
SessionInfoContext	1103
SqlAttributesContext	1105
SsoTokenContext	1105
StsContext	1105
TransactionIdContext	1106
UriRouterContext	1106
UserProfileContext	1107
Requests and responses	1108
Request	1108
Response	1109
Status	1110
URI	1111
Access token resolvers	1112
CacheAccessTokenResolver	1113
ConfirmationKeyVerifierAccessTokenResolver	1116
ScriptableAccessTokenResolver	1117
StatelessAccessTokenResolver	1118
TokenIntrospectionAccessTokenResolver	1119
Caches	1121
Secrets	1122
Base64EncodedSecretStore	1123
FileSystemSecretStore	1125
HsmSecretStore	1128
JwkPropertyFormat	1134
JwkSetSecretStore	1135
KeyStoreSecretStore	1138
PemPropertyFormat	1146
SecretsKeyManager	1147
SecretKeyPropertyFormat	1149
SecretsProvider	1150
SecretsTrustManager	1152
SystemAndEnvSecretStore	1154
TrustManager (deprecated)	1156
Supported standards	1157
Internationalization	1159
About Common REST	1160

PingGateway

PingGateway uses Ping Identity Platform capabilities to protect web applications, APIs, and microservices.



Release notes

- [All versions](#) 



Get started with PingGateway

- [Getting started with PingGateway](#)
- [Installing PingGateway](#)
- [PingGateway upgrades](#)



Use PingGateway

- [With PingOne](#)
- [With PingOne Advanced Identity Cloud](#)
- [With PingAM](#)



Troubleshoot PingGateway

- [Maintaining PingGateway deployments](#)
- [Managing PingGateway logs](#)
- [Troubleshooting PingGateway issues](#)



Learn More

- [PingGateway community](#)
- [Support portal](#)
- [Partner portal \(partners\)](#)

Introduction to PingGateway

PingGateway uses Ping Identity Platform capabilities to protect web applications, APIs, and microservices.



Reverse proxy

Front protected applications with PingGateway.



Forward proxy

Add capabilities to applications with PingGateway.



Microservice

Run PingGateway as a microgateway in containerized environments.



Object model

Understand the PingGateway processing model.



Sessions

Understand PingGateway sessions.




API descriptors

Get API descriptors for PingGateway endpoints.

PingGateway as a reverse proxy

As a reverse proxy, PingGateway is an intermediate connection point between external clients and internal services. PingGateway intercepts client requests and server responses, enforcing policies, and routing and shaping traffic.

The following image illustrates PingGateway as a reverse proxy:




PingGateway provides the following features as a reverse proxy:

- Ping Identity Platform integration
- Application and API security
- Credential replay
- OAuth 2.0 support
- OpenID Connect 1.0 support
- Network traffic control
- Proxy with request and response capture
- Request and response rewriting
- SAML 2.0 federation support
- Single sign-on (SSO)

PingGateway as a forward proxy

As a forward proxy, PingGateway is an intermediate connection point between an internal client and an external service. PingGateway regulates outbound traffic to the service and can adapt and enrich requests.

The following image illustrates PingGateway as a forward proxy:




PingGateway provides the following features as a forward proxy:

- Addition of authentication or authorization to the request
- Addition of tracer IDs to the requests
- Addition or removal of request headers or scopes

PingGateway as a microgateway

In containerized environments, PingGateway runs as a microgateway. Use PingGateway with business microservices to separate the security concerns of your applications from their business logic. For example, use PingGateway with the Token Validation Microservice to provide access token validation at the edge of your namespace. Find an example in [PingGateway as a microgateway](#).

The following image illustrates the request flow in an example deployment:




PingGateway processes the request in the following steps:

1. A client requests access to Secured Microservice A, providing a stateful OAuth 2.0 access token as credentials.
2. Microgateway A intercepts the request and passes the access token to the Token Validation Microservice for validation using the `/introspect` endpoint.
3. The Token Validation Microservice requests the Authorization Server to validate the token.
4. The Authorization Server introspects the token and sends the introspection result to the Token Validation Microservice.
5. The Token Validation Microservice caches the introspection result and sends it to Microgateway A. Microgateway A forwards the result to Secured Microservice A.
6. Secured Microservice A uses the introspection result to decide how to process the request. In this case, it continues processing the request. Secured Microservice A asks for additional information from Secured Microservice B, providing the validated token as credentials.
7. Microgateway B intercepts the request and passes the access token to the Token Validation Microservice for validation using the `/introspect` endpoint.
8. The Token Validation Microservice retrieves the introspection result from the cache and sends it back to Microgateway B. Microgateway B forwards the result to Secured Microservice B.
9. Secured Microservice B uses the introspection result to decide how to process the request. In this case, it passes its response to Secured Microservice A through Microgateway B.
10. Secured Microservice A passes its response to the client through Microgateway A.

PingGateway object model

PingGateway processes HTTP requests and responses by passing them through user-defined chains of filters and handlers. The filters and handlers can access the request and response at each step in the chain. They make it possible to alter the request or response and collect contextual information.

The following image illustrates how PingGateway processes a request and response through a chain:



When PingGateway processes a request, it first builds an object representation of the request. The object representation includes parsed query/form parameters, cookies, headers, and the entity. PingGateway initializes a runtime context to provide metadata about the request and applied transformations. PingGateway passes the request representation into the chain.

In the request flow, filters modify the request representation and can enrich the runtime context with computed information. A **ClientHandler** serializes the entity content and can encode additional query parameters as described in [RFC 3986: Query](#).

In the response flow, filters build a response representation with headers and the entity.

The route configuration in [Adding headers and logging results](#) shows the flow through a chain to a protected application.

PingGateway sessions

PingGateway uses sessions to group requests from a user-agent or other source and to collect and share information across the requests.

PingGateway supports [stateful](#) and [stateless](#) sessions.

- For stateful sessions, PingGateway stores the session data (default). It sets a session cookie on the user-agent that references the session.

- For stateless sessions, the user-agent stores the session data, and PingGateway puts the session data in a JWT stored as one or more session cookies on the user-agent.

Handlers and filters can access session data through the [SessionContext](#).

Session sharing is not thread-safe, so it is not suitable for concurrent exchanges.

Stateful and stateless sessions

Feature	Stateful sessions	Stateless sessions
Cookie size	Unlimited	The maximum size of the JWT session cookie for a user-agent is 4 KBytes. If the cookie exceeds this size, PingGateway automatically splits it into multiple cookies.
Default session cookie name	<code>IG_SESSIONID</code>	<code>openid-jwt-session</code>
Data types the session can store	All types	JSON-compatible types [↗] , such as strings, numbers, booleans, null, and arrays, lists, and maps containing only JSON-compatible types.
Session sharing between PingGateway servers for load balancing and failover	Possible using session stickiness	Possible because the session is a cookie on the user-agent; PingGateway servers must share any encryption keys.
Risk of data inconsistency when simultaneous requests modify the content of a session	Low because PingGateway stores the session content for all exchanges. Processing is not thread-safe.	Higher because the session content is reconstructed from the JWT for each request. Concurrent exchanges don't have the same content.

Stateful sessions

PingGateway uses stateful sessions by default.

To configure sessions explicitly, use an [InMemorySessionManager](#) as the `"session"` in the [AdminHttpApplication](#) (`admin.json`) for administrative requests and the [GatewayHttpApplication](#) (`config.json`) or individual [Route](#) for other requests.

The default session duration is 30 minutes. Even if the session is empty, the session remains usable until the timeout.

PingGateway can store any object type in a stateful session.

Because PingGateway stores stateful session content and shares it across all exchanges, simultaneous requests can update the session with low risk of the data becoming inconsistent. Sessions aren't thread-safe, however; different requests can simultaneously read and modify a shared session.

Stateless sessions

To configure stateless sessions, use a [JwtSessionManager](#) for the `"session"` in the [AdminHttpApplication \(admin.json \)](#) for administrative requests and the [GatewayHttpApplication \(config.json \)](#) or individual [Route](#) for other requests.

PingGateway serializes session information as a JWT that is encrypted using authenticated encryption and optionally compressed. PingGateway stores the JWT in one or more session cookies on the user-agent. The JWT contains session attributes as JSON with a marker for the session timeout:

- PingGateway can only serialize [JSON-compatible types](#) in JWT session cookies.
- The maximum size of the JWT session cookie for a user-agent is 4 KBytes. If the cookie exceeds this size, PingGateway automatically splits it into multiple cookies.
- When PingGateway serializes an empty session, it marks the supporting cookie as expired, so the user-agent effectively discards it.

To prevent PingGateway from cleaning up empty session cookies, add information to the session context with an [AssignmentFilter](#).

PingGateway manages stateless sessions as follows:

- When a request enters a route using stateless sessions, PingGateway creates the `SessionContext`, verifies the cookie signature, decrypts the content of the cookie, and checks the current date is before the session timeout.
- As the request passes through the filters and handlers in the route, the filters and handlers can read and modify the session content.
- When the request returns to the point where the session was created, such the entrance to a route or `config.json`, PingGateway updates the cookie as follows:
 - If the session content has changed, PingGateway serializes the session, creates one or more new JWT session cookies with the new content, encrypts the cookies using authenticated encryption, assigns them an appropriate expiration time, and returns them in the response.
 - If the session is empty, PingGateway deletes the session, creates a new expired JWT session cookie, and returns the cookie in the response.
 - If the session content has not changed, PingGateway does nothing.

Because the session content is stored on the user-agent, PingGateway servers can easily share stateless sessions. The user-agent returns the JWT cookies and any PingGateway server can unpack and use the session content.

When PingGateway updates stateless sessions in simultaneous requests, there is a high risk of the data becoming inconsistent. PingGateway reconstructs the session content for each exchange. Concurrent exchanges don't have the same content. PingGateway doesn't share sessions across requests. Each request has its own session objects that it modifies as necessary, writing its own session to the session cookie regardless of what other requests do.

Session stickiness

Session stickiness helps ensure a client request goes to the server holding the original session data. With session stickiness, a load balancer in front of multiple PingGateway servers sends all requests from the same client session to the same server.

How you configure session stickiness depends on your load balancer.

Configure session stickiness whenever PingGateway stores session data attached to a server-side context. For example, configure session stickiness when using stateful sessions and multiple PingGateway servers.

PingGateway API descriptors

Common REST endpoints in PingGateway serve API descriptors at runtime.

When you get an API descriptor for an endpoint, PingGateway returns a resource describing the APIs at the endpoint and any child endpoints. Use the API descriptor with an OpenAPI tool like [Swagger UI](#) to generate documentation.

When you start PingGateway or add or edit routes, PingGateway records endpoint locations in the PingGateway `logs/route-system.log` file and endpoint locations for subroutes in the specific log files for the routes.

To get the API descriptor for a specific endpoint, PingGateway must be in development mode. Make an HTTP GET request to the endpoint with one of the following query string parameters:

- `_api` for the API accessible over HTTP.

You can get this API descriptor for partial URLs.

The JSON API descriptor follows the OpenAPI specification.

- `_crestapi` for a proprietary, compact representation independent of the transport protocol.

You can't get this API descriptor for partial URLs.

The JSON API descriptor follows the proprietary specification for Common REST endpoints.

Learn more in [Common REST API documentation](#).

Get API descriptors for a router



Important

Switch to [development mode](#) to get API descriptors.

With PingGateway running as described in [Getting started with PingGateway](#), use the following query to get an API descriptor for the router:

```
$ curl http://ig.example.com:8085/api/system/objects/_router/routes\?_api
```

Output

```
{
  "swagger": "2.0",
  "info": {
    "version": "2025.6.1",
    "title": "PingGateway"
  },
  "host": "0:0:0:0:0:0:0:1",
  "basePath": "/api/system/objects/_router/routes",
  "tags": [
    {
      "name": "Routes Endpoint"
    }
  ],
  "...": "..."
}
```

Alternatively, get a Common REST API descriptor with the `?_crestapi` query string.

Get an API descriptor for the UMA service



Important

Switch to [development mode](#) to get API descriptors.

With the UMA tutorial running as described in [UMA support with PingAM](#), use the following query to get an API descriptor for the UMA share API:

```
$ curl http://ig.example.com:8085/api/system/objects/_router/routes/00-uma/objects/umaservice/share?\_api
```

Output

```
{
  "swagger": "2.0",
  "info": {
    "version": "2025.6.1",
    "title": "PingGateway"
  },
  "host": "0:0:0:0:0:0:0:1",
  "basePath": "/api/system/objects/_router/routes/00-uma/objects/umaservice/share",
  "tags": [
    {
      "name": "Manage UMA Share objects"
    }
  ],
  "...": "..."
}
```

Alternatively, get a Common REST API descriptor with the `?_crestapi` query string.

Get an API descriptor for the main router



Important

Switch to [development mode](#) to get API descriptors.

With PingGateway running, use the following query to get an API descriptor for the main router and child endpoints:

```
$ curl http://ig.example.com:8085/api/system/objects/_router?_api
```

Output

```
{
  "swagger": "2.0",
  "info": {
    "version": "2025.6.1",
    "title": "PingGateway"
  },
  "host": "ig.example.com:8085",
  "basePath": "/api/system/objects/_router",
  "tags": [
    {
      "name": "Monitoring endpoint"
    },
    {
      "name": "Manage UMA Share objects"
    },
    {
      "name": "Routes Endpoint"
    }
  ],
  "...": "..."
}
```

The above URL is a partial URL, so you can't use the `?_crestapi` query string to get a Common REST API descriptor.

Get an API descriptor for PingGateway instances



Important

Switch to [development mode](#) to get API descriptors.

With a PingGateway instance running, use the following query to get an API descriptor:

```
$ curl http://ig.example.com:8085/api?_api
```


Output

```
{
  "swagger": "2.0",
  "info": {
    "version": "2025.6.1",
    "title": "PingGateway"
  },
  "host": "ig.example.com:8085",
  "basePath": "/api",
  "tags": [
    {
      "name": "Internal Storage for UI Models"
    },
    {
      "name": "Monitoring endpoint"
    },
    {
      "name": "Manage UMA Share objects"
    },
    {
      "name": "Routes Endpoint"
    },
    {
      "name": "Server Info"
    }
  ],
  "...": "..."
}
```

If you add routes after the request is performed, run the query again to get the updated API descriptor.

The above URL is a partial URL, so you can't use the `?_crestapi` query string to get a Common REST API descriptor.

Getting started with PingGateway

Use this guide to get a quick, hands-on look at what PingGateway software can do. You will download, install, and use PingGateway on your local computer. Find more installation options in [Installing PingGateway](#).

This guide assumes familiarity with the following topics:

- HTTP, including how clients and servers exchange messages, and the role that a reverse proxy (gateway) plays
- JSON, the format for PingGateway configuration files
- Managing services on operating systems and application servers
- Configuring network connections on operating systems

Product names changed when ForgeRock became part of Ping Identity. PingGateway was formerly known as ForgeRock Identity Gateway, for example. Learn more about the name changes from [New names for ForgeRock products](#).

Downloading PingGateway

The .zip file unpacks into a `/path/to/identity-gateway-2025.6.1` directory with the following content:

- `bin`: Start and stop executables
- `classes`: Initially empty; used to install patches from support
- `docker/Dockerfile`: Dockerfile and README to build a PingGateway Docker image
- `legal-notices`: Licenses and copyrights
- `lib`: PingGateway and third-party libraries

1. Create a local installation directory for PingGateway like `/path/to`.



Important

The installation directory should be a new, empty directory. Installing PingGateway into an existing installation directory can cause errors.

2. Download `PingGateway-2025.6.1.zip` from the [Backstage download site](#), and copy the .zip file to the installation directory:

```
$ cp PingGateway-2025.6.1.zip /path/to/PingGateway-2025.6.1.zip
```

3. Unzip the file:

```
$ unzip PingGateway-2025.6.1.zip
```

The directory `/path/to/identity-gateway-2025.6.1` is created.

Preparing the network for PingGateway

Configure the network to include hosts for PingGateway, AM, and the sample application. Learn more about hosts files in [Hosts \(file\)](#).

Add the following entry to your hosts file:

```
127.0.0.1 localhost ig.example.com app.example.com am.example.com
```

The hosts file path depends on the platform:

Linux

```
/etc/hosts
```

Windows

```
%SystemRoot%\system32\drivers\etc\hosts
```

Starting and stopping PingGateway

Start PingGateway with default settings

When you start PingGateway, specify the configuration directory where PingGateway looks for configuration files.

1. Start PingGateway:

Linux

```
/path/to/identity-gateway-2025.6.1/bin/start.sh
```

Windows

```
C:\path\to\identity-gateway-2025.6.1\bin\start.bat
```

By default, PingGateway configuration files are located under `$HOME/.openig` on Linux, `%appdata%\OpenIG` on Windows. Learn how to use a different location in [Configuration location](#).

2. Check that PingGateway is running in one of the following ways:

- Check the PingGateway endpoint at `http://ig.example.com:8085/health/startup` to make sure PingGateway it returns `HTTP 200 OK`.

If PingGateway hasn't finished starting up or is shutting down, the endpoint returns `HTTP 503 Service Unavailable`.

- Display the product version and build information at `http://ig.example.com:8085/api/info`.

Stop PingGateway

Use the `stop.sh` or `stop.bat` script to stop an instance of PingGateway, specifying the instance directory as an argument.

If the instance directory isn't specified, PingGateway uses the default instance directory as in these examples:

Linux

```
/path/to/identity-gateway-2025.6.1/bin/stop.sh $HOME/.openig
```

Windows

```
C:\path\to\identity-gateway-2025.6.1\bin\stop.bat %appdata%\OpenIG
```

Using the sample application

Ping Identity provides a mockup web application for testing PingGateway configurations. The sample application is used in the examples throughout the PingGateway documentation.

Download the sample application

1. Download `PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar`, from the [Backstage download site](#).

Start the sample application

1. Start the sample application:

```
$ java -jar PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar
```

Output

```
...  
[...] [INFO    ] Press Ctrl+C to stop the server.
```

By default this server listens for HTTP on port 8081 and for HTTPS on port 8444. If one or both of those ports aren't free, specify other ports:

```
$ java -jar PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar 8888 8889
```

By default, OpenTelemetry support is disabled in the sample application. To enable it, set `OTEL_SDK_DISABLED=false` when starting the sample application:

```
$ OTEL_SDK_DISABLED=false java -jar PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar
```

The tracing configuration for the sample application uses automatic configuration. For example, to enable OpenTelemetry support and publish to a remote service:

```
$ OTEL_SDK_DISABLED=false \
OTEL_EXPORTER_OTLP_TRACES_ENDPOINT=http://exporter.example.com:1234/traces \
java -jar PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar
```

Learn more about configuration options in the OpenTelemetry documentation on [automatic configuration](#). The sample application supports only `http/protobuf` for the exporter protocol.

2. Check that the sample application is running in one of the following ways:

1. Go to <http://app.example.com:8081/home> to access the home page of the sample application. Information about the browser request is displayed.
2. Go to <http://app.example.com:8081/login> to access the login page of the sample application, and then log in with username `demo` and password `Ch4ng31t`. The username and some information about the browser request is displayed.

Stop the sample application

In the terminal where the sample application is running, enter CTRL+C to stop the sample application.

Serve static resources

When the sample application is used with PingGateway in examples, it must serve static resources, such as the .css. Similarly, browser requests often serve resources that don't need protection, such as icons and .gif files.

Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/..*\\\\\\.ico$') or matchesWithRegex(request.uri.path, '^/..*\\\\\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

Configuration options

To view the command-line options for the sample application, start it with the `-h` option:

```
$ java -jar PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar -h
```


Output

```
Usage: <main class> [options]
Options:
  --http
    The HTTP port number.
    Default: 8081
  --https
    The HTTPS port number.
    Default: 8444
  --session
    The session timeout in seconds.
    Default: 60
  --am-discovery-url
    The AM URL base for OpenID Provider Configuration.
    Default: http://openam.example.com:8088/openam/oauth2
  --latency
    The simulated request latency in seconds.
    Default: 2
  -h, --help
    Default: false
```

Protecting an application with PingGateway

This section gives a simple example of how to use PingGateway to protect an application. For many more examples of how to protect applications with PingGateway, refer to the [Gateway guide](#).

In the following example, a browser requests access to the sample application, and PingGateway intercepts the request to log the user into the application. The following image shows the flow of data in the example:



1. The browser sends an HTTP GET request to the HTTP server on `ig.example.com`.
2. PingGateway replaces the HTTP GET request with an HTTP POST login request containing credentials to authenticate.
3. The sample application validates the credentials, and returns the page for the user `demo`.

If PingGateway did not provide the credentials, or if the sample application couldn't validate the credentials, the sample application returns the login page.

4. PingGateway returns this response to the browser.

Configure PingGateway to log you in to an application

1. Set up PingGateway and the sample application as described in this guide.
2. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name": "00-static-resources",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^.*\\.ico$') or matchesWithRegex(request.uri.path, '^.*\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/01-static.json
```

Windows

```
%appdata%\OpenIG\config\routes\01-static.json
```



```
{
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "StaticRequestFilter",
          "config": {
            "method": "POST",
            "uri": "http://app.example.com:8081/login",
            "form": {
              "username": [
                "demo"
              ],
              "password": [
                "Ch4ng31t"
              ]
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  },
  "condition": "${find(request.uri.path, '^/static')}"
}
```

Source: [01-static.json](#)

Notice the following features of the route:

- The route matches requests to `/static`.
- The StaticRequestFilter replaces the request with an HTTP POST, specifying the resource to post the request to, and a form to include in the request. The form includes credentials for the username `demo`.
- The ReverseProxyHandler replays the request to the sample application.

4. Check that the route system log includes a message that the new files are loaded into the config:

```
INFO o.f.o.handler.router.RouterHandler - Loaded the route with id '00-static-resources' registered with the
name '00-static-resources'
INFO o.f.o.handler.router.RouterHandler - Loaded the route with id '01-static' registered with the name '01-
static'
```

5. Go to <http://ig.example.com:8080/static>.

You are directed to the sample application, and logged in automatically with the username `demo`.

Next steps with PingGateway

This section describes some basic options to help you with PingGateway. Learn about other installation options in [Installing PingGateway](#).

Add a base configuration file

The entry point for requests coming in to PingGateway is a JSON-encoded configuration file, expected by default at:

Linux

```
$HOME/.openig/config/config.json
```

Windows

```
%appdata%\OpenIG\config\config.json
```

The base configuration file initializes a heap of objects and provides the main handler to receive incoming requests. Configuration in the file is inherited by all applicable objects in the configuration.

At startup, if PingGateway doesn't find a base configuration file, it provides a default version given in [Default configuration](#). The default looks for routes in:

Linux

```
$HOME/.openig/config/routes
```

Windows

```
%appdata%\OpenIG\config\routes
```

Consider adding a custom `config.json` for these reasons:

- To prevent using the default `config.json`, whose configuration might not be appropriate in your deployment.
- To define an object once in `config.json`, and then use it multiple times in your configuration.

After adding or editing `config.json`, stop and restart PingGateway to bring the changes into effect.

Learn more in [GatewayHttpApplication \(config.json \)](#), [Heap objects](#), and [Router](#).

Add a base configuration for PingGateway

1. Add the following file to PingGateway:

Linux

```
$HOME/.openig/config/config.json
```

Windows

```
%appdata%\OpenIG\config\config.json
```

```
{
  "handler": {
    "type": "Router",
    "name": "_router",
    "capture": "all"
  },
  "heap": [
    {
      "name": "capture",
      "type": "CaptureDecorator",
      "config": {
        "captureEntity": true,
        "_captureContext": true
      }
    }
  ],
  "session": {
    "type": "JwtSessionManager"
  }
}
```

Source: [config.json](#)

Notice the following features of the file:

- The handler contains a main router named `_router`. When PingGateway receives an incoming request, `_router` routes the request to the first route in the configuration whose condition is satisfied.
- The `capture` captures the body of the HTTP request and response.
- The configuration uses stateless sessions. Learn more in [PingGateway sessions](#).

2. Stop and restart PingGateway.

3. Check that the route system log includes a message that the file is loaded into the config:

```
INFO o.f.openig.web.Initializer - Reading the configuration from ...config.json
```

Add a default route

When there are multiple routes in the PingGateway configuration, they are ordered lexicographically, by route name. For example, `01-static.json` is ordered before `zz-default.json`.

When PingGateway processes a request, the request traverses the routes in the configuration. If the request matches the condition for `01-static.json` it is processed by that route. Otherwise, it passes to the next route in the configuration. If a route has no condition, it can process any request.

A default route is the last route in a configuration to which a request is routed. If a request matches no other route in the configuration, it is processed by the default route.

Add a default route to prevent errors described in [No handler to dispatch to](#).

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/zz-default.json
```

Windows

```
%appdata%\OpenIG\config\routes\zz-default.json
```

```
{
  "baseURI": "http://app.example.com:8081",
  "handler": "ReverseProxyHandler"
}
```

Source: [zz-default.json](#)

Notice the following features of the route:

- The route name starts with `zz`, so it is the last route loaded into the configuration.
- There is no `condition` property, so the route processes all requests.
- The route calls a `ReverseProxyHandler` with the default configuration, which proxies the request to the application and returns the response, without changing either the request or the response.

2. Check that the route system log includes a message that the file is loaded into the config:

```
INFO o.f.o.handler.router.RouterHandler - Loaded the route with id
'zz-default' registered with the name 'zz-default'
```

Switch from production mode to development mode

To prevent unwanted changes to the configuration, PingGateway is by default in production mode after installation. For a description of the modes and information about switching between modes, refer to [PingGateway operating modes](#).

Use PingGateway Studio

PingGateway Studio is a user interface to help you build and deploy your PingGateway configuration. Learn more in [PingGateway Studio](#).

Installing PingGateway

These pages describe how to install and remove PingGateway software. Learn how to install PingGateway for evaluation in [Getting started with PingGateway](#).

Read the [Release notes](#) before you install PingGateway.

Product names changed when ForgeRock became part of Ping Identity. PingGateway was formerly known as ForgeRock Identity Gateway, for example. Learn more about the name changes from [New names for ForgeRock products](#).

Preparing to install PingGateway

Before you install, make sure your installation meets the requirements in the [release notes](#).

Create a PingGateway service account

To limit the impact of a security breach, install and run PingGateway from a dedicated service account. This is optional when evaluating PingGateway, but essential in production installations.

A hacker is constrained by the rights granted to the user account where PingGateway runs; therefore, never run PingGateway as root user.

1. In a terminal window, use a command similar to the following to create a service account:

Linux

```
$ sudo /usr/sbin/useradd \  
--create-home \  
--comment "Account for running PingGateway" \  
--shell /bin/bash PingGateway
```

Windows

```
net user username password /add /comment:"Account for running PingGateway"
```

2. Apply the principle of least privilege to the account, for example:
 - Read/write permissions on the installation directory, `/path/to/identity-gateway-2025.6.1`.
 - Execute permissions on the scripts in the installation `bin` directory, `/path/to/identity-gateway-2025.6.1/bin`.

Preparing the network for PingGateway

Configure the network to include hosts for PingGateway, AM, and the sample application. Learn more about hosts files in [Hosts \(file\)](#).

Add the following entry to your hosts file:

```
127.0.0.1 localhost ig.example.com app.example.com am.example.com
```

The hosts file path depends on the platform:

Linux

```
/etc/hosts
```

Windows

```
%SystemRoot%\system32\drivers\etc\hosts
```

Set up PingOne Advanced Identity Cloud

This documentation contains procedures for setting up items in PingOne Advanced Identity Cloud that you can use with PingGateway. For more information about setting up PingOne Advanced Identity Cloud, refer to the [PingOne Advanced Identity Cloud documentation](#).

About authentication to PingOne Advanced Identity Cloud

PingOne Advanced Identity Cloud provides an authentication journey to validate the agent credentials with an Agent Data Store Decision node.

When you register PingGateway with PingOne Advanced Identity Cloud, PingOne Advanced Identity Cloud uses the journey to authenticate PingGateway.

Register a PingGateway agent in PingOne Advanced Identity Cloud

This procedure registers an agent profile for PingGateway.

1. Log in to the Advanced Identity Cloud admin UI as an administrator.
2. Click  **Gateways & Agents** > **+ New Gateway/Agent** > **Identity Gateway** > **Next** and use the hints in the following table to create the agent profile:

Field	Description	Example
ID	Set the unique agent profile name PingGateway uses to connect.	ig_agent

Field	Description	Example
Password	Store the password PingGateway uses to connect in the agent profile. Record the password to use when configuring PingGateway.	A strong password. The examples in the documentation use <code>password</code> and its base64-encoding <code>cGFzc3dvcmQ=</code> .
Use Secret Store for password	Store the password in a secret and reference the secret by its label. Follow the steps in Use the secret store for the password after you create the agent profile.	Click to enable
Secret Label Identifier	This field appears when you select Use Secret Store for password . This value represents the <code>identifier</code> part of the secret label for the agent. PingOne Advanced Identity Cloud uses the identifier to generate a secret label in the following format: <code>am.application.agents.identifier.secret</code> . Learn more in Secret labels . After setting this, add an ESV secret for the password and map the ESV to the secret label.	<code>ig</code>



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

- Click **Save Profile > Done** to display the new agent profile.
- (Optional) Add the list of **Redirect URLs** used in PingGateway routes and click **Save** to update the profile.

Use the secret store for the password

When you select **Use Secret Store for password** and set a secret label for the agent profile, PingOne Advanced Identity Cloud creates the secret label but the secret isn't yet defined or mapped to the label:


- Define an ESV secret, such as `esv-ig_agent`, holding the password for PingGateway to connect.

The examples in the documentation use `password`.

Learn how in [creating ESV secrets](#). In production deployments, [restrict access to the password](#) from configuration placeholder and script contexts.

- Map the ESV to the label created when you set the **Secret Label Identifier**:
 - Click [Native Consoles](#) > **Access Management** > **Secret Stores** > **ESV** > **Mappings** > **+ Add mappings**.
 - In the **Add Mapping** modal, select the label, such as `am.application.agents.ig.secret`, in the **Secret Label** list.
 - In the **aliases** field, enter the ESV secret, such as `esv-ig_agent`, and click **Add**.

4. Click **Create** to add the mapping:



Learn more in [Map ESV secrets to secret labels](#).

Note the following points:

- If you update or delete the **Secret Label Identifier**, AM updates or deletes the corresponding mapping for the previous identifier unless another agent shares the mapping.
- When you rotate a secret, update the corresponding mapping.

Optional settings

In the AM admin UI, consider the following additional optional settings for the agent profile under **Applications > Agents > Identity Gateway > agent ID**:

1. To direct login to a custom URL instead of the default AM login page, configure **Login URL Template for CDSSO**.
2. To apply a different introspection scope, click **Token Introspection** and select a scope from the list.
3. Click **Save** to update the profile.

Set up a demo user in PingOne Advanced Identity Cloud

This procedure sets up a demo user in the alpha realm.

1. Log in to the Advanced Identity Cloud admin UI as an administrator.
2. Go to **Identities > Manage > Alpha realm - Users**, and add a user with the following values:
 - **Username:** demo
 - **First name:** demo
 - **Last name:** user
 - **Email Address:** demo@example.com
 - **Password:** Ch4ng3!t

Recommendations

Use PingGateway with PingOne Advanced Identity Cloud as you would with any other service.

- During updates, individual PingOne Advanced Identity Cloud tenant servers go offline temporarily. PingGateway can receive HTTP 502 Bad Gateway responses for some requests during the update.

In your [ClientHandler](#) and [ReverseProxyHandler](#) configurations, configure PingGateway to retry operations when this occurs:

```
"retries": {
  "enabled": true,
  "condition": "${response.status.code == 502}"
}
```

- Update PingGateway to use the latest version you can to benefit from fixes and improvements.

Set up AM

This section helps you prepare to use PingGateway with AM.

About authentication to AM

Unless you upgrade from an earlier version using the file-based configuration, AM 8 and later provide an [authentication tree](#) called **Agent**. The **Agent** tree validates the agent credentials with an [Agent Data Store Decision](#) node. All PingGateway, Java agent, and Web agent profiles use the **Agent** tree. Don't change its configuration.

For AM 7.3, 7.4, and 7.5, when AM is [installed with a default configuration](#), PingGateway authenticates to AM with a tree. Otherwise, PingGateway authenticates to AM with an AM authentication module. AM 7 deprecated authentication chains and modules and AM 8 removed support for them.

Register PingGateway with AM

Follow these steps to register an PingAM agent that acts on behalf of PingGateway.

1. In the AM admin UI, select the top-level realm, and then select **Applications > Agents > Identity Gateway**.
2. Add an agent with the following configuration, leaving other options blank or with the default value:

For SSO

- **Agent ID** : `ig_agent`
- **Password** : `password`

For CDSSO

- **Agent ID** : `ig_agent`
- **Password** : `password`
- **Redirect URL for CDSSO** : <https://ig.ext.com:8443/home/cdsso/redirect>
- **Login URL Template for CDSSO**: Configure this property to direct login to a custom URL instead of the default AM login page.

3. (Optional - From AM 7.5) Use AM's secret service to manage the agent profile password.

If AM finds a matching secret in a secret store, it uses that secret instead of a password in the agent profile.

1. In the agent profile page, set a label for the agent password in **Secret Label Identifier**.

AM uses the identifier to generate a secret label for the agent.

The secret label has the format `am.application.agents.identifier.secret`, where identifier is the **Secret Label Identifier**.

The **Secret Label Identifier** can contain only characters `a-z`, `A-Z`, `0-9`, and periods (`.`). It can't start or end with a period.

2. Select  **Secret Stores** and configure a secret store.
3. Map the label to the secret. Learn more from AM's [mapping](#).

Note the following points for using AM's secret service:

- Set a **Secret Label Identifier** that clearly identifies the agent.
- If you update or delete the **Secret Label Identifier**, AM updates or deletes the corresponding mapping for the previous identifier provided no other agent shares the mapping.
- When you rotate a secret, update the corresponding mapping.

Set up a demo user in AM

AM is provided with a demo user in the top-level realm, with the following credentials:

- ID/username: `demo`
- Last name: `user`
- Password: `Ch4ng31t`
- Email address: `demo@example.com`
- Employee number: `123`

Learn more about managing identities in AM's [Identity stores](#) documentation.

Find the AM session cookie name

In routes that use an AmService, PingGateway retrieves AM's SSO cookie name from the `ssoTokenHeader` property or from AM's `/serverinfo/*` endpoint.

In other circumstances where you need to find the SSO cookie name, access `http://am-base-url/serverinfo/*`. For example, access the AM endpoint with `curl`:

```
$ curl http://am.example.com:8088/openam/json/serverinfo/*
```

Downloading PingGateway

The .zip file unpacks into a `/path/to/identity-gateway-2025.6.1` directory with the following content:

- `bin`: Start and stop executables
- `classes`: Initially empty; used to install patches from support
- `docker/Dockerfile`: Dockerfile and README to build a PingGateway Docker image
- `legal-notices`: Licenses and copyrights
- `lib`: PingGateway and third-party libraries

1. Create a local installation directory for PingGateway like `/path/to`.



Important

The installation directory should be a new, empty directory. Installing PingGateway into an existing installation directory can cause errors.

2. Download `PingGateway-2025.6.1.zip` from the [Backstage download site](#), and copy the .zip file to the installation directory:

```
$ cp PingGateway-2025.6.1.zip /path/to/PingGateway-2025.6.1.zip
```

3. Unzip the file:

```
$ unzip PingGateway-2025.6.1.zip
```

The directory `/path/to/identity-gateway-2025.6.1` is created.

Starting and stopping PingGateway

Start PingGateway with default settings

When you start PingGateway, specify the configuration directory where PingGateway looks for configuration files.

1. Start PingGateway:

Linux

```
/path/to/identity-gateway-2025.6.1/bin/start.sh
```

Windows

```
C:\path\to\identity-gateway-2025.6.1\bin\start.bat
```

By default, PingGateway configuration files are located under `$HOME/.openig` on Linux, `%appdata%\OpenIG` on Windows. Learn how to use a different location in [Configuration location](#).

2. Check that PingGateway is running in one of the following ways:

- Check the PingGateway endpoint at `http://ig.example.com:8085/health/startup` to make sure PingGateway it returns `HTTP 200 OK`.

If PingGateway hasn't finished starting up or is shutting down, the endpoint returns `HTTP 503 Service Unavailable`.

- Display the product version and build information at `http://ig.example.com:8085/api/info`.

Start PingGateway with custom settings

By default, PingGateway runs on HTTP, on port `8080`, from the instance directory `$HOME/.openig`.

To start PingGateway with custom settings, add the configuration file `admin.json` with the following properties, and restart PingGateway:

- `vertx`: Finely tune Vert.x instances.
- `connectors`: Customize server port, TLS, and Vert.x-specific configurations. Each `connectors` object represents the configuration of an individual port.

The following example starts PingGateway on non-default ports, and configures Vert.x-specific options for the connection on port 9091:

```
{
  "connectors": [{
    "port": 9090
  },
  {
    "port": 9091,
    "vertex": {
      "maxWebSocketFrameSize": 128000,
      "maxWebSocketMessageSize": 256000,
      "compressionLevel": 4
    }
  }
  ]
}
```

For more information, refer to [AdminHttpApplication \(admin.json \)](#).

Allow startup when there is an existing PID file

By default, if there is an existing PID file during startup the startup fails. Use one of the following ways to allow startup when there is an existing PID file. PingGateway then removes the existing PID file and creates a new one during startup.

1. Add the following configuration to `admin.json` and restart PingGateway:

```
{
  "pidFileMode": "override"
}
```

Source: [admin-pidfilemode.json](#) [↗](#)

2. Define an environment variable for the configuration token `ig.pid.file.mode`, and then start PingGateway in the same terminal:

Linux

```
$ IG_PID_FILE_MODE=override /path/to/identity-gateway-2025.6.1/bin/start.sh
```

Windows

```
C:\IG_PID_FILE_MODE=override
C:\path\to\identity-gateway-2025.6.1\bin\start.bat %appdata%\OpenIG
```

3. Define a system property for the configuration token `ig.pid.file.mode` when you start PingGateway:

Linux

```
$HOME/.openig/env.sh
```

Windows

```
%appdata%\OpenIG\env.sh
```

```
export "IG_OPTS=-Dig.pid.file.mode=override"
```

Stop PingGateway

Use the `stop.sh` script to stop an instance of PingGateway, specifying the instance directory as an argument.

If the instance directory isn't specified, PingGateway uses the default instance directory as in these examples:

Linux

```
/path/to/identity-gateway-2025.6.1/bin/stop.sh $HOME/.openig
```

Windows

```
C:\path\to\identity-gateway-2025.6.1\bin\stop.bat %appdata%\OpenIG
```

Graceful shutdown

By default, the `stop.sh` or `stop.bat` script waits up to 2.5 seconds before forcing the PingGateway process to terminate. Technically, the script sleeps 500 milliseconds up to five times.

To give PingGateway more time to shut down gracefully, specify the sleep time in milliseconds and the number of intervals after the instance directory argument. The following examples cause the script to wait up to 10 seconds before forcing termination:

Linux

```
/path/to/identity-gateway-2025.6.1/bin/stop.sh $HOME/.openig 1000 10
```

Windows

```
C:\path\to\identity-gateway-2025.6.1\bin\stop.bat %appdata%\OpenIG 1000 10
```

When you specify the sleep time in milliseconds without the number of intervals, the number of intervals defaults to five.

Setting up PingGateway environment variables and system properties

Configure environment variables and system properties as follows:

- By adding environment variables on the command line when you start PingGateway.

- By adding environment variables in `$HOME/.openig/bin/env.sh`, where `$HOME/.openig` is the instance directory. After changing `env.sh`, restart PingGateway to load the new configuration.

Start PingGateway with a customized router scan interval

By default, PingGateway scans every 10 seconds for changes to the route configuration files. Any changes to the files are automatically loaded into the configuration without restarting PingGateway. Learn more about the router scan interval in [Router](#).

The following example overwrites the default value of the Router scan interval to 2 seconds when you start up PingGateway:

Linux

```
$ IG_ROUTER_SCAN_INTERVAL='2 seconds' /path/to/identity-gateway-2025.6.1/bin/start.sh
```

Windows

```
C:\IG_ROUTER_SCAN_INTERVAL='2 seconds'  
C:\start.bat %appdata%\OpenIG
```

Define environment variables for startup, runtime, and stop

PingGateway provides the following environment variables for Java runtime options:

IG_OPTS

(Optional) Java runtime options for PingGateway and its startup process, such as JVM memory sizing options.

Include all options that aren't shared with the `stop` script.

The following example specifies environment variables in the `env.sh` file to customize JVM options and keys:

Linux

```
# Specify JVM options
JVM_OPTS="-XX:+UseG1GC -Xmx2048m"

# Specify the DH key size for stronger ephemeral DH keys and to protect against weak keys
JSSE_OPTS="-Djdk.tls.ephemeralDHKeySize=2048"

# Wrap them up into the IG_OPTS environment variable
export IG_OPTS="${IG_OPTS} ${JVM_OPTS} ${JSSE_OPTS}"
```

Windows

```
set "JVM_OPTS=-XX:+UseG1GC -Xmx2048m"
set "JSSE_OPTS=-Djdk.tls.ephemeralDHKeySize=2048"
set "IG_OPTS=%IG_OPTS% %JVM_OPTS% %JSSE_OPTS%"
```

JAVA_OPTS

(Optional) Java runtime options for PingGateway include all options that are shared by the `start` and `stop` script.

Encrypting and sharing PingGateway JWT sessions

PingGateway stateless sessions store session information in JWT cookies on the user-agent. Learn more in [PingGateway sessions](#).

This page describes how to set authenticated encryption for stateless sessions using symmetric keys.

With [authenticated encryption](#), PingGateway encrypts data and signs it with HMAC in a single step.

Encrypt JWT sessions

This section describes how to set up a keystore with a symmetric key for authenticated encryption of a JWT session.

1. Set up a keystore to contain the encryption key, where the keystore and the key have the password `password`:

1. Locate a directory for secrets and go to it:

```
$ cd /path/to/secrets
```

2. Generate the key:

```
$ keytool \  
-genseckey \  
-alias symmetric-key \  
-keystore jwtsessionkeystore.pkcs12 \  
-storepass password \  
-storetype pkcs12 \  
-keyalg HmacSHA512 \  
-keysize 512
```

 Note

Because keytool converts all characters in its key aliases to lowercase, use only lowercase in alias definitions of a keystore.

2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/jwt-session-encrypt.json
```

Windows

```
%appdata%\OpenIG\config\routes\jwt-session-encrypt.json
```

```
{
  "name": "jwt-session-encrypt",
  "heap": [{
    "name": "KeyStoreSecretStore-1",
    "type": "KeyStoreSecretStore",
    "config": {
      "file": "/path/to/secrets/jwtsessionkeystore.pkcs12",
      "storeType": "PKCS12",
      "storePasswordSecretId": "keystore.secret.id",
      "secretsProvider": ["SystemAndEnvSecretStore-1"],
      "mappings": [{
        "secretId": "jwtsession.symmetric.secret.id",
        "aliases": ["symmetric-key"]
      }]
    }
  }],
  {
    "name": "SystemAndEnvSecretStore-1",
    "type": "SystemAndEnvSecretStore"
  }
],
  "session": {
    "type": "JwtSessionManager",
    "config": {
      "authenticatedEncryptionSecretId": "jwtsession.symmetric.secret.id",
      "encryptionMethod": "A256CBC-HS512",
      "secretsProvider": ["KeyStoreSecretStore-1"],
      "cookie": {
        "name": "IG",
        "domain": ".example.com"
      }
    }
  },
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/plain; charset=UTF-8" ]
      },
      "entity": "Hello world!"
    }
  },
  "condition": "${request.uri.path == '/jwt-session-encrypt'}"
}
```

Source: [jwt-session-encrypt.json](#)

Notice the following features of the route:

- The route matches requests to `/jwt-session-encrypt`.
- The `KeyStoreSecretStore` uses the `SystemAndEnvSecretStore` in the heap to manage the store password.
- The `JwtSessionManager` uses the `KeyStoreSecretStore` in the heap to manage the session encryption secret.


3. In the terminal where you will run the PingGateway instance, create an environment variable for the value of the keystore password:

```
$ export KEYSTORE_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by the SystemAndEnvSecretStore, and must be base64-encoded.

Share JWT sessions between multiple instances of PingGateway

This section shows how to set up a deployment with three PingGateway servers sharing stateless sessions.



1. Set up a keystore to contain the encryption key, where the keystore and the key have the password **password** :

1. Locate a directory for secrets and go to it:

```
$ cd /path/to/secrets
```

2. Generate the key:

```
$ keytool \
  -genseckey \
  -alias symmetric-key \
  -keystore jwtsessionkeystore.pkcs12 \
  -storepass password \
  -storetype pkcs12 \
  -keyalg HmacSHA512 \
  -keysize 512
```

Note

Because keytool converts all characters in its key aliases to lowercase, use only lowercase in alias definitions of a keystore.

2. Prepare the PingGateway installation:

1. Create an installation directory for PingGateway in `/path/to`.
2. Download and unzip PingGateway-2025.6.1.zip in `/path/to`, as described in the [Installing PingGateway](#). The directory `/path/to/identity-gateway-2025.6.1` is created.

3. Set up the first instance of PingGateway, which acts as the load balancer:

1. Create a configuration directory for the instance and go to it:

```
$ mkdir -p /path/to/config-instance1/config/routes
```

2. Add the following route:

Linux

```
/path/to/config-instance1/config/routes/instance1-loadbalancer.json
```

Windows

```
%appdata%\path\to\config-instance1\config\routes\instance1-loadbalancer.json
```

```

{
  "name": "instance1-loadbalancer",
  "heap": [{
    "name": "KeyStoreSecretStore-1",
    "type": "KeyStoreSecretStore",
    "config": {
      "file": "/path/to/secrets/jwtsessionkeystore.pkcs12",
      "storeType": "PKCS12",
      "storePasswordSecretId": "keystore.secret.id",
      "secretsProvider": ["SystemAndEnvSecretStore-1"],
      "mappings": [{
        "secretId": "jwtsession.symmetric.secret.id",
        "aliases": ["symmetric-key"]
      }]
    }
  ]
},
{
  "name": "SystemAndEnvSecretStore-1",
  "type": "SystemAndEnvSecretStore"
}
],
"session": {
  "type": "JwtSessionManager",
  "config": {
    "authenticatedEncryptionSecretId": "jwtsession.symmetric.secret.id",
    "encryptionMethod": "A256CBC-HS512",
    "secretsProvider": ["KeyStoreSecretStore-1"],
    "cookie": {
      "name": "IG",
      "domain": ".example.com"
    }
  }
},
"handler": {
  "type": "DispatchHandler",
  "config": {
    "bindings": [{
      "condition": "${find(request.uri.path, '/webapp/browsing') and (contains(request.uri.query, 'one') or empty(request.uri.query))}",
      "baseURI": "http://ig.example.com:8002",
      "handler": "ReverseProxyHandler"
    }, {
      "condition": "${find(request.uri.path, '/webapp/browsing') and contains(request.uri.query, 'two')}",
      "baseURI": "http://ig.example.com:8003",
      "handler": "ReverseProxyHandler"
    }, {
      "condition": "${find(request.uri.path, '/log-in-and-generate-session')}",
      "handler": {
        "type": "Chain",
        "config": {
          "filters": [{
            "type": "AssignmentFilter",
            "config": {
              "onRequest": [{
                "target": "${session.authUsername}",
                "value": "Sam Carter"
              }]
            }
          ]
        }
      }
    }
  ]
}
}

```

```

        "handler": {
          "type": "StaticResponseHandler",
          "config": {
            "status": 200,
            "headers": {
              "Content-Type": [ "text/html; charset=UTF-8" ]
            },
            "entity": "<html><body>Sam Carter logged IN. (JWT session generated)</body></html>"
          }
        }
      }
    }
  }
}
},
"capture": "all"
}

```

Source: [instance1-loadbalancer.json](#)

Notice the following features of the route:

- The route has no condition, so it matches all requests.
- When the request matches `/log-in-and-generate-session`, the `DispatchHandler` creates a JWT session, whose `authUsername` attribute contains the name `Sam Carter`.
- When the request matches `/webapp/browsing`, the `DispatchHandler` dispatches the request to instance 2 or instance 3, depending on the rest of the request path.

3. Add the following configuration:

Linux

```
/path/to/config-instance1/config/admin.json
```

Windows

```
%appdata%\path\to\config-instance1\config\admin.json
```

```

{
  "connectors": [{
    "port": 8001
  }]
}

```

4. In the terminal where you will run the PingGateway instance, create an environment variable for the value of the keystore password:

```
$ export KEYSTORE_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by the `SystemAndEnvSecretStore`, and must be base64-encoded.

5. Start PingGateway:

Linux

```
/path/to/identity-gateway-2025.6.1/bin/start.sh /path/to/config-instance1/
```

Windows

```
C:\path\to\identity-gateway-2025.6.1\bin\start.bat %appdata%\path\to\config-instance1
```

4. Set up and start the second instance of PingGateway:

1. Create a configuration directory for the instance:

```
$ mkdir -p /path/to/config-instance2/config/routes
```

2. Add the following route:

Linux

```
/path/to/config-instance2/config/routes/instance2-retrieve-session-username.json
```

Windows

```
%appdata%\path\to\config-instance2\config\routes\instance2-retrieve-session-username.json
```



```

{
  "name": "instance2-retrieve-session-username",
  "heap": [{
    "name": "KeyStoreSecretStore-1",
    "type": "KeyStoreSecretStore",
    "config": {
      "file": "/path/to/secrets/jwtsessionkeystore.pkcs12",
      "storeType": "PKCS12",
      "storePasswordSecretId": "keystore.secret.id",
      "secretsProvider": ["SystemAndEnvSecretStore-1"],
      "mappings": [{
        "secretId": "jwtsession.symmetric.secret.id",
        "aliases": ["symmetric-key"]
      }]
    }
  }],
  {
    "name": "SystemAndEnvSecretStore-1",
    "type": "SystemAndEnvSecretStore"
  }
],
  "session": {
    "type": "JwtSessionManager",
    "config": {
      "authenticatedEncryptionSecretId": "jwtsession.symmetric.secret.id",
      "encryptionMethod": "A256CBC-HS512",
      "secretsProvider": ["KeyStoreSecretStore-1"],
      "cookie": {
        "name": "IG",
        "domain": ".example.com"
      }
    }
  },
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/html; charset=UTF-8" ]
      },
      "entity": [
        "<html>",
        "  <body>",
        "    ${session.authUsername!= null?'Hello,",
        "'.concat(session.authUsername).concat(' !'):'Session.authUsername is not defined'}! (instance2)",
        "  </body>",
        "</html>"
      ]
    }
  },
  "condition": "${find(request.uri.path, '/webapp/browsing')}",
  "capture": "all"
}

```

Source: [instance2-retrieve-session-username.json](#)

Notice the following features of the route compared to the route for instance 1:

- The route matches the condition `/webapp/browsing`. When a request matches `/webapp/browsing`, the `DispatchHandler` dispatches it to instance 2.
- The `StaticResponseHandler` displays information from the session context.

3. Add the following configuration:

Linux

```
/path/to/config-instance2/config/admin.json
```

Windows

```
%appdata%\path\to\config-instance2\config\admin.json
```

```
{
  "connectors": [{
    "port": 8002
  }]
}
```

4. In the terminal where you will run the PingGateway instance, create an environment variable for the value of the keystore password:

```
$ export KEYSTORE_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by the `SystemAndEnvSecretStore`, and must be base64-encoded.

5. Start PingGateway:

Linux

```
/path/to/identity-gateway-2025.6.1/bin/start.sh /path/to/config-instance2/
```

Windows

```
C:\path\to\identity-gateway-2025.6.1\bin\start.bat %appdata%\path\to\config-instance2
```

5. Set up and start the third instance of PingGateway:

1. Create a configuration directory:

```
$ mkdir -p /path/to/config-instance3/config/routes
```

2. Add the following route:

Linux

```
/path/to/config-instance3/config/routes/instance3-retrieve-session-username.json
```

Windows

`%appdata%\path\to\config-instance3\config\routes\instance3-retrieve-session-username.json`

```
{
  "name": "instance3-retrieve-session-username",
  "heap": [{
    "name": "KeyStoreSecretStore-1",
    "type": "KeyStoreSecretStore",
    "config": {
      "file": "/path/to/secrets/jwtsessionkeystore.pkcs12",
      "storeType": "PKCS12",
      "storePasswordSecretId": "keystore.secret.id",
      "secretsProvider": ["SystemAndEnvSecretStore-1"],
      "mappings": [{
        "secretId": "jwtsession.symmetric.secret.id",
        "aliases": ["symmetric-key"]
      }]
    }
  }],
  {
    "name": "SystemAndEnvSecretStore-1",
    "type": "SystemAndEnvSecretStore"
  }
],
  "session": {
    "type": "JwtSessionManager",
    "config": {
      "authenticatedEncryptionSecretId": "jwtsession.symmetric.secret.id",
      "encryptionMethod": "A256CBC-HS512",
      "secretsProvider": ["KeyStoreSecretStore-1"],
      "cookie": {
        "name": "IG",
        "domain": ".example.com"
      }
    }
  },
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/html; charset=UTF-8" ]
      },
      "entity": [
        "<html>",
        "  <body>",
        "    ${session.authUsername!= null?'Hello,",
        "'.concat(session.authUsername).concat(' !'):'Session.authUsername is not defined'}! (instance3)",
        "  </body>",
        "</html>"
      ]
    }
  },
  "condition": "${find(request.uri.path, '/webapp/browsing')}",
  "capture": "all"
}
```

Source: [instance3-retrieve-session-username.json](#) 

Notice that the route is the same as for instance 2, apart from the text in the entity of the StaticResponseHandler.

3. Add the following configuration:

Linux

```
/path/to/config-instance3/config/admin.json
```

Windows

```
%appdata%\path\to\config-instance3\config\admin.json
```

```
{
  "connectors": [{
    "port": 8003
  }]
}
```

4. In the terminal where you will run the PingGateway instance, create an environment variable for the value of the keystore password:

```
$ export KEYSTORE_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by the SystemAndEnvSecretStore, and must be base64-encoded.

5. Start PingGateway:

Linux

```
/path/to/identity-gateway-2025.6.1/bin/start.sh /path/to/config-instance3/
```

Windows

```
C:\path\to\identity-gateway-2025.6.1\bin\start.bat %appdata%\path\to\config-instance3
```

6. Test the setup:

1. Access instance 1, to generate a session:

```
$ curl -v http://ig.example.com:8001/log-in-and-generate-session
```

Output

```
GET /log-in-and-generate-session HTTP/1.1
...

HTTP/1.1 200 OK
Content-Length: 84
Set-Cookie: IG=eyJ...HyI; Path=/; Domain=.example.com; HttpOnly
...
Sam Carter logged IN. (JWT session generated)
```

2. Using the JWT cookie returned in the previous step, access instance 2:

```
$ curl -v http://ig.example.com:8001/webapp/browsing?one --header "cookie:IG=eyJ...HyI"
```

Output

```
GET /webapp/browsing?one HTTP/1.1
...
cookie: IG=eyJ...HyI
...
HTTP/1.1 200 OK
...
Hello, Sam Carter !! (instance2)
```

Note that instance 2 can access the session info.

3. Using the JWT cookie again, access instance 3:

```
$ curl -v http://ig.example.com:8001/webapp/browsing?two --header "cookie:IG=eyJ...HyI"
```

Output

```
GET /webapp/browsing?two HTTP/1.1
...
cookie: IG=eyJ...HyI
...
HTTP/1.1 200 OK
...
Hello, Sam Carter !! (instance3)
```

Note that instance 3 can access the session info.

Preparing PingGateway for load balancing and failover

For high scale or highly available deployments, consider using a pool of PingGateway servers with nearly identical configurations. Load balance requests across the pool to handle more load. Route around any servers that become unavailable.

Manage state information

Before spreading requests across multiple servers, decide how to manage state information. PingGateway manages state information in the following ways:

Stores state information in a context

By using filters that can store information in the context. Most filters depend on information in the request, response, or context, some of which is first stored by PingGateway. For a summary of filters that can populate a context, refer to [Summary of contexts](#).

By using a handler such as the [ScriptableHandler](#) that can store state information in the context. Most handlers depend on information in the context, some of which is first stored by PingGateway.

Retrieves state information to local memory

By using filters and handlers that depend on the configuration of the local file system, such as the following filters:

- [FileAttributesFilter](#)
- [ScriptableFilter](#)
- [ScriptableHandler](#)
- [SqlAttributesFilter](#)

When a server becomes unavailable, state information held in local memory is lost. To prevent data loss when a server becomes unavailable, set up failover. Server failover should be transparent to client applications.

Prepare stateless sessions

For example configurations, refer to [Encrypting and sharing PingGateway JWT sessions](#).

Stateless sessions

Use a [JwtSessionManager](#). PingGateway stores session content in a JWT cookie on the user-agent.

So that any server can read or update a JWT cookie from any other server in the same cookie domain, encrypt JWT sessions and share keys and secret across all PingGateway configurations.

[Encrypt JWT sessions](#). The maximum size of the JWT session cookie is 4 KBytes, as defined by the browser. If the cookie exceeds this size, PingGateway automatically splits it into multiple cookies.

Session stickiness

Session stickiness helps to ensure that a client request goes to the server holding the original session data.

If data attached to a context must be stored on the server-side, configure session stickiness so that the load balancer sends all requests from the same client session to the same server.

For an example configuration, refer to [Share JWT sessions between multiple instances of PingGateway](#).

SAML in deployments with multiple instances of PingGateway

PingGateway uses AM federation libraries to implement SAML. When PingGateway acts as a SAML service provider, some internal state information is maintained in the fedlet instead of the session cookie. In deployments that use multiple instances of PingGateway as a SAML service provider, set up sticky sessions so that requests go to the server that started the SAML interaction.

For information, refer to [Session state considerations](#) in AM's *SAML v2.0 guide*.

Securing connections with PingGateway

PingGateway is often deployed to replay credentials or other security information. In a real world deployment, this information must be communicated over a secure connection using HTTPS, meaning HTTP over encrypted Transport Layer Security (TLS). Never send real credentials, bearer tokens, or other security information unprotected over HTTP.

Learn about how to use well-known CA-signed certificates from the documentation for the Java Virtual Machine (JVM).

After installing certificates for client-server trust, consider which cipher suites to use. PingGateway inherits the list of cipher suites from the underlying Java environment.

PingGateway uses the JSSE to secure connections. You can set security and system properties to configure the JSSE. For a list of properties to customize the JSSE in Oracle Java, refer to the *Customization* section of the [JSSE Reference guide](#).

Configure PingGateway for TLS (client-side)

When PingGateway sends requests over HTTP to a proxied application, or requests services from a third-party application, PingGateway is acting as a client of the application, and the application is acting as a server. PingGateway is *client-side*.

When PingGateway sends requests securely over HTTPS, PingGateway must be able to trust the server. By default, PingGateway uses the Java environment truststore to trust server certificates. The Java environment truststore includes public key signing certificates from many well-known Certificate Authorities (CAs).

When servers present certificates signed by trusted CAs, then PingGateway can send requests over HTTPS to those servers, without any configuration to set up the HTTPS client connection. When server certificates are self-signed or signed by a CA whose certificate is not automatically trusted, the following objects can be required to configure the connection:

- [KeyStoreSecretStore](#), to manage a secret store for cryptographic keys and certificates, based on a standard Java keystore.
- [SecretsTrustManager](#), to manage trust material that verifies the credentials presented by a peer.
- (Optional) [SecretsKeyManager](#), to manage keys that authenticate a TLS connection to a peer.
- ClientHandler and ReverseProxyHandler reference to [ClientTlsOptions](#), for connecting to TLS-protected endpoints.

The following procedure describes how to set up PingGateway for HTTPS (client-side), when server certificates are self-signed or signed by untrusted CAs.

Set up PingGateway for HTTPS (client-side) for untrusted servers

1. Locate or set up the following directories:

- Directory containing the sample application .jar: `sampleapp_install_dir`
- Directory to store the sample application certificate and PingGateway keystore: `/path/to/secrets`

2. Extract the public certificate from the sample application:

```
$ cd /path/to/secrets
```

```
$ jar --verbose --extract \  
--file sampleapp_install_dir/PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar tls/sampleapp-  
cert.pem
```

Output

```
inflated: tls/sampleapp-cert.pem
```

The file `/path/to/secrets/tls/sampleapp-cert.pem` is created.

3. Import the certificate into the PingGateway keystore, and answer **yes** to trust the certificate:

```
$ keytool -importcert \  
-alias ig-sampleapp \  
-file tls/sampleapp-cert.pem \  
-keystore reverseproxy-truststore.p12 \  
-storetype pkcs12 \  
-storepass password
```

Output

```
...  
Trust this certificate? [no]: yes  
  
Certificate was added to keystore
```

Note

Because keytool converts all characters in its key aliases to lowercase, use only lowercase in alias definitions of a keystore.

4. List the keys in the PingGateway keystore to make sure that a key with the alias `ig-sampleapp` is present:


```
$ keytool -list \  
-v \  
-keystore /path/to/secrets/reverseproxy-truststore.p12 \  
-storetype pkcs12 \  
-storepass password
```

Output

```
Keystore type: PKCS12  
Keystore provider: SUN  
Your keystore contains 1 entry  
Alias name: ig-sampleapp  
...
```

5. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{  
  "name" : "00-static-resources",  
  "baseURI" : "http://app.example.com:8081",  
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/*\\\\\\\\.ico$') or  
matchesWithRegex(request.uri.path, '^/*\\\\\\\\.gif$')}",  
  "handler": "ReverseProxyHandler"  
}
```

Source: [00-static-resources.json](#) 

6. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/client-side-https.json
```

Windows

```
%appdata%\OpenIG\config\routes\client-side-https.json
```

```

{
  "name": "client-side-https",
  "condition": "${find(request.uri.path, '/home/client-side-https')}",
  "baseURI": "https://app.example.com:8444",
  "heap": [
    {
      "name": "Base64EncodedSecretStore-1",
      "type": "Base64EncodedSecretStore",
      "config": {
        "secrets": {
          "keystore.secret.id": "cGFzc3dvcmQ="
        }
      }
    },
    {
      "name": "KeyStoreSecretStore-1",
      "type": "KeyStoreSecretStore",
      "config": {
        "file": "/path/to/secrets/reverseproxy-truststore.p12",
        "storeType": "PKCS12",
        "storePasswordSecretId": "keystore.secret.id",
        "secretsProvider": "Base64EncodedSecretStore-1",
        "mappings": [
          {
            "secretId": "trust.manager.secret.id",
            "aliases": [ "ig-sampleapp" ]
          }
        ]
      }
    }
  ],
  {
    "name": "SecretsTrustManager-1",
    "type": "SecretsTrustManager",
    "config": {
      "verificationSecretId": "trust.manager.secret.id",
      "secretsProvider": "KeyStoreSecretStore-1"
    }
  },
  {
    "name": "ReverseProxyHandler-1",
    "type": "ReverseProxyHandler",
    "config": {
      "tls": {
        "type": "ClientTlsOptions",
        "config": {
          "trustManager": "SecretsTrustManager-1",
          "hostnameVerifier": "ALLOW_ALL"
        }
      }
    },
    "capture": "all"
  }
],
  "handler": "ReverseProxyHandler-1"
}

```

Source: [client-side-https.json](#) 

Notice the following features of the route:

- The route matches requests to `/home/client-side-https`.
- The `baseURI` changes the request URI to point to the HTTPS port for the sample application.
- The `Base64EncodedSecretStore` provides the keystore password.
- The `SecretsTrustManager` points to the secret bound to the sample application certificate, coming from the `KeyStoreSecretStore`.
- The `KeyStoreSecretStore` contains the sample application certificate to validate the TLS connection. The password to access the keystore is provided by the `SystemAndEnvSecretStore`.
- The `ReverseProxyHandler` uses the `SecretsTrustManager` for the connection to TLS-protected endpoints. All hostnames are allowed.

7. Test the setup:

1. Start the sample application.

```
$ java -jar sampleapp_install_dir/PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar
```

2. Go to <http://ig.example.com:8080/home/client-side-https>.

The request is proxied transparently to the sample application, on the TLS port `8444`.

3. Check the route log for a line like this:

```
GET https://app.example.com:8444/home/client-side-https
```

Configure PingGateway for TLS (server-side)

When PingGateway is *server-side*, applications send requests to PingGateway or request services from PingGateway. PingGateway is acting as a server of the application, and the application is acting as a client.

To run PingGateway as a server over TLS:

- In the `admin.json` heap, add a `SecretsKeyManager` to authenticate PingGateway to the client. Key material is a private key and its certificate for PingGateway.
- In `admin.json`, update the `connectors` list to include a connector for the HTTPS port. The connector `tls` property must refer to a `ServerTlsOptions`.
- The `ServerTlsOptions` must configure `keyManager` to refer to the `SecretsKeyManager`.

The following example connector includes a `ServerTlsOptions` that refers to a `SecretsKeyManager` in the heap:

```
"connectors": [
  {
    "port": 8443,
    "tls": {
      "type": "ServerTlsOptions",
      "config": {
        "keyManager": "SecretsKeyManager-1"
      }
    }
  }
]
```

Learn more from [About keys and certificates](#).

Serve one certificate for TLS connections to all server names

This example uses PEM files and a PKCS#12 keystore for self-signed certificates, but you can adapt it to use official (non self-signed) keys and certificates.

Before you start, install PingGateway, as described in the [Installing PingGateway](#).

1. Locate a directory for the secrets, for example, `/path/to/secrets`.
2. Create self-signed keys in one of the following ways. If you have your own keys, use them and skip this step.

If you have your own keys, use them and skip this step.

1. Create the keystore:

```
$ keytool \
-genkey \
-alias https-connector-key \
-keyalg RSA \
-keystore /path/to/secrets/keystore.pkcs12 \
-storepass password \
-keypass password \
-dname "CN=ig.example.com,O=Example Corp,C=FR"
```

Note

Because keytool converts all characters in its key aliases to lowercase, use only lowercase in alias definitions of a keystore.

2. In the secrets directory, add a file called `keystore.pass`, containing the keystore password `password`:

```
$ cd /path/to/secrets
$ echo -n 'password' > keystore.pass
```

Make sure the password file contains only the password, with no trailing spaces or carriage returns.

1. Locate a directory for secrets and go to it:

```
$ cd /path/to/secrets
```

2. Create the following secret key and certificate pair as PEM files:

```
$ openssl req \
  -newkey rsa:2048 \
  -new \
  -nodes \
  -x509 \
  -days 3650 \
  -subj "/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr" \
  -keyout ig.example.com-key.pem \
  -out ig.example.com-certificate.pem
```

Two PEM files are created, one for the secret key, and another for the associated certificate.

3. Map the key and certificate to the same secret ID in PingGateway:

```
$ cat ig.example.com-key.pem ig.example.com-certificate.pem > key.manager.secret.id.pem
```

3. Set up TLS on PingGateway in one of the following ways:

Add the following file to PingGateway, replacing `/path/to/secrets` with your path:

Linux

```
$HOME/.openig/config/admin.json
```

Windows

```
%appdata%\OpenIG\config\admin.json
```

```

{
  "connectors": [
    {
      "port": 8080
    },
    {
      "port": 8443,
      "tls": "ServerTlsOptions-1"
    }
  ],
  "heap": [
    {
      "name": "ServerTlsOptions-1",
      "type": "ServerTlsOptions",
      "config": {
        "keyManager": {
          "type": "SecretsKeyManager",
          "config": {
            "signingSecretId": "key.manager.secret.id",
            "secretsProvider": "ServerIdentityStore"
          }
        }
      }
    },
    {
      "type": "FileSystemSecretStore",
      "name": "SecretsPasswords",
      "config": {
        "directory": "/path/to/secrets",
        "format": "PLAIN"
      }
    }
  ],
  {
    "name": "ServerIdentityStore",
    "type": "KeyStoreSecretStore",
    "config": {
      "file": "/path/to/secrets/IG-keystore",
      "storePasswordSecretId": "keystore.pass",
      "secretsProvider": "SecretsPasswords",
      "mappings": [
        {
          "secretId": "key.manager.secret.id",
          "aliases": ["https-connector-key"]
        }
      ]
    }
  }
]
}

```

Source: [admin-https.json](#)

Notice the following features of the file:

- PingGateway listens for:
 - Administrative HTTP requests on port **8085** (default).
 - HTTP requests on port **8080**.

- HTTPS requests on port 8443 .

- PingGateway's private keys for TLS are managed by the SecretsKeyManager, whose ServerIdentityStore references a KeyStoreSecretStore.
- The KeyStoreSecretStore maps the keystore alias to the secret ID for retrieving the server keys (private key + certificate).
- The password of the KeyStoreSecretStore is provided by the FileSystemSecretStore.

Add the following file to PingGateway, replacing `/path/to/secrets` with your path:

Linux

```
$HOME/.openig/config/admin.json
```

Windows

```
%appdata%\OpenIG\config\admin.json
```

```

{
  "connectors": [
    {
      "port": 8080
    },
    {
      "port": 8443,
      "tls": "ServerTlsOptions-1"
    }
  ],
  "heap": [
    {
      "name": "ServerTlsOptions-1",
      "type": "ServerTlsOptions",
      "config": {
        "keyManager": {
          "type": "SecretsKeyManager",
          "config": {
            "signingSecretId": "key.manager.secret.id",
            "secretsProvider": "ServerIdentityStore"
          }
        }
      }
    },
    {
      "name": "ServerIdentityStore",
      "type": "FileSystemSecretStore",
      "config": {
        "format": "PLAIN",
        "directory": "/path/to/secrets",
        "suffix": ".pem",
        "mappings": [{
          "secretId": "key.manager.secret.id",
          "format": {
            "type": "PemPropertyFormat"
          }
        }]
      }
    }
  ]
}

```

Source: [admin-https-pem.json](#)

Notice how this file differs to that for the keystore-based approach:

- The ServerIdentityStore is a FileSystemSecretStore.
- The FileSystemSecretStore reads the keys that are stored as files in the PEM standard format.

4. Start PingGateway:

Linux

```
/path/to/identity-gateway-2025.6.1/bin/start.sh
```


Windows

```
C:\path\to\identity-gateway-2025.6.1\bin\start.bat
```

By default, PingGateway configuration files are located under `$HOME/.openig` on Linux, `%appdata%\OpenIG` on Windows. Learn how to use a different location, in [Configuration location](#).

5. Test the connection by going to the PingGateway welcome page, <https://ig.example.com:8443/>.

The browser won't recognize the certificate, but you can safely access the page.

Use Server Name Indication (SNI) to serve different certificates for TLS connections to different server names

This example uses PEM files for self-signed certificates, but you can adapt it to use official (non self-signed) keys and certificates.

Before you start, install PingGateway, as described in the [Installing PingGateway](#).

1. Locate a directory for secrets and go to it.

```
$ cd /path/to/secrets
```

2. Create the following secret key and certificate pair as PEM files:

1. For `ig.example.com`:

1. Create a key and certificate:

```
$ openssl req \
  -newkey rsa:2048 \
  -new \
  -nodes \
  -x509 \
  -days 3650 \
  -subj "/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr" \
  -keyout ig.example.com-key.pem \
  -out ig.example.com-certificate.pem
```

Two PEM files are created, one for the secret key, and another for the associated certificate.

2. Map the key and certificate to the same secret ID in PingGateway:

```
$ cat ig.example.com-key.pem ig.example.com-certificate.pem > key.manager.secret.id.pem
```

2. For servers grouped by a wildcard:

1. Create a key and certificate:

```
$ openssl req \  
-newkey rsa:2048 \  
-new \  
-nodes \  
-x509 \  
-days 3650 \  
-subj "/CN=*.example.com/OU=example/O=com/L=fr/ST=fr/C=fr" \  
-keyout wildcard.example.com-key.pem \  
-out wildcard.example.com-certificate.pem
```

2. Map the key and certificate to the same secret ID in PingGateway:

```
$ cat wildcard.example.com-key.pem wildcard.example.com-certificate.pem > wildcard.secret.id.pem
```

3. For other, unmapped servers

1. Create a key and certificate:

```
$ openssl req \  
-newkey rsa:2048 \  
-new \  
-nodes \  
-x509 \  
-days 3650 \  
-subj "/CN=un.mapped.com/OU=example/O=com/L=fr/ST=fr/C=fr" \  
-keyout default.example.com-key.pem \  
-out default.example.com-certificate.pem
```

2. Map the key and certificate to the same secret ID in PingGateway:

```
$ cat default.example.com-key.pem default.example.com-certificate.pem > default.secret.id.pem
```

3. Add the following file to PingGateway, replacing `/path/to/secrets` with your path, and restart PingGateway:

Linux

```
$HOME/.openig/config/admin.json
```

Windows

```
%appdata%\OpenIG\config\admin.json
```

```

{
  "connectors": [
    {
      "port": 8080
    },
    {
      "port": 8443,
      "tls": "ServerTlsOptions-1"
    }
  ],
  "heap": [
    {
      "name": "ServerTlsOptions-1",
      "type": "ServerTlsOptions",
      "config": {
        "sni": {
          "serverNames": {
            "ig.example.com": "key.manager.secret.id",
            "*.example.com": "wildcard.secret.id"
          },
          "defaultSecretId": "default.secret.id",
          "secretsProvider": "ServerIdentityStore"
        }
      }
    },
    {
      "name": "ServerIdentityStore",
      "type": "FileSystemSecretStore",
      "config": {
        "format": "PLAIN",
        "directory": "path/to/secrets",
        "suffix": ".pem",
        "mappings": [
          {
            "secretId": "key.manager.secret.id",
            "format": {
              "type": "PemPropertyFormat"
            }
          },
          {
            "secretId": "wildcard.secret.id",
            "format": {
              "type": "PemPropertyFormat"
            }
          },
          {
            "secretId": "default.secret.id",
            "format": {
              "type": "PemPropertyFormat"
            }
          }
        ]
      }
    }
  ]
}

```

Source: [admin-https-sni.json](#)

Notice the following features of the file:

- The `ServerTlsOptions` object maps two servers to secret IDs, and includes a default secret ID
- The secret IDs correspond to the secret IDs in the `FileSystemSecretStore`, and the PEM files generated in an earlier step.

4. Run the following commands to request TLS connections to different servers, using different certificates:

1. Connect to `ig.example.com`, and note that the certificate subject corresponds to the certificate created for `ig.example.com`:

```
$ openssl s_client -connect localhost:8443 -servername ig.example.com
```

Output

```
...
Server certificate
-----BEGIN CERTIFICATE-----
MII...dZC
-----END CERTIFICATE-----
subject=/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr
issuer=/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr
```

2. Connect to `other.example.com`, and note that the certificate subject corresponds to the certificate created with the wildcard, `*.example.com`:

```
$ openssl s_client -connect localhost:8443 -servername other.example.com
```

Output

```
...
Server certificate
-----BEGIN CERTIFICATE-----
MII...fY=
-----END CERTIFICATE-----
subject=/CN=*.example.com/OU=example/O=com/L=fr/ST=fr/C=fr
issuer=/CN=*.example.com/OU=example/O=com/L=fr/ST=fr/C=fr
```

3. Connect to `unmapped.site.com`, and note that the certificate subject corresponds to the certificate created for the default secret ID:

```
$ openssl s_client -connect localhost:8443 -servername unmapped.site.com
```

Output

```
...
Server certificate
-----BEGIN CERTIFICATE-----
MII..rON
-----END CERTIFICATE-----
subject=/CN=un.mapped.com/OU=example/O=com/L=fr/ST=fr/C=fr
issuer=/CN=un.mapped.com/OU=example/O=com/L=fr/ST=fr/C=fr
```

Configure PingGateway for mutual TLS (server-side)

When PingGateway is *server-side*, applications send requests to PingGateway or request services from PingGateway. PingGateway is acting as a server of the application, and the application is acting as a client.

To run PingGateway as a server for mutual TLS:

- Using information from [Configure PingGateway for TLS \(server-side\)](#), configure PingGateway for TLS connections.
- In `admin.json`, add a [SecretsTrustManager](#) to verify the credentials presented by the client:
 - The trust material is a public key certificate for a client or certificate authority.
 - The SecretsTrustManager must refer to a secret in a secrets store, where the secret is mapped to the certificate.
 - ServerTlsOptions must configure `trustManager` to refer to that SecretsTrustManager and `clientAuth` to require or request the client to authenticate.

The following example is used in [Mutual TLS with PingAM](#).

Linux

```
$HOME/.openig/config/admin.json
```

Windows

```
%appdata%\OpenIG\config\admin.json
```

```

{
  "mode": "DEVELOPMENT",
  "properties": {
    "ig_keystore_directory": "/path/to/ig/secrets",
    "oauth2_client_keystore_directory": "/path/to/client/secrets"
  },
  "connectors": [
    {
      "port": 8080
    },
    {
      "port": 8443,
      "tls": {
        "type": "ServerTlsOptions",
        "config": {
          "alpn": {
            "enabled": true
          },
          "clientAuth": "REQUEST",
          "keyManager": "SecretsKeyManager-1",
          "trustManager": "SecretsTrustManager-1"
        }
      }
    }
  ],
  "heap": [
    {
      "name": "SecretsPasswords",
      "type": "FileSystemSecretStore",
      "config": {
        "directory": "&{ig_keystore_directory}",
        "format": "PLAIN"
      }
    },
    {
      "name": "SecretsKeyManager-1",
      "type": "SecretsKeyManager",
      "config": {
        "signingSecretId": "key.manager.secret.id",
        "secretsProvider": "ServerIdentityStore"
      }
    },
    {
      "name": "SecretsTrustManager-1",
      "type": "SecretsTrustManager",
      "config": {
        "verificationSecretId": "trust.manager.secret.id",
        "secretsProvider": {
          "type": "KeyStoreSecretStore",
          "config": {
            "file": "&{oauth2_client_keystore_directory}/cacerts.p12",
            "storePasswordSecretId": "keystore.pass",
            "secretsProvider": "SecretsPasswords",
            "mappings": [
              {
                "secretId": "trust.manager.secret.id",
                "aliases": ["client-cert"]
              }
            ]
          }
        }
      }
    }
  ]
}

```

```
    }
  },
  {
    "name": "ServerIdentityStore",
    "type": "FileSystemSecretStore",
    "config": {
      "format": "PLAIN",
      "directory": "&{ig_keystore_directory}",
      "suffix": ".pem",
      "mappings": [{
        "secretId": "key.manager.secret.id",
        "format": {
          "type": "PemPropertyFormat"
        }
      }]
    }
  }
]
```

Source: [admin-mtls.json](#)

FIPS 140-3 compliance with PingGateway

To achieve [FIPS 140-3](#) compliance, configure the [Bouncy Castle FIPS libraries](#) with PingGateway. This enables the use of the Bouncy Castle FIPS keystore and security provider in FIPS-approved mode.

Bouncy Castle FIPS is useful when dealing with government data, where meeting the FIPS 140-3 security requirements is necessary for regulatory compliance. Bouncy Castle FIPS doesn't require use of an HSM through a PKCS#11 interface.

Note

Bouncy Castle FIPS is less performant than other keystores. The destroyable keys can't be cached and must be read from the keystore with every use.

To configure PingGateway to use Bouncy Castle FIPS:

1. [Download the Bouncy Castle libraries](#).
2. [Add the libraries to PingGateway](#).
3. [Enable the Bouncy Castle FIPS provider](#).

Download the Bouncy Castle libraries

Before you begin, download the [Bouncy Castle FIPS libraries](#):

File	Description
<code>bc-fips-latestVersion.jar</code>	Bouncy Castle FIPS security provider implementation

File	Description
<code>bcpkix-fips-latestVersion.jar</code>	PKI support
<code>bctls-fips-latestVersion.jar</code>	TLS support
<code>bcutil-fips-latestVersion.jar</code>	ASN.1 utility classes

Ping Identity supports PingGateway and its use of the Bouncy Castle libraries. Ping Identity doesn't support third-party libraries themselves.

Add the libraries to PingGateway

1. Create an `extra` folder to hold additional `.jar` files:

Linux

```
$HOME/.openig/extra
```

Windows

```
%appdata%\OpenIG\extra
```

2. Copy the Bouncy Castle libraries you downloaded into the PingGateway `extra` folder.
3. Create Bouncy Castle FIPS format keystores or truststores from any PingGateway keystores or truststores.

The following example command creates a BCFKS keystore from a PKCS12 `gateway-keystore` file, where the `gateway-keystore.pin` file holds the keystore password:

```
$ keytool \
  -importkeystore \
  -srckeystore /path/to/secrets/gateway-keystore \
  -srcstoretype PKCS12 \
  -srcstorepass:file /path/to/secrets/gateway-keystore.pin \
  -destkeystore /path/to/secrets/gateway-keystore.bcfks \
  -deststoretype BCFKS \
  -deststorepass:file /path/to/secrets/gateway-keystore.pin \
  -providerpath $HOME/.openig/extra/bc-fips-2.0.0.jar \
  -providerclass org.bouncycastle.jcajce.provider.BouncyCastleFipsProvider \
  -noprompt
```

Make sure you do this for all your PingGateway keystore and truststore files.

Enable the Bouncy Castle FIPS provider

Update the PingGateway Java settings to use Bouncy Castle FIPS support:

1. Copy the `$JAVA_HOME/conf/security/java.security` file into the PingGateway `$HOME/.openig` (Linux) or `%appdata%\OpenIG` (Windows) folder.

2. Update the `java.security` file you copied to use the Bouncy Castle FIPS provider:

1. Replace the list of security providers with the following:

```
security.provider.1=org.bouncycastle.jcajce.provider.BouncyCastleFipsProvider
# If entropy in the system is too limited to use the default
# deterministic random bits generator, try with C:HYBRID;ENABLE{All};
#security.provider.1=org.bouncycastle.jcajce.provider.BouncyCastleFipsProvider C:HYBRID;ENABLE{All};
security.provider.2=org.bouncycastle.jsse.provider.BouncyCastleJsseProvider BCFIPS
security.provider.3=SUN
```

2. Update the default key manager factory algorithm:

```
ssl.KeyManagerFactory.algorithm=PKIX
```

3. Save your work.

3. Update the PingGateway `IG_OPTS` environment variable to use the Bouncy Castle FIPS provider:

Linux

```
export IG_OPTS="{IG_OPTS} -Dorg.bouncycastle.fips.approved_only=true -Djava.security.properties=$HOME/.openig/java.security"
```

Windows

```
set "IG_OPTS=%IG_OPTS% -Dorg.bouncycastle.fips.approved_only=true -Djava.security.properties=%appdata%\OpenIG\java.security"
```

4. Start PingGateway.

You have successfully configured PingGateway to use Bouncy Castle FIPS.

Configuring PingGateway

This guide shows you how to configure PingGateway software features.

PingGateway configuration files and routes

PingGateway processes requests and responses by using the following JSON files: [admin.json](#), [config.json](#), [Route](#), and [Router](#).

Configuration location

The following table summarizes the default location of the PingGateway configuration and logs.

Purpose	Default location on Linux	Default location on Windows
Log messages from PingGateway and third-party dependencies	<code>\$HOME/.openig/logs</code>	<code>%appdata%\OpenIG\logs</code>
Administration (admin.json) Gateway (config.json)	<code>\$HOME/.openig/config</code>	<code>%appdata%\OpenIG\config</code>
Routes (Route)	<code>\$HOME/.openig/config/routes</code>	<code>%appdata%\OpenIG\config\routes</code>
SAML 2.0	<code>\$HOME/.openig/SAML</code>	<code>%appdata%\OpenIG\SAML</code>
Groovy scripts for scripted filters and handlers, and other objects	<code>\$HOME/.openig/scripts/groovy</code>	<code>%appdata%\OpenIG\scripts\groovy</code>
Temporary directory To change the directory, configure <code>temporaryDirectory</code> in admin.json	<code>\$HOME/.openig/tmp</code>	<code>%appdata%\OpenIG\tmp</code>
JSON schema for custom audit To change the directory, configure <code>topicSchemasDirectory</code> in AuditService .	<code>\$HOME/.openig/audit-schemas</code>	<code>%appdata%\OpenIG\audit-schemas</code>

Configuration security

Allow the following access to `$HOME/.openig/logs`, `$HOME/.openig/tmp`, and all configuration directories:

- Highest privilege the PingGateway system account.
- Least privilege for specific accounts, on a case-by-case basis
- No privilege for all other accounts, by default

Change the base location

By default, the base location for PingGateway configuration files is in the following directory:

Linux

```
$HOME/.openig
```

Windows

```
%appdata%\OpenIG
```

Change the location by using an argument with the startup command. The following example reads the configuration from the `config` directory under `/path/to/config-dir`:

Linux

```
/path/to/identity-gateway-2025.6.1/bin/start.sh /path/to/config-dir
```

Windows

```
C:\path\to\identity-gateway-2025.6.1\bin\start.bat /path/to/config-dir
```

Route names, IDs, and filenames

The filenames of routes have the extension `.json`, in lowercase.

The router scans the `$HOME/.openig/config/routes` folder for files with the `.json` extension. It uses the route `name` property to order the routes in the configuration. If the route doesn't have a `name` property, the router uses the route ID.

The route ID is managed as follows:

- When you add a route manually to the routes folder, the route ID is the value of the `_id` field. If there is no `_id` field, the route ID is the filename of the added route.
- When you add a route through the Common REST endpoint, the route ID is the value of the mandatory `_id` field.
- When you add a route through Studio, you can edit the default route ID.

Caution

The filename of a route can't be `default.json`, and the route's `name` property and route ID can't be `default`.

Inline and heap objects

Inline objects

An inline object is declared in a route or configuration, outside of the heap.

The following example shows an inline declaration for a handler to route requests:

```
{
  "handler": {
    "name": "My Router",
    "type": "Router"
  }
}
```

The `name` property for inline objects is optional but useful for logging.

Other objects in the configuration can never refer to named or unnamed inline objects.

Heap objects

A heap object is declared inside the heap.

The following example shows a named router in the heap, and a handler that refers to the router by its name:

```
{
  "handler": "My Router",
  "heap": [
    {
      "name": "My Router",
      "type": "Router"
    }
  ]
}
```

The `name` property for heap objects is required. Other objects in the configuration or its child configurations can refer to the heap object by its `name` property.

Comment the configuration

JSON format doesn't specify a notation for comments. If PingGateway does not recognize a JSON field name, it ignores the field. As a result, it's possible to use comments in configuration files.

The following conventions are available for commenting:

- A `comment` field to add text comments. The following example includes a text comment.

```
{
  "name": "capture",
  "type": "CaptureDecorator",
  "comment": "Write request and response information to the logs",
  "config": {
    "captureEntity": true
  }
}
```

- An underscore (`_`) to comment a field temporarily. The following example comments out `"captureEntity": true`, and as a result it uses the default setting (`"captureEntity": false`).

```
{
  "name": "capture",
  "type": "CaptureDecorator",
  "config": {
    "_captureEntity": true
  }
}
```

Restart after configuration change

You can change routes or change a property that's read at runtime or that relies on a runtime expression without needing to restart PingGateway to take the change into account.

Stop and restart PingGateway only when you make the following changes:

- Change the configuration of any route, when the `scanInterval` of Router is `disabled` (refer to [Router](#)).
- Add or change an external object used by the route, such as an environment variable, system property, external URL, or keystore.
- Add or update `config.json` or `admin.json`.

Prevent reload of routes

To prevent routes from being reloaded after startup, stop PingGateway, edit the router `scanInterval`, and restart PingGateway. When the interval is set to `disabled`, routes are loaded only at startup:

```
{
  "name": "Router",
  "type": "Router",
  "config": {
    "scanInterval": "disabled"
  }
}
```

The following example changes the location where the router looks for the routes:

```
{
  "name": "Router",
  "type": "Router",
  "config": {
    "directory": "/path/to/safe/routes",
    "scanInterval": "disabled"
  }
}
```

Reserved routes

Learn more in [Reserved routes](#).

PingGateway routes and common REST

Note

When PingGateway is in production mode, you can't manage, list, or read routes through Common REST. For information about switching to development mode, refer to [PingGateway operating modes](#).

Through Common REST, you can read, add, delete, and edit routes on PingGateway without manually accessing the file system. You can also list the routes in the order that they're loaded in the configuration, and set fields to filter the information about the routes.

The following examples show some ways to manage routes through Common REST. For more information, refer to [About Common REST](#).

Manage routes through Common REST

Before you start, prepare PingGateway as described in the [Getting started with PingGateway](#).

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/00-crest.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-crest.json
```

```
{
  "name": "crest",
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/plain; charset=UTF-8" ]
      },
      "entity": "Hello world!"
    }
  },
  "condition": "${find(request.uri.path, '^/crest')}"
}
```

Source: [00-crest.json](#)

To check that the route is working, access the route on: <http://ig.example.com:8080/crest>.

2. To read a route through Common REST:

1. Enter the following command in a terminal window:

```
$ curl -v http://ig.example.com:8085/api/system/objects/_router/routes/00-crest?\_prettyPrint\=true
```

The route is displayed. Note that the route `_id` is displayed in the JSON of the route.

3. To add a route through Common REST:

1. Move `$HOME/.openig/config/routes/00-crest.json` to `/tmp/00-crest.json`.
2. Check in `$HOME/.openig/logs/route-system.log` that the route has been removed from the configuration, where `$HOME/.openig` is the instance directory. To double check, go to <http://ig.example.com:8080/crest>. You should get an HTTP 404 error.
3. Enter the following command in a terminal window:

```
$ curl -X PUT http://ig.example.com:8085/api/system/objects/_router/routes/00-crest \
-d "@tmp/00-crest.json" \
--header "Content-Type: application/json"
```

This command posts the file in `/tmp/00-crest.json` to the `routes` directory.

4. Check in `$HOME/.openig/logs/route-system.log` that the route has been added to configuration, where `$HOME/.openig` is the instance directory. To double-check, go to <http://ig.example.com:8080/crest>. You should see the "Hello world!" message.

4. To edit a route through Common REST:

1. Edit `/tmp/00-crest.json` to change the message displayed by the response handler in the route.
2. Enter the following command in a terminal window:

```
$ curl -X PUT http://ig.example.com:8085/api/system/objects/_router/routes/00-crest \
-d "@tmp/00-crest.json" \
--header "Content-Type: application/json" \
--header "If-Match: *"
```

This command deploys the route with the new configuration. Because the changes are persisted into the configuration, the existing `$HOME/.openig/config/routes/00-crest.json` is replaced with the edited version in `/tmp/00-crest.json`.

3. Check in `$HOME/.openig/logs/route-system.log` that the route has been updated, where `$HOME/.openig` is the instance directory. To double-check, go to <http://ig.example.com:8080/crest> to confirm that the displayed message has changed.

5. To delete a route through Common REST:

1. Enter the following command in a terminal window:

```
$ curl -X DELETE http://ig.example.com:8085/api/system/objects/_router/routes/00-crest
```


2. Check in `$HOME/.openig/logs/route-system.log` that the route has been removed from the configuration, where `$HOME/.openig` is the instance directory. To double-check, go to <http://ig.example.com:8080/crest>. You should get an HTTP 404 error.

6. To list the routes deployed on the router, in the order that they are tried by the router:

1. Enter the following command in a terminal window:

```
$ curl "http://ig.example.com:8085/api/system/objects/_router/routes?_queryFilter=true"
```

The list of loaded routes is displayed.

PingGateway decorators

Decorators are heap objects to extend what other objects can do. PingGateway defines `baseURI`, `capture`, `timer`, and `tracing` decorators you can use without explicitly configuring them. You can find more information about available decorators in [PingGateway decorators](#).

Use decorations that are compatible with the object type. For example, `timer` records the time to process filters and handlers, but doesn't record information for other object types. Similarly, `baseURI` overrides the scheme, host, and ports, but has no other effect.

In a route, you can decorate individual objects, the route handler, and the heap. PingGateway applies decorations in this order:

1. Decorations declared on individual objects. Local decorations that are part of an object's declaration are inherited wherever the object is used.
2. `globalDecorations` declared in parent routes, then in child routes, and then in the current route.
3. Decorations declared on the route handler.

Decorate individual objects in a route

To decorate individual objects, add the decorator's name value as a top-level field of the object, next to `type` and `config`.

In this example, the decorator captures all requests going into the `SingleSignOnFilter`, and all responses coming out of the `SingleSignOnFilter`:

```

{
  "baseURI" : "http://app.example.com:8081",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "capture": "all",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

Source: [decorate-indiv.json](#) 

Decorate the route handler

To decorate the handler for a route, add the decorator as a top-level field of the route.

In this example, the decorator captures all requests and responses that traverse the route:

```

{
  "baseURI" : "http://app.example.com:8081",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent" : {
          "username" : "ig_agent",
          "passwordSecretId" : "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "capture": "all",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  }
}

```

Source: [decorate-route-handler.json](#)

Decorate the route heap

To decorate all compatible objects in a route, configure `globalDecorators` as a top-level field of the route. The `globalDecorators` field takes a map of the decorations to apply.

To decorate all compatible objects declared in `config.json` or `admin.json`, configure `globalDecorators` as a top-level field in `config.json` or `admin.json`.

In the following example, the route has capture and timer decorations. The capture decoration applies to `AmService`, `Chain`, `SingleSignOnFilter`, and `ReverseProxyHandler`. The timer decoration doesn't apply to `AmService` because it is not a filter or handler, but does apply to `Chain`, `SingleSignOnFilter`, and `ReverseProxyHandler`:

```

{
  "baseURI" : "http://app.example.com:8081",
  "globalDecorators":
  {
    "capture": "all",
    "timer": true
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  }
}

```

Source: [decorate-route-heap.json](#)

Decorate named objects differently in different parts of the configuration

When a filter or handler is configured in `config.json` or in the heap, it can be used many times in the configuration. To decorate each use of the filter or handler individually, use a [Delegate](#).

In the following example, an `AmService` heap object configures an `amHandler` to delegate tasks to `ForgeRockClientHandler`, and capture all requests and responses passing through the handler.

```
{
  "type": "AmService",
  "config": {
    "agent": {
      "agent": {
        "username": "ig_agent",
        "passwordSecretId": "agent.secret.id"
      },
      "secretsProvider": "SystemAndEnvSecretStore-1",
      "amHandler": {
        "type": "Delegate",
        "capture": "all",
        "config": {
          "delegate": "ForgeRockClientHandler"
        }
      },
      "url": "http://am.example.com:8088/openam"
    }
  }
}
```

You can use the same `ForgeRockClientHandler` in another part of the configuration, in a different route for example, without adding a capture decorator. Requests and responses that pass through that use of the handler are not captured.

Decorate PingGateway's interactions with AM

To log interactions between PingGateway and AM, delegate message handling to a `ForgeRockClientHandler`, and capture the requests and responses passing through the handler. When the `ForgeRockClientHandler` communicates with an application, it sends Common Audit transaction IDs.

In the following example, the `accessTokenResolver` delegates message handling to a decorated `ForgeRockClientHandler`:

```
"accessTokenResolver": {
  "name": "token-resolver-1",
  "type": "TokenIntrospectionAccessTokenResolver",
  "config": {
    "amService": "AmService-1",
    "providerHandler": {
      "capture": "all",
      "type": "Delegate",
      "config": {
        "delegate": "ForgeRockClientHandler"
      }
    }
  }
}
```

To try the example, replace the `accessTokenResolver` in the PingGateway route of [Validating PingAM access tokens with introspection](#). Test the setup as described for the example, and note that the route's log file contains an HTTP call to the introspection endpoint.

Decorate an object multiple times

Decorations can apply more than once. For example, if you set a decoration on a route and another decoration on an object defined within the route, PingGateway applies the decoration twice. In the following route, the request is captured twice:

```
{
  "handler": {
    "type": "ReverseProxyHandler",
    "capture": "request"
  },
  "capture": "all"
}
```

When an object has multiple decorations, the decorations are applied in the order they appear in the JSON.

In the following route, the handler is decorated with a `baseURI` first, and a `capture` second:

```
{
  "name": "myroute",
  "baseURI": "http://app.example.com:8081",
  "capture": "all",
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/plain; charset=UTF-8" ]
      },
      "entity": "Hello world, from myroute!"
    }
  },
  "condition": "${find(request.uri.path, '^/myroute1')}"
}
```

The decoration can be represented as `capture[ baseUri[ handler ] ]`. When a request is processed, it is captured, and then rebased, and then processed by the handler: The log for this route shows that the capture occurs before the rebase:

```
2018-09-10T13:23:18,990Z | INFO | http-nio-8080-exec-1 | o.f.o.d.c.C.c.top-level-handler | @myroute |

--- (request) id:f792d2ad-4409-4907-bc46-28e1c3c19ac3-7 --->

GET http://ig.example.com:8080/myroute HTTP/1.1
...
```

Conversely, in the following route, the handler is decorated with a `capture` first, and a `baseURI` second:

```
{
  "name": "myroute",
  "capture": "all",
  "baseURI": "http://app.example.com:8081",
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/plain; charset=UTF-8" ]
      },
      "entity": "Hello, world from myroute1!"
    }
  },
  "condition": "${find(request.uri.path, '^/myroute')}"
}
```

The decoration can be represented as `baseUri[ capture[ handler ] ]`. When a request is processed, it is rebased, and then captured, and then processed by the handler. The log for this route shows that the rebase occurs before the capture:

```
2018-09-10T13:07:07,524Z | INFO | http-nio-8080-exec-1 | o.f.o.d.c.C.c.top-level-handler | @myroute |
--- (request) id:3c26ab12-3cc0-403e-bec6-43bf5621f657-7 --->
GET http://app.example.com:8081/myroute HTTP/1.1
...
```

Guidelines for naming decorators

To prevent unwanted behavior, consider the following points when you name decorators:

- Avoid decorators named `comment` or `comments`, and avoid reserved field names. Instead of using alphanumeric field names, consider using dots in your decorator names, such as `my.decorator`.
- For heap objects, avoid the reserved names `config`, `name`, and `type`.
- For routes, avoid the reserved names `auditService`, `baseURI`, `condition`, `globalDecorators`, `heap`, `handler`, `name`, `secrets`, and `session`.
- In `config.json`, avoid the reserved name `temporaryStorage`.

PingGateway operating modes

Production mode (immutable mode)

To prevent unwanted changes to the configuration, PingGateway is by default in production mode after installation. Production mode has the following characteristics:

- The `/routes` endpoint isn't exposed or accessible.

- Studio is effectively disabled. You can't manage, list, or even read routes through Common REST.
- By default, other endpoints, such as `/share` and `api/info` are exposed to the loopback address only.

To change the default protection for specific endpoints, configure an `"apiProtectionFilter"` in `admin.json`.

Development mode (mutable mode)

In development mode, by default all endpoints are open and accessible.

You can create, edit, and deploy routes through [PingGateway Studio](#), manage routes through [Common REST](#) without authentication or authorization, and access [PingGateway API descriptors](#).

Use development mode to evaluate or demo PingGateway, or to develop configurations on a single instance. This mode isn't suitable for production.

For information about Restrict access to Studio in development mode, refer to [Restrict access to Studio](#).

Switch from production mode to development mode

Switch from production mode to development mode in one of the following ways, applied in order of precedence:

1. Add the following configuration to `admin.json`, and restart PingGateway:

```
{
  "mode": "DEVELOPMENT",
  "connectors": [
    { "port" : 8080 }
  ]
}
```

Source: [admin-dev.json](#) 

2. Define an environment variable for the configuration token `ig.run.mode`, and then start PingGateway in the same terminal.

If `mode` is not defined in `admin.json`, the following example starts an instance of PingGateway in development mode:

Linux

```
$ IG_RUN_MODE=development /path/to/identity-gateway-2025.6.1/bin/bin/start.sh
```


Windows

```
C:\IG_RUN_MODE=development
C:\path\to\identity-gateway-2025.6.1\bin\start.bat %appdata%\OpenIG
```

3. Define a system property for the configuration token `ig.run.mode` when you start PingGateway.

If `mode` is not defined in `admin.json` or an `IG_RUN_MODE` environment variable is not set, the following file starts PingGateway with the system property `ig.run.mode` to force development mode:

Linux

```
$HOME/.openig/env.sh
```

Windows

```
%appdata%\OpenIG\env.sh
```

```
export JAVA_OPTS='-Dig.run.mode=development'
```

Switch from development mode to production mode

Switch from development mode to production mode to prevent unwanted changes to the configuration.

1. In `$HOME/.openig/config/admin.json` (on Windows, `%appdata%\OpenIG\config`), change the value of `mode` from `DEVELOPMENT` to `PRODUCTION`:

```
{
  "mode": "PRODUCTION"
}
```

Source: [admin.json](#)

The file changes the operating mode from development mode to production mode. For more information about the `admin.json` file, refer to [AdminHttpApplication \(admin.json\)](#).

The value set in `admin.json` overrides any value set by the `ig.run.mode` configuration token when it is used in an environment variable or system property. For information about `ig.run.mode`, refer to [Configuration Tokens](#).

2. (Optional) Prevent routes from being reloaded after startup:
 - To prevent all routes in the configuration from being reloaded, add a `config.json` as described in the [Getting started with PingGateway](#), and configure the `scanInterval` property of the main Router.
 - To prevent individual routes from being reloaded, configure the `scanInterval` of the routers in those routes.

```
{
  "type": "Router",
  "config": {
    "scanInterval": "disabled"
  }
}
```

Learn more in [Router](#).

3. Restart PingGateway.

When PingGateway starts up, the route endpoints aren't displayed in the logs, and aren't available. You can't access Studio on <http://ig.example.com:8085/studio>.

PingGateway configuration templates

This page shows template routes for common configurations. Before you start, set up PingGateway as described in [Getting started with PingGateway](#).

Modify the template routes for your deployment. Before you use a route in production, review the points in [PingGateway security](#).

Proxy and capture

When you followed the instructions in [Getting started with PingGateway](#), you enabled PingGateway to proxy and capture application requests and server responses.

This template route uses a Dispatcher to change the scheme to HTTPS on login.

```

{
  "heap": [
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "comment": "Testing only: blindly trust the server cert for HTTPS.",
      "config": {
        "tls": {
          "type": "ClientTlsOptions",
          "config": {
            "trustManager": {
              "type": "TrustAllManager"
            },
            "hostnameVerifier": "ALLOW_ALL"
          }
        }
      }
    }
  ],
  "handler": {
    "type": "DispatchHandler",
    "config": {
      "bindings": [
        {
          "condition": "${request.uri.path == '/login'}",
          "handler": "ReverseProxyHandler",
          "baseURI": "https://app.example.com:8444"
        },
        {
          "condition": "${request.uri.scheme == 'http'}",
          "handler": "ReverseProxyHandler",
          "baseURI": "http://app.example.com:8081"
        },
        {
          "handler": "ReverseProxyHandler",
          "baseURI": "https://app.example.com:8444"
        }
      ]
    }
  },
  "condition": "${find(request.uri.query, 'demo=capture')}"
}

```

Source: [20-capture.json](#)

Try this example with the sample application:

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/20-capture.json
```

Windows

```
%appdata%\OpenIG\config\routes\20-capture.json
```

2. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^.*\\.ico$') or matchesWithRegex(request.uri.path, '^.*\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

3. Go to <http://ig.example.com:8080/login?demo=capture>.

The sample application display the login page.

To use this as a default route with a real application:

1. Replace the test ReverseProxyHandler with one that is configured to trust the application's public key server certificate. Otherwise, use a ReverseProxyHandler that references a truststore holding the certificate.

Configure the ReverseProxyHandler to strictly verify hostnames for outgoing SSL connections.

In production, don't use `TrustAllManager` for `trustManager`, or `ALLOW_ALL` for `hostnameVerifier`.

2. Change the baseURI settings to match the target application.
3. Remove the route-level condition on the handler that specifies a `demo` query string parameter.

Simple login form

This template route intercepts the login page request, replaces it with a login form, and logs the user into the target application with hard-coded username and password credentials.

```

{
  "heap": [
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "comment": "Testing only: blindly trust the server cert for HTTPS.",
      "config": {
        "tls": {
          "type": "ClientTlsOptions",
          "config": {
            "trustManager": {
              "type": "TrustAllManager"
            },
            "hostnameVerifier": "ALLOW_ALL"
          }
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "PasswordReplayFilter",
          "config": {
            "loginPage": "${request.uri.path == '/login'}",
            "request": {
              "method": "POST",
              "uri": "https://app.example.com:8444/login",
              "form": {
                "username": [
                  "MY_USERNAME"
                ],
                "password": [
                  "MY_PASSWORD"
                ]
              }
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
},
"condition": "${find(request.uri.query, 'demo=simple')}"
}

```

Source: [21-simple.json](#)

Try this example with the sample application:

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/21-simple.json
```

Windows

```
%appdata%\OpenIG\config\routes\21-simple.json
```

2. Replace `MY_USERNAME` with `demo`, and `MY_PASSWORD` with `Ch4ng31t`.
3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^.*\\\\\\.ico$') or matchesWithRegex(request.uri.path, '^.*\\\\\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

4. Go to <http://ig.example.com:8080/login?demo=simple>.

The sample application profile page for the demo user displays information about the request.

To use this as a default route with a real application:

1. Replace the test `ReverseProxyHandler` with one that is configured to trust the application's public key server certificate. Otherwise, use a `ReverseProxyHandler` that references a truststore holding the certificate.

Configure the `ReverseProxyHandler` to strictly verify hostnames for outgoing SSL connections.

In production, don't use `TrustAllManager` for `trustManager`, or `ALLOW_ALL` for `hostnameVerifier`.

2. Change the `uri`, `form`, and `baseURI` to match the target application.
3. Remove the route-level condition on the handler that specifies a `demo` query string parameter.

Login form with cookie from login page

This template route intercepts the login page request, replaces it with the login form, and signs the user on to the target application with hard-coded username and password credentials.

The route uses a default [CookieFilter](#) to manage cookies. By default, the filter intercepts cookies from the protected application and stores them in the PingGateway session. It doesn't send the cookies to the browser.

```

{
  "heap": [
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "comment": "Testing only: blindly trust the server cert for HTTPS.",
      "config": {
        "tls": {
          "type": "ClientTlsOptions",
          "config": {
            "trustManager": {
              "type": "TrustAllManager"
            },
            "hostnameVerifier": "ALLOW_ALL"
          }
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "PasswordReplayFilter",
          "config": {
            "loginPage": "${request.uri.path == '/login'}",
            "request": {
              "method": "POST",
              "uri": "https://app.example.com:8444/login",
              "form": {
                "username": [
                  "MY_USERNAME"
                ],
                "password": [
                  "MY_PASSWORD"
                ]
              }
            }
          }
        },
        {
          "type": "CookieFilter"
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  },
  "condition": "${find(request.uri.query, 'demo=cookie')}"
}

```

Source: [22-cookie.json](#)

Try this example with the sample application:

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/22-cookie.json
```

Windows

```
%appdata%\OpenIG\config\routes\22-cookie.json
```

2. Replace `MY_USERNAME` with `kramer`, and `MY_PASSWORD` with `N3wman12`.
3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name": "00-static-resources",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^.*\\\\\\\\.ico$') or matchesWithRegex(request.uri.path, '^.*\\\\\\\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

4. Go to <http://ig.example.com:8080/login?demo=cookie>.

The sample application page displays.

5. Refresh your connection to <http://ig.example.com:8080/login?demo=cookie>.

Compared to [Login form with cookie from login page](#), this example displays additional information about the session cookie:

```
Cookies session-cookie=123...
```

To use this as a default route with a real application:

1. Replace the test `ReverseProxyHandler` with one that is configured to trust the application's public key server certificate. Otherwise, use a `ReverseProxyHandler` that references a truststore holding the certificate.

Configure the `ReverseProxyHandler` to strictly verify hostnames for outgoing SSL connections.

In production, don't use `TrustAllManager` for `trustManager`, or `ALLOW_ALL` for `hostnameVerifier`.

2. Change the `uri` and `form` to match the target application.
3. Remove the route-level condition on the handler that specifies a `demo` query string parameter.

Login form with password replay and cookie filters

When a user without a valid session tries to access a protected application, this template route works with an application to return a login page.

The route uses a `PasswordReplayFilter` to find the login page with a pattern to match a mock AM classic UI page.

The route uses a default `CookieFilter` to manage cookies. The `CookieFilter` retains cookies from the browser and doesn't forward them to the protected application. Similarly, the `CookieFilter` retains cookies in set-cookie headers from the protected application and doesn't forward them to the browser.

```

{
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "PasswordReplayFilter",
          "config": {
            "loginPageContentMarker": "OpenAM\\s\\(Login\\)",
            "request": {
              "comments": [
                "An example based on OpenAM classic UI: ",
                "uri is for the OpenAM login page; ",
                "IDToken1 is the username field; ",
                "IDToken2 is the password field; ",
                "host takes the OpenAM FQDN:port.",
                "The sample app simulates OpenAM."
              ],
              "method": "POST",
              "uri": "http://app.example.com:8081/openam/UI/Login",
              "form": {
                "IDToken0": [
                  ""
                ],
                "IDToken1": [
                  "demo"
                ],
                "IDToken2": [
                  "Ch4ng31t"
                ],
                "IDButton": [
                  "Log+In"
                ],
                "encoded": [
                  "false"
                ]
              },
              "headers": {
                "host": [
                  "app.example.com:8081"
                ]
              }
            }
          }
        },
        {
          "type": "CookieFilter"
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  },
  "condition": "${find(request.uri.query, 'demo=classic')}"
}

```

Source: [23-classic.json](#)

Try this example with the sample application:

1. Save the file as `$HOME/.openig/config/routes/23-classic.json`.
2. Use the following `curl` command to check that it works:

```
$ curl -D- http://ig.example.com:8080/login?demo=classic
```

Output

```
HTTP/1.1 200 OK
Set-Cookie: IG_SESSIONID=24446BA29E866F840197C8E0EAD57A89; Path=/; HttpOnly
...
```

To use this as a default route with a real application:

1. Change the `uri` and `form` to match the target application.
2. Remove the route-level condition on the handler that specifies a `demo` query string parameter.

Login which requires a hidden value from the login page

This template route extracts a hidden value from the login page and posts a static login form to the target application.

```

{
  "properties": {
    "appBaseUri": "https://app.example.com:8444"
  },
  "heap": [
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "comment": "Testing only: blindly trust the server cert for HTTPS.",
      "config": {
        "tls": {
          "type": "ClientTlsOptions",
          "config": {
            "trustManager": {
              "type": "TrustAllManager"
            },
            "hostnameVerifier": "ALLOW_ALL"
          }
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "PasswordReplayFilter",
          "config": {
            "loginPage": "${request.uri.path == '/login'}",
            "loginPageExtractions": [
              {
                "name": "hidden",
                "pattern": "loginToken\\s+value=\"(.*)\""
              }
            ]
          }
        },
        {
          "type": "RequestForm",
          "config": {
            "method": "POST",
            "uri": "${appBaseUri}/login",
            "form": {
              "username": [
                "MY_USERNAME"
              ],
              "password": [
                "MY_PASSWORD"
              ],
              "hiddenValue": [
                "${attributes.extracted.hidden}"
              ]
            }
          }
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  },
  "condition": "${find(request.uri.query, 'demo=hidden')}",
  "baseUri": "${appBaseUri}"
}

```

Source: [24-hidden.json](#)

The parameters in the PasswordReplayFilter form, `MY_USERNAME` and `MY_PASSWORD`, take string values or expressions.

Try this example with the sample application:

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/24-hidden.json
```

Windows

```
%appdata%\OpenIG\config\routes\24-hidden.json
```

2. Replace `MY_USERNAME` with `scarter`, and `MY_PASSWORD` with `S9rain12`.
3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^.*\\.ico$') or matchesWithRegex(request.uri.path, '^.*\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

4. Go to <http://ig.example.com:8080/login?demo=hidden>.

To use this as a default route with a real application:

1. Replace the test ReverseProxyHandler with one that is configured to trust the application's public key server certificate. Otherwise, use a ReverseProxyHandler that references a truststore holding the certificate.

Configure the ReverseProxyHandler to strictly verify hostnames for outgoing SSL connections.

In production, don't use `TrustAllManager` for `trustManager`, or `ALLOW_ALL` for `hostnameVerifier`.

2. Change the `loginPage`, `loginPageExtractions`, `uri`, and `form` to match the target application.
3. Remove the route-level condition on the handler that specifies a `demo` query string parameter.

HTTP and HTTPS application

This template route proxies traffic to an application with both HTTP and HTTPS ports. The application uses HTTPS for authentication and HTTP for the general application features. When all login requests use HTTPS, you must add the login filters and handlers to the chain.

```
{
  "heap": [
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "comment": "Testing only: blindly trust the server cert for HTTPS.",
      "config": {
        "tls": {
          "type": "ClientTlsOptions",
          "config": {
            "trustManager": {
              "type": "TrustAllManager"
            },
            "hostnameVerifier": "ALLOW_ALL"
          }
        }
      }
    }
  ],
  "handler": {
    "type": "DispatchHandler",
    "config": {
      "bindings": [
        {
          "condition": "${request.uri.scheme == 'http'}",
          "handler": "ReverseProxyHandler",
          "baseURI": "http://app.example.com:8081"
        },
        {
          "condition": "${request.uri.path == '/login'}",
          "handler": {
            "type": "Chain",
            "config": {
              "comment": "Add one or more filters to handle login.",
              "filters": [],
              "handler": "ReverseProxyHandler"
            }
          },
          "baseURI": "https://app.example.com:8444"
        },
        {
          "handler": "ReverseProxyHandler",
          "baseURI": "https://app.example.com:8444"
        }
      ]
    }
  },
  "condition": "${find(request.uri.query, 'demo=https')}"
}
```

Source: [25-https.json](#)

Try this example with the sample application:

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/25-https.json
```

Windows

```
%appdata%\OpenIG\config\routes\25-https.json
```

2. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^.*\\\\\\\\.ico$') or matchesWithRegex(request.uri.path, '^.*\\\\\\\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

3. Go to <http://ig.example.com:8080/login?demo=https>.

The login page of the sample application is displayed.

To use this as a default route with a real application:

1. Replace the test ReverseProxyHandler with one that is configured to trust the application's public key server certificate. Otherwise, use a ReverseProxyHandler that references a truststore holding the certificate.

Configure the ReverseProxyHandler to strictly verify hostnames for outgoing SSL connections.

In production, don't use `TrustAllManager` for `trustManager`, or `ALLOW_ALL` for `hostnameVerifier`.

2. Change the `loginPage`, `loginPageExtractions`, `uri`, and `form` to match the target application.
3. Remove the route-level condition on the handler that specifies a `demo` query string parameter.

AM integration with headers

This template route logs the user into the target application using headers like those from AM policy agents. If a header contains only a username or subject to look up in an external data source, you must add an attribute filter to the chain to retrieve the credentials.

```

{
  "heap": [
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "comment": "Testing only: blindly trust the server cert for HTTPS.",
      "config": {
        "tls": {
          "type": "ClientTlsOptions",
          "config": {
            "trustManager": {
              "type": "TrustAllManager"
            },
            "hostnameVerifier": "ALLOW_ALL"
          }
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "PasswordReplayFilter",
          "config": {
            "loginPage": "${request.uri.path == '/login'}",
            "request": {
              "method": "POST",
              "uri": "https://app.example.com:8444/login",
              "form": {
                "username": [
                  "${request.headers['username']}[0]}"
                ],
                "password": [
                  "${request.headers['password']}[0]}"
                ]
              }
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
},
"condition": "${find(request.uri.query, 'demo=headers')}"
}

```

Source: [26-headers.json](#)

Try this example with the sample application:

1. Add the route to PingGateway:

Linux

```
$HOME/.openig/config/routes/26-headers.json
```


Windows

```
%appdata%\OpenIG\config\routes\26-headers.json
```

2. Use the `curl` command to simulate the headers from a policy agent:

```
$ curl \
--header "username: kvaughan" \
--header "password: B5ibery12" \
http://ig.example.com:8080/login?demo=headers
```

Output

```
...
<title id="title">Howdy, kvaughan</title>
...
```

To use this as a default route with a real application:

1. Replace the test `ReverseProxyHandler` with one that is configured to trust the application's public key server certificate. Otherwise, use a `ReverseProxyHandler` that references a truststore holding the certificate.

Configure the `ReverseProxyHandler` to strictly verify hostnames for outgoing SSL connections.

In production, don't use `TrustAllManager` for `trustManager`, or `ALLOW_ALL` for `hostnameVerifier`.

2. Change the `loginPage`, `uri`, and `form` to match the target application.
3. Remove the route-level condition on the handler that specifies a `demo` query string parameter.

Extending PingGateway

To achieve complex server interactions or intensive data transformations that you can't currently achieve with scripts or existing handlers, filters, or expressions, extend PingGateway through scripting and customization. The following sections describe how to extend PingGateway:

Add .jar files for extensions

PingGateway includes a complete Java [application programming interface](#) for extending your deployment with customizations. Learn more in [Extend PingGateway through the Java API](#).

Create a directory to hold .jar files for PingGateway extensions:

Linux

```
$HOME/.openig/extra
```

Windows

```
%appdata%\OpenIG\extra
```

When PingGateway starts up, the JVM loads .jar files in the `extra` directory.

Extend PingGateway through scripts

The following sections describe how to extend PingGateway through scripts:

About scripts

Important

When writing scripts or Java extensions that use the Promise API, avoid the blocking methods `get()`, `getOrThrow()`, and `getOrThrowUninterruptibly()`. A promise represents the result of an asynchronous operation; therefore, using a blocking method to wait for the result can cause deadlocks and/or race issues.

Instead, consider using `then()` methods, such as `thenOnResult()`, `thenAsync()`, or `thenCatch()`, which allow execution blocks to be executed when the response is available.

Blocking code example

```
def response = next.handle(ctx, req).get() // Blocking method 'get' used
response.headers['new'] = "new header value"
return response
```

Non-blocking code example

```
return next.handle(ctx, req)
    .thenOnResult { response ->
        response.headers['new'] = "new header value"
    }
```

PingGateway supports the Groovy dynamic scripting language through the use of the scriptable objects. For information about scriptable object types, their configuration, and properties, refer to [PingGateway scripts](#).

Scriptable objects are configured by the script's Internet media type, and either a source script included in the JSON configuration, or a file script that PingGateway reads from a file. The configuration can optionally supply arguments to the script.

PingGateway provides global variables to scripts at runtime, and provides access to Groovy's built-in functionality. Scripts can:

- Access the request and the context.
- Store variables across executions.
- Write messages to logs.
- Make requests to a web service.
- Access responses returned in promise callback methods.

Before trying the scripts in this chapter, install and configure PingGateway as described in the [Getting started with PingGateway](#).

When developing and debugging your scripts, consider configuring a capture decorator to log requests, responses, and context data in JSON form. You can then turn off capturing when you move to production. Learn more in [CaptureDecorator](#).

Use a reference file script

The following example defines a ScriptableFilter written in Groovy and stored in the following file:

Linux

```
$HOME/.openig/scripts/groovy/SimpleFormLogin.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\SimpleFormLogin.groovy
```

```
{
  "name": "SimpleFormLogin",
  "type": "ScriptableFilter",
  "config": {
    "type": "application/x-groovy",
    "file": "SimpleFormLogin.groovy"
  }
}
```

Relative paths in the file field depend on how PingGateway is installed. If PingGateway is installed in an application server, then paths for Groovy scripts are relative to `$HOME/.openig/scripts/groovy` (or `%appdata%\OpenIG\scripts\groovy`).

The base location `$HOME/.openig/scripts/groovy` (or `%appdata%\OpenIG\scripts\groovy`) is on the classpath when the scripts are executed. If some Groovy scripts aren't in the default package, but instead have their own package names, they belong in the directory corresponding to their package name. For example, a script in package `com.example.groovy` belongs in `$HOME/.openig/scripts/groovy/com/example/groovy/` (or `%appdata%\OpenIG\scripts\groovy\com\example\groovy\`).

Scripts in Studio

You can use Studio to configure a ScriptableFilter or scriptableThrottlingPolicy, or use scripts to configure scopes in OAuth2ResourceServerFilter.

During configuration, you can enter the script directly into the object, or you can use a stored reference script. Note the following points about creating and using reference scripts:

- When you enter a script directly into an object, the script is added to the list of reference scripts.
- You can use a reference script in multiple objects in a route, but if you edit a reference script, all objects that use it are updated with the change.
- If you delete an object that uses a script, or remove the object from the chain, the script that it references remains in the list of scripts.
- If a reference script is used in an object, you can't rename or delete the script.

For an example of creating a ScriptableThrottlingPolicy in Studio, refer to [Configure Scriptable Throttling](#). For information about using Studio, refer to [Adding Configuration to a Route](#).

Script dispatch

To route requests when the conditions are complicated, use a `ScriptableHandler` instead of a `DispatchHandler` as described in [DispatchHandler](#).

1. Add the following script to PingGateway:

Linux

```
$HOME/.openig/scripts/groovy/DispatchHandler.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\DispatchHandler.groovy
```

```
/*
 * This simplistic dispatcher matches the path part of the HTTP request.
 * If the path is /mylogin, it checks Username and Password headers,
 * accepting bjensen:H1falutin, and returning HTTP 403 Forbidden to others.
 * Otherwise it returns HTTP 401 Unauthorized.
 */

// Rather than returning a Promise of a Response from an external source,
// this script returns the response itself.
response = new Response(Status.OK);

switch (request.uri.path) {

    case "/mylogin":

        if (request.headers.Username.values[0] == "bjensen" &&
            request.headers.Password.values[0] == "H1falutin") {

            response.status = Status.OK
            response.entity = "<html><p>Welcome back, Babs!</p></html>"

        } else {

            response.status = Status.FORBIDDEN
            response.entity = "<html><p>Authorization required</p></html>"

        }

        break

    default:

        response.status = Status.UNAUTHORIZED
        response.entity = "<html><p>Please <a href='./mylogin'>log in</a>.</p></html>"

        break

}

// Return the locally created response, no need to wrap it into a Promise
return response
```

Source: [DispatchHandler.groovy](#)

2. Add the following route to PingGateway to set up headers required by the script when the user logs in:

Linux

```
$HOME/.openig/config/routes/98-dispatch.json
```

Windows

```
%appdata%\OpenIG\config\routes\98-dispatch.json
```

```

{
  "heap": [
    {
      "name": "DispatchHandler",
      "type": "DispatchHandler",
      "config": {
        "bindings": [{
          "condition": "${find(request.uri.path, '/mylogin')}",
          "handler": {
            "type": "Chain",
            "config": {
              "filters": [
                {
                  "type": "HeaderFilter",
                  "config": {
                    "messageType": "REQUEST",
                    "add": {
                      "Username": [
                        "bjensen"
                      ],
                      "Password": [
                        "H1falutin"
                      ]
                    }
                  }
                }
              ]
            }
          },
          "handler": "Dispatcher"
        }
      ],
      "handler": "Dispatcher"
    },
    {
      "handler": "Dispatcher",
      "condition": "${find(request.uri.path, '/dispatch')}"
    }
  ]
},
{
  "name": "Dispatcher",
  "type": "ScriptableHandler",
  "config": {
    "type": "application/x-groovy",
    "file": "DispatchHandler.groovy"
  }
},
{
  "handler": "DispatchHandler",
  "condition": "${find(request.uri.path, '^/dispatch') or find(request.uri.path, '^/mylogin')}"
}

```

Source: [98-dispatch.json](#)

- Go to <http://ig.example.com:8080/dispatch> and click **log in**.

The HeaderFilter sets **Username** and **Password** headers in the request, and passes the request to the script. The script responds, **Welcome back, Babs!**

Script HTTP basic access authentication

HTTP basic access authentication is a simple challenge and response mechanism, where a server requests credentials from a client, and the client passes them to the server in an **Authorization** header. The credentials are base-64 encoded. To protect them, use SSL encryption for the connections between the server and client. For more information, refer to [RFC 2617](#).

1. Add the following script to PingGateway to add an **Authorization** header based on a username and password combination:

Linux

```
$HOME/.openig/scripts/groovy/BasicAuthFilter.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\BasicAuthFilter.groovy
```

```
/*
 * Perform basic authentication with the user name and password
 * that are supplied using a configuration like the following:
 *
 * {
 *   "name": "BasicAuth",
 *   "type": "ScriptableFilter",
 *   "config": {
 *     "type": "application/x-groovy",
 *     "file": "BasicAuthFilter.groovy",
 *     "args": {
 *       "username": "bjensen",
 *       "password": "H1falutin"
 *     }
 *   }
 * }
 */

def userPass = username + ":" + password
def base64UserPass = userPass.getBytes().encodeBase64()
request.headers.add("Authorization", "Basic ${base64UserPass}" as String)

// Credentials are only base64-encoded, not encrypted: Set scheme to HTTPS.

/*
 * When connecting over HTTPS, by default the client tries to trust the server.
 * If the server has no certificate
 * or has a self-signed certificate unknown to the client,
 * then the most likely result is an SSLPeerUnverifiedException.
 *
 * To avoid an SSLPeerUnverifiedException,
 * set up HTTPS correctly on the server.
 * Either use a server certificate signed by a well-known CA,
 * or set up the gateway to trust the server certificate.
 */
request.uri.scheme = "https"

// Calls the next Handler and returns a Promise of the Response.
// The Response can be handled with asynchronous Promise callbacks.
next.handle(context, request)
```

Source: [BasicAuthFilter.groovy](#)

2. Add the following route to PingGateway to set up headers required by the script when the user logs in:

Linux

```
$HOME/.openig/config/routes/09-basic.json
```

Windows

```
%appdata%\OpenIG\config\routes\09-basic.json
```

```
{
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "ScriptableFilter",
          "config": {
            "type": "application/x-groovy",
            "file": "BasicAuthFilter.groovy",
            "args": {
              "username": "bjensen",
              "password": "H1falutin"
            }
          },
          "capture": "filtered_request"
        }
      ],
      "handler": {
        "type": "StaticResponseHandler",
        "config": {
          "status": 200,
          "headers": {
            "Content-Type": [ "text/plain; charset=UTF-8" ]
          },
          "entity": "Hello bjensen!"
        }
      }
    }
  },
  "condition": "${find(request.uri.path, '^/basic')}"
}
```

Source: [09-basic.json](#)

When the request path matches `/basic`, the route calls the Chain, which runs the ScriptableFilter. The capture setting captures the request as updated by the ScriptableFilter. Finally, PingGateway returns a static page.

3. Go to <http://ig.example.com:8080/basic>.

The captured request in the console log shows that the scheme is now HTTPS, and that the `Authorization` header is set for HTTP Basic:


```
GET https://app.example.com:8081/basic HTTP/1.1
...
Authorization: Basic Ymp...aW4=
```

Script SQL queries



Important

The example in this section uses `SqlClient`, which exposes a [JdbcDataSource](#). Because the JDBC API provides only blocking APIs, the example code offloads `JdbcDataSource` calls to another thread.

This example builds on [Password replay from a database](#) to use scripts to look up credentials in a database, set the credentials in headers, and set the scheme in HTTPS to protect the request.

1. Set up and test the example in [Password replay from a database](#).
2. Add the following script to PingGateway, to look up user credentials in the database, by email address, and set the credentials in the request headers for the next handler:

Linux

```
$HOME/.openig/scripts/groovy/SqlAccessFilter.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\SqlAccessFilter.groovy
```

```

/*
 * Look up user credentials in a relational database
 * based on the user's email address provided in the request form data,
 * and set the credentials in the request headers for the next handler.
 */
import org.forgerock.openig.http.protocol.ResponseUtils
import org.forgerock.util.promise.Promises

// Return a promise.
Promises
    // Submit the task to another thread (asynchronous execution).
    .executeAsync(service) {
        // Get the credentials with the synchronous JDBC APIs.
        new SqlClient(dataSource).getCredentials(request.queryParams?.mail[0])
    }
    // When the task completes...
    .thenAsync { credentials ->
        // ...with a result, it successfully got the credentials.
        // Add the credentials as headers in the request object.
        request.headers.add('Username', credentials.Username)
        request.headers.add('Password', credentials.Password)

        // The credentials are not protected in the headers, so use HTTPS.
        request.uri.scheme = 'https'

        // Let the chain continue to process the request.
        next.handle(context, request)
    } { exception ->
        // ...with a checked exception
        // because the dataSource has thrown a JDBC exception,
        // fail the promise with an illegal state exception.
        ResponseUtils.newIllegalStateExceptionPromise(exception)
    } { runtimeException ->
        // ...with a runtime exception
        // because the dataSource had an unrecoverable error,
        // fail the promise with an illegal state exception.
        ResponseUtils.newIllegalStateExceptionPromise(runtimeException)
    }
}

```

Source: [SqlAccessFilter.groovy](#)

3. Add the following script to PingGateway to access the database, and get credentials:

Linux

```
$HOME/.openig/scripts/groovy/SqlClient.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\SqlClient.groovy
```

```

import groovy.sql.Sql

import javax.sql.DataSource

/**
 * Access a database with a well-known structure,
 * in particular to get credentials given an email address.
 */
class SqlClient {

    // DataSource supplied as constructor parameter.
    def sql

    SqlClient(DataSource dataSource) {
        if (dataSource == null) {
            throw new IllegalArgumentException("DataSource is null")
        }
        this.sql = new Sql(dataSource)
    }

    // The expected table is laid out like the following.

    // Table USERS
    // -----
    // | USERNAME | PASSWORD | EMAIL | ... |
    // -----
    // | <username> | <passwd> | <mail@...> | ... |
    // -----

    String tableName = "USERS"
    String usernameColumn = "USERNAME"
    String passwordColumn = "PASSWORD"
    String mailColumn = "EMAIL"

    /**
     * Get the Username and Password given an email address.
     *
     * @param mail Email address used to look up the credentials
     * @return Username and Password from the database
     */
    def getCredentials(mail) {
        def credentials = [:]
        def query = "SELECT " + usernameColumn + ", " + passwordColumn +
            " FROM " + tableName + " WHERE " + mailColumn + "='$mail';"

        sql.eachRow(query) {
            credentials.put("Username", it.$usernameColumn)
            credentials.put("Password", it.$passwordColumn)
        }
        return credentials
    }
}

```

Source: [SqlClient.groovy](#)

4. Add the following route to PingGateway to set up headers required by the scripts when the user logs in:

Linux

```
$HOME/.openig/config/routes/11-db.json
```

Windows

```
%appdata%\OpenIG\config\routes\11-db.json
```

```

{
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "JdbcDataSource-1",
      "type": "JdbcDataSource",
      "config": {
        "driverClassName": "org.h2.Driver",
        "jdbcUrl": "jdbc:h2:tcp://localhost/~:/test",
        "username": "sa",
        "passwordSecretId": "database.password",
        "secretsProvider": "SystemAndEnvSecretStore-1"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "ScriptableFilter",
          "config": {
            "args": {
              "dataSource": "${heap['JdbcDataSource-1']}",
              "service": "${heap['ScheduledExecutorService']}"
            },
            "type": "application/x-groovy",
            "file": "SqlAccessFilter.groovy"
          }
        },
        {
          "type": "StaticRequestFilter",
          "config": {
            "method": "POST",
            "uri": "http://app.example.com:8081/login",
            "form": {
              "username": [
                "${request.headers['Username']}[0]}"
              ],
              "password": [
                "${request.headers['Password']}[0]}"
              ]
            }
          }
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  },
  "condition": "${find(request.uri.path, '^/db')}"
}

```

Source: [11-db.json](#)

Notice the following features of the route:

- The route matches requests to `/db`.
- The `JdbcDataSource` in the heap sets up the connection to the database.
- The `ScriptableFilter` calls `SqlAccessFilter.groovy` to look up credentials over SQL.
`SqlAccessFilter.groovy`, in turn, calls `SqlClient.groovy` to access the database to get the credentials.
- The `StaticRequestFilter` uses the credentials to build a login request.

Although the script sets the scheme to HTTPS, for convenience in this example, the `StaticRequestFilter` resets the URI to HTTP.

5. To test the setup, go to a URL with a query string parameter that specifies an email address in the database, such as `http://ig.example.com:8080/db?mail=george@example.com`.

The sample application profile page for the user is displayed.

Extend PingGateway through the Java API

Important

When writing scripts or Java extensions that use the Promise API, avoid the blocking methods `get()`, `getOrThrow()`, and `getOrThrowUninterruptibly()`. A promise represents the result of an asynchronous operation; therefore, using a blocking method to wait for the result can cause deadlocks and/or race issues. Instead, consider using `then()` methods, such as `thenOnResult()`, `thenAsync()`, or `thenCatch()`, which allow execution blocks to be executed when the response is available.

Blocking code example

```
def response = next.handle(ctx, req).get() // Blocking method 'get' used
response.headers['new'] = "new header value"
return response
```

Non-blocking code example

```
return next.handle(ctx, req)
    .thenOnResult { response ->
        response.headers['new'] = "new header value"
    }
```

PingGateway includes a complete Java [application programming interface](#) to allow you to customize PingGateway to perform complex server interactions or intensive data transformations that you cannot achieve with scripts or the existing handlers, filters, and expressions described in [Expressions](#). The following sections describe how to extend PingGateway through the Java API:

Key extension points

Interface Stability: Evolving, as defined in [product stability labels](#).

The following interfaces are available:

[Decorator](#)

A **Decorator** adds new behavior to another object without changing the base type of the object.

When suggesting custom **Decorator** names, know that PingGateway reserves all field names that use only alphanumeric characters. To avoid clashes, use dots or dashes in your field names, such as **my-decorator**.

[ExpressionPlugin](#)

An **ExpressionPlugin** adds a node to the **Expression** context tree, alongside **env** (for environment variables), and **system** (for system properties). For example, the expression `${system['user.home']}` yields the home directory of the user running the application server for PingGateway.

In your **ExpressionPlugin**, the **getKey()** method returns the name of the node, and the **getObject()** method returns the unified expression language context object that contains the values needed to resolve the expression. The plugins for **env** and **system** return Map objects, for example.

When you add your own **ExpressionPlugin**, you must make it discoverable within your custom library. You do this by adding a services file named after the plugin interface, where the file contains the fully qualified class name of your plugin, under **META-INF/services/org.forgerock.openig.el.ExpressionPlugin** in the .jar file for your customizations. When you have more than one plugin, add one fully qualified class name per line. For information, refer to the reference documentation for the Java class [ServiceLoader](#). If you build your project using Maven, then you can add this under the **src/main/resources** directory. Add custom libraries, as described in [Embed customizations in PingGateway](#).

Remember to provide documentation for PingGateway administrators on how your plugin extends expressions.

[Filter](#)

A **Filter** serves to process a request before handing it off to the next element in the chain, in a similar way to an interceptor programming model.

The **Filter** interface exposes a **filter()** method, which takes a **ROOT:attachment\$apidocs/org/forgerock/services/context/Context.html[Context]**, a [Request](#), and the [Handler](#), which is the next filter or handler to dispatch to. The **filter()** method returns a [Promise](#) that provides access to the [Response](#) with methods for dealing with both success and failure conditions.

A filter can elect not to pass the request to the next filter or handler, and instead handle the request itself. It can achieve this by merely avoiding a call to **next.handle(context, request)**, creating its own response object and returning that in the promise. The filter is also at liberty to replace a response with another of its own. A filter can exist in more than one chain, therefore should make no assumptions or correlations using the chain it is supplied. The only valid use of a chain by a filter is to call its **handle()** method to dispatch the request to the rest of the chain.

[Handler](#)

A **Handler** generates a response for a request.

The `Handler` interface exposes a `handle()` method, which takes a `ROOT:attachment$apidocs/org/forgerock/services/context/Context.html`, and a [Request](#). It processes the request and returns a [Promise](#) that provides access to the [Response](#) with methods for dealing with both success and failure conditions. A handler can elect to dispatch the request to another handler or chain.

[ClassAliasResolver](#)

A `ClassAliasResolver` makes it possible to replace a fully qualified class name with a short name (an alias) in an object declaration's type.

The `ClassAliasResolver` interface exposes a `resolve(String)` method to do the following:

- Return the class mapped to a given alias
- Return `null` if the given alias is unknown to the resolver

All resolvers available to PingGateway are asked until the first non-null value is returned or until all resolvers have been contacted.

The order of resolvers is nondeterministic. To prevent conflicts, don't use the same alias for different types.

Implement a customized sample filter

The `SampleFilter` class implements the `Filter` interface to set a header in the incoming request and in the outgoing response.

In the following example, the sample filter adds an arbitrary header:


```

package org.forgerock.openig.doc.examples;

import org.forgerock.http.Filter;
import org.forgerock.http.Handler;
import org.forgerock.http.protocol.Request;
import org.forgerock.http.protocol.Response;
import org.forgerock.openig.heap.GenericHeaplet;
import org.forgerock.openig.heap.HeapException;
import org.forgerock.openig.model.type.service.NoTypeInfo;
import org.forgerock.services.context.Context;
import org.forgerock.util.promise.NeverThrowsException;
import org.forgerock.util.promise.Promise;

/**
 * Filter to set a header in the incoming request and in the outgoing response.
 */
public class SampleFilter implements Filter {

    /** Header name. */
    String name;

    /** Header value. */
    String value;

    /**
     * Set a header in the incoming request and in the outgoing response.
     * A configuration example looks something like the following.
     *
     * <pre>
     * {
     *   "name": "SampleFilter",
     *   "type": "SampleFilter",
     *   "config": {
     *     "name": "X-Greeting",
     *     "value": "Hello world"
     *   }
     * }
     * </pre>
     *
     * @param context      Execution context.
     * @param request      HTTP Request.
     * @param next         Next filter or handler in the chain.
     * @return A {@code Promise} representing the response to be returned to the client.
     */
    @Override
    public Promise<Response, NeverThrowsException> filter(final Context context,
                                                         final Request request,
                                                         final Handler next) {

        // Set header in the request.
        request.getHeaders().put(name, value);

        // Pass to the next filter or handler in the chain.
        return next.handle(context, request)
            .thenOnResult(response -> {
                // Set header in the response.
                response.getHeaders().put(name, value);
            });
    }
}

```

```

/**
 * Create and initialize the filter, based on the configuration.
 * The filter object is stored in the heap.
 */
@NoTypeInfo(reason = "documentation sample")
public static class Heaplet extends GenericHeaplet {

    /**
     * Create the filter object in the heap,
     * setting the header name and value for the filter,
     * based on the configuration.
     *
     * @return The filter object.
     * @throws HeapException Failed to create the object.
     */
    @Override
    public Object create() throws HeapException {

        SampleFilter filter = new SampleFilter();
        filter.name = config.get("name").as(evaluatedWithHeapProperties()).required().asString();
        filter.value = config.get("value").as(evaluatedWithHeapProperties()).required().asString();

        return filter;
    }
}

```

Source: [SampleFilter.java](#) 

The corresponding filter configuration is similar to this:

```

{
  "name": "SampleFilter",
  "type": "org.forgerock.openig.doc.examples.SampleFilter",
  "config": {
    "name": "X-Greeting",
    "value": "Hello world"
  }
}

```

Note how `type` is configured with the fully qualified class name for `SampleFilter`. To simplify the configuration, implement a class alias resolver, as described in [Implement a Class Alias Resolver](#).

Implement a class alias resolver

To simplify the configuration of a customized object, implement a `ClassAliasResolver` to allow the use of short names instead of fully qualified class names.

In the following example, a `ClassAliasResolver` is created for the `SampleFilter` class:

```

package org.forgerock.openig.doc.examples;

import static java.util.stream.Collectors.toUnmodifiableSet;

import java.util.HashMap;
import java.util.Map;
import java.util.Optional;
import java.util.Set;

import org.forgerock.openig.alias.ClassAliasResolver;
import org.forgerock.openig.heap.Heaplet;
import org.forgerock.openig.heap.Heaplets;

/**
 * Allow use of short name aliases in configuration object types.
 *
 * This allows a configuration with {@code "type": "SampleFilter"}
 * instead of {@code "type": "org.forgerock.openig.doc.examples.SampleFilter"}.
 */
public class SampleClassAliasResolver implements ClassAliasResolver {

    private static final Map<String, Class<?>> ALIASES =
        new HashMap<>();

    static {
        ALIASES.put("SampleFilter", SampleFilter.class);
    }

    /**
     * Get the class for a short name alias.
     *
     * @param alias Short name alias.
     * @return The class, or null if the alias is not defined.
     */
    @Override
    public Class<?> resolve(final String alias) {
        return ALIASES.get(alias);
    }

    @Override
    public Set<Class<? extends Heaplet>> supportedTypes() {
        return ALIASES.values()
            .stream()
            .map(Heaplets::findHeapletClass)
            .filter(Optional::isPresent)
            .map(Optional::get)
            .collect(toUnmodifiableSet());
    }
}

```

Source: [SampleClassAliasResolver.java](#) 

With this `ClassAliasResolver`, the filter configuration in [Implement a Customized Sample Filter](#) can use the alias instead of the fully qualified class name, as follows:

```
{
  "name": "SampleFilter",
  "type": "SampleFilter",
  "config": {
    "name": "X-Greeting",
    "value": "Hello world"
  }
}
```

To create a customized `ClassAliasResolver`, add a services file with the following characteristics:

- Name the file after the class resolver interface.
- Store the file under `META-INF/services/org.forgerock.openig.alias.ClassAliasResolver`, in the customization .jar file.
- If you build your project using Maven, you can add the file under the `src/main/resources` directory.
- In your `ClassAliasResolver` file, add a line for the fully qualified class name of your resolver as follows:

```
org.forgerock.openig.doc.examples.SampleClassAliasResolver
```

If you have more than one resolver in your .jar file, add one line for each fully qualified class name.

Configure the heap object for the customization

Objects are added to the heap and supplied with configuration artifacts at initialization time. To be integrated with the configuration, a class must have an accompanying implementation of the [Heaplet](#) interface. The easiest and most common way of exposing the heaplet is to extend the [GenericHeaplet](#) class in a nested class of the class you want to create and initialize, overriding the heaplet's `create()` method.

Within the `create()` method, you can access the object's configuration through the `config` field.

Embed customizations in PingGateway

1. Build your PingGateway extension into a .jar file.
2. Create the directory `$HOME/.openig/extra`, where `$HOME/.openig` is the instance directory:

```
$ mkdir $HOME/.openig/extra
```

3. Add the .jar file to the directory.

The following example adds `sample-filter.jar` to `$HOME/.openig/extra`:

```
$ cp ~/sample-filter/target/sample-filter.jar $HOME/.openig/extra
```

4. If the extension has dependencies that aren't included in PingGateway, add them to the directory.

5. Start PingGateway, as described in [Starting and stopping PingGateway](#).

Record custom audit events

This section describes how to record a custom audit event to standard output. The example is based on the example in [Validating PingAM access tokens with introspection](#), adding an audit event for the custom topic `OAuth2AccessTopic`.

To record custom audit events to other outputs, adapt the route in the following procedure to use another audit event handler.

For information about how to configure supported audit event handlers, and exclude sensitive data from log files, refer to [Auditing the PingGateway deployment](#). For more information about audit event handlers, refer to [PingGateway audit framework](#).

Record custom audit events to standard output

Before you start, prepare PingGateway and the sample application as described in the [Getting started with PingGateway](#).

1. Set up AM as described in [Validating PingAM access tokens with introspection](#).
2. Define the schema of an event topic called `OAuth2AccessTopic` by adding the following route to PingGateway:

Linux

```
$HOME/.openig/audit-schemas/OAuth2AccessTopic.json
```

Windows

```
%appdata%\OpenIG\audit-schemas/OAuth2AccessTopic.json
```

```

{
  "schema": {
    "$schema": "http://json-schema.org/draft-04/schema#",
    "id": "OAuth2Access",
    "type": "object",
    "properties": {
      "_id": {
        "type": "string"
      },
      "timestamp": {
        "type": "string"
      },
      "transactionId": {
        "type": "string"
      },
      "eventName": {
        "type": "string"
      },
      "accessToken": {
        "type": "object",
        "properties": {
          "scopes": {
            "type": "array",
            "items": {
              "type": "string"
            }
          },
          "expiresAt": "number",
          "sub": "string"
        },
        "required": [ "scopes" ]
      },
      "resource": {
        "type": "object",
        "properties": {
          "path": {
            "type": "string"
          },
          "method": {
            "type": "string"
          }
        }
      }
    }
  },
  "filterPolicies": {
    "field": {
      "includeIf": [
        "/_id",
        "/timestamp",
        "/eventName",
        "/transactionId",
        "/accessToken",
        "/resource"
      ]
    }
  },
  "required": [ "_id", "timestamp", "transactionId", "eventName" ]
}

```

Source: [OAuth2AccessTopic.json](#) 

Notice that the schema includes the following fields:

- Mandatory fields `_id`, `timestamp`, `transactionId`, and `eventName`.
- `accessToken`, to include the access token scopes, expiry time, and the subject.
- `resource`, to include the path and method.
- `filterPolicies`, to specify additional event fields to include in the logs.

3. Define a script to generate audit events on the topic named `OAuth2AccessTopic`.

Add the following file to the PingGateway configuration as:

Linux

```
$HOME/.openig/scripts/groovy/OAuth2Access.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\OAuth2Access.groovy
```

```

import static org.forgerock.json.resource.Requests.newCreateRequest;
import static org.forgerock.json.resource.ResourcePath.resourcePath;

// Helper functions
def String transactionId() {
    return contexts.transactionId.transactionId.value;
}

def JsonValue auditEvent(String eventName) {
    return json(object(field('eventName', eventName),
        field('transactionId', transactionId()),
        field('timestamp', clock.instant().toEpochMilli())));
}

def auditEventRequest(String topicName, JsonValue auditEvent) {
    return newCreateRequest(resourcePath("/") + topicName, auditEvent);
}

def accessTokenInfo() {
    def accessTokenInfo = contexts.oauth2.accessToken;
    return object(field('scopes', accessTokenInfo.scopes as List),
        field('expiresAt', accessTokenInfo.expiresAt),
        field('subname', accessTokenInfo.info.subname));
}

def resourceEvent() {
    return object(field('path', request.uri.path),
        field('method', request.method));
}

// -----

// Build the event
JsonValue auditEvent = auditEvent('OAuth2AccessEvent')
    .add('accessToken', accessTokenInfo())
    .add('resource', resourceEvent());

// Send the event, and log a message if there is an error
auditService.handleCreate(context, auditEventRequest("OAuth2AccessTopic", auditEvent))
    .thenOnException(e -> logger.warn("An error occurred while sending the audit event", e));

// Continue onto the next filter
return next.handle(context, request)

```

Source: [OAuth2Access.groovy](#)

The script generates audit events named `OAuth2AccessEvent` on a topic named `OAuth2AccessTopic`. The events conform to the topic schema.

4. Set an environment variable for the PingGateway agent password and restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFZc3dvcnQ='
```

The password is retrieved by a `SystemAndEnvSecretStore` and must be base64-encoded.

5. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/30-custom.json
```

Windows

```
%appdata%\OpenIG\config\routes\30-custom.json
```

```

{
  "name": "30-custom",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/rs-introspect-audit')}",
  "heap": [
    {
      "name": "AuditService-1",
      "type": "AuditService",
      "config": {
        "config": {},
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.json.stdout.JsonStdoutAuditEventHandler",
            "config": {
              "name": "jsonstdout",
              "elasticsearchCompatible": false,
              "topics": [
                "OAuth2AccessTopic"
              ]
            }
          }
        ]
      }
    },
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [
              "mail",
              "employeenumber"
            ]
          },
          "requireHttps": false,
          "accessTokenResolver": {
            "name": "token-resolver-1",
            "type": "TokenIntrospectionAccessTokenResolver",
            "config": {
              "amService": "AmService-1",
              "providerHandler": {

```

```

        "type": "Chain",
        "config": {
          "filters": [
            {
              "type": "HttpBasicAuthenticationClientFilter",
              "config": {
                "username": "ig_agent",
                "passwordSecretId": "agent.secret.id",
                "secretsProvider": "SystemAndEnvSecretStore-1"
              }
            }
          ],
          "handler": "ForgeRockClientHandler"
        }
      },
      {
        "type": "ScriptableFilter",
        "config": {
          "type": "application/x-groovy",
          "file": "0Auth2Access.groovy",
          "args": {
            "auditService": "${heap['AuditService-1']}",
            "clock": "${heap['Clock']}"
          }
        }
      }
    ],
    "handler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 200,
        "headers": {
          "Content-Type": [ "text/html; charset=UTF-8" ]
        },
        "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></html>"
      }
    }
  }
}

```

Source: [30-custom.json](#)

Notice the following features of the route:

- The route matches requests to `/rs-introspect-audit`.
- The `accessTokenResolver` uses the token introspection endpoint to validate the access token.
- The `HttpBasicAuthenticationClientFilter` adds the credentials to the outgoing token introspection request.
- The `ScriptableFilter` uses the Groovy script `0Auth2Access.groovy` to generate audit events named `0Auth2AccessEvent` with a topic named `0Auth2AccessTopic`.

- The audit service publishes the custom audit event to the `JsonStdoutAuditEventHandler`. A single line per audit event is published to standard output.

6. Test the setup

1. In a terminal window, use a `curl` command similar to the following to retrieve an access token:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail%20employeenumber" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

2. Access the route, with the `access_token` returned in the previous step:

```
$ curl -v http://ig.example.com:8080/rs-introspect-audit --header "Authorization: Bearer ${mytoken}"
```

Information about the decoded `access_token` is returned.

3. Search the standard output for an audit message like the following example, that includes an audit event on the topic `OAuth2AccessTopic`:

```
{
  "_id": "fa2...-14",
  "timestamp": 155...541,
  "eventName": "OAuth2AccessEvent",
  "transactionId": "fa2...-13",
  "accessToken": {
    "scopes": ["employeenumber", "mail"],
    "expiresAt": 155...000,
    "subname": "demo"
  },
  "resource": {
    "path": "/rs-introspect-audit",
    "method": "GET"
  },
  "source": "audit",
  "topic": "OAuth2AccessTopic",
  "level": "INFO"
}
```

PingGateway upgrades

This guide shows you how to upgrade PingGateway software.

Read the [Release notes](#) before you upgrade.

Product names changed when ForgeRock became part of Ping Identity. PingGateway was formerly known as ForgeRock Identity Gateway, for example. Learn more about the name changes from [New names for ForgeRock products](#).

Planning the PingGateway upgrade

Do these planning tasks **before** you start an upgrade:

Planning task	Description
Find the upgrade path	Refer to Upgrading PingGateway to see if you need a drop-in upgrade or a major upgrade.
Find out what changed	Read the release notes for all releases between the current version and the new version. Understand the new features and changes in the new version compared to the current version.
Check the requirements	Make sure you meet all the requirements in the release notes for the new version. In particular, make sure you have a recent, supported Java version .
Plan for server downtime	At least one of your PingGateway servers will be down during upgrade. Plan to route client applications to another server until the upgrade process is complete and you have validated the result. Make sure the owners of client application are aware of the change, and let them know what to expect. If you have a single PingGateway server, make sure the downtime happens in a low-usage window, and make sure you let client application owners plan accordingly.
Back up	The PingGateway configuration is a set of files, including <code>admin.json</code> , <code>config.json</code> , <code>logback.xml</code> , routes, and scripts. Back up the PingGateway configuration and store it in version control, so that you can roll back if something goes wrong. Back up any tools scripts you have edited for your deployment and any trust stores used to connect securely.
Plan for rollback	Sometimes even a well-planned upgrade fails to go smoothly. In such cases, you need a plan to roll back smoothly to the pre-upgrade version. For PingGateway servers, roll back by restoring a backed-up configuration.
Prepare a test environment	Before applying the upgrade in your production environment, always try to upgrade PingGateway in a test environment. This will help you gauge the amount of work required, without affecting your production environment, and will help smooth out unforeseen problems. The test environment should resemble your production environment as closely as possible.

Upgrading PingGateway

Learn about upgrade between supported versions of PingGateway in [Product Support Lifecycle Policy | PingGateway and Agents](#) [🔗](#).

Learn about upgrade of routes in Studio in [Upgrade from an earlier version of Studio](#).

This section describes how to upgrade a single PingGateway instance. The most straightforward option when upgrading sites with multiple PingGateway instances is to upgrade in place. One by one, stop, upgrade, and then restart each server individually, leaving the service running during the upgrade.

PingGateway supports the following types of upgrade:

Drop-in software update

Usually, an update from a version of PingGateway to a newer minor version, as defined in [Product Support Lifecycle Policy | PingGateway and Agents](#) [🔗](#). For example, the update from 2023.2 to 2023.4.

Drop-in software updates can introduce additional functionality and fix bugs or security issues. Consider the following restrictions for drop-in software updates:

- Don't require any update to the configuration
- Cannot cause feature regression
- Can change default or previously configured behavior **only** for bug fixes and security issues
- Can deprecate **but not remove** existing functionality

Major upgrade

Usually, an upgrade from a version of PingGateway to a newer major version, as defined in [Product Support Lifecycle Policy | PingGateway and Agents](#) [🔗](#). For example, the upgrade from 7.2 to 2023.2.

Major upgrades can introduce additional functionality and fix bugs or security issues. Major upgrades don't have the restrictions of drop-in software update. Consider the following features of major upgrades:

- Can require code or configuration changes
- Can cause feature regression
- Can change default or previously configured behavior
- Can deprecate **and** remove existing functionality

Drop-in software update with binaries

1. Read and act on [Planning the PingGateway upgrade](#).
2. Back up the PingGateway configuration and store it in version control so that you can roll back if something goes wrong.
3. [Downloading PingGateway](#)
4. [Stop PingGateway](#).

5. Make the new configuration available on the file system.

By default, PingGateway configuration files are located under `$HOME/.openig` (on Windows `%appdata%\OpenIG`). For information about how to use a different location, refer to [Configuration location](#).

6. [Restart PingGateway](#) from the new installation directory.
7. In a test environment that simulates your production environment, validate that the upgraded service performs as expected with the new configuration. Check the logs for new or unexpected notifications or errors.
8. Allow client application traffic to flow to the upgraded site.

Drop-in software update with Docker files

1. Read and act on [Planning the PingGateway upgrade](#).
2. Back up the PingGateway configuration and store it in version control so that you can roll back if something goes wrong.
3. [Stop the Docker image](#).
4. [Build the new base image for PingGateway](#).
5. [Run the Docker image](#).
6. In a test environment that simulates your production environment, validate that the upgraded service performs as expected with the new configuration. Check the logs for new or unexpected notifications or errors.
7. Allow client application traffic to flow to the upgraded site.

Major upgrade with binaries

1. Read and act on [Planning the PingGateway upgrade](#).
2. Use the [release notes](#)  for **all** releases between the version you currently use and the new version, and create a new configuration as follows:
 - Review all incompatible changes and removed functionality, and adjust your configuration as necessary.
 - Switch to the replacement settings for deprecated functionality. Although [deprecated](#)  objects continue to work, they add to the notifications in the logs and are eventually removed.
 - Check the lists of fixes, limitations, and known issues to find out if they impact your deployment.
 - Recompile your Java extensions. The method signature or imports for supported and evolving APIs can change in each version.
 - Read the documentation updates for new examples and information that can help with your configuration.
3. Back up the PingGateway configuration and store it in version control so that you can roll back if something goes wrong.
4. [Downloading PingGateway](#)
5. [Stop PingGateway](#).
6. Make the new configuration available on the file system.

By default, PingGateway configuration files are located under `$HOME/.openig` (on Windows `%appdata%\OpenIG`). For information about how to use a different location, refer to [Configuration location](#).

7. [Restart PingGateway](#) from the new installation directory.
8. In a test environment that simulates your production environment, validate that the upgraded service performs as expected with the new configuration. Check the logs for new or unexpected notifications or errors.
9. Allow client application traffic to flow to the upgraded site.

Major upgrade with Docker files

1. Read and act on [Planning the PingGateway upgrade](#).
2. Use the [release notes](#) for **all** releases between the version you currently use and the new version, and create a new configuration as follows:
 - Review all incompatible changes and removed functionality, and adjust your configuration as necessary.
 - Switch to the replacement settings for deprecated functionality. Although [deprecated](#) objects continue to work, they add to the notifications in the logs and are eventually removed.
 - Check the lists of fixes, limitations, and known issues to find out if they impact your deployment.
 - Recompile your Java extensions. The method signature or imports for supported and evolving APIs can change in each version.
 - Read the documentation updates for new examples and information that can help with your configuration.
3. Back up the PingGateway configuration and store it in version control so that you can roll back if something goes wrong.
4. [Stop the Docker image](#).
5. [Build the new base image for PingGateway](#).
6. [Run the Docker image](#).
7. In a test environment that simulates your production environment, validate that the upgraded service performs as expected with the new configuration. Check the logs for new or unexpected notifications or errors.
8. Allow client application traffic to flow to the upgraded site.

Post upgrade tasks

After upgrade, review the [what's new](#) section in the release notes and consider activating new features and functionality.

Rollback



Important

Before you roll back to a previous version of PingGateway, consider whether any change to the configuration during or since upgrade could be incompatible with the previous version.

Roll back with binaries

1. Plan for server downtime

Plan to route client applications to another server until the rollback process is complete and you have validated the result. Make sure the owners of client application are aware of the change, and let them know what to expect.

2. [Stop PingGateway](#)

3. [Download the replacement PingGateway .zip file](#)

4. Make the new configuration available on the file system.

By default, PingGateway configuration files are located under `$HOME/.openig` (on Windows `%appdata%\OpenIG`). For information about how to use a different location, refer to [Configuration location](#).

5. [Restart PingGateway](#).

Roll back with Dockerfiles

1. Plan for server downtime

Plan to route client applications to another server until the rollback process is complete and you have validated the result. Make sure the owners of client application are aware of the change, and let them know what to expect.

2. [Stop the Docker image](#).

3. [Build the new base image for PingGateway](#).

4. [Run the Docker image](#).

Migrating from web container mode to PingGateway standalone mode

An PingGateway .war file isn't created or delivered from PingGateway 2024.3. Consider these points when migrating from a .war delivery to a .zip delivery.

Session replication between PingGateway instances

High-availability of sessions isn't supported by PingGateway in the .zip delivery.

Streaming asynchronous responses and events

In [ClientHandler](#) and [ReverseProxyHandler](#), use only the default mode of `asyncBehavior:non_streaming`; responses are processed when the entity content is entirely available.

If the property is set to `streaming`, the setting is ignored.

Connection reuse when client certificates are used for authentication

In [ClientHandler](#) and [ReverseProxyHandler](#), use only the default mode of `stateTrackingEnabled:true`; when a client certificate is used for authentication, connections can't be reused.

If the property is set to `false`, the setting is ignored.

Replacement settings for migration from web container mode with Tomcat

Feature	Setting for web container mode with Tomcat	Replacement setting
Port number	Configure in the <code>Connector</code> element of <code>/path/to/tomcat/conf/server.xml</code> : <pre><Connector port="8080" protocol="HTTP/1.1" connectionTimeout="20000" redirectPort="8443" /></pre>	Configure the <code>connectors</code> property of <code>admin.json</code> .
HTTPS server-side configuration	Create a keystore, and set up the SSL port in the <code>Connector</code> element of <code>/path/to/tomcat/conf/server.xml</code> .	Create a keystore, set up secrets, and configure secrets stores, ports, and <code>ServerTlsOptions</code> in <code>admin.json</code> . For information, refer to Configure PingGateway for TLS (server-side) .
Session cookie name	Configure <code>WEB-INF/web.xml</code> when you unpack the PingGateway .war file.	Configure the <code>session</code> property of <code>admin.json</code> .
Access logs	Configure with <code>AccessLogValve</code> .	Configure in the Audit framework. For information, refer to Auditing the PingGateway deployment and PingGateway audit framework .
JDBC datasource	Configure in the <code>GlobalNamingResources</code> element of <code>/path/to/tomcat/conf/server.xml</code> .	Configure with the <code>JdbcDataSource</code> object. For information, refer to JdbcDataSource . For an example, refer to Password replay from a database .
Environment variables	Configure in <code>/path/to/tomcat/bin/setenv.sh</code> .	Configure in <code>\$HOME/.openig/bin/env.sh</code> , where <code>\$HOME/.openig</code> is the instance directory.
Jar files	Add to web container classpath; for example <code>/path/to/tomcat/webapps/ROOT/WEB-INF/lib</code> .	Add to <code>\$HOME/.openig/extra</code> , where <code>\$HOME/.openig</code> is the instance directory.

Deploying PingGateway with Docker

These pages show you how to build an evaluation-only Docker image from the Dockerfile provided inside `PingGateway-2025.6.1.zip`.

Warning

Ping Identity provides no commercial support for production deployments that use the evaluation-only Docker images. When deploying, you must build and use your own Docker images for production deployments.

These pages are for Ping Identity Platform developers who want an easy-to-use example of containerized deployment, and for PingGateway developers who want to configure a production environment for containerized deployment.

Learn about deploying Ping Identity Platform by using DevOps techniques in the ForgeOps [Start here](#) documentation.

These pages assume you are familiar with the following topics:

- PingGateway, to edit the basic configuration and test the changes.
- Docker, to build and run and Docker images.

The examples in this guide use some of the following third-party tools:

- `curl`: <https://curl.haxx.se>
- `HTTPie`: <https://httpie.org>
- `jq`: <https://stedolan.github.io/jq/>
- `keytool`: <https://docs.oracle.com/en/java/javase/21/docs/specs/man/keytool.html>

Building and running a PingGateway Docker image

A Dockerfile is delivered inside `PingGateway-2025.6.1.zip` to help you build an evaluation-only, base Docker image for PingGateway. After building and running the Docker image, add a configuration as described in [Adding PingGateway configuration to a Docker image](#).

Warning

Ping Identity provides no commercial support for production deployments that use the evaluation-only Docker images. When deploying, you must build and use your own Docker images for production deployments.

The Docker image has the following characteristics:

- The Docker image runs on Linux and Mac operating systems.
- PingGateway binaries are delivered in `/opt/ig`.
- The environment variable `$IG_INSTANCE_DIR` has the value `/var/ig`.
- A user with username: `forgerock` and uid: `11111` runs the PingGateway process and owns the configuration files.

Build the base image for PingGateway

1. Download PingGateway-2025.6.1.zip from the [Backstage download site](#), and unzip. The directory `/path/to/identity-gateway-2025.6.1` is created.
2. Go to `/path/to/identity-gateway-2025.6.1`.
3. With a Docker daemon running, build a base Docker image:

```
$ docker build . -f docker/Dockerfile -t ig-image
```

Output

```
Sending build context to Docker daemon
Step 1/7 : FROM gcr.io/forgerock-io/...:latest
latest: Pulling from forgerock-io/...
...
Successfully tagged ig-image:latest
```

4. Make sure the Docker image is available:

```
$ docker image list
```

Output

REPOSITORY	TAG	IMAGE ID
ig-image	latest	
gcr.io/forgerock-io/...	latest	

Run the Docker image

The following steps run the Docker image on port `8080`. Make sure the port is not being used, or use a different port as described in the procedure.

1. With a Docker daemon running, run the Docker image:

```
$ docker run -p 8080:8080 ig-image
```

PingGateway starts up, and the console displays the message log.

2. Go to <http://localhost:8080> to view the PingGateway welcome page.

Stop the Docker image

1. List the Docker containers that are running:

```
$ docker container ls
```

2. For a container with the status `Up`, use the container ID to stop the container:

```
$ docker container stop CONTAINER_ID
```

Run options

Consider using the following options when you run the Docker image:

-e IG_OPTS=-Dig.pid.file.mode=value ig-image

Allow startup if there is an existing PID file. PingGateway removes the existing PID file and creates a new one during startup. The following example passes an environment variable with the value `override` as a Java runtime option:

```
$ docker run -e "IG_OPTS=-Dig.pid.file.mode=override" ig-image
```

To prevent restart if there is an existing PID file, set the value to the default `fail`.

-p port:port

The default ports `8080:8080` equate to `local-machine-port:internal-container-port`. PingGateway can run on a different port, but the container must always run on `8080`. The following example runs PingGateway on port `8090`:

```
$ docker run -p 8090:8080 ig-image
```

-v configuration directory

The default configuration directory is `/var/ig/`. The following example sets the configuration directory to `$HOME/.openig`:

```
$ docker run -v $HOME/.openig:/var/ig/ ig-image
```

-user user

Run the image as the provided user. The following example uses the ID `11111`:

```
$ docker run --user 11111 ig-image
```

it

Run the image in interactive mode:

```
$ docker run -it ig-image
```

sh

Run the image in sh shell:

```
$ docker run ig-image sh
```

Adding PingGateway configuration to a Docker image

The following sections describe how to add configuration to your Docker image. Before working through this section, complete the procedures in [Building and running a PingGateway Docker image](#).

Run an image with a mutable configuration

This section describes how to add a basic route to your local PingGateway configuration folder, and mount the configuration to the Docker container.

If you change your configuration in a way that doesn't require PingGateway to restart, you see the change in your running Docker image without restarting it or rebuilding it. For information changes that require restart, refer to [When to restart PingGateway after changing the configuration](#).

Use this procedure to manage configuration externally to the Docker image. For example, use it when developing routes.

1. Add the following route to your local PingGateway configuration as `$HOME/.openig/config/routes/hello.json`:

```
{
  "name": "hello",
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/plain; charset=UTF-8" ]
      },
      "entity": "Hello world!"
    }
  },
  "condition": "${find(request.uri.path, '^/hello')}"
}
```

Source: [hello.json](#) 

The configuration contains a static response handler to return a "Hello world!" statement when the URI of a request finishes with `/hello`.

2. Run the Docker image, using the option to mount the local PingGateway configuration directory:

```
$ docker run -p 8080:8080 -v $HOME/.openig:/var/ig/ ig-image
```

3. Go to <http://localhost:8080/hello> to access the route in the mounted configuration.

The "Hello world!" statement is displayed.

4. Edit `hello.json` to change the "Hello world!" statement, and save the file.

Go again to <http://localhost:8080/hello> to see that the message changed without changing your Docker image.

Run an image with an immutable configuration

This section describes how to add a basic route to your local PingGateway configuration folder, copy it into a new Docker image, and run that Docker image.

Unlike the previous example, the Docker image is immutable. If you change your configuration locally, the Docker image is not changed.

Use this procedure to manage configuration within the Docker image. For example, use it when you want to deploy the same configuration multiple times.

1. Add the following route to your local PingGateway configuration as `$HOME/.openig/config/routes/hello.json`:

```
{
  "name": "hello",
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/plain; charset=UTF-8" ]
      },
      "entity": "Hello world!"
    }
  },
  "condition": "${find(request.uri.path, '^/hello')}"
}
```

Source: [Source: hello.json](#)

The configuration contains a static response handler to return a "Hello world!" statement when the URI of a request finishes with `/hello`.

2. Add the following file to your local PingGateway configuration as `$HOME/.openig/Dockerfile`, where `$HOME/.openig` is the instance directory:

```
FROM ig-image
COPY config/routes/hello.json "$IG_INSTANCE_DIR"/config/routes/hello.json
```

The Dockerfile copies `hello.json` into the Docker image. The `$IG_INSTANCE_DIR` environment variable is defined in the PingGateway base image.

3. Build the Docker image:

```
$ docker build . -t ig-custom
```

Output

```
Sending build context to Docker daemon
Step 1/2 : FROM ig-image
Step 2/2 : COPY config/routes/hello.json "$IG_INSTANCE_DIR"/config/routes/hello.json
Successfully tagged ig-custom:latest
```

4. Make sure the Docker image is available:

```
$ docker image list
```

Output

REPOSITORY	TAG	IMAGE ID
ig-custom	image_tag	51b...3b7
gcr.io/forgerock-io/ig	image_tag	404...a2b

5. Run the Docker image on port `8080`:

```
$ docker run -p 8080:8080 ig-custom
```

6. Go to <http://localhost:8080/hello>. The "Hello world!" statement is displayed.

PingGateway gateway guide

This guide shows you how to set up examples that use PingGateway. It is for access management designers and administrators who develop, build, deploy, and maintain PingGateway for their organizations.

This guide assumes familiarity with the following topics:

- Hypertext Transfer Protocol (HTTP), including how clients and servers exchange messages, and the role that a reverse proxy (gateway) plays
- JavaScript Object Notation (JSON), which is the format for PingGateway configuration files
- Managing services on operating systems and application servers
- Configuring network connections on operating systems
- Managing Public Key Infrastructure (PKI) used to establish HTTPS connections
- Access management for web applications

Depending on the features you use, you should also have basic familiarity with the following topics:

- Structured Query Language (SQL) if you use PingGateway with relational databases
- Configuring AM if you use password capture and replay, or if you plan to follow the OAuth 2.0 or SAML 2.0 tutorials
- The Groovy programming language if you plan to extend PingGateway with scripts
- The Java programming language if you plan to extend PingGateway with plugins, and Apache Maven for building plugins

Example installation for this guide

Unless otherwise stated, the examples in this guide assume the following installation:

- PingGateway accessible on `http://ig.example.com:8080` and `https://ig.example.com:8443`, as described in [Getting started with PingGateway](#).
- Sample application installed on `http://app.example.com:8081`, as described in [Using the sample application](#).
- AM installed on `http://am.example.com:8088/openam`, with the default configuration.

If you use a different configuration, substitute in the procedures accordingly.

Set up AM

This section helps you prepare to use PingGateway with AM.

About authentication to AM

Unless you upgrade from an earlier version using the file-based configuration, AM 8 and later provide an [authentication tree](#)  called **Agent**. The **Agent** tree validates the agent credentials with an [Agent Data Store Decision](#)  node. All PingGateway, Java agent, and Web agent profiles use the **Agent** tree. Don't change its configuration.

For AM 7.3, 7.4, and 7.5, when AM is [installed with a default configuration](#), PingGateway authenticates to AM with a tree. Otherwise, PingGateway authenticates to AM with an AM authentication module. AM 7 deprecated authentication chains and modules and AM 8 removed support for them.

Register PingGateway with AM

Follow these steps to register an PingAM agent that acts on behalf of PingGateway.

1. In the AM admin UI, select the top-level realm, and then select **Applications > Agents > Identity Gateway**.
2. Add an agent with the following configuration, leaving other options blank or with the default value:

For SSO

- **Agent ID** : `ig_agent`
- **Password** : `password`

For CDSSO

- **Agent ID** : `ig_agent`
- **Password** : `password`
- **Redirect URL for CDSSO** : <https://ig.ext.com:8443/home/cdssso/redirect>
- **Login URL Template for CDSSO**: Configure this property to direct login to a custom URL instead of the default AM login page.

3. (Optional - From AM 7.5) Use AM's secret service to manage the agent profile password.

If AM finds a matching secret in a secret store, it uses that secret instead of a password in the agent profile.

1. In the agent profile page, set a label for the agent password in **Secret Label Identifier**.

AM uses the identifier to generate a secret label for the agent.

The secret label has the format `am.application.agents.identifier.secret`, where identifier is the **Secret Label Identifier**.

The **Secret Label Identifier** can contain only characters `a-z`, `A-Z`, `0-9`, and periods (`.`). It can't start or end with a period.

2. Select  **Secret Stores** and configure a secret store.
3. Map the label to the secret. Learn more from AM's [mapping](#).

Note the following points for using AM's secret service:

- Set a **Secret Label Identifier** that clearly identifies the agent.
- If you update or delete the **Secret Label Identifier**, AM updates or deletes the corresponding mapping for the previous identifier provided no other agent shares the mapping.
- When you rotate a secret, update the corresponding mapping.

Set up a demo user in AM

AM is provided with a demo user in the top-level realm, with the following credentials:

- ID/username: `demo`
- Last name: `user`
- Password: `Ch4ng31t`
- Email address: `demo@example.com`
- Employee number: `123`

Learn more about managing identities in AM's [Identity stores](#) documentation.

Find the AM session cookie name

In routes that use an AmService, PingGateway retrieves AM's SSO cookie name from the `ssoTokenHeader` property or from AM's `/serverinfo/*` endpoint.

In other circumstances where you need to find the SSO cookie name, access `http://am-base-url/serverinfo/*`. For example, access the AM endpoint with `curl`:

```
$ curl http://am.example.com:8088/openam/json/serverinfo/*
```

External tools used in this guide

The examples in this guide use some of the following third-party tools:

- `curl`: <https://curl.haxx.se>
- `HTTPie`: <https://httpie.org>
- `jq`: <https://stedolan.github.io/jq/>
- `keytool`: <https://docs.oracle.com/en/java/javase/21/docs/specs/man/keytool.html>

Authentication with PingAM

- [Single sign-on with PingAM](#)
 - [Using the default PingAM journey](#)
 - [Using a specific PingAM journey](#)
- [Cross-domain single sign-on for PingAM](#)
- [Password replay with AM](#)
- [Password replay from a database](#)
- [Password replay from a file](#)
- [Session cache eviction with PingAM](#)

Single sign-on with PingAM

The following sections describe how to set up Single Sign-On (SSO) for requests in the same domain:




Important

To require users to authenticate in the correct realm for security reasons, configure SSO or CDSSO with a `PolicyEnforcementFilter` that refers to an AM policy where the realm is enforced. Find an example in [Requiring authentication to an PingAM realm](#).

In SSO using the `SingleSignOnFilter`, PingGateway processes a request using AM authentication. PingGateway and the authentication provider must run on the same domain.

The following sequence diagram shows the flow of information during SSO between PingGateway and AM as the authentication provider.



- The browser sends an unauthenticated request to access the sample application.
- PingGateway intercepts the request, and redirects the browser to AM for authentication.
- AM authenticates the user, creates an SSO token.
- AM redirects the request back to the original URI with the token in a cookie and the browser follows the redirect to PingGateway.
- PingGateway validates the token it gets from the cookie. It adds the AM session info to the request and stores the SSO token in the context for downstream filters and handlers.
- PingGateway forwards the request to the sample application and the sample application returns the requested resource to the browser.

Next steps

- [Using the default PingAM journey](#)
- [Using a specific PingAM journey](#)

Using the default PingAM journey

This page shows how to authenticate with SSO using the default AM authentication journey (tree).

Before you begin, prepare AM, PingGateway, and the sample application. Learn more in the [example installation for this guide](#).

1. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

3. Select **Configure > Global Services > Platform**, and add `example.com` as an AM cookie domain.

By default, AM sets host-based cookies. After authentication with AM, requests can be redirected to AM instead of to the resource.

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

4. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/sso.json
```

Windows

```
%appdata%\OpenIG\config\routes\sso.json
```

```
{
  "name": "sso",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/sso$')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SingleSignOnFilter-1",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  }
}
```

Source: [sso.json](#)

Learn how to use Studio set up the PingGateway route in [Policy enforcement in Structured Editor](#) or [Protecting a web app with Freeform Designer](#).

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/sso>.
2. Log in to AM as user `demo`, password `Ch4ng31t`.

The SingleSignOnFilter passes the request to sample application, which displays the sample application home page.

Using a specific PingAM journey

This page shows how to authenticate with SSO and the example AM authentication journey (tree) instead of the default authentication journey.

1. Set up the example in [Using the default PingAM journey](#).
2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/sso-authservice.json
```

Windows

```
%appdata%\OpenIG\config\routes\sso-authservice.json
```

```

{
  "name": "sso-authservice",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/sso-authservice')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SingleSignOnFilter-1",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1",
            "authenticationService": "Example"
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

Source: [sso-authservice.json](#)

Notice the features of the route compared to `sso.json`:

- The route matches requests to `/home/sso-authservice`.
- The `authenticationService` property of `SingleSignOnFilter` refers to `Example`, the name of the example authentication tree in AM. This authentication tree is used for authentication instead of the AM admin UI.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/sso-authservice>.
2. If you see warnings that the site isn't secure, respond to the warnings to access the site.
3. Note that the login page is different from [Using the default PingAM journey](#).

Cross-domain single sign-on for PingAM

This page shows how to set up Cross-Domain Single Sign-On (CDSSO) for requests in a different domain:




Important

To require users to authenticate in the correct realm for security reasons, configure SSO or CDSSO with a `PolicyEnforcementFilter` that refers to an AM policy where the realm is enforced. You can find an example in [Requiring authentication to an PingAM realm](#).

The SSO mechanism depicted in the following diagram can be used when PingGateway and AM are running in the same domain. When PingGateway and AM are running in different domains, AM cookies aren't visible to PingGateway because of the same-origin policy.

CDSSO using the `CrossDomainSingleSignOnFilter` provides a mechanism to push tokens issued by AM to PingGateway running in a different domain.

The following sequence diagram shows the flow of information between PingGateway, AM, and the sample application during CDSSO. In this example, AM is running on `am.example.com`, and PingGateway is running on `ig.ext.com`.



1. The browser sends an unauthenticated request to access the sample app.

2-3. PingGateway intercepts the request, and redirects the browser to AM for authentication.

4. AM authenticates the user and creates a CDSSO token.
5. AM responds to a successful authentication with an HTML autosubmit form containing the issued token.
6. The browser loads the HTML and autosubmit form parameters to the PingGateway callback URL for the redirect endpoint.
7. When `verificationSecretId` in `CrossDomainSingleSignOnFilter` is configured, PingGateway uses it to verify signature of AM session tokens.

When `verificationSecretId` isn't configured, PingGateway discovers and uses the AM JWK set to verify the signature of AM session tokens.

If that fails, the `CrossDomainSingleSignOnFilter` fails to load.

8. PingGateway checks the nonce found inside the CDSSO token to confirm that the callback comes from an authentication initiated by PingGateway.
9. PingGateway constructs a cookie, and fulfills it with a cookie name, path, and domain, using the `CrossDomainSingleSignOnFilter` property `authCookie`. The domain must match that set in the AM PingGateway agent.
- 10-11. PingGateway redirects the request back to the original URI, with the cookie, and the browser follows the redirect back to PingGateway.
12. PingGateway validates the SSO token inside of the CDSSO token
- 13-15. PingGateway adds the AM session info to the request, and stores the SSO token and CDSSO token in the contexts for use by downstream filters and handlers.
- 16-18. PingGateway forwards the request to the sample application, and the sample application returns the requested resource to the browser.

Before you begin, prepare AM, PingGateway, and the sample application. Learn more in the [example installation for this guide](#).

1. Set up AM:

1. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent_cdsso`
- **Password:** `password`
- **Redirect URL for CDSSO:** `https://ig.ext.com:8443/home/cdsso/redirect`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

2. Select **Services > Add a Service**, and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.ext.com:8443/*`
- `https://ig.ext.com:8443/*?*`

3. Select **Configure > Global Services > Platform**, and add `example.com` as an AM cookie domain.

By default, AM sets host-based cookies. After authentication with AM, requests can be redirected to AM instead of to the resource.

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).

2. Add the following `session` configuration to `admin.json`.

This ensures the browser passes the session cookie in the form-POST to the redirect endpoint (step 6 of [Information flow during CDSSO](#)):

```
{
  "connectors": [...],
  "session": {
    "type": "InMemorySessionManager",
    "config": {
      "cookie": {
        "sameSite": "none",
        "secure": true
      }
    }
  },
  "heap": [...]
}
```

This step is required for the following reasons:

- When `sameSite` is `strict` or `lax`, the browser doesn't send the session cookie, which contains the nonce used in validation. If PingGateway doesn't find the nonce, it assumes that the authentication failed.
- When `secure` is `false`, the browser is likely to reject the session cookie.

Learn more in [AdminHttpApplication \(admin.json\)](#).

3. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a `SystemAndEnvSecretStore`, and must be base64-encoded.

4. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/..*\\\\\\\\.ico$')
or matchesWithRegex(request.uri.path, '^/..*\\\\\\\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) 

5. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/cdsso.json
```

Windows

```
%appdata%\OpenIG\config\routes\cdsso.json
```



```

{
  "name": "cdsso",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/cdsso')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "http://am.example.com:8088/openam",
        "realm": "/",
        "agent": {
          "username": "ig_agent_cdsso",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "sessionCache": {
          "enabled": false
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "CrossDomainSingleSignOnFilter-1",
          "type": "CrossDomainSingleSignOnFilter",
          "config": {
            "redirectEndpoint": "/home/cdsso/redirect",
            "authCookie": {
              "path": "/home",
              "name": "ig-token-cookie"
            },
            "amService": "AmService-1"
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

Source: [cdsso.json](#)

Notice the following features of the route:

- The route matches requests to `/home/cdsso`.
- The agent password for AmService is provided by a SystemAndEnvSecretStore in the heap.

- Because the `CrossDomainSingleSignOnFilter`'s `verificationSecretId` isn't configured, PingGateway discovers and uses the AM JWK set to verify the signature of AM session tokens. If that fails, the `CrossDomainSingleSignOnFilter` fails to load.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.ext.com:8443/home/cdsso>.

The `CrossDomainSingleSignOnFilter` redirects the request to AM for authentication.

2. Log in to AM as user `demo`, password `Ch4ng31t`.

When you have authenticated, AM calls `/home/cdsso/redirect`, and includes the CDSO token. The `CrossDomainSingleSignOnFilter` passes the request to sample app, which returns the home page.

Password replay with AM

Password replay brings SSO to legacy web applications without the need to edit, upgrade, or recode them.

Use PingGateway with an appropriate AM authentication tree to capture and replay username password credentials. PingGateway and AM share a secret key to encrypt and decrypt the password and keep it safe.

When running PingOne Advanced Identity Cloud, read [Password replay and PingOne Advanced Identity Cloud](#) instead.

Request flow

The following figure illustrates the flow of requests when an unauthenticated user accesses a protected application. After authenticating with AM, the user is logged into the application with the username and password from the AM login session.




Figure 1. Password replay sequence diagram

- PingGateway intercepts the browser's HTTP GET request.
- PingGateway redirects the user to AM for authentication.

- AM authenticates the user and stores the encrypted password in a JWT.
- AM redirects the browser back to the protected application with the JWT.
- PingGateway intercepts the browser's HTTP GET request again:
 - The user is authenticated.
 - PingGateway gets the password from the JWT and decrypts it.
 - PingGateway gets the username from AM based on the user `_id`.
- PingGateway replaces the request with an HTTP POST to the application, taking the credentials from the context.
- The sample application validates the credentials from the HTTP POST request.
- The sample application responds with the user's profile page.
- PingGateway passes the response from the sample application to the browser.

Tasks

Before you begin

Before you begin, prepare AM, PingGateway, and the sample application. Learn more in the [example installation for this guide](#).

Task 1: Prepare a shared secret

PingGateway and AM share a secret symmetric key to encrypt and decrypt the password.



Tip

The following tasks use the AM default `aestest` 256-bit AES test key as the shared secret. Don't use the test key in production. In a production deployment, generate a random AES 256-bit key to use as a shared secret. How you generate the secret key is up to you. For example:

```
$ openssl rand -base64 32
```

Output

```
YWJjZGVmZ2hpamtsbW5vcHFyc3R1dnd5eHowMTIzNDU=
```

Keep the secret safe.

You'll set the AM secret label `scripted.node.aes.key` to reference it in a script to encrypt the user's credentials. You'll also share the secret with PingGateway to decrypt the user's credentials before replaying them.

Task 2: Configure AM

This example uses the `default-passwords-store` secret store for the shared secret. In a production deployment, use your own secret store and shared secret:

1. Go to <http://am.example.com:8088/openam/encode.jsp> and use the page to encode the base64-encoded AES key.

In this example, the base64-encoded AES key is `YWJjZGVmZ2hpamtsbW5vcHFyc3R1dnd5eHowMTIzNDU=`.

2. Write the result to a `default-passwords-store` file named `scripted.node.aes.key`:

```
$ echo -n <encoded-aes-key> > /path/to/openam/security/secrets/encrypted/scripted.node.aes.key
```

Only secret labels that begin with the string `scripted.node.` are accessible to scripts.

3. Select **Realms > Top Level Realm > Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

4. In the agent profile for PingGateway, add a redirect URI for CDSSO that PingGateway can use in the route for password replay.

Go to **Applications > Agents > Identity Gateway > ig_agent**, set **Redirect URLs for CDSSO** to `https://ig.example.com:8443/replay/redirect`, and click **Save Changes**.

5. Go to **Scripts**, click **+ New Script** and create a **Decision node script for authentication trees** with the **Legacy** engine named `Password replay` and the following JavaScript content.

The script adds a JWT encrypted with the shared secret key to the session:

```

var fr = JavaImporter(
    org.forgerock.openam.auth.node.api.Action,
    org.forgerock.openam.auth.node.api,
    javax.security.auth.callback.TextOutputCallback,
    org.forgerock.json.jose.builders.JwtBuilderFactory,
    org.forgerock.json.jose.jwt.JwtClaimsSet,
    org.forgerock.json.jose.jwe.JweAlgorithm,
    org.forgerock.json.jose.jwe.EncryptionMethod,
    javax.crypto.spec.SecretKeySpec,
    org.forgerock.secrets.SecretBuilder,
    org.forgerock.util.encode.Base64
);

var NodeOutcome = {
    ERROR: 'false',
    SUCCESS: 'true'
};

var config = {
    encryptionKey: secrets.getGenericSecret("scripted.node.aes.key").getAsUtf8()
};

function getKey () {
    logger.message("encKey: " + config.encryptionKey)
    return new fr.SecretKeySpec(fr.Base64.decode(config.encryptionKey), 'AES');
}

function buildJwt (claims) {
    logger.message('Building response JWT');
    var encryptionKey = getKey();
    var jwtClaims = new fr.JwtClaimsSet;
    jwtClaims.setClaims(claims);
    var jwt = new fr.JwtBuilderFactory()
        .jwe(encryptionKey)
        .headers()
        .alg(fr.JweAlgorithm.DIRECT)
        .enc(fr.EncryptionMethod.A128CBC_HS256)
        .done()
        .claims(jwtClaims)
        .build();

    return jwt;
}

try {
    password=nodeState.get("password").asString()
    var registrationClaims = { password: password };
    passwordJwt = buildJwt(registrationClaims);
    action = fr.Action.goTo(NodeOutcome.SUCCESS).putSessionProperty("sunIdentityUserPassword",
passwordJwt).build();
} catch (e) {
    logger.error('ERROR ' + e);
    action = fr.Action.send(new fr.TextOutputCallback(fr.TextOutputCallback.ERROR, e.toString())).build();
}

```

You can download the script as [password-replay-am.js](#).

- Go to **Authentication > Trees**, click **+ Create Tree**, and create an authentication tree named **Password replay** configured with the nodes shown in this screenshot:



- The Page node presents a page with input fields to prompt for the username and password.
 - The Username collector node collects and injects the `userName` into the shared node state.
 - The Password collector node collects and injects the `password` into the shared node state.
- The Data Store Decision node uses the username and password to determine whether authentication is successful.
- The Scripted Decision node references your script and has the same outcomes: `true` and `false`.

7. Make sure the allowlist for scripted decision nodes includes all the classes the script requires.

Go to **Configure** > **Global Services** > **Scripting** > **Secondary Configurations** >

AUTHENTICATION_TREE_DECISION_NODE > **Secondary Configurations** > **engineConfiguration**, add these Java classes to the allowlist, then click **Save Changes**:

- `javax.crypto.spec.SecretKeySpec`
- `org.forgerock.json.jose.builders.EncryptedJwtBuilder`
- `org.forgerock.json.jose.builders.JweHeaderBuilder`
- `org.forgerock.json.jose.builders.JwtBuilderFactory`
- `org.forgerock.json.jose.jwe.EncryptionMethod`
- `org.forgerock.json.jose.jwe.JweAlgorithm`
- `org.forgerock.json.jose.jwt.JwtClaimsSet`
- `org.forgerock.secrets.SecretBuilder`
- `org.forgerock.util.encode.Base64`

8. Make sure the test user can log in with the tree before continuing.

To verify the tree works as expected, in your browser's privacy or incognito mode, go to <http://am.example.com:8088/openam/XUI/?service=Password%20replay#login> and log in as test user `demo` with password `Ch4ng31t`.

Task 3: Configure PingGateway

The password replay configuration includes the PingGateway password to connect to AM, the shared secret, and the route for password replay.

1. Set up PingGateway for HTTPS.

Learn more in [Configure PingGateway for TLS \(server-side\)](#).

- Set an environment variable locally on the computer running PingGateway to access the base64-encoded agent password:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

PingGateway retrieves the password with a SystemAndEnvSecretStore, which requires it to be base64-encoded.

The password must match the agent profile password you set in AM. PingGateway uses the password to connect to AM.

- Set an environment variable locally on the computer running PingGateway to access the base64-encoded shared secret key:

```
$ export AES_KEY='YWJjZGVmZ2hpamtsbW5vcHFyc3R1dnd5eHowMTIzNDU='
```

PingGateway retrieves the shared secret with a SystemAndEnvSecretStore, which requires it to be base64-encoded.

The shared secret key must match the secret key the AM script uses to encrypt the password to replay. PingGateway uses the secret key to decrypt the password to replay.

- Restart PingGateway to read the secrets from the environment.
- Add a route to PingGateway to serve the sample application CSS and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^.*\\.ico$') or matchesWithRegex(request.uri.path, '^.*\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

- Add a route for password replay:

Linux

```
$HOME/.openig/config/routes/04-replay.json
```

Windows

```
%appdata%\OpenIG\config\routes\04-replay.json
```

```

{
  "name": "04-replay",
  "condition": "${find(request.uri.path, '^/replay')}",
  "properties": {
    "amInstanceUrl": "http://am.example.com:8088/openam/"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore",
      "config": {
        "mappings": [
          {
            "secretId": "aes.key",
            "format": {
              "type": "SecretKeyPropertyFormat",
              "config": {
                "format": "BASE64",
                "algorithm": "AES"
              }
            }
          }
        ]
      }
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "&{amInstanceUrl}"
      }
    },
    {
      "name": "CapturedUserPasswordFilter-1",
      "type": "CapturedUserPasswordFilter",
      "config": {
        "ssoToken": "${contexts.ssoToken.value}",
        "keySecretId": "aes.key",
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "amService": "AmService-1"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "CrossDomainSingleSignOnFilter-1",
          "type": "CrossDomainSingleSignOnFilter",
          "config": {
            "redirectEndpoint": "/replay/redirect",
            "authCookie": {
              "path": "/replay",
              "name": "ig-token-cookie"
            }
          }
        }
      ]
    }
  }
}

```



```

    },
    "amService": "AmService-1",
    "authenticationService": "Password replay"
  }
},
{
  "name": "UserProfileFilter-1",
  "type": "UserProfileFilter",
  "config": {
    "username": "${contexts.ssoToken.info.uid}",
    "userService": {
      "type": "UserProfileService",
      "config": {
        "amService": "AmService-1",
        "profileAttributes": [
          "username"
        ]
      }
    }
  }
},
{
  "name": "PasswordReplayFilter-1",
  "type": "PasswordReplayFilter",
  "config": {
    "loginPage": "${true}",
    "credentials": "CapturedUserPasswordFilter-1",
    "request": {
      "method": "POST",
      "uri": "http://app.example.com:8081/login",
      "form": {
        "username": [
          "${contexts.userProfile.username}"
        ],
        "password": [
          "${contexts.capturedPassword.value}"
        ]
      }
    }
  },
  "capture": [
    "all"
  ]
},
{
  "handler": "ReverseProxyHandler"
}
}
}

```

Source: [04-replay.json](#)

The route:

- Matches requests whose path starts with `/replay`.
- Sets an `amInstanceUrl` property to the URL for AM.
- Loads the `aes.key` secret key from the local `AES_KEY` environment variable.

- Connects to AM as `ig_agent` with the `agent.secret.id` password from the local `AGENT_SECRET_ID` environment variable.
- Extracts the captured password from the SSO token context and decrypts it with the `aes.key` secret key.
- Uses a `CrossDomainSingleSignOnFilter` to redirect to the AM `Password replay` tree for authentication, getting the authentication information from the `ig-token-cookie`.
- Queries AM to retrieve the username for logging in.

You can retrieve other profile attributes with the `UserProfileFilter`, such as the email address or first and last names. The sample application expects the username in this example, so the route gets the username.

- Logs in to the sample application with the username and password.
- Returns the result to the browser.

In production, remove `"capture": ["all"]` from the `PasswordReplayFilter` to avoid recording credentials in the logs.

Validation

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/replay/>.

PingGateway redirects to the AM authentication tree.

2. Log in as test user `demo` with password `Ch4ng31t`.

PingGateway successfully replays the credentials against the sample application. The sample application displays its user profile page:


Howdy, wolkig

USER INFORMATION

Username wolkig

REQUEST INFORMATION

Method POST
URI /login
Cookies
Headers **Content-Length:** 37
Content-Type: application/x-www-form-urlencoded
host: app.example.com:8081
Query Parameters

3. Review the PingGateway output.

On success, the output displays the credentials and the profile page:

```

...INFO  o.f.o.d.c.C.c.PasswordReplayFilter-1 @04-replay -

[CONTINUED]--- (filtered-request) exchangeId:<id> - transactionId:<id> --->

[CONTINUED]POST http://app.example.com:8081/login HTTP/1.1
[CONTINUED]Content-Length: 31
[CONTINUED]Content-Type: application/x-www-form-urlencoded

[CONTINUED]password=Ch4ng31t&username=demo

...INFO  o.f.o.d.c.C.c.PasswordReplayFilter-1 @04-replay -

[CONTINUED]<--- (response) exchangeId:<id> - transactionId:<id> ---

[CONTINUED]HTTP/1.1 200 OK
...

[CONTINUED]<!DOCTYPE html>
...

```

You have successfully demonstrated password replay with PingGateway and AM.

If password replay fails, consider the outcome of the HTTP POST from PingGateway to the sample application:

HTTP 401 Unauthorized

PingGateway is not replaying the credentials.

Review the PingGateway output to determine whether the username or password is missing when PingGateway replays the credentials.

If the password is missing, make sure PingGateway and AM share the same AES secret key.

HTTP 403 Forbidden


PingGateway is not replaying the right credentials.

Make sure you're using a username-password combination known to the sample application.

Password replay from a database

This page shows how to configure PingGateway to get credentials from a database. This example is tested with H2 1.4.197.

The following figure illustrates the flow of requests when PingGateway uses credentials from a database to log a user in to the sample application:



- PingGateway intercepts the browser's HTTP GET request.
- The PasswordReplayFilter confirms that a login page is required, and passes the request to the SqlAttributesFilter.
- The SqlAttributesFilter uses the email address to look up credentials in H2, and stores them in the request context attributes map.
- The PasswordReplayFilter retrieves the credentials from the attributes map, builds the login form, and performs the HTTP POST request to the sample app.
- The sample application validates the credentials, and responds with a profile page.

Before you start, prepare PingGateway and the sample application as described in the [Getting started with PingGateway](#).

1. Set up the database:

1. On your system, add the following data in a comma-separated value file:

Linux

```
/tmp/userfile.txt
```

Windows

```
C:\Temp\userfile.txt
```

```
username,password,fullname,email
george,C0stanza,George Costanza,george@example.com
kramer,N3wman12,Kramer,kramer@example.com
bjensen,H1falutin,Babs Jensen,bjensen@example.com
demo,Ch4ng31t,Demo User,demo@example.com
kvaughan,B5ibery12,Kirsten Vaughan,kvaughan@example.com
scarter,S9rain12,Sam Carter,scarter@example.com
wolkig,Geh3imnis!,Wilhelm Wolkig,wolkig@example.com
```

Source: [userfile.txt](#)

2. Download the [H2 database](#), unpack it, and start it:

```
$ sh /path/to/h2/bin/h2.sh
```

H2 starts listening on port 8082 and opens the H2 Console in a browser.

3. In the H2 Console, select the following options, and then select Connect to access the console:

- **Saved Settings**: Generic H2 (Server)
- **Setting Name**: Generic H2 (Server)
- **Driver Class**: org.h2.Driver
- **JDBC URL**: jdbc:h2:~/ig-credentials
- **User Name**: sa
- **Password**: password



Tip

If you have run this example before but can't access the console now, try deleting your local ~/ig-credentials files and starting H2 again.

4. In the console, add the following text, and then run it to create the user table:

```
DROP TABLE IF EXISTS USERS;  
CREATE TABLE USERS AS SELECT * FROM CSVREAD('/tmp/userfile.txt');
```

5. In the console, add the following text, and then run it to verify that the table contains the same users as the file:

```
SELECT * FROM users;
```

6. Add the .jar file `/path/to/h2/bin/h2-*.jar` to the PingGateway configuration:

- Create the directory `$HOME/.openig/extra`, where `$HOME/.openig` is the instance directory, and add .jar files to the directory.

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the database password, and then restart PingGateway:

```
$ export DATABASE_PASSWORD='cGFzc3dvcmQ='
```

The password is retrieved by a `SystemAndEnvSecretStore`, and must be base64-encoded.

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) 

4. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/03-sql.json
```

Windows

```
%appdata%\OpenIG\config\routes\03-sql.json
```

```

{
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "JdbcDataSource-1",
      "type": "JdbcDataSource",
      "config": {
        "driverClassName": "org.h2.Driver",
        "jdbcUrl": "jdbc:h2:tcp://localhost/~ig-credentials",
        "username": "sa",
        "passwordSecretId": "database.password",
        "secretsProvider": "SystemAndEnvSecretStore-1"
      }
    }
  ],
  "name": "sql",
  "condition": "${find(request.uri.path, '^/profile')}",
  "handler": {
    "type": "Chain",
    "baseURI": "http://app.example.com:8081",
    "config": {
      "filters": [
        {
          "type": "PasswordReplayFilter",
          "config": {
            "loginPage": "${find(request.uri.path, '^/profile/george') and (request.method == 'GET')}",
            "credentials": {
              "type": "SqlAttributesFilter",
              "config": {
                "dataSource": "JdbcDataSource-1",
                "preparedStatement":
                  "SELECT username, password FROM users WHERE email = ?;",
                "parameters": [
                  "george@example.com"
                ]
              }
            }
          },
          "request": {
            "method": "POST",
            "uri": "http://app.example.com:8081/login",
            "form": {
              "username": [
                "${contexts.sqlAttributes.row.USERNAME}"
              ],
              "password": [
                "${contexts.sqlAttributes.row.PASSWORD}"
              ]
            }
          }
        }
      ]
    }
  },
  "handler": "ReverseProxyHandler"
}

```

Source: [03-sql.json](#)

Notice the following features of the route:

- The route matches requests to `/profile`.
- The `PasswordReplayFilter` specifies a `loginPage` page property:
- When a request is an HTTP GET, and the request URI path is `/profile/george`, the expression resolves to `true`. The request is directed to a login page.

The `SqlAttributesFilter` specifies the data source to access, a prepared statement to look up the user's record, and a parameter to pass into the statement.

The `request` object retrieves the username and password from the context, and replaces the browser's original HTTP GET request with an HTTP POST login request, containing the credentials to authenticate.

The request is for `username`, `password`, but H2 returns the fields as `USERNAME` and `PASSWORD`. The configuration reflects this difference.

- For other requests, the expression resolves to `false`. The request passes to the `ReverseProxyHandler`, which directs it to the profile page of the sample app.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/profile>.

If you see warnings that the site isn't secure, respond to the warnings to access the site.


Because the property `loginPage` resolves to `false`, the `PasswordReplayFilter` passes the request directly to the `ReverseProxyHandler`. The sample app returns the login page.

2. Go to <https://ig.example.com:8443/profile/george>.

Because the property `loginPage` resolves to `true`, the `PasswordReplayFilter` processes the request to obtain the login credentials. The sample app returns the profile page for George.

Password replay from a file

The following figure illustrates the flow of requests when PingGateway uses credentials in a file to log a user in to the sample application:



- PingGateway intercepts the browser's HTTP GET request, which matches the route condition.
- The PasswordReplayFilter confirms that a login page is required, and
- The FileAttributesFilter uses the email address to look up the user credentials in a file, and stores the credentials in the request context attributes map.
- The PasswordReplayFilter retrieves the credentials from the attributes map, builds the login form, and performs the HTTP POST request to the sample app.
- The sample application validates the credentials, and responds with a profile page.
- The ReverseProxyHandler passes the response to the browser.

Before you start, prepare PingGateway and the sample application as described in the [Getting started with PingGateway](#).

1. On your system, add the following data in a comma-separated value file:

Linux

```
/tmp/userfile.txt
```

Windows

```
C:\Temp\userfile.txt
```

```
username,password,fullname,email
george,C0stanz4,George Costanza,george@example.com
kramer,N3wman12,Kramer,kramer@example.com
bjensen,H1falutin,Babs Jensen,bjensen@example.com
demo,Ch4ng31t,Demo User,demo@example.com
kvaughan,B5ibery12,Kirsten Vaughan,kvaughan@example.com
scarter,S9rain12,Sam Carter,scarter@example.com
wolkgig,Geh3imnis!,Wilhelm Wolkgig,wolkgig@example.com
```

Source: [userfile.txt](#)

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) 

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/02-file.json
```

Windows

```
%appdata%\OpenIG\config\routes\02-file.json
```

```

{
  "name": "02-file",
  "condition": "${find(request.uri.path, '^/profile')}",
  "capture": "all",
  "handler": {
    "type": "Chain",
    "baseURI": "http://app.example.com:8081",
    "config": {
      "filters": [
        {
          "type": "PasswordReplayFilter",
          "config": {
            "loginPage": "${find(request.uri.path, '^/profile/george') and (request.method == 'GET')}",
            "credentials": {
              "type": "FileAttributesFilter",
              "config": {
                "file": "/tmp/userfile.txt",
                "key": "email",
                "value": "george@example.com"
              }
            }
          },
          "request": {
            "method": "POST",
            "uri": "http://app.example.com:8081/login",
            "form": {
              "username": [
                "${contexts.fileAttributes.record.username}"
              ],
              "password": [
                "${contexts.fileAttributes.record.password}"
              ]
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

Source: [02-file.json](#)

Notice the following features of the route:

- The route matches requests to `/profile`.
- The `PasswordReplayFilter` specifies a `loginPage` page property:
 - When a request is an HTTP GET, and the request URI path is `/profile/george`, the expression resolves to `true`. The request is directed to a login page.
- The `FileAttributesFilter` looks up the key and value in `/tmp/userfile.txt`, and stores them in the context.

The `request` object retrieves the username and password from the context, and replaces the browser's original HTTP GET request with an HTTP POST login request, containing the credentials to authenticate.

- For other requests, the expression resolves to `false`. The request passes to the `ReverseProxyHandler`, which directs it to the profile page of the sample app.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/profile/george>.
2. If you see warnings that the site isn't secure, respond to the warnings to access the site.

Because the property `loginPage` resolves to `true`, the `PasswordReplayFilter` processes the request to obtain the login credentials. The sample app returns the profile page for George.

3. Go to <https://ig.example.com:8443/profile/bob>, or to any other URI starting with `https://ig.example.com:8443/profile`.

Because the property `loginPage` resolves to `false`, the `PasswordReplayFilter` passes the request directly to the `ReverseProxyHandler`. The sample app returns the login page.

Session cache eviction with PingAM

When WebSocket notifications are enabled in PingGateway, PingGateway receives notifications when the following events occur:

- A user logs out of AM
- An AM session is modified, closed, or times out
- An AM admin forces logout of user sessions (from AM 7.3)

The following procedure gives an example of how to change the configurations in [Single sign-on with PingAM](#) and [Cross-domain single sign-on for PingAM](#) to receive WebSocket notifications for session logout and to evict entries related to the session from the cache. For information about WebSocket notifications, refer to [WebSocket notifications](#).

Before you start, set up and test the example in [Single sign-on with PingAM](#).

1. Websocket notifications are enabled by default. If they are disabled, enable them by adding the following configuration to the `AmService` in your route:

```
"notifications": {  
  "enabled": true  
}
```

2. Enable the session cache by adding the following configuration to the `AmService` in your route:

```
"sessionCache": {  
  "enabled": true  
}
```

3. In `logback.xml` add the following logger for WebSocket notifications, and then restart PingGateway:

```
<logger name="org.forgerock.openig.tools.notifications.ws" level="TRACE" />
```

For information, refer to [Changing the log level for different object types](#).

4. On the AM console, log the demo user out of AM to end the AM session.
5. Note that the PingGateway system logs are updated with Websocket notifications about the logout:

```
... | TRACE | vert.x-eventloop-thread-4 | o.f.o.t.n.w.l.DirectAmLink | @system | Received a message:
{ "topic": ... "eventType": "LOGOUT" } }
... | TRACE | vert.x-eventloop-thread-4 | o.f.o.t.n.w.SubscriptionService | @system | Notification received...
"eventType": "LOGOUT" }}
... | TRACE | vert.x-eventloop-thread-4 | o.f.o.t.n.w.SubscriptionService | @system | Notification sent to a
[/agent/session.v2] listener
```

PingAM policy enforcement


PingGateway as a policy enforcement point (PEP) uses the `PolicyEnforcementFilter` to intercept requests for a resource and provide information about the request to AM.

AM as a policy decision point (PDP) evaluates requests based on their context and the configured policies. AM then returns decisions indicating what actions are allowed or denied and any advice, subject attributes, or static attributes for the specified resources.

You can find more information in the [PolicyEnforcementFilter](#) and AM's [Authentication and SSO](#) [documentation](#).

Deny requests without advice


The following image shows a simplified flow of information when AM denies a request without advice.



Deny requests with advice as parameters in a redirect response

The following image shows a simplified flow of information when AM denies a request with advice and PingGateway returns the advices as parameters in a redirect response.

This is the default flow, most used for web applications.




Deny requests with advice in a header

The following image shows a simplified flow of information when the request to PingGateway includes an `x-authenticate-response` header with the value `header`. If the header has any other value, the flow in [Deny requests with advice as parameters in a redirect response](#) takes place.

To change the name of the `x-authenticate-response` header, refer to the `authenticateResponseRequestHeader` property of the [PolicyEnforcementFilter](#).

In this flow, AM denies the request with advice and PingGateway sends the response with the advice in the `WWW-authenticate` header.

Use this method for SDKs and single page applications. Placing advice in a header gives these applications more options for handling the advice.



Consider the following example GET with an `x-authenticate-response` header with the value `HEADER` :

```
[CONTINUED]GET https://ig.example.com:8443/home HTTP/1.1
[CONTINUED]accept-encoding: gzip, deflate
[CONTINUED]Connection: close
[CONTINUED]cookie: iPlanetDirectoryPro=0Dx...e3A.*....; amlbcookie=01
[CONTINUED]Host: ig.example.com:8443
[CONTINUED]x-authenticate-response: HEADER
```

PingGateway returns a `WWW-Authenticate` header containing advice:

```
HTTP/1.1 401 Unauthorized
WWW-Authenticate: SSOADVICE realm="/",advices="eyJ...XX0=",am_uri="http://openam.example.com:8080/am/"
transfer-encoding: chunked
connection: close
```

The advice decodes to a transaction condition advice:

```
{"TransactionConditionAdvice":["493...3c4"]}
```


Next steps

- [Enforce AM policy decisions](#)
 - [Decisions in the same domain with PingAM](#)
 - [Requiring authentication to an PingAM realm](#)
 - [Decisions in different domains with PingAM](#)
 - [Decisions with a claimsSubject and PingAM](#)
 - [Notifications and the PingAM policy cache](#)
- [Hardening PingAM authorization](#)
 - [Stepping up the PingAM authentication level](#)
 - [Authorizing a single transaction with PingAM](#)

Enforce AM policy decisions

The following pages show how to use PingGateway to enforce AM policy decisions:

- [Decisions in the same domain with PingAM](#)
- [Requiring authentication to an PingAM realm](#)
- [Decisions in different domains with PingAM](#)
- [Decisions with a claimsSubject and PingAM](#)
- [Notifications and the PingAM policy cache](#)

Decisions in the same domain with PingAM

The following procedure gives an example of how to create a policy in AM and configure an agent that can request policy decisions, when PingGateway and AM are in the same domain.

Before you start, set up and test the example in [Using the default PingAM journey](#).

1. Set up AM:

1. Select  **Authorization** > **Policy Sets** > **New Policy Set**, and add a policy set with the following values:

- **Id** : PEP-SSO
- **Resource Types** : URL

2. In the policy set, add a policy with the following values:

- **Name** : PEP-SSO
- **Resource Type** : URL

- **Resource pattern** : `*://*:*/*`
- **Resource value** : `http://app.example.com:8081/home/pep-sso*`

This policy protects the home page of the sample application.

3. On the **Actions** tab, add an action to allow HTTP `GET`.
 4. On the **Subjects** tab, remove any default subject conditions, add a subject condition for all `Authenticated Users`.
2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/04-pep.json
```

Windows

```
%appdata%\OpenIG\config\routes\04-pep.json
```

```

{
  "name": "pep-sso",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/pep-sso')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SingleSignOnFilter-1",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        },
        {
          "name": "PolicyEnforcementFilter-1",
          "type": "PolicyEnforcementFilter",
          "config": {
            "application": "PEP-SSO",
            "ssoTokenSubject": "${contexts.ssoToken.value}",
            "amService": "AmService-1"
          }
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  }
}

```

Source: [04-pep-sso.json](#)

Learn how to use Studio to set up the PingGateway route in [Policy enforcement in Structured Editor](#) or [Protecting a web app with Freeform Designer](#).

Find an example route that uses `claimsSubject` instead of `ssoTokenSubject` to identify the subject in [Example policy enforcement using claimsSubject](#).

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/pep-ssso>.
2. If you see warnings that the site isn't secure, respond to the warnings to access the site.

Because you haven't previously authenticated to AM, the request does not contain a cookie with an SSO token. The SingleSignOnFilter redirects you to AM for authentication.

3. Log in to AM as user `demo`, password `Ch4ng31t`.

When you have authenticated, AM redirects you back to the request URL, and PingGateway requests a policy decision using the AM session cookie.

AM returns a policy decision that grants access to the sample application.

Requiring authentication to an PingAM realm

This example creates a policy that requires users to authenticate in a specific realm.

To reduce the attack surface on the top level realm, ForgeRock advises you to create federation entities, agent profiles, authorizations, OAuth2/OIDC, and STS services in a subrealm. For this reason, the AM policy, AM agent, and services are in a subrealm.

1. Set up AM:

1. In the AM admin UI, click  **Realms** and add a realm named `alpha`. Leave all other values as default.

For the rest of the steps in this procedure, make sure you are managing the alpha realm by checking that the  **alpha** icon is displayed on the top left.

2. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

3. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

4. Add a policy:

1. Select  **Authorization > Policy Sets > New Policy Set**, and add a policy set with the following values:

- **Id :** `PEP-SSO-REALM`
- **Resource Types :** `URL`

2. In the policy set, add a policy with the following values:

- **Name** : PEP-SSO-REALM
- **Resource Type** : URL
- **Resource pattern** : *//*:*/*
- **Resource value** : http://app.example.com:8081/home/pep-sso-realm

This policy protects the home page of the sample application.

3. On the **Actions** tab, add an action to allow HTTP **GET**.

4. On the **Subjects** tab, remove any default subject conditions, add a subject condition for all **Authenticated Users**.

5. On the **Environments** tab, add an environment condition that requires the user to authenticate to the **alpha** realm:

- **Type** : Authentication to a Realm
- **Authenticate to a Realm** : /alpha

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*/.*\\.ico$') or matchesWithRegex(request.uri.path, '^/.*/.*\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

4. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/04-pep-sso-realm.json
```

Windows

```
%appdata%\OpenIG\config\routes\04-pep-sso-realm.json
```

```
{
  "name": "pep-sso-realm",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/pep-sso-realm')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/",
        "realm": "/alpha"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SingleSignOnFilter-1",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        },
        {
          "name": "PolicyEnforcementFilter-1",
          "type": "PolicyEnforcementFilter",
          "config": {
            "application": "PEP-SSO-REALM",
            "ssoTokenSubject": "${contexts.ssoToken.value}",
            "amService": "AmService-1"
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}
```

Source: [04-pep-sso-realm.json](#)

Notice the following differences compared to `04-pep-sso.json` :

- The AmService is in the `alpha` realm. That means that the user authenticates to AM in that realm.
- The PolicyEnforcementFilter realm is not specified, so it takes the same value as the AmService realm. If refers to a policy in the AM `alpha` realm.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/pep-sso-realm>.
2. If you see warnings that the site isn't secure, respond to the warnings to access the site.
3. Log in to AM as user `demo`, password `Ch4ng31t`.

Because you are authenticating in the `alpha` realm, AM returns a policy decision that grants access to the sample application.

If you were to send the request from a different realm, AM would redirect the request with an `AuthenticateToRealmConditionAdvice`.

Decisions in different domains with PingAM

The following procedure gives an example of how to create a policy in AM and configure an agent that can request policy decisions, when PingGateway and AM are in different domains.

Before you start, set up and test the example in [Cross-domain single sign-on for PingAM](#).

1. Set up AM:

1. In the AM admin UI, select **Applications > Agents > Identity Gateway**, and change the redirect URL for `ig_agent_cdsso` :

- **Redirect URL for CDSO** : `https://ig.ext.com:8443/home/pep-cdsso/redirect`

2. Select **Authorization > Policy Sets > New Policy Set**, and add a policy set with the following values:

- **Id** : `PEP-CDSSO`

- **Resource Types** : `URL`

- In the new policy set, add a policy with the following values:

- **Name** : `CDSSO`

- **Resource Type** : `URL`

- **Resource pattern** : `*://*:*/*`

- **Resource value** : `http://app.example.com:8081/home/pep-cdsso*`

This policy protects the home page of the sample application.

- On the **Actions** tab, add an action to allow HTTP `GET`.

- On the **Subjects** tab, remove any default subject conditions, add a subject condition for all **Authenticated Users**.

2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/04-pep-cdsso.json
```

Windows

```
%appdata%\OpenIG\config\routes\04-pep-cdsso.json
```



```

{
  "name": "pep-cdsso",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/pep-cdsso')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent_cdsso",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "CrossDomainSingleSignOnFilter-1",
          "type": "CrossDomainSingleSignOnFilter",
          "config": {
            "redirectEndpoint": "/home/pep-cdsso/redirect",
            "authCookie": {
              "path": "/home",
              "name": "ig-token-cookie"
            },
            "amService": "AmService-1"
          }
        },
        {
          "name": "PolicyEnforcementFilter-1",
          "type": "PolicyEnforcementFilter",
          "config": {
            "application": "PEP-CDSSO",
            "ssoTokenSubject": "${contexts.cdsso.token}",
            "amService": "AmService-1"
          }
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  }
}

```

Source: [04-pep-cdsso.json](#)

**Warning**

When `verificationSecretId` isn't configured, PingGateway discovers and uses the AM JWK set to verify the signature of AM session tokens. If the JWK set isn't available, PingGateway doesn't verify the tokens.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.ext.com:8443/home/pep-cdsso>.
2. If you see warnings that the site isn't secure, respond to the warnings to access the site.

PingGateway redirects you to AM for authentication.
3. Log in to AM as user `demo`, password `Ch4ng31t`.

When you have authenticated, AM redirects you back to the request URL, and PingGateway requests a policy decision. AM returns a policy decision that grants access to the sample application.

Decisions with a claimsSubject and PingAM

This example extends [Decisions in the same domain with PingAM](#) to enforce a policy decision from AM using the `claimsSubject` instead of `ssoTokenSubject` to identify the subject.

Before you start, set up and test the example in [Decisions in the same domain with PingAM](#).

1. Set up AM:

1. Select the policy `PEP-SSO` and add a new resource:

- **Resource Type:** `URL`
- **Resource pattern:** `*://*:*/*`
- **Resource value:** `http://app.example.com:8081/home/pep-claims`

2. In the same policy, add the following subject condition:

- **Any of**
- **Type :** `OpenID Connect/JwtClaim`
- **claimName :** `iss`
- **claimValue :** `am.example.com`

2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/04-pep-claims.json
```

Windows

```
%appdata%\OpenIG\config\routes\04-pep-claims.json
```

```

{
  "name": "pep-claims",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/pep-claims')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "http://am.example.com:8088/openam",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SingleSignOnFilter-1",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        },
        {
          "name": "PolicyEnforcementFilter-1",
          "type": "PolicyEnforcementFilter",
          "config": {
            "application": "PEP-SSO",
            "claimsSubject": {
              "sub": "${contexts.ssoToken.info.uid}",
              "iss": "am.example.com"
            },
            "amService": "AmService-1"
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

Source: [04-pep-claims.json](#)

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/pep-claims>.
2. If you see warnings that the site isn't secure, respond to the warnings to access the site.

3. Log in to AM as user `demo` , password `Ch4ng31t` .

AM returns a policy decision that grants access to the sample application.

Notifications and the PingAM policy cache

When WebSocket notifications are enabled, PingGateway receives notifications whenever AM creates, deletes, or changes a policy.

The following procedure gives an example of how to change the configuration in [Decisions in the same domain with PingAM](#) and [Decisions in different domains with PingAM](#) to evict outdated entries from the policy cache. For information about WebSocket notifications, refer to [WebSocket notifications](#).

Before you start, set up and test the example in [Decisions in the same domain with PingAM](#).

1. Websocket notifications are enabled by default. If they are disabled, enable them by adding the following configuration to the `AmService` in your route:

```
"notifications": {  
  "enabled": true  
}
```

2. Enable policy cache in the `PolicyEnforcementFilter` in your route:

```
"cache": {  
  "enabled": true  
}
```

3. In `logback.xml` add the following logger for WebSocket notifications, and then restart PingGateway:

```
<logger name="org.forgerock.openig.tools.notifications.ws" level="TRACE" />
```

For information, refer to [Changing the log level for different object types](#).

4. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.ext.com:8443/home/pep-sso>.
2. If you see warnings that the site isn't secure, respond to the warnings to access the site.
3. Log in to AM as user `demo` , password `Ch4ng31t` .
4. In a separate terminal, log on to AM as admin, and change the PEP-SSO policy. For example, in the **Actions** tab, add an action to allow HTTP `DELETE` .
5. Note that the PingGateway system logs are updated with Websocket notifications about the change:

```
... | TRACE | vert.x-eventloop-thread-14 | o.f.o.t.n.w.l.DirectAmLink | @system | Received a
message: ... "policy": "PEP-SSO", "policySet": "PEP-SSO", "eventType": "UPDATE" } }
... | TRACE | vert.x-eventloop-thread-14 | o.f.o.t.n.w.SubscriptionService | @system | Notification
received, ... "policy": "PEP-SSO", "policySet": "PEP-SSO", "eventType": "UPDATE" }}
... | TRACE | vert.x-eventloop-thread-14 | o.f.o.t.n.w.SubscriptionService | @system | Notification
sent to a [/agent/policy] listener
```

Hardening PingAM authorization

To protect sensitive resources, AM policies can use additional conditions to harden the authorization. When AM communicates a policy decision to PingGateway, the decision includes advice to indicate extra conditions the user must meet.

Conditions can include requirements to access the resource over a secure channel, access during working hours, or a higher authentication level. For more information, refer to AM's [Authorization guide](#).

The following pages build on the policies to [Enforce AM policy decisions](#):

- [Stepping up the PingAM authentication level](#)
- [Authorizing a single transaction with PingAM](#)

Stepping up the PingAM authentication level

When you step up the authentication level for an AM session, the authorization is verified and then captured as part of the AM session, and the user agent is authorized to that authentication level for the duration of the AM session.


This page uses the policies you created in [Decisions in the same domain with PingAM](#) and [Decisions in different domains with PingAM](#), adding an authorization policy with an environment condition to step up the authentication level. Except for the paths where noted, procedures for single domain and cross-domain are the same.

After the user agent redirects the user to AM, if the user is not already authenticated they are presented with a login page. If the user is already authenticated, or after they authenticate, they are presented with a second page asking for an OTP verification code to step up the authentication level. You need a mobile device such as a phone to generate the OTP code.

Update AM settings

Before you start, set up one of the examples in [Decisions in the same domain with PingAM](#) or [Decisions in different domains with PingAM](#).

1. In the AM admin UI, add a tree to step up authentication.
 1. Select **Authentication > Trees > + Create Tree**.
 2. Name the new tree **StepUpAuthentication**.
 3. Add nodes to the tree as in the following image:



- The **OATH Token Verifier** [node](#) has the default settings.

It validates the user's OTP verification code or leads the unregistered user to register an OTP generator application.

- The **OATH Registration** [node](#) registers an OTP generator application for the user.
- The second **OATH Token Verifier** [node](#) verifies an initial OTP after registration.
- The **OATH Device Storage** [node](#) stores the OTP generator application setting in the user's profile.
- Update the **Modify Auth Level** [node](#) to set **Value to Add:** `1` , raising the authentication level.

4. Click **Save**.

2. Update the policy to use the new authentication tree.

1. Select a policy set:

- For SSO, select **Authorization > Policy Sets > PEP-SSO**.
- For CDSSO, select **Authorization > Policy Sets > PEP-CDSSO**.

2. In the policy, select **Environments** and add the following environment condition:

- **All of**
- **Type :** `Authentication by Service`
- **Authenticate to Service :** `StepUpAuthentication`

3. Click ✓ and **Save Changes**.

The summary of the policy looks similar to the following image:

Authorization - Policy Sets > PEP-CDSSO > policies > CDSSO


POLICY | Active

CDSSO

Summary
Resources
Actions
Subjects
Environments
Response Attributes


Resources

<http://app.example.com:8081/home/pep-cdsso>


Subjects

```
{
  "type": "AuthenticatedUsers"
}
```


Actions

[GET: Allowed](#)


Environments

```
{
  "type": "AuthenticateToService",
  "authenticateToService": "StepUpAuthentication"
}
```


Response Attributes

[+ Add Response Attributes](#)

Validation

1. In your browser's privacy or incognito mode, go to the appropriate URL:

- For SSO, go to <https://ig.example.com:8443/home/pep-sso>.
- For CDSSO, go to <https://ig.ext.com:8443/home/pep-cdsso>.

2. Log in to AM as user `demo`, password `Ch4ng31t`.

AM creates a session with the default authentication level `0`, and PingGateway requests a policy decision.

The updated policy requires authentication level `1`, which is higher than the AM session's current authentication level. AM issues a redirect with a `AuthenticateToServiceConditionAdvice` to authenticate at level `1`.

3. If you haven't registered an OTP generator application, follow the instructions in your browser to register one.

4. Enter the OTP verification code from the application you registered on your device.

AM upgrades the authentication level for the session to `1`, and grants access to the sample application. If you try to access the sample application again in the same session, you don't need to provide the verification code.

Authorizing a single transaction with PingAM

Transactional authorization requires a user to perform additional actions for one-time access to a resource.

Performing the additional action successfully grants access to the protected resource, but only once. Additional attempts to access the resource require the user to perform the configured actions again.

This section builds on the example in [Stepping up the PingAM authentication level](#), adding a simple authorization policy with a **Transaction** environment condition. Each time the user agent tries to access the protected resource, they confirm the transaction again.

Update AM settings


Before you start, configure AM as described in [Stepping up the PingAM authentication level](#). The PingGateway configuration is not changed.

1. In the AM admin UI, add a tree to confirm the transaction.

1. Select **Authentication > Trees > + Create Tree**.

2. Name the new tree **ConfirmTransaction**.

3. Set up the tree as in the following image:



The **Choice Collector** [node](#) has these settings:

- **Choices:** Yes and No
- **Default Choice:** No
- **Prompt:** Confirm transaction?

4. Click **Save**.

2. Update the policy to use the new authentication tree.

1. Select the policy set:

- For SSO, select **Authorization > Policy Sets > PEP-SSO**.
- For CDSSO, select **Authorization > Policy Sets > PEP-CDSSO**.

2. In the policy, select **Environments** and add another environment condition:

- **All of**
- **Type:** Transaction

- **Authentication strategy:** `Authenticate To Tree`
- **Strategy specifier:** `ConfirmTransaction`

3. Click ✓ and **Save Changes**.

4. Select **Resources** and update the resources to point to the PingGateway endpoint for SSO or CDSSO.

For transactional authorization with trees, AM requires authorization *through* PingGateway:

- `https://ig.example.com:8443/home/pep-sso*`
- `https://ig.ext.com:8443/home/pep-cdsso*`

The summary of the policy looks similar to the following image. This example is for CSSSO:

Authorization - Policy Sets > PEP-CDSSO > policies > CDSSO


POLICY | Active

CDSSO

Summary
Resources
Actions
Subjects
Environments
Response Attributes


Resources

`http://app.example.com:8081/home/pep-cdsso*`


Actions

`GET: Allowed`


Response Attributes

[+ Add Response Attributes](#)


Subjects

```
{
  "type": "AuthenticatedUsers"
}
```


Environments

```
{
  "type": "AND",
  "conditions": [
    {
      "type": "AuthenticateToService",
      "authenticateToService": "StepUpAuthentication"
    },
    {
      "type": "Transaction",
      "authenticationStrategy": "AuthenticateToTreeConditionAdvice",
      "strategySpecifier": "ConfirmTransaction"
    }
  ]
}
```

Update the PingGateway route

- Edit the route you created:
 - SSO: `04-pep.json`
 - CDSSO: `04-pep-cdsso.json`
- Find the `PolicyEnforcementFilter-1` filter and add a `resourceUriProvider`:

SSO

```
{
  "name": "PolicyEnforcementFilter-1",
  "type": "PolicyEnforcementFilter",
  "config": {
    "application": "PEP-SSO",
    "ssoTokenSubject": "${contexts.ssoToken.value}",
    "amService": "AmService-1",
    "resourceUriProvider": {
      "type": "RequestResourceUriProvider",
      "config": {
        "useOriginalUri": true,
        "includeQueryParams": false
      }
    }
  }
}
```

CDSSO

```
{
  "name": "PolicyEnforcementFilter-1",
  "type": "PolicyEnforcementFilter",
  "config": {
    "application": "PEP-CDSSO",
    "ssoTokenSubject": "${contexts.cdsso.token}",
    "amService": "AmService-1",
    "resourceUriProvider": {
      "type": "RequestResourceUriProvider",
      "config": {
        "useOriginalUri": true,
        "includeQueryParams": false
      }
    }
  }
}
```

3. Save the updated route file.

Validation


1. In your browser's privacy or incognito mode, go to the appropriate URL:
 - For SSO, go to <https://ig.example.com:8443/home/pep-sso>.
 - For CDSSO, go to <https://ig.ext.com:8443/home/pep-cdsso>.
2. Log in to AM as user `demo`, password `Ch4ng31t`.

AM creates a session with the default authentication level `0`, and PingGateway requests a policy decision.

3. Enter the OTP verification code from the application you registered on your device.

AM steps up the authentication level and displays a `Confirm transaction?` choice.

4. Confirm the transaction by selecting **Yes** and logging in.



The screenshot shows a user interface for confirming a transaction. At the top, the text "Confirm transaction?" is displayed. Below this text are two buttons: "Yes" and "No". The "Yes" button is highlighted with a blue border. Below these buttons is a large green button labeled "LOG IN".

AM returns a policy decision granting one-time access to the sample application. If you reload the sample application page, you must confirm the new transaction.

OAuth 2.0 and PingAM

As an authorization server, PingGateway *authenticates* resource owners and gets their *authorization* to return access tokens to clients.

Before you configure OAuth 2.0 in your environment, familiarize yourself with the [OAuth 2.0 authorization framework](#) and related standards.

OAuth 2.0 concepts

RFC 6749, the [OAuth 2.0 authorization framework](#) lets a third-party application obtain limited access to a resource (usually user data) on behalf of the resource owner or the application itself.

The main actors in the OAuth 2.0 authorization framework are the following:

Actor	Description
Resource owner (RO)	The owner of the resource. For example, a user who stores their photos in a photo-sharing service. The resource owner uses a <i>user-agent</i> , usually a web-browser, to communicate with the client.
Client	The third-party application that wants to access the resource. The client makes requests on behalf of the resource owner and with their authorization. For example, a printing service that needs to access the resource owner's photos to print them. Learn more from PingGateway as an OAuth 2.0 client .

Actor	Description
Authorization server (AS)	The authorization service that authenticates the resource owner and/or the client, issues access tokens to the client, and tracks their validity. Access tokens prove that the resource owner authorizes the client to act on their behalf over specific resources for a limited period of time. PingOne Advanced Identity Cloud or PingAM can act as an authorization server.
Resource server (RS)	The service hosting the protected resources. For example, a photo-sharing service. The resource server must be able to validate the tokens issued by the authorization server. Learn more from PingGateway as an OAuth 2.0 resource server .

PingGateway as an OAuth 2.0 client

PingGateway as an OAuth 2.0 client supports the OAuth 2.0 filters and flows in the following table:

Filter	OAuth 2.0 flow	Description
AuthorizationCodeOAuth2ClientFilter	Authorization Code Grant 	This filter requires the user agent to authorize the request interactively to obtain an access token and optional ID token. The access token is maintained only for the OAuth 2.0 session, and is valid only for the configured scopes. This filter can act as an OpenID Connect relying party or as an OAuth 2.0 client. Use for Web applications running on a server.
ResourceOwnerOAuth2ClientFilter	Resource Owner Password Credentials Grant 	According to information in the The OAuth 2.0 Authorization Framework  , minimize use of this grant type and use other grant types when possible. This filter supports the transformation of client credentials and user credentials to obtain an access token from the Authorization Server. It injects the access token into the inbound request as a Bearer Authorization header. The access token is valid only for the configured scopes. Use for clients trusted with the resource owner credentials.
ClientCredentialsOAuth2ClientFilter	Client Credentials Grant 	This filter is similar to the Resource Owner Password Credentials grant type, but the resource owner is not part of the flow and the client accesses only information relevant to itself. Use when the client is the resource owner, or the client doesn't act on behalf of the resource owner.

PingGateway as an OAuth 2.0 resource server

The following image illustrates the steps for a client application to access a user's protected resources, with AM as the Authorization Server and PingGateway as the resource server:




Figure 1. PingGateway as an OAuth 2.0 resource server handling OAuth 2.0 requests

- The application obtains an *authorization grant*, representing the resource owner's consent. Learn more about the different OAuth 2.0 grant mechanisms supported by AM in the AM documentation on [OAuth 2.0 grant flows](#).
- The application authenticates to the Authorization Server and requests an *access token*. The Authorization Server returns an access token to the application.

An OAuth 2.0 access token is an opaque string issued by the authorization server. When the client interacts with the resource server, the client presents the access token in the `Authorization` header. For example:

```
Authorization: Bearer 7af...da9
```

Access tokens are the credentials to access protected resources. The advantage of access tokens over passwords or other credentials is that access tokens can be granted and revoked without exposing the user's credentials.

The access token represents the authorization to access protected resources. Because an access token is a bearer token, anyone who has the access token can use it to get the resources. Access tokens must therefore be protected, so that requests involving them go over HTTPS.

In OAuth 2.0, the token scopes are strings that identify the scope of access authorized to the client, but can also be used for other purposes.

- The application supplies the access token to the resource server, which then resolves and validates the access token by using an access token resolver, as described in [PingGateway access token resolvers](#).

If the access token is valid, the resource server permits the client access to the requested resource.

The [OAuth2ResourceServerFilter](#) grants access to a resource by using an OAuth 2.0 access token from the HTTP Authorization header of a request.

When auditing is enabled, OAuth 2.0 token tracking IDs can be logged in access audit events for routes that contain an [OAuth2ResourceServerFilter](#). Learn more in [Auditing the PingGateway deployment](#) and [PingGateway audit framework](#).

Next steps

- [Validating PingAM access tokens with introspection](#)
- [Scripting required scopes with PingAM](#)
- [Validating PingAM stateless access tokens](#)
 - [With JwkSetSecretStore and PingAM](#)
 - [Signed PingAM tokens with KeyStoreSecretStore](#)
 - [Encrypted PingAM tokens with KeyStoreSecretStore](#)
- [Mutual TLS with PingAM](#)
 - [mTLS with PingAM using client certificates](#)
 - [mTLS with PingAM and trusted headers](#)
- [OAuth 2.0 context for authentication with PingAM](#)
- [Caching PingAM access tokens](#)
- [Client credentials grant with PingAM](#)
- [Resource owner password credentials grant with PingAM](#)

Validating PingAM access tokens with introspection

This page sets up PingGateway as an OAuth 2.0 resource server using the introspection endpoint.

Learn more about configuring AM as an OAuth 2.0 authorization server in the AM [OAuth 2.0 documentation](#) .

 Important

This procedure uses the *Resource Owner Password Credentials* grant type. As suggested in [The OAuth 2.0 Authorization Framework](#), use other grant types whenever possible.

Before you begin, prepare AM, PingGateway, and the sample application. Learn more in the [example installation for this guide](#).

1. Set up AM:

1. Select **Applications > Agents > Identity Gateway**, and register a PingGateway agent with the following values:

- **Agent ID:** `ig_agent`
- **Password:** `password`
- **Token Introspection:** `Realm Only`

 Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

2. Create an OAuth 2.0 Authorization Server:

1. Select **Services > Add a Service > OAuth2 Provider**.
2. Add a service with the default values.

3. Create an OAuth 2.0 Client to request OAuth 2.0 access tokens:

1. Select **Applications > OAuth 2.0 > Clients**, and add a client with the following values:

- **Client ID:** `client-application`
- **Client secret:** `password`
- **Scope(s):** `mail`, `employeenumber`

2. (Optional) On the **Core** tab, switch to using a client secret associated with a secret label by setting a **Secret Label Identifier** and mapping the label to a secret.

To learn more, read [Create a client profile](#) and [Map and rotate secrets](#) in the AM documentation.

3. On the **Advanced** tab, select the following value:

- **Grant Types:** `Resource Owner Password Credentials`

2. Set up PingGateway

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/rs-introspect.json
```

Windows

```
%appdata%\OpenIG\config\routes\rs-introspect.json
```



```

{
  "name": "rs-introspect",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/rs-introspect$')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [
              "mail",
              "employeenumber"
            ],
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "TokenIntrospectionAccessTokenResolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "amService": "AmService-1",
                "providerHandler": {
                  "type": "Chain",
                  "config": {
                    "filters": [
                      {
                        "type": "HttpBasicAuthenticationClientFilter",
                        "config": {
                          "username": "ig_agent",
                          "passwordSecretId": "agent.secret.id",
                          "secretsProvider": "SystemAndEnvSecretStore-1"
                        }
                      }
                    ],
                    "handler": "ForgeRockClientHandler"
                  }
                }
              }
            }
          }
        }
      ]
    }
  }
}

```

```

    },
    "handler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 200,
        "headers": {
          "Content-Type": [ "text/html; charset=UTF-8" ]
        },
        "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></html>"
      }
    }
  }
}

```

Source: [rs-introspect.json](#)

Learn how to set up the PingGateway route in [Token validation using the introspection endpoint in Structured Editor](#).

Notice the following features of the route:

- The route matches requests to `/rs-introspect`.
- The `OAuth2ResourceServerFilter` expects an OAuth 2.0 access token in the `authorization` header of the incoming authorization request, with the scopes `mail` and `employeenumber`.

The `accessTokenResolver` uses the AM server declared in the heap. The introspection endpoint to validate the access token is extrapolated from the URL of the AM server.

For convenience in this test, `requireHttps` is false. In production environments, set it to true.

- After the filter validates the access token, it creates a new context from the Authorization Server response. The context is named `oauth2`, and can be reached at `contexts.oauth2` or `contexts['oauth2']`.

The context contains information about the access token, which can be reached at `contexts.oauth2.accessToken.info`. Filters and handlers further down the chain can access the token info through the context.

If there is no access token in the request, or token validation does not complete successfully, the filter returns an HTTP error status to the user agent, and PingGateway doesn't continue processing the request. This is done as specified in the RFC, [The OAuth 2.0 Authorization Framework: Bearer Token Usage](#).

- The `HttpBasicAuthenticationClientFilter` adds the credentials to the outgoing token introspection request.
- The `StaticResponseHandler` returns the content of the access token from the context `${contexts.oauth2.accessToken.info}`.

3. Test the setup:

1. In a terminal window, use a `curl` command similar to the following to retrieve an access token:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail%20employeeenumber" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

2. Validate the access token returned in the previous step:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/rs-introspect
```

Output

```
{
  active = true,
  scope = employeeenumber mail,
  realm=/,
  client_id = client-application,
  user_id = demo,
  token_type = Bearer,
  exp = 158...907,
  ...
}
```

Scripting required scopes with PingAM

This example builds on the example in [Validating PingAM access tokens with introspection](#) to use a script to define the scopes that a request requires in an access token.

- If the request path is `/rs-tokeninfo`, the request requires only the scope `mail`.
- If the request path is `/rs-tokeninfo/employee`, the request requires the scopes `mail` and `employeeenumber`.

Before you start, set up and test the example in [Validating PingAM access tokens with introspection](#).

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/rs-dynamicscope.json
```

Windows

```
%appdata%\OpenIG\rs-dynamicscope.json
```

```

{
  "name": "rs-dynamicscope",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/rs-dynamicscope')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": {
              "name": "myscript",
              "type": "ScriptableResourceAccess",
              "config": {
                "type": "application/x-groovy",
                "source": [
                  "// Minimal set of required scopes",
                  "def scopes = [ 'mail' ] as Set",
                  "if (request.uri.path =~ /employee$/) {",
                  "  // Require another scope to access this resource",
                  "  scopes += 'employeenumber'",
                  "}",
                  "return scopes"
                ]
              }
            }
          },
          "requireHttps": false,
          "accessTokenResolver": {
            "name": "token-resolver-1",
            "type": "TokenIntrospectionAccessTokenResolver",
            "config": {
              "amService": "AmService-1",
              "providerHandler": {
                "type": "Chain",
                "config": {
                  "filters": [
                    {
                      "type": "HttpBasicAuthenticationClientFilter",
                      "config": {
                        "username": "ig_agent",

```

```
        "passwordSecretId": "agent.secret.id",
        "secretsProvider": "SystemAndEnvSecretStore-1"
    }
}
],
    "handler": "ForgeRockClientHandler"
}
}
}
}
},
    ],
    "handler": {
        "type": "StaticResponseHandler",
        "config": {
            "status": 200,
            "headers": {
                "Content-Type": [ "text/html; charset=UTF-8" ]
            },
            "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></>"
        }
    }
}
```

Source: [rs-dynamicscope.json](#)

2. Test the setup with the `mail` scope only:

1. In a terminal, use a `curl` command to retrieve an access token with the scope `mail`:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

2. Confirm that the access token is returned for the `/rs-dynamicscope` path:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/rs-dynamicscope
```

Output

```
{
  active = true,
  scope = mail,
  client_id = client-application,
  user_id = demo,
  token_type = Bearer,
  exp = 158...907,
  sub = demo,
  iss = http://am.example.com:8088/openam/oauth2, ...
  ...
}
```

3. Confirm that the access token **is not** returned for the `/rs-dynamicscope/employee` path:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/rs-dynamicscope/employee
```

3. Test the setup with the scopes `mail` and `employeenumber`:

1. In a terminal window, use a `curl` command similar to the following to retrieve an access token with the scopes `mail` and `employeenumber`:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail%20employeenumber" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

2. Confirm that the access token **is** returned for the `/rs-dynamicscope/employee` path:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/rs-dynamicscope/employee
```

Validating PingAM stateless access tokens

The `StatelessAccessTokenResolver` confirms that stateless access tokens provided by AM are well-formed, have a valid issuer, have the expected access token name, and have a valid signature.

After the `StatelessAccessTokenResolver` resolves an access token, the `OAuth2ResourceServerFilter` checks that the token is within the expiry time, and that it provides the required scopes. For more information, refer to [StatelessAccessTokenResolver](#).

The following pages show how to validate signed and encrypted access tokens:

- [With JwkSetSecretStore and PingAM](#)
- [Signed PingAM tokens with KeyStoreSecretStore](#)
- [Encrypted PingAM tokens with KeyStoreSecretStore](#)

With JwkSetSecretStore and PingAM

This page shows how to validate signed access tokens with the StatelessAccessTokenResolver using a [JwkSetSecretStore](#).



Important

This procedure uses the *Resource Owner Password Credentials* grant type. As suggested in [The OAuth 2.0 Authorization Framework](#), use other grant types whenever possible.

1. Set up AM:

1. Configure an OAuth 2.0 Authorization Provider:

1. Select **Services**, and add an OAuth 2.0 Provider.
2. Accept the default values and select **Create**. The service is added to the **Services** list.
3. On the **Core** tab, select the following option:

■ **Use Client-Based Access & Refresh Tokens** : on

4. On the **Advanced** tab, select the following options:

■ **Client Registration Scope Allowlist** : myscope

■ **OAuth2 Token Signing Algorithm** : RS256

■ **Encrypt Client-Based Tokens** : Deselected

2. Create an OAuth2 Client to request OAuth 2.0 access tokens:

1. Select **Applications > OAuth 2.0 > Clients**, and add a client with the following values:

■ **Client ID** : client-application

■ **Client secret** : password

■ **Scope(s)** : myscope

2. (Optional) On the **Core** tab, switch to using a client secret associated with a secret label by setting a **Secret Label Identifier** and mapping the label to a secret.

To learn more, read [Create a client profile](#) and [Map and rotate secrets](#) in the AM documentation.

3. On the **Advanced** tab, select the following values:

■ **Grant Types** : Resource Owner Password Credentials

■ **Response Types** : code token

4. On the **Signing and Encryption** tab, include the following setting:

■ **ID Token Signing Algorithm** : RS256

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).

2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/rs-stateless-signed.json
```

Windows

```
%appdata%\OpenIG\config\routes\rs-stateless-signed.json
```



```

{
  "name": "rs-stateless-signed",
  "condition": "${find(request.uri.path, '/rs-stateless-signed')}",
  "heap": [
    {
      "name": "SecretsProvider-1",
      "type": "SecretsProvider",
      "config": {
        "stores": [
          {
            "type": "JwkSetSecretStore",
            "config": {
              "jwkUrl": "http://am.example.com:8088/openam/oauth2/connect/jwk_uri"
            }
          }
        ]
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "capture": "all",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": ["myscope"],
            "requireHttps": false,
            "accessTokenResolver": {
              "type": "StatelessAccessTokenResolver",
              "config": {
                "secretsProvider": "SecretsProvider-1",
                "issuer": "http://am.example.com:8088/openam/oauth2",
                "verificationSecretId": "any.value.in.regex.format"
              }
            }
          }
        }
      ]
    },
    "handler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 200,
        "headers": {
          "Content-Type": [ "text/html; charset=UTF-8" ]
        },
        "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></html>"
      }
    }
  }
}

```

Source: [rs-stateless-signed.json](#) 

Notice the following features of the route:

- The route matches requests to `/rs-stateless-signed`.
- A `SecretsProvider` in the heap declares a `JwkSetSecretStore` to manage secrets for signed access tokens.
- The `JwkSetSecretStore` specifies the URL to a JWK set on AM, that contains the signing keys.
- The `OAuth2ResourceServerFilter` expects an OAuth 2.0 access token in the header of the incoming authorization request, with the scope `myscope`.
- The `StatelessAccessTokenResolver` uses the `SecretsProvider` to verify the signature of the provided access token.
- After the `OAuth2ResourceServerFilter` validates the access token, it creates the `OAuth2Context` context. You can find more information in [OAuth2Context](#).
- If there is no access token in a request, or token validation doesn't complete successfully, the filter returns an HTTP error status to the user agent, and PingGateway doesn't continue processing the request. This is done as specified in the RFC [The OAuth 2.0 Authorization Framework: Bearer Token Usage](#).
- The `StaticResponseHandler` returns the content of the access token from the context.

3. Test the setup for a signed access token:

1. Get an access token for the demo user, using the scope `myscope`:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=myscope" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

2. Display the token:

```
$ echo ${mytoken}
```

Note that the token is structured as a signed token.

3. Access the route by providing the token returned in the previous step:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/rs-stateless-signed
```

Output

```
...
Decoded access_token: {
  sub=(usr!demo),
  cts=0AUTH2_STATELESS_GRANT,
  ...
}
```

Signed PingAM tokens with KeyStoreSecretStore

This page shows how to validate signed access tokens with the StatelessAccessTokenResolver using a [KeyStoreSecretStore](#).

Set up signing keys

1. Locate the following directories for keys, keystores, and certificates, and in a terminal create variables for them:

- Directory where the keystore is created: `keystore_directory`
- AM keystore directory: `am_keystore_directory`
- PingGateway keystore directory: `ig_keystore_directory`

2. Set up the keystore for signing keys:

1. Generate a private key called `signature-key`, and a corresponding public certificate called `x509certificate.pem`:

```
$ openssl req -x509 \
-newkey rsa:2048 \
-nodes \
-subj "/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr" \
-keyout $keystore_directory/signature-key.key \
-out $keystore_directory/x509certificate.pem \
-days 365
```

Output

```
...
writing new private key to '$keystore_directory/signature-key.key'
```

2. Convert the private key and certificate files into a PKCS#12 file, called `signature-key`, and store them in a keystore named `keystore.p12`:

```
$ openssl pkcs12 \  
-export \  
-in $keystore_directory/x509certificate.pem \  
-inkey $keystore_directory/signature-key.key \  
-out $keystore_directory/keystore.p12 \  
-passout pass:password \  
-name signature-key
```

3. List the keys in `keystore.p12` :

```
$ keytool -list \  
-v \  
-keystore "$keystore_directory/keystore.p12" \  
-storepass "password" \  
-storetype PKCS12
```

Output

```
...  
Your keystore contains 1 entry  
Alias name: signature-key
```

3. Set up keys for AM:

1. Copy the signing key `keystore.p12` to AM:

```
$ cp $keystore_directory/keystore.p12 $am_keystore_directory/AM_keystore.p12
```

2. List the keys in the AM keystore:

```
$ keytool -list \  
-v \  
-keystore "$am_keystore_directory/AM_keystore.p12" \  
-storepass "password" \  
-storetype PKCS12
```

Output

```
...  
Your keystore contains 1 entry  
Alias name: signature-key
```

3. Add a file called `keystore.pass` , containing the store password `password` :

```
$ cd $am_keystore_directory
$ echo -n 'password' > keystore.pass
```

Note

Make sure the password file contains only the password, with no trailing spaces or carriage returns.

The filename corresponds to the secret ID of the store password and entry password for the KeyStoreSecretStore.

4. Restart AM.

4. Set up keys for PingGateway:

1. Import the public certificate to the IG keystore, with the alias **verification-key**:

```
$ keytool -import \
-trustcacerts \
-rfc \
-alias verification-key \
-file "$keystore_directory/x509certificate.pem" \
-keystore "$ig_keystore_directory/IG_keystore.p12" \
-storetype PKCS12 \
-storepass "password"
```

Output

```
...
Trust this certificate? [no]: yes
Certificate was added to keystore
```

2. List the keys in the PingGateway keystore:

```
$ keytool -list \
-v \
-keystore "$ig_keystore_directory/IG_keystore.p12" \
-storepass "password" \
-storetype PKCS12
```

Output

```
...
Your keystore contains 1 entry
Alias name: verification-key
```

3. In the PingGateway configuration, set an environment variable for the keystore password:

```
$ export KEYSTORE_SECRET_ID='cGFzc3dvcmQ='
```

4. Restart PingGateway.

Validate tokens



Important

This procedure uses the *Resource Owner Password Credentials* grant type. As suggested in [The OAuth 2.0 Authorization Framework](#), use other grant types whenever possible.

1. Set up AM:

1. Create a KeyStoreSecretStore to manage the new AM keystore:

1. In AM, select  **Secret Stores**, and then add a secret store with the following values:

- **Secret Store ID** : `keystoresecretstore`
- **Store Type** : `Keystore`
- **File** : `am_keystore_directory/AM_keystore.p12`
- **Keystore type** : `PKCS12`
- **Store password secret label** : `keystore.pass`
- **Entry password secret label** : `keystore.pass`

2. Select the **Mappings** tab, and add a mapping with the following values:

- **Secret Label** : `am.services.oauth2.stateless.signing.RSA`
- **Aliases** : `signature-key`

The mapping sets `signature-key` as the active alias to use for signature generation.

2. Create a FileSystemSecretStore to manage secrets for the KeyStoreSecretStore:

1. Select  **Secret Stores**, and then create a secret store with the following configuration:

- **Secret Store ID** : `filesystemsecretstore`
- **Store Type** : `File System Secret Volumes`
- **Directory** : `am_keystore_directory`
- **File format** : `Plain text`

3. Configure an OAuth 2.0 Authorization Provider:

1. Select **Services**, and add an OAuth 2.0 Provider.

2. Accept all of the default values, and select **Create**. The service is added to the **Services** list.

3. On the **Core** tab, select the following option:

- **Use Client-Based Access & Refresh Tokens** : on

4. On the **Advanced** tab, select the following options:

- **Client Registration Scope Allowlist** : myscope
- **OAuth2 Token Signing Algorithm** : RS256
- **Encrypt Client-Based Tokens** : Deselected

4. Create an OAuth2 Client to request OAuth 2.0 access tokens:

1. Select **Applications > OAuth 2.0 > Clients**, and add a client with the following values:

- **Client ID** : client-application
- **Client secret** : password
- **Scope(s)** : myscope

2. (Optional) On the **Core** tab, switch to using a client secret associated with a secret label by setting a **Secret Label Identifier** and mapping the label to a secret.

To learn more, read [Create a client profile](#) and [Map and rotate secrets](#) in the AM documentation.

3. On the **Advanced** tab, select the following values:

- **Grant Types** : Resource Owner Password Credentials
- **Response Types** : code token

4. On the **Signing and Encryption** tab, include the following setting:

- **ID Token Signing Algorithm** : RS256

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).

2. Add the following route to PingGateway, replacing `<ig_keystore_directory>` :

Linux

```
$HOME/.openig/config/routes/rs-stateless-signed-ksss.json
```

Windows

```
%appdata%\OpenIG\config\routes\rs-stateless-signed-ksss.json
```

```

{
  "name": "rs-stateless-signed-ksss",
  "condition" : "${find(request.uri.path, '/rs-stateless-signed-ksss')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "KeyStoreSecretStore-1",
      "type": "KeyStoreSecretStore",
      "config": {
        "file": "<ig_keystore_directory>/IG_keystore.p12",
        "storeType": "PKCS12",
        "storePasswordSecretId": "keystore.secret.id",
        "entryPasswordSecretId": "keystore.secret.id",
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "mappings": [
          {
            "secretId": "stateless.access.token.verification.key",
            "aliases": [ "verification-key" ]
          }
        ]
      }
    }
  ],
  "handler" : {
    "type" : "Chain",
    "capture" : "all",
    "config" : {
      "filters" : [ {
        "name" : "OAuth2ResourceServerFilter-1",
        "type" : "OAuth2ResourceServerFilter",
        "config" : {
          "scopes" : [ "myscope" ],
          "requireHttps" : false,
          "accessTokenResolver": {
            "type": "StatelessAccessTokenResolver",
            "config": {
              "secretsProvider": "KeyStoreSecretStore-1",
              "issuer": "http://am.example.com:8088/openam/oauth2",
              "verificationSecretId": "stateless.access.token.verification.key"
            }
          }
        }
      } ],
      "handler": {
        "type": "StaticResponseHandler",
        "config": {
          "status": 200,
          "headers": {
            "Content-Type": [ "text/html; charset=UTF-8" ]
          },
          "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></html>"
        }
      }
    }
  }
}

```


Source: [rs-stateless-signed-ksss.json](#)

Notice the following features of the route:

- The route matches requests to `/rs-stateless-signed-ksss`.
- The keystore password is provided by the `SystemAndEnvSecretStore` in the heap.
- The `OAuth2ResourceServerFilter` expects an OAuth 2.0 access token in the header of the incoming authorization request, with the scope `myscope`.
- The `accessTokenResolver` uses a `StatelessAccessTokenResolver` to resolve and verify the authenticity of the access token. The secret is provided by the `KeyStoreSecretStore` in the heap.
- After the `OAuth2ResourceServerFilter` validates the access token, it creates the `OAuth2Context` context. You can find more information in [OAuth2Context](#).
- If there is no access token in a request, or if the token validation doesn't complete successfully, the filter returns an HTTP error status to the user agent, and PingGateway stops processing the request, as specified in the RFC, [The OAuth 2.0 Authorization Framework: Bearer Token Usage](#).
- The `StaticResponseHandler` returns the content of the access token from the context.

3. Test the setup for a signed access token:

1. Get an access token for the demo user, using the scope `myscope`:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=myscope" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

2. Display the token:

```
$ echo ${mytoken}
```

3. Access the route by providing the token returned in the previous step:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/rs-stateless-signed-ksss
```

Output

```
...
Decoded access_token: {
  sub=(usr!demo),
  cts=0AUTH2_STATELESS_GRANT,
  ...
}
```

Encrypted PingAM tokens with KeyStoreSecretStore

This page shows how to validate encrypted access tokens with the StatelessAccessTokenResolver using a [JwkSetSecretStore](#).

Set up encryption keys

1. Locate the following directories for keys, keystores, and certificates, and in a terminal create variables for them:

- Directory where the keystore is created: `keystore_directory`
- AM keystore directory: `am_keystore_directory`
- PingGateway keystore directory: `ig_keystore_directory`

2. Set up keys for AM:

1. Generate the encryption key:

```
$ keytool -genseckey \
  -alias encryption-key \
  -dname "CN=ig.example.com, OU=example, O=com, L=fr, ST=fr, C=fr" \
  -keystore "$am_keystore_directory/AM_keystore.p12" \
  -storetype PKCS12 \
  -storepass "password" \
  -keyalg AES \
  -keysize 256
```

2. List the keys in the AM keystore:

```
$ keytool -list \
  -v \
  -keystore "$am_keystore_directory/AM_keystore.p12" \
  -storepass "password" \
  -storetype PKCS12
```

Output

```
...
Your keystore contains 1 entry
Alias name: encryption-key
```

3. Add a file called `keystore.pass`, with the content `password`:

```
$ cd $am_keystore_directory
$ echo -n 'password' > keystore.pass
```

 Note

Make sure the password file contains only the password, with no trailing spaces or carriage returns.

The filename corresponds to the secret ID of the store password and entry password for the KeyStoreSecretStore.

4. Restart AM.

3. Set up keys for PingGateway:

1. Import `encryption-key` into the PingGateway keystore, with the alias `decryption-key`:

```
$ keytool -importkeystore \
-srcalias encryption-key \
-srckeystore "$am_keystore_directory/AM_keystore.p12" \
-srcstoretype PKCS12 \
-srcstorepass "password" \
-destkeystore "$ig_keystore_directory/IG_keystore.p12" \
-deststoretype PKCS12 \
-destalias decryption-key \
-deststorepass "password" \
-destkeypass "password"
```

2. List the keys in the PingGateway keystore:

```
$ keytool -list \
-v \
-keystore "$ig_keystore_directory/IG_keystore.p12" \
-storepass "password" \
-storetype PKCS12
```

Output

```
...
Your keystore contains 1 entry
Alias name: decryption-key
```

3. In the PingGateway configuration, set an environment variable for the keystore password:

```
$ export KEYSTORE_SECRET_ID='cGFzc3dvcmQ='
```

4. Restart PingGateway.

Validate tokens

1. Set up AM:

1. Set up AM as described in [Validate tokens](#).

2. Add a mapping for the encryption keystore:

1. Select  **Secret Stores** > `keystoresecretstore`.

2. Select the **Mappings** tab, and add a mapping with the following values:

■ **Secret Label** : `am.services.oauth2.stateless.token.encryption`

■ **Alias** : `encryption-key`

3. Enable token encryption on the OAuth 2.0 Authorization Provider:

1. Select **Services** > **OAuth2 Provider**.

2. On the **Advanced** tab, select **Encrypt Client-Side Tokens**.

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).

2. Add the following route to PingGateway, replacing `<ig_keystore_directory>`:

Linux

```
$HOME/.openig/config/routes/rs-stateless-encrypted.json
```

Windows

```
%appdata%\OpenIG\config\routes\rs-stateless-encrypted.json
```

```

{
  "name": "rs-stateless-encrypted",
  "condition": "${find(request.uri.path, '/rs-stateless-encrypted')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "KeyStoreSecretStore-1",
      "type": "KeyStoreSecretStore",
      "config": {
        "file": "<ig_keystore_directory>/IG_keystore.p12",
        "storeType": "PKCS12",
        "storePasswordSecretId": "keystore.secret.id",
        "entryPasswordSecretId": "keystore.secret.id",
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "mappings": [
          {
            "secretId": "stateless.access.token.decryption.key",
            "aliases": [ "decryption-key" ]
          }
        ]
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "capture": "all",
    "config": {
      "filters": [ {
        "name": "OAuth2ResourceServerFilter-1",
        "type": "OAuth2ResourceServerFilter",
        "config": {
          "scopes": [ "myscope" ],
          "requireHttps": false,
          "accessTokenResolver": {
            "type": "StatelessAccessTokenResolver",
            "config": {
              "secretsProvider": "KeyStoreSecretStore-1",
              "issuer": "http://am.example.com:8088/openam/oauth2",
              "decryptionSecretId": "stateless.access.token.decryption.key"
            }
          }
        }
      } ],
      "handler": {
        "type": "StaticResponseHandler",
        "config": {
          "status": 200,
          "headers": {
            "Content-Type": [ "text/html; charset=UTF-8" ]
          },
          "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></html>"
        }
      }
    }
  }
}

```

Source: [rs-stateless-encrypted.json](#)

Notice the following features of the route compared to `rs-stateless-signed.json` from [Validate tokens](#).

- The route matches requests to `/rs-stateless-encrypted`.
- The `OAuth2ResourceServerFilter` and `KeyStoreSecretStore` refer to the configuration for a decryption key instead of a verification key.

3. Test the setup

1. Get an access token for the demo user, using the scope `myscope`:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=myscope" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

2. Display the token:

```
$ echo ${mytoken}
```

Note that the token is structured as an encrypted token.

3. Access the route by providing the token returned in the previous step:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/rs-stateless-encrypted
```

Output

```
...
Decoded access_token: {
  sub=demo,
  cts=OAUTH2_STATELESS_GRANT,
  ...
}
```

Mutual TLS with PingAM

Clients can authenticate to AM through mutual TLS (mTLS) and X.509 certificates. Certificates must be self-signed or use public key infrastructure (PKI), as described in version 12 of the draft [OAuth 2.0 Mutual TLS Client Authentication and Certificate Bound Access Tokens](#).

For a client using mTLS, its OAuth 2.0 profile includes a means to access its certificate. When the client requests an access token from AM with mTLS, it authenticates with its certificate to establish the HTTPS connection. This is known as mutual authentication—because the server and client authenticate each other—or client certificate authentication. The client proves it has the private key for the certificate.

The authorization server (AS), such as AM, *binds* the access token to the client certificate with a *confirmation key*. The confirmation key is a certificate *thumbprint*, computed as `base64url-encode(sha256(der(certificate)))`. The access token is then *certificate-bound*, restricted to the client having the corresponding private key. The confirmation key is not necessarily visible in the access token, but the AS provides it on token introspection.

A resource server (RS), such as PingGateway, has the client use HTTPS mutual authentication when requesting a resource with the certificate-bound access token. The RS gets the certificate and proves the client has its private key when setting up HTTPS. The RS gets the confirmation key for the access token and verifies the certificate matches the key. The RS only grants access when the certificate matches the confirmation key.

This proof-of-possession interaction ensures only the client with the private key for the certificate can use the token to access protected resources.

Access to the client certificate

Service	Terminates HTTPS?	Do this
AM in an application container	Yes	Configure the container to allow mutual authentication for HTTPS. Get the client certificate from the HTTPS connection.
	No	Configure the service terminating HTTPS to allow mutual authentication and to forward the request with the client certificate in a trusted header. Get the client certificate from the trusted header.
PingGateway	Yes	Configure PingGateway to allow mutual authentication for HTTPS. Get the client certificate from the HTTPS connection.
	No	Configure the service terminating HTTPS to allow mutual authentication and to forward the request with the client certificate in a trusted header. Get the client certificate from the trusted header.

Next steps


When implementing mTLS, make sure AM and PingGateway either support HTTPS mutual authentication or get the client certificate in a trusted header from the service that supports HTTPS mutual authentication.


- [mTLS with PingAM using client certificates](#) shows how to configure PingGateway to get the client certificate from mutual authentication.
- [mTLS with PingAM and trusted headers](#) shows how to configure PingGateway to get the client certificate from a trusted header.

mTLS with PingAM using client certificates

PingGateway can validate the thumbprint of certificate-bound access tokens by reading the client certificate from the TLS connection.

For this example, the client must be connected directly to PingGateway through a TLS connection, for which PingGateway is the TLS termination point, as shown in the following image. If TLS is terminated at a reverse proxy or load balancer before PingGateway, use the example in [mTLS with PingAM and trusted headers](#).





Follow the steps in this example to try mTLS using standard TLS client certificate authentication.

Prepare the keys

1. To make it easy to identify and refer to secrets used in mTLS examples, create directories and environment variables:

```
$ export ig_keystore_directory=/path/to/ig/secrets
$ export am_keystore_directory=/path/to/am/secrets
$ export oauth2_client_keystore_directory=/path/to/client/secrets
```

2. Create keys and certificates for the example:

1. Create self-signed RSA key pairs for AM and the client:

```
$ keytool -genkeypair \  
-alias openam-server \  
-keyalg RSA \  
-keysize 2048 \  
-keystore $am_keystore_directory/keystore.p12 \  
-storepass changeit \  
-storetype PKCS12 \  
-keypass changeit \  
-validity 360 \  
-dname CN=am.example.com,O=Example,C=FR  
  
$ keytool -genkeypair \  
-alias oauth2-client \  
-keyalg RSA \  
-keysize 2048 \  
-keystore $oauth2_client_keystore_directory/keystore.p12 \  
-storepass changeit \  
-storetype PKCS12 \  
-keypass changeit \  
-validity 360 \  
-dname CN=test
```

2. Export the certificates to .pem so that the `curl` client can verify the identity of the AM and PingGateway servers:

```
$ keytool -export \  
-rfc \  
-alias openam-server \  
-keystore $am_keystore_directory/keystore.p12 \  
-storepass changeit \  
-storetype PKCS12 \  
-file $am_keystore_directory/openam-server.cert.pem
```

Output

Certificate stored in file ../openam-server.cert.pem

3. Extract the certificate and client private key to .pem so that the `curl` command can identify itself as the client for the HTTPS connection:

```
$ keytool -export \  
-rfc \  
-alias oauth2-client \  
-keystore $oauth2_client_keystore_directory/keystore.p12 \  
-storepass changeit \  
-storetype PKCS12 \  
-file $oauth2_client_keystore_directory/client.cert.pem
```

Output

Certificate stored in file ../client.cert.pem

```
$ openssl pkcs12 \
-in $oauth2_client_keystore_directory/keystore.p12 \
-nocerts \
-nodes \
-passin pass:changeit \
-out $oauth2_client_keystore_directory/client.key.pem
```

Output

...verified OK

4. Create the CACerts truststore so that AM can validate the client identity:

```
$ keytool -import \
-noprompt \
-trustcacerts \
-file $oauth2_client_keystore_directory/client.cert.pem \
-keystore $oauth2_client_keystore_directory/cacerts.p12 \
-storepass changeit \
-storetype PKCS12 \
-alias client-cert
```

Output

Certificate was added to keystore

5. In the *ig_keystore_directory*, add a file called `keystore.pass` containing the keystore password:

```
$ cd $ig_keystore_directory
$ echo -n 'changeit' > keystore.pass
```

Prepare AM

1. Configure AM for HTTPS connections using information in the AM documentation about [Secure HTTP and LDAP connections](#).
1. Add a connector configuration for port `8445` to AM's Tomcat `server.xml`, replacing the values for the keystore directories with your path. If the file already contains a connector for the port, edit that connector or replace it:

```
<Connector port="8445" protocol="HTTP/1.1" SSLEnabled="true" scheme="https" secure="true">
  <SSLHostConfig protocols="+TLSv1.2,-TLSv1.1,-TLSv1,-SSLv2Hello,-SSLv3"
    certificateVerification="optionalNoCA"
    truststoreFile="oauth2_client_keystore_directory/cacerts.p12"
    truststorePassword="changeit"
    truststoreType="PKCS12">
    <Certificate certificateKeystoreFile="am_keystore_directory/keystore.p12"
      certificateKeystorePassword="changeit"
      certificateKeystoreType="PKCS12" />
  </SSLHostConfig>
</Connector>
```

2. In AM, export an environment variable for the base64-encoded value of the password (`changeit`) for the `cacerts.p12` truststore:

```
$ export PASSWORDSECRETID='Y2hhbmdlaXQ='
```

3. Restart AM, and make sure you can access it on the secure port `https://am.example.com:8445/openam`.

2. Configure AM for mutual TLS using information in the AM documentation about [Mutual TLS](#).

1. In the AM admin UI, select **Applications > Agents > Identity Gateway**, and register a PingGateway agent that can introspect access tokens:

- **Agent ID:** `ig_agent`
- **Password:** `password`
- **Token Introspection:** `Realm Only`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

2. Configure an OAuth 2.0 Authorization Server with settings for mTLS:

1. Select **Services > Add a Service > OAuth2 Provider**, and add a service with the default values.
2. On the **Advanced** tab, select the following value:

- **Support TLS Certificate-Bound Access Tokens:** `enabled`

3. Configure an OAuth 2.0 client to request access tokens:

1. Select **Applications > OAuth 2.0 > Clients**, and add a client with the following values:

- **Client ID:** `client-application`
- **Client secret:** `password`
- **Scope(s):** `test`

2. (Optional) On the **Core** tab, switch to using a client secret associated with a secret label by setting a **Secret Label Identifier** and mapping the label to a secret.

To learn more, read [Create a client profile](#) and [Map and rotate secrets](#) in the AM documentation.

3. On the **Advanced** tab, select the following values:

- **Grant Types:** `Client Credentials`

The `password` is the only grant type used by the client in the example.

- **Token Endpoint Authentication Method:** `self_signed_tls_client_auth`

4. On the **Signing and Encryption** tab, set the following values:

- **mTLS Self-Signed Certificate:** Enter the content of the X.509 certificate, `client.cert.pem`.

- **mTLS Subject DN:** `CN=test`

When this option is set, AM requires the subject DN in the client certificate to have the same value. This ensures that the certificate is from the client and not just a valid certificate trusted by the trust manager.

- **Public key selector:** `x509`

- **Use Certificate-Bound Access Tokens:** Enabled

Prepare PingGateway

1. Configure PingGateway for HTTPS using information from [Configure PingGateway for TLS \(server-side\)](#).

This example uses a self-signed certificate stored in a PEM file.

2. Configure PingGateway for mutual TLS using information from [Configure PingGateway for mTLS \(server-side\)](#).

This example uses the following `admin.json` with a SecretsTrustManager:

Linux

```
$HOME/.openig/config/admin.json
```

Windows

```
%appdata%\OpenIG\config\admin.json
```

```

{
  "mode": "DEVELOPMENT",
  "properties": {
    "ig_keystore_directory": "/path/to/ig/secrets",
    "oauth2_client_keystore_directory": "/path/to/client/secrets"
  },
  "connectors": [
    {
      "port": 8080
    },
    {
      "port": 8443,
      "tls": {
        "type": "ServerTlsOptions",
        "config": {
          "alpn": {
            "enabled": true
          },
          "clientAuth": "REQUEST",
          "keyManager": "SecretsKeyManager-1",
          "trustManager": "SecretsTrustManager-1"
        }
      }
    }
  ],
  "heap": [
    {
      "name": "SecretsPasswords",
      "type": "FileSystemSecretStore",
      "config": {
        "directory": "&{ig_keystore_directory}",
        "format": "PLAIN"
      }
    },
    {
      "name": "SecretsKeyManager-1",
      "type": "SecretsKeyManager",
      "config": {
        "signingSecretId": "key.manager.secret.id",
        "secretsProvider": "ServerIdentityStore"
      }
    },
    {
      "name": "SecretsTrustManager-1",
      "type": "SecretsTrustManager",
      "config": {
        "verificationSecretId": "trust.manager.secret.id",
        "secretsProvider": {
          "type": "KeyStoreSecretStore",
          "config": {
            "file": "&{oauth2_client_keystore_directory}/cacerts.p12",
            "storePasswordSecretId": "keystore.pass",
            "secretsProvider": "SecretsPasswords",
            "mappings": [
              {
                "secretId": "trust.manager.secret.id",
                "aliases": ["client-cert"]
              }
            ]
          }
        }
      }
    }
  ]
}

```

```

    }
  },
  {
    "name": "ServerIdentityStore",
    "type": "FileSystemSecretStore",
    "config": {
      "format": "PLAIN",
      "directory": "&{ig_keystore_directory}",
      "suffix": ".pem",
      "mappings": [{
        "secretId": "key.manager.secret.id",
        "format": {
          "type": "PemPropertyFormat"
        }
      }]
    }
  }
]
}

```

Source: [admin-mtls.json](#)

Notice the `ServerTlsOptions`:

- The trust manager settings let PingGateway trust the self-signed client certificate.
- The `"clientAuth": "REQUEST"` setting permits optional HTTPS mutual authentication.

Clients using mTLS authenticate with their certificates when setting up HTTPS. Other clients can connect over HTTPS without presenting a client certificate.

3. Replace the values of the secret directories with your directories, and then start PingGateway.

Make PingGateway an RS

1. Configure PingGateway as a resource server for mTLS:

1. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a `SystemAndEnvSecretStore`, and must be base64-encoded.

2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/mtls-certificate.json
```

Windows

```
%appdata%\OpenIG\config\routes\mtls-certificate.json
```

```

{
  "name": "mtls-certificate",
  "condition": "${find(request.uri.path, '/mtls-certificate')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "capture": "all",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [
              "test"
            ],
            "requireHttps": false,
            "accessTokenResolver": {
              "type": "ConfirmationKeyVerifierAccessTokenResolver",
              "config": {
                "delegate": {
                  "name": "token-resolver-1",
                  "type": "TokenIntrospectionAccessTokenResolver",
                  "config": {
                    "amService": "AmService-1",
                    "providerHandler": {
                      "type": "Chain",
                      "config": {
                        "filters": [
                          {
                            "type": "HttpBasicAuthenticationClientFilter",
                            "config": {
                              "username": "ig_agent",
                              "passwordSecretId": "agent.secret.id",
                              "secretsProvider": "SystemAndEnvSecretStore-1"
                            }
                          }
                        ],
                        "handler": "ForgeRockClientHandler"
                      }
                    }
                  }
                }
              }
            ]
          }
        }
      ]
    }
  }
}

```



```

    }
  }
}
],
"handler": {
  "name": "StaticResponseHandler-1",
  "type": "StaticResponseHandler",
  "config": {
    "status": 200,
    "headers": {
      "Content-Type": [ "text/plain; charset=UTF-8" ]
    },
    "entity": "mTLS\n Valid token: ${contexts.oauth2.accessToken.token}\n Confirmation keys: $
{contexts.oauth2}"
  }
}
}
}
}
}

```

Source: [mtls-certificate.json](#)

Notice the following features of the route:

- The route matches requests to `/mtls-certificate`.
- The `OAuth2ResourceServerFilter` uses the `ConfirmationKeyVerifierAccessTokenResolver` to validate the certificate thumbprint against the thumbprint from the resolved access token provided by AM.
The `ConfirmationKeyVerifierAccessTokenResolver` then delegates token resolution to the `TokenIntrospectionAccessTokenResolver`.
- The `providerHandler` adds an authorization header to the request, containing the username and password of the OAuth 2.0 client with the scope to examine (introspect) access tokens.
- The `OAuth2ResourceServerFilter` checks the resolved token has the required scopes and injects the token info into the context.
- The `StaticResponseHandler` returns the content of the access token from the context.

Try certificate-based mTLS

1. Get a certificate-bound access token from AM as the client application:

```
$ export ACCESS_TOKEN=$(curl \
--request POST \
--cacert $am_keystore_directory/openam-server.cert.pem \
--cert $oauth2_client_keystore_directory/client.cert.pem \
--key $oauth2_client_keystore_directory/client.key.pem \
--header 'cache-control: no-cache' \
--header 'content-type: application/x-www-form-urlencoded' \
--data 'client_id=client-application' \
--data 'grant_type=client_credentials' \
--data 'scope=test' \
https://am.example.com:8445/openam/oauth2/access_token | jq -r .access_token)
```

Notice the client gets an access token without using a client secret. It authenticates with its self-signed certificate.

2. Introspect the access token on AM using the PingGateway agent credentials:

```
$ curl \
--request POST \
--user ig_agent:password \
--header 'content-type: application/x-www-form-urlencoded' \
--data "token=$ACCESS_TOKEN" \
http://am.example.com:8088/openam/oauth2/realms/root/introspect | jq
```

Output

```
{
  "active": true,
  "scope": "test",
  "realm": "/",
  "client_id": "client-application",
  "user_id": "client-application",
  "username": "client-application",
  "token_type": "Bearer",
  "exp": 1724250516,
  "sub": "(age!client-application)",
  "iss": "http://am.example.com:8088/openam/oauth2",
  "subname": "client-application",
  "cnf": {
    "x5t#S256": "TTXH27YoFFCg0AQ0189KMBKeqxU1ZfZ_2nYGxrsjH1M"
  },
  "authGrantId": "JqckJ_KhDLDeb4cKRkeBJcXZZUE",
  "auditTrackingId": "962fd5f6-fc2f-43c1-b044-ed1eb33d7aef-429"
}
```

The `cnf` property indicates the value of the confirmation code:

- `x5`: X509 certificate
- `t`: thumbprint
- `#`: separator

- **S256** : algorithm used to hash the raw certificate bytes

3. Access the PingGateway route to validate the confirmation key with the `ConfirmationKeyVerifierAccessTokenResolver`:

```
$ curl \
--request POST \
--cacert $ig_keystore_directory/ig.example.com-certificate.pem \
--cert $oauth2_client_keystore_directory/client.cert.pem \
--key $oauth2_client_keystore_directory/client.key.pem \
--header "Authorization: Bearer ${ACCESS_TOKEN}" \
https://ig.example.com:8443/mtls-certificate
```

Output

```
mTLS
Valid token: <ACCESS_TOKEN>
Confirmation keys: { ... }
```

The command displays the validated token and confirmation keys.

mTLS with PingAM and trusted headers

PingGateway can validate the thumbprint of certificate-bound access tokens by reading the client certificate from a configured, trusted HTTP header.

Use this method when TLS is terminated at a reverse proxy or load balancer before PingGateway. PingGateway cannot authenticate the client through the TLS connection's client certificate because:

- If the connection is over TLS, the connection presents the certificate of the TLS termination point before PingGateway.
- If the connection is not over TLS, the connection presents no client certificate.



If the client is connected directly to PingGateway through a TLS connection, for which PingGateway is the TLS termination point, use the example in [mTLS with PingAM using client certificates](#).

Configure the proxy or load balancer to:

- Forward the encoded certificate to PingGateway in the trusted header. Encode the certificate in an HTTP-header compatible format that can convey a full certificate, so that PingGateway can rebuild the certificate.
- Strip the trusted header from incoming requests, and change the default header name to something an attacker can't guess.

Because there is a trust relationship between PingGateway and the TLS termination point, PingGateway doesn't authenticate the contents of the trusted header. PingGateway accepts any value in a header from a trusted TLS termination point.

The following image illustrates the connections and certificates required by the example:



Follow the steps in this example to try mTLS using trusted headers.

Before you start

1. Set up the keystores, truststores, AM, and PingGateway as described in [mTLS with PingAM using client certificates](#).
2. URL-encode the value of `$oauth2_client_keystore_directory/client.cert.pem`.

PingGateway needs the certificate to validate the confirmation key.

Make PingGateway an RS

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/mtls-header.json
```

Windows

```
%appdata%\OpenIG\config\routes\mtls-header.json
```

```

{
  "name": "mtls-header",
  "condition": "${find(request.uri.path, '/mtls-header')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "capture": "all",
    "config": {
      "filters": [
        {
          "name": "CertificateThumbprintFilter-1",
          "type": "CertificateThumbprintFilter",
          "config": {
            "certificate": "${pemCertificate(urlDecode(request.headers['x-ssl-cert'][0]))}",
            "failureHandler": {
              "type": "ScriptableHandler",
              "config": {
                "type": "application/x-groovy",
                "source": [
                  "def response = new Response(Status.TEAPOT);",
                  "response.entity = 'Failure in CertificateThumbprintFilter'",
                  "return response"
                ]
              }
            }
          }
        }
      ],
      {
        "name": "OAuth2ResourceServerFilter-1",
        "type": "OAuth2ResourceServerFilter",
        "config": {
          "scopes": [
            "test"
          ],
          "requireHttps": false,
          "accessTokenResolver": {
            "type": "ConfirmationKeyVerifierAccessTokenResolver",
            "config": {
              "delegate": {
                "name": "token-resolver-1",
                "type": "TokenIntrospectionAccessTokenResolver",
                "config": {
                  "amService": "AmService-1",

```

```

        "providerHandler": {
          "type": "Chain",
          "config": {
            "filters": [
              {
                "type": "HttpBasicAuthenticationClientFilter",
                "config": {
                  "username": "ig_agent",
                  "passwordSecretId": "agent.secret.id",
                  "secretsProvider": "SystemAndEnvSecretStore-1"
                }
              }
            ],
            "handler": "ForgeRockClientHandler"
          }
        },
        "handler": {
          "name": "StaticResponseHandler-1",
          "type": "StaticResponseHandler",
          "config": {
            "status": 200,
            "headers": {
              "Content-Type": [ "text/plain; charset=UTF-8" ]
            },
            "entity": "mTLS\n Valid token: ${contexts.oauth2.accessToken.token}\n Confirmation keys: ${contexts.oauth2}"
          }
        }
      }
    }
  }
}

```

Source: [mtls-header.json](#)

Notice the following features of the route compared to `mtls-certificate.json`:

- The route matches requests to `/mtls-header`.
- The `CertificateThumbprintFilter` extracts the client certificate from the trusted header.

In this example, the filter is configured as if NGINX were sending the trusted header. Find additional examples in the [CertificateThumbprintFilter reference](#).

The filter computes the certificate thumbprint and makes the thumbprint available to the `ConfirmationKeyVerifierAccessTokenResolver`.

Try mTLS with trusted headers

1. Get a certificate-bound access token from AM as the client application:

```
$ export ACCESS_TOKEN=$(curl \
--request POST \
--cacert $am_keystore_directory/openam-server.cert.pem \
--cert $oauth2_client_keystore_directory/client.cert.pem \
--key $oauth2_client_keystore_directory/client.key.pem \
--header 'cache-control: no-cache' \
--header 'content-type: application/x-www-form-urlencoded' \
--data 'client_id=client-application' \
--data 'grant_type=client_credentials' \
--data 'scope=test' \
https://am.example.com:8445/openam/oauth2/access_token | jq -r .access_token)
```

Notice the client gets an access token without using a client secret. It authenticates with its self-signed certificate.

2. Introspect the access token on AM using the PingGateway agent credentials:

```
$ curl \
--request POST \
--user ig_agent:password \
--header 'content-type: application/x-www-form-urlencoded' \
--data "token=$ACCESS_TOKEN" \
http://am.example.com:8088/openam/oauth2/realms/root/introspect | jq
```

Output

```
{
  "active": true,
  "scope": "test",
  "realm": "/",
  "client_id": "client-application",
  "user_id": "client-application",
  "username": "client-application",
  "token_type": "Bearer",
  "exp": 1724249775,
  "sub": "(age!client-application)",
  "iss": "http://am.example.com:8088/openam/oauth2",
  "subname": "client-application",
  "cnf": {
    "x5t#S256": "TTXH27YoFFCg0AQ0189KMBKexU1ZfZ_2nYGxrsjH1M",
  },
  "authGrantId": "LMhPEqYaxMbrd2zXMAQjHcc8JYE",
  "auditTrackingId": "962fd5f6-fc2f-43c1-b044-ed1eb33d7aef-403"
}
```

The `cnf` property indicates the value of the confirmation code:

- `x5`: X509 certificate
- `t`: thumbprint
- `#`: separator

- **S256** : algorithm used to hash the raw certificate bytes

3. Access the PingGateway route to validate the confirmation key.

The `<url-encoded-cert>` is the URL-encoded value of `$oauth2_client_keystore_directory/client.cert.pem`:

```
$ curl \
--request POST \
--cacert $ig_keystore_directory/ig.example.com-certificate.pem \
--header "Authorization: Bearer $ACCESS_TOKEN" \
--header 'x-ssl-cert: <url-encoded-cert>'
https://ig.example.com:8443/mtls-header
```

Output

```
mTLS
Valid token: UnUxGRuwXx_ugUCvNKFM3GJo3Cc
Confirmation keys: { ... }
```

The command displays the validated token and confirmation keys.

OAuth 2.0 context for authentication with PingAM

This section contains an example route that retrieves scopes from a token introspection, assigns them as the PingGateway session username and password, and uses them to log the user directly in to the sample application.

For information about the context, refer to [OAuth2Context](#).

Before you start, set up and test the example in [Validating PingAM access tokens with introspection](#).

1. Set up AM:

1. Select  **Identities**, and change the email address of the demo user to `demo`.
2. Select  **Scripts** > **OAuth2 Access Token Modification Script**, and replace the default script as follows:

```
import org.forgerock.http.protocol.Request
import org.forgerock.http.protocol.Response
import com.iplanet.sso.SSOException
import groovy.json.JsonSlurper

def attributes = identity.getAttributes(["mail"]).toSet()
accessToken.setField("mail", attributes["mail"][0])
accessToken.setField("password", "Ch4ng31t")
```

The AM script adds user profile information to the access token, and adds a `password` field with the value `Ch4ng31t`.

**Warning**

Don't use this example in production. If the token is stateless and unencrypted, the password value is easily accessible when you have the token.

2. Set up PingGateway:**1. Add the following route to PingGateway:*****Linux***

```
$HOME/.openig/config/routes/rs-pwreplay.json
```

Windows

```
%appdata%\OpenIG\config\routes\rs-pwreplay.json
```

```

{
  "name" : "rs-pwreplay",
  "baseURI" : "http://app.example.com:8081",
  "condition" : "${find(request.uri.path, '^/rs-pwreplay')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler" : {
    "type" : "Chain",
    "config" : {
      "filters" : [
        {
          "name" : "OAuth2ResourceServerFilter-1",
          "type" : "OAuth2ResourceServerFilter",
          "config" : {
            "scopes" : [ "mail", "employeenumber" ],
            "requireHttps" : false,
            "accessTokenResolver": {
              "name": "TokenIntrospectionAccessTokenResolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "amService": "AmService-1",
                "providerHandler": {
                  "type": "Chain",
                  "config": {
                    "filters": [
                      {
                        "type": "HttpBasicAuthenticationClientFilter",
                        "config": {
                          "username": "ig_agent",
                          "passwordSecretId": "agent.secret.id",
                          "secretsProvider": "SystemAndEnvSecretStore-1"
                        }
                      }
                    ],
                    "handler": "ForgeRockClientHandler"
                  }
                }
              }
            }
          }
        }
      ]
    }
  },
  {
    "type": "AssignmentFilter",
    "config": {

```

```

      "onRequest": [{
        "target": "${session.username}",
        "value": "${contexts.oauth2.accessToken.info.mail}"
      },
      {
        "target": "${session.password}",
        "value": "${contexts.oauth2.accessToken.info.password}"
      }
    ]
  },
  {
    "type": "StaticRequestFilter",
    "config": {
      "method": "POST",
      "uri": "http://app.example.com:8081/login",
      "form": {
        "username": [
          "${session.username}"
        ],
        "password": [
          "${session.password}"
        ]
      }
    }
  }
],
"handler": "ReverseProxyHandler"
}
}
}

```

Source: [rs-pwreplay.json](#)

Notice the following features of the route compared to `rs-introspect.json`:

- The route matches requests to `/rs-pwreplay`.
- The AssignmentFilter accesses the context, and injects the username and password into the SessionContext, `${Session}`.
- The StaticRequestFilter retrieves the username and password from `session`, and replaces the original HTTP GET request with an HTTP POST login request that contains the credentials to authenticate.

3. Test the setup:

1. In a terminal window, use a `curl` command similar to the following to retrieve an access token:

```

$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail%20employeeenumber" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")

```

2. Validate the access token returned in the previous step:

```
$ curl -v \  
--cacert /path/to/secrets/ig.example.com-certificate.pem \  
--header "Authorization: Bearer ${mytoken}" \  
https://ig.example.com:8443/rs-pwreplay
```

HTML for the sample application is displayed.

Caching PingAM access tokens

This section builds on the example in [Validating PingAM access tokens with introspection](#) to cache and then revoke access tokens.

When the access token **is not** cached, PingGateway calls AM to validate the access token. When the access token **is** cached, PingGateway doesn't validate the access token with AM.

When an access token is revoked on AM, the CacheAccessTokenResolver can delete the token from the cache when both of the following conditions are true:

- The `notification` property of AmService is enabled.
- The delegate AccessTokenResolver provides the token metadata required to update the cache.

When a refresh_token is revoked on AM, all associated access tokens are automatically and immediately revoked.

Before you start, set up and test the example in [Validating PingAM access tokens with introspection](#).

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/rs-introspect-cache.json
```

Windows

```
%appdata%\OpenIG\config\routes\rs-introspect-cache.json
```

```

{
  "name": "rs-introspect-cache",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/rs-introspect-cache$')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "http://am.example.com:8088/openam",
        "realm": "/",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [
              "mail",
              "employeenumber"
            ],
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "CacheAccessTokenResolver-1",
              "type": "CacheAccessTokenResolver",
              "config": {
                "enabled": true,
                "defaultTimeout": "1 hour",
                "maximumTimeToCache": "1 day",
                "amService": "AmService-1",
                "delegate": {
                  "name": "TokenIntrospectionAccessTokenResolver-1",
                  "type": "TokenIntrospectionAccessTokenResolver",
                  "config": {
                    "amService": "AmService-1",
                    "providerHandler": {
                      "type": "Chain",
                      "config": {
                        "filters": [
                          {
                            "type": "HttpBasicAuthenticationClientFilter",
                            "config": {
                              "username": "ig_agent",
                              "passwordSecretId": "agent.secret.id",
                              "secretsProvider": "SystemAndEnvSecretStore-1"
                            }
                          }
                        ]
                      }
                    }
                  }
                }
              }
            }
          }
        }
      ]
    }
  }
}

```

```

    },
    ],
    "handler": {
      "type": "Delegate",
      "capture": "all",
      "config": {
        "delegate": "ForgeRockClientHandler"
      }
    }
  }
}
}
}
}
}
}
},
],
"handler": {
  "type": "StaticResponseHandler",
  "config": {
    "status": 200,
    "headers": {
      "Content-Type": [ "text/html; charset=UTF-8" ]
    },
    "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></html>"
  }
}
}
}
}
}
```

Source: [rs-introspect-cache.json](#) 

Notice the following features of the route compared to `rs-introspect.json`, in [Validating PingAM access tokens with introspection](#):

- The `OAuth2ResourceServerFilter` uses a `CacheAccessTokenResolver` to cache the access token, and then delegate token resolution to the `TokenIntrospectionAccessTokenResolver`.
- The `amService` property in `CacheAccessTokenResolver` enables WebSocket notifications from AM, for events such as token revocation.
- The `TokenIntrospectionAccessTokenResolver` uses a `ForgeRockClientHandler` and a capture decorator to capture `PingGateway`'s interactions with AM.

2. Test token caching:

1. In a terminal window, use a `curl` command similar to the following to retrieve an access token:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail%20employeeenumber" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

2. Access the route, using the access token returned in the previous step:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/rs-introspect-cache
```

Output

```
{
  active = true,
  scope = employeeemail mail,
  client_id = client-application,
  user_id = {amDemoUn},
  token_type = Bearer,
  exp = 158...907,
  ...
}
```

3. In the route log, note that PingGateway calls AM to introspect the access token:

```
POST http://am.example.com:8088/openam/oauth2/realms/root/introspect HTTP/1.1
```

4. Access the route again. In the route log note that this time PingGateway doesn't call AM, because the token is cached.
5. Disable the cache and repeat the previous steps to cause PingGateway to call AM to validate the access token for each request.

3. Test token revocation:

1. In a terminal window, use a `curl` command similar to the following to revoke the access token obtained in the previous step:

```
$ curl --request POST \
--data "token=${mytoken}" \
--data "client_id=client-application" \
--data "client_secret=password" \
"http://am.example.com:8088/openam/oauth2/realms/root/token/revoke"
```

2. Access the route using the access token and note that the request isn't authorized because the token is revoked:


```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/rs-introspect-cache
```


Output

```
...
HTTP/1.1 401 Unauthorized
```

Client credentials grant with PingAM

This example shows how a client service accesses an OAuth 2.0-protected resource by using its OAuth 2.0 client credentials.



1. Set up the AM as an Authorization Server:

1. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`
- **Token Introspection:** `Realm Only`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

2. Create an OAuth 2.0 Authorization Server:

1. Select **Services > Add a Service > OAuth2 Provider**.
2. Add a service with the default values.

3. Create an OAuth 2.0 client to request access tokens, using client credentials for authentication:

1. Select **Applications** > **OAuth 2.0** > **Clients**, and add a client with the following values:

- **Client ID** : `client-service`
- **Client secret** : `password`
- **Scope(s)** : `client-scope`

2. (Optional) On the **Core** tab, switch to using a client secret associated with a secret label by setting a **Secret Label Identifier** and mapping the label to a secret.

To learn more, read [Create a client profile](#) and [Map and rotate secrets](#) in the AM documentation.

3. On the **Advanced** tab, select the following value:

- **Grant Types** : `Client Credentials`

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).

2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/oauth2-protected-resource.json
```

Windows

```
%appdata%\OpenIG\config\routes\oauth2-protected-resource.json
```

```

{
  "name": "oauth2-protected-resource",
  "condition": "${find(request.uri.path, '^/oauth2-protected-resource')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [ "client-scope" ],
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "TokenIntrospectionAccessTokenResolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "amService": "AmService-1",
                "providerHandler": {
                  "type": "Chain",
                  "config": {
                    "filters": [
                      {
                        "type": "HttpBasicAuthenticationClientFilter",
                        "config": {
                          "username": "ig_agent",
                          "passwordSecretId": "agent.secret.id",
                          "secretsProvider": "SystemAndEnvSecretStore-1"
                        }
                      }
                    ],
                    "handler": "ForgeRockClientHandler"
                  }
                }
              }
            }
          }
        }
      ]
    }
  },
  "handler": {
    "type": "StaticResponseHandler",
    "config": {

```

```

        "status": 200,
        "headers": {
          "Content-Type": [ "text/html; charset=UTF-8" ]
        },
        "entity": "<html><body><h2>Access Granted</h2></body></html>"
      }
    }
  }
}

```

Source: [oauth2-protected-resource.json](#)

Notice the following features of the route:

- The route matches requests to `/oauth2-protected-resource`.
- The `OAuth2ResourceServerFilter` expects an OAuth 2.0 access token in the header of the incoming request, with the scope `client-scope`.
- The filter uses a `TokenIntrospectionAccessTokenResolver` to resolve the access token. The introspect endpoint is protected with HTTP Basic Authentication, and the `providerHandler` uses an `HttpBasicAuthenticationClientFilter` to provide the resource server credentials.
- For convenience in this test, `"requireHttps"` is false. In production environments, set it to true.
- After the filter successfully validates the access token, it creates a new context from the Authorization Server response, containing information about the access token.
- The `StaticResponseHandler` returns a message that access is granted.

4. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/client-credentials.json
```

Windows

```
%appdata%\OpenIG\config\routes\client-credentials.json
```

```

{
  "name": "client-credentials",
  "baseURI": "http://ig.example.com:8080",
  "condition": "${find(request.uri.path, '^/client-credentials')}",
  "heap": [ {
    "name": "clientSecretAccessTokenExchangeHandler",
    "type": "Chain",
    "capture": "all",
    "config": {
      "filters": [ {
        "type": "ClientSecretBasicAuthenticationFilter",
        "config": {
          "clientId": "client-service",
          "clientSecretId": "client.secret.id",
          "secretsProvider": {
            "type": "Base64EncodedSecretStore",
            "config": {
              "secrets": {
                "client.secret.id": "cGFZc3dvcmQ="
              }
            }
          }
        }
      ]
    },
    "handler": "ForgeRockClientHandler"
  } ], {
    "name": "oauth2EnabledClientHandler",
    "type": "Chain",
    "capture": "all",
    "config": {
      "filters": [ {
        "type": "ClientCredentialsOAuth2ClientFilter",
        "config": {
          "tokenEndpoint": "http://am.example.com:8088/openam/oauth2/access_token",
          "endpointHandler": "clientSecretAccessTokenExchangeHandler",
          "scopes": [ "client-scope" ]
        }
      ]
    },
    "handler": "ForgeRockClientHandler"
  } ],
  "handler": {
    "type": "ScriptableHandler",
    "config": {
      "type": "application/x-groovy",
      "clientHandler": "oauth2EnabledClientHandler",
      "source": [ "request.uri.path = '/oauth2-protected-resource'", "return http.send(context, request);" ]
    }
  }
}

```

Source: [client-credentials.json](#)

Note the following features of the route:

- The route matches requests to `/client-credentials`.

- The ScriptableHandler rewrites the request to target the `/oauth2-protected-resource` endpoint and then calls the HTTP client that has been redefined to use the `oauth2EnabledClientHandler`.
- The `oauth2EnabledClientHandler` calls the `ClientCredentialsOAuth2ClientFilter` to obtain an access token from AM.
- The `ClientCredentialsOAuth2ClientFilter` calls the `clientSecretAccessTokenExchangeHandler` to exchange tokens on the authorization endpoint.
- The `clientSecretAccessTokenExchangeHandler` calls a `ClientSecretBasicAuthenticationFilter` to authenticate the client through the HTTP basic access authentication scheme, and a `ForgeRockClientHandler` to propagate the request.
- The route `oauth2-protected-resource.json` uses the AM introspection endpoint to resolve the access token and display its contents.


3. Test the setup:

1. In your browser's privacy or incognito mode, go to to <https://ig.example.com:8443/client-credentials>.
2. If you see warnings that the site isn't secure, respond to the warnings to access the site.

A message shows that access is granted.

Resource owner password credentials grant with PingAM

This example shows how a client service accesses an OAuth 2.0-protected resource by using resource owner password credentials.



 Important

This procedure uses the *Resource Owner Password Credentials* grant type. As suggested in [The OAuth 2.0 Authorization Framework](#), use other grant types whenever possible.

1. Set up the AM as an Authorization Server:

1. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`
- **Token Introspection:** `Realm Only`

 Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

2. Create an OAuth 2.0 Authorization Server:

1. Select **Services > Add a Service > OAuth2 Provider**.

2. Add a service with the default values.

3. Create an OAuth 2.0 client to request access tokens, using the resource owner's password for authentication:

1. Select **Applications > OAuth 2.0 > Clients**, and add a client with the following values:

- **Client ID:** `resource-owner-client`
- **Client secret:** `password`
- **Scope(s):** `client-scope`

2. (Optional) On the **Core** tab, switch to using a client secret associated with a secret label by setting a **Secret Label Identifier** and mapping the label to a secret.

To learn more, read [Create a client profile](#) and [Map and rotate secrets](#) in the AM documentation.

3. On the **Advanced** tab, select the following value:

- **Grant Types:** `Resource Owner Password Credentials`

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).

2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/oauth2-protected-resource.json
```

Windows

```
%appdata%\OpenIG\config\routes\oauth2-protected-resource.json
```



```

{
  "name": "oauth2-protected-resource",
  "condition": "${find(request.uri.path, '^/oauth2-protected-resource')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [ "client-scope" ],
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "TokenIntrospectionAccessTokenResolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "amService": "AmService-1",
                "providerHandler": {
                  "type": "Chain",
                  "config": {
                    "filters": [
                      {
                        "type": "HttpBasicAuthenticationClientFilter",
                        "config": {
                          "username": "ig_agent",
                          "passwordSecretId": "agent.secret.id",
                          "secretsProvider": "SystemAndEnvSecretStore-1"
                        }
                      }
                    ]
                  }
                }
              }
            },
            "handler": "ForgeRockClientHandler"
          }
        }
      ]
    }
  },
  "handler": {
    "type": "StaticResponseHandler",
    "config": {

```

```

        "status": 200,
        "headers": {
            "Content-Type": [ "text/html; charset=UTF-8" ]
        },
        "entity": "<html><body><h2>Access Granted</h2></body></html>"
    }
}
}
}
}
}

```

Source: [oauth2-protected-resource.json](#)

Notice the following features of the route:

- The route matches requests to `/oauth2-protected-resource`.
- The `OAuth2ResourceServerFilter` expects an OAuth 2.0 access token in the header of the incoming request, with the scope `client-scope`.
- The filter uses a `TokenIntrospectionAccessTokenResolver` to resolve the access token. The introspect endpoint is protected with HTTP Basic Authentication, and the `providerHandler` uses an `HttpBasicAuthenticationClientFilter` to provide the resource server credentials.
- For convenience in this test, `"requireHttps"` is false. In production environments, set it to true.
- After the filter successfully validates the access token, it creates a new context from the Authorization Server response, containing information about the access token.
- The `StaticResponseHandler` returns a message that access is granted.

4. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/resource-owner.json
```

Windows

```
%appdata%\OpenIG\config\routes\resource-owner.json
```

```

{
  "name": "resource-owner",
  "baseURI": "http://ig.example.com:8080",
  "condition": "${find(request.uri.path, '^/resource-owner')}",
  "heap": [ {
    "name": "clientSecretAccessTokenExchangeHandler",
    "type": "Chain",
    "capture": "all",
    "config": {
      "filters": [ {
        "type": "ClientSecretBasicAuthenticationFilter",
        "config": {
          "clientId": "resource-owner-client",
          "clientSecretId": "client.secret.id",
          "secretsProvider": {
            "type": "Base64EncodedSecretStore",
            "config": {
              "secrets": {
                "client.secret.id": "cGFzc3dvcmQ="
              }
            }
          }
        }
      }
    ],
    "handler": "ForgeRockClientHandler"
  }
], {
  "name": "oauth2EnabledClientHandler",
  "type": "Chain",
  "capture": "all",
  "config": {
    "filters": [ {
      "type": "ResourceOwnerOAuth2ClientFilter",
      "config": {
        "tokenEndpoint": "http://am.example.com:8088/openam/oauth2/access_token",
        "endpointHandler": "clientSecretAccessTokenExchangeHandler",
        "scopes": [ "client-scope" ],
        "username": "demo",
        "passwordSecretId": "user.password.secret.id",
        "secretsProvider": {
          "type": "Base64EncodedSecretStore",
          "config": {
            "secrets": {
              "user.password.secret.id": "Q2g0bmczMlRQ="
            }
          }
        }
      }
    }
  ],
  "handler": "ForgeRockClientHandler"
}
], {
  "handler": {
    "type": "ScriptableHandler",
    "config": {
      "type": "application/x-groovy",
      "clientHandler": "oauth2EnabledClientHandler",

```

```

        "source" : [ "request.uri.path = '/oauth2-protected-resource'", "return http.send(context,
request);" ]
    }
  }
}

```

Source: [resource-owner.json](#)

Note the following features of the route:

- The route matches requests to `/resource-owner`.
- The ScriptableHandler rewrites the request to target it to `/oauth2-protected-resource`, and then calls the HTTP client, that has been redefined to use the `oauth2EnabledClientHandler`.
- The `oauth2EnabledClientHandler` calls the `ResourceOwnerOAuth2ClientFilter` to obtain an access token from AM.
- The `ResourceOwnerOAuth2ClientFilter` calls the `clientSecretAccessTokenExchangeHandler` to exchange tokens on the authorization endpoint. The demo user authenticates with their username and password.
- The `clientSecretAccessTokenExchangeHandler` calls a `ClientSecretBasicAuthenticationFilter` to authenticate the client through the HTTP basic access authentication scheme, and a `ForgeRockClientHandler` to propagate the request.
- The route `oauth2-protected-resource.json` uses the AM introspection endpoint to resolve the access token and display its contents.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to to <https://ig.example.com:8443/resource-owner>.
2. If you see warnings that the site isn't secure, respond to the warnings to access the site.

A message shows that access is granted.

OpenID Connect and PingAM

The following pages provide an overview of how PingGateway supports [OpenID Connect 1.0 \(OIDC\)](#), an authentication layer built on OAuth 2.0. The pages show how to set up PingGateway as an OIDC relying party in different deployment scenarios.

About PingGateway with OIDC

PingGateway supports OIDC deployments where the identity provider holds the protected resource third-party applications want to access.

OIDC specifications refer to the following entities:

- *End user*: An OAuth 2.0 resource owner whose user information the application needs to access.

The end user wants to use an application through an existing identity provider account without signing up and creating credentials for another web service.

- *Relying Party* (RP): An OAuth 2.0 client that needs access to the end user's protected user information.

For example, an online mail application needs to know which end user is accessing the application to present the correct inbox.

As another example, an online shopping site needs to know which end user is accessing the site to present the right offerings, account, and shopping cart.

- *OpenID Provider* (OP): An OAuth 2.0 Authorization Server and resource server that holds the user information and grants access.

The OP requires the end user to give the RP permission to access to some of its user information. Because OIDC defines unique identification for an account (subject identifier + issuer identifier), the RP can use that identification to bind its own user profile to a remote identity.

For the online mail application, this key could be used to access the mailboxes and related account information. For the online shopping site, this key could be used to access the offerings, account, shopping cart and others. The key makes it possible to serve users as if they had local accounts.

- *UserInfo*: The protected resource that the third-party application wants to access. The information about the authenticated end user is expressed in a standard format. The user-info endpoint is hosted on the Authorization Server and is protected with OAuth 2.0.

When PingGateway acts as an RP, its role is to retrieve user information from the OP and to inject the information into the context for use by later filters and handlers.


Next steps

- [AM as OIDC provider](#)
- [PingOne Advanced Identity Cloud as OIDC provider](#)
- [PingGateway with PingOne as an OIDC provider](#)
- [Multiple OIDC providers using PingAM and PingOne Advanced Identity Cloud](#)
- [Discovery and dynamic registration with PingAM](#)
- [ID token validation with PingAM](#)

AM as OIDC provider

This page gives an example of how to set up AM as an OIDC provider and PingGateway as a relying party for browser requests to the home page of the sample application.

The following sequence diagram shows the flow of information for a request to access the home page of the sample application. AM is the single, preregistered OIDC provider and PingGateway is the relying party:



Before you begin, prepare AM, PingGateway, and the sample application. Learn more in the [example installation for this guide](#).

1. Set up AM as an OIDC provider:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

2. Create an OAuth 2.0 Authorization Server:

1. Select **Services > Add a Service > OAuth2 Provider**.
2. Add a service with the default values.

3. Create an OAuth 2.0 Client to request OAuth 2.0 access tokens:

1. Select **Applications > OAuth 2.0 > Clients**.
2. Add a client with the following values:

- **Client ID:** `oidc_client`
- **Client secret:** `password`
- **Redirection URIs:** `https://ig.example.com:8443/home/id_token/callback`

■ **Scope(s):** openid, profile, and email

3. (Optional) On the **Core** tab, switch to using a client secret associated with a secret label by setting a **Secret Label Identifier** and mapping the label to a secret.

To learn more, read [Create a client profile](#) and [Map and rotate secrets](#) in the AM documentation.

4. On the **Advanced** tab, select the following values:

■ **Grant Types:** Authorization Code

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).

2. Set an environment variable for `oidc_client`, and then restart PingGateway:

```
$ export OIDC_SECRET_ID='cGFzc3dvcmQ='
```

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

4. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/07-openid.json
```

Windows

```
%appdata%\OpenIG\config\routes\07-openid.json
```

```

{
  "name": "07-openid",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/id_token')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AuthenticatedRegistrationHandler-1",
      "type": "Chain",
      "config": {
        "filters": [
          {
            "name": "ClientSecretBasicAuthenticationFilter-1",
            "type": "ClientSecretBasicAuthenticationFilter",
            "config": {
              "clientId": "oidc_client",
              "clientSecretId": "oidc.secret.id",
              "secretsProvider": "SystemAndEnvSecretStore-1"
            }
          }
        ],
        "handler": "ForgeRockClientHandler"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "AuthorizationCodeOAuth2ClientFilter-1",
          "type": "AuthorizationCodeOAuth2ClientFilter",
          "config": {
            "clientEndpoint": "/home/id_token",
            "failureHandler": {
              "type": "StaticResponseHandler",
              "config": {
                "status": 500,
                "headers": {
                  "Content-Type": [
                    "text/plain"
                  ]
                }
              },
              "entity": "Error in OAuth 2.0 setup."
            }
          }
        }
      ],
      "registrations": [
        {
          "name": "oidc-user-info-client",
          "type": "ClientRegistration",
          "config": {
            "clientId": "oidc_client",
            "issuer": {
              "name": "Issuer",
              "type": "Issuer",
              "config": {
                "wellKnownEndpoint": "http://am.example.com:8088/openam/oauth2/.well-known/"
              }
            }
          }
        }
      ]
    }
  }
}

```



```

openid-configuration"
    }
  },
  "scopes": [
    "openid",
    "profile",
    "email"
  ],
  "authenticatedRegistrationHandler": "AuthenticatedRegistrationHandler-1"
}
},
],
"requireHttps": false,
"cacheExpiration": "disabled"
}
},
],
"handler": "ReverseProxyHandler"
}
}
}

```

Source: [07-openid.json](#)

Learn how to use Studio to set up the PingGateway route in [OpenID Connect in Structured Editor](#).

Notice the following features about the route:

- The route matches requests to `/home/id_token`.
- The `AuthorizationCodeOAuth2ClientFilter` enables PingGateway to act as a relying party. It uses a single client registration defined inline.
- The filter has a base client endpoint of `/home/id_token`, which creates the following service URIs:
 - Requests to `/home/id_token/login` start the delegated authorization process.
 - Requests to `/home/id_token/callback` are expected as redirects from the OAuth 2.0 Authorization Server (OIDC provider). This is why the redirect URI in the client profile in AM is set to `https://ig.example.com:8443/home/id_token/callback`.
 - Requests to `/home/id_token/logout` remove the authorization state for the end user, and redirect to the specified URL if a `goto` parameter is provided.

These endpoints are implicitly reserved. Attempts to access them directly can cause undefined errors.
- For convenience in this test, `"requireHttps"` is false. In production environments, set it to true. So that you see the delegated authorization process when you make a request, `"requireLogin"` has the default value `true`.
- The target for storing authorization state information is `${attributes.openid}`. This is where subsequent filters and handlers can find access tokens and user information.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to https://ig.example.com:8443/home/id_token.

The AM login page is displayed.

2. Log in to AM as user `demo`, password `Ch4ng31t`, and then allow the application to access user information.

The home page of the sample application is displayed.

Authenticate automatically to the sample application

To authenticate automatically to the sample application, change the last name of the user `demo` to match the password `Ch4ng31t`, and add a `StaticRequestFilter` like the following to the end of the chain in `07-openid.json`:

```
{
  "type": "StaticRequestFilter",
  "config": {
    "method": "POST",
    "uri": "http://app.example.com:8081/login",
    "form": {
      "username": [
        "${attributes.openid.user_info.sub}"
      ],
      "password": [
        "${attributes.openid.user_info.family_name}"
      ]
    }
  }
}
```

The `StaticRequestFilter` retrieves the username and password from the context, and replaces the original HTTP GET request with an HTTP POST login request containing credentials.

Multiple OIDC providers using PingAM and PingOne Advanced Identity Cloud

This page shows OIDC with two identity providers.

Client registrations for an AM identity provider and PingOne Advanced Identity Cloud identity provider are declared in the heap. The Nascar page helps the user to choose an identity provider.

1. Set up AM as the first identity provider, as described in [AM as OIDC provider](#).
2. Set up PingOne Advanced Identity Cloud as a second identity provider, as described in [OpenID Connect and PingOne Advanced Identity Cloud](#).
3. Add the following route to PingGateway, replacing the value for the property `amInstanceUrl`:

Linux

```
$HOME/.openig/config/routes/07-openid-nascar.json
```

Windows

```
%appdata%\OpenIG\config\routes\07-openid-nascar.json
```

```

{
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AuthenticatedRegistrationHandler-1",
      "type": "Chain",
      "config": {
        "filters": [
          {
            "name": "ClientSecretBasicAuthenticationFilter-1",
            "type": "ClientSecretBasicAuthenticationFilter",
            "config": {
              "clientId": "oidc_client",
              "clientSecretId": "oidc.secret.id",
              "secretsProvider": "SystemAndEnvSecretStore-1"
            }
          }
        ],
        "handler": "ForgeRockClientHandler"
      }
    },
    {
      "name": "openam",
      "type": "ClientRegistration",
      "config": {
        "clientId": "oidc_client",
        "issuer": {
          "name": "am_issuer",
          "type": "Issuer",
          "config": {
            "wellKnownEndpoint": "http://am.example.com:8088/openam/oauth2/.well-known/openid-configuration"
          }
        },
        "scopes": [
          "openid",
          "profile",
          "email"
        ],
        "authenticatedRegistrationHandler": "AuthenticatedRegistrationHandler-1"
      }
    },
    {
      "name": "idcloud",
      "type": "ClientRegistration",
      "config": {
        "clientId": "oidc_client",
        "issuer": {
          "name": "idc_issuer",
          "type": "Issuer",
          "config": {
            "wellKnownEndpoint": "&{amInstanceUrl}/oauth2/realms/alpha/.well-known/openid-configuration"
          }
        },
        "scopes": [
          "openid",
          "profile",
          "email"
        ]
      }
    }
  ]
}

```

```

    ],
    "authenticatedRegistrationHandler": "AuthenticatedRegistrationHandler-1"
  }
},
{
  "name": "NascarPage",
  "type": "StaticResponseHandler",
  "config": {
    "status": 200,
    "headers": {
      "Content-Type": [ "text/html; charset=UTF-8" ]
    },
    "entity": [
      "<html>",
      "  <body>",
      "    <p><a href='/home/id_token/login?registration=oidc_client&issuer=am_issuer&goto=${urlEncodeQueryParameterNameOrValue('https://ig.example.com:8443/home/id_token')}'>Access Management login</a></p>",
      "    <p><a href='/home/id_token/login?registration=oidc_client&issuer=idc_issuer&goto=${urlEncodeQueryParameterNameOrValue('https://ig.example.com:8443/home/id_token')}'>Identity Cloud login</a></p>",
      "  </body>",
      "</html>"
    ]
  }
}
],
"name": "07-openid-nascar",
"baseURI": "http://app.example.com:8081",
"condition": "${find(request.uri.path, '^/home/id_token')}",
"properties": {
  "amInstanceUrl": "https://myTenant.forgeblocks.com/am"
},
"handler": {
  "type": "Chain",
  "config": {
    "filters": [
      {
        "type": "AuthorizationCode0Auth2ClientFilter",
        "config": {
          "clientEndpoint": "/home/id_token",
          "failureHandler": {
            "type": "StaticResponseHandler",
            "config": {
              "comment": "Trivial failure handler for debugging only",
              "status": 500,
              "headers": {
                "Content-Type": [ "text/plain; charset=UTF-8" ]
              },
              "entity": "${contexts.oauth2Failure.error}: ${contexts.oauth2Failure.description}"
            }
          },
          "loginHandler": "NascarPage",
          "registrations": [ "openam", "idcloud" ],
          "requireHttps": false,
          "cacheExpiration": "disabled"
        }
      }
    ]
  }
}

```

```
    ],
    "handler": "ReverseProxyHandler"
  }
}
```

Source: [07-openid-nascar.json](#)

Consider the differences with `07-openid.json`:

- The heap objects `openam` and `idcloud` define client registrations.
- The `StaticResponseHandler` provides links to the client registrations.
- The `AuthorizationCodeOAuth2ClientFilter` uses a `loginHandler` to allow users to choose a client registration and therefore an identity provider.

4. Test the setup:

1. In your browser's privacy or incognito mode, go to https://ig.example.com:8443/home/id_token.

The Nascar page offers the choice of identity provider.

2. Using the following credentials, select a provider, log in, and allow the application to access user information:

- AM: user `demo`, password `Ch4ng3!t`.
- PingOne Advanced Identity Cloud: user `demo`, password `Ch4ng3!t`

The home page of the sample application is displayed.

Discovery and dynamic registration with PingAM

OIDC defines mechanisms for discovering and dynamically registering with an identity provider that isn't known in advance, as specified in the following publications: [OpenID Connect Discovery](#), [OpenID Connect Dynamic Client Registration](#), and [OAuth 2.0 Dynamic Client Registration Protocol](#).

In dynamic registration, issuer and client registrations are generated dynamically. They are held in memory and can be reused, but don't persist when PingGateway is restarted.

This section builds on the example in [AM as OIDC provider](#) to give an example of discovering and dynamically registering with an identity provider that isn't known in advance. In this example, the client sends a signed JWT to the Authorization Server.

To facilitate the example, a WebFinger service is embedded in the sample application. In a normal deployment, the WebFinger server is likely to be a service on the issuer's domain.

1. Set up a key

1. Locate a directory for secrets and go to it:

```
$ cd /path/to/secrets
```

2. Create a key:

```
$ keytool -genkey \
  -alias myprivatekeyalias \
  -keyalg RSA \
  -keysize 2048 \
  -keystore keystore.p12 \
  -storepass keystore \
  -storetype PKCS12 \
  -keypass keystore \
  -validity 360 \
  -dname "CN=ig.example.com, OU=example, O=com, L=fr, ST=fr, C=fr"
```

2. Set up AM:

1. Set up AM as described in [AM as OIDC provider](#).
2. Select the user `demo`, and change the last name to `Ch4ng31t`. For this example, the last name must be the same as the password.
3. Configure the OAuth 2.0 Authorization Server for dynamic registration:
 1. Select **Services > OAuth2 Provider**.
 2. On the **Advanced** tab, add the following scopes to **Client Registration Scope Allowlist**: `openid`, `profile`, `email`.
 3. On the **Client Dynamic Registration** tab, select these settings:
 - **Allow Open Dynamic Client Registration**: Enabled
 - **Generate Registration Access Tokens**: Disabled
4. Configure the authentication method for the OAuth 2.0 Client:
 1. Select **Applications > OAuth 2.0 > Clients**.
 2. Select `oidc_client`, and on the **Advanced** tab, select **Token Endpoint Authentication Method**: `private_key_jwt`.

3. Set up PingGateway:

1. In the PingGateway configuration, set an environment variable for the keystore password, and then restart PingGateway:

```
$ export KEYSTORE_SECRET_ID='a2V5c3RvcnU='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

2. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openid/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.\.\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\.\.\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) 

3. Add the following script to PingGateway:

Linux

```
$HOME/.openig/scripts/groovy/discovery.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\discovery.groovy
```

```

/*
 * OIDC discovery with the sample application
 */
response = new Response(Status.OK)
response.getHeaders().put(ContentTypeHeader.NAME, "text/html");
response.entity = """
<!doctype html>
<html>
  <head>
    <title>OpenID Connect Discovery</title>
    <meta charset='UTF-8'>
  </head>
  <body>
    <form id='form' action='/discovery/login?'>
      Enter your user ID or email address:
      <input type='text' id='discovery' name='discovery'
        placeholder='demo or demo@example.com' />
      <input type='hidden' name='goto'
        value='${contexts.idpSelectionLogin.originalUri}' />
    </form>
    <script>
      // Make sure sampleAppUrl is correct for your sample app.
      window.onload = function() {
        document.getElementById('form').onsubmit = function() {
          // Fix the URL if not using the default settings.
          var sampleAppUrl = 'http://app.example.com:8081/';
          var discovery = document.getElementById('discovery');
          discovery.value = sampleAppUrl + discovery.value.split('@', 1)[0];
        };
      };
    </script>
  </body>
</html>""" as String
return response

```

Source: [discovery.groovy](#)

The script transforms the input into a **discovery** value for PingGateway. This is not a requirement for deployment, only a convenience for the purposes of this example. Alternatives are described in the discovery protocol specification.

4. Add the following route to PingGateway, replacing `/path/to/secrets/keystore.p12` with your path:

Linux

```
$HOME/.openig/config/routes/07-discovery.json
```

Windows

```
%appdata%\OpenIG\config\routes\07-discovery.json
```



```

{
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "SecretsProvider-1",
      "type": "SecretsProvider",
      "config": {
        "stores": [
          {
            "type": "KeyStoreSecretStore",
            "config": {
              "file": "/path/to/secrets/keystore.p12",
              "mappings": [
                {
                  "aliases": [ "myprivatekeyalias" ],
                  "secretId": "private.key.jwt.signing.key"
                }
              ],
              "storePasswordSecretId": "keystore.secret.id",
              "storeType": "PKCS12",
              "secretsProvider": "SystemAndEnvSecretStore-1"
            }
          ]
        }
      },
    },
    {
      "name": "DiscoveryPage",
      "type": "ScriptableHandler",
      "config": {
        "type": "application/x-groovy",
        "file": "discovery.groovy"
      }
    }
  ],
  "name": "07-discovery",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/discovery')}",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "DynamicallyRegisteredClient",
          "type": "AuthorizationCodeOAuth2ClientFilter",
          "config": {
            "clientEndpoint": "/discovery",
            "requireHttps": false,
            "requireLogin": true,
            "target": "${attributes.openid}",
            "failureHandler": {
              "type": "StaticResponseHandler",
              "config": {
                "comment": "Trivial failure handler for debugging only",
                "status": 500,
                "headers": {
                  "Content-Type": [ "text/plain; charset=UTF-8" ]
                }
              }
            }
          }
        }
      ]
    }
  }
}

```

```

        },
        "entity": "${contexts.oauth2Failure.error}: ${contexts.oauth2Failure.description}"
    }
},
"loginHandler": "DiscoveryPage",
"discoverySecretId": "private.key.jwt.signing.key",
"tokenEndpointAuthMethod": "private_key_jwt",
"secretsProvider": "SecretsProvider-1",
"metadata": {
    "client_name": "My Dynamically Registered Client",
    "redirect_uris": [ "http://ig.example.com:8080/discovery/callback" ],
    "scopes": [ "openid", "profile", "email" ]
}
}
},
{
    "type": "StaticRequestFilter",
    "config": {
        "method": "POST",
        "uri": "http://app.example.com:8081/login",
        "form": {
            "username": [
                "${attributes.openid.user_info.name}"
            ],
            "password": [
                "${attributes.openid.user_info.family_name}"
            ]
        }
    }
}
],
"handler": "ReverseProxyHandler"
}
}
}

```

Source: [07-discovery.json](#)

Consider the differences with `07-openid.json`:

- The route matches requests to `/discovery`.
- The `AuthorizationCodeOAuth2ClientFilter` uses `DiscoveryPage` as the login handler, and specifies metadata to prepare the dynamic registration request.
- `DiscoveryPage` uses a `ScriptableHandler` and script to provide the `discovery` parameter and `goto` parameter.

If there is a match, then it can use the issuer's registration endpoint and avoid an additional request to look up the user's issuer using the [WebFinger](#) protocol.

If there is no match, PingGateway uses the `discovery` value as the `resource` for a WebFinger request using the OIDC discovery protocol.

- PingGateway uses the `discovery` parameter to find an identity provider. PingGateway extracts the domain host and port from the value, and attempts to find a match in the `supportedDomains` lists for issuers configured for the route.

- When `discoverySecretId` is set, the `tokenEndpointAuthMethod` is always `private_key_jwt`. Clients send a signed JWT to the Authorization Server.

Redirects PingGateway to the end user's browser, using the `goto` parameter, after the process is complete and PingGateway has injected the OIDC user information into the context.

4. Test the setup:

1. Log out of AM, and clear any cookies.
2. Go to <http://ig.example.com:8080/discovery>.
3. Enter the following email address: `demo@example.com`. The AM login page is displayed.
4. Log in as user `demo`, password `Ch4ng31t`, and then allow the application to access user information. The sample application returns the user's page.

ID token validation with PingAM

This page uses an `IdTokenValidationFilter` to validate an ID token.

1. Set up AM:

1. Set up AM as described in [Validating PingAM access tokens with introspection](#).
2. Select **Applications > OAuth 2.0 > Clients** and add the additional scope `openid` to `client-application`.

2. Set up PingGateway:

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/idthokenvalidation.json
```

Windows

```
%appdata%\OpenIG\config\routes\idthokenvalidation.json
```

```

{
  "name": "idtokenvalidation",
  "condition": "${find(request.uri.path, '^/idtokenvalidation')}",
  "capture": "all",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [{
        "type": "IdTokenValidationFilter",
        "config": {
          "idToken": "<id_token_value>",
          "audience": "client-application",
          "issuer": "http://am.example.com:8088/openam/oauth2",
          "failureHandler": {
            "type": "ScriptableHandler",
            "config": {
              "type": "application/x-groovy",
              "source": [
                "def response = new Response(Status.FORBIDDEN)",
                "response.headers['Content-Type'] = 'text/html; charset=utf-8'",
                "def errors = contexts.jwtValidationError.violations.collect{it.description}",
                "def display = \"<html>Can't validate id_token:<br> ${contexts.jwtValidationError.jwt}
\","",
                "display <=<br><br>For the following errors:<br> ${errors.join(\"<br>\")}</html>\"",
                "response.entity=display as String",
                "return response"
              ]
            }
          },
          "verificationSecretId": "verify",
          "secretsProvider": {
            "type": "JwkSetSecretStore",
            "config": {
              "jwkUrl": "http://am.example.com:8088/openam/oauth2/connect/jwk_uri"
            }
          }
        }
      ]},
    "handler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 200,
        "headers": {
          "Content-Type": [ "text/html; charset=UTF-8" ]
        },
        "entity": "<html><body>Validated id_token:<br> ${contexts.jwtValidation.value}</body></html>"
      }
    }
  }
}

```

Source: [idtokenvalidation.json](#)

Notice the following features of the route:

- The route matches requests to `/idtokenvalidation`.

- A `SecretsProvider` declares a `JwkSetSecretStore` to validate secrets for signed JWTs. The `JwkSetSecretStore` specifies a URL to a JWK set on AM that contains the signing keys.
- The property `verificationSecretId` is configured with an arbitrary value. If this property isn't configured, the filter doesn't verify the signature of tokens.
- The `JwkSetSecretStore` specifies the URL to a JWK set on AM, that contains verification keys identified by a `kid`. PingGateway validates the token signature as follows:
 - If the value of a `kid` in the JWK set matches a `kid` in the signed JWT, the `JwkSetSecretStore` verifies the signature.
 - If the JWT doesn't have a `kid`, or if the JWK set doesn't contain a key with the same value, the `JwkSetSecretStore` looks for valid secrets with the same purpose as the value of `verificationSecretId`.
- If the filter validates the token, the `StaticResponseHandler` displays the token value from the context `${contexts.jwtValidation.value}`. Otherwise, the `ScriptableHandler` displays the token value and a list of violations from the context `${contexts.jwtValidationError.violations}`.

3. Test the setup:

1. In a terminal window, use a `curl` command similar to the following to retrieve an `id_token`:

```
$ curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=openid" \
http://am.example.com:8088/openam/oauth2/access_token
```

Output

```
{
  "access_token": "...",
  "scope": "openid",
  "id_token": "...",
  "token_type": "Bearer",
  "expires_in": 3599
}
```

2. In the route, replace `<id_token_value>` with the value of the `id_token` returned in the previous step.
3. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/idthokenvalidation>.

The validated token is displayed.

4. In the route, invalidate the token by changing the value of the audience or issuer, and then access the route again.

The value of the token, and the reasons that the token is invalid, are displayed.

Passing PingAM data along the chain

Pass profile data downstream

Retrieve user profile attributes of an AM user, and provide them in the `UserProfileContext` to downstream filters and handlers. Profile attributes that are enabled in AM can be retrieved, except the `roles` attribute.

The `userProfile` property of `AmService` is configured to retrieve `employeeNumber` and `mail`. When the property is not configured, all available attributes in `rawInfo` or `asJsonValue()` are displayed.

Retrieve profile attributes for a user authenticated with an SSO token

In this example, the user is authenticated with AM through the `SingleSignOnFilter`, which stores the SSO token and its validation information in the `SsoTokenContext`. The `UserProfileFilter` retrieves the user's mail and employee number, as well as the `username`, `_id`, and `_rev`, from that context.

1. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

3. Select **Services > Add a Service**, and add a **Validation Service** with the following **Valid goto URL Resources**:

- `http://ig.example.com:8080/*`
- `http://ig.example.com:8080/?`

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFZc3dvcmQ='
```

The password is retrieved by a `SystemAndEnvSecretStore`, and must be base64-encoded.

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/user-profile-sso.json
```

Windows

```
%appdata%\OpenIG\config\routes\user-profile-sso.json
```

```

{
  "name": "user-profile-sso",
  "condition": "${find(request.uri.path, '^/user-profile-sso')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "http://am.example.com:8088/openam",
        "realm": "/",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "amHandler": "ForgeRockClientHandler"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SingleSignOnFilter",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        },
        {
          "name": "UserProfileFilter-1",
          "type": "UserProfileFilter",
          "config": {
            "username": "${contexts.ssoToken.info.uid}",
            "userService": {
              "type": "UserProfileService",
              "config": {
                "amService": "AmService-1",
                "profileAttributes": [ "employeeNumber", "mail" ]
              }
            }
          }
        }
      ]
    },
    "handler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 200,
        "headers": {
          "Content-Type": [ "text/html; charset=UTF-8" ]
        },
        "entity": "<html><body>username: ${contexts.userProfile.username}<br><br>rawInfo: <pre>${contexts.userProfile.rawInfo}</pre></body></html>"
      }
    }
  }
}

```



```
}  
}  
}  
}  
}
```

Source: [user-profile-sso.json](#)

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/user-profile-sso>.
2. Log in to AM with username `demo` and password `Ch4ng31t`.

The `UserProfileFilter` retrieves the user's profile data and stores it in the `UserProfileContext`. The `StaticResponseHandler` displays the username and the profile data available in `rawInfo`:

```
username: demo  
  
rawInfo:  
  
{_id=demo, _rev=-1, mail=[demo@example.com], username=demo}
```

Retrieve a username from the sessionInfo context

In this example, the `UserProfileFilter` retrieves AM profile information for the user identified by the `SessionInfoContext`, at `${contexts.amSession.username}`. The `SessionInfoFilter` validates an SSO token without redirecting the request to an authentication page.

1. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/user-profile-ses-info.json
```

Windows

```
%appdata%\OpenIG\config\routes\user-profile-ses-info.json
```

```

{
  "name": "user-profile-ses-info",
  "condition": "${find(request.uri.path, '^/user-profile-ses-info')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "http://am.example.com:8088/openam",
        "realm": "/",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "amHandler": "ForgeRockClientHandler"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "capture": "all",
    "config": {
      "filters": [
        {
          "name": "SessionInfoFilter-1",
          "type": "SessionInfoFilter",
          "config": {
            "amService": "AmService-1"
          }
        },
        {
          "name": "UserProfileFilter-1",
          "type": "UserProfileFilter",
          "config": {
            "username": "${contexts.amSession.username}",
            "userService": {
              "type": "UserProfileService",
              "config": {
                "amService": "AmService-1",
                "profileAttributes": [ "employeeNumber", "mail" ]
              }
            }
          }
        }
      ]
    },
    "handler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 200,
        "headers": {
          "Content-Type": [ "application/json" ]
        },
        "entity": "{ \"username\": \"${contexts.userProfile.username}\", \"user_profile\": ${contexts.userProfile.asJsonValue()} }"
      }
    }
  }
}

```

```

    }
  }
}
}
}

```

Source: [user-profile-ses-info.json](#)

3. Test the setup:

1. In a terminal window, use a `curl` command similar to the following to retrieve an access token:

```

$ curl --request POST \
--url http://am.example.com:8088/openam/json/realms/root/authenticate \
--header 'accept-api-version: resource=2.0' \
--header 'content-type: application/json' \
--header 'x-openam-username: demo' \
--header 'x-openam-password: Ch4ng31t' \
--data '{}'
```

```
{ "tokenId": "AQI...AA*", "successUrl": "/openam/console" }
```

2. Access the route, providing the path to the certificate and token ID retrieved in the previous step:

```

$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--cookie 'iPlanetDirectoryPro=tokenId' \
https://ig.example.com:8443/user-profile-ses-info | jq .
```

```

{
  "username": "demo",
  "user_profile": {
    "_id": "demo",
    "_rev": "123...456",
    "employeeNumber": ["123"],
    "mail": ["demo@example.com"],
    "username": "demo"
  }
}
```

iPlanetDirectoryPro is the name of the AM session cookie. For more information, refer to [Find the AM session cookie name](#).

The UserProfileFilter retrieves the user's profile data and stores it in the UserProfileContext. The StaticResponseHandler displays the username and the profile data available in `asJsonValue()`.

Retrieve a username from the OAuth2Context

In this example, the OAuth2ResourceServerFilter validates a request containing an OAuth 2.0 access token, using the introspection endpoint, and injects the token into the OAuth2Context context. The UserProfileFilter retrieves AM profile information for the user identified by this context.

Before you start, set up and test the example in [Validating PingAM access tokens with introspection](#).

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/user-profile-oauth.json
```

Windows

```
%appdata%\OpenIG\config\routes\user-profile-oauth.json
```

```

{
  "name": "user-profile-oauth",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/user-profile-oauth')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "http://am.example.com:8088/openam",
        "realm": "/",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "amHandler": "ForgeRockClientHandler"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [
              "mail",
              "employeenumber"
            ],
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "token-resolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "amService": "AmService-1",
                "providerHandler": {
                  "type": "Chain",
                  "config": {
                    "filters": [
                      {
                        "type": "HttpBasicAuthenticationClientFilter",
                        "config": {
                          "username": "ig_agent",
                          "passwordSecretId": "agent.secret.id",
                          "secretsProvider": "SystemAndEnvSecretStore-1"
                        }
                      }
                    ],
                    "handler": "ForgeRockClientHandler"
                  }
                }
              }
            }
          }
        }
      ]
    }
  }
}

```

```

    }
  },
  {
    "name": "UserProfileFilter-1",
    "type": "UserProfileFilter",
    "config": {
      "username": "${contexts.oauth2.accessToken.info.sub}",
      "userService": {
        "type": "UserProfileService",
        "config": {
          "amService": "AmService-1",
          "profileAttributes": [ "employeeNumber", "mail" ]
        }
      }
    }
  }
],
"handler": {
  "type": "StaticResponseHandler",
  "config": {
    "status": 200,
    "headers": {
      "Content-Type": [ "application/json" ]
    },
    "entity": "{ \"username\": \"${contexts.userProfile.username}\", \"user_profile\": ${contexts.userProfile.asJsonValue()} }"
  }
}
}
}
}

```

Source: [user-profile-oauth.json](#)

2. Test the setup:

1. In a terminal window, use a `curl` command similar to the following to retrieve an access token:

```

$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail%20employeenumber" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")

```

2. Validate the access token returned in the previous step:

```

$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/user-profile-oauth | jq .

```

Output

```
{
  "username": "demo",
  "user_profile": {
    "_id": "demo",
    "_rev": "123...456",
    "employeeNumber": ["123"],
    "mail": ["demo@example.com"],
    "username": "demo"
  }
}
```

The `UserProfileFilter` retrieves the user's profile data and stores it in the `UserProfileContext`. The `StaticResponseHandler` displays the username and the profile data that is available in `asJsonValue()`.

Passing runtime data downstream

The following sections describe how to pass identity or other runtime information in a JWT, downstream to a protected application:

The examples in this section use the following objects:

- [JwtBuilderFilter](#) to collect runtime information and pack it into a JWT
- [HeaderFilter](#) to add the information to the forwarded request

To help with development, the sample application includes a `/jwt` endpoint to display the JWT, verify its signature, and decrypt the JWT.

Pass runtime data in a JWT signed with a PEM

1. Set up secrets

1. Locate a directory for secrets and go to it:

```
$ cd /path/to/secrets
```

2. Generate PEM files to sign and verify the JWT:

```
$ openssl req \
  -newkey rsa:2048 \
  -new \
  -nodes \
  -x509 \
  -days 3650 \
  -subj "/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr" \
  -keyout id.key.for.signing.jwt.pem \
  -out id.key.for.verifying.jwt.pem
```


2. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

3. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) [↗](#)

4. Add the following route to PingGateway, replacing value of the property `secretsDir` with the directory for the PEM file:

Linux

```
$HOME/.openig/config/routes/jwt-builder-sign-pem.json
```

Windows

```
%appdata%\OpenIG\config\routes\jwt-builder-sign-pem.json
```

```

{
  "name": "jwt-builder-sign-pem",
  "condition": "${find(request.uri.path, '/jwt-builder-sign-pem')}",
  "baseURI": "http://app.example.com:8081",
  "properties": {
    "secretsDir": "/path/to/secrets"
  },
  "capture": "all",
  "heap": [
    {
      "name": "pemPropertyFormat",
      "type": "PemPropertyFormat"
    },
    {
      "name": "FileSystemSecretStore-1",
      "type": "FileSystemSecretStore",
      "config": {
        "format": "PLAIN",
        "directory": "${secretsDir}",
        "suffix": ".pem",
        "mappings": [{
          "secretId": "id.key.for.signing.jwt",
          "format": "pemPropertyFormat"
        }]
      }
    },
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [{
        "name": "SingleSignOnFilter",
        "type": "SingleSignOnFilter",
        "config": {
          "amService": "AmService-1"
        }
      }, {
        "name": "UserProfileFilter",
        "type": "UserProfileFilter",
        "config": {
          "username": "${contexts.ssoToken.info.uid}",
          "userService": {
            "type": "UserProfileService",
            "config": {

```

```

        "amService": "AmService-1"
      }
    }
  }, {
    "name": "JwtBuilderFilter-1",
    "type": "JwtBuilderFilter",
    "config": {
      "template": {
        "name": "${contexts.userProfile.commonName}",
        "email": "${contexts.userProfile.rawInfo.mail[0]}"
      },
      "secretsProvider": "FileSystemSecretStore-1",
      "signature": {
        "secretId": "id.key.for.signing.jwt",
        "algorithm": "RS512"
      }
    }
  }, {
    "name": "HeaderFilter-1",
    "type": "HeaderFilter",
    "config": {
      "messageType": "REQUEST",
      "add": {
        "x-openig-user": ["${contexts.jwtBuilder.value}"]
      }
    }
  }
],
"handler": "ReverseProxyHandler"
}
}
}

```

Source: [jwt-builder-sign-pem.json](#)

Notice the following features of the route:

- The route matches requests to `/jwt-builder-sign-pem`.
- The agent password for AmService is provided by a SystemAndEnvSecretStore.
- If the request doesn't have a valid AM session cookie, the SingleSignOnFilter redirects the request to authenticate with AM. If the request already has a valid AM session cookie, the SingleSignOnFilter passes the request to the next filter, and stores the cookie value in an SsoTokenContext.
- The UserProfileFilter reads the username from the SsoTokenContext, uses it to retrieve the user's profile info from AM, and places the data into the UserProfileContext.
- The JwtBuilderFilter refers to the secret ID of the PEM, and uses the FileSystemSecretStore to manage the secret.
- The FileSystemSecretStore mapping refers to the secret ID of the PEM, and uses the PemPropertyFormat to define the format.
- The HeaderFilter retrieves the JWT from the JwtBuilderContext, and adds it to the header field `x-openig-user` in the request, so that the sample app can display the JWT.
- The ClientHandler passes the request to the sample app, which displays the JWT.

4. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/jwt-builder-sign-pem>.
2. Sign on to AM as user `demo`, password `Ch4ng31t`. The sample application displays the signed JWT along with its header and payload.
3. In `USE PEM FILE` in the sample app, enter the path to `id.key.for.verifying.jwt.pem` to verify the JWT signature.

Pass runtime data in a JWT signed with PEM then encrypted with a symmetric key

This example passes runtime data in a JWT that is signed with a PEM, and then encrypted with a symmetric key.

1. Set up secrets

1. Locate a directory for secrets and go to it:

```
$ cd /path/to/secrets
```

2. From the secrets directory, generate PEM files to sign and verify the JWT:

```
$ openssl req \
  -newkey rsa:2048 \
  -new \
  -nodes \
  -x509 \
  -days 3650 \
  -subj "/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr" \
  -keyout id.key.for.signing.jwt.pem \
  -out id.key.for.verifying.jwt.pem
```

3. Encrypt the PEM file used to sign the JWT:

```
$ openssl pkcs8 \
  -topk8 \
  -inform PEM \
  -outform PEM \
  -in id.key.for.signing.jwt.pem \
  -out id.encrypted.key.for.signing.jwt.pem \
  -passout pass:encryptedpassword \
  -v1 PBE-SHA1-3DES
```

The encrypted PEM file used for signatures is `id.encrypted.key.for.signing.jwt.pem`. The password to decode the file is `encryptedpassword`.

Tip

If encryption fails, make sure your encryption methods and ciphers are supported by the Java Cryptography Extension.

4. Generate a symmetric key to encrypt the JWT:

```
$ openssl rand -base64 32 > symmetric.key.for.encrypting.jwt
```

5. Make sure you have the following keys in your secrets directory:

- id.encrypted.key.for.signing.jwt.pem
- id.key.for.signing.jwt.pem
- id.key.for.verifying.jwt.pem
- symmetric.key.for.encrypting.jwt

2. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- https://ig.example.com:8443/*
- https://ig.example.com:8443/*?*

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** ig_agent
- **Password:** password



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

3. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcnQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.\.\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\.\.\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

4. In PingGateway, create an environment variable for the base64-encoded password to decrypt the PEM file used to sign the JWT:

```
$ export ID_DECRYPTED_KEY_FOR_SIGNING_JWT='ZW5jcnlwdGVkcGFzc3dvcmQ='
```

5. Add the following route to PingGateway, replacing the value of `secretsDir` with your secrets directory:

Linux

```
$HOME/.openig/config/routes/jwtbuilder-sign-then-encrypt.json
```

Windows

```
%appdata%\OpenIG\config\routes\jwtbuilder-sign-then-encrypt.json
```

```

{
  "name": "jwtbuilder-sign-then-encrypt",
  "condition": "${find(request.uri.path, '/jwtbuilder-sign-then-encrypt')}",
  "baseURI": "http://app.example.com:8081",
  "properties": {
    "secretsDir": "/path/to/secrets"
  },
  "capture": "all",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore",
      "type": "SystemAndEnvSecretStore",
      "config": {
        "mappings": [{
          "secretId": "id.decrypted.key.for.signing.jwt",
          "format": "BASE64"
        }]
      }
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore",
        "url": "http://am.example.com:8088/openam"
      }
    },
    {
      "name": "pemPropertyFormat",
      "type": "PemPropertyFormat",
      "config": {
        "decryptionSecretId": "id.decrypted.key.for.signing.jwt",
        "secretsProvider": "SystemAndEnvSecretStore"
      }
    },
    {
      "name": "FileSystemSecretStore-1",
      "type": "FileSystemSecretStore",
      "config": {
        "format": "PLAIN",
        "directory": "&{secretsDir}",
        "mappings": [{
          "secretId": "id.encrypted.key.for.signing.jwt.pem",
          "format": "pemPropertyFormat"
        }], {
          "secretId": "symmetric.key.for.encrypting.jwt",
          "format": {
            "type": "SecretKeyPropertyFormat",
            "config": {
              "format": "BASE64",
              "algorithm": "AES"
            }
          }
        }
      ]
    }
  ]
}

```



```

],
"handler": {
  "type": "Chain",
  "config": {
    "filters": [{
      "name": "SingleSignOnFilter",
      "type": "SingleSignOnFilter",
      "config": {
        "amService": "AmService-1"
      }
    }, {
      "name": "UserProfileFilter",
      "type": "UserProfileFilter",
      "config": {
        "username": "${contexts.ssoToken.info.uid}",
        "userProfileService": {
          "type": "UserProfileService",
          "config": {
            "amService": "AmService-1"
          }
        }
      }
    }, {
      "name": "JwtBuilderFilter-1",
      "type": "JwtBuilderFilter",
      "config": {
        "template": {
          "name": "${contexts.userProfile.commonName}",
          "email": "${contexts.userProfile.rawInfo.mail[0]}"
        },
        "secretsProvider": "FileSystemSecretStore-1",
        "signature": {
          "secretId": "id.encrypted.key.for.signing.jwt.pem",
          "algorithm": "RS512",
          "encryption": {
            "secretId": "symmetric.key.for.encrypting.jwt",
            "algorithm": "dir",
            "method": "A128CBC-HS256"
          }
        }
      }
    }, {
      "name": "AddBuiltJwtToHeader",
      "type": "HeaderFilter",
      "config": {
        "messageType": "REQUEST",
        "add": {
          "x-openig-user": ["${contexts.jwtBuilder.value}"]
        }
      }
    }, {
      "name": "AddBuiltJwtAsCookie",
      "type": "HeaderFilter",
      "config": {
        "messageType": "RESPONSE",
        "add": {
          "set-cookie": ["my-jwt=${contexts.jwtBuilder.value};PATH=/"]
        }
      }
    }
  ]
}

```

```

    }},
    "handler": "ReverseProxyHandler"
  }
}
}

```

Source: [jwtbuilder-sign-then-encrypt.json](#)

Notice the following features of the route:

- The route matches requests to `/jwtbuilder-sign-then-encrypt`.
- The `SystemAndEnvSecretStore` provides the PingGateway agent password and the password to decode the PEM file for the signing keys.
- The `FileSystemSecretStore` maps the secret IDs of the encrypted PEM file used to sign the JWT, and the symmetric key used to encrypt the JWT.
- After authentication, the `UserProfileFilter` reads the username from the `SsoTokenContext`, uses it to retrieve the user's profile info from AM, and places the data into the `UserProfileContext`.
- The `JwtBuilderFilter` takes the username and email from the `UserProfileContext`, and stores them in a JWT in the `JwtBuilderContext`. It uses the secrets mapped in the `FileSystemSecretStore` to sign then encrypt the JWT.
- The `AddBuiltJwtToHeader` HeaderFilter retrieves the JWT from the `JwtBuilderContext`, and adds it to the header field `x-openig-user` in the request so that the sample app can display the JWT.
- The `AddBuiltJwtAsCookie` HeaderFilter adds the JWT to a cookie called `my-jwt` so that it can be retrieved by the `JwtValidationFilter` in [JWT validation with PingAM](#). The cookie is ignored in this example.
- The `ClientHandler` passes the request to the sample app.

4. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/jwtbuilder-sign-then-encrypt>.
2. Log in to AM as user `demo`, password `Ch4ng31t`. The sample app displays the encrypted JWT. The payload is concealed because the JWT is encrypted.
3. In the `ENTER SECRET` box, enter the value of `symmetric.key.for.encrypting.jwt` to decrypt the JWT. The signed JWT and its payload are now displayed.
4. In the `USE PEM FILE` box, enter the path to `id.key.for.verifying.jwt.pem` to verify the JWT signature.

Pass runtime data in JWT encrypted with a symmetric key

1. Set up secrets:

1. Locate a directory for secrets and go to it:

```
$ cd /path/to/secrets
```

2. In the secrets folder, generate an AES 256-bit key:

```
$ openssl rand -base64 32
```

Output

```
1oH...UFQ=
```

3. In the secrets folder, create a file called `symmetric.key.for.encrypting.jwt` containing the AES key:

```
$ echo -n '1oH...UFQ=' > symmetric.key.for.encrypting.jwt
```

Make sure the password file contains only the password, with no trailing spaces or carriage returns.

2. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

3. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) 

4. Add the following route to PingGateway, replacing the value of the property `secretsDir` with your value:

Linux

```
$HOME/.openig/config/routes/jwtbuilder-encrypt-symmetric.json
```

Windows

```
%appdata%\OpenIG\config\routes\jwtbuilder-encrypt-symmetric.json
```

```

{
  "name": "jwtbuilder-encrypt-symmetric",
  "condition": "${find(request.uri.path, '/jwtbuilder-encrypt-symmetric')}",
  "baseURI": "http://app.example.com:8081",
  "properties": {
    "secretsDir": "/path/to/secrets"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam"
      }
    }
  ],
  {
    "name": "FileSystemSecretStore-1",
    "type": "FileSystemSecretStore",
    "config": {
      "format": "PLAIN",
      "directory": "${secretsDir}",
      "mappings": [{
        "secretId": "symmetric.key.for.encrypting.jwt",
        "format": {
          "type": "SecretKeyPropertyFormat",
          "config": {
            "format": "BASE64",
            "algorithm": "AES"
          }
        }
      ]
    }
  }
],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [{
        "name": "SingleSignOnFilter-1",
        "type": "SingleSignOnFilter",
        "config": {
          "amService": "AmService-1"
        }
      }, {
        "name": "UserProfileFilter-1",
        "type": "UserProfileFilter",
        "config": {
          "username": "${contexts.ssoToken.info.uid}",
          "userService": {
            "type": "UserProfileService",
            "config": {

```

```

        "amService": "AmService-1"
      }
    }
  }, {
    "name": "JwtBuilderFilter-1",
    "type": "JwtBuilderFilter",
    "config": {
      "template": {
        "name": "${contexts.userProfile.commonName}",
        "email": "${contexts.userProfile.rawInfo.mail[0]}"
      },
      "secretsProvider": "FileSystemSecretStore-1",
      "encryption": {
        "secretId": "symmetric.key.for.encrypting.jwt",
        "algorithm": "dir",
        "method": "A128CBC-HS256"
      }
    }
  }, {
    "name": "HeaderFilter-1",
    "type": "HeaderFilter",
    "config": {
      "messageType": "REQUEST",
      "add": {
        "x-openig-user": ["${contexts.jwtBuilder.value}"]
      }
    }
  }
],
"handler": "ReverseProxyHandler"
}
}
}

```

Source: [jwtbuilder-encrypt-symmetric.json](#)

Notice the following features of the route:

- The route matches requests to `/jwtbuilder-encrypt-symmetric`.
- The JWT encryption key is managed by the `FileSystemSecretStore` in the heap, which defines the `SecretKeyPropertyFormat`.
- The `JwtBuilderFilter` `encryption` property refers to key in the `FileSystemSecretStore`.
- The `HeaderFilter` retrieves the JWT from the `JwtBuilderContext`, and adds it to the header field `x-openig-user` in the request, so that the sample app can display the JWT.

4. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/jwtbuilder-encrypt-symmetric>.
2. Log in to AM as user `demo`, password `Ch4ng31t`, or as another user. The JWT is displayed in the sample app.
3. In the `ENTER SECRET` field, enter the value of the AES 256-bit key to decrypt the JWT and display its payload.

Pass runtime data in JWT encrypted with an asymmetric key

The asymmetric key in this example is a PEM, but you can equally use a keystore.

1. Set up secrets:

1. Locate a directory for secrets and go to it:

```
$ cd /path/to/secrets
```

2. Generate an encrypted PEM file:

```
$ openssl req \
-newkey rsa:2048 \
-new \
-nodes \
-x509 \
-days 3650 \
-subj "/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr" \
-keyout id.key.for.encrypting.jwt.pem \
-out id.key.for.decrypting.jwt.pem
```

2. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

3. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

4. Add the following route to PingGateway, replacing value of the property `secretsDir` with the directory for the PEM file:

Linux

```
$HOME/.openig/config/routes/jwtbuilder-encrypt-asymmetric.json
```

Windows

```
%appdata%\OpenIG\config\routes\jwtbuilder-encrypt-asymmetric.json
```



```

{
  "name": "jwtbuilder-encrypt-asymmetric",
  "condition": "${find(request.uri.path, '/jwtbuilder-encrypt-asymmetric')}",
  "baseURI": "http://app.example.com:8081",
  "properties": {
    "secretsDir": "/path/to/secrets"
  },
  "capture": "all",
  "heap": [
    {
      "name": "pemPropertyFormat",
      "type": "PemPropertyFormat"
    },
    {
      "name": "FileSystemSecretStore-1",
      "type": "FileSystemSecretStore",
      "config": {
        "format": "PLAIN",
        "directory": "${secretsDir}",
        "suffix": ".pem",
        "mappings": [{
          "secretId": "id.key.for.decrypting.jwt",
          "format": "pemPropertyFormat"
        }]
      }
    },
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [{
        "name": "SingleSignOnFilter",
        "type": "SingleSignOnFilter",
        "config": {
          "amService": "AmService-1"
        }
      }, {
        "name": "UserProfileFilter",
        "type": "UserProfileFilter",
        "config": {
          "username": "${contexts.ssoToken.info.uid}",
          "userService": {
            "type": "UserProfileService",
            "config": {

```

```

        "amService": "AmService-1"
      }
    }
  }, {
    "name": "JwtBuilderFilter-1",
    "type": "JwtBuilderFilter",
    "config": {
      "template": {
        "name": "${contexts.userProfile.commonName}",
        "email": "${contexts.userProfile.rawInfo.mail[0]}"
      },
      "secretsProvider": "FileSystemSecretStore-1",
      "encryption": {
        "secretId": "id.key.for.decrypting.jwt",
        "algorithm": "RSA-OAEP-256",
        "method": "A128CBC-HS256"
      }
    }
  }, {
    "name": "HeaderFilter-1",
    "type": "HeaderFilter",
    "config": {
      "messageType": "REQUEST",
      "add": {
        "x-openig-user": ["${contexts.jwtBuilder.value}"]
      }
    }
  }
],
"handler": "ReverseProxyHandler"
}
}
}

```

Source: [jwtbuilder-encrypt-asymmetric.json](#)

Notice the following features of the route:

- The route matches requests to `/jwtbuilder-encrypt-asymmetric`.
- The `JwtBuilderFilter` refers to the secret ID of the PEM, and uses the `FileSystemSecretStore` to manage the secret.
- The `FileSystemSecretStore` mapping refers to the secret ID of the PEM, and uses the default `PemPropertyFormat`.
- The `HeaderFilter` retrieves the JWT from the `JwtBuilderContext`, and adds it to the header field `x-openig-user` in the request, so that the sample app can display the JWT.

4. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/jwtbuilder-encrypt-asymmetric>.
2. Log in to AM as user `demo`, password `Ch4ng31t`, or as another user. The JWT is displayed in the sample app.
3. In the **USE PEM FILE** field, enter the path to `id.key.for.encrypting.jwt.pem` to decrypt the JWT and display its payload.

SAML v2.0 and PingGateway

PingGateway implements SAML 2.0 to validate users and log them in to protected applications.

For more information about the SAML 2.0 standard, refer to [RFC 7522](#). The following terms are used:

- *Identity Provider* (IdP): The service that manages the user identity, for example PingOne Advanced Identity Cloud or AM.
- *Service Provider* (SP): The service that a user wants to access. PingGateway acts as a SAML 2.0 SP for SSO, providing an interface to applications that don't support SAML 2.0.
- *Circle of trust* (CoT): An IdP and SP that participate in federation.
- *Fedlet*: SAML configuration files.

SAML assertions

SAML assertions can be signed and encrypted. Use SHA-256 variants (rsa-sha256 or ecdsa-sha256).

SAML assertions can contain configurable attribute values, such as user meta-information or anything else provided by the IdP. The attributes of a SAML assertion can contain one or more values, made available as a list of strings. Even if an attribute contains a single value, it is made available as a list of strings.

SAML configuration

PingGateway scans SAML configuration files once, the first time that a request accesses the [SamlFederationFilter](#) or [SamlFederationHandler \(deprecated\)](#) after startup. Restart PingGateway after any change to the SAML configuration files.

SAML in deployments with multiple instances of PingGateway

When PingGateway acts as a SAML service provider, session information is stored in the fedlet not the session cookie. In deployments with multiple instances of PingGateway as a SAML service provider, it is necessary to set up sticky sessions so that requests always hit the instance where the SAML interaction was started.

For information, refer to [Session state considerations](#) in AM's *SAML v2.0 guide*.


About SP-initiated SSO

SP-initiated single sign-on (SSO) occurs when a user attempts to access a protected application directly through the service provider (SP). Because the user's federated identity is managed by the identity provider (IdP), the SP sends a SAML authentication request to the IdP. After the IdP authenticates the user, it provides the SP with a SAML assertion for the user.

For the `SamlFederationFilter`, prefer SP-initiated SSO to IdP-initiated SSO:

- A dedicated SAML URI is not required to start SP-initiated authentication.
- The HTTP session tracks the state of the user session.

The following sequence diagram shows the flow of information in SP-initiated SSO when PingGateway acts as a SAML 2.0 SP:



AM as IdP

- [Unsigned/unencrypted SAML v2.0 assertions](#)
- [Signed/encrypted SAML v2.0 assertions](#)

PingOne as IdP

- [PingGateway with PingOne as a SAML IdP](#)

Federation using the SamlFederationHandler (deprecated)



Important

The SamlFederationHandler is deprecated. Use the [SamlFederationFilter](#) instead.

- [About SP-initiated SSO with the SamlFederationHandler and PingAM](#)
- [About IdP-initiated SSO with PingAM](#)
- [Unsigned/unencrypted SAML v2.0 assertions](#)

- [Signed/encrypted SAML v2.0 assertions](#)
- [SAML 2.0 and multiple applications](#)

Additional topics

- [Non-transient SAML v2.0 NameID format](#)
- [Example SAML v2.0 Fedlet files](#)

AM as IdP

Unsigned/unencrypted SAML v2.0 assertions

This example sets up federation using AM as the identity provider with unsigned/unencrypted assertions.

1. Set up the network:

Add `sp.example.com` to your `/etc/hosts` file:

```
127.0.0.1 localhost am.example.com ig.example.com app.example.com sp.example.com
```

Traffic to the application is proxied through PingGateway, using the host name `sp.example.com`.

2. Configure a Java Fedlet:

Note

The SAML library component validates the SP's AssertionConsumerService Location against the incoming IdP SAML Assertion, based on the request information, including the port. In `sp.xml`, always specify the port in the Location value of `AssertionConsumerService`, even when using defaults of 443 or 80, as follows:

```
<AssertionConsumerService isDefault="true"
    index="0"
    Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
    Location="https://sp.example.com:443/fedletapplication" />
```

For more information about Java Fedlets, refer to [Creating and configuring the Fedlet](#) in AM's *SAML v2.0 guide*.

1. Copy and unzip the fedlet zip file, `Fedlet-8.0.0.zip`, delivered with the AM installation, into a local directory.

```
$ unzip $HOME/openam/Fedlet-8.0.0.zip
```

Output

```
Archive:  Fedlet-8.0.0.zip
creating:  conf/
inflating: README
inflating: conf/FederationConfig.properties
inflating: conf/fedlet.cot-template
inflating: conf/idp-extended.xml-template
inflating: conf/sp-extended.xml-template
inflating: conf/sp.xml-template
inflating: fedlet.war
```

2. In each file, search and replace the following properties:

Replace this	With this
IDP_ENTITY_ID	openam
FEDLET_ENTITY_ID	sp
FEDLET_PROTOCOL://FEDLET_HOST:FEDLET_PORT/ FEDLET_DEPLOY_URI	https://sp.example.com:8443/home/saml
fedletcot and FEDLET_COT	Circle of Trust
sp.example.com:8443/home/saml/ fedletapplication	sp.example.com:8443/home/saml/ fedletapplication/metaAlias/sp

3. Save the files as .xml, without the `-template` extension, so that the directory looks like this:

```
conf
├─ FederationConfig.properties
├─ fedlet.cot
├─ idp-extended.xml
├─ sp-extended.xml
└─ sp.xml
```

By default, AM as an IdP uses the NameID format `urn:oasis:names:tc:SAML:2.0:nameid-format:transient` to communicate about a user. For information about using a different NameID format, refer to [Non-transient SAML v2.0 NameID format](#).

3. Set up AM:

1. In the AM admin UI, select  **Identities**, select the user `demo`, and change the last name to `Ch4ng31t`. Note that, for this example, the last name must be the same as the password.
2. Select **Applications > Federation > Circles of Trust**, and add a circle of trust called `Circle of Trust`, with the default settings.

3. Set up a remote service provider:

1. Select **Applications > Federation > Entity Providers**, and add a remote entity provider.
2. Drag in or import `sp.xml` created in the previous step.
3. Select **Circles of Trust**: `Circle of Trust`.

4. Set up a hosted identity provider:

1. Select **Applications > Federation > Entity Providers**, and add a hosted entity provider with the following values:

- **Entity ID**: `openam`
- **Entity Provider Base URL**: `http://am.example.com:8088/openam`
- **Identity Provider Meta Alias**: `idp`
- **Circles of Trust**: `Circle of Trust`

2. Select **Assertion Processing > Attribute Mapper**, map the following SAML attribute keys and values, and then save your changes:

- **SAML Attribute**: `cn`, **Local Attribute**: `cn`
- **SAML Attribute**: `sn`, **Local Attribute**: `sn`

3. In a terminal, export the XML-based metadata for the IdP:

```
$ curl -v \  
--output idp.xml \  
"http://am.example.com:8088/openam/saml2/jsp/exportmetadata.jsp?entityid=openam"
```

The `idp.xml` file is created locally.

4. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Copy the edited fedlet files, and the exported `idp.xml` file into the PingGateway configuration, at `$HOME/.openig/SAML`.

```
$ ls -l $HOME/.openig/SAML
```

Output

```
FederationConfig.properties
fedlet.cot
idp-extended.xml
idp.xml
sp-extended.xml
sp.xml
```

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/..*\\\\\\\\.ico$')
or matchesWithRegex(request.uri.path, '^/..*\\\\\\\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) 

4. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/saml-filter.json
```

Windows

```
%appdata%\OpenIG\config\routes\saml-filter.json
```



```

{
  "name": "saml-filter",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home')}",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SamlFilter",
          "type": "SamlFederationFilter",
          "config": {
            "assertionMapping": {
              "name": "cn",
              "surname": "sn"
            },
            "subjectMapping": "sp-subject-name",
            "redirectURI": "/home/saml-filter"
          }
        },
        {
          "name": "SetSamlHeaders",
          "type": "HeaderFilter",
          "config": {
            "messageType": "REQUEST",
            "add": {
              "x-saml-cn": [ "${toString(session.name)}" ],
              "x-saml-sn": [ "${toString(session.surname)}" ]
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

Source: [saml-filter.json](#)

Notice the following features of the route:

- The route matches requests to `/home`.
- The SamlFederationFilter extracts `cn` and `sn` from the SAML assertion, and maps them to the SessionContext, at `session.name[0]` and `session.surname[0]`.
- The HeaderFilter adds the session name and surname as headers to the request so that they are displayed by the sample application.

5. Restart PingGateway.

5. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://sp.example.com:8443/home>.
2. Log in to AM as user `demo`, password `Ch4ng31t`. The request is redirected to the sample application.

**Tip**

If a request returns an HTTP 414 URI Too Long error, consider the information in [URI Too Long error](#).

Signed/encrypted SAML v2.0 assertions

This example set up federation using AM as the identity provider with signed/encrypted assertions.

Before you start, set up and test the example in [Unsigned/unencrypted SAML v2.0 assertions](#).

1. Set up the SAML keystore:

1. Find the values of AM's default SAML keypass and storepass:

```
$ more /path/to/am/secrets/default/.keypass
$ more /path/to/am/secrets/default/.storepass
```

2. Copy the SAML keystore from the AM configuration to PingGateway:

```
$ cp /path/to/am/secrets/keystores/keystore.jceks /path/to/ig/secrets/keystore.jceks
```

**Warning**

Legacy keystore types such as JKS and JCEKS are supported but aren't secure. Consider using the PKCS#12 keystore type.

2. Configure the Fedlet in PingGateway:

1. In `FederationConfig.properties`, make the following changes:

1. Delete the following lines:

- `com.sun.identity.saml.xmlsig.keystore=%BASE_DIR%/security/keystores/keystore.jks`
- `com.sun.identity.saml.xmlsig.storepass=%BASE_DIR%/.storepass`
- `com.sun.identity.saml.xmlsig.keypass=%BASE_DIR%/.keypass`
- `com.sun.identity.saml.xmlsig.certalias=test`
- `com.sun.identity.saml.xmlsig.storetype=JKS`
- `am.encryption.pwd=@AM_ENC_PWD@`

2. Add the following line:

```
org.forgerock.openam.saml2.credential.resolver.class=org.forgerock.openig.handler.saml.SecretsSam2CredentialResolver
```

This class is responsible for resolving secrets and supplying credentials.

**Tip**

Be sure to leave no space at the end of the line.

2. In `sp.xml`, make the following changes:

1. Change `AuthnRequestsSigned="false"` to `AuthnRequestsSigned="true"`.
2. Add the following `KeyDescriptor` just before `</SPSSODescriptor>`

```
<KeyDescriptor use="signing">
  <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#" >
    <ds:X509Data>
      <ds:X509Certificate>

      </ds:X509Certificate>
    </ds:X509Data>
  </ds:KeyInfo>
</KeyDescriptor>
</SPSSODescriptor>
```

3. Copy the value of the signing certificate from `idp.xml` to this file:

```
<KeyDescriptor use="signing">
  <ds:KeyInfo>
    <ds:X509Data>
      <ds:X509Certificate>

      MII...zA6

      </ds:X509Certificate>
```

This is the public key used for signing so that the IdP can verify request signatures.

3. Replace the remote service provider in AM:

1. Select **Applications > Federation > Entity Providers**, and remove the `sp` entity provider.
2. Drag in or import the new `sp.xml` updated in the previous step.
3. Select **Circles of Trust: Circle of Trust**.

4. Set up PingGateway

1. In the PingGateway configuration, set environment variables for the following secrets, and then restart PingGateway:

```
$ export KEYSTORE_SECRET_ID='a2V5c3RvcmlU='
$ export SAML_KEYSTORE_STOREPASS_SECRET_ID='base64-encoded value of the SAML storepass'
$ export SAML_KEYSTORE_KEYPASS_SECRET_ID='base64-encoded value of the SAML keypass'
```

The passwords are retrieved by a `SystemAndEnvSecretStore`, and must be base64-encoded.

2. Remove `saml-filter.json` from the configuration, and add the following route, replacing the path to `keystore.jceks` with your path:

Linux

```
$HOME/.openig/config/routes/saml-filter-secure.json
```

Windows

```
%appdata%\OpenIG\config\routes\saml-filter-secure.json
```

```

{
  "name": "saml-filter-secure",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "KeyStoreSecretStore-1",
      "type": "KeyStoreSecretStore",
      "config": {
        "file": "/path/to/ig/keystore.jceks",
        "storeType": "jceks",
        "storePasswordSecretId": "saml.keystore.storepass.secret.id",
        "entryPasswordSecretId": "saml.keystore.keypass.secret.id",
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "mappings": [ {
          "secretId": "sp.signing.sp",
          "aliases": [ "rsajwtsigningkey" ]
        }, {
          "secretId": "sp.decryption.sp",
          "aliases": [ "test" ]
        } ]
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SamlFilter",
          "type": "SamlFederationFilter",
          "config": {
            "assertionMapping": {
              "name": "cn",
              "surname": "sn"
            },
            "subjectMapping": "sp-subject-name",
            "redirectURI": "/home/saml-filter",
            "secretsProvider": "KeyStoreSecretStore-1"
          }
        },
        {
          "name": "SetSamlHeaders",
          "type": "HeaderFilter",
          "config": {
            "messageType": "REQUEST",
            "add": {
              "x-saml-cn": [ "${toString(session.name)}" ],
              "x-saml-sn": [ "${toString(session.surname)}" ]
            }
          }
        }
      ]
    }
  }
}

```

```
    ],
    "handler": "ReverseProxyHandler"
  }
}
```

Source: [saml-filter-secure.json](#)

Notice the following features of the route compared to `saml-filter.json`:

- The `SamLFederationHandler` refers to the `KeyStoreSecretStore` to provide the keys for the signed and encrypted SAML assertions.
- The secret IDs, `sp.signing.sp` and `sp.decryption.sp`, follow a naming convention based on the name of the service provider, `sp`.
- The alias for the signing key corresponds to the PEM in `keystore.jceks`.

3. Restart PingGateway.

5. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://sp.example.com:8443/home>.
2. Log in to AM as user `demo`, password `Ch4ng31t`. The request is redirected to the sample application.



Tip


If a request returns an HTTP 414 URI Too Long error, consider the information in [URI Too Long error](#).

SamLFederationHandler (deprecated)

About SP-initiated SSO with the SamLFederationHandler and PingAM

SP-initiated SSO occurs when a user attempts to access a protected application directly through the SP. Because the user's federated identity is managed by the IdP, the SP sends a SAML authentication request to the IdP. After the IdP authenticates the user, it provides the SP with a SAML assertion for the user.

The following sequence diagram shows the flow of information in SP-initiated SSO, when PingGateway acts as a SAML 2.0 SP:


SP-Initiated SSO**About IdP-initiated SSO with PingAM**

IdP-initiated SSO occurs when a user attempts to access a protected application, using the IdP for authentication. The IdP sends an unsolicited authentication statement to the SP.

Before IdP-initiated SSO can occur:

- The user must access a link on the IdP that refers to the remote SP.
- The user must authenticate to the IdP.
- The IdP must be configured with links that refer to the SP.

The following sequence diagram shows the flow of information in IdP-initiated SSO when PingGateway acts as a SAML 2.0 SP:



Unsigned/unencrypted SAML v2.0 assertions

For examples of the federation configuration files, refer to [Example SAML v2.0 Fedlet files](#). To set up multiple SPs, work through this page and [SAML 2.0 and multiple applications](#).

1. Set up the network:

Add `sp.example.com` to your `/etc/hosts` file:

```
127.0.0.1 localhost am.example.com ig.example.com app.example.com sp.example.com
```

Traffic to the application is proxied through PingGateway, using the host name `sp.example.com`.

2. Configure a Java Fedlet:

Note

The SAML library component validates the SP's AssertionConsumerService Location against the incoming IdP SAML Assertion, based on the request information, including the port. In `sp.xml`, always specify the port in the Location value of `AssertionConsumerService`, even when using defaults of 443 or 80, as follows:

```
<AssertionConsumerService isDefault="true"
  index="0"
  Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
  Location="https://sp.example.com:443/fedletapplication" />
```

For more information about Java Fedlets, refer to [Creating and configuring the Fedlet](#) in AM's *SAML v2.0 guide*.

1. Copy and unzip the fedlet zip file, `Fedlet-8.0.0.zip`, delivered with the AM installation, into a local directory.


```
$ unzip $HOME/openam/Fedlet-8.0.0.zip
```

Output

```
Archive:  Fedlet-8.0.0.zip
creating:  conf/
inflating: README
inflating: conf/FederationConfig.properties
inflating: conf/fedlet.cot-template
inflating: conf/idp-extended.xml-template
inflating: conf/sp-extended.xml-template
inflating: conf/sp.xml-template
inflating: fedlet.war
```

2. In each file, search and replace the following properties:

Replace this	With this
IDP_ENTITY_ID	openam
FEDLET_ENTITY_ID	sp
FEDLET_PROTOCOL://FEDLET_HOST:FEDLET_PORT/ FEDLET_DEPLOY_URI	http://sp.example.com:8080/saml
fedletcot and FEDLET_COT	Circle of Trust
sp.example.com:8080/saml/fedletapplication	sp.example.com:8080/saml/fedletapplication/ metaAlias/sp

3. Save the files as .xml, without the `-template` extension, so that the directory looks like this:

```
conf
├─ FederationConfig.properties
├─ fedlet.cot
├─ idp-extended.xml
├─ sp-extended.xml
└─ sp.xml
```

By default, AM as an IdP uses the NameID format `urn:oasis:names:tc:SAML:2.0:nameid-format:transient` to communicate about a user. For information about using a different NameID format, refer to [Non-transient SAML v2.0 NameID format](#).

3. Set up AM:

- 1. In the AM admin UI, select  **Identities**, select the user `demo`, and change the last name to `Ch4ng31t`. Note that, for this example, the last name must be the same as the password.

2. Select **Applications > Federation > Circles of Trust**, and add a circle of trust called `Circle of Trust`, with the default settings.
3. Set up a remote service provider:
 1. Select **Applications > Federation > Entity Providers**, and add a remote entity provider.
 2. Drag in or import `sp.xml` created in the previous step.
 3. Select **Circles of Trust**: `Circle of Trust`.
4. Set up a hosted identity provider:
 1. Select **Applications > Federation > Entity Providers**, and add a hosted entity provider with the following values:
 - **Entity ID**: `openam`
 - **Entity Provider Base URL**: `http://am.example.com:8088/openam`
 - **Identity Provider Meta Alias**: `idp`
 - **Circles of Trust**: `Circle of Trust`
 2. Select **Assertion Processing > Attribute Mapper**, map the following SAML attribute keys and values, and then save your changes:
 - **SAML Attribute**: `cn`, **Local Attribute**: `cn`
 - **SAML Attribute**: `sn`, **Local Attribute**: `sn`
 3. In a terminal, export the XML-based metadata for the IdP:

```
$ curl -v \  
--output idp.xml \  
"http://am.example.com:8088/openam/saml2/jsp/exportmetadata.jsp?entityid=openam"
```

The `idp.xml` file is created locally.

4. Set up PingGateway:

1. Copy the edited fedlet files, and the exported `idp.xml` file into the PingGateway configuration, at `$HOME/.openig/SAML`.

```
$ ls -l $HOME/.openig/SAML
```

Output

```
FederationConfig.properties
fedlet.cot
idp-extended.xml
idp.xml
sp-extended.xml
sp.xml
```

2. Don't use a `baseURI` setting.

Requests to the SamlFederationHandler must not be rebased because the request URI must match the endpoint in the SAML metadata.

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

4. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/saml-handler.json
```

Windows

```
%appdata%\OpenIG\config\routes\saml-handler.json
```

```
{
  "name": "saml-handler",
  "condition": "${find(request.uri.path, '^/saml')}",
  "handler": {
    "type": "SamlFederationHandler",
    "config": {
      "useOriginalUri": true,
      "assertionMapping": {
        "username": "cn",
        "password": "sn"
      },
      "subjectMapping": "sp-subject-name",
      "redirectURI": "/home/federate"
    }
  }
}
```

Source: [saml-handler.json](#)

Notice the following features of the route:

- The route matches requests to `/saml`.
- After authentication, the `SamlFederationHandler` extracts `cn` and `sn` from the SAML assertion, and maps them to the `SessionContext`, at `session.username` and `session.password`.
- The handler stores the subject name as a string in the session field `session.sp-subject-name`, which is named by the `subjectMapping` property. By default, the subject name is stored in the session field `session.subjectName`.
- The handler redirects the request to the `/federate` route.

5. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/federate-handler.json
```

Windows

```
%appdata%\OpenIG\config\routes\federate-handler.json
```

```

{
  "name": "federate-handler",
  "condition": "${find(request.uri.path, '^/home/federate')}",
  "baseURI": "http://app.example.com:8081",
  "handler": {
    "type": "DispatchHandler",
    "config": {
      "bindings": [
        {
          "condition": "${empty session.username}",
          "handler": {
            "type": "StaticResponseHandler",
            "config": {
              "status": 302,
              "headers": {
                "Location": [
                  "http://sp.example.com:8080/saml/SPInitiatedSSO?metaAlias=/sp"
                ]
              }
            }
          }
        }
      ],
      {
        "handler": {
          "type": "Chain",
          "config": {
            "filters": [
              {
                "type": "HeaderFilter",
                "config": {
                  "messageType": "REQUEST",
                  "add": {
                    "x-username": ["${session.username[0]}"],
                    "x-password": ["${session.password[0]}"]
                  }
                }
              }
            ],
            "handler": "ReverseProxyHandler"
          }
        }
      ]
    }
  }
}

```

Source: [federate-handler.json](#)

Notice the following features of the route:

- The route matches requests to `/home/federate`.
- If the user is not authenticated with AM, the username is not populated in the context. The DispatchHandler then dispatches the request to the StaticResponseHandler, which redirects it to the SP-initiated SSO endpoint.

If the credentials are in the context, or after successful authentication, the `DispatcherHandler` dispatches the request to the Chain.

- The `HeaderFilter` adds headers for the first value for the `username` and `password` attributes of the SAML assertion.

6. Restart PingGateway.

5. Test the setup:

1. Log out of AM, and test the setup with the following links:

- [IdP-initiated SSO](#)
- [SP-initiated SSO](#)

2. Log in to AM with username `demo` and password `Ch4ng31t`.

PingGateway returns the response page showing that the demo user has logged in.

Tip

For more control over the URL where the user agent is redirected, use the `RelayState` query string parameter in the URL of the redirect `Location` header. `RelayState` specifies where to redirect the user when the SAML 2.0 web browser SSO process is complete. It overrides the `redirectURI` set in the `SamlFederationHandler`. The `RelayState` value must be URL-encoded. When using an expression, use a function to encode the value. For example, use `${urlencodeQueryParameterNameOrValue(contexts.router.originalUri)}`. In the following example, the user is finally redirected to the original URI from the request:

```
"headers": {
  "Location": [
    "http://ig.example.com:8080/saml/SPInitiatedSSO?RelayState=${urlencodeQueryParameterNameOrValue(contexts.router.originalUri)}"
  ]
}
```

Signed/encrypted SAML v2.0 assertions

1. Set up the example in [Unsigned/unencrypted SAML v2.0 assertions](#).

2. Set up the SAML keystore:

1. Find the values of AM's default SAML keypass and storepass:

```
$ more /path/to/am/secrets/default/.keypass
$ more /path/to/am/secrets/default/.storepass
```

2. Copy the SAML keystore from the AM configuration to PingGateway:

```
$ cp /path/to/am/secrets/keystores/keystore.jceks /path/to/ig/secrets/keystore.jceks
```

Warning

Legacy keystore types such as JKS and JCEKS are supported but aren't secure. Consider using the PKCS#12 keystore type.

3. Configure the Fedlet in PingGateway:

1. In `FederationConfig.properties`, make the following changes:

1. Delete the following lines:

- `com.sun.identity.saml.xmlsig.keystore=%BASE_DIR%/security/keystores/keystore.jks`
- `com.sun.identity.saml.xmlsig.storepass=%BASE_DIR%/storepass`
- `com.sun.identity.saml.xmlsig.keypass=%BASE_DIR%/keypass`
- `com.sun.identity.saml.xmlsig.certalias=test`
- `com.sun.identity.saml.xmlsig.storetype=JKS`
- `am.encryption.pwd=@AM_ENC_PWD@`

2. Add the following line:

```
org.forgerock.openam.saml2.credential.resolver.class=org.forgerock.openig.handler.saml.SecretsSaml2CredentialResolver
```

This class is responsible for resolving secrets and supplying credentials.

Tip

Be sure to leave no space at the end of the line.

2. In `sp.xml`, make the following changes:

1. Change `AuthnRequestsSigned="false"` to `AuthnRequestsSigned="true"`.
2. Add the following KeyDescriptor just before `</SPSSODescriptor>`

```
<KeyDescriptor use="signing">
  <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#" >
    <ds:X509Data>
      <ds:X509Certificate>

      </ds:X509Certificate>
    </ds:X509Data>
  </ds:KeyInfo>
</KeyDescriptor>
</SPSSODescriptor>
```

3. Copy the value of the signing certificate from `idp.xml` to this file:

```
<KeyDescriptor use="signing">
  <ds:KeyInfo>
    <ds:X509Data>
      <ds:X509Certificate>

        MII...ZA6

      </ds:X509Certificate>
    </ds:X509Data>
  </ds:KeyInfo>
</KeyDescriptor>
```

This is the public key used for signing so that the IdP can verify request signatures.

4. Replace the remote service provider in AM:

1. Select **Applications > Federation > Entity Providers**, and remove the `sp` entity provider.
2. Drag in or import the new `sp.xml` updated in the previous step.
3. Select **Circles of Trust: Circle of Trust**.

5. Set up PingGateway:

1. In the PingGateway configuration, set environment variables for the following secrets, and then restart PingGateway:

```
$ export KEYSTORE_SECRET_ID='a2V5c3RvcmlU='
$ export SAML_KEYSTORE_STOREPASS_SECRET_ID='base64-encoded value of the SAML storepass'
$ export SAML_KEYSTORE_KEYPASS_SECRET_ID='base64-encoded value of the SAML keypass'
```

The passwords are retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

2. Remove `saml-handler.json` from the configuration and add the following route, replacing the path to `keystore.jceks` with your path:

Linux

```
$HOME/.openig/config/routes/saml-handler-secure.json
```

Windows

```
%appdata%\OpenIG\config\routes\saml-handler-secure.json
```



```

{
  "name": "saml-handler-secure",
  "condition": "${find(request.uri.path, '^/saml')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "KeyStoreSecretStore-1",
      "type": "KeyStoreSecretStore",
      "config": {
        "file": "/path/to/ig/keystore.jceks",
        "storeType": "jceks",
        "storePasswordSecretId": "saml.keystore.storepass.secret.id",
        "entryPasswordSecretId": "saml.keystore.keypass.secret.id",
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "mappings": [ {
          "secretId": "sp.signing.sp",
          "aliases": [ "rsajwt signingkey" ]
        }, {
          "secretId": "sp.decryption.sp",
          "aliases": [ "test" ]
        } ]
      }
    }
  ],
  "handler": {
    "type": "SamlFederationHandler",
    "config": {
      "useOriginalUri": true,
      "assertionMapping": {
        "username": "cn",
        "password": "sn"
      },
      "subjectMapping": "sp-subject-name",
      "redirectURI": "/home/federate",
      "secretsProvider": "KeyStoreSecretStore-1"
    }
  }
}

```

Source: [saml-handler-secure.json](#)

Notice the following features of the route compared to `saml-handler.json`:

- The `SamlFederationHandler` refers to the `KeyStoreSecretStore` to provide the keys for the signed and encrypted SAML assertions.
- The secret IDs, `sp.signing.sp` and `sp.decryption.sp`, follow a naming convention based on the name of the service provider, `sp`.
- The alias for the signing key corresponds to the PEM in `keystore.jceks`.

3. Restart PingGateway.

6. Test the setup:

1. Log out of AM, and test the setup with the following links:

- [IdP-initiated SSO](#)
- [SP-initiated SSO](#)

2. Log in to AM with username `demo` and password `Ch4ng31t`.

PingGateway returns the response page showing that the demo user has logged in.

SAML 2.0 and multiple applications

This page extends the previous example to add a second service provider.

The new service provider has entity ID `sp2` and runs on the host `sp2.example.com`. To prevent unwanted behavior, the service providers must have different values.

1. Add `sp2.example.com` to your `/etc/hosts` file:

```
127.0.0.1 localhost am.example.com ig.example.com app.example.com sp.example.com sp2.example.com
```

2. In PingGateway, configure the service provider files for `sp2`, using the files you created to configure the Fedlet.

1. In `fedlet.cot`, add `sp2` to the list of sun-fm-trusted-providers:

```
cot-name=Circle of Trust
sun-fm-cot-status=Active
sun-fm-trusted-providers=openam, sp, sp2
sun-fm-saml2-readerservice-url=
sun-fm-saml2-writerservice-url=
```

2. Copy `sp.xml` to `sp2.xml`, and copy `sp-extended.xml` to `sp2-extended.xml`.

3. In both files, search and replace the following strings:

- `entityID=sp`: replace with `entityID=sp2`
- `sp.example.com`: replace with `sp2.example.com`
- `metaAlias=/sp`: replace with `metaAlias=/sp2`
- `/metaAlias/sp`: replace with `/metaAlias/sp2`

4. Restart PingGateway.

3. In AM, set up a remote service provider for `sp2`:

1. Select **Applications > Federation > Entity Providers**.
2. Drag in or import `sp2.xml` created in the previous step.

3. Select **Circles of Trust**: **Circle of Trust**.

4. Add the following routes to PingGateway:

Linux

```
$HOME/.openig/config/routes/saml-handler-sp2.json
```

Windows

```
%appdata%\OpenIG\config\routes\saml-handler-sp2.json
```

```
{
  "name": "saml-handler-sp2",
  "condition": "${find(request.uri.host, 'sp2.example.com') and find(request.uri.path, '^/saml')}",
  "handler": {
    "type": "SamlFederationHandler",
    "config": {
      "comment": "Use unique session properties for this SP.",
      "useOriginalUri": true,
      "assertionMapping": {
        "sp2Username": "cn",
        "sp2Password": "sn"
      },
      "authnContext": "sp2AuthnContext",
      "sessionIndexMapping": "sp2SessionIndex",
      "subjectMapping": "sp2SubjectName",
      "redirectURI": "/sp2"
    }
  }
}
```

Source: [saml-handler-sp2.json](#)

Linux

```
$HOME/.openig/config/routes/federate-handler-sp2.json
```

Windows

```
%appdata%\OpenIG\config\routes\federate-handler-sp2.json
```

```

{
  "name": "federate-handler-sp2",
  "condition": "${find(request.uri.host, 'sp2.example.com') and not find(request.uri.path, '^/saml')}",
  "baseURI": "http://app.example.com:8081",
  "handler": {
    "type": "DispatchHandler",
    "config": {
      "bindings": [
        {
          "condition": "${empty session.sp2Username}",
          "handler": {
            "type": "StaticResponseHandler",
            "config": {
              "status": 302,
              "headers": {
                "Location": [
                  "http://sp2.example.com:8080/saml/SPInitiatedSSO?metaAlias=/sp2"
                ]
              }
            }
          }
        }
      ],
      "handler": {
        "type": "Chain",
        "config": {
          "filters": [
            {
              "type": "HeaderFilter",
              "config": {
                "messageType": "REQUEST",
                "add": {
                  "x-username": ["${session.sp2Username[0]}"],
                  "x-password": ["${session.sp2Password[0]}"]
                }
              }
            }
          ],
          "handler": "ReverseProxyHandler"
        }
      }
    }
  }
}

```

Source: [federate-handler-sp2.json](#)

5. Test the setup:

1. Log out of AM, and test the setup with the following links:

- [IdP-initiated SSO](#)
- [SP-initiated SSO](#)

2. Log in to AM with username `demo` and password `Ch4ng31t`.

PingGateway returns the response page showing that the user has logged in.

Additional topics

Non-transient SAML v2.0 NameID format

By default, AM as an IdP uses the NameID format `urn:oasis:names:tc:SAML:2.0:nameid-format:transient`. Learn more in the AM documentation on [Hosted identity provider configuration properties](#).

When the IdP uses another NameID format, configure PingGateway to use that NameID format by editing the Fedlet configuration file `sp-extended.xml`:

- To use the NameID value provided by the IdP, add the following attribute:

```
<Attribute name="useNameIDAsSPUserID">
  <Value>true</Value>
</Attribute>
```

- To use an attribute from the assertion, add the following attribute:

```
<Attribute name="autofedEnabled">
  <Value>true</Value>
</Attribute>
<Attribute name="autofedAttribute">
  <Value>sn</Value>
</Attribute>
```

This example uses the value in **SN** to identify the subject.

Although PingGateway supports the `persistent` NameID format, PingGateway doesn't store the mapping. To configure this behavior, edit the file `sp-extended.xml`:

- To disable attempts to persist the user mapping, add the following attribute:

```
<Attribute name="spDoNotWriteFederationInfo">
  <Value>true</Value>
</Attribute>
```

- To enable attempts to persist the user mapping, add the following attribute:

```
<Attribute name="spDoNotWriteFederationInfo">
  <Value>false</Value>
</Attribute>
```

If a sign on request doesn't contain a NameID format query parameter, the value is defined by the presence and content of the NameID format list for the SP and IdP. For example, an SP-initiated login can be constructed with the binding and **NameIDFormat** as a parameter, as follows:

```
http://fedlet.example.org:7070/fedlet/SPInitiatedSSO?binding=urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST&NameIDFormat=urn:oasis:names:tc:SAML:1.1:nameid-format:unspecified
```

When the NameID format is provided in a list, it is resolved as follows:

- If both the IdP and SP have a list, the first matching NameID format in the lists.
- If either the IdP or SP list is empty, the first NameID format in the other list.
- If neither the IdP nor SP has a list, AM defaults to **transient** and PingGateway defaults to **persistent**.

Example SAML v2.0 Fedlet files

PingGateway uses the PingAM Fedlet to act as a SAML v2.0 SP. This page provides example Fedlet configuration files PingGateway can use with specific IdPs.

These examples don't include settings for every possible scenario. Learn more about the Fedlet configuration in the AM documentation [Implement SAML v2.0 SPs by using Fedlets](#).

File	Description
<code>FederationConfig.properties</code>	Fedlet properties
<code>fedlet.cot</code>	Circle of trust for PingGateway and the IdP
<code>idp.xml</code>	Standard metadata for the IdP
<code>idp-extended.xml</code>	Metadata extensions for the IdP
<code>sp.xml</code>	Standard metadata for the PingGateway SP
<code>sp-extended.xml</code>	Metadata extensions for the PingGateway SP

AM as IdP

The following example of `$HOME/.openig/SAML/FederationConfig.properties` defines the fedlet properties:

```

#
# DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
#
# Copyright (c) 2006 Sun Microsystems Inc. All Rights Reserved
#
# The contents of this file are subject to the terms
# of the Common Development and Distribution License
# (the License). You may not use this file except in
# compliance with the License.
#
# You can obtain a copy of the License at
# https://opensso.dev.java.net/public/CDDLv1.0.html or
# opensso/legal/CDDLv1.0.txt
# See the License for the specific language governing
# permission and limitations under the License.
#
# When distributing Covered Code, include this CDDL
# Header Notice in each file and include the License file
# at opensso/legal/CDDLv1.0.txt.
# If applicable, add the following below the CDDL Header,
# with the fields enclosed by brackets [] replaced by
# your own identifying information:
# "Portions Copyrighted [year] [name of copyright owner]"
#
# $Id: FederationConfig.properties,v 1.21 2010/01/08 22:41:28 exu Exp $
#
# Portions Copyright 2016-2024 Ping Identity Corporation.

# If a component wants to use a different datastore provider than the
# default one defined above, it can define a property like follows:
# com.sun.identity.plugin.datastore.class.<componentName>=<provider class>

# com.sun.identity.plugin.configuration.class specifies implementation for
# com.sun.identity.plugin.configuration.ConfigurationInstance interface.
com.sun.identity.plugin.configuration.class=com.sun.identity.plugin.configuration.impl.FedletConfigurationImpl

# Specifies implementation for
# com.sun.identity.plugin.datastore.DataStoreProvider interface.
# This property defines the default datastore provider.
com.sun.identity.plugin.datastore.class.default=com.sun.identity.plugin.datastore.impl.FedletDataStoreProvider

# Specifies implementation for
# org.forgerock.openam.federation.plugin.rooturl.RootUrlProvider interface.
# This property defines the default base url provider.
com.sun.identity.plugin.root.url.class.default=org.forgerock.openam.federation.plugin.rooturl.impl.FedletRootUrlProvider

# com.sun.identity.plugin.log.class specifies implementation for
# com.sun.identity.plugin.log.Logger interface.
com.sun.identity.plugin.log.class=com.sun.identity.plugin.log.impl.FedletLogger

# com.sun.identity.plugin.session.class specifies implementation for
# com.sun.identity.plugin.session.SessionProvider interface.
com.sun.identity.plugin.session.class=com.sun.identity.plugin.session.impl.FedletSessionProvider

# com.sun.identity.plugin.monitoring.agent.class specifies implementation for
# com.sun.identity.plugin.monitoring.FedMonAgent interface.
com.sun.identity.plugin.monitoring.agent.class=com.sun.identity.plugin.monitoring.impl.FedletAgentProvider

# com.sun.identity.plugin.monitoring.saml2.class specifies implementation for

```

```

# com.sun.identity.plugin.monitoring.FedMonSAML2Svc interface.
com.sun.identity.plugin.monitoring.saml2.class=com.sun.identity.plugin.monitoring.impl.FedletMonSAML2SvcProvider

# com.sun.identity.saml.xmlsig.keyprovider.class specified the implementation
# class for com.sun.identity.saml.xmlsig.KeyProvider interface
com.sun.identity.saml.xmlsig.keyprovider.class=com.sun.identity.saml.xmlsig.JKSKeyProvider

# com.sun.identity.saml.xmlsig.signatureprovider.class specified the
# implementation class for com.sun.identity.saml.xmlsig.SignatureProvider
# interface
com.sun.identity.saml.xmlsig.signatureprovider.class=com.sun.identity.saml.xmlsig.AMSignatureProvider

com.ipplanet.am.server.protocol=http
com.ipplanet.am.server.host=am.example.com
com.ipplanet.am.server.port=8080
com.ipplanet.am.services.deploymentDescriptor=/openam
com.ipplanet.am.logstatus=ACTIVE

# Name of the webcontainer.
# Even though the servlet/JSP are web container independent,
# Access/Federation Manager uses servlet 2.3 API request.setCharacterEncoding()
# to decode incoming non English characters. These APIs will not work if
# Access/Federation Manager is deployed on Sun Java System Web Server 6.1.
# We use gx_charset mechanism to correctly decode incoming data in
# Sun Java System Web Server 6.1 and S1AS7.0. Possible values
# are BEA6.1, BEA 8.1, IBM5.1 or IAS7.0.
# If the web container is Sun Java System Webserver, the tag is not replaced.
com.sun.identity.webcontainer=WEB_CONTAINER

# Identify saml xml signature keystore file, keystore password file
# key password file
com.sun.identity.saml.xmlsig.keystore=%BASE_DIR%/security/kestores/keystore.jks
com.sun.identity.saml.xmlsig.storepass=%BASE_DIR%/.storepass
com.sun.identity.saml.xmlsig.keypass=%BASE_DIR%/.keypass
com.sun.identity.saml.xmlsig.certalias=test

# Type of keystore used for saml xml signature. Default is JKS.
#
# com.sun.identity.saml.xmlsig.storetype=JKS

# Specifies the implementation class for
# com.sun.identity.saml.xmlsig.PasswordDecoder interface.
com.sun.identity.saml.xmlsig.passwordDecoder=com.sun.identity.fedlet.FedletEncodeDecode

# The following key is used to specify the maximum content-length
# for an HttpRequest that will be accepted by the OpenSSO
# The default value is 16384 which is 16k
com.ipplanet.services.comm.server.pllrequest.maxContentLength=16384

# The following keys are used to configure the Debug service.
# Possible values for the key 'level' are: off | error | warning | message.
# The key 'directory' specifies the output directory where the debug files
# will be created.
# Trailing spaces are significant.
# Windows: Use forward slashes "/" separate directories, not backslash "\".
# Windows: Spaces in the file name are allowed for Windows.
#
com.ipplanet.services.debug.level=message
com.ipplanet.services.debug.directory=%BASE_DIR%SERVER_URI%/debug

# The following keys are used to configure the Stats service.
# Possible values for the key 'level' are: off | file | console

```



```
# Stats state 'file' will write to a file under the specified directory,
# and 'console' will write into webserver log files
# The key 'directory' specifies the output directory where the debug files
# will be created.
# Trailing spaces are significant.
# Windows: Use forward slashes "/" separate directories, not backslash "\".
# Windows: Spaces in the file name are allowed for Windows.
# Stats interval should be atleast 5 secs to avoid CPU saturation,
# the product would assume any thing less than 5 secs is 5 secs.
com.ipplanet.am.stats.interval=60
com.ipplanet.services.stats.state=file
com.ipplanet.services.stats.directory=%BASE_DIR%/var/stats

# The key that will be used to encrypt and decrypt passwords.
am.encryption.pwd=@AM_ENC_PWD@

# SecureRandom Properties: The key
# "com.ipplanet.security.SecureRandomFactoryImpl"
# specifies the factory class name for SecureRandomFactory
# Available impl classes are:
#   com.ipplanet.am.util.JSSSecureRandomFactoryImpl (uses JSS)
#   com.ipplanet.am.util.SecureRandomFactoryImpl (pure Java)
com.ipplanet.security.SecureRandomFactoryImpl=com.ipplanet.am.util.SecureRandomFactoryImpl

# SocketFactory properties: The key "com.ipplanet.security.SSLSocketFactoryImpl"
# specifies the factory class name for LDAPSocketFactory
# Available classes are:
#   com.ipplanet.services.ldap.JSSSocketFactory (uses JSS)
#   com.sun.identity.shared.ldap.factory.JSSESocketFactory (pure Java)
com.ipplanet.security.SSLSocketFactoryImpl=com.sun.identity.shared.ldap.factory.JSSESocketFactory

# Encryption: The key "com.ipplanet.security.encryptor" specifies
# the encrypting class implementation.
# Available classes are:
#   com.ipplanet.services.util.JCEEncryption
#   com.ipplanet.services.util.JSSEncryption
com.ipplanet.security.encryptor=com.ipplanet.services.util.JCEEncryption

# Determines if JSS will be added with highest priority to JCE
# Set this to "true" if other JCE providers should be used for
# digital signatures and encryptions.
com.sun.identity.jss.donotInstallAtHighestPriority=true

# Configuration File (serverconfig.xml) Location
com.ipplanet.services.configpath=@BASE_DIR@
```

Source: [FederationConfig.properties](#)

The following example of `$HOME/.openig/SAML/fed1et.cot` defines a circle of trust between AM as the IdP and PingGateway as the SP:

```
cot-name=Circle of Trust
sun-fm-cot-status=Active
sun-fm-trusted-providers=openam, sp
sun-fm-saml2-readerservice-url=
sun-fm-saml2-writerservice-url=
```

Source: [fedlet.cot](#)

The following example of `$HOME/.openig/SAML/idp.xml` defines a SAML configuration file for the AM IdP, `idp`:

```

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<EntityDescriptor entityID="openam" xmlns="urn:oasis:names:tc:SAML:2.0:metadata"
xmlns:query="urn:oasis:names:tc:SAML:metadata:ext:query" xmlns:mdattr="urn:oasis:names:tc:SAML:metadata:attribute"
xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion" xmlns:xenc="http://www.w3.org/2001/04/xmenc#"
xmlns:xenc11="http://www.w3.org/2009/xmenc11#" xmlns:alg="urn:oasis:names:tc:SAML:metadata:algsupport"
xmlns:x509qry="urn:oasis:names:tc:SAML:metadata:X509:query" xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
  <IDPSSODescriptor protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    <KeyDescriptor use="signing">
      <ds:KeyInfo>
        <ds:X509Data>
          <ds:X509Certificate>
            ...
          </ds:X509Certificate>
        </ds:X509Data>
      </ds:KeyInfo>
    </KeyDescriptor>
    <KeyDescriptor use="encryption">
      <ds:KeyInfo>
        <ds:X509Data>
          <ds:X509Certificate>
            ...
          </ds:X509Certificate>
        </ds:X509Data>
      </ds:KeyInfo>
      <EncryptionMethod Algorithm="http://www.w3.org/2009/xmenc11#rsa-oaep">
        <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmenc#sha256"/>
        <xenc11:MGF Algorithm="http://www.w3.org/2009/xmenc11#mgf1sha256"/>
      </EncryptionMethod>
      <EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmenc#aes128-cbc">
        <xenc:KeySize>128</xenc:KeySize>
      </EncryptionMethod>
    </KeyDescriptor>
    <ArtifactResolutionService index="0" Binding="urn:oasis:names:tc:SAML:2.0:bindings:SOAP" Location="http://
am.example.com:8088/openam/ArtifactResolver/metaAlias/idp"/>
    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Redirect" Location="http://
am.example.com:8088/openam/IDPSloRedirect/metaAlias/idp" ResponseLocation="http://am.example.com:8088/openam/
IDPSloRedirect/metaAlias/idp"/>
    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST" Location="http://
am.example.com:8088/openam/IDPSloPOST/metaAlias/idp" ResponseLocation="http://am.example.com:8088/openam/IDPSloPOST/
metaAlias/idp"/>
    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:SOAP" Location="http://am.example.com:
8088/openam/IDPSloSoap/metaAlias/idp"/>
    <ManageNameIDService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Redirect" Location="http://
am.example.com:8088/openam/IDPMniRedirect/metaAlias/idp" ResponseLocation="http://am.example.com:8088/openam/
IDPMniRedirect/metaAlias/idp"/>
    <ManageNameIDService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST" Location="http://
am.example.com:8088/openam/IDPMniPOST/metaAlias/idp" ResponseLocation="http://am.example.com:8088/openam/IDPMniPOST/
metaAlias/idp"/>
    <ManageNameIDService Binding="urn:oasis:names:tc:SAML:2.0:bindings:SOAP" Location="http://am.example.com:
8088/openam/IDPMniSoap/metaAlias/idp"/>
    <NameIDFormat>urn:oasis:names:tc:SAML:2.0:nameid-format:persistent</NameIDFormat>
    <NameIDFormat>urn:oasis:names:tc:SAML:2.0:nameid-format:transient</NameIDFormat>
    <NameIDFormat>urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress</NameIDFormat>
    <NameIDFormat>urn:oasis:names:tc:SAML:1.1:nameid-format:unspecified</NameIDFormat>
    <NameIDFormat>urn:oasis:names:tc:SAML:1.1:nameid-format:WindowsDomainQualifiedName</NameIDFormat>
    <NameIDFormat>urn:oasis:names:tc:SAML:2.0:nameid-format:kerberos</NameIDFormat>
    <NameIDFormat>urn:oasis:names:tc:SAML:1.1:nameid-format:X509SubjectName</NameIDFormat>
    <SingleSignOnService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Redirect" Location="http://
am.example.com:8088/openam/SSORedirect/metaAlias/idp"/>
    <SingleSignOnService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST" Location="http://

```

```
am.example.com:8088/openam/SSOPOST/metaAlias/idp"/>
  <SingleSignOnService Binding="urn:oasis:names:tc:SAML:2.0:bindings:SOAP" Location="http://am.example.com:
8088/openam/SSOSoap/metaAlias/idp"/>
  <NameIDMappingService Binding="urn:oasis:names:tc:SAML:2.0:bindings:SOAP" Location="http://am.example.com:
8088/openam/NIMSoap/metaAlias/idp"/>
  <AssertionIDRequestService Binding="urn:oasis:names:tc:SAML:2.0:bindings:SOAP" Location="http://
am.example.com:8088/openam/AIDReqSoap/IDPRole/metaAlias/idp"/>
  <AssertionIDRequestService Binding="urn:oasis:names:tc:SAML:2.0:bindings:URI" Location="http://
am.example.com:8088/openam/AIDReqUri/IDPRole/metaAlias/idp"/>
  </IDPSSODescriptor>
</EntityDescriptor>
```

Source: [idp.xml](#)

The following example of `$HOME/.openig/SAML/idp-extended.xml` defines an AM SAML descriptor file for the IdP:

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<!--
  DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

  Copyright (c) 2002-2010 Sun Microsystems Inc. All Rights Reserved

  The contents of this file are subject to the terms
  of the Common Development and Distribution License
  (the License). You may not use this file except in
  compliance with the License.

  You can obtain a copy of the License at
  https://opensso.dev.java.net/public/CDDLv1.0.html or
  opensso/legal/CDDLv1.0.txt
  See the License for the specific language governing
  permission and limitations under the License.

  When distributing Covered Code, include this CDDL
  Header Notice in each file and include the License file
  at opensso/legal/CDDLv1.0.txt.
  If applicable, add the following below the CDDL Header,
  with the fields enclosed by brackets [] replaced by
  your own identifying information:
  "Portions Copyrighted [year] [name of copyright owner]"

  Portions Copyrighted 2010-2017 Ping Identity Corporation.
-->
<EntityConfig entityID="openam" hosted="0" xmlns="urn:sun:fm:SAML:2.0:entityconfig">
  <IDPSSOConfig>
    <Attribute name="description">
      <Value/>
    </Attribute>
    <Attribute name="cotlist">
      <Value>Circle of Trust</Value>
    </Attribute>
  </IDPSSOConfig>
  <AttributeAuthorityConfig>
    <Attribute name="cotlist">
      <Value>Circle of Trust</Value>
    </Attribute>
  </AttributeAuthorityConfig>
  <XACMLPDPCConfig>
    <Attribute name="wantXACMLAuthzDecisionQuerySigned">
      <Value></Value>
    </Attribute>
    <Attribute name="cotlist">
      <Value>Circle of Trust</Value>
    </Attribute>
  </XACMLPDPCConfig>
</EntityConfig>
```

Source: [idp-extended.xml](#) 

 Note

The SAML library component validates the SP's AssertionConsumerService Location against the incoming IdP SAML Assertion, based on the request information including the port. Always specify the port in the Location value of **AssertionConsumerService** even when using defaults of 443 or 80:

```
<AssertionConsumerService isDefault="true"
    index="0"
    Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
    Location="https://sp.example.com:443/fedletapplication" />
```

The following example of `$HOME/.openid/SAML/sp.xml` defines a SAML configuration file for the PingGateway SP, `sp`.

```

<!--
DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

Copyright (c) 2002-2010 Sun Microsystems Inc. All Rights Reserved

The contents of this file are subject to the terms
of the Common Development and Distribution License
(the License). You may not use this file except in
compliance with the License.

You can obtain a copy of the License at
https://opensso.dev.java.net/public/CDDLv1.0.html or
opensso/legal/CDDLv1.0.txt
See the License for the specific language governing
permission and limitations under the License.

When distributing Covered Code, include this CDDL
Header Notice in each file and include the License file
at opensso/legal/CDDLv1.0.txt.
If applicable, add the following below the CDDL Header,
with the fields enclosed by brackets [] replaced by
your own identifying information:
"Portions Copyrighted [year] [name of copyright owner]"

Portions Copyrighted 2010-2017 Ping Identity Corporation.
-->
<EntityDescriptor entityID="sp" xmlns="urn:oasis:names:tc:SAML:2.0:metadata">
  <SPSSODescriptor AuthnRequestsSigned="false" WantAssertionsSigned="false"
protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Redirect" Location="http://
sp.example.com:8080/saml/fedletSloRedirect" ResponseLocation="http://sp.example.com:8080/saml/fedletSloRedirect"/>
    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST" Location="http://
sp.example.com:8080/saml/fedletSloPOST" ResponseLocation="http://sp.example.com:8080/saml/fedletSloPOST"/>
    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:SOAP" Location="http://sp.example.com:
8080/saml/fedletSloSoap"/>
    <NameIDFormat>urn:oasis:names:tc:SAML:2.0:nameid-format:transient</NameIDFormat>
    <AssertionConsumerService isDefault="true" index="0" Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
Location="http://sp.example.com:8080/saml/fedletapplication/metaAlias/sp"/>
    <AssertionConsumerService index="1" Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Artifact"
Location="http://sp.example.com:8080/saml/fedletapplication/metaAlias/sp"/>
  </SPSSODescriptor>
  <RoleDescriptor xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:query="urn:oasis:names:tc:SAML:metadata:ext:query" xsi:type="query:AttributeQueryDescriptorType"
protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    </RoleDescriptor>
    <XACMLAuthzDecisionQueryDescriptor WantAssertionsSigned="false"
protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    </XACMLAuthzDecisionQueryDescriptor>
  </EntityDescriptor>

```

Source: [sp.xml](#)

The following example of `$HOME/.openid/SAML/sp-extended.xml` defines an AM SAML descriptor file for the SP:

```

<!--
DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

Copyright (c) 2002-2010 Sun Microsystems Inc. All Rights Reserved

The contents of this file are subject to the terms
of the Common Development and Distribution License
(the License). You may not use this file except in
compliance with the License.

You can obtain a copy of the License at
https://opensso.dev.java.net/public/CDDLv1.0.html or
opensso/legal/CDDLv1.0.txt
See the License for the specific language governing
permission and limitations under the License.

When distributing Covered Code, include this CDDL
Header Notice in each file and include the License file
at opensso/legal/CDDLv1.0.txt.
If applicable, add the following below the CDDL Header,
with the fields enclosed by brackets [] replaced by
your own identifying information:
"Portions Copyrighted [year] [name of copyright owner]"

Portions Copyrighted 2010-2017 Ping Identity Corporation.
-->
<EntityConfig xmlns="urn:sun:fm:SAML:2.0:entityconfig" xmlns:fm="urn:sun:fm:SAML:2.0:entityconfig" hosted="1"
entityID="sp">
  <SPSSOConfig metaAlias="/sp">
    <Attribute name="description">
      <Value></Value>
    </Attribute>
    <Attribute name="signingCertAlias">
      <Value></Value>
    </Attribute>
    <Attribute name="encryptionCertAlias">
      <Value></Value>
    </Attribute>
    <Attribute name="basicAuthOn">
      <Value>>false</Value>
    </Attribute>
    <Attribute name="basicAuthUser">
      <Value></Value>
    </Attribute>
    <Attribute name="basicAuthPassword">
      <Value></Value>
    </Attribute>
    <Attribute name="autofedEnabled">
      <Value>>false</Value>
    </Attribute>
    <Attribute name="autofedAttribute">
      <Value></Value>
    </Attribute>
    <Attribute name="transientUser">
      <Value>anonymous</Value>
    </Attribute>
    <Attribute name="spAdapter">
      <Value></Value>
    </Attribute>
    <Attribute name="spAdapterEnv">

```



```

        <Value></Value>
    </Attribute>
    <Attribute name="fedletAdapter">
        <Value></Value>
    </Attribute>
    <Attribute name="fedletAdapterEnv">
        <Value></Value>
    </Attribute>
    <Attribute name="spAccountMapper">
        <Value>com.sun.identity.saml2.plugins.DefaultLibrarySPAccountMapper</Value>
    </Attribute>
    <Attribute name="spAttributeMapper">
        <Value>com.sun.identity.saml2.plugins.DefaultSPAttributeMapper</Value>
    </Attribute>
    <Attribute name="spAuthncontextMapper">
        <Value>com.sun.identity.saml2.plugins.DefaultSPAuthnContextMapper</Value>
    </Attribute>
    <Attribute name="spAuthncontextClassrefMapping">
        <Value>urn:oasis:names:tc:SAML:2.0:ac:classes:PasswordProtectedTransport|0|default</Value>
    </Attribute>
    <Attribute name="spAuthncontextComparisonType">
        <Value>exact</Value>
    </Attribute>
    <Attribute name="attributeMap">
        <Value>*</Value>
    </Attribute>
    <Attribute name="saml2AuthModuleName">
        <Value></Value>
    </Attribute>
    <Attribute name="localAuthURL">
        <Value></Value>
    </Attribute>
    <Attribute name="intermediateUrl">
        <Value></Value>
    </Attribute>
    <Attribute name="defaultRelayState">
        <Value></Value>
    </Attribute>
    <Attribute name="appLogoutUrl">
        <Value>http://sp.example.com:8080/saml/logout</Value>
    </Attribute>
    <Attribute name="assertionTimeSkew">
        <Value>300</Value>
    </Attribute>
    <Attribute name="wantAttributeEncrypted">
        <Value></Value>
    </Attribute>
    <Attribute name="wantAssertionEncrypted">
        <Value></Value>
    </Attribute>
    <Attribute name="wantNameIDEncrypted">
        <Value></Value>
    </Attribute>
    <Attribute name="wantPOSTResponseSigned">
        <Value></Value>
    </Attribute>
    <Attribute name="wantArtifactResponseSigned">
        <Value></Value>
    </Attribute>
    <Attribute name="wantLogoutRequestSigned">
        <Value></Value>
    </Attribute>

```

```

    <Attribute name="wantLogoutResponseSigned">
      <Value></Value>
    </Attribute>
    <Attribute name="wantMNIRrequestSigned">
      <Value></Value>
    </Attribute>
    <Attribute name="wantMNIRresponseSigned">
      <Value></Value>
    </Attribute>
    <Attribute name="cotlist">
      <Value>Circle of Trust</Value></Attribute>
    <Attribute name="saeAppSecretList">
    </Attribute>
    <Attribute name="saeSPUrl">
      <Value></Value>
    </Attribute>
    <Attribute name="saeSPLogoutUrl">
    </Attribute>
    <Attribute name="ECPRequestIDPListFinderImpl">
      <Value>com.sun.identity.saml2.plugins.ECPIDPFinder</Value>
    </Attribute>
    <Attribute name="ECPRequestIDPList">
      <Value></Value>
    </Attribute>
    <Attribute name="enableIDPProxy">
      <Value>false</Value>
    </Attribute>
    <Attribute name="idpProxyList">
      <Value></Value>
    </Attribute>
    <Attribute name="idpProxyCount">
      <Value>0</Value>
    </Attribute>
    <Attribute name="useIntroductionForIDPProxy">
      <Value>false</Value>
    </Attribute>
  </SPSSOConfig>
  <AttributeQueryConfig metaAlias="/attrQuery">
    <Attribute name="signingCertAlias">
      <Value></Value>
    </Attribute>
    <Attribute name="encryptionCertAlias">
      <Value></Value>
    </Attribute>
    <Attribute name="wantNameIDEncrypted">
      <Value></Value>
    </Attribute>
    <Attribute name="cotlist">
      <Value>Circle of Trust</Value>
    </Attribute>
  </AttributeQueryConfig>
  <XACMLAuthzDecisionQueryConfig metaAlias="/pep">
    <Attribute name="signingCertAlias">
      <Value></Value>
    </Attribute>
    <Attribute name="encryptionCertAlias">
      <Value></Value>
    </Attribute>
    <Attribute name="basicAuthOn">
      <Value>false</Value>
    </Attribute>
    <Attribute name="basicAuthUser">

```

```
<Value></Value>
</Attribute>
<Attribute name="basicAuthPassword">
  <Value></Value>
</Attribute>
<Attribute name="wantXACMLAuthzDecisionResponseSigned">
  <Value></Value>
</Attribute>
<Attribute name="wantAssertionEncrypted">
  <Value></Value>
</Attribute>
<Attribute name="cotlist">
  <Value>Circle of Trust</Value>
</Attribute>
</XACMLAuthzDecisionQueryConfig>
</EntityConfig>
```

Source: [sp-extended.xml](#)

Find additional hints for extended SAML v2.0 SP (`sp-extended.xml`) settings in the AM documentation on [Service Provider Extended XML](#).

PingOne as IdP

```

# If a component wants to use a different datastore provider than the
# default one defined above, it can define a property like follows:
# com.sun.identity.plugin.datastore.class.<componentName>=<provider class>

# com.sun.identity.plugin.configuration.class specifies implementation for
# com.sun.identity.plugin.configuration.ConfigurationInstance interface.
com.sun.identity.plugin.configuration.class=com.sun.identity.plugin.configuration.impl.FedletConfigurationImpl

# Specifies implementation for
# com.sun.identity.plugin.datastore.DataStoreProvider interface.
# This property defines the default datastore provider.
com.sun.identity.plugin.datastore.class.default=com.sun.identity.plugin.datastore.impl.FedletDataStoreProvider

# Specifies implementation for
# org.forgerock.openam.federation.plugin.rooturl.RootUrlProvider interface.
# This property defines the default base url provider.
com.sun.identity.plugin.root.url.class.default=org.forgerock.openam.federation.plugin.rooturl.impl.FedletRootUrlProvider

# com.sun.identity.plugin.log.class specifies implementation for
# com.sun.identity.plugin.log.Logger interface.
com.sun.identity.plugin.log.class=com.sun.identity.plugin.log.impl.FedletLogger

# com.sun.identity.plugin.session.class specifies implementation for
# com.sun.identity.plugin.session.SessionProvider interface.
com.sun.identity.plugin.session.class=com.sun.identity.plugin.session.impl.FedletSessionProvider

# com.sun.identity.plugin.monitoring.agent.class specifies implementation for
# com.sun.identity.plugin.monitoring.FedMonAgent interface.
com.sun.identity.plugin.monitoring.agent.class=com.sun.identity.plugin.monitoring.impl.FedletAgentProvider

# com.sun.identity.plugin.monitoring.saml2.class specifies implementation for
# com.sun.identity.plugin.monitoring.FedMonSAML2Svc interface.
com.sun.identity.plugin.monitoring.saml2.class=com.sun.identity.plugin.monitoring.impl.FedletMonSAML2SvcProvider

# com.sun.identity.saml.xmlsig.keyprovider.class specified the implementation
# class for com.sun.identity.saml.xmlsig.KeyProvider interface
com.sun.identity.saml.xmlsig.keyprovider.class=com.sun.identity.saml.xmlsig.JKSKeyProvider

# com.sun.identity.saml.xmlsig.signatureprovider.class specified the
# implementation class for com.sun.identity.saml.xmlsig.SignatureProvider
# interface
com.sun.identity.saml.xmlsig.signatureprovider.class=com.sun.identity.saml.xmlsig.AMSignatureProvider

com.iplanet.am.server.protocol=http
com.iplanet.am.server.host=am.example.com
com.iplanet.am.server.port=8080
com.iplanet.am.services.deploymentDescriptor=/openam
com.iplanet.am.logstatus=ACTIVE

# Name of the webcontainer.
# Even though the servlet/JSP are web container independent,
# Access/Federation Manager uses servlet 2.3 API request.setCharacterEncoding()
# to decode incoming non English characters. These APIs will not work if
# Access/Federation Manager is deployed on Sun Java System Web Server 6.1.
# We use gx_charset mechanism to correctly decode incoming data in
# Sun Java System Web Server 6.1 and S1AS7.0. Possible values
# are BEA6.1, BEA 8.1, IBM5.1 or IAS7.0.
# If the web container is Sun Java System Webserver, the tag is not replaced.
com.sun.identity.webcontainer=WEB_CONTAINER

```

```

# Identify saml xml signature keystore file, keystore password file
# key password file
com.sun.identity.saml.xmlsig.keystore=%BASE_DIR%/security/kestores/keystore.jks
com.sun.identity.saml.xmlsig.storepass=%BASE_DIR%/.storepass
com.sun.identity.saml.xmlsig.keypass=%BASE_DIR%/.keypass
com.sun.identity.saml.xmlsig.certalias=test

# Type of keystore used for saml xml signature. Default is JKS.
#
# com.sun.identity.saml.xmlsig.storetype=JKS

# Specifies the implementation class for
# com.sun.identity.saml.xmlsig.PasswordDecoder interface.
com.sun.identity.saml.xmlsig.passwordDecoder=com.sun.identity.fedlet.FedletEncodeDecode

# The following key is used to specify the maximum content-length
# for an HttpRequest that will be accepted by the OpenSSO
# The default value is 16384 which is 16k
com.ipplanet.services.comm.server.pllrequest.maxContentLength=16384

# The following keys are used to configure the Debug service.
# Possible values for the key 'level' are: off | error | warning | message.
# The key 'directory' specifies the output directory where the debug files
# will be created.
# Trailing spaces are significant.
# Windows: Use forward slashes "/" separate directories, not backslash "\".
# Windows: Spaces in the file name are allowed for Windows.
#
com.ipplanet.services.debug.level=message
com.ipplanet.services.debug.directory=%BASE_DIR%SERVER_URI%/debug

# The following keys are used to configure the Stats service.
# Possible values for the key 'level' are: off | file | console
# Stats state 'file' will write to a file under the specified directory,
# and 'console' will write into webserver log files
# The key 'directory' specifies the output directory where the debug files
# will be created.
# Trailing spaces are significant.
# Windows: Use forward slashes "/" separate directories, not backslash "\".
# Windows: Spaces in the file name are allowed for Windows.
# Stats interval should be atleast 5 secs to avoid CPU saturation,
# the product would assume any thing less than 5 secs is 5 secs.
com.ipplanet.am.stats.interval=60
com.ipplanet.services.stats.state=file
com.ipplanet.services.stats.directory=%BASE_DIR%/var/stats

# The key that will be used to encrypt and decrypt passwords.
am.encryption.pwd=@AM_ENC_PWD@

# SecureRandom Properties: The key
# "com.ipplanet.security.SecureRandomFactoryImpl"
# specifies the factory class name for SecureRandomFactory
# Available impl classes are:
#   com.ipplanet.am.util.JSSSecureRandomFactoryImpl (uses JSS)
#   com.ipplanet.am.util.SecureRandomFactoryImpl (pure Java)
com.ipplanet.security.SecureRandomFactoryImpl=com.ipplanet.am.util.SecureRandomFactoryImpl

# SocketFactory properties: The key "com.ipplanet.security.SSLSocketFactoryImpl"
# specifies the factory class name for LDAPSocketFactory
# Available classes are:
#   com.ipplanet.services.ldap.JSSSocketFactory (uses JSS)

```

```
# com.sun.identity.shared.ldap.factory.JSSESocketFactory      (pure Java)
com.ipplanet.security.SSLSocketFactoryImpl=com.sun.identity.shared.ldap.factory.JSSESocketFactory

# Encryption: The key "com.ipplanet.security.encryptor" specifies
# the encrypting class implementation.
# Available classes are:
#   com.ipplanet.services.util.JCEEncryption
#   com.ipplanet.services.util.JSSEEncryption
com.ipplanet.security.encryptor=com.ipplanet.services.util.JCEEncryption

# Determines if JSS will be added with highest priority to JCE
# Set this to "true" if other JCE providers should be used for
# digital signatures and encryptions.
com.sun.identity.jss.donotInstallAtHighestPriority=true

# Configuration File (serverconfig.xml) Location
com.ipplanet.services.configpath=@BASE_DIR@
```

Source: [ping-FederationConfig.properties](#)

```
cot-name=Circle of Trust
sun-fm-cot-status=Active
sun-fm-trusted-providers=idp-entityID, sp
sun-fm-saml2-readerservice-url=
sun-fm-saml2-writerservice-url=
```

Source: [ping-fedlet.cot](#)

```
<EntityConfig entityID="idp-entityID" hosted="0" xmlns="urn:sun:fm:SAML:2.0:entityconfig">
  <IDPSSOConfig>
    <Attribute name="description">
      <Value/>
    </Attribute>
    <Attribute name="cotlist">
      <Value>Circle of Trust</Value>
    </Attribute>
  </IDPSSOConfig>
  <AttributeAuthorityConfig>
    <Attribute name="cotlist">
      <Value>Circle of Trust</Value>
    </Attribute>
  </AttributeAuthorityConfig>
  <XACMLPDPCConfig>
    <Attribute name="wantXACMLAuthzDecisionQuerySigned">
      <Value></Value>
    </Attribute>
    <Attribute name="cotlist">
      <Value>Circle of Trust</Value>
    </Attribute>
  </XACMLPDPCConfig>
</EntityConfig>
```

Source: [ping-idp-extended.xml](#)

```

<EntityDescriptor entityID="sp" xmlns="urn:oasis:names:tc:SAML:2.0:metadata">
  <SPSSODescriptor AuthnRequestsSigned="false" WantAssertionsSigned="false"
protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Redirect" Location="https://
sp.example.com:8443/home/saml/fedletSloRedirect" ResponseLocation="https://sp.example.com:8443/home/saml/
fedletSloRedirect" />
    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST" Location="https://
sp.example.com:8443/home/saml/fedletSloPOST" ResponseLocation="https://sp.example.com:8443/home/saml/fedletSloPOST" />
    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:SOAP" Location="https://sp.example.com:
8443/home/saml/fedletSloSoap" />
    <NameIDFormat>urn:oasis:names:tc:SAML:2.0:nameid-format:transient</NameIDFormat>
    <AssertionConsumerService isDefault="true" index="0" Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
Location="https://sp.example.com:8443/home/saml/fedletapplication" />
    <AssertionConsumerService index="1" Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Artifact"
Location="https://sp.example.com:8443/home/saml/fedletapplication" />
  </SPSSODescriptor>
  <RoleDescriptor xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:query="urn:oasis:names:tc:SAML:metadata:ext:query" xsi:type="query:AttributeQueryDescriptorType"
protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    </RoleDescriptor>
    <XACMLAuthzDecisionQueryDescriptor WantAssertionsSigned="false"
protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
      </XACMLAuthzDecisionQueryDescriptor>
    </EntityDescriptor>

```

Source: [ping-sp.xml](#) 


```

<EntityConfig xmlns="urn:sun:fm:SAML:2.0:entityconfig" xmlns:fm="urn:sun:fm:SAML:2.0:entityconfig" hosted="1"
entityID="sp">
  <SPSSOConfig metaAlias="/sp">
    <Attribute name="description">
      <Value></Value>
    </Attribute>
    <Attribute name="signingCertAlias">
      <Value></Value>
    </Attribute>
    <Attribute name="encryptionCertAlias">
      <Value></Value>
    </Attribute>
    <Attribute name="basicAuthOn">
      <Value>false</Value>
    </Attribute>
    <Attribute name="basicAuthUser">
      <Value></Value>
    </Attribute>
    <Attribute name="basicAuthPassword">
      <Value></Value>
    </Attribute>
    <Attribute name="autofedEnabled">
      <Value>false</Value>
    </Attribute>
    <Attribute name="autofedAttribute">
      <Value></Value>
    </Attribute>
    <Attribute name="transientUser">
      <Value>anonymous</Value>
    </Attribute>
    <Attribute name="spAdapter">
      <Value></Value>
    </Attribute>
    <Attribute name="spAdapterEnv">
      <Value></Value>
    </Attribute>
    <Attribute name="fedletAdapter">
      <Value></Value>
    </Attribute>
    <Attribute name="fedletAdapterEnv">
      <Value></Value>
    </Attribute>
    <Attribute name="spAccountMapper">
      <Value>com.sun.identity.saml2.plugins.DefaultLibrarySPAccountMapper</Value>
    </Attribute>
    <Attribute name="spAttributeMapper">
      <Value>com.sun.identity.saml2.plugins.DefaultSPAttributeMapper</Value>
    </Attribute>
    <Attribute name="spAuthncontextMapper">
      <Value>com.sun.identity.saml2.plugins.DefaultSPAuthnContextMapper</Value>
    </Attribute>
    <Attribute name="spAuthncontextClassrefMapping">
      <Value>urn:oasis:names:tc:SAML:2.0:ac:classes:unspecified|0|default</Value>
    </Attribute>
    <Attribute name="spAuthncontextComparisonType">
      <Value>exact</Value>
    </Attribute>
    <Attribute name="attributeMap">
      <Value>*</Value>
    </Attribute>
  </SPSSOConfig>
</EntityConfig>

```

```
<Attribute name="saml2AuthModuleName">
  <Value></Value>
</Attribute>
<Attribute name="localAuthURL">
  <Value></Value>
</Attribute>
<Attribute name="intermediateUrl">
  <Value></Value>
</Attribute>
<Attribute name="defaultRelayState">
  <Value></Value>
</Attribute>
<Attribute name="appLogoutUrl">
  <Value>https://sp.example.com:8443/home/saml/logout</Value>
</Attribute>
<Attribute name="assertionTimeSkew">
  <Value>300</Value>
</Attribute>
<Attribute name="wantAttributeEncrypted">
  <Value></Value>
</Attribute>
<Attribute name="wantAssertionEncrypted">
  <Value></Value>
</Attribute>
<Attribute name="wantNameIDEncrypted">
  <Value></Value>
</Attribute>
<Attribute name="wantPOSTResponseSigned">
  <Value></Value>
</Attribute>
<Attribute name="wantArtifactResponseSigned">
  <Value></Value>
</Attribute>
<Attribute name="wantLogoutRequestSigned">
  <Value></Value>
</Attribute>
<Attribute name="wantLogoutResponseSigned">
  <Value></Value>
</Attribute>
<Attribute name="wantMNIRRequestSigned">
  <Value></Value>
</Attribute>
<Attribute name="wantMNIRResponseSigned">
  <Value></Value>
</Attribute>
<Attribute name="cotlist">
  <Value>Circle of Trust</Value></Attribute>
<Attribute name="saeAppSecretList">
</Attribute>
<Attribute name="saeSPUrl">
  <Value></Value>
</Attribute>
<Attribute name="saeSPLogoutUrl">
</Attribute>
<Attribute name="ECPRequestIDPLListFinderImpl">
  <Value>com.sun.identity.saml2.plugins.ECPIDPFinder</Value>
</Attribute>
<Attribute name="ECPRequestIDPLList">
  <Value></Value>
</Attribute>
<Attribute name="enableIDPProxy">
  <Value>>false</Value>
```

```

</Attribute>
<Attribute name="idpProxyList">
  <Value></Value>
</Attribute>
<Attribute name="idpProxyCount">
  <Value>0</Value>
</Attribute>
<Attribute name="useIntroductionForIDPProxy">
  <Value>>false</Value>
</Attribute>
</SPSSOConfig>
<AttributeQueryConfig metaAlias="/attrQuery">
  <Attribute name="signingCertAlias">
    <Value></Value>
  </Attribute>
  <Attribute name="encryptionCertAlias">
    <Value></Value>
  </Attribute>
  <Attribute name="wantNameIDEncrypted">
    <Value></Value>
  </Attribute>
  <Attribute name="cotlist">
    <Value>Circle of Trust</Value>
  </Attribute>
</AttributeQueryConfig>
<XACMLAuthzDecisionQueryConfig metaAlias="/pep">
  <Attribute name="signingCertAlias">
    <Value></Value>
  </Attribute>
  <Attribute name="encryptionCertAlias">
    <Value></Value>
  </Attribute>
  <Attribute name="basicAuthOn">
    <Value>>false</Value>
  </Attribute>
  <Attribute name="basicAuthUser">
    <Value></Value>
  </Attribute>
  <Attribute name="basicAuthPassword">
    <Value></Value>
  </Attribute>
  <Attribute name="wantXACMLAuthzDecisionResponseSigned">
    <Value></Value>
  </Attribute>
  <Attribute name="wantAssertionEncrypted">
    <Value></Value>
  </Attribute>
  <Attribute name="cotlist">
    <Value>Circle of Trust</Value>
  </Attribute>
</XACMLAuthzDecisionQueryConfig>
</EntityConfig>

```

Source: [ping-sp-extended.xml](#)

Find additional hints for extended SAML v2.0 SP (`sp-extended.xml`) settings in the AM documentation on [Service Provider Extended XML](#).

Token transformation with PingAM


- [OIDC ID tokens to SAML assertions with PingAM](#)
- [OAuth 2.0 token exchange with PingAM](#)

OIDC ID tokens to SAML assertions with PingAM

This page builds on the example in [OpenID Connect and PingAM](#) to transform OpenID Connect ID tokens into SAML 2.0 assertions.


Many enterprises use existing or legacy, SAML 2.0-based SSO, but many mobile and social applications are managed by OpenID Connect. Use the PingGateway `TokenTransformationFilter` to bridge the gap between OpenID Connect and SAML 2.0 frameworks.

The following figure illustrates the data flow:



1. A user tries to access a protected resource.
2. If the user isn't authenticated, the `AuthorizationCodeOAuth2ClientFilter` redirects the request to AM. After authentication, AM asks for the user's consent to give PingGateway access to private information.
3. If the user consents, AM returns an `id_token` to the `AuthorizationCodeOAuth2ClientFilter`. The filter opens the `id_token` JWT and makes it available in `attributes.openid.id_token` and `attributes.openid.id_token_claims` for downstream filters.
4. The `TokenTransformationFilter` calls the AM STS to transform the `id_token` into a SAML 2.0 assertion.
5. The STS validates the signature, decodes the payload, and verifies the user issued the transaction. The STS then issues a SAML assertion to PingGateway on behalf of the user.
6. The `TokenTransformationFilter` puts the SAML assertion in `${contexts.sts.issuedToken}`.

The following sequence diagram shows a more detailed view of the flow:



Update AM settings

Before you start, set up and test the example in [AM as OIDC provider](#).

The following example uses an authentication tree for the [Security Token Service \(STS\)](#) to validate the incoming ID token and map its subject to an account.

Token signing

Change the token signature algorithm in the `oidc_client` profile.

1. In the AM admin UI, select **Applications > OAuth 2.0 > Clients > oidc_client**.
2. Under **Signing and Encryption**, set **ID Token Signing Algorithm** to `HS256` and click **Save Changes**.

Client secret

Store the client secret in a secret store.

1. Go to <http://am.example.com:8088/openam/encode.jsp> and use the page to encode the client secret, `password`.
2. Write the result to a AM default password secret store file named `clientpass`:

```
$ echo -n <encoded-client-secret> > /path/to/openam/security/secrets/encrypted/clientpass
```

**Tip**

In production, use your own secret store.

ID token normalization script

Create a script to normalize the ID token for the STS.

1. Select **</> Scripts > + New Script**.
2. Create a script with the following settings:
 - **Name:** `Normalize id_token`
 - **Script Type:** `Social Identity Provider Profile Transformation`
 - **Language:** `JavaScript`
 - **Evaluator Version:** `Legacy`
3. In the script editor, add the following JavaScript and click **Save Changes**:

```
// The ID token "subname" claim holds the account username:
(function () {
  var fr = JavaImporter( org.forgerock.json.JsonValue);
  var identity = fr.JsonValue.json(fr.JsonValue.object());
  identity.put('userName', jwtClaims.get('subname'));
  return identity;
})();
```

Account mapping script

Create a script to map the normalized ID token to the AM account username.


1. Select **</> Scripts > + New Script**.
2. Create a script with the following settings:
 - **Name:** `Add username to shared state`
 - **Script Type:** `Decision node script for authentication trees`
 - **Evaluator Version:** `Next Generation`
3. In the script editor, add the following JavaScript and click **Save Changes**:

```
// Get the username from the identity returned by the previous script:
var attributes = nodeState.get("lookupAttributes");
var userName = attributes.get("userName");
nodeState.putShared("username", userName);
action.goTo('true');
```

Tree for STS

Add a tree to validate the incoming ID token and map its subject to the AM demo user account.

1. Select **Authentication > Trees > + Create Tree**.
2. Name the new tree **TransformIdToken**.
3. Add nodes to the tree as in the following image:



- The **OIDC ID Token Validator** [node](#) lets the STS validate the incoming ID token.

The node has the following non-default settings:

- **OpenID Connect Validation Type:** `Client Secret`
- **OpenID Connect Validation Value:** `password` (Although required, the value isn't used.)
- **Client Secret Label:** `clientpass`
- **Token Issuer:** `http://am.example.com:8088/openam/oauth2`
- **Audience name:** `oidc_client`
- **Authorized parties:** `oidc_client`
- **Transformation Script:** `Normalize id_token`

- The **Scripted Decision** [node](#) maps the ID token subject claim to an AM username.

The node has the following non-default settings:

- **Script:** `Add username to shared state`
- **Outcomes:** `true`

4. Click **Save**.

Add REST STS

Add a REST STS instance to transform the ID token to a SAML v2.0 assertion.

1. Click **STS > + Add Rest STS**, add the following non-default settings:

Deployment URL Element

`openig` (must match the TokenTransformationFilter `"instance"`)

Deployment

- **Authentication Target Mappings:** replace the existing `OPENIDCONNECT|...` value with:

`OPENIDCONNECT|service|TransformIdToken|oidc_id_token_auth_target_header_key=oidc_id_token`

SAML2 Token

Note

For STS, it isn't necessary to create a SAML SP configuration in AM.

- **SAML2 issuer Id:** `OpenAM`
- **Service Provider Entity Id:** `openig_sp`
- **NameIdFormat:** `urn:oasis:names:tc:SAML:2.0:nameid-format:transient`

OpenID Connect Token

- **OpenID Connect Token Provider Issuer Id:** `oidc`
- **Token signature algorithm:** `HMAC SHA 256`
- **Client Secret:** `password`
- **Issued Tokens Audience:** `oidc_client`

2. Click **Create**.
3. Under **SAML 2 Token** on the new STS instance, add the following **Attribute Mappings**:
 - **Key:** `userName` , **Value:** `uid`
 - **Key:** `password` , **Value:** `mail`
4. Click **Save Changes**.

Configure PingGateway

1. Set environment variables for `oidc_client` and `ig_agent` , then restart PingGateway:

```
$ export OIDC_SECRET_ID='cGFzc3dvcmQ='
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```


2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/50-identity.json
```

Windows

```
%appdata%\OpenIG\config\routes\50-identity.json
```

```

{
  "name": "50-idtoken",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/id_token')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AuthenticatedRegistrationHandler-1",
      "type": "Chain",
      "config": {
        "filters": [
          {
            "name": "ClientSecretBasicAuthenticationFilter-1",
            "type": "ClientSecretBasicAuthenticationFilter",
            "config": {
              "clientId": "oidc_client",
              "clientSecretId": "oidc.secret.id",
              "secretsProvider": "SystemAndEnvSecretStore-1"
            }
          }
        ],
        "handler": "ForgeRockClientHandler"
      }
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "AuthorizationCodeOAuth2ClientFilter-1",
          "type": "AuthorizationCodeOAuth2ClientFilter",
          "config": {
            "clientEndpoint": "/home/id_token",
            "failureHandler": {
              "type": "StaticResponseHandler",
              "config": {
                "status": 500,
                "headers": {
                  "Content-Type": [
                    "text/plain"
                  ]
                }
              },
              "entity": "An error occurred during the OAuth2 setup."
            }
          }
        }
      ]
    }
  }
}

```

```

    },
    "registrations": [
      {
        "name": "oidc-user-info-client",
        "type": "ClientRegistration",
        "config": {
          "clientId": "oidc_client",
          "issuer": {
            "name": "Issuer",
            "type": "Issuer",
            "config": {
              "wellKnownEndpoint": "http://am.example.com:8088/openam/oauth2/.well-known/openid-
configuration"
            }
          },
          "clientSecretIdUsage": "ID_TOKEN_VALIDATION_ONLY",
          "secretsProvider": "SystemAndEnvSecretStore-1",
          "clientSecretId": "oidc.secret.id",
          "scopes": [
            "openid",
            "profile",
            "email"
          ],
          "authenticatedRegistrationHandler": "AuthenticatedRegistrationHandler-1"
        }
      }
    ],
    "requireHttps": false,
    "cacheExpiration": "disabled"
  }
},
{
  "name": "TokenTransformationFilter-1",
  "type": "TokenTransformationFilter",
  "config": {
    "idToken": "${attributes.openid.id_token}",
    "instance": "openig",
    "amService": "AmService-1"
  }
}
],
"handler": {
  "type": "StaticResponseHandler",
  "config": {
    "status": 200,
    "headers": {
      "Content-Type": [ "text/plain; charset=UTF-8" ]
    },
    "entity": "{\n  \"id_token\": \"\n${attributes.openid.id_token}\n\" }\n\n{\n  \"saml_assertions\": \"\n${
{contexts.sts.issuedToken}\n\" }"
  }
}
}
}
}
}

```

Source: [50-idtoken.json](#)

Learn how to use Studio to set up the PingGateway route in [Token transformation in Structured Editor](#).

Notice the following features of the route:

- The route matches requests to `/home/id_token`.
- The `AmService` in the heap is used for authentication and REST STS requests.
- The `AuthorizationCodeOAuth2ClientFilter` enables PingGateway to act as an OIDC relying party:
 - The client endpoint is `/home/id_token`, so the service URIs for this filter in PingGateway are `/home/id_token/login`, `/home/id_token/logout`, and `/home/id_token/callback`.
 - For convenience in this test, `requireHttps` is false.
 - The target for storing authorization state information is `${attributes.openid}`. Later filters and handlers can find access tokens and user information at this target.
- The `ClientRegistration` holds configuration provided in [AM as OIDC provider](#). PingGateway uses it to connect to AM and verify the ID token signature with the client secret.
- The `TokenTransformationFilter` transforms an ID token into a SAML assertion:
 - The `id_token` parameter defines where this filter gets the ID token.

The `TokenTransformationFilter` puts the result in `${contexts.sts.issuedToken}`.
- On success, a `StaticResponseHandler` displays the ID token and SAML assertion.

Validation

1. In your browser's privacy or incognito mode, go to https://ig.example.com:8443/home/id_token.

AM displays the login screen.

2. Log in to AM as username `demo`, password `Ch4ng31t`.

AM prompts you to allow access to your account information.

3. Select **Allow**.

The `StaticResponseHandler` displays the ID token and SAML assertion:

```
{ "id_token":
  "<id-token>"
}

{ "saml_assertions":
  "...<saml:Subject><saml:NameID...>demo</saml:NameID>..." }
```

Tip

If a request returns an HTTP 414 URI Too Long error, refer to [URI Too Long error](#).

OAuth 2.0 token exchange with PingAM


This page describes how to exchange an OAuth 2.0 access token for another access token with AM as an Authorization Server. Other authorization providers can be used instead of AM.

Token exchange requires a *subject token* and provides an *issued token*. The subject token is the original access token, obtained using the OAuth 2.0/OpenID Connect flow. The issued token is provided in exchange for the subject token.

The token exchange can be conducted only by an OAuth 2.0 client that "may act" on the subject token, as configured in the authorization service.

This example is a typical scenario for *token impersonation*. For more information, refer to [Token exchange](#) in the AM documentation.

The following sequence diagram shows the flow of information during token exchange between PingGateway and AM:



Important

This procedure uses the *Resource Owner Password Credentials* grant type. As suggested in [The OAuth 2.0 Authorization Framework](#), use other grant types whenever possible.

Before you begin, prepare AM, PingGateway, and the sample application. Learn more in the [example installation for this guide](#).

1. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`

- `https://ig.example.com:8443/*?*`

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`
- **Token Introspection:** `Realm Only`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

3. Select **Services > Add a Service**, and add an **OAuth2 Provider** service with the following values:

- **OAuth2 Access Token May Act Script:** `OAuth2 May Act Script`
- **OAuth2 ID Token May Act Script:** `OAuth2 May Act Script`

4. Select **</> Scripts# > OAuth2 May Act Script**, and replace the example script with the following script:

```
import org.forgerock.json.JsonValue
token.setMayAct(
  JsonValue.json(JsonValue.object(
    JsonValue.field("client_id", "serviceConfidentialClient"))))
```

This script adds a `may_act` claim to the token, indicating that the OAuth 2.0 client, `serviceConfidentialClient`, may act to exchange the subject token in the impersonation use case.

5. Add an OAuth 2.0 Client to request OAuth 2.0 access tokens:

1. Select **Applications > OAuth 2.0 > Clients**, and add a client with the following values:

- **Client ID:** `client-application`
- **Client secret:** `password`
- **Scope(s):** `mail`, `employeenumber`

2. On the **Advanced** tab, select **Grant Types:** `Resource Owner Password Credentials`.

6. Add an OAuth 2.0 client to perform the token exchange:

1. Select **Applications > OAuth 2.0 > Clients**, and add a client with the following values:

- **Client ID:** `serviceConfidentialClient`
- **Client secret:** `password`
- **Scope(s):** `mail`, `employeenumber`

2. On the **Advanced** tab, select:

- **Grant Types:** `Token Exchange`

■ Token Endpoint Authentication Methods : `client_secret_post`

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set the following environment variables for the serviceConfidentialClient password:

```
$ export CLIENT_SECRET_ID='cGFzc3dvcmQ='
```

3. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

4. Add the following route to PingGateway to exchange the access token:

Linux

```
$HOME/.openig/config/routes/token-exchange.json
```

Windows

```
%appdata%\OpenIG\config\routes\token-exchange.json
```

```

{
  "name": "token-exchange",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/token-exchange')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    },
    {
      "name": "ExchangeHandler",
      "type": "Chain",
      "capture": "all",
      "config": {
        "handler": "ForgeRockClientHandler",
        "filters": [
          {
            "type": "ClientSecretBasicAuthenticationFilter",
            "config": {
              "clientId": "serviceConfidentialClient",
              "clientSecretId": "client.secret.id",
              "secretsProvider": "SystemAndEnvSecretStore-1"
            }
          }
        ]
      }
    },
    {
      "name": "ExchangeFailureHandler",
      "type": "StaticResponseHandler",
      "capture": "all",
      "config": {
        "status": 400,
        "entity": "${contexts.oauth2Failure.error}: ${contexts.oauth2Failure.description}",
        "headers": {
          "Content-Type": [
            "application/json"
          ]
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "oauth2TokenExchangeFilter",

```



```
"type": "OAuth2TokenExchangeFilter",
"config": {
    "amService": "AmService-1",
    "endpointHandler": "ExchangeHandler",
    "subjectToken": "#{request.entity.form['subject_token']}[0]}",
    "scopes": ["mail"],
    "failureHandler": "ExchangeFailureHandler"
}
},
],
"handler": {
    "type": "StaticResponseHandler",
    "config": {
        "status": 200,
        "headers": {
            "content-type": [
                "application/json"
            ]
        },
        "entity": "{\n\"access_token\": \"${contexts.oauth2TokenExchange.issuedToken}\",
\n\"issued_token_type\": \"${contexts.oauth2TokenExchange.issuedTokenType}\"}"
    }
}
```

Source: [token-exchange.json](#)

Notice the following features of the route:

- The route matches requests to `/token-exchange`
- PingGateway reads the `subjectToken` from the request entity.
- The StaticResponseHandler returns an issued token.

3. Test the setup:

1. In a terminal window, use a `curl` command similar to the following to retrieve an access token, which is the *subject token*:

```
$ subjecttoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail%20employeeenumber" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token") \
&& echo $subjecttoken
```

Output

hc-...c6A

2. Introspect the subject token at the AM introspection endpoint:

```
$ curl --location \
--request POST 'http://am.example.com:8088/openam/oauth2/realms/root/introspect' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--data-urlencode "token=${subjecttoken}" \
--data-urlencode 'client_id=client-application' \
--data-urlencode 'client_secret=password'
```

Output

```
Decoded access_token: {
  "active": true,
  "scope": "employee number mail",
  "realm": "/",
  "client_id": "client-application",
  "user_id": "demo",
  "username": "demo",
  "token_type": "Bearer",
  "exp": 1626796888,
  "sub": "(usr!demo)",
  "subname": "demo",
  "iss": "http://am.example.com:8088/openam/oauth2",
  "auth_level": 0,
  "authGrantId": "W-j...E1E",
  "may_act": {
    "client_id": "serviceConfidentialClient"
  },
  "auditTrackingId": "4be...169"
}
```

Note that in the subject token, the `client_id` is `client-application`, and the scopes are `employee number` and `mail`. The `may_act` claim indicates that `serviceConfidentialClient` is authorized to exchange this token.

3. Exchange the subject token for an issued token:

```
$ issuedtoken=$(curl \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--location \
--request POST 'https://ig.example.com:8443/token-exchange' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--data "subject_token=${subjecttoken}" | jq -r ".access_token") \
&& echo $issuedtoken
```

Output

```
F8e...Q3E
```

4. Introspect the issued token at the AM introspection endpoint:

```
$ curl --location \
--request POST 'http://am.example.com:8088/openam/oauth2/realms/root/introspect' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--data-urlencode "token=${issuedtoken}" \
--data-urlencode 'client_id=serviceConfidentialClient' \
--data-urlencode 'client_secret=password'
```

Output

```
{
  "active": true,
  "scope": "mail",
  "realm": "/",
  "client_id": "serviceConfidentialClient",
  "user_id": "demo",
  "username": "demo",
  "token_type": "Bearer",
  "exp": 1629200490,
  "sub": "(usr!demo)",
  "subname": "demo",
  "iss": "http://am.example.com:8088/openam/oauth2",
  "auth_level": 0,
  "authGrantId": "aYK...EPA",
  "may_act": {
    "client_id": "serviceConfidentialClient"
  },
  "auditTrackingId": "814...367"
}
```

Note that in the issued token, the `client_id` is `serviceConfidentialClient` and the only scope is `mail`.

Not-enforced URIs

By default, PingGateway routes protect access to resources for all requests matching the route's condition path. For assets that don't need protection, like the welcome page of a website, public images, and favicons, you can avoid enforcing protection.

The following sections show routes that don't enforce authentication for some request URLs or URL patterns.

With a SwitchFilter

Before you start:

- Prepare PingGateway and the sample app as described in [Getting started with PingGateway](#).
- Install and configure AM on <http://am.example.com:8088/openam> [↗](#) using the default configuration.

1. On your system, add the following data in a comma-separated value file:

Linux

```
/tmp/userfile.txt
```

Windows

```
C:\Temp\userfile.txt
```

```
username,password,fullname,email
george,C0stanza,George Costanza,george@example.com
kramer,N3wman12,Kramer,kramer@example.com
bjensen,H1falutin,Babs Jensen,bjensen@example.com
demo,Ch4ng31t,Demo User,demo@example.com
kvaughan,B5ibery12,Kirsten Vaughan,kvaughan@example.com
scarter,S9rain12,Sam Carter,scarter@example.com
wolkig,Geh3imnis!,Wilhelm Wolkig,wolkig@example.com
```

Source: [userfile.txt](#)

2. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

3. Set up PingGateway:

1. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

2. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path,
    '^/..*\\\\\\.ico$') or matchesWithRegex(request.uri.path, '^/..*\\\\\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) 

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/not-enforced-switch.json
```

Windows

```
%appdata%\OpenIG\config\routes\not-enforced-switch.json
```

```

{
  "properties": {
    "notEnforcedPathPatterns": "^/home|^/favicon.ico|^/css"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "name": "not-enforced-switch",
  "condition": "${find(request.uri.path, '^/')}",
  "baseURI": "http://app.example.com:8081",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SwitchFilter-1",
          "type": "SwitchFilter",
          "config": {
            "onRequest": [{
              "condition": "${find(request.uri.path, '&{notEnforcedPathPatterns}')}",
              "handler": "ReverseProxyHandler"
            }]
          }
        },
        {
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        },
        {
          "type": "PasswordReplayFilter",
          "config": {
            "loginPage": "${true}",
            "credentials": {
              "type": "FileAttributesFilter",
              "config": {
                "file": "/tmp/userfile.txt",
                "key": "email",
                "value": "${contexts.ssoToken.info.uid}@example.com"
              }
            }
          }
        },
        {
          "request": {
            "method": "POST",
            "uri": "http://app.example.com:8081/login",

```

```

        "form": {
            "username": [
                "${contexts.fileAttributes.record.username}"
            ],
            "password": [
                "${contexts.fileAttributes.record.password}"
            ]
        }
    },
    "handler": "ReverseProxyHandler"
}

```

Source: [not-enforced-switch.json](#)

Notice the following features of the route:

- The route condition is `/`, so the route matches all requests.
- The SwitchFilter passes requests on the path `^/home`, `^/favicon.ico`, and `^/css` directly to the ReverseProxyHandler. All other requests continue along the chain to the SingleSignOnFilter.
- If the request doesn't have a valid AM session cookie, the SingleSignOnFilter redirects the request to AM for authentication. The SingleSignOnFilter stores the cookie value in an `SsoTokenContext`.
- Because the PasswordReplayFilter detects that the response is a login page, it uses the FileAttributesFilter to replay the password, and logs the request into the sample application.

4. Test the setup:

1. If you are signed in to AM, sign off and clear any cookies.
2. Access the route on the not-enforced URL <http://ig.example.com:8080/home>. The home page of the sample app is displayed without authentication.
3. Access the route on the enforced URL <http://ig.example.com:8080/profile>. The SingleSignOnFilter redirects the request to AM for authentication.
4. Sign on to AM as user `demo`, password `Ch4ng31t`. The PasswordReplayFilter replays the credentials for the demo user. The request is passed to the sample app's profile page for the demo user.

With a DispatcherHandler

To use a DispatcherHandler for not-enforced URIs, replace the route in [With a SwitchFilter](#) with the following route. If the request is on the path `^/home`, `^/favicon.ico`, or `^/css`, the DispatcherHandler sends it directly to the ReverseProxyHandler, without authentication. It passes all other requests into the Chain for authentication.

```

{
  "properties": {
    "notEnforcedPathPatterns": "^/home|^/favicon.ico|^/css"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "name": "not-enforced-dispatch",
  "condition": "${find(request.uri.path, '^/')}",
  "baseURI": "http://app.example.com:8081",
  "handler": {
    "type": "DispatchHandler",
    "config": {
      "bindings": [
        {
          "condition": "${find(request.uri.path, '&{notEnforcedPathPatterns}')}",
          "handler": "ReverseProxyHandler"
        },
        {
          "handler": {
            "type": "Chain",
            "config": {
              "filters": [
                {
                  "type": "SingleSignOnFilter",
                  "config": {
                    "amService": "AmService-1"
                  }
                },
                {
                  "type": "PasswordReplayFilter",
                  "config": {
                    "loginPage": "${true}",
                    "credentials": {
                      "type": "FileAttributesFilter",
                      "config": {
                        "file": "/tmp/userfile.txt",
                        "key": "email",
                        "value": "${contexts.ssoToken.info.uid}@example.com"
                      }
                    }
                  }
                }
              ],
              "request": {
                "method": "POST",
                "uri": "http://app.example.com:8081/login",
                "form": {

```



```
"username": [
    "${contexts.fileAttributes.record.username}"
],
"password": [
    "${contexts.fileAttributes.record.password}"
]
}
}
}
},
"handler": "ReverseProxyHandler"
}
}
}
}
```

Source: [not-enforced-dispatch.json](#)

POST data preservation

The [DataPreservationFilter](#) triggers POST data preservation when an unauthenticated client posts HTML form data to a protected resource.


When an authentication redirect is triggered, the filter stores the data in the HTTP session, and redirects the client for authentication. After authentication, the filter generates an empty self-submitting form POST to emulate the original POST. It then replays the stored data into the request before passing it along the chain.

The data can be any POST content, such as HTML form data or a file upload.

Consider the following points for POST data preservation:

- The size of the POST data is important because the data is stored in the HTTP session.
- Stateless sessions store form content in encrypted JWT session cookies. To prevent requests from being rejected because the HTTP headers are too long, configure `connectors:maxTotalHeadersSize` in [admin.json](#).
- Sticky sessions may be required for deployments with stateful sessions, and multiple PingGateway instances.

The following image shows a simplified data flow for POST data preservation:



1. An unauthenticated client requests a POST to a protected resource.
 2. The DataPreservationFilter tags the the request with a unique identifier, and passes it along the chain. The next filter should be an authentication filter such as a SingleSignOnFilter.
 3. The next filter triggers the authentication, and includes a goto URL tagged with the unique identifier from the previous step.
 - 4-5. The DataPreservationFilter stores the POST data in the HTTP session, and redirects the request for authentication. The POST data is identified by the unique identifier.
 - 6-7. The client authenticates with AM, and AM provides an authentication response to the goto URL.
 8. The authenticated client sends a GET request containing the unique identifier.
 - 9-10. The DataPreservationFilter validates the unique identifier, and generates a self-posting form response for the client.
- The presence of the unique identifier in the goto URL ensures that requests at the URL can be individually identified. Additionally, it is more difficult to hijack user data, because there is little chance of guessing the code within the login window.
- If the identifier is not validated, PingGateway denies the request.
11. The client resends the POST request, including the identifier.
 - 12-13. The DataPreservationFilter updates the request with the POST data, and sends it along the chain.

Preserve POST data during CDSSO

Before you start, set up and test the example in [Cross-domain single sign-on for PingAM](#).

1. In PingGateway, replace `cdsso.json` with the following route:

Linux

```
$HOME/.openig/config/routes/pdp.json
```

Windows

```
%appdata%\OpenIG\config\routes\pdp.json
```

```

{
  "name": "pdp",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/cdsso')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "http://am.example.com:8088/openam",
        "realm": "/",
        "agent": {
          "username": "ig_agent_cdsso",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "sessionCache": {
          "enabled": false
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "DataPreservationFilter",
          "type": "DataPreservationFilter"
        },
        {
          "name": "CrossDomainSingleSignOnFilter-1",
          "type": "CrossDomainSingleSignOnFilter",
          "config": {
            "redirectEndpoint": "/home/cdsso/redirect",
            "authCookie": {
              "path": "/home",
              "name": "ig-token-cookie"
            },
            "amService": "AmService-1",
            "logoutExpression": "${find(request.uri.query, 'logOff=true')}",
            "defaultLogoutLandingPage": "/form"
          }
        }
      ]
    },
    "handler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 200,
        "headers": {
          "Content-Type": [
            "text/html; charset=UTF-8"
          ]
        }
      },
      "entity": [
        "<html>",

```

```

        "    <body>",
        "        <h1>Request Information</h1>",
        "        <p>Request method: #{request.method}",
        "        <p>Request URI: #{request.uri}",
        "        <p>Query string: #{request.queryParams}",
        "        <p>Form: #{request.entity.form}",
        "        <p>Content length: #{request.headers['Content-Length'][0]}",
        "        <p>Content type: #{request.headers['Content-Type'][0]}",
        "    </body>",
        "</html>"
    ]
}
}
}
}
}
}
}

```

Source: [pdp.json](#)

Notice the following differences compared to `cdsso.json`:

- A `DataPreservationFilter` is positioned in front of the `CrossDomainSingleSignOnFilter` to manage POST data preservation before authentication.
- The `ReverseProxyHandler` is replaced by a `StaticResponseHandler` that displays the POST data provided in the request.

2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/form.json
```

Windows

```
%appdata%\OpenIG\config\routes\form.json
```

```

{
  "condition": "${request.uri.path == '/form'}",
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/html" ]
      },
      "entity" : [
        "<html>",
        "  <body>",
        "    <h1>Test page : POST Data Preservation containing visible and hidden form elements</h1>",
        "    <form id='testingPDP' enctype='application/x-www-form-urlencoded' name='test_form' action='/home/cdsso/pdp.info?foo=bar&baz=pdp' method='post'>",
        "      <input name='email' value='user@example.com' size='60'>",
        "      <input type='hidden' name='phone' value='555-123-456' />",
        "      <input type='hidden' name='manager' value='Bob' />",
        "      <input type='hidden' name='dept' value='Engineering' />",
        "      <input type='submit' value='Press to demo form posting' id='form_post_button' />",
        "    </form>",
        "  </body>",
        "</html>"
      ]
    }
  }
}

```

Source: [form.json](#)

Notice the following features of the route:

- The route matches requests to `/home/form`.
- The `StaticResponseHandler` includes the following entity to present visible and hidden form elements from the original request:

```
<!DOCTYPE html>
<html>
  <body>
    <h1>Test page : POST Data Preservation containing visible and hidden form elements</h1>
    <form
      id='testingPDP'
      enctype='application/x-www-form-urlencoded'
      name='test_form'
      action='/home/cdsso/pdp.info?foo=bar&baz=pdp'
      method='post'>
      <input
        name='email'
        value='user@example.com'
        size='60'>
      <input
        type='hidden'
        name='phone'
        value='555-123-456' />
      <input
        type='hidden'
        name='manager'
        value='Bob' />
      <input
        type='hidden'
        name='dept'
        value='Engineering' />
      <input
        type='submit'
        value='Press to demo form posting'
        id='form_post_button' />
    </form>
  </body>
</html>
```

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.ext.com:8443/form>.

The script in the StaticResponseHandler entity of `form.json` creates a button to demonstrate form posting.

2. Press the button, and log in to AM as user `demo`, password `Ch4ng31t`.

When you have authenticated, the script presents the POST data from the original request.

CSRF protection with PingGateway

In a Cross Site Request Forgery (CSRF) attack, a user unknowingly executes a malicious request on a website where they're authenticated. A CSRF attack usually includes a link or script in a web page. When a user accesses the link or script, the page executes an HTTP request on the site where the user is authenticated.

CSRF attacks interact with HTTP requests as follows:


- CSRF attacks can execute POST, PUT, and DELETE requests on the targeted server. For example, a CSRF attack can transfer funds out of a bank account or change a user's password.

- Because of same-origin policy, CSRF attacks **cannot** access any response from the targeted server.

When PingGateway processes POST, PUT, and DELETE requests, it checks a custom HTTP header in the request. If a CSRF token isn't present in the header or not valid, PingGateway rejects the request and returns a valid CSRF token in the response.


Rogue websites that attempt CSRF attacks operate in a different website domain to the targeted website. Because of same-origin policy, rogue websites can't access a response from the targeted website, and can't, therefore, access the response or CSRF token.

The following example shows the data flow when an authenticated user sends a POST request to an application protected against CSRF:



The following example shows the data flow when an authenticated user sends a POST request from a rogue site to an application protected against CSRF:

Flow of requests from rogue site to application protected against CSRF



1. Set up SSO, so that AM authenticates users to the sample app through PingGateway:

1. Set up AM and PingGateway as described in [Using the default PingAM journey](#).
2. Remove the condition in `sso.json`, so that the route matches all requests:

```
"condition": "${find(request.uri.path, '^/home/sso')}"
```

2. Test the setup without CSRF protection:

1. Go to <https://ig.example.com:8443/bank/index>, and log in to the Sample App Bank through AM, as user `demo`, password `Ch4ng31t`.
2. Send a bank transfer of \$10 to Bob, and note that the transfer is successful.
3. Go to <http://localhost:8081/bank/attack-autosubmit> to simulate a CSRF attack.

💡 Tip

In deployments that use a different protocol, hostname, or port for PingGateway, append the `igUrl` parameter, as follows:

```
http://localhost:8081/bank/attack-autosubmit?igUrl=protocol://hostname:port
```

When you access this page, a hidden HTML form is automatically submitted to transfer \$1000 to the rogue user, using the PingGateway session cookie to authenticate to the bank.

In the bank transaction history, note that \$1000 is debited.

3. Test the setup with CSRF protection:

1. In PingGateway, replace `sso.json` with the following route:

```

{
  "name": "Csrf",
  "baseURI": "http://app.example.com:8081",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    },
    {
      "name": "FailureHandler-1",
      "type": "StaticResponseHandler",
      "config": {
        "status": 403,
        "headers": {
          "Content-Type": [ "text/plain; charset=UTF-8" ]
        },
        "entity": "Request forbidden"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SingleSignOnFilter-1",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        },
        {
          "name": "CsrfFilter-1",
          "type": "CsrfFilter",
          "config": {
            "cookieName": "iPlanetDirectoryPro",
            "failureHandler": "FailureHandler-1"
          }
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  }
}

```

Source: [csrf.json](#)

Notice the following features of the route compared to `sso.json`:

- The `CsrfFilter` checks the AM session cookie for the `X-CSRF-Token` header. If a CSRF token isn't present in the header or not valid, the filter rejects the request and provides a valid CSRF token in the header.

2. Go to <https://ig.example.com:8443/bank/index>, and send a bank transfer of \$10 to Alice.

Because there is no CSRF token, PingGateway responds with an HTTP 403, and provides the token.

3. Send the transfer again, and note that because the CSRF token is provided the transfer is successful.

4. Go to <http://localhost:8081/bank/attack-autosubmit> to automatically send a rogue transfer.

Tip

In deployments that use a different protocol, hostname, or port for PingGateway, append the `igUrl` parameter, as follows:

```
http://localhost:8081/bank/attack-autosubmit?igUrl=protocol://hostname:port
```


Because there is no CSRF token, PingGateway rejects the request and provides the CSRF token. However, because the rogue site is in a different domain to `ig.example.com` it can't access the CSRF token.

Throttling requests with PingGateway

To protect applications from being overused by clients, use a throttling filter to limit how many requests can be made in a defined time. The maximum number of requests that are allowed in a defined time is called the *throttling rate*. The following sections describe how to set up simple, mapped, and scriptable throttling filters:

About throttling

The throttling filter uses the token bucket algorithm, allowing some unevenness or bursts in the request flow. The following image shows how PingGateway manages requests for a throttling rate of 10 requests/10 seconds:



- At 7 seconds, 2 requests have previously passed when there is a burst of 9 requests. PingGateway allows 8 requests, but disregards the 9th because the throttling rate for the 10-second throttling period has been reached.

- At 8 and 9 seconds, although 10 requests have already passed in the 10-second throttling period, PingGateway allows 1 request each second.
- At 17 seconds, 4 requests have passed in the previous 10-second throttling period, and PingGateway allows another burst of 6 requests.


When the throttling rate is reached, PingGateway issues an HTTP status code 429 `Too Many Requests` and a `Retry-After` header like the following, where the value is the number of seconds to wait before trying the request again:

```
GET https://ig.example.com:8443/home/throttle-scriptable HTTP/2
. . .

HTTP/2 429 Too Many Requests
Retry-After: 10
```

Configure simple throttling

This section describes how to configure a simple throttling filter that applies a throttling rate of 6 requests/10 seconds. When an application is protected by this throttling filter, no more than 6 requests, irrespective of their origin, can access the sample application in a 10 second period.



1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/00-throttle-simple.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-throttle-simple.json
```

```
{
  "name": "00-throttle-simple",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/throttle-simple')}",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "ThrottlingFilter",
          "name": "ThrottlingFilter-1",
          "config": {
            "requestGroupingPolicy": "",
            "rate": {
              "numberOfRequests": 6,
              "duration": "10 s"
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}
```

Source: [00-throttle-simple.json](#)

Learn how to use Studio to set up the PingGateway route in [Simple throttling filter in Structured Editor](#).

Notice the following features of the route:

- The route matches requests to `/home/throttle-simple`.
- The ThrottlingFilter contains a request grouping policy that is blank. This means that all requests are in the same group.
- The rate defines the number of requests allowed to access the sample application in a given time.

3. Test the setup:

1. In a terminal window, use a `curl` command similar to the route in a loop:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
https://ig.example.com:8443/home/throttle-simple/[01-10] \
> /tmp/throttle-simple.txt 2>&1
```

2. Search the output file for the result:

```
$ grep "< HTTP/2" /tmp/throttle-simple.txt | sort | uniq -c
```

Output

```
6 < HTTP/2 200 OK
4 < HTTP/2 429 Too Many Requests
```


Notice that the first six requests returned a success response, and the following four requests returned an HTTP 429 **Too Many Requests**. This result demonstrates that the throttling filter has allowed only six requests to access the application, and has blocked the other requests.

Configure mapped throttling

This section describes how to configure a mapped throttling policy, where the grouping policy defines criteria to group requests, and the rate policy defines the criteria by which rates are mapped.

The following image illustrates how different throttling rates can be applied to users.

The following image illustrates how each user with a **gold** status has a throttling rate of 6 requests/10 seconds, and each user with a **silver** status has 3 requests/10 seconds. The **bronze** status is not mapped to a throttling rate, and so a user with the **bronze** status has the default rate.



Before you begin, set up and test the example in [Validating PingAM access tokens with introspection](#).

1. In the AM console, select **</> Scripts > OAuth2 Access Token Modification Script** and replace the default script as follows:

```
import org.forgerock.http.protocol.Request
import org.forgerock.http.protocol.Response

def attributes = identity.getAttributes(["mail", "employeeNumber"].toSet())
accessToken.setField("mail", attributes["mail"][0])
def mail = attributes['mail'][0]
if (mail.endsWith('@example.com')) {
    status = "gold"
} else if (mail.endsWith('@other.com')) {
    status = "silver"
} else {
    status = "bronze"
}
accessToken.setField("status", status)
```

The AM script adds user profile information to the access token, and defines the content of the users `status` field according to the email domain.

2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/00-throttle-mapped.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-throttle-mapped.json
```

```

{
  "name": "00-throttle-mapped",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/throttle-mapped')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [
              "mail",
              "employeenumber"
            ],
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "token-resolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "amService": "AmService-1",
                "providerHandler": {
                  "type": "Chain",
                  "config": {
                    "filters": [
                      {
                        "type": "HttpBasicAuthenticationClientFilter",
                        "config": {
                          "username": "ig_agent",
                          "passwordSecretId": "agent.secret.id",
                          "secretsProvider": "SystemAndEnvSecretStore-1"
                        }
                      }
                    ],
                    "handler": "ForgeRockClientHandler"
                  }
                }
              }
            }
          }
        }
      ]
    }
  }
},

```



```

{
  "name": "ThrottlingFilter-1",
  "type": "ThrottlingFilter",
  "config": {
    "requestGroupingPolicy": "${contexts.oauth2.accessToken.info.mail}",
    "throttlingRatePolicy": {
      "name": "MappedPolicy",
      "type": "MappedThrottlingPolicy",
      "config": {
        "throttlingRateMapper": "${contexts.oauth2.accessToken.info.status}",
        "throttlingRatesMapping": {
          "gold": {
            "numberOfRequests": 6,
            "duration": "10 s"
          },
          "silver": {
            "numberOfRequests": 3,
            "duration": "10 s"
          },
          "bronze": {
            "numberOfRequests": 1,
            "duration": "10 s"
          }
        },
        "defaultRate": {
          "numberOfRequests": 1,
          "duration": "10 s"
        }
      }
    }
  },
  "handler": "ReverseProxyHandler"
}

```

Source: [00-throttle-mapped.json](#)

Learn how to use Studio to set up the PingGateway route in [Mapped throttling filter in Structured Editor](#).

Notice the following features of the route:

- The route matches requests to `/home/throttle-mapped`.
- The OAuth2ResourceServerFilter validates requests with the AccessTokenResolver, and makes it available for downstream components in the `oauth2` context.
- The ThrottlingFilter bases the request grouping policy on the AM user's email. The throttling rate is applied independently to each email address.

The throttling rate is mapped to the AM user's `status`, which is defined by the email domain, in the AM script.

3. Test the setup:

1. In a terminal window, use a `curl` command similar to this to retrieve an access token:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail%20employeeenumber" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

- Using the access token, access the route multiple times. The following example accesses the route 10 times and writes the output to a file:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/home/throttle-mapped/\[01-10\] \
> /tmp/throttle-mapped.txt 2>&1
```

- Search the output file for the result:

```
$ grep "< HTTP/2" /tmp/throttle-mapped.txt | sort | uniq -c
```

Output


```
6 < HTTP/2 200
4 < HTTP/2 429
```

Notice that with a `gold` status, the user can access the route 6 times in 10 seconds.

- In AM, change the demo user's email to `demo@other.com`, and then run the last two steps again to find how the access is reduced.

Considerations for dynamic throttling

The following image illustrates what can happen when the throttling rate defined by `throttlingRateMapping` changes frequently or quickly:



In the image, the user starts out with a **gold** status. In a two second period, the users sends five requests, is downgraded to silver, sends four requests, is upgraded back to **gold**, and then sends three more requests.

After making five requests with a **gold** status, the user has almost reached their throttling rate. When his status is downgraded to silver, those requests are disregarded and the full throttling rate for **silver** is applied. The user can now make three more requests even though they have nearly reached their throttling rate with a **gold** status.

After making three requests with a **silver** status, the user has reached their throttling rate. When the user makes a fourth request, the request is refused.

The user is now upgraded back to **gold** and can now make six more requests even though they had reached his throttling rate with a **silver** status.

When you configure `requestGroupingPolicy` and `throttlingRateMapper`, bear in mind what happens when the throttling rate defined by the `throttlingRateMapper` is changed.

Configure scriptable throttling

This section builds on the example in [Configure mapped throttling](#). It creates a scriptable throttling filter, where the script applies a throttling rate of 6 requests/10 seconds to requests from gold status users. For all other requests, the script returns `null`, and applies the default rate of 1 request/10 seconds.

Before you start, set up and test the example in [Configure mapped throttling](#).

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/00-throttle-scriptable.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-throttle-scriptable.json
```

```

{
  "name": "00-throttle-scriptable",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/throttle-scriptable')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [
              "mail",
              "employeenumber"
            ],
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "token-resolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "amService": "AmService-1",
                "providerHandler": {
                  "type": "Chain",
                  "config": {
                    "filters": [
                      {
                        "type": "HttpBasicAuthenticationClientFilter",
                        "config": {
                          "username": "ig_agent",
                          "passwordSecretId": "agent.secret.id",
                          "secretsProvider": "SystemAndEnvSecretStore-1"
                        }
                      }
                    ],
                    "handler": "ForgeRockClientHandler"
                  }
                }
              }
            }
          }
        }
      ]
    }
  }
},

```

```

{
  "name": "ThrottlingFilter-1",
  "type": "ThrottlingFilter",
  "config": {
    "requestGroupingPolicy": "${contexts.oauth2.accessToken.info.mail}",
    "throttlingRatePolicy": {
      "type": "DefaultRateThrottlingPolicy",
      "config": {
        "delegateThrottlingRatePolicy": {
          "name": "ScriptedPolicy",
          "type": "ScriptableThrottlingPolicy",
          "config": {
            "type": "application/x-groovy",
            "source": [
              "if (contexts.oauth2.accessToken.info.status == status) {",
              "  return new ThrottlingRate(rate, duration)",
              "} else {",
              "  return null",
              "}"
            ],
            "args": {
              "status": "gold",
              "rate": 6,
              "duration": "10 seconds"
            }
          }
        },
        "defaultRate": {
          "numberOfRequests": 1,
          "duration": "10 s"
        }
      }
    }
  },
  "handler": "ReverseProxyHandler"
}

```

Source: [00-throttle-scriptable.json](#)

+ Learn how to use Studio to set up the PingGateway route in [Scriptable throttling filter in Structured Editor](#).

Notice the following features of the route, compared to path] `00-throttle-mapped.json` :

- The route matches requests to `/home/throttle-scriptable`.
- The `DefaultRateThrottlingPolicy` delegates the management of throttling to the `ScriptableThrottlingPolicy`.
- The script applies a throttling rate to requests from users with gold status. For all other requests, the script returns null and the default rate is applied.

2. Test the setup:

1. In a terminal window, use a `curl` command similar to this to retrieve an access token:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail%20employeeenumber" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

- Using the access token, access the route multiple times. The following example accesses the route 10 times and writes the output to a file:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/home/throttle-scriptable/\[01-10\] \
> /tmp/throttle-script.txt 2>&1
```

- Search the output file for the result:

```
$ grep "< HTTP/2" /tmp/throttle-script.txt | sort | uniq -c
```

Output

```
6 < HTTP/2 200
4 < HTTP/2 429
```

Notice that with a `gold` status, the user can access the route 6 times in 10 seconds.

- In AM, change the user's email to `demo@other.com`, and then run the last two steps again to find how the access is reduced.

URI fragments in redirect

URI fragments are optional last parts of a URL for a document, typically used to identify or navigate to a particular part of the document. The fragment part follows the URL after a hash `#`, for example

```
https://www.rfc-editor.org/rfc/rfc1234#section5.
```


When an unauthenticated user requests a resource that includes a URI fragment, the user agent sends the URI but doesn't send the fragment. The fragment is lost during the authentication flow.

PingGateway provides a [FragmentFilter](#) to track the fragment part of a URI when a request triggers a login redirect.

The `FragmentFilter` doesn't handle multiple fragment captures in parallel. If a fragment capture is in progress while PingGateway performs another login redirect, a second fragment capture process isn't triggered and the fragment is lost.

When a browser request loads a favicon, it can cause the fragment part of a URI to be lost. Prevent problems by serving static resources with a separate route. As an example, use the route in [Serve static resources](#).

The following image shows the flow of information when the `FragmentFilter` is included in the SSO authentication flow:



1-2. An unauthenticated client requests access to a fragment URL.

3. The FragmentFilter adds the AuthRedirectContext, so that downstream filters can mark the response as redirected.

4-5. The SingleSignOnFilter adds to the context to notify upstream filters that a redirect is pending, and redirects the request for authentication.

6-7. The FragmentFilter is notified by the context that a redirect is pending, and returns a new response object containing the response cookies, an autosubmit HTML form, and Javascript.

8. The user agent runs the Javascript or displays the form's submit button for the user to click on. This operation POSTs a form request back to a fragment endpoint URI, containing the following parts:

- Request URI path (`/profile`)
- Captured fragment (`#fragment`)
- Login URI (`http://am.example.com/login?goto=...`)

9. The FragmentFilter creates the fragment cookie.

10-12. The client authenticates with AM.

13. The FragmentFilter intercepts the request because it contains a fragment cookie, and its URI matches the original request URI.

The filter redirects the client to the original request URI containing the fragment. The fragment cookie then expires.

14-19. The client follows the final redirect to the original request URI containing the fragment, and the sample app returns the response.

This procedure shows how to persist a URI fragment in an SSO authentication. Before you start, set up and test the example in [Using the default PingAM journey](#).

1. In PingGateway, replace `sso.json` with the following route:

Linux

```
$HOME/.openig/config/routes/fragment.json
```

Windows

```
%appdata%\OpenIG\config\routes\fragment.json
```



```

{
  "name": "fragment",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/sso')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "FragmentFilter-1",
          "type": "FragmentFilter",
          "config": {
            "fragmentCaptureEndpoint": "/home/sso"
          }
        },
        {
          "name": "SingleSignOnFilter-1",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

Source: [fragment.json](#)

Compared to `sso.json` the `FragmentFilter` captures the fragment form data from the route condition endpoint.

2. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/sso#fragment>.

The `SingleSignOnFilter` redirects the request to AM for authentication.

2. Log in to AM as user `demo`, password `Ch4ng31t`.

The SingleSignOnFilter passes the request to sample application, which returns the home page. Note that the URL of the page has preserved the fragment: `https://ig.example.com:8443/home/sso?_ig=true#fragment`

3. Remove the FragmentFilter from the route and test the route again.

Note that this time the URL of the page hasn't preserved the fragment.


JWT validation with PingAM

The following examples show how to use the [JwtValidationFilter](#) to validate signed and encrypted JWT.

The JwtValidationFilter can access JWTs in the request, provided in a header, query parameter, form parameter, cookie, or other way. If an upstream filter makes the JWT available in the request's attributes context, the JwtValidationFilter can access the JWT through the context, for example, at `${attributes.jwtToValidate}`.

For convenience, the JWT in this example is provided by the JwtBuilderFilter, and passed to the JwtValidationFilter in a cookie.

The following figure shows the flow of information in the example:



Before you begin, set up and test the example in [Pass runtime data in a JWT signed with PEM then encrypted with a symmetric key](#).

1. Add a second route to PingGateway, replacing value of the property `secretsDir` with the directory for the PEM files:

Linux

```
$HOME/.openig/config/routes/jwt-validate.json
```

Windows

```
%appdata%\OpenIG\config\routes\jwt-validate.json
```

```

{
  "name": "jwt-validate",
  "condition": "${find(request.uri.path, '^/jwt-validate')}",
  "properties": {
    "secretsDir": "path/to/secrets"
  },
  "capture": "all",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore",
      "type": "SystemAndEnvSecretStore",
      "config": {
        "mappings": [{
          "secretId": "id.decrypted.key.for.signing.jwt",
          "format": "BASE64"
        }]
      }
    },
    {
      "name": "pemPropertyFormat",
      "type": "PemPropertyFormat",
      "config": {
        "decryptionSecretId": "id.decrypted.key.for.signing.jwt",
        "secretsProvider": "SystemAndEnvSecretStore"
      }
    },
    {
      "name": "FileSystemSecretStore-1",
      "type": "FileSystemSecretStore",
      "config": {
        "format": "PLAIN",
        "directory": "&{secretsDir}",
        "mappings": [{
          "secretId": "id.encrypted.key.for.signing.jwt.pem",
          "format": "pemPropertyFormat"
        }], {
          "secretId": "symmetric.key.for.encrypting.jwt",
          "format": {
            "type": "SecretKeyPropertyFormat",
            "config": {
              "format": "BASE64",
              "algorithm": "AES"
            }
          }
        }
      ]
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [{
        "type": "JwtValidationFilter",
        "config": {
          "jwt": "${request.cookies['my-jwt'][0].value}",
          "secretsProvider": "FileSystemSecretStore-1",
          "decryptionSecretId": "symmetric.key.for.encrypting.jwt",
          "customizer": {
            "type": "ScriptableJwtValidatorCustomizer",
            "config": {

```

```
"type": "application/x-groovy",
"source": [
    "builder.claim('name', JsonValue::asString, isEqualTo('demo'))",
    "builder.claim('email', JsonValue::asString, isEqualTo('demo@example.com'));"
]
},
"failureHandler": {
    "type": "ScriptableHandler",
    "config": {
        "type": "application/x-groovy",
        "source": [
            "def response = new Response(Status.FORBIDDEN)",
            "response.headers['Content-Type'] = 'text/html; charset=utf-8'",
            "def errors = contexts.jwtValidationError.violations.collect{it.description}",
            "def display = \"<html>Can't validate JWT:<br> ${contexts.jwtValidationError.jwt} \",",
            "display <<=\"<br><br>For the following errors:<br> ${errors.join(\"<br>\")}</html>\"",
            "response.entity=display as String",
            "return response"
        ]
    }
}
}],
"handler": {
    "type": "StaticResponseHandler",
    "config": {
        "status": 200,
        "headers": {
            "Content-Type": [ "text/html; charset=UTF-8" ]
        },
        "entity": [
            "<html>",
            "  <h2>Validated JWT:</h2>",
            "  <p>${contexts.jwtValidation.value}</p>",
            "  <h2>JWT payload:</h2>",
            "  <p>${contexts.jwtValidation.info}</p>",
            "</html>"
        ]
    }
}
```

Source: [jwt-validate.json](#)

Notice the following features of the route:

- The route matches requests to `/jwt-validate`.
- The `JwtValidationFilter` takes the value of the JWT from `my-jwt`.
- The `SystemAndEnvSecretStore`, `PemPropertyFormat`, and `FileSystemSecretStore` objects in the heap are the same as those in the route to create the JWT. The `JwtValidationFilter` uses the same objects to validate the JWT.
- The `JwtBuilderFilter` `customizer` requires that the JWT claims match `name:demo` and `email:demo@example.com`.

- If the JWT is validated, the StaticResponseHandler displays the validated value. Otherwise, the FailureHandler displays the reason for the failed validation.

2. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/jwtbuilder-sign-then-encrypt> to build a JWT.
2. Log in to AM as user `demo`, password `Ch4ng31t`. The sample application displays the signed JWT.
3. Go to <https://ig.example.com:8443/jwt-validate> to validate the JWT. The validated JWT and its payload are displayed.
4. Test the setup again, but log in to AM as a different user, or change the email address of the demo user in AM. The JWT isn't validated, and an error is displayed.


WebSocket traffic with PingAM

When a user agent requests an upgrade from HTTP or HTTPS to the WebSocket protocol, PingGateway detects the request and performs an HTTP handshake request between the user agent and the protected application.

If the handshake is successful, PingGateway upgrades the connection and provides a dedicated tunnel to route WebSocket traffic between the user agent and the protected application. PingGateway doesn't intercept messages to or from the WebSocket server.

The tunnel remains open until it's closed by the user agent or protected application. When the user agent closes the tunnel, the connection between PingGateway and the protected application is automatically closed.

The following sequence diagram shows the flow of information when PingGateway proxies WebSocket traffic:



To configure PingGateway to proxy WebSocket traffic, configure the `websocket` property of [ReverseProxyHandler](#). By default, PingGateway doesn't proxy WebSocket traffic.

Proxy WebSocket traffic

1. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*/.*\\.ico$')
or matchesWithRegex(request.uri.path, '^/.*/.*\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) 

4. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/websocket.json
```

Windows

```
%appdata%\OpenIG\config\routes\websocket.json
```



```

{
  "name": "websocket",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/websocket')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    },
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "config": {
        "websocket": {
          "enabled": true,
          "vertx": {
            "maxFrameSize": 200000000,
            "maxMessageSize": 200000000,
            "tryUsePerMessageCompression": true
          }
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SingleSignOnFilter-1",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

Source: [websocket.json](#)

Learn how to set up the route in Studio in [Proxy for WebSocket traffic in Structured Editor](#).

Learn more about Vert.x options for WebSocket connections in [HttpClientOptions](#).

Notice the following features of the route:

- The route matches requests to `/websocket`, the endpoint on the sample app that exposes a WebSocket server.
- The `SingleSignOnFilter` redirects unauthenticated requests to AM for authentication.
- The `ReverserProxyHandler` enables PingGateway to proxy WebSocket traffic. After PingGateway upgrades the HTTP connection to the WebSocket protocol, the `ReverserProxyHandler` passes the messages to the WebSocket server.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/websocket>.
2. Sign on to AM as user `demo`, password `Ch4ng31t`.

AM authenticates the user, creates an SSO token, and redirects the request back to the original URI, with the token in a cookie.

The request then passes to the `ReverseProxyHandler`, which routes the request to the HTML page `/websocket/index.html` of the sample app. The page initiates the HTTP handshake for connecting to the WebSocket endpoint `/websocket/echo`.


3. Enter text on the WebSocket echo screen and note that the text is echoed back.

UMA support with PingAM


PingGateway includes support for [User-Managed Access \(UMA\) 2.0 Grant for OAuth 2.0 Authorization](#) specifications.

About PingGateway as an UMA resource server


The following figure shows an UMA environment, with PingGateway protecting a resource, and AM acting as an Authorization Server. Learn more in the AM documentation on [User-Managed Access \(UMA\) 2.0](#).



The following figure shows the data flow when the resource owner registers a resource with AM, and sets up a share using a Protection API Token (PAT):



The following figure shows the data flow when the client accesses the resource, using a Requesting Party Token (RPT):



You can find information about CORS support in the AM documentation on [configuring CORS support](#). This procedure describes how to modify the AM configuration to allow cross-site access.

Limitations of PingGateway as an UMA resource server

When using PingGateway as an UMA resource server, note the following points:

- When you deploy the administrative endpoint on another port using "adminConnector" settings in `admin.json`, expose the port for use in the UMA deployment.
- PingGateway depends on the resource owner for the PAT.

When a PAT expires, no refresh token is available to PingGateway. The resource owner must repeat the entire share process with a new PAT in order to authorize access to protected resources. The resource owner should delete the old resource and create a new one.

- Data about PATs and shared resources is held in memory.

PingGateway has no mechanism for persisting the data across restarts. When PingGateway stops and starts again, the resource owner must repeat the entire share process.

- UMA client applications for sharing and accessing protected resources must deal with UMA error conditions and PingGateway error conditions.
- By default, the REST API to manage share objects exposed by PingGateway is protected only by CORS.
- When matching protected resource paths with share patterns, PingGateway takes the longest match.

For example, if resource owner Alice shares `/photos/.*` with Bob, and `/photos/vacation.png` with Charlie, and then Bob attempts to access `/photos/vacation.png`, PingGateway applies the sharing permissions for Charlie, not Bob. As a result, Bob can be denied access.

Set up the UMA example

This section describes tasks to set up AM as an Authorization Server:

- Enabling cross-origin resource sharing (CORS) support in AM
- Configuring AM as an Authorization Server
- Registering UMA client profiles with AM
- Setting up a resource owner (Alice) and requesting party (Bob)

Caution

The settings in this section are suggestions for this tutorial. They aren't intended as instructions for setting up AM CORS support on a server in production.

If you need to accept all origins, by allowing the use of `Access-Control-Allow-Origin=*`, don't allow `Content-Type` headers. Allowing the use of both types of headers exposes AM to cross-site request forgery (CSRF) attacks.

Important

This procedure uses the *Resource Owner Password Credentials* grant type. As suggested in [The OAuth 2.0 Authorization Framework](#), use other grant types whenever possible.

Before you begin, prepare AM, PingGateway, and the sample application. Learn more in the [example installation for this guide](#).

You can find more information about using different settings for the sample application in [Edit the example to match custom settings](#).

1. Set up AM:

1. Find the name of the AM session cookie at the `/json/serverinfo/*` endpoint. This procedure assumes that you are using the default AM session cookie, `iPlanetDirectoryPro`.

2. Create an OAuth 2.0 Authorization Server:

1. Select **Services > Add a Service > OAuth2 Provider**.
2. Add a service with the default values.

3. Configure an UMA Authorization Server:

1. Select **Services > Add a Service > UMA Provider**.
2. Add a service with the default values.

4. Add an OAuth 2.0 client for UMA protection:

1. Select **Applications > OAuth 2.0 > Clients**.

2. Add a client with these values:

- **Client ID** : OpenIG
- **Client secret** : password
- **Scope** : uma_protection

3. (Optional) On the **Core** tab, switch to using a client secret associated with a secret label by setting a **Secret Label Identifier** and mapping the label to a secret.

To learn more, read [Create a client profile](#) and [Map and rotate secrets](#) in the AM documentation.

4. On the **Advanced** tab, select the following option:

- **Grant Types** : Resource Owner Password Credentials

5. Add an OAuth 2.0 client for accessing protected resources:

1. Select **Applications > OAuth 2.0 > Clients**.

2. Add a client with these values:

- **Client ID** : UmaClient
- **Client secret** : password
- **Scope** : openid

3. On the **Advanced** tab, select the following option:

- **Grant Types** : Resource Owner Password Credentials and UMA

6. Select  **Identities**, and add an identity for a resource owner with the following values:

- **ID** : alice
- **Password** : UMAexample
- **Email Address** : alice@example.com

7. Select  **Identities**, and add an identity for a requesting party, with the following values:

- **ID** : bob
- **Password** : UMAexample
- **Email Address** : bob@example.com

8. Enable the CORS filter on AM:

1. In a terminal window, retrieve an SSO token from AM:

```
$ mytoken=$(curl --request POST \  
--header "Accept-API-Version: resource=2.1" \  
--header "X-OpenAM-Username: amadmin" \  
--header "X-OpenAM-Password: password" \  
--header "Content-Type: application/json" \  
--data "{}" \  
http://am.example.com:8088/openam/json/authenticate | jq -r ".tokenId")
```

2. Using the token retrieved in the previous step, enable the CORS filter on AM by using the `/global-config/services/CorsService` REST endpoint:

```
$ curl \
--request PUT \
--header "Content-Type: application/json" \
--header "iPlanetDirectoryPro: $mytoken" http://am.example.com:8088/openam/json/global-config/
services/CorsService/configuration/CorsService \
--data '{
  "acceptedMethods": [
    "POST",
    "GET",
    "PUT",
    "DELETE",
    "PATCH",
    "OPTIONS"
  ],
  "acceptedOrigins": [
    "http://app.example.com:8081",
    "http://ig.example.com:8080",
    "http://am.example.com:8088/openam"
  ],
  "allowCredentials": true,
  "acceptedHeaders": [
    "Authorization",
    "Content-Type",
    "iPlanetDirectoryPro",
    "X-OpenAM-Username",
    "X-OpenAM-Password",
    "Accept",
    "Accept-Encoding",
    "Connection",
    "Content-Length",
    "Host",
    "Origin",
    "User-Agent",
    "Accept-Language",
    "Referer",
    "Dnt",
    "Accept-API-Version",
    "If-None-Match",
    "Cookie",
    "X-Requested-With",
    "Cache-Control",
    "X-Password",
    "X-Username",
    "X-NoSession"
  ],
  "exposedHeaders": [
    "Access-Control-Allow-Origin",
    "Access-Control-Allow-Credentials",
    "Set-Cookie",
    "WWW-Authenticate"
  ],
  "maxAge": 600,
  "enabled": true,
  "allowCredentials": true
}'
```

A CORS configuration is displayed.

**Tip**

To delete the CORS configuration and create another, first run the following command:

```
$ curl \
  --request DELETE \
  --header "X-Requested-With: XMLHttpRequest" \
  --header "iPlanetDirectoryPro: $mytoken" \
  http://am.example.com:8088/openam/json/global-config/services/CorsService/
CorsService/configuration/CorsService
```

2. Set up PingGateway as an UMA resource server:

1. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/..*\\\\.ico$')
or matchesWithRegex(request.uri.path, '^/..*\\\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

2. Add the following settings to `admin.json` configuration and restart PingGateway:

```
{
  "connectors": [
    { "port" : 8080 }
  ],
  "heap": [
    {
      "name": "ClientHandler",
      "type": "ClientHandler"
    }
  ],
  "apiProtectionFilter": {
    "type": "CorsFilter",
    "config": {
      "policies": [
        {
          "acceptedOrigins": [ "http://app.example.com:8081" ],
          "acceptedMethods": [ "GET", "POST", "DELETE" ],
          "acceptedHeaders": [ "Content-Type" ]
        }
      ]
    }
  }
}
```

Source: [admin_uma.json](#)

Notice the following feature:

- The default "apiProtectionFilter" uses a [CorsFilter](#) to allow requests from the origin `http://app.example.com:8081`.

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/00-uma.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-uma.json
```

```

{
  "name": "00-uma",
  "condition": "${request.uri.host == 'app.example.com'}",
  "baseURI" : "http://app.example.com:8081",
  "heap": [
    {
      "name": "UmaService",
      "type": "UmaService",
      "config": {
        "protectionApiHandler": "ClientHandler",
        "wellKnownEndpoint": "http://am.example.com:8088/openam/uma/.well-known/uma2-configuration",
        "resources": [
          {
            "comment": "Protects all resources matching the following pattern.",
            "pattern": ".*",
            "actions": [
              {
                "scopes": [
                  "#read"
                ],
                "condition": "${request.method == 'GET'}"
              },
              {
                "scopes": [
                  "#create"
                ],
                "condition": "${request.method == 'POST'}"
              }
            ]
          }
        ]
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "CorsFilter",
          "config": {
            "policies": [
              {
                "acceptedOrigins": [ "http://app.example.com:8081" ],
                "acceptedMethods": [ "GET" ],
                "acceptedHeaders": [ "Authorization" ],
                "exposedHeaders": [ "WWW-Authenticate" ],
                "allowCredentials": true
              }
            ]
          }
        },
        {
          "type": "UmaFilter",
          "config": {
            "protectionApiHandler": "ClientHandler",
            "umaService": "UmaService"
          }
        }
      ]
    }
  }
}

```

```

    ],
    "handler": "ReverseProxyHandler"
  }
}
}

```

Source: [00-uma.json](#)

Notice the following features of the route:

- The route matches requests from `app.example.com`.
- The UmaService describes the resources that a resource owner can share, using AM as the Authorization Server. It provides a REST API to manage sharing of resource sets.
- The CorsFilter defines the policy for cross-origin requests, listing the methods and headers that the request can use, the headers that are exposed to the frontend JavaScript code, and whether the request can use credentials.
- The UmaFilter manages requesting party access to protected resources, using the UmaService. Protected resources are on the sample application, which responds to requests on port 8081.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <http://app.example.com:8081/uma/>.

2. Share resources:

1. Select **Alice shares resources**.

2. On Alice's page, select **Share with Bob**. The following items are displayed:

- The PAT that Alice receives from AM.
- The metadata for the resource set that Alice registers through PingGateway.
- The result of Alice authenticating with AM in order to create a policy.
- The successful result when Alice configures the authorization policy attached to the shared resource.

If the step fails, run the following command to get an access token for Alice:

```

$ curl -X POST \
-H "Cache-Control: no-cache" \
-H "Content-Type: application/x-www-form-urlencoded" \
-d
'grant_type=password&scope=uma_protection&username=alice&password=UMAexample&client_id=OpenIG&client_secret=password' \
http://am.example.com:8088/openam/oauth2/access_token

```

If you fail to get an access token, check that AM is configured as described in this procedure. If you continue to have problems, make sure that your PingGateway configuration matches that shown when you are running the test on <http://app.example.com:8081/uma/>.

3. Access resources:

1. Go back to the first page, and select **Bob accesses resources**.
2. On Bob's page, select **Get Alice's resources**. The following items are displayed:
 - The WWW-Authenticate Header.
 - The OpenID Connect Token that Bob gets to obtain the RPT.
 - The RPT that Bob gets in order to request the resource again.
 - The final response containing the body of the resource.

Edit the example to match custom settings

If you use a configuration that is different to that described in this chapter, consider the following tasks to adjust the sample to your configuration:

1. Unpack the UMA files from the sample application described in [Using the sample application](#) to temporary folder:

```
$ mkdir /tmp/uma
$ cd /tmp/uma
$ jar -xvf /path/to/PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar webroot-uma
```

Output

```
created: webroot-uma/
inflated: webroot-uma/bob.html
inflated: webroot-uma/common.js
inflated: webroot-uma/alice.html
inflated: webroot-uma/index.html
inflated: webroot-uma/style.css
```

2. Edit the configuration in `common.js`, `alice.html`, and `bob.html` to match your settings.
3. Repack the UMA sample client files and then restart the sample application:

```
$ jar -uvf /path/to/PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar webroot-uma
```

Output

```
adding: webroot-uma/(in = 0) (out= 0)(stored 0%)
adding: webroot-uma/bob.html(in = 26458) (out= 17273)(deflated 34%)
adding: webroot-uma/common.js(in = 3652) (out= 1071)(deflated 70%)
adding: webroot-uma/alice.html(in = 27775) (out= 17512)(deflated 36%)
adding: webroot-uma/index.html(in = 22046) (out= 16060)(deflated 27%)
adding: webroot-uma/style.css(in = 811) (out= 416)(deflated 48%)
updated module-info: module-info.class
```

4. If necessary, adjust the CORS settings for AM.

Understand the UMA API with an API descriptor

The UMA share endpoint serves API descriptors at runtime. When you retrieve an API descriptor for the endpoint, a JSON that describes the API for the endpoint is returned.

You can use the API descriptor with a tool such as [Swagger UI](#) to generate a web page that helps you to view and test the endpoint. For information, refer to [PingGateway API descriptors](#).

Protecting PingAM with PingGateway

In its role as a reverse proxy, PingGateway can protect PingAM.

Choose what you allow

The best practice is to allow access only to required AM services:

- Limit access to specified AM realms.
- Prevent AM admin UI access.

Learn more about this process in the following articles:

- [Best practice for blocking the top-level realm in a proxy for PingAM](#)
- [How do I remove admin UI access in PingAM?](#)

Example route

The following example allows access to the following:

- Key services in the `customers` realm.
- Authentication and logout through XUI and the legacy UI.
- SAML v2.0 services.

Before you begin

- Install and run PingGateway as described in the [Getting started with PingGateway](#).
- Install and configure AM with a `customers` subrealm of the top-level realm.

Allow-only route

Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/protect-am.json
```

Windows

```
%appdata%\OpenIG\config\routes\protect-am.json
```

```

{
  "name": "protect-am",
  "comment": "Allow authentication and subrealm access only (not the top-level realm or admin UI)",
  "properties": {
    "amBase": "/am",
    "amInstanceUrl": "http://am.example.com:8088/am",
    "subrealm": "customers"
  },
  "baseURI": "&{amInstanceUrl}",
  "condition": "${find(request.uri.path, '^&{amBase}')}\"",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "AllowOnlyFilter",
          "config": {
            "rules": [
              {
                "comment": "Allow authentication to the subrealm",
                "destination": [
                  {
                    "paths": [
                      "&{amBase}/json/realms/root/realms/&{subrealm}/authenticate"
                    ],
                    "when": "${find(request.queryParams, 'realm') and !(contains(request.queryParams['realm'], '/') or contains(request.queryParams['realm'], '2F') or contains(request.queryParams['authIndexValue'], 'Application') or contains(request.queryParams['module'], 'Application'))}"
                  }
                ]
              },
              {
                "comment": "Allow authentication to the legacy UI",
                "destination": [
                  {
                    "paths": [
                      "&{amBase}/UI/Login"
                    ],
                    "when": "${find(request.queryParams, 'realm') and !(contains(request.queryParams['realm'], '/') or contains(request.queryParams['realm'], '2F') or contains(request.queryParams['authIndexValue'], 'Application') or contains(request.queryParams['module'], 'Application'))}"
                  }
                ]
              },
              {
                "comment": "Allow OAuth 2.0 and OID to the subrealm",
                "destination": [
                  {
                    "paths": [
                      "&{amBase}/oauth2/realms/root/realms/&{subrealm}/authorize",
                      "&{amBase}/oauth2/realms/root/realms/&{subrealm}/access_token",
                      "&{amBase}/oauth2/realms/root/realms/&{subrealm}/userinfo",
                      "&{amBase}/oauth2/realms/root/realms/&{subrealm}/connect/endSession"
                    ]
                  }
                ]
              }
            ]
          },
          {
            "comment": "Allow base requests for sessions and users",
            "destination": [

```



```

        {
            "paths": [
                "&{amBase}/json/sessions",
                "&{amBase}/json/users"
            ]
        }
    ],
    {
        "comment": "Allow base action requests for sessions",
        "destination": [
            {
                "paths": [
                    "&{amBase}/json/realms/root/sessions"
                ]
            }
        ],
        "when": "${(request.queryParams['_action'] == 'getMaxIdle') or (request.queryParams['_action'] == 'logout') or (request.queryParams['_action'] == 'validate')}}"
    },
    {
        "comment": "Allow base action requests for users",
        "destination": [
            {
                "paths": [
                    "&{amBase}/json/realms/root/users"
                ]
            }
        ],
        "when": "${request.queryParams['_action'] == 'idFromSession'}"
    },
    {
        "comment": "Allow subrealm requests for sessions, serverinfo, and users",
        "destination": [
            {
                "paths": [
                    "&{amBase}/json/realms/root/realms/{subrealm}/sessions",
                    "&{amBase}/json/realms/root/realms/{subrealm}/serverinfo/*",
                    "&{amBase}/json/realms/root/realms/{subrealm}/users"
                ]
            }
        ]
    },
    {
        "comment": "Allow access to the XUI",
        "destination": [
            {
                "paths": [
                    "^&{amBase}/XUI"
                ]
            }
        ]
    },
    {
        "comment": "Allow access to the legacy UI for logout",
        "destination": [
            {
                "paths": [
                    "&{amBase}/UI/Logout"
                ]
            }
        ]
    }
]

```

```

    },
    {
      "comment": "Allow SAML v2.0 requests",
      "destination": [
        {
          "paths": [
            "^&{amBase}/ArtifactResolver/",
            "^&{amBase}/Consumer/",
            "^&{amBase}/IDPSloPOST/",
            "^&{amBase}/IDPSloRedirect/",
            "^&{amBase}/IDPSloSoap/",
            "^&{amBase}/SSORedirect/",
            "^&{amBase}/idpsaehandler/",
            "^&{amBase}/saml2/jsp/"
          ]
        }
      ]
    },
    ],
    "failureHandler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 404,
        "headers": {
          "Content-Type": [
            "text/html; charset=UTF-8"
          ]
        }
      },
      "entity": "<html><p>HTTP 404 Not Found</p></html>"
    }
  }
}
],
"handler": "ReverseProxyHandler"
}
}
}

```

Source: [protect-am.json](#)

Notice the key features of the route:

- An **AllowOnlyFilter** defines the rules for requests PingGateway allows; PingGateway denies all requests not explicitly allowed.



Tip

Adapt the route for the deployment, for example, by setting the `amBase`, `amInstanceUrl`, and `subrealm` properties.

- When access to a resource is denied, PingGateway returns HTTP 404 Not Found.



Tip

In deployment, avoid leaking information by returning the same response for missing and denied resources.

When you save the updated route file, PingGateway reloads it.

Validation

1. Try an allowed request.

In your browser's privacy or incognito mode, go to the XUI login page for the subrealm, such as <https://ig.example.com:8443/am/XUI/?realm=/customers#login> in this example.

PingGateway displays the login page for the realm.

2. Try a request that's not allowed.

In your browser's privacy or incognito mode, go to the top-level realm server version information resource, such as <https://ig.example.com:8443/am/json/serverinfo/version>.

PingGateway returns 404 and displays a message: `HTTP 404 Not Found`.

3. Notice you can still access AM directly, as long as you don't traverse PingGateway.

For example, go to the base URL for AM, such as <http://am.example.com:8088/am>.

AM displays the login page.




Tip

In deployment, route client traffic to AM through PingGateway, as for other protected applications. Don't expose AM endpoints directly.

PingGateway as a microgateway

This section describes how to use the ForgeRock Token Validation Microservice to resolve and cache OAuth 2.0 access tokens when protecting API resources. The section is based on the example in [Introspecting stateful access tokens](#), in the Token Validation Microservice's *User guide*.

For information about the architecture, refer to [PingGateway as a microgateway](#). The following figure illustrates the flow of information when a client requests access to a protected microservice, providing a stateful access token as credentials:



Before you start, download and run the sample application as described in [Using the sample application](#). The sample application acts as Microservice A.

1. Set up the example in [Introspect stateful access tokens](#), in the Token Validation Microservice's *User guide*.
2. In AM, edit the microservice client to add a scope to access the protected microservice:
 1. Select **Applications > OAuth 2.0 > Clients**.
 2. Select `microservice-client`, and add the scope `microservice-A`.
3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/mgw.json
```

Windows

```
%appdata%\OpenIG\config\routes\mgw.json
```

```
{
  "properties": {
    "introspectOAuth2Endpoint": "http://mstokval.example.com:9090"
  },
  "capture": "all",
  "name": "mgw",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/mgw')}",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "TokenIntrospectionAccessTokenResolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "endpoint": "&{introspectOAuth2Endpoint}/introspect",
                "providerHandler": "ForgeRockClientHandler"
              }
            }
          }
        },
        {
          "name": "ReverseProxyHandler-1",
          "type": "ReverseProxyHandler",
          "config": {
            "uri": "http://app.example.com:8081"
          }
        }
      ],
      "scopes": ["microservice-A"]
    }
  },
  "handler": "ReverseProxyHandler"
}
```

Source: [mgw.json](#)

Notice the following features of the route:

- The route matches requests to PingGateway on `http://ig.example.com:8080/home/mgw`, and rebases them to the sample application, on `http://app.example.com:8081`.
- The OAuth2ResourceServerFilter expects an OAuth 2.0 access token in the header of the incoming authorization request, with the scope `microservice-A`.
- If the filter successfully validates the access token, the ReverseProxyHandler passes the request to the sample application.

4. Test the setup:

1. With AM, PingGateway, the Token Validation Microservice, and the sample application running, get an access token from AM, using the scope `microservice-A`:

```
$ mytoken=$(curl -s \
--request POST \
--url http://am.example.com:8088/openam/oauth2/access_token \
--user microservice-client:password \
--data grant_type=client_credentials \
--data scope=microservice-A --silent | jq -r .access_token)
```

2. View the access token:

```
$ echo $mytoken
```

3. Call PingGateway to access microservice A:

```
$ curl -v --header "Authorization: Bearer ${mytoken}" http://ig.example.com:8080/home/mgw
```

The home page of the sample application is displayed.

PingGateway and PingOne

These pages show you how to use PingGateway with PingOne for SSO and API security. The examples target PingOne evaluators, administrators, and architects.

Before you start

Unless otherwise stated, the examples in these pages assume you have:

- PingGateway [installed](#).
- The sample application [installed](#).
- A PingOne environment as described in [Create a PingOne environment](#).
- A PingOne test user as described in [Add a PingOne test user](#).

Create a PingOne environment

In the PingOne console, create an environment with the following values:

- **Select a solution for your Environment:** Build your own solution
- **Select solution(s) for your Environment:** PingOne SSO
- **ENVIRONMENT NAME:** My environment
- **DESCRIPTION:** OIDC My environment
- **ENVIRONMENT TYPE:** Sandbox

Learn more in the PingOne documentation on [Adding an environment](#).

Add a PingOne test user

1. In the PingOne environment under **Directory > Users**, add a user.

To match a user known to the sample application, use the following values:

- **Given Name:** Wilhelm
- **Family Name:** Wolkig
- **Username:** wolkig
- **Email:** wolkig@example.com
- **Password:** Click **Generate Password** and record the generated password.

Learn more in the PingOne documentation on [Adding a user](#).

2. Under **Settings > Environment Properties > URLs**, copy the **Self-Service Url** for your environment.
3. In your browser's privacy or incognito mode, go to the URL you copied and sign on as the user you created.
4. When prompted, change the password so you won't have to change it again when trying an example.

To match the credentials to those known to the sample application, set the new password to `Geh3imnis!` .

PingGateway with PingOne as an OIDC provider

This example sets up PingOne as an OIDC provider with PingGateway as a relying party.

Prepare PingOne

After you [prepare the PingOne environment and test user](#), follow these steps to [create a PingOne OIDC web application](#):

1. In the environment, create a web application with the following values:
 - **Application Name:** `oidc_client`
 - **Description:** `OIDC client`
 - **Application Type:** `OIDC Web App`
2. In the application, select the **Overview** panel and click **Protocol OpenID Connect**.
3. In the **Redirect URIs** field, add `https://ig.example.com:8443/home/id_token/callback` and save the application.
4. In the **Overview** panel, click **Resource Access**, select the `email` and `profile` scopes in addition to the default `openid` scope, and click **Save**.

Learn more from the PingOne documentation on [Editing an application - OIDC](#).

5. At the top-right of the page, click the slider to enable the application.
6. Go to the **Configuration** panel and make a note of the following values in the **URLs** drop-down list:
 - **OIDC Discovery Endpoint**
 - **Client ID**
 - **Client Secret**

You need the values to set up PingGateway.

Prepare PingGateway

1. Add the following basic PingGateway configuration if you have not already done so:
 1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
 2. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```



```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/..*\\\\\\\\.ico$')
or matchesWithRegex(request.uri.path, '^/..*\\\\\\\\.gif$')}",
  "handler" : "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) 

2. Base64-encode the OIDC application's **Client Secret** and set the value as an environment variable:

```
$ export OIDC_SECRET_ID='<base64-encoded-client-secret>'
```

3. Add the following route to PingGateway, replacing the following property values with those of the OIDC application:

- **OIDC_Discovery_Endpoint**: The OIDC discovery endpoint for the client application you registered.
- **Client_ID**: The client ID of the application.

Linux

```
$HOME/.openig/config/routes/oidc-ping.json
```

Windows

```
%appdata%\OpenIG\config\routes\oidc-ping.json
```

```

{
  "name": "oidc-ping",
  "condition": "${find(request.uri.path, '^/home/id_token')}",
  "properties": {
    "OIDC_Discovery_Endpoint": "OIDC Discovery endpoint of the web app",
    "Client_ID": "Client ID of the web app"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AuthenticatedRegistrationHandler-1",
      "type": "Chain",
      "config": {
        "filters": [
          {
            "name": "ClientSecretBasicAuthenticationFilter-1",
            "type": "ClientSecretBasicAuthenticationFilter",
            "config": {
              "clientId": "&{Client_ID}",
              "clientSecretId": "oidc.secret.id",
              "secretsProvider": "SystemAndEnvSecretStore-1"
            }
          }
        ],
        "handler": "ForgeRockClientHandler"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "AuthorizationCodeOAuth2ClientFilter-1",
          "type": "AuthorizationCodeOAuth2ClientFilter",
          "config": {
            "clientEndpoint": "/home/id_token",
            "failureHandler": {
              "type": "StaticResponseHandler",
              "config": {
                "status": 500,
                "headers": {
                  "Content-Type": [
                    "text/html; charset=UTF-8"
                  ]
                }
              },
              "entity": "<html><body>Error in OAuth 2.0 setup.<br> ${contexts.oauth2Failure.exception.message}</body></html>"
            }
          }
        },
        "registrations": [
          {
            "name": "oauth2-client",
            "type": "ClientRegistration",
            "config": {
              "clientId": "${Client_ID}",
              "issuer": {

```

```

        "name": "PingOne",
        "type": "Issuer",
        "config": {
            "wellKnownEndpoint": "&{OIDC_Discovery_Endpoint}"
        }
    },
    "scopes": [
        "openid",
        "profile",
        "email"
    ],
    "authenticatedRegistrationHandler": "AuthenticatedRegistrationHandler-1"
}

}

],
"requireHttps": false,
"cacheExpiration": "disabled"
}

}

],
"handler": {
    "type": "StaticResponseHandler",
    "name": "HTMLResponse",
    "config": {
        "status": 200,
        "entity": "<!DOCTYPE html><html><head><title>Authentication Success</title></head><body><p>Welcome, ${attributes.openid.user_info.preferred_username}!</p><code>${attributes.openid.user_info}</code></body></html>",
        "headers": {
            "Content-Type": [
                "text/html"
            ]
        }
    }
}

}

}

}

}

}

```

Source: [oidc-ping.json](#)

4. Restart PingGateway.

Validation

1. In your browser's privacy or incognito mode, go to https://ig.example.com:8443/home/id_token.

PingOne displays the sign-on page.

2. Sign on to PingOne as the test user.

The route displays a welcome page:

```
Welcome, wolkig!
```

```
{sub=..., preferred_username=wolkig, given_name=Wilhelm, updated_at=..., family_name=Wolkig,
email=wolkig@example.com, ...}
```

PingGateway with PingOne as a SAML IdP

This example shows how to use PingOne as the identity provider with unsigned/unencrypted assertions.

Before you start

1. Add the following basic PingGateway configuration if you have not already done so:
 1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
 2. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*/.*\\.ico$')
or matchesWithRegex(request.uri.path, '^/.*/.*\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

2. Set up the network:

Add `sp.example.com` to your `/etc/hosts` file:

```
127.0.0.1 localhost am.example.com ig.example.com app.example.com sp.example.com
```

Traffic to the application is proxied through PingGateway, using the host name `sp.example.com`.

3. Save the `sp.xml` file as the SAML service provider configuration file `$HOME/.openig/SAML/sp.xml`.

Prepare PingOne

1. Prepare the PingOne environment and test user.

Make sure you match the test user's credentials to those known to the sample application.

2. In the PingOne environment, create a SAML web application with the following values:

- **Application Name:** `saml_app`
- **Description:** `SAML application`
- **Application Type:** `SAML Application`

3. In the application, select the **Import Metadata** panel, add the SAML configuration file `sp.xml` and save the application.

4. On the **Attribute Mappings** panel, click (edit) and add the following mappings:

saml_app	PingOne
cn	Given Name
sn	Family Name

5. On the **Configuration** panel, click (edit) and set the SLO BINDING's **SUBJECT NAMEID FORMAT** to `urn:oasis:names:tc:SAML:2.0:nameid-format:transient`.

6. On the **Configuration** panel, click **Download Metadata** and save the downloaded file as the identity provider configuration file `$HOME/.openig/SAML/idp.xml`.

7. On the **Configuration** panel, record the **Initiate Single Sign-on URL**.

You need the value to set up PingGateway.

8. At the top-right of the page, click the slider to enable the application.

Learn more from the PingOne documentation [Add a SAML application](#) .

Prepare PingGateway

1. Copy the following [example SAML configuration files](#) to `$HOME/.openig/SAML` and edit them to match your configuration:

File	Required changes
<code>FederationConfig.properties</code>	None
<code>fedlet.cot</code>	Replace <code>idp-entityID</code> with the value of <code>EntityDescriptor entityID</code> in <code>idp.xml</code> .
<code>idp-extended.xml</code>	Replace <code>idp-entityID</code> with the value of <code>EntityDescriptor entityID</code> in <code>idp.xml</code> .

File	Required changes
sp-extended.xml	None

2. Make sure the PingGateway configuration at `$HOME/.openig/SAML` contains the following files:

```
$ ls -l $HOME/.openig/SAML
```

Output

```
FederationConfig.properties
fedlet.cot
idp-extended.xml
idp.xml
sp-extended.xml
sp.xml
```

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/saml-filter.json
```

Windows

```
%appdata%\OpenIG\config\routes\saml-filter.json
```

```

{
  "name": "saml-filter",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home')}",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SamlFilter",
          "type": "SamlFederationFilter",
          "config": {
            "assertionMapping": {
              "name": "cn",
              "surname": "sn"
            },
            "subjectMapping": "sp-subject-name",
            "redirectURI": "/home/saml-filter"
          }
        },
        {
          "name": "SetSamlHeaders",
          "type": "HeaderFilter",
          "config": {
            "messageType": "REQUEST",
            "add": {
              "x-saml-cn": [ "${toString(session.name)}" ],
              "x-saml-sn": [ "${toString(session.surname)}" ]
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

Source: [saml-filter.json](#)

4. Restart PingGateway.

Validation

Test IdP-initiated login:

1. In your browser's privacy or incognito mode, go to the URL given by the web application property **Initiate Single Sign-on URL**.

PingOne displays the sign-on page.

2. Sign on to PingOne as the test user.

PingGateway displays the sample application home page.

Test SP-initiated login:

1. In your browser's privacy or incognito mode, go to <https://sp.example.com:8443/home>.

2. Sign on as the test user.

The request is redirected to the sample application.

PingGateway displays the sample application home page.



Tip

If a request returns an HTTP 414 URI Too Long error, read [URI Too Long error](#).

PingOne Authorize integration with PingGateway

Use [PingOne Authorize](#) with PingGateway to protect APIs and web applications. When you add a [PingOneApiAccessManagementFilter](#) to a route, PingGateway requests an authorization decision from PingOne Authorize.

About the example

This example uses PingOne as the IdP and OIDC provider. It uses PingOne Authorize [API access management](#) capabilities to protect a sample application path.

When a user tries to access a sample application resource, PingGateway directs the user to PingOne for authentication. On successful authentication, PingOne issues an ID token for the user and an access token that PingGateway uses when getting an access decision from PingOne Authorize. If PingGateway was protecting an API rather than a sample application page, the access token would act as the bearer token that an OAuth 2.0 API client application provides to access the API. In this example, however, PingGateway gets the access token because it's acting as the client application.

PingOne Authorize either grants access or denies it and then PingGateway enforces the decision from PingOne Authorize.

In this example, the decision to authorize access depends on group membership. Learn more about a similar decision to authorize access that depends on group membership in the [Controlling access to specific API operations](#) tutorial in the PingOne Authorize documentation.

Before you begin

If you haven't already done so:

- Install PingGateway.
- Install the sample application.
- Create a PingOne environment.

Learn more in the [PingGateway and PingOne examples](#).

Configure PingOne

Complete the tasks in this section to prepare the PingOne environment for this example.

On completing these tasks, you will have:

- A group for users who can access the sample application

- A test user who belongs to the group
- A test user who doesn't belong to the group
- PingOne Authorize enabled in the environment
- An OIDC client profile for PingGateway to authenticate users with PingOne
- An API gateway account for PingGateway to authenticate to PingOne Authorize
- An API service that PingOne Authorize uses to make access decisions
- PingOne configured to issue access tokens to PingGateway alongside ID tokens for users

Add a group who can access to the sample application

In your PingOne environment, go to **Directory > Groups** and add a group named **Full access**. This group's members get access to the sample application.

Learn more in [Creating a group](#) in the PingOne documentation.

Add a test user who gets access

If you haven't already done so, add a test user.

1. Go to **Directory > Users** and add a user:
 - **Given Name:** Wilhelm
 - **Family Name:** Wolkig
 - **Username:** wolkig
 - **Email:** wolkig@example.com
 - **Password:** Click **Generate Password** and record the generated password.

Learn more in the PingOne documentation on [Adding a user](#).

2. In the profile for **wolkig**, add the user to the **Full access** group and save your work.

In this example, PingOne Authorize will grant access to the sample application based on membership in this group.

Add a test user who doesn't get access

1. Add a second test user:
 - **Given Name:** Demo
 - **Family Name:** User
 - **Username:** demo
 - **Email:** demo@example.com
 - **Password:** Click **Generate Password** and record the generated password.

2. *Don't* add the **demo** user to the **Full access** group.

The `demo` user won't get access to the sample application.

Enable PingOne Authorize

[Add PingOne Authorize to the environment](#).

Add a PingGateway OIDC client profile

In this example, PingGateway acts as a PingOne OIDC client (RP) where PingOne is the OIDC provider for user identities and authentication.

Follow these steps to [create a PingOne OIDC web application for PingGateway](#):

1. Go to **Applications > Applications** and click + to add a new application:
 - **Application Name:** `oidc_client`
 - **Application Type:** `OIDC Web App`
2. In the application **Overview**, click **Protocol OpenID Connect** , add a redirect URI, and save your work:
 - **Redirect URIs:** `https://ig.example.com:8443/home/sso/callback`.
3. Copy the following values from the application **Overview** and save them somewhere convenient for later use:
 - **General > Client ID**
 - **General > Client Secret**
 - **Connection Details > OIDC Discovery Endpoint**

You need the values to set up PingGateway.

4. Enable the application.

Add an API gateway

PingGateway uses a PingOne API gateway account to authenticate to PingOne Authorize:

1. Go to **Authorization > API Gateways** and click +.
2. Use `PingGateway` as the **Name** and save your work.
3. Next to **Credentials**, click + and copy the API gateway credential somewhere convenient for later use.

You need the credential value to set up PingGateway.

Add an API service

PingOne Authorize bases authorization decisions on an API service definition. Follow these steps to add the API service:

1. Go to **Authorization > API Services** and add a new API service with the following values:
 - **Name:** `PingGateway`
 - **Base URLs:** `https://app.example.com:8444` (for the sample application)
`https://ig.example.com:8443` (for PingGateway)

2. Define an operation for protected access to the sample application.

This grants users in the **Full access** group access to the sample application page at **/home/sso**:

- **Method:** GET
- **Paths:** /home/sso
- **Rules:** The user must be a member of any of these groups: **Full access**

Learn more in the PingOne Authorize documentation on [Defining operations for protected actions](#).

3. Click **Deploy** to deploy the new API service.

Make sure PingGateway gets an access token

When you added the PingGateway API service, PingOne Authorize automatically created a corresponding PingOne resource by default. Update the resource so PingOne issues access tokens to PingGateway.

To do so, set the audience claim (**aud**) to the PingGateway URL and add a scope specifically for PingGateway:

1. Go to **Applications > Resources** and click the **PingGateway** resource.
2. Edit the following settings and save your work:
 - **Audience:** `https://ig.example.com:8443`
 - **Scopes:** Click **Add Scope**, add **Scope Name:** **gateway**, and click **Save**.
3. Go to **Applications > Applications** and click **oidc_client**, the OIDC application for PingGateway.
4. Edit **Allowed Scopes**, select the **gateway** scope checkbox, and click **Save**.

PingOne is now ready to issue access tokens with the scope **gateway** to PingGateway. PingGateway uses the tokens when requesting PingOne Authorize access decisions.

Configure PingGateway

1. Prepare the secrets PingGateway needs to act as an OIDC RP and an API gateway when making requests to PingOne.

Base64-encode the API gateway's credential and the OIDC application's client secret and set both values as environment variables:

```
$ export GATEWAY_SECRET_ID='<base64-encoded-api-gateway-credential>'
$ export OIDC_SECRET_ID='<base64-encoded-client-secret>'
```

2. Restart PingGateway to read the environment variables.
3. Add the following route to PingGateway, replacing the property values to match those from the environment:

Linux

```
$HOME/.openig/config/routes/pingone-aam.json
```

Windows

```
%appdata%\OpenIG\config\routes\pingone-aam.json
```

```

{
  "name": "pingone-aam",
  "condition": "${find(request.uri.path, '^/home/sso')}",
  "baseURI": "https://app.example.com:8444",
  "properties": {
    "gatewayServiceUrl": "https://http-access-api.pingone.eu/v1/environments/test-environment-id",
    "oidcClientId": "oidc-client-id",
    "oidcWellKnownEndpoint": "https://auth.pingone.eu/test-environment-id/as/.well-known/openid-configuration"
  },
  "heap": [
    {
      "name": "BlindTrustReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "comment": "For evaluation and testing only",
      "config": {
        "tls": {
          "type": "ClientTlsOptions",
          "config": {
            "trustManager": {
              "type": "TrustAllManager"
            },
            "hostnameVerifier": "ALLOW_ALL"
          }
        }
      }
    },
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AuthenticatedRegistrationHandler-1",
      "type": "Chain",
      "config": {
        "filters": [
          {
            "name": "ClientSecretBasicAuthenticationFilter-1",
            "type": "ClientSecretBasicAuthenticationFilter",
            "config": {
              "clientId": "${oidcClientId}",
              "clientSecretId": "oidc.secret.id",
              "secretsProvider": "SystemAndEnvSecretStore-1"
            }
          }
        ]
      },
      "handler": "ForgeRockClientHandler"
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "AuthorizationCode0Auth2ClientFilter",
          "config": {
            "clientEndpoint": "/home/sso",
            "failureHandler": {
              "type": "StaticResponseHandler",
              "config": {

```

```

        "status": 500,
        "headers": {
          "Content-Type": [
            "text/plain"
          ]
        },
        "entity": "Error: ${contexts.oauth2Failure.error}\nDescription: ${contexts.oauth2Failure.description}"
      }
    },
    "registrations": [
      {
        "type": "ClientRegistration",
        "config": {
          "clientId": "&{oidcClientId}",
          "issuer": {
            "type": "Issuer",
            "config": {
              "wellKnownEndpoint": "&{oidcWellKnownEndpoint}"
            }
          },
          "scopes": [
            "openid",
            "gateway"
          ],
          "authenticatedRegistrationHandler": "AuthenticatedRegistrationHandler-1"
        }
      }
    ]
  },
  {
    "type": "PingOneApiAccessManagementFilter",
    "config": {
      "gatewayServiceUri": "&{gatewayServiceUri}",
      "secretsProvider": "SystemAndEnvSecretStore-1",
      "gatewayCredentialSecretId": "gateway.secret.id",
      "accessToken": "${attributes.openid.access_token}",
      "_sidebandHandler": {
        "_comment": "s/_sidebandHandler/sidebandHandler/ to troubleshoot AAM decisions",
        "type": "ClientHandler",
        "capture": "all"
      }
    }
  },
  {
    "handler": "BlindTrustReverseProxyHandler"
  }
}

```

Source: [pingone-aam.json](#)

Notice the following features of the route:

- The route properties use the settings you collected from the PingOne environment.
- The heap has:
 - A handler to trust the self-signed sample application certificate for HTTPS blindly.

**Note**

For production applications and APIs, use certificates you don't have to trust blindly.

- A `SystemAndEnvSecretStore` to get the base64-encoded secrets from the environment variables.
- A handler to get an ID token and access token.
- The `AuthorizationCodeOAuth2ClientFilter` authenticates the end user.
- The `PingOneApiAccessManagementFilter` uses the access token when making the authorization decision request to PingOne Authorize.
- If PingOne Authorize grants access, the `BlindTrustReverseProxyHandler` gets the resource from the sample application.

Validation

Access granted to a group member

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/sso>.

PingOne displays the sign-on page.

2. Sign on to PingOne as the `wolkig` test user.

PingOne Authorize grants access and PingGateway displays the sample application home page:



Welcome

SAMPLE APPLICATION HOME PAGE

The sample application is a mockup web application for testing PingGateway configurations.

REQUEST INFORMATION

```

Version HTTP/2
Method GET
URI /home/sso
Cookies IG_SESSIONID=kGA_cLXhcHwgOUbLIc3l7MCriok
Headers accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
  accept-encoding: gzip, deflate, br, zstd
  accept-language: en-GB,en;q=0.9
  cookie: IG_SESSIONID=kGA_cLXhcHwgOUbLIc3l7MCriok
  priority: u=0, i
  referer: https://apps.pingone.eu/
  sec-ch-ua: "Chromium";v="128", "Not;A=Brand";v="24", "Google Chrome";v="128"
  sec-ch-ua-mobile: ?0
  sec-ch-ua-platform: "macOS"
  sec-fetch-dest: document
  sec-fetch-mode: navigate
  sec-fetch-site: cross-site
  sec-fetch-user: ?1
  upgrade-insecure-requests: 1
  user-agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/128.0.0.0 Safari/537.36
Authority app.example.com:8444
Query
Parameters

```

Access denied for a non-member

1. In your browser's privacy or incognito mode, go again to <https://ig.example.com:8443/home/sso>.

PingOne displays the sign-on page.

2. Sign on to PingOne as the **demo** test user.

PingOne Authorize denies access to the sample application and the browser displays the result:

```

{
  "id" : "<uuid>",
  "code" : "ACCESS_FAILED",
  "message" : "The request could not be completed. You do not have access to this resource."
}

```

Tip

When PingOne Authorize denies access or the example route fails to get an access token, the browser displays text, which isn't user-friendly.

If you are protecting web pages rather than an API, use a [StaticResponseHandler](#) to show a more friendly page to the user.

Troubleshooting

If you get unexpected errors, try these debugging options:

- In the PingGateway route, update the `PingOneApiAccessManagementFilter` to enable the capture decorator.

Change `"_sidebandHandler"` to `"sidebandHandler"` and save your work to let PingGateway reload the route.

- In the PingOne environment, go to **Authorization > Recent Decisions**, select the PingGateway decision endpoint, and select a decision to visualize.

PingOne shows you how PingOne Authorize arrived at the authorization decision.

On the **Request** and **Response** tabs, you find detailed traces of the parameters for each. Learn more in [Recent decisions](#) in the PingOne Authorize documentation.

PingOne Protect integration with PingGateway

Use PingOne Protect risk evaluations with web applications protected by PingGateway. PingGateway routes requests based on the level of risk PingOne Protect associates with them.


Risk management

PingOne Protect monitors end-user requests and generates a risk score of low, medium, or high based on the user's activity and device context. You configure and fine-tune risk policies and train risk models prior to using PingGateway with PingOne Protect. Learn more in [Threat Protection using PingOne Protect](#).

You configure PingGateway routes to react to risk scores from PingOne Protect dynamically. For example, if the risk score is medium, PingGateway can direct the user to complete additional verification. If the risk score is high, PingGateway can deny access to the resource instead.

The following sequence diagram shows the PingGateway configuration objects involved in a risk management flow:

- The `PingOneProtectEvaluationFilter` calls PingOne Protect.
- It populates the `PingOneProtectEvaluationContext` based on the response.
- The `PingOneProtectThreatLevelRoutingHandler` dispatches the request based on its risk level.
- After prompting the user to complete additional actions following a risk evaluation, the `PingOneProtectFeedbackSuccessFilter` or `PingOneProtectFeedbackFailureFilter` can send feedback to PingOne Protect and override the risk level in the session context.



1. The initial request enters a Chain configured for risk evaluation with PingOne Protect.
2. The PingOneProtectEvaluationFilter includes data about the request in an API call to PingOne Protect.
3. PingOne Protect provides a risk evaluation response.
4. The PingOneProtectEvaluationFilter populates the PingOneProtectEvaluationContext with the risk level based on the evaluation response and passes control to the PingOneProtectThreatLevelRoutingHandler.
- 5.-10. The PingOneProtectThreatLevelRoutingHandler dispatches the request based on the risk level. The downstream handler returns a response to the initial request that is appropriate for the risk level. The downstream handlers can prompt additional actions to verify the user's identity.

Although not shown in the sequence diagram, when a **medium** risk level leads to additional authentication steps and the user successfully completes the steps, a PingOneProtectFeedbackSuccessFilter included in the process updates PingOne Protect to indicate the successful outcome.

The sequence diagram also omits device profile data collection. When the PingOneProtectEvaluationFilter includes "deviceProfile" settings, PingGateway gathers profile data from the user-agent by sending it a self-submitting form page that uses JavaScript to retrieve the profile information. (If JavaScript is disabled in the browser, PingGateway can't get the device profile data.) PingGateway includes the device profile in PingOne Protect risk evaluation requests.

PingGateway runs at the outer edge of your systems, the place where all inbound traffic first arrives and all outbound traffic leaves, just inside the network infrastructure.

PingGateway is well-placed to capture signals about the traffic and its risk profile.

Example: protect against session degradation

Session degradation arises when a valid user session gets used in unexpected ways, increasing the risk the session has been hijacked or otherwise compromised. Session degradation is why we can't let users stay signed in forever unless we can authenticate them again.

Together, PingGateway and PingOne Protect help you automate fine-grained risk evaluation, avoiding the distraction of additional authentication steps unless they're required for a risky request. Users stay signed in with their current session, which they experience as a **keep me signed in** feature. You nevertheless protect their assets from hijacking without needing constantly to verify their identity.

This example demonstrates risk management where the principal already has a valid session. The example doesn't demonstrate how to configure PingOne Protect.

When PingOne Protect returns a risk evaluation, PingGateway responds based on the risk level. This example demonstrates the following responses:

High risk

Deny access to the requested resource.

Although not shown in this brief example, you could route the request to a honeypot.

Medium risk

Prompt the user to reauthenticate to verify their identity.

The user can perform step up or transactional authentication at this point.

Low risk

Let the request pass through unchanged.

Before you begin

- Configure PingOne Protect. Learn more in the [PingOne Protect](#) documentation.
- Implement [CDSSO with PingOne Advanced Identity Cloud](#) or [CDSSO for self-managed AM](#). This example opts for CDSSO with PingOne Advanced Identity Cloud. When using self-managed AM, also read [Self-managed AM](#).
- For additional protection with medium-risk requests, implement [Step up authorization for a transaction](#).
- Verify you can successfully authenticate with CDSSO to the sample application.

Configure PingGateway

What follows extends the CDSSO route to protect against session degradation:

1. Sign on to the PingOne environment with PingOne Protect as an administrator and add an application for PingGateway.

Use the following hints regarding non-default configuration settings:

Setting	Value
Application Name	PingGateway
Application Type	Worker
Application profile > Roles	Environment Admin Identity Data Admin

2. In the PingOne environment, find and record the values of the following settings:

Property	Description
Environment UUID	This is <code><env-uuid></code> in other property examples.
PingGateway client ID	PingGateway credentials to access PingOne as the application you registered.
PingGateway client secret	
Policy set UUID	The PingOne Protect policy for risk evaluation requests.
Service endpoint	For risk evaluation and feedback service requests. Example: <code>https://api.pingone.eu/v1/environments/<env-uuid></code>
Token endpoint	For PingGateway to get an access token. Example: <code>https://auth.pingone.eu/<env-uuid>/as/token</code>

- In the PingGateway `AdminHttpApplication (admin.json)` file, make sure the maximum total headers size is large enough to accommodate request headers for the device profile cookies.

After PingGateway collects device profile data, it stores the data in cookies on the user-agent. The user-agent returns these to PingGateway in the `Cookie` request header. Set the `maxTotalHeadersSize` for the PingGateway server ports large enough to avoid HTTP 431 Request Header Fields Too Large errors; for example:

```
"connectors": [
  {
    "port": 8080,
    "maxTotalHeadersSize": 32768
  },
  {
    "port": 8443,
    "maxTotalHeadersSize": 32768,
    "tls": "TlsConf"
  }
],
```

You can skip this step if you don't use `"deviceProfile"` settings in the `PingOneProtectEvaluationFilter`.

- Set an environment variable for the PingGateway client secret.

PingGateway uses a `SystemAndEnvSecretStore` to retrieve the client secret, so you must base64-encode the value you found in the PingOne application profile:

```
$ export CLIENT_SECRET_ID='<base-64-encoded-client-secret>'
```

- Restart PingGateway to load the updated `admin.json` settings and the environment variable.
- Update the CDSSO route to add risk management:

```

{
  "name": "risk",
  "baseURI": "https://app.example.com:8444/login",
  "condition": "${find(request.uri.path, '^/home/cdsso')}",
  "properties": {
    "amInstanceUrl": "https://myTenant.forgeblocks.com/am",
    "clientId": "my-application-client-id",
    "policySetId": "my-policy-set-id",
    "serviceEndpoint": "https://api.pingone.eu/v1/environments/my-environment-id",
    "tokenEndpoint": "https://auth.pingone.eu/my-environment-id/as/token"
  },
  "heap": [
    {
      "name": "BlindTrustReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "comment": "For evaluation and testing only",
      "config": {
        "tls": {
          "type": "ClientTlsOptions",
          "config": {
            "trustManager": {
              "type": "TrustAllManager"
            },
            "hostnameVerifier": "ALLOW_ALL"
          }
        }
      }
    },
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "${amInstanceUrl}",
        "realm": "/alpha",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "sessionCache": {
          "enabled": false
        }
      }
    },
    {
      "name": "ClientCredentialsOAuth2ClientFilter-1",
      "type": "ClientCredentialsOAuth2ClientFilter",
      "config": {
        "tokenEndpoint": "${tokenEndpoint}",
        "scopes": [
          "openid",
          "profile",
          "email",
          "p1"
        ],
        "endpointHandler": {

```

```

        "name": "AccessTokenHandler",
        "type": "Chain",
        "config": {
          "filters": [
            {
              "type": "ClientSecretBasicAuthenticationFilter",
              "config": {
                "clientId": "&{clientId}",
                "clientSecretId": "client.secret.id",
                "secretsProvider": "SystemAndEnvSecretStore-1"
              }
            }
          ],
          "handler": "ForgeRockClientHandler"
        }
      },
    },
    {
      "name": "RiskEndpointHandler",
      "type": "Chain",
      "config": {
        "filters": [
          "ClientCredentialsOAuth2ClientFilter-1"
        ],
        "handler": "ForgeRockClientHandler"
      }
    },
    {
      "name": "PingOneService-1",
      "type": "PingOneService",
      "config": {
        "serviceEndpoint": "&{serviceEndpoint}",
        "endpointHandler": "RiskEndpointHandler"
      }
    },
    {
      "name": "StepUpHandler",
      "type": "Chain",
      "config": {
        "filters": [
          {
            "name": "PolicyEnforcementFilter-1",
            "type": "PolicyEnforcementFilter",
            "config": {
              "application": "PEP-CDSSO",
              "ssoTokenSubject": "${contexts.cdsso.token}",
              "amService": "AmService-1"
            }
          },
          {
            "name": "SuccessFeedbackFilter",
            "type": "PingOneProtectFeedbackSuccessFilter",
            "config": {
              "pingOneService": "PingOneService-1",
              "postEvaluationAssumedRiskLevel": "low"
            }
          }
        ],
        "handler": "ReverseProxyHandler"
      }
    },
  ],
},

```

```

{
  "name": "FailureHandler",
  "type": "Chain",
  "config": {
    "filters": [
      {
        "name": "FailureFeedbackFilter",
        "type": "PingOneProtectFeedbackFailureFilter",
        "config": {
          "pingOneService": "PingOneService-1"
        }
      }
    ],
    "handler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 403,
        "headers": {
          "Content-Type": [
            "text/plain; charset=UTF-8"
          ]
        },
        "entity": "HTTP 403 Forbidden"
      }
    }
  }
},
{
  "name": "PingOneProtectThreatLevelRoutingHandler",
  "type": "Chain",
  "config": {
    "filters": [
      {
        "name": "CrossDomainSingleSignOnFilter-1",
        "type": "CrossDomainSingleSignOnFilter",
        "config": {
          "redirectEndpoint": "/home/cdsso/redirect",
          "authCookie": {
            "path": "/home",
            "name": "ig-token-cookie"
          },
          "amService": "AmService-1"
        }
      },
      {
        "name": "PingOneProtectEvaluationFilter-1",
        "type": "PingOneProtectEvaluationFilter",
        "config": {
          "pingOneService": "PingOneService-1",
          "policySet": "&{policySetId}",
          "userId": "${contexts.cdsso.claimsSet.getClaim('subname')}",
          "nonEvaluatedUrls": "${find(request.uri.path, '/home/cdsso/redirect')}",
          "deviceProfile": {
            "callbackEndpoint": "/home/cdsso/profilecallback"
          }
        }
      }
    ],
    "handler": {
      "name": "PingOneProtectThreatLevelRoutingHandler-1",
      "type": "PingOneProtectThreatLevelRoutingHandler",
      "config": {

```

```
    "levels": {  
      "low": "BlindTrustReverseProxyHandler",  
      "medium": "StepUpHandler",  
      "high": "FailureHandler"  
    }  
  }  
}  
}  
}
```

Source: [risk.json](#)

Notice the following features of the updated route:

- The route properties use the settings you collected from the PingOne environment.
Replace the placeholders in the route properties with the settings you collected.
- The heap has an evaluation endpoint handler to get an access token for risk evaluation requests.
- The PingOneProtectEvaluationFilter uses the evaluation endpoint handler to make the risk evaluation request and populate the PingOneProtectEvaluationContext (implicit in the configuration).
- The PingOneProtectThreatLevelRoutingHandler uses the context to route the request based on the risk level:
 - Low-risk requests pass through unchanged.
 - Medium-risk requests use step up authorization for the request.
 - High-risk requests and requests where the PingOneProtectEvaluationFilter failed to update the context get denied.

Validation

1. In your browser's privacy or incognito mode, go to <https://ig.ext.com:8443/home/cdsso>.

PingOne Advanced Identity Cloud displays the login page.

2. Log in to PingOne Advanced Identity Cloud as the test user.

After authentication, PingGateway gets an access token and uses it to make a risk evaluation request. The PingOneProtectThreatLevelRoutingHandler routes the result:

- Low-risk requests go directly to the sample app.
- Medium-risk requests prompt the user for the authorization passcode **7890**.
- PingGateway denies access to other requests.

You've successfully demonstrated risk management to prevent session degradation. Adapt the route to the specifics of your use case.

Self-managed AM

When you use transactional authorization with self-managed AM in this example, you must configure PingGateway to use *its* URI rather than the URI of the protected application when confirming the transaction.

You can do this by using a PolicyEnforcementFilter `"resourceUriProvider"` to rebase the protected URI on the PingGateway URI.

1. Add the following [ScriptableResourceUri.groovy](#)  script to PingGateway:

Linux

```
$HOME/.openig/scripts/groovy/ScriptableResourceUri.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\ScriptableResourceUri.groovy
```

```

package scripts.groovy

import org.forgerock.http.routing.UriRouterContext
import org.forgerock.http.util.Uris

/**
 * Sample scriptable {@code RequestResourceUriProvider} (for use with a {@code PolicyEnforcementFilter}).
 *
 * This sample script "rebases" the in-flight request URI on top of the original URI. The term "in-flight"
 * represents
 * the request's URI as it's manipulated as it progresses through the route. This is to ensure route
 * components have had
 * the opportunity to act on the request prior to policy evaluation - e.g. to manipulate query parameters they
 * may be
 * responsible for managing.
 *
 * <p>Example - indicates in-flight request URI's path, query and fragment retained and rebased on to original
 * URI:
 * <ul>
 * <li><b>original request URI</b>: https://ig.ext.com:8443/home?param1=1&param2</li>
 * <li><b>in-flight request URI</b>: http://app.example.com:8080/home?param2</li>
 * <li><b>result (rebased) URI</b>: https://ig.ext.com:8443/home?param2</li>
 * </ul>
 *
 * <p>Example config:
 * <pre>
 * {@code {
 *   "name" : "RebasingResourceUriProvider",
 *   "type" : "ScriptableResourceUriProvider",
 *   "config" : {
 *     "file" : "ScriptableResourceUri.groovy",
 *     "type": "application/x-groovy"
 *   }
 * }
 * }
 * }
 * </pre>
 *
 * <p>Example {@code PolicyEnforcementFilter} usage:
 * <pre>
 * {@code {
 *   "type" : "PolicyEnforcementFilter",
 *   "config" : {
 *     "amService" : "...",
 *     "application" : "...",
 *     "resourceUriProvider": "RebasingResourceUriProvider",
 *     ...
 *   }
 * }
 * }
 * }
 * </pre>
 */
def uriRouterContext = context.asContext(UriRouterContext.class)

URI originalUri = uriRouterContext.getOriginalUri();
URI requestUri = request.getUri().asURI();
URI pathAndParams = new URI(null,
                           null,
                           requestUri.getPath(),
                           requestUri.getQuery(),

```

```

        requestUri.getFragment());
logger.trace("ScriptableResourceUri rebasing {} with request parameters {}", originalUri, pathAndParams);
String rebasedUri = Uris.rebase(pathAndParams, originalUri).toASCIIString();
logger.trace("ScriptableResourceUri rebased to URI '{}'", rebasedUri);
return rebasedUri;

```

2. Add a reference to the script in the route heap:

```

{
  "name": "RebasingResourceUriProvider",
  "type": "ScriptableResourceUriProvider",
  "config": {
    "file": "ScriptableResourceUri.groovy",
    "type": "application/x-groovy"
  }
}

```

3. In the PolicyEnforcementFilter for the route, use the reference to the script in the `"resourceUriProvider"` setting:

```

{
  "name": "PolicyEnforcementFilter-1",
  "type": "PolicyEnforcementFilter",
  "config": {
    "application": "PEP-CDSSO",
    "ssoTokenSubject": "${contexts.cdsso.token}",
    "amService": "AmService-1",
    "resourceUriProvider": "RebasingResourceUriProvider"
  }
}

```

4. Make sure the route's `"amInstanceUri"` reflects your self-managed AM.

5. Save your changes to the route.

After PingGateway reloads the route, you can validate the scenario with your self-managed AM deployment.

PingGateway and PingOne Advanced Identity Cloud

These pages show how to use PingGateway with PingOne Advanced Identity Cloud for single sign-on and API security. They're for PingOne Advanced Identity Cloud evaluators, administrators, and architects.

Example installation

Unless otherwise stated, the examples with PingOne Advanced Identity Cloud assume the following installation:

- PingGateway installed on `http://ig.example.com:8080` , as described in the [Installing PingGateway](#) .
- Sample application installed on `http://app.example.com:8081` , as described in [Using the sample application](#).
- A PingOne Advanced Identity Cloud tenant with the default configuration, as described in the [PingOne Advanced Identity Cloud documentation](#) .

When using PingOne Advanced Identity Cloud, you need to know the value of the following properties:

- The root URL of your PingOne Advanced Identity Cloud tenant. For example, `https://myTenant.forgeblocks.com` .

The URL of the PingAM component of PingOne Advanced Identity Cloud is the root URL of your PingOne Advanced Identity Cloud tenant followed by `/am` . For example, `https://myTenant.forgeblocks.com/am` .
- The realm where you work. The examples in this document use `alpha` .

Prefix each realm in the hierarchy with the `realms` keyword. For example, `/realms/root/realms/alpha` .

If you use a different configuration, substitute in the procedures accordingly.

About authentication to PingOne Advanced Identity Cloud

PingOne Advanced Identity Cloud provides an authentication journey to validate the agent credentials with an Agent Data Store Decision node.

When you register PingGateway with PingOne Advanced Identity Cloud, PingOne Advanced Identity Cloud uses the journey to authenticate PingGateway.

Register a PingGateway agent in PingOne Advanced Identity Cloud

This procedure registers an agent profile for PingGateway.

1. Log in to the Advanced Identity Cloud admin UI as an administrator.
2. Click  **Gateways & Agents** > **+ New Gateway/Agent** > **Identity Gateway** > **Next** and use the hints in the following table to create the agent profile:

Field	Description	Example
ID	Set the unique agent profile name PingGateway uses to connect.	<code>ig_agent</code>

Field	Description	Example
Password	Store the password PingGateway uses to connect in the agent profile. Record the password to use when configuring PingGateway.	A strong password. The examples in the documentation use <code>password</code> and its base64-encoding <code>cGFzc3dvcmQ=</code> .
Use Secret Store for password	Store the password in a secret and reference the secret by its label. Follow the steps in Use the secret store for the password after you create the agent profile.	Click to enable
Secret Label Identifier	This field appears when you select Use Secret Store for password . This value represents the <code>identifier</code> part of the secret label for the agent. PingOne Advanced Identity Cloud uses the identifier to generate a secret label in the following format: <code>am.application.agents.identifier.secret</code> . Learn more in Secret labels . After setting this, add an ESV secret for the password and map the ESV to the secret label.	<code>ig</code>



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

3. Click **Save Profile > Done** to display the new agent profile.
4. (Optional) Add the list of **Redirect URLs** used in PingGateway routes and click **Save** to update the profile.

Use the secret store for the password

When you select **Use Secret Store for password** and set a secret label for the agent profile, PingOne Advanced Identity Cloud creates the secret label but the secret isn't yet defined or mapped to the label:


1. Define an ESV secret, such as `esv-ig_agent`, holding the password for PingGateway to connect.

The examples in the documentation use `password`.

Learn how in [creating ESV secrets](#). In production deployments, [restrict access to the password](#) from configuration placeholder and script contexts.

2. Map the ESV to the label created when you set the **Secret Label Identifier**:
 1. Click  **Native Consoles > Access Management > Secret Stores > ESV > Mappings > + Add mappings**.
 2. In the **Add Mapping** modal, select the label, such as `am.application.agents.ig.secret`, in the **Secret Label** list.
 3. In the **aliases** field, enter the ESV secret, such as `esv-ig_agent`, and click **Add**.

4. Click **Create** to add the mapping:



Learn more in [Map ESV secrets to secret labels](#).

Note the following points:

- If you update or delete the **Secret Label Identifier**, AM updates or deletes the corresponding mapping for the previous identifier unless another agent shares the mapping.
- When you rotate a secret, update the corresponding mapping.

Optional settings

In the AM admin UI, consider the following additional optional settings for the agent profile under **Applications > Agents > Identity Gateway > agent ID**:

1. To direct login to a custom URL instead of the default AM login page, configure **Login URL Template for CDSSO**.
2. To apply a different introspection scope, click **Token Introspection** and select a scope from the list.
3. Click **Save** to update the profile.

Set up a demo user in PingOne Advanced Identity Cloud

This procedure sets up a demo user in the alpha realm.

1. Log in to the Advanced Identity Cloud admin UI as an administrator.
2. Go to **Identities > Manage > Alpha realm - Users**, and add a user with the following values:
 - **Username:** demo
 - **First name:** demo
 - **Last name:** user
 - **Email Address:** demo@example.com

- **Password:** Ch4ng3!t

Recommendations

Use PingGateway with PingOne Advanced Identity Cloud as you would with any other service.

- During updates, individual PingOne Advanced Identity Cloud tenant servers go offline temporarily. PingGateway can receive HTTP 502 Bad Gateway responses for some requests during the update.

In your [ClientHandler](#) and [ReverseProxyHandler](#) configurations, configure PingGateway to retry operations when this occurs:


```
"retries": {  
  "enabled": true,  
  "condition": "${response.status.code == 502}"  
}
```

- Update PingGateway to use the latest version you can to benefit from fixes and improvements.

PingGateway and PingOne Advanced Identity Cloud

PingOne Advanced Identity Cloud simplifies the consumption of the identity platform. Meanwhile, many organizations have business web applications and APIs deployed across multiple clouds or on-premise.

PingGateway facilitates non-intrusive integration of your web applications and APIs with PingOne Advanced Identity Cloud for SSO and API security. The following image illustrates how PingGateway bridges your business to PingOne Advanced Identity Cloud:



Learn more in the [PingOne Advanced Identity Cloud documentation](#).

OAuth 2.0 and PingOne Advanced Identity Cloud

This example sets up OAuth 2.0, using the standard introspection endpoint, where PingOne Advanced Identity Cloud is the Authorization Server and PingGateway is the resource server.

For more information about PingGateway as an OAuth 2.0 resource server, refer to [Validating PingAM access tokens with introspection](#).



Important

This procedure uses the *Resource Owner Password Credentials* grant type. As suggested in [The OAuth 2.0 Authorization Framework](#), use other grant types whenever possible.

Before you start, prepare PingOne Advanced Identity Cloud, PingGateway, and the sample application as described in [Example installation for this guide](#).

1. Set up PingOne Advanced Identity Cloud:

1. Log in to the Advanced Identity Cloud admin UI as an administrator.
2. Make sure you are managing the `alpha` realm. If not, click the current realm at the top of the screen, and switch realm.
3. Go to  **Identities** > **Manage** >  **Alpha realm - Users**, and add a user with the following values:

- **Username:** `demo`
- **First name:** `demo`
- **Last name:** `user`
- **Email Address:** `demo@example.com`
- **Password:** `Ch4ng3!t`

4. Go to  **Custom Application** > **+ Custom Application** > **OIDC - OpenId Connect** > **Web** and add a web application with the following values:

- **Name:** `oauth2-client`
- **Owners:** `demo user`
- **Client Secret:** `password`
- (Optional) **Use Secret Store for password:** Select this to store the password in an ESV secret.

If you select this option, enter a **Secret Label Identifier**. This value represents the `identifier` part of the secret label for the client. PingOne Advanced Identity Cloud uses the identifier to generate a secret label in the following format: `am.applications.oauth2.client.identifier.secret`.

To complete the client profile, add an ESV secret for the password and map the ESV to the secret label. To learn more, read [Secret labels](#) in the PingOne Advanced Identity Cloud documentation.

- **Sign On > Grant Types:** Authorization Code, Resource owner Password Credentials
- **Sign On > Scopes:** mail

For more information, refer to PingOne Advanced Identity Cloud's [Application management](#).

5. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in PingOne Advanced Identity Cloud](#):

- **ID:** ig_agent
- **Password:** password

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway, replacing the value for the property `amInstanceUrl`:

Linux

```
$HOME/.openig/config/routes/oauth2rs-idc.json
```

Windows

```
%appdata%\OpenIG\config\routes\oauth2rs-idc.json
```

```

{
  "name": "oauth2rs-idx",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/oauth2rs-idx')}",
  "properties": {
    "amInstanceUrl": "https://myTenant.forgeblocks.com/am"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "${amInstanceUrl}",
        "realm": "/alpha",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [
              "mail"
            ],
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "TokenIntrospectionAccessTokenResolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "amService": "AmService-1",
                "providerHandler": {
                  "type": "Chain",
                  "config": {
                    "filters": [
                      {
                        "type": "HttpBasicAuthenticationClientFilter",
                        "config": {
                          "username": "ig_agent",
                          "passwordSecretId": "agent.secret.id",
                          "secretsProvider": "SystemAndEnvSecretStore-1"
                        }
                      }
                    ],
                    "handler": "ForgeRockClientHandler"
                  }
                }
              }
            }
          }
        }
      ]
    }
  }
}

```

```

    }
  }
},
"handler": {
  "type": "StaticResponseHandler",
  "config": {
    "status": 200,
    "headers": {
      "Content-Type": [ "text/html; charset=UTF-8" ]
    },
    "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></html>"
  }
}
}
}
}
}
}

```

Source: [oauth2rs-idc.json](#)

Notice the following features of the route compared to `rs-introspect.json` in [Validating PingAM access tokens with introspection](#), where a local PingAM instance is the Authorization Server:

- The AmService `URL` points to PingAM in PingOne Advanced Identity Cloud.
- The AmService `realm` points to the realm where you have configured your web application and the PingGateway agent.

3. Test the setup:

1. In a terminal, export an environment variable for the URL of PingAM in PingOne Advanced Identity Cloud:

```
$ export amInstanceUrl='myAmInstanceUrl'
```

2. Use a `curl` command similar to the following to retrieve an access token:

```
$ mytoken=$(curl -s \
--user "oauth2-client:password" \
--data 'grant_type=password&username=demo&password=Ch4ng3!t&scope=mail' \
$amInstanceUrl/oauth2/realms/alpha/access_token | jq -r ".access_token")
```

3. Validate the access token returned in the previous step:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/oauth2rs-idc
```

Output

```
{
  active = true,
  scope = mail,
  realm = /alpha,
  client_id = oauth2-client,
  ...
}
```

OpenID Connect and PingOne Advanced Identity Cloud

This example sets up PingOne Advanced Identity Cloud as an OpenID Connect (OIDC) provider with PingGateway as a relying party.

For more information about PingGateway and OIDC, refer to [OpenID Connect and PingAM](#).

Before you start, prepare PingOne Advanced Identity Cloud, PingGateway, and the sample application as described in [Example installation for this guide](#).

1. Set up PingOne Advanced Identity Cloud:

1. Log in to the Advanced Identity Cloud admin UI as an administrator.
2. Make sure you are managing the **alpha** realm. If not, click the current realm at the top of the screen, and switch realm.

3. Go to  **Identities > Manage >  Alpha realm - Users**, and add a user with the following values:

- **Username:** demo
- **First name:** demo
- **Last name:** user
- **Email Address:** demo@example.com
- **Password:** Ch4ng3!t

4. Go to  **Custom Application > + Custom Application > OIDC - OpenId Connect > Web** and add a web application with the following values:

- **Name:** oidc_client
- **Owners:** demo user
- **Client Secret:** password
- (Optional) **Use Secret Store for password:** Select this to store the password in an ESV secret.

If you select this option, enter a **Secret Label Identifier**. This value represents the `identifier` part of the secret label for the client. PingOne Advanced Identity Cloud uses the identifier to generate a secret label in the following format: `am.applications.oauth2.client.identifier.secret`.

To complete the client profile, add an ESV secret for the password and map the ESV to the secret label. To learn more, read [Secret labels](#) in the PingOne Advanced Identity Cloud documentation.

- **Sign On > Sign-in URLs:** `https://ig.example.com:8443/home/id_token/callback`
- **Sign On > Grant Types:** `Authorization Code`
- **Sign On > Scopes:** `openid, profile, email`
- **Show advanced settings > Authentication > Implied Consent:** `On`

For more information, refer to PingOne Advanced Identity Cloud's [Application management](#).

2. Set up PingGateway:

1. Set an environment variable for the `oidc_client` password, and then restart PingGateway:

```
$ export OIDC_SECRET_ID='cGFzc3dvcmQ='
```

1. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*/.*\\.ico$') or matchesWithRegex(request.uri.path, '^/.*/.*\\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

2. Add the following route to PingGateway, replacing the value for the property `amInstanceUrl`:

Linux

```
$HOME/.openig/config/routes/oidc-idx.json
```

Windows

```
%appdata%\OpenIG\config\routes\oidc-idx.json
```

```

{
  "name": "oidc-oidc",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/id_token')}",
  "properties": {
    "amInstanceUrl": "https://myTenant.forgeblocks.com/am"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AuthenticatedRegistrationHandler-1",
      "type": "Chain",
      "config": {
        "filters": [
          {
            "name": "ClientSecretBasicAuthenticationFilter-1",
            "type": "ClientSecretBasicAuthenticationFilter",
            "config": {
              "clientId": "oidc_client",
              "clientSecretId": "oidc.secret.id",
              "secretsProvider": "SystemAndEnvSecretStore-1"
            }
          }
        ],
        "handler": "ForgeRockClientHandler"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "AuthorizationCodeOAuth2ClientFilter-1",
          "type": "AuthorizationCodeOAuth2ClientFilter",
          "config": {
            "clientEndpoint": "/home/id_token",
            "failureHandler": {
              "type": "StaticResponseHandler",
              "config": {
                "status": 500,
                "headers": {
                  "Content-Type": [
                    "text/plain"
                  ]
                }
              },
              "entity": "Error in OAuth 2.0 setup."
            }
          }
        },
        {
          "name": "RegistrationHandler-1",
          "type": "Chain",
          "config": {
            "filters": [
              {
                "name": "ClientRegistrationFilter-1",
                "type": "ClientRegistrationFilter",
                "config": {
                  "clientId": "oidc_client",
                  "issuer": {
                    "name": "Issuer",

```

```

        "type": "Issuer",
        "config": {
            "wellKnownEndpoint": "&{amInstanceUrl}/oauth2/realms/alpha/.well-known/openid-configuration"
        },
        "scopes": [
            "openid",
            "profile",
            "email"
        ],
        "authenticatedRegistrationHandler": "AuthenticatedRegistrationHandler-1"
    },
    ],
    "requireHttps": false,
    "cacheExpiration": "disabled"
}
],
"handler": "ReverseProxyHandler"
}
}
}

```

Source: [oidc-idc.json](#)

Compared to `07-openid.json` in [AM as OIDC provider](#), where PingAM is running locally, the `ClientRegistration.wellKnownEndpoint` points to PingOne Advanced Identity Cloud.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to https://ig.example.com:8443/home/id_token.

The PingOne Advanced Identity Cloud login page is displayed.

2. Log in to PingOne Advanced Identity Cloud as user `demo`, password `Ch4ng3!t`. The home page of the sample application is displayed.

PingOne Advanced Identity Cloud cross-domain single sign-on

For organizations relying on AM's session and policy services with SSO, consider Cross-Domain Single Sign-On (CDSSO) as an alternative to SSO through OpenID Connect.

This example sets up PingOne Advanced Identity Cloud as an SSO authentication server for requests processed by PingGateway. For more information about PingGateway and CDSSO, refer to [Cross-domain single sign-on for PingAM](#).

Before you start, prepare PingOne Advanced Identity Cloud, PingGateway, and the sample application as described in [Example installation for this guide](#).

1. Set up PingOne Advanced Identity Cloud:

1. Log in to the Advanced Identity Cloud admin UI as an administrator.

2. Make sure you are managing the `alpha` realm. If not, click the current realm at the top of the screen, and switch realm.

3. Go to  **Identities > Manage >  Alpha realm - Users**, and add a user with the following values:

- **Username:** `demo`
- **First name:** `demo`
- **Last name:** `user`
- **Email Address:** `demo@example.com`
- **Password:** `Ch4ng3!t`

4. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in PingOne Advanced Identity Cloud](#):

- **ID:** `ig_agent`
- **Password:** `password`
- **Redirect URLs:** `https://ig.ext.com:8443/home/cdsso/redirect`

5. Add a Validation Service:

1. In PingOne Advanced Identity Cloud, select  **Native Consoles > Access Management**. The AM admin UI is displayed.

2. Select **Services**, and add a validation service with the following **Valid goto URL Resources**:

- `https://ig.ext.com:8443/*`
- `https://ig.ext.com:8443/*?*`

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).

2. Add the following `session` configuration to `admin.json`.

This ensures the browser passes the session cookie in the form-POST to the redirect endpoint (step 6 of [Information flow during CDSO](#)):

```
{
  "connectors": [...],
  "session": {
    "type": "InMemorySessionManager",
    "config": {
      "cookie": {
        "sameSite": "none",
        "secure": true
      }
    }
  },
  "heap": [...]
}
```

This step is required for the following reasons:

- When `sameSite` is `strict` or `lax`, the browser doesn't send the session cookie, which contains the nonce used in validation. If PingGateway doesn't find the nonce, it assumes that the authentication failed.
- When `secure` is `false`, the browser is likely to reject the session cookie.

Learn more in [AdminHttpApplication \(admin.json\)](#).

3. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a `SystemAndEnvSecretStore`, and must be base64-encoded.

4. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.ico$') or matchesWithRegex(request.uri.path, '^/.*\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#) 

5. Add the following route to PingGateway and correct the value for the property `amInstanceUrl` :

Linux

```
$HOME/.openig/config/routes/cdsso-idx.json
```

Windows

```
%appdata%\OpenIG\config\routes\cdsso-idx.json
```

```
{
  "name": "cdsso-idx",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/cdsso')}",
  "properties": {
    "amInstanceUrl": "https://myTenant.forgeblocks.com/am"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "${amInstanceUrl}",
        "realm": "/alpha",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "sessionCache": {
          "enabled": false
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "CrossDomainSingleSignOnFilter-1",
          "type": "CrossDomainSingleSignOnFilter",
          "config": {
            "redirectEndpoint": "/home/cdsso/redirect",
            "authCookie": {
              "path": "/home",
              "name": "ig-token-cookie"
            },
            "amService": "AmService-1"
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}
```

Source: [cdsso-idc.json](#)

Notice the following features of the route where PingAM is running locally:

- The AmService `URL` points to PingAM in PingOne Advanced Identity Cloud.
- The AmService `realm` points to the realm where you configure your PingGateway agent.

6. Restart PingGateway.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.ext.com:8443/home/cdsso>.

The PingOne Advanced Identity Cloud login page is displayed.

2. Log in to PingOne Advanced Identity Cloud as user `demo`, password `Ch4ng3!t`.

PingAM calls `/home/cdsso/redirect`, and includes the CDSSO token. The CrossDomainSingleSignOnFilter passes the request to sample app.

Password replay and PingOne Advanced Identity Cloud

Password replay brings single sign-on (SSO) to legacy web applications without the need to edit, upgrade, or recode them.

Use PingGateway with an appropriate PingOne Advanced Identity Cloud journey to capture and replay username password credentials. PingGateway and PingOne Advanced Identity Cloud share a secret key to encrypt and decrypt the password and keep it safe.

When running AM in a self-hosted deployment, read [Password replay with AM](#).

Request flow




Figure 1. Password replay sequence diagram

- PingGateway intercepts the browser's HTTP GET request.
- PingGateway redirects the user to the appropriate PingOne Advanced Identity Cloud journey for authentication.
- PingOne Advanced Identity Cloud authenticates the user and stores the encrypted password in a JWT.
- PingOne Advanced Identity Cloud redirects the browser back to the protected application with the JWT.
- PingGateway intercepts the browser's HTTP GET request again:
 - The user is authenticated.
 - PingGateway gets the password from the JWT and decrypts it.
 - PingGateway gets the username from PingOne Advanced Identity Cloud based on the user `_id`.
- PingGateway replaces the request with an HTTP POST to the application, taking the credentials from the context.
- The sample application validates the credentials from the HTTP POST request.
- The sample application responds with the user's profile page.
- PingGateway passes the response from the sample application to the browser.

Tasks

Before you begin

- Make sure you can access the PingOne Advanced Identity Cloud tenant as an administrator.
- Choose the realm to use in the PingOne Advanced Identity Cloud tenant.

The following tasks use the `alpha` realm.

- [Prepare hostnames](#) for PingGateway and the sample application.

The following tasks use `ig.example.com` for PingGateway and `app.example.com` for the sample application.

Task 1: Run the sample application

1. [Download the sample application](#).
2. Open a command-line window and [start the sample application](#):

```
$ java -jar PingGateway-sample-application-2025.6.1-jar-with-dependencies.jar
```

The sample application runs in the foreground until you stop it.

3. Check you can access the sample application by browsing <http://app.example.com:8081/login>.

The sample application displays a login screen.

Task 2: Install PingGateway

This task installs PingGateway, but doesn't configure it for password replay yet.

1. [Download and unpack PingGateway](#).
2. [Configure PingGateway for HTTPS](#).
3. Set a top-level `session` property in `config.json` alongside the `heap` and `connections`:

```
"session": {
  "type": "InMemorySessionManager",
  "config": {
    "cookie": {
      "sameSite": "none",
      "secure": true
    }
  }
}
```

PingOne Advanced Identity Cloud prompts the browser to send a session cookie on successful authentication.

- When `sameSite` is `strict` or `lax`, the browser doesn't send the session cookie with the nonce used in validation. If PingGateway doesn't find the nonce, it assumes that the authentication failed.
- When `secure` is `false`, the browser is likely to reject the session cookie.

4. [Add a base configuration file](#).

Comment captures in the handler to avoid flooding the PingGateway log, `"_capture": "all"`.

5. [Configure static routes for use with the sample application](#).
6. Check you can access the sample application through PingGateway by browsing <https://ig.example.com:8443/static>.

You might have used a self-signed certificate for the PingGateway HTTPS configuration. If your browser doesn't recognize the PingGateway certificate and flags it as a security risk, choose to continue.

PingGateway displays a basic profile page for the `demo` user.

PingGateway now has the configuration required as a basis on which to build password replay.

Task 3: Register PingGateway with PingOne Advanced Identity Cloud

If you have not yet registered PingGateway with PingOne Advanced Identity Cloud, follow these steps:

1. [Configure an Agent journey](#) PingGateway uses to authenticate with PingOne Advanced Identity Cloud.
2. [Register a profile for PingGateway](#).

Field	Value	Description
ID	<code>ig-agent</code>	The PingGateway username when connecting to the <code>AmService</code> in PingOne Advanced Identity Cloud.
Password	<code>password</code>	The PingGateway password when connecting to the <code>AmService</code> in PingOne Advanced Identity Cloud. In production tenants, use a strong password.
Redirect URLs	<code>https://ig.example.com:8443/replay/redirect</code>	The PingGateway endpoint to process the encrypted JWT from PingOne Advanced Identity Cloud.

PingOne Advanced Identity Cloud is now ready for PingGateway to connect. You'll share the credentials with PingGateway in [Task 6: Configure PingGateway](#).

Task 4: Prepare a shared secret

PingGateway and PingOne Advanced Identity Cloud share a secret symmetric key to encrypt and decrypt the password.

1. Generate a random AES 256-bit key to use as a shared secret.

How you generate the secret key is up to you. For example:

```
$ openssl rand -base64 32
```

Output

```
YWJjZGVmZ2hpamtsbW5vcHFyc3R1dnd5eHowMTIzNDU=
```

Keep the secret safe.

2. Store the shared secret key as an ESV in PingOne Advanced Identity Cloud.

1. Sign on to the Advanced Identity Cloud admin UI as an administrator and go to **Tenant Settings > Global Settings > Environment Secrets & Variables**.

2. Click **Variables > + Add Variable**.

3. In the **Add a Variable** modal, enter the following settings:

Field	Value	Description
Name	esv-ig-shared-secret	The ESV name for the secret.
Value	YWJjZGVmZ2hpamtsbW5vcHFyc3R1dnd5eHowMTIzNDU=	The base64-encoded random AES 256-bit key.

4. Click **Save** to create the variable.

PingOne Advanced Identity Cloud can now access the secret through the `esv.ig.shared.secret` system property. You will share the secret with PingGateway in [Task 6: Configure PingGateway](#).

Task 5: Prepare PingOne Advanced Identity Cloud

Update the PingOne Advanced Identity Cloud validation service for PingGateway, create a script to capture the password, and a journey to use the script.

1. Sign on to the Advanced Identity Cloud admin UI as an administrator and go to **Native Consoles > Access Management**, select **Services**, and the following **Valid goto URL Resources** to the **Validation Service**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

2. Go to **Scripts > Auth Scripts**, click **+ New Script** and create a **Journey Decision Node** script with the **Legacy** engine named `Password replay` and the following JavaScript content.

The script adds a JWT encrypted with the shared secret key to the session:


```

var fr = JavaImporter(
  org.forgerock.openam.auth.node.api.Action,
  org.forgerock.openam.auth.node.api,
  javax.security.auth.callback.TextOutputCallback,
  org.forgerock.json.jose.builders.JwtBuilderFactory,
  org.forgerock.json.jose.jwt.JwtClaimsSet,
  org.forgerock.json.jose.jwe.JweAlgorithm,
  org.forgerock.json.jose.jwe.EncryptionMethod,
  javax.crypto.spec.SecretKeySpec,
  org.forgerock.secrets.SecretBuilder,
  org.forgerock.util.encode.Base64
);

var NodeOutcome = {
  ERROR: 'false',
  SUCCESS: 'true'
};

var config = {
  encryptionKey: systemEnv.getProperty("esv.ig.shared.secret")
};

function getKey () {
  logger.message("encKey: " + config.encryptionKey)
  return new fr.SecretKeySpec(fr.Base64.decode(config.encryptionKey), 'AES');
}

function buildJwt (claims) {
  logger.message('Building response JWT');
  var encryptionKey = getKey();
  var jwtClaims = new fr.JwtClaimsSet;
  jwtClaims.setClaims(claims);
  var jwt = new fr.JwtBuilderFactory()
    .jwe(encryptionKey)
    .headers()
    .alg(fr.JweAlgorithm.DIRECT)
    .enc(fr.EncryptionMethod.A128CBC_HS256)
    .done()
    .claims(jwtClaims)
    .build();

  return jwt;
}


try {
  password=nodeState.get("password").asString()
  var registrationClaims = { password: password };
  passwordJwt = buildJwt(registrationClaims);
  action = fr.Action.goTo(NodeOutcome.SUCCESS).putSessionProperty("sunIdentityUserPassword",
passwordJwt).build();
} catch (e) {
  logger.error('ERROR ' + e);
  action = fr.Action.send(new fr.TextOutputCallback(fr.TextOutputCallback.ERROR, e.toString())).build();
}

```

You can download the script as [password-replay.js](#).

- Go to **Journeys**, click **+ New Journey**, and create a journey named **Password replay** whose **Identity Object** is **managed/alpha_user**.

4. Configure and save the journey with the nodes shown in this screenshot:



- The Page node presents a page with input fields to prompt for the username and password.
 - The Platform Username node collects and injects the `userName` into the shared node state.
 - The Platform Password node collects and injects the `password` into the shared node state.
- The Data Store Decision node uses the username and password to determine whether authentication is successful.
- The Scripted Decision node references your script and has the same outcomes: `true` and `false`.
- The Increment Login Count node updates the login count on successful authentication.

5. In your browser's privacy or incognito mode, go to the new journey and sign on with the credentials of a known user in the `alpha` realm.

PingOne Advanced Identity Cloud authenticates you and displays the user profile page.

You can now configure PingGateway to use the journey to capture the password.

Task 6: Configure PingGateway

The password replay configuration includes the PingGateway password to connect to PingOne Advanced Identity Cloud, the shared secret, and a route.

1. Set an environment variable locally on the computer running PingGateway to access the base64-encoded agent password:

```
$ export AGENT_SECRET_ID='cGFZc3dvcmQ='
```

PingGateway retrieves the password with a `SystemAndEnvSecretStore`, which requires it to be base64-encoded.

The password must match the agent profile password you set in PingOne Advanced Identity Cloud. PingGateway uses the password to connect to PingOne Advanced Identity Cloud.

2. Set an environment variable locally on the computer running PingGateway to access the base64-encoded shared secret key:

```
$ export AES_KEY='YWJjZGVmZ2hpamtsbW5vcHFyc3R1dnd5eHowMTIzNDU='
```

PingGateway retrieves the shared secret with a `SystemAndEnvSecretStore`, which requires it to be base64-encoded.

The shared secret key must match the secret key you stored in the PingOne Advanced Identity Cloud ESV. PingOne Advanced Identity Cloud uses the secret key to encrypt the password to replay. PingGateway uses the secret key to decrypt the password to replay.

3. Add a route for password replay.

Linux

```
$HOME/.openig/config/routes/04-replay-aic.json
```

Windows

```
%appdata%\OpenIG\config\routes\04-replay-aic.json
```

```

{
  "name": "04-replay-aic",
  "condition": "${find(request.uri.path, '^/replay')}",
  "properties": {
    "amInstanceUrl": "https://myTenant.forgeblocks.com/am/"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore",
      "config": {
        "mappings": [
          {
            "secretId": "aes.key",
            "format": {
              "type": "SecretKeyPropertyFormat",
              "config": {
                "format": "BASE64",
                "algorithm": "AES"
              }
            }
          }
        ]
      }
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "&{amInstanceUrl}",
        "realm": "/alpha",
        "agent": {
          "username": "ig-agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1"
      },
      "sessionCache": {
        "enabled": false
      }
    },
    {
      "name": "CapturedUserPasswordFilter-1",
      "type": "CapturedUserPasswordFilter",
      "config": {
        "ssoToken": "${contexts.ssoToken.value}",
        "keySecretId": "aes.key",
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "amService": "AmService-1"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "CrossDomainSingleSignOnFilter-1",
          "type": "CrossDomainSingleSignOnFilter",
          "config": {

```

```

        "redirectEndpoint": "/replay/redirect",
        "authCookie": {
            "path": "/replay",
            "name": "ig-token-cookie"
        },
        "amService": "AmService-1",
        "authenticationService": "Password replay"
    },
    {
        "name": "UserProfileFilter-1",
        "type": "UserProfileFilter",
        "config": {
            "username": "${contexts.ssoToken.info.uid}",
            "userService": {
                "type": "UserProfileService",
                "config": {
                    "amService": "AmService-1",
                    "profileAttributes": [
                        "username"
                    ]
                }
            }
        }
    },
    {
        "name": "PasswordReplayFilter-1",
        "type": "PasswordReplayFilter",
        "config": {
            "loginPage": "${true}",
            "credentials": "CapturedUserPasswordFilter-1",
            "request": {
                "method": "POST",
                "uri": "http://app.example.com:8081/login",
                "form": {
                    "username": [
                        "${contexts.userProfile.username}"
                    ],
                    "password": [
                        "${contexts.capturedPassword.value}"
                    ]
                }
            }
        },
        "capture": [
            "all"
        ]
    },
    {
        "handler": "ReverseProxyHandler"
    }
}

```

Source: [04-replay-aic.json](#).

The route:

- Matches requests whose path starts with `/replay`.

- Sets an `amInstanceUrl` property to the access management service in PingOne Advanced Identity Cloud.

Update the URL to target your tenant.

- Loads the `aes.key` secret key from the local `AES_KEY` environment variable.
- Connects to PingOne Advanced Identity Cloud as `ig-agent` with the `agent.secret.id` password from the local `AGENT_SECRET_ID` environment variable.
- Extracts the captured password from the SSO token context and decrypts it with the `aes.key` secret key.
- Uses a `CrossDomainSingleSignOnFilter` to redirect to the PingOne Advanced Identity Cloud `Password replay` journey for authentication, getting the authentication information from the `ig-token-cookie`.
- Queries the access management service in PingOne Advanced Identity Cloud to retrieve the username for signing on.

You can retrieve other profile attributes with the `UserProfileFilter`, such as the email address or first and last names. The sample application expects the username in this example, so the route gets the username.

- Signs on to the sample application with the username and password.
- Returns the result to the browser.

In production, remove `"capture": ["all"]` from the `PasswordReplayFilter` to avoid recording credentials in the logs.

- Restart PingGateway to read the secrets from the environment and load the new route.

In the PingGateway output, make sure the route loaded successfully with no errors or warnings: `@system - Loaded the route with id '04-replay-aic' registered with the name '04-replay-aic'`.

Task 7: Create a test user in PingOne Advanced Identity Cloud

The sample application validates the credentials for password replay. It must recognize the username and password you use.

The sample application has built-in username-password combinations. The username and password credentials shown in the following steps are one of the built-in pairs.

- In your browser's privacy or incognito mode, go to the default login journey for the realm you're using.

For example, `https://myTenant.forgeblocks.com/am/XUI/?realm=/alpha#/`.

- Click the **Create an account** link and enter the following settings in the **Sign Up** page:

Field	Value
Username	wolkig
First name	Wilhelm
Last name	Wolkig
Email Address	Your email. PingOne Advanced Identity Cloud sends a confirmation mail to this address.

Field	Value
Password	Geh3imnis!
Select a security question	What's your favorite color?
Answer	Red

3. Click **Next** to complete account creation and view the user profile.

4. Sign off.

Validation

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/replay/>.

PingGateway redirects to the PingOne Advanced Identity Cloud journey.

2. Sign on as user **wolkig** with password **Geh3imnis!**.

PingGateway successfully replays the credentials against the sample application. The sample application displays its user profile page:

 **ForgeRock**

Howdy, wolkig

USER INFORMATION

Username wolkig

REQUEST INFORMATION

Method POST
URI /login
Cookies
Headers **Content-Length:** 37
Content-Type: application/x-www-form-urlencoded
host: app.example.com:8081
Query Parameters

3. Review the PingGateway output.

On success, the output displays the credentials and the profile page:

```

...INFO o.f.o.d.c.c.PasswordReplayFilter-1 @04-replay-aic -

[CONTINUED]--- (filtered-request) exchangeId:<id> - transactionId:<id> --->

[CONTINUED]POST http://app.example.com:8081/login HTTP/1.1
[CONTINUED]Content-Length: 37
[CONTINUED]Content-Type: application/x-www-form-urlencoded

[CONTINUED]password=Geh3imnis%21&username=wolkig

...INFO o.f.o.d.c.c.PasswordReplayFilter-1 @04-replay-aic -

[CONTINUED]<--- (response) exchangeId:<id> - transactionId:<id> ---

[CONTINUED]HTTP/1.1 200 OK
...

[CONTINUED]<!DOCTYPE html>
...

```

You have successfully demonstrated password replay with PingGateway and PingOne Advanced Identity Cloud.

If password replay fails, consider the outcome of the HTTP POST from PingGateway to the sample application:

HTTP 401 Unauthorized

PingGateway is not replaying the credentials.

Review the PingGateway output to determine whether the username or password is missing when PingGateway replays the credentials.

If the password is missing, make sure PingGateway and PingOne Advanced Identity Cloud share the same AES secret key.

HTTP 403 Forbidden

PingGateway is not replaying the right credentials.

Make sure you're using a username-password combination known to the sample application.

Policy enforcement and PingOne Advanced Identity Cloud

The following procedure gives an example of how to request and enforce policy decisions from PingOne Advanced Identity Cloud.

Enforce a simple policy

Before you start, set up and test the example in [PingOne Advanced Identity Cloud cross-domain single sign-on](#).

1. Set up PingOne Advanced Identity Cloud:

1. In the Advanced Identity Cloud admin UI, select  **Native Consoles > Access Management**. The AM admin UI is displayed.

2. Select  **Authorization** > **Policy Sets** > **New Policy Set**, and add a policy set with the following values:

■ **Id** : PEP-CDSSO

■ **Resource Types** : URL

3. In the new policy set, add a policy with the following values:

■ **Name** : CDSSO

■ **Resource Type** : URL

■ **Resource pattern** : `*:/*:*/*`

■ **Resource value** : `http://app.example.com:8081/home/cdsso`

This policy protects the home page of the sample application.

4. On the **Actions** tab, add an action to allow HTTP `GET`.

5. On the **Subjects** tab, remove any default subject conditions, add a subject condition for all `Authenticated Users`.

2. Set up PingGateway:

1. Replace `cdsso-idc.json` with the following route and correct the value for the property `amInstanceUrl`:

Linux

```
$HOME/.openig/config/routes/pep-cdsso-idc.json
```

Windows

```
%appdata%\OpenIG\config\routes\pep-cdsso-idc.json
```

```

{
  "name": "pep-cdsso-idc",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/cdsso')}",
  "properties": {
    "amInstanceUrl": "https://myTenant.forgeblocks.com/am"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "&{amInstanceUrl}",
        "realm": "/alpha",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "sessionCache": {
          "enabled": false
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "CrossDomainSingleSignOnFilter-1",
          "type": "CrossDomainSingleSignOnFilter",
          "config": {
            "redirectEndpoint": "/home/cdsso/redirect",
            "authCookie": {
              "path": "/home",
              "name": "ig-token-cookie"
            },
            "amService": "AmService-1"
          },
          "amService": "AmService-1"
        },
        {
          "name": "PolicyEnforcementFilter-1",
          "type": "PolicyEnforcementFilter",
          "config": {
            "application": "PEP-CDSSO",
            "ssoTokenSubject": "${contexts.cdsso.token}",
            "amService": "AmService-1"
          }
        }
      ],
      "handler": "ReverseProxyHandler"
    }
  }
}

```

Source: [pep-cdsso-idc.json](#)

Notice that compared to `cdsso-idc.json` the `CrossDomainSingleSignOnFilter` is followed by a `PolicyEnforcementFilter` to enforce the policy `PEP-CDSSO`.

3. Test the setup:

1. Go to <https://ig.ext.com:8443/home/cdsso>.

If you have warnings that the site is not secure respond to the warnings to access the site.

PingGateway redirects you to PingOne Advanced Identity Cloud for authentication.

2. Log in to PingOne Advanced Identity Cloud as user `demo`, password `Ch4ng3!t`.

PingOne Advanced Identity Cloud redirects you back to the request URL, and PingGateway requests a policy decision. PingOne Advanced Identity Cloud returns a policy decision that grants access to the sample application.

Step up authorization for a transaction

Before you start, set up and test the example in [Enforce a simple policy](#).

1. In the Advanced Identity Cloud admin UI, select **<> Scripts > Auth Scripts > New Script > Journey Decision Node > Next**, and add a default Journey Decision Node Script called `TxTestPassword`:

```
/*
 * - Data made available by nodes that have already executed are available in the sharedState variable.
 * - The script should set outcome to either "true" or "false".
 */

var givenPassword = nodeState.get("password").asString()

if (givenPassword.equals("7890")) {
    outcome = "true"
} else {
    outcome = "false"
}
```

Source: [TxTestPassword.js](#)

2. Configure a journey:

1. Click  **Journeys** and add a journey with the following configuration:

■ **Name:** `Tx01_Tree`

■ **Identity Object:** `Alpha realm users`


The journey canvas is displayed.

2. In **Nodes > Basic Authentication**, drag a **Password Collector** node onto the canvas.
3. In **Nodes > Utilities**, drag a **Scripted decision** node onto the canvas.

4. Configure the scripted decision node as follows:

- **Script:** select `TxTestPassword`
- **Outcomes:** enter `true` and `false`

5. Connect the nodes as shown:



For information about configuring trees, refer to [PingOne Advanced Identity Cloud Docs](#)

3. Edit the authorization policy:

1. In the Advanced Identity Cloud admin UI, select [Native Consoles > Access Management](#). The AM admin UI is displayed.
2. Select [Authorization > Policy Sets > PEP-CDSSO](#), and add the following environment condition to the `CDSSO` policy:
 - **All of**
 - **Type:** Transaction
 - **Script name:** Authenticate to tree
 - **Strategy Specifier:** Tx01_Tree

4. Test the setup:

1. In a browser, go to <https://ig.ext.com:8443/home/cdsso>

If you have not previously authenticated to PingOne Advanced Identity Cloud, the CrossDomainSingleSignOnFilter redirects the request to PingOne Advanced Identity Cloud for authentication.

2. Log in to PingOne Advanced Identity Cloud as user `demo`, password `Ch4ng3!t`.

3. Enter the password `7890` required by the script `TxTestPassword`.

PingOne Advanced Identity Cloud redirects you back to the request URL, and PingGateway requests a policy decision. PingOne Advanced Identity Cloud returns a policy decision based on the authentication journey.

PingOne Advanced Identity Cloud Proxy Connect

With [Proxy Connect](#), PingOne Advanced Identity Cloud provides a way to secure traffic to your tenant environments in seamless compliance with the security controls you apply to your company's other network resources.

You use Proxy Connect rules to restrict access to a PingOne Advanced Identity Cloud tenant environment based on an IP address range or a required security header. If the request matches any of the rules, Proxy Connect lets the request through. If not, PingOne Advanced Identity Cloud responds with HTTP 404 Not Found. This affects the PingOne Advanced Identity Cloud UIs, too, as Proxy Connect prevents browser requests that don't follow the rules.

For externally facing applications, Proxy Connect works well with a web application firewall (WAF). A WAF protects against distributed denial-of-service, cross-site scripting, and injection attacks. The WAF isn't application-specific and so doesn't make application-specific decisions.

Requests from PingGateway can go through the WAF, but they don't always need to.

When PingGateway redirects the browser to an end-user UI page, such as the sign-on page, target the WAF. There's nothing special to do in PingGateway other than redirect to the WAF instead of the tenant. This includes the following use cases, where you let the WAF add the required security header to the browser and PingGateway requests:

- SSO and CDSSO
- SAML v2.0
- OpenID Connect
- Step-up and transactional authorization where a policy can return advices

When PingGateway uses PingOne Advanced Identity Cloud APIs directly without redirecting the browser, you can skip the WAF. This includes headless interactions that involve direct REST requests, not redirects, where you let PingGateway decorate requests with the required security header:

- PingGateway as an OAuth 2.0 resource server
- Using a [SessionInfoFilter](#)
- Using a [PolicyEnforcementFilter](#) in an SDK-based client application
- Using a [UserProfileFilter](#)

Goals

The following example builds on the [OAuth 2.0 and PingOne Advanced Identity Cloud](#) use case.

It shows how to decorate requests to PingOne Advanced Identity Cloud with a security header for Proxy Connect.

Prerequisites

- Get access as an administrator to a PingOne Advanced Identity Cloud tenant with the Proxy Connect add-on feature.

Wait to add Proxy Connect rules until you have [added a route to PingGateway](#) and [verified the route works without restrictions](#).

- Complete the [example installation](#) steps to use PingGateway with PingOne Advanced Identity Cloud.

You don't need the sample application for this example.

Tasks

Task 1: Configure an OAuth 2.0 profile

Configure an OAuth 2.0 client profile for PingGateway as a resource server:

1. Sign on to the Advanced Identity Cloud admin UI as an administrator.
2. Go to **Applications > + Custom Application > OIDC - OpenId Connect > Web** and add a web application with the following settings:

Name

oauth2-client

Owners

demo user

Client Secret

password

Sign On > Grant Types

Add Resource Owner Password Credentials

Sign On > Scopes

Add mail

Task 2: Configure PingGateway

1. [Configure PingGateway for HTTPS](#).
2. Set an environment variable for the base64-encoded PingGateway agent password.

The following command sets the variable to a base64-encoding of the string `password`.

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

- A `SystemAndEnvSecretStore` in the route that follows reads the base64-encoded password.
3. Restart PingGateway to reload `admin.json` and access the agent password.
 4. Add a route for token introspection that decorates requests with the security header.

Linux

```
$HOME/.openig/config/routes/proxy-connect.json
```

Windows

```
%appdata%\OpenIG\config\routes\proxy-connect.json
```

```

{
  "name": "proxy-connect",
  "condition": "${find(request.uri.path, '^/proxy-connect')}",
  "properties": {
    "gatewayUsername": "ig_agent",
    "gatewayPasswordSecretId": "agent.secret.id",
    "amServiceUrl": "https://myTenant.forgeblocks.com/am"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "SecurityHeaderFilter",
      "type": "HeaderFilter",
      "config": {
        "messageType": "REQUEST",
        "add": {
          "X-Security-Header": [
            "f1drybngmqj5loposddd5p98z886jp9"
          ]
        },
        "_comment": "The Proxy Connect rule you configure matches this header."
      },
      "capture": "filtered_request"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "&{amServiceUrl}",
        "realm": "/alpha",
        "agent": {
          "username": "&{gatewayUsername}",
          "passwordSecretId": "&{gatewayPasswordSecretId}"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "amHandler": {
          "type": "Chain",
          "config": {
            "filters": [
              "SecurityHeaderFilter"
            ],
            "handler": "ForgeRockClientHandler"
          }
        },
        "notifications": {
          "_comment": "Avoid UpgradeRejectedException: WebSocket upgrade failure: 404",
          "enabled": false
        }
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",

```



```

    "type": "OAuth2ResourceServerFilter",
    "config": {
      "scopes": [
        "mail"
      ],
      "requireHttps": false,
      "accessTokenResolver": {
        "name": "TokenIntrospectionAccessTokenResolver-1",
        "type": "TokenIntrospectionAccessTokenResolver",
        "config": {
          "amService": "AmService-1",
          "providerHandler": {
            "type": "Chain",
            "config": {
              "filters": [
                "SecurityHeaderFilter",
                {
                  "type": "HttpBasicAuthenticationClientFilter",
                  "config": {
                    "username": "&{gatewayUsername}",
                    "passwordSecretId": "&{gatewayPasswordSecretId}",
                    "secretsProvider": "SystemAndEnvSecretStore-1"
                  }
                }
              ],
              "handler": "ForgeRockClientHandler"
            }
          }
        }
      },
      "handler": "StaticResponseHandler",
      "config": {
        "status": 200,
        "headers": {
          "Content-Type": [
            "text/html; charset=UTF-8"
          ]
        },
        "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></html>"
      }
    }
  },
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [
          "text/html; charset=UTF-8"
        ]
      },
      "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></html>"
    }
  }
}

```

Source: [proxy-connect.json](#).

The Proxy Connect route:

- Matches requests whose path starts with `proxy-connect`.
- Defines a [HeaderFilter](#) to add the security header.

The header name and value must match the Proxy Connect header rule you configure. This route uses `f1drybngmqj51oposddd5p98z886jp9` to match the header rule set in [Task 4: Set a Proxy Connect rule](#).

- Configures an [AmService](#) whose requests PingGateway decorates with the security header.

As the service can't decorate websocket requests for notifications, the configuration disables notifications.

- Uses a [OAuth2ResourceServerFilter](#) with a [TokenIntrospectionAccessTokenResolver](#) to introspect access tokens.
- Adds a [StaticResponseHandler](#) to display the results of introspection.

5. Update the route's `amServiceUrl` setting to target the PingOne Advanced Identity Cloud tenant and save your work.

PingGateway loads the route.

Task 3: Pre-validation

Before you add Proxy Connect rules to restrict access, verify the route works *without* restrictions.

1. Get an access token using the resource owner password credentials flow:

```
$ export ACCESS_TOKEN=$(curl \
--request POST 'https://myTenant.forgeblocks.com/am/oauth2/realms/alpha/access_token' \
--user 'oauth2-client:password' \
--data 'grant_type=password' \
--data 'username=demo' \
--data 'password=Ch4ng3!t' \
--data 'scope=mail' \
--silent | jq -r ".access_token")
```

You don't need the security header until you configure a Proxy Connect header rule.

2. Use the route to introspect the access token:

```
$ curl \
--request GET 'https://ig.example.com:8443/proxy-connect' \
--insecure \
--header "Authorization: Bearer ${ACCESS_TOKEN}"
```

Output

```
<html><body><h2>Decoded access_token:
{active=true,
scope=mail,
realm=/alpha,
client_id=oauth2-client,
user_id=<uuid>,
username=<uuid>,
token_type=Bearer,
exp=<seconds>,
sub=<uuid>,
iss=https://myTenant.forgeblocks.com:443/am/oauth2/realms/root/realms/alpha,
subname=<uuid>,
auth_level=0,
authGrantId=<id>,
auditTrackingId=<uuid>,
expires_in=<seconds>}</h2></body></html>
```

Task 4: Set a Proxy Connect rule

Learn about this in the [Proxy Connect](#) documentation. Once you understand the steps:

1. Configure a Proxy Connect rule to require the following security header, which is the same one set in the Proxy Connect route configuration:

```
'X-Security-Header: f1drybngmqj51oposddd5p98z886jp9'
```

When you first update the header rules, the change is pending (`"requestStatus": "PENDING"`). PingOne Advanced Identity Cloud doesn't check for the security header when the update is still pending.

2. Poll the Proxy Connection configuration in PingOne Advanced Identity Cloud until the request has `"requestStatus": "SUCCESS"` .



Important

Once the request is successful, you can't use the Advanced Identity Cloud admin UI. Your browser doesn't add the security header by default.

If you must use the Advanced Identity Cloud admin UI again, either reset the header rules to `{"enabled": false, "headers": []}` or [configure your browser to add the security header](#).

Validation

1. Get an access token using the resource owner password credentials flow:

```
$ export ACCESS_TOKEN=$(curl \
--request POST 'https://myTenant.forgeblocks.com/am/oauth2/realms/alpha/access_token' \
--user 'oauth2-client:password' \
--data 'grant_type=password' \
--data 'username=demo' \
--data 'password=Ch4ng3!t' \
--data 'scope=mail' \
--header 'X-Security-Header: f1drybngmqj5lposddd5p98z886jp9' \
--silent | jq -r ".access_token")
```

2. Use the route to introspect the access token:

```
$ curl \
--request GET 'https://ig.example.com:8443/proxy-connect' \
--insecure \
--header "Authorization: Bearer ${ACCESS_TOKEN}"
```

Output

```
<html><body><h2>Decoded access_token:
{active=true,
scope=mail,
realm=/alpha,
client_id=oauth2-client,
user_id=<uuid>,
username=<uuid>,
token_type=Bearer,
exp=<seconds>,
sub=<uuid>,
iss=https://myTenant.forgeblocks.com:443/am/oauth2/realms/root/realms/alpha,
subname=<uuid>,
auth_level=0,
authGrantId=<id>,
auditTrackingId=<uuid>,
expires_in=<seconds>}</h2></body></html>
```

3. In the PingGateway log, notice the filtered requests have the security header:

```
[CONTINUED]--- (filtered-request) exchangeId:<uuid> - transactionId:<uuid> --->

[CONTINUED]POST https://myTenant.forgeblocks.com/am/oauth2/realms/root/realms/alpha/introspect HTTP/1.1
[CONTINUED]Accept: application/json
[CONTINUED]Content-Length: 918
[CONTINUED]Content-Type: application/x-www-form-urlencoded
[CONTINUED]X-Security-Header: f1drybngmqj5lposddd5p98z886jp9

[CONTINUED]token=<token>&token_type_hint=access_token
```

Change "capture" to "_capture" in the Proxy Connect route to avoid flooding the PingGateway logs.

You've successfully shown how to use PingGateway with Proxy Connect.

Passing PingOne Advanced Identity Cloud runtime data downstream in a JWT

This example sets up PingOne Advanced Identity Cloud as an identity provider, to pass identity or other runtime information downstream, in a JWT signed with a PEM.

For more information about using runtime data, refer to [Passing PingAM data along the chain](#). To help with development, the sample application includes a `/jwt` endpoint to display the JWT, verify its signature, and decrypt it.

Before you start, prepare PingOne Advanced Identity Cloud, PingGateway, and the sample application as described in [Example installation for this guide](#).

1. Set up secrets:

1. Locate a directory for secrets and go to it:

```
$ cd /path/to/secrets
```

2. Create the following secret key and certificate pair as PEM files:

```
$ openssl req \
  -newkey rsa:2048 \
  -new \
  -nodes \
  -x509 \
  -days 3650 \
  -subj "/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr" \
  -keyout ig.example.com-key.pem \
  -out ig.example.com-certificate.pem
```

Two PEM files are created, one for the secret key, and another for the associated certificate.

3. Map the key and certificate to the same secret ID in PingGateway:

```
$ cat ig.example.com-key.pem ig.example.com-certificate.pem > key.manager.secret.id.pem
```

4. Generate PEM files to sign and verify the JWT:

```
$ openssl req \
  -newkey rsa:2048 \
  -new \
  -nodes \
  -x509 \
  -days 3650 \
  -subj "/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr" \
  -keyout id.key.for.signing.jwt.pem \
  -out id.key.for.verifying.jwt.pem
```

5. Make sure the following files have been added to your secrets directory:

- `id.key.for.signing.jwt.pem`
- `id.key.for.verifying.jwt.pem`
- `key.manager.secret.id.pem`
- `ig.example.com-certificate.pem`
- `ig.example.com-key.pem`

2. Set up PingOne Advanced Identity Cloud:

1. Log in to the Advanced Identity Cloud admin UI as an administrator.

2. Go to  **Identities > Manage >  Alpha realm - Users**, and add a user with the following values:

- **Username:** `demo`
- **First name:** `demo`
- **Last name:** `user`
- **Email Address:** `demo@example.com`
- **Password:** `Ch4ng3!t`

3. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in PingOne Advanced Identity Cloud](#):

- **ID:** `ig_agent_jwt`
- **Password:** `password`
- **Redirect URLs:** `https://ig.example.com:8443/jwt/redirect`

4. Add a Validation Service:

1. In PingOne Advanced Identity Cloud, select  **Native Consoles > Access Management**. The AM admin UI is displayed.

2. Select **Services**, and add a validation service with the following **Valid goto URL Resources**:

- `https://ig.example.com:8443/*`
- `https://ig.example.com:8443/*?*`

3. Set up PingGateway:

1. Set up TLS by adding the following file to PingGateway, replacing the value for the property `secretsDir`:

Linux

```
$HOME/.openig/config/admin.json
```

Windows

%appdata%\OpenIG\config\admin.json

```
{
  "mode": "DEVELOPMENT",
  "properties": {
    "secretsDir": "/path/to/secrets"
  },
  "connectors": [
    {
      "port": 8080
    },
    {
      "port": 8443,
      "tls": "ServerTlsOptions-1"
    }
  ],
  "heap": [
    {
      "name": "ServerTlsOptions-1",
      "type": "ServerTlsOptions",
      "config": {
        "keyManager": {
          "type": "SecretsKeyManager",
          "config": {
            "signingSecretId": "key.manager.secret.id",
            "secretsProvider": "ServerIdentityStore"
          }
        }
      }
    },
    {
      "name": "ServerIdentityStore",
      "type": "FileSystemSecretStore",
      "config": {
        "format": "PLAIN",
        "directory": "&{secretsDir}",
        "suffix": ".pem",
        "mappings": [{
          "secretId": "key.manager.secret.id",
          "format": {
            "type": "PemPropertyFormat"
          }
        }]
      }
    }
  ]
}
```

Source: [admin-https-jwt.json](#)

2. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFzc3dvcmQ='
```

The password is retrieved by a SystemAndEnvSecretStore, and must be base64-encoded.

3. Add the following route to PingGateway to serve the sample application .css and other static resources:

Linux

```
$HOME/.openig/config/routes/00-static-resources.json
```

Windows

```
%appdata%\OpenIG\config\routes\00-static-resources.json
```

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.ico$')
or matchesWithRegex(request.uri.path, '^/.*\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

4. Add the following route to PingGateway, replacing the value for the properties `secretsDir` and `amInstanceUrl`:

Linux

```
$HOME/.openig/config/routes/jwt-idc.json
```

Windows

```
%appdata%\OpenIG\config\routes\jwt-idc.json
```



```

{
  "name": "jwt-idx",
  "condition": "${find(request.uri.path, '/jwt')}",
  "baseURI": "http://app.example.com:8081",
  "properties": {
    "secretsDir": "/path/to/secrets",
    "amInstanceUrl": "https://myTenant.forgeblocks.com/am"
  },
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "${amInstanceUrl}",
        "realm": "/alpha",
        "agent": {
          "username": "ig_agent_jwt",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "sessionCache": {
          "enabled": false
        }
      }
    }
  ],
  {
    "name": "pemPropertyFormat",
    "type": "PemPropertyFormat"
  },
  {
    "name": "FileSystemSecretStore-1",
    "type": "FileSystemSecretStore",
    "config": {
      "format": "PLAIN",
      "directory": "${secretsDir}",
      "suffix": ".pem",
      "mappings": [{
        "secretId": "id.key.for.signing.jwt",
        "format": "pemPropertyFormat"
      }]
    }
  }
],
"session": {
  "type": "InMemorySessionManager",
  "config": {
    "cookie": {
      "sameSite": "none",
      "secure": true
    }
  }
},
"handler": {
  "type": "Chain",
  "config": {
    "filters": [

```

```

    {
      "name": "CrossDomainSingleSignOnFilter-1",
      "type": "CrossDomainSingleSignOnFilter",
      "config": {
        "redirectEndpoint": "/jwt/redirect",
        "authCookie": {
          "path": "/jwt",
          "name": "ig-token-cookie"
        },
        "amService": "AmService-1"
      }
    },
    {
      "name": "UserProfileFilter",
      "type": "UserProfileFilter",
      "config": {
        "username": "${contexts.ssoToken.info.uid}",
        "userService": {
          "type": "UserProfileService",
          "config": {
            "amService": "AmService-1"
          }
        }
      }
    },
    {
      "name": "JwtBuilderFilter-1",
      "type": "JwtBuilderFilter",
      "config": {
        "template": {
          "name": "${contexts.userProfile.commonName}",
          "email": "${contexts.userProfile.rawInfo.mail[0]}"
        },
        "secretsProvider": "FileSystemSecretStore-1",
        "signature": {
          "secretId": "id.key.for.signing.jwt",
          "algorithm": "RS512"
        }
      }
    },
    {
      "name": "HeaderFilter-1",
      "type": "HeaderFilter",
      "config": {
        "messageType": "REQUEST",
        "add": {
          "x-openig-user": ["${contexts.jwtBuilder.value}"]
        }
      }
    }
  ],
  "handler": "ReverseProxyHandler"
}

```

Source: [jwt-idc.json](#)

4. Test the setup:

1. Go to <https://ig.example.com:8443/jwt>.

If you receive warnings that the site is not secure, respond to the warnings to access the site. The PingOne Advanced Identity Cloud login page is displayed.

2. Log in to PingOne Advanced Identity Cloud as user `demo`, password `Ch4ng3!t`. The sample app displays the signed JWT along with its header and payload.
3. In `USE PEM FILE`, enter the absolute path to `id.key.for.verifying.jwt.pem` to verify the JWT signature.

Securing the OAuth 2.0 access token endpoint with PingOne Advanced Identity Cloud

This page uses a [GrantSwapJwtAssertionOAuth2ClientFilter](#) to transform requests for OAuth 2.0 access tokens into secure [JWT bearer grant type](#) requests. It propagates the transformed requests to PingOne Advanced Identity Cloud to obtain an access token.


Use [GrantSwapJwtAssertionOAuth2ClientFilter](#) to increase the security of less-secure grant-type requests, such as [Client credentials grant](#) requests or [Resource owner password credentials grant](#) requests.

Caution

The [GrantSwapJwtAssertionOAuth2ClientFilter](#) obtains access tokens from the `/oauth2/access_token` endpoint. To prevent unwanted or malicious access to the endpoint, make sure only a well-defined set of clients can use this filter. Consider the following options to secure access to the [GrantSwapJwtAssertionOAuth2ClientFilter](#):

- Deploy PingGateway on a trusted network.
- Use mutual TLS (mTLS) and X.509 certificates for authentication between clients and PingGateway. For more information, refer to [OAuth 2.0 Mutual TLS Client Authentication and Certificate Bound Access Tokens](#).
- Configure an [AllowOnlyFilter](#) in front of the [GrantSwapJwtAssertionOAuth2ClientFilter](#) to control access within a route.
- Define restrictive [Route](#) conditions to allow access only for expected grant-type requests. For example, define a route condition that requires a specific client ID, grant-type, or scope.
- Configure a [ScriptableFilter](#) in front of the [GrantSwapJwtAssertionOAuth2ClientFilter](#) to validate requests.

The following figure shows the flow of information for a grant swap:



Before you start, prepare PingOne Advanced Identity Cloud, PingGateway, and the sample application as described in [Example installation for this guide](#).

1. Set up PingOne Advanced Identity Cloud:

1. Log in to the Advanced Identity Cloud admin UI as an administrator.
2. Create a service account with the following values, as described in [Create a new service account](#):

■ **Name:** myServiceAccount

■ **Scopes:** fr:idm:* All Identity Management APIs

The service account ID is displayed and you are prompted to download the private key. The public key is held in PingOne Advanced Identity Cloud.

For more information, refer to [Service accounts](#).

3. Make a note of the service account ID and download the private key to your secrets directory.
4. Rename the key to match the regex format `(\.[a-zA-Z0-9])*`. For example, rename `myServiceAccount_privateKey.jwk` to `privateKey.jwk`.

2. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/grant-swap.json
```

Windows

```
%appdata%\OpenIG\config\routes\grant-swap.json
```

```

{
  "name" : "grant-swap",
  "properties": {
    "idcInstanceUrl": "https://myTenant.forgeblocks.com",
    "issuer": "service-account-id",
    "secretsDir": "path-to-secrets",
    "privateKeyFilename": "privateKey.jwk"
  },
  "condition" : "#{find(request.uri.path, '^/am/oauth2/access_token') &&
request.entity.form['grant_type'][0] == 'client_credentials'}",
  "baseURI" : "&{idcInstanceUrl}:443/",
  "heap" : [ {
    "name": "JwkPropertyFormat-01",
    "type": "JwkPropertyFormat"
  },
  {
    "name": "FileSystemSecretStore-01",
    "type": "FileSystemSecretStore",
    "config": {
      "format": "JwkPropertyFormat-01",
      "directory": "&{secretsDir}",
      "mappings": [ {
        "secretId": "&{privateKeyFilename}",
        "format": "JwkPropertyFormat-01"
      }
    ]
  }
  ],
  "handler" : {
    "type" : "Chain",
    "capture" : "all",
    "config" : {
      "filters" : [
        {
          "name" : "GrantSwapJwtAssertionOAuth2ClientFilter-01",
          "description": "access /access_token endpoint with jwt-bearer-profile",
          "type" : "GrantSwapJwtAssertionOAuth2ClientFilter",
          "capture" : "all",
          "config" : {
            "clientId" : "service-account",
            "assertion" : {
              "issuer" : "&{issuer}",
              "audience" : "&{idcInstanceUrl}/am/oauth2/access_token",
              "subject" : "&{issuer}",
              "expiryTime": "2 minutes"
            },
            "signature": {
              "secretId": "&{privateKeyFilename}",
              "includeKeyId": false
            },
            "secretsProvider": "FileSystemSecretStore-01",
            "scopes" : {
              "type": "RequestFormResourceAccess"
            }
          }
        }
      ]
    }
  }
}

```

```

    },
    "handler" : "ForgeRockClientHandler"
  }
}
}

```

Source: [grant-swap.json](#)

3. In the route, replace the values for the following properties with your values:

- `idcInstanceUrl` : The root URL of your PingOne Advanced Identity Cloud tenant.
- `issuer` : The ID of the service account created in PingOne Advanced Identity Cloud
- `secretsDir` : The directory containing the downloaded private key
- `privateKeyFilename` : The filename of the downloaded private key

4. Notice the following features of the route:

- The condition intercepts only `client_credentials` grant-type requests on the path `/am/oauth2/access_token`. A more secure condition can be set on the client ID.
- Requests are rebased to the PingOne Advanced Identity Cloud URL.
- A `FileSystemSecretStore` loads the private-key JWK used to sign the JWT.
- The `GrantSwapJwtAssertionOAuth2ClientFilter`:
 - Requires the core JWT claims `issuer`, `subject`, `audience`, and `expiryTime`.
 - Uses `RequestFormResourceAccess` to extract scopes from the inbound request for inclusion in the JWT-assertion grant-type request propagated to AM.
 - Signs the JWT with the JWK provided by the service account.
- The `GrantSwapJwtAssertionOAuth2ClientFilter` `clientId` refers to the OAuth 2.0 client ID created by AM. The value must be `service-account`.

5. Add the following route to PingGateway to return a standard OAuth 2.0 error response if the request fails the route condition:

Linux

```
$HOME/.openig/config/routes/zz-returns-invalid-request.json
```

Windows

```
%appdata%\OpenIG\config\routes\zz-returns-invalid-request.json
```

```
{
  "name" : "zz-returns-invalid-request",
  "handler" : {
    "type" : "StaticResponseHandler",
    "capture" : "all",
    "config" : {
      "status": 400,
      "headers": {"Content-Type": ["application/json; charset=UTF-8"]},
      "entity": "{ \"error\": \"Invalid_request\", \"error_description\": \"Invalid request\" }"
    }
  }
}
```

Source: [zz-returns-invalid-request.json](#)

3. Test the setup by accessing the route with a `curl` command similar to this:

```
$ curl \
  --cacert /path/to/secrets/ig.example.com-certificate.pem \
  --location \
  --request POST 'https://ig.example.com:8443/am/oauth2/access_token' \
  --header 'Content-Type: application/x-www-form-urlencoded' \
  --data-urlencode 'client_id=myServiceAccount' \
  --data-urlencode 'grant_type=client_credentials' \
  --data-urlencode 'scope=fr:idm:*'
```

Output

```
{"access_token":"eyJ...", "scope":"fr:idm:*", "token_type":"Bearer", "expires_in":899}
```

The command makes a `client_credentials` grant-type request on the path `/am/oauth2/access_token`, supplying the client ID and scopes. PingGateway transforms the request into a JWT-assertion grant-type request and propagates it to PingOne Advanced Identity Cloud.

Because the service account in PingOne Advanced Identity Cloud supports the requested scope, the `GrantSwapJwtAssertionOAuth2ClientFilter` returns an access token.

PingGateway Studio

This guide gives an overview of how to use Studio to design and develop routes to protect applications.

Starting with Studio

PingGateway Studio is a user interface to help you build and deploy your PingGateway configuration. There are two ways to create routes in Studio:

- With the *structured editor* (deprecated) to build simple routes by using predefined menus and templates. The structured editor presents valid options and default values as you add filters, decorators, and other objects to your configuration.
- With the *FreeForm Designer* to design complex, multi-branched routes. Drag handlers and filters from a side bar onto the canvas to begin designing the route. The FreeForm Designer helps you to visualize the chain, and track the path of requests, responses, and contexts.

After installation, PingGateway is by default in production mode. The `/routes` endpoint is not exposed or accessible, and Studio is effectively disabled. To access Studio, switch to development mode. For example, add the following configuration to `admin.json`, and restart PingGateway:

```
{
  "mode": "DEVELOPMENT",
  "connectors": [
    { "port" : 8080 }
  ]
}
```

Source: [admin-dev.json](#) 

For additional details, refer to [PingGateway operating modes](#).

If you provide a custom `config.json`, include a main router named `_router`. If a custom `config.json` is not provided, PingGateway includes this router by default.

When PingGateway is installed and running in development mode, as described in [Getting started with PingGateway](#), access Studio on <http://ig.example.com:8085/studio> . The **Routes** screen is displayed:

Running in development mode - by default, all endpoints are open and accessible. Do not use this mode in a production environment.

PingIdentity  **ROUTES**  **DOCS**

Routes

Configure IG to protect your applications

+ Create a route

Import a route



Filter...

NAME ▲

URL

STATUS

During PingGateway upgrade, routes that were previously created in Studio are automatically transferred to the new version of PingGateway. Where possible, PingGateway replaces deprecated settings with the newer evolved setting. If PingGateway needs additional information to upgrade the route, the route status becomes **Compatibility update required**. Select the route and provide the requested information.



Important

SecretsProviders can't be configured in Studio. Documentation examples generated with Studio might refer to SecretsProviders that must be configured separately in `config.json`.

Upgrade from an earlier version of Studio

From PingGateway 2024.3, Studio manages the migration of deprecated objects for routes created and managed in earlier versions of Studio.

PingGateway doesn't manage migration for the following:

- Routes in Studio editor mode
- Custom filters in routes

Migration for routes containing secrets

PingGateway automatically:

- Updates the route to use SecretsProvider and SecretIds
- Removes references to the password

You must manually create the required SecretsProvider in `config.json` and create its referenced secrets.

Migration for routes containing Splunk or ElasticSearch audit event handlers

PingGateway automatically deletes the Splunk or ElasticSearch audit event handlers from the route.

Create and edit routes with Structured Editor (deprecated)

This section describes basic tasks for creating and deploying routes in the structured editor of Studio.



Important

The structured editor of Studio is deprecated. For more information, refer to the [Deprecated](#) section of the *Release Notes*.

Creating simple routes

1. In PingGateway Studio, create a route:

1. Go to <http://ig.example.com:8085/studio>, and select **+ Create a route**.

2. Select **Structured** to use the structured editor.

2. Enter the URL of the application you want to protect, followed by a path condition to access the route. For example, enter `http://app.example.com:8081/my-basic-route`.

The route is created, and menus to add configuration objects to the route are displayed.

3. On the top-right of the screen, select **Display** to review the route.

A route similar to this is displayed, where the path condition is used for the route name:

```
{
  "name": "my-basic-route",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/my-basic-route')}",
  "handler": "ReverseProxyHandler"
}
```

Change the basic settings of a route

1. In Studio, select **ROUTES**, and then select a route with the **Structured** icon.

2. On the top-right of the screen select **Route settings**.

3. Using the on-screen hints for guidance, change the name, condition, or other features of the route, and save the changes.

4. On the top-right of the screen, select **Display** to review the route.

Adding configuration to a route

After creating a route in the structured editor, you can add filters, decorators, scripts, and other configuration to the route.

Add other configuration to a route

1. In Studio, select **ROUTES**, and then select a route with the **Structured** icon.

2. Select one of the configuration options, and follow the on-screen hints to select configuration settings.

For routes to test with the examples in the Gateway guide, refer to [Example routes created with Structured Editor \(deprecated\)](#).

Add other filters to a route

Use this procedure to add any filter type to the configuration.

1. In Studio, select  **ROUTES**, and then select a route with the  icon.
2. Select  **Other filters** > **+ New filter** > **Other filter**.
3. In **Create filter**, select a filter type from the list, enter a name, and optionally enter a configuration for the filter.



Note

Studio checks that the JSON is valid, but doesn't check that the configuration of the filter is valid. If the filter configuration isn't valid, when you deploy the route it fails to load.

When you save, the filter is added to the list of other filters but is not added to the configuration.

4. Enable the filter to add it to the configuration.

If you disable the filter again, it is removed from the route's chain but the configuration is saved. Simply enable the filter again to add it back in the chain.

Managing the route chain

The  **Chain** view lists the filters in the order that they appear in the configuration.

Some filters have a natural position in the chain. For example, so that an authenticated user is given the correct permissions, an authentication filter must come before an authorization filter. Similarly, so that an authorization token is transformed, an authorization filter always comes before a token transformation filter.

Other filters have a flexible position in the chain. For example, an AssignmentFilter can be used before a request is handled or after a response is handled.

When the position of a filter is fixed, it is automatically placed in the correct position in the chain; you cannot change the position. When the position of a filter is flexible, the  icon is displayed, and you can drag the filter into a different position in the chain.

Select  **Chain** to view and manage the filters in the chain as follows:

- When the  icon is displayed, drag a filter up or down the chain.
- Select  to edit a filter.
- Select  **Realm Settings** to disable and remove a filter from the chain.

For information about chains, refer to [Chain](#).

Deploy and undeploy routes

Deploy a Route

1. In Studio, select  **ROUTES**, and then select a route created with the structured editor (with the  icon).
2. On the top-right of the screen, select  and  **Display** to review the route.
3. If the route is okay, select  **Deploy** to push the route to the PingGateway configuration.



Important

If the route configuration is not valid, or if a service that the route relies on, such as an AM service, is not available, the route fails to deploy.

If the route deploys successfully,  **Deployed** is displayed and the  **Deploy** button is greyed out.

4. Check the `$HOME/.openig/config/routes` folder in your PingGateway configuration to see that the route is there.

By default, routes are loaded automatically into the PingGateway configuration. You don't need to stop and restart PingGateway. For more information, refer to [Prevent the reload of routes](#).

5. Check the system log to confirm that the route was loaded successfully into the configuration. For information about logs, refer to [Managing PingGateway logs](#).

Undeploy a Route

1. In Studio, select  **ROUTES** and then select a route with the status  **Deployed**.
2. On the top-right of the screen, select  and  **Undeploy**, and then confirm your request.

The route is removed from the PingGateway configuration. On the Studio screen, the route status  **Deployed** is no longer displayed and the  **Deploy** option is active again.

Create and edit routes with Freeform Designer

The following sections describe how to create a simple route in the FreeForm Designer of Studio, and then add configuration to the route. You can find examples of routes created with the FreeForm Designer in [Example routes created with Freeform Designer](#).

Create a simple route

1. In PingGateway Studio, create a route:
 1. Go to `http://ig.example.com:8085/studio`, and then select  **Create a route**.
 2. Select  **Freeform** to use the FreeForm Designer.
2. Select  **Basic** to create a route from a blank template.
3. Enter a URL for the application you want to protect, followed by a path condition to access the route. For example, enter `http://app.example.com:8081/my-basic-route`.

The route is displayed on the  **Flow** tab of the canvas.

4. On the top-right of the screen, select  and  **Display** to review the route.

```
{
  "name": "my-basic-route",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/my-basic-route')}",
  "handler": "ReverseProxyHandler",
  "heap": [
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler"
    },
    {
      "type": "BaseUriDecorator",
      "name": "baseUri"
    },
    {
      "type": "TimerDecorator",
      "name": "timer",
      "config": {
        "timeUnit": "ms"
      }
    },
    {
      "type": "CaptureDecorator",
      "name": "capture",
      "config": {
        "captureEntity": false,
        "captureContext": false,
        "maxEntityLength": 524288
      }
    }
  ]
}
```

Change the basic settings of a route

1. Using the route created in [Create a simple route](#), on the top-right of the screen select  **Route settings**.
2. Using the on-screen hints for guidance, change the name, condition, or other features of the route, and save the changes.
3. On the top-right of the screen, select  and  **Display** to review the route.

Add objects to a route heap

1. Using the route created in [Create a simple route](#), select  **All Objects** > **Create Object**.
2. In **Node Type**, select an object type from the drop down list. For example, create an AmService object, using the following values:

- **Name:** AmService-1
- **URI:** http://am.example.com:8088/openam/

- **Agent:**

- **Agent:** `ig-agent`

- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

When you save, the object is added to route heap but is not used in the route.

3. On the top-right of the screen, select  and  **Display** to review the route.

Add configuration to a route

1. Using the route created in [Create a simple route](#), select the  **Flow** tab, and delete the connector between **Start** and **ReverseProxyHandler**.
2. Drag a  **Chain** from the side bar onto the canvas, and then drag a **SingleSignOnFilter** into the chain.
3. In the menu for the **SingleSignOnFilter**, enter the name of the **AmService** object you created in [Add objects to a route heap](#), `AmService-1`. The filter uses the object previously defined in the heap.
4. Connect **Start** to **Chain-1**, and **Chain-1** to **ReverseProxyHandler**.
5. On the top-right of the screen, select  and  **Display** to review the route.

Decorate objects in the route

1. Using the route created in [Create a simple route](#), select the  **All Objects** tab.
A list of objects in the route is displayed. By default, all available decorators are included in the route heap, but they don't decorate any objects.
2. For the **ReverseProxyHandler** or filter, select , select the **Decorations** tab, and then enable one or more of the decorators.
3. On the top-right of the screen, select  and  **Display** to review the route.

Editing and importing routes in Studio

The following sections describe basic tasks for Edit and import routes in Studio:

Edit routes in editor mode

After creating a route in Studio, you can edit it by using the options offered in Studio, or by switching to editor mode and using the JSON editor.

Routes created only in the menus of structured editor have the icon . Routes created only in the menus of FreeForm Designer have the icon . Imported routes and routes edited in editor mode have the icon .

 Important

When you go into editor mode, you can use the JSON editor to manually edit the route, but can no longer use the full Studio interface to add to or edit the configuration.

1. In Studio, select  **ROUTES**, and then select a route created with the structured editor (with the  icon).
2. Edit the route in Studio or manually:
 - To edit in Studio, select options offered in Studio.
 - To edit manually, select  and **Editor mode** and use the JSON editor to edit the route.

If the route status is  **Deployed**, it changes to  **Changes pending**.

3. Deploy the route as described in [Deploying and undeploying routes](#).

Import routes into Studio

When you import a route into Studio, it is imported in editor mode. You can use the JSON editor to manually edit the route, but can't use the full Studio interface to add or edit filters.

Routes created only in the menus of structured editor have the icon . Routes created only in the menus of FreeForm Designer have the icon . Imported routes and routes edited in editor mode have the icon .

1. In Studio, select  **ROUTES** and then  **Import a route**.
2. Click in the window to import a route, or drag a route from your filesystem.

If the route has a `name` property, the name is automatically used for the **Name** and **ID** fields in Studio.

3. If necessary, make the following changes, and then select **Import**:
 - If the **Name** and **ID** fields are empty, enter a unique name and ID for the route.
 - If the **Name** and **ID** fields are outlined in red, the route name or ID already exists in Studio. Change the name and ID to be unique.
 - If an error message is displayed, the route is not valid JSON. Fix the route and then try again to import it.

The route is added to the list of routes on the  **ROUTES** page.

4. Deploy the route as described in [Deploying and undeploying routes](#).

View and search for routes in your configuration

All of the routes that exist in your backend configuration are displayed on the  **ROUTES** page, including imported routes and routes created outside Studio.

To search for a route, select  **ROUTES**, and type part of the route name in the search box. Matching routes are displayed as you enter the search criteria.

Restrict access to Studio

When PingGateway is running in development mode, by default the Studio endpoint is open and accessible. To allow only specific users to access Studio, configure a `"studioProtectionFilter"` in `admin.json` with a `SingleSignOnFilter` or `CrossDomainSingleSignOnFilter`.

The following example uses a `SingleSignOnFilter` to require users to authenticate with AM before they can access Studio, and protects the request from Cross Site Request Forgery (CSRF) attacks.

1. Set up AM:

1. Select **Services > Add a Service** and add a **Validation Service** with the following **Valid goto URL Resources**:

- `http://ig.example.com:8085/*`
- `http://ig.example.com:8085/*?*`

2. Register a PingGateway agent with the following values, as described in [Register a PingGateway agent in AM](#):

- **Agent ID:** `ig_agent`
- **Password:** `password`



Important

Use secure passwords in a production environment. Consider using a password manager to generate secure passwords.

2. Set up PingGateway:

1. Set an environment variable for the PingGateway agent password, and then restart PingGateway:

```
$ export AGENT_SECRET_ID='cGFZc3dvcmQ='
```

The password is retrieved by a `SystemAndEnvSecretStore`, and must be base64-encoded.

2. Add the following `admin.json` configuration to PingGateway:

```

{
  "mode": "DEVELOPMENT",
  "properties": {
    "SsoTokenCookieOrHeader": "iPlanetDirectoryPro"
  },
  "adminConnector": {
    "host": "ig.example.com",
    "port": 8085
  },
  "connectors": [
    {
      "port": 8080
    },
    {
      "port": 8443
    }
  ],
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/",
        "ssoTokenHeader": "&{SsoTokenCookieOrHeader}"
      }
    }
  ],
  "studioProtectionFilter": {
    "type": "ChainOfFilters",
    "config": {
      "filters": [
        {
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        },
        {
          "type": "CsrfFilter",
          "config": {
            "cookieName": "&{SsoTokenCookieOrHeader}",
            "failureHandler": {
              "type": "StaticResponseHandler",
              "config": {
                "status": 403,
                "headers": {
                  "Content-Type": [
                    "text/plain"
                  ]
                }
              },
              "entity": "Request forbidden"
            }
          }
        }
      ]
    }
  }
}

```

```

    }
  }
}
]
}
}
}

```

Source: [admin-StudioProtectionFilter.json](#)

Notice the following features of the configuration:

- The `mode` is `development`, so by default the Studio endpoint is open and unfiltered.
- The `properties` object sets a configuration parameter for the value of the SSO token cookie or header, which is used in AmService and CorsFilter.
- The AmService uses the PingGateway agent in AM for authentication.
The agent password for AmService is provided by a SystemAndEnvSecretStore in the heap.
- The `"studioProtectionFilter"` calls the [SingleSignOnFilter](#) to redirect unauthenticated requests to AM. It uses the [CsrfFilter](#) to protect requests from CSRF attacks.

3. Restart PingGateway to take into account the changes to `admin.json`.

3. Test the setup:

1. If you are logged in to AM, log out and clear any cookies.
2. Go to <http://ig.example.com:8085/studio>. The SingleSignOnFilter redirects the request to AM for authentication.
3. Log in to AM with user `demo`, password `Ch4ng31t`. The Studio **Routes** screen is displayed.

Example routes created with Structured Editor (deprecated)

The following sections give examples of how to set up some of the routes used in the [Gateway guide](#) by using the structured editor of Studio.



Important

The structured editor of Studio is deprecated. For more information, refer to the [Deprecated](#) section of the *Release Notes*.



Important

SecretsProviders can't be configured in Studio. Documentation examples generated with Studio might refer to SecretsProviders that must be configured separately in `config.json`.

Single sign-on in Structured Editor

This section describes how to set up SSO in the structured editor of Studio. For more information about setting up SSO, refer to [Authentication with PingAM](#).

1. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
2. Select **Structured** to use the structured editor.

2. Select **Advanced options** on the right, and create a route with the following options:

- **Base URI:** `http://app.example.com:8081`
- **Condition: Path:** `/home/sso-studio`
- **Name :** `sso-studio`

3. Configure authentication:

1. Select **Authentication**.
2. Select **Single Sign-On**, and enter the following information:
 - **AM service :** Configure an AM service to use for authentication:
 - **URI:** `http://am.example.com:8088/openam`
 - **Secrets Provider:** `SystemAndEnvSecretStore-1`
 - **Agent :**
 - **Username :** `ig_agent`
 - **Password Secret ID :** `password.secret.id`

Leave all other values as default.

4. On the top-right of the screen, select **Display** to review the route.

5. Select **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

Policy enforcement in Structured Editor

This section describes how to set up PingGateway as a policy enforcement point in the structured editor of Studio. For more information about setting up policy enforcement, refer to [Enforce AM policy decisions](#).

1. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
2. Select **Structured** to use the structured editor.

2. Select **Advanced options** on the right, and create a route with the following options:

- **Base URI:** `http://app.example.com:8081`
- **Condition: Path:** `/home/pep-sso`
- **Name :** `pep-sso`

The structured editor is displayed.

3. Configure authentication:

1. Select  **Authentication**.
2. Select **Single Sign-On**, and enter the following information:
 - **AM service :** Configure an AM service to use for authentication:
 - **URI:** `http://am.example.com:8088/openam`
 - **Secrets Provider:** `SystemAndEnvSecretStore-1`
 - **Agent :** The credentials of the agent you created in AM.
 - **Username :** `ig_agent`
 - **Password Secret ID :** `password.secret.id`

Leave all other values as default.

4. Configure a PolicyEnforcementFilter:

1. Select  **Authorization**.
2. Select **AM Policy Enforcement**, and then select the following options:
 - Access Management configuration:
 - **AM service :** `http://am.example.com:8088/openam (/)`.
 - Access Management policies:
 - **Policy set :** `PEP-SSO`
 - **AM SSO token :** `${contexts.ssoToken.value}`

Leave all other values as default.

5. On the top-right of the screen, select  and  **Display** to review the route.

6. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

Policy enforcement for CDSSO in Structured Editor

This section describes how to set up PingGateway as a policy enforcement point for CDSSO in the structured editor of Studio. For more information about how to set up SSO, refer to [Decisions in different domains with PingAM](#)

1. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
2. Select **Structured** to use the structured editor.

2. Select **Advanced options** on the right, and create a route with the following options:

- **Base URI:** `http://app.example.com:8081`
- **Condition: Path:** `/home/pep-cdsso`
- **Name :** `pep-cdsso`

3. Configure authentication:

1. Select **Authentication**.
2. Select **Cross-Domain Single Sign-On**, and enter the following information:

■ **AM service :**

- **URI:** `http://am.example.com:8088/openam`
- **Secrets Provider:** `SystemAndEnvSecretStore-1`
- **Agent :** The credentials of the agent you created in AM.
 - **Username :** `ig_agent_cdsso`
 - **Password Secret ID :** `password.secret.id`

- **Redirect endpoint :** `/home/pep-cdsso/redirect`

■ **Authentication cookie :**

- **Path :** `/home`

Leave all other values as default.

4. Configure a PolicyEnforcementFilter:

1. Select **Authorization**.
2. Select **AM Policy Enforcement**, and select the following options to reflect the configuration of the PingGateway agent in AM:

■ **Access Management configuration:**

- **AM service :** `http://am.example.com:8088/openam (/)`.

- Access Management policies:

- Policy set : PEP-CDSSO

- AM SSO token ID : \${contexts.cdsso.token}

Leave all other values as default.

5. On the top-right of the screen, select  and **Display** to review the route.

6. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

Token validation using the introspection endpoint in Structured Editor

This section sets up PingGateway as an OAuth 2.0 resource server, using the introspection endpoint, in the structured editor of Studio.

1. Set up AM as described in [Validating PingAM access tokens with introspection](#). In addition, create an OAuth 2.0 Client authorized to introspect tokens with the following values:

- **Client ID** : resource-server
- Client secret password
- **Scope(s)** : am-introspect-all-tokens

2. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
2. Select  **Structured** to use the structured editor.
3. Create a route with the following option:

- Application URL: `http://app.example.com:8081/rs-introspect-se`

3. Configure authorization:

1. Select  **Authorization** > **OAuth 2.0 Resource Server**, and then select the following options:

- **Token resolver configuration:**

- **Access token resolver**: OAuth 2.0 introspection endpoint

- **Introspection endpoint URI**: `http://am.example.com:8088/openam/oauth2/introspect`

- **Client name** and **Client secret** : resource-server and password

This is the name and password of the OAuth 2.0 client with the scope to examine (introspect) tokens, configured in AM.

- **Scope configuration:**

- **Evaluate scopes**: Statically

- **Scopes**: mail, employeenumber

■ OAuth 2.0 Authorization settings:

- **Require HTTPS:** Deselect this option
- **Enable cache:** Deselect this option

Leave all other values as default.

4. Add a StaticResponseHandler:

1. On the top-right of the screen, select  and  **Editor mode** to switch into editor mode.



Warning

After switching to Editor mode, you cannot go back. You will be able to use the JSON file editor to manually edit the route but will no longer be able use the full Studio interface to add or edit filters.

2. Replace the last ReverseProxyHandler in the route with the following StaticResponseHandler, and then save the route:

```
"handler": {
  "type": "StaticResponseHandler",
  "config": {
    "status": 200,
    "headers": {
      "Content-Type": [ "text/html; charset=UTF-8" ]
    },
    "entity": "<html><body><h2>Decoded access_token: ${contexts.oauth2.accessToken.info}</h2></body></html>"
  }
}
```

5. On the top-right of the screen, select  and  **Display** to review the route.
6. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

OpenID Connect in Structured Editor

This section describes how to set up PingGateway as an OpenID Connect relying party in the structured editor of Studio. For more information, refer to [AM as OIDC provider](#).

1. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
2. Select **Structured** to use the structured editor.

2. Select **Advanced options** on the right, and create a route with the following options:

- **Base URI:** `http://app.example.com:8081`
- **Condition: Path:** `/home/id_token`

- **Name:** 07-openid

3. Configure authentication:

1. Select  **Authentication**.
2. Select **OpenID Connect**, and then select the following options:

- **Client Filter:**

- **Client Endpoint:** /home/id_token
- **Require HTTPS:** Deselect this option

- **Client Registration:**

- **Client ID:** oidc_client
- **Client secret:** password
- **Scopes:** openid, profile, and email
- **Basic authentication:** Select this option

- **Issuer:**

- **Well-known Endpoint:** http://am.example.com:8088/openam/oauth2/.well-known/openid-configuration

Leave all other values as default.

4. On the top-right of the screen, select  and  **Display** to review the route.
5. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openid/config/routes` folder to see that the route is there.

Token transformation in Structured Editor

This section describes how to set up token transformation in the structured editor of Studio. For more information about setting up token transformation, refer to [OIDC ID tokens to SAML assertions with PingAM](#).

1. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
2. Select  **Structured** to use the structured editor.

2. Select **Advanced options** on the right, and create a route with the following options:

- **Base URI:** `http://app.example.com:8081`
- **Condition:** Path: `/home/id_token`
- **Name:** `50-idtoken`

3. Configure authentication:

1. Select  **Authentication**.

2. Select **OpenID Connect**, and enter the following information:

■ **Client Filter :**

- **Client Endpoint:** `/home/id_token`
- **Require HTTPS:** Deselect this option

■ **Client Registration :**

- **Client ID :** `oidc_client`
- **Client secret :** `password`
- **Scopes:** `openid`, `profile`, and `email`
- **Basic authentication:** Select this option

■ **Issuer :**

- **Well-known endpoint:** `http://am.example.com:8088/openam/oauth2/.well-known/openid-configuration`

Leave all other values as default, and save your settings.

4. Set up token transformation:

1. Select and enable **Token transformation**.

2. Enter the following information:

■ **AM service :** Configure an AM service to use for authentication and REST STS requests.

- **URI:** `http://am.example.com:8088/openam`
- **Secrets Provider:** `SystemAndEnvSecretStore-1`
- **Agent :** The credentials of the agent you created in AM.
 - **Username :** `ig_agent`
 - **Password Secret ID :** `password.secret.id`

- **Username :** `oidc_client`
- **Password :** `password`
- **id_token :** `${attributes.openid.id_token}`
- **Instance :** `openig`

5. Add a StaticResponseHandler:

1. On the top-right of the screen, select  and  **Editor mode** to switch into editor mode.

Warning

After switching to Editor mode, you cannot go back. You will be able to use the JSON file editor to manually edit the route but will no longer be able use the full Studio interface to add or edit filters.

2. Replace the last ReverseProxyHandler in the route with the following StaticResponseHandler, and then save the route:

```
"handler": {
  "type": "StaticResponseHandler",
  "config": {
    "status": 200,
    "headers": {
      "Content-Type": [ "text/plain; charset=UTF-8" ]
    },
    "entity": " {\\"id_token\\":\n\"${attributes.openid.id_token}\"} \n\n\n{\\"saml_assertions\\":\n\"${contexts.sts.issuedToken}\"}"
  }
}
```

6. On the top-right of the screen, select  **Display** to review the route.
7. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

Simple throttling filter in Structured Editor

This section describes how to set up a simple throttling filter in the structured editor of Studio. For more information about how to set up throttling, refer to [Configure simple throttling](#).

1. In PingGateway Studio, create a route:
 1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
 2. Select **≡ Structured** to use the structured editor.
2. Select **Advanced options** on the right, and create a route with the following options:
 - **Base URI:** `http://app.example.com:8081`
 - **Condition: Path:** `/home/throttle-simple`
 - **Name:** `00-throttle-simple`

3. Select and enable **▼ Throttling**.

4. In **GROUPING POLICY**, apply the rate to a single group.

All requests are grouped together, and the default throttling rate is applied to the group. By default, no more than 100 requests can access the sample application each second.

5. In **RATE POLICY**, select **Fixed**, and allow 6 requests each 10 seconds.
6. On the top-right of the screen, select  **Display** to review the route.

7. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

Mapped throttling filter in Structured Editor

This section describes how to set up a mapped throttling filter in the structured editor of Studio. For more information about how to set up throttling, refer to [Configure mapped throttling](#).

1. Set up AM as described in [Validating PingAM access tokens with introspection](#). In addition, create an OAuth 2.0 Client authorized to introspect tokens with the following values:

- **Client ID** : `resource-server`
- Client secret `password`
- **Scope(s)** : `am-introspect-all-tokens`

2. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
2. Select  **Structured** to use the structured editor.

3. Select **Advanced options** on the right, and create a route with the following options:

- **Base URI**: `http://app.example.com:8081`
- **Condition: Path**: `/home/throttle-mapped-se`
- **Name** : `00-throttle-mapped-se`

4. Configure authorization:

1. Select  **Authorization** > **OAuth 2.0 Resource Server**, and then select the following options:

■ **Token resolver configuration:**

- **Access token resolver**: `OAuth 2.0 introspection endpoint`
- **Introspection endpoint URI**: `http://am.example.com:8088/openam/oauth2/introspect`
- **Client name** and **Client secret** : `resource-server` and `password`

This is the name and password of the OAuth 2.0 client with the scope to examine (introspect) tokens, configured in AM.

■ **Scope configuration:**

- **Evaluate scopes**: `Statically`
- **Scopes**: `mail`, `employeenumber`

■ **OAuth 2.0 Authorization settings:**

- **Require HTTPS**: Deselect this option
- **Enable cache**: Deselect this option

Leave all other values as default.

5. Configure throttling:

1. Select and enable  **Throttling**.

2. Set up the grouping policy:

1. In **GROUPING POLICY**, apply the rate to independent groups of requests.

Requests are split into different groups according to criteria, and the throttling rate is applied to each group.

2. Select to group requests by custom criteria.

Enter `${contexts.oauth2.accessToken.info.mail}` as the custom expression. This expression defines the subject in the OAuth2Context.

3. Set up the rate policy:

1. In **RATE POLICY**, select **Mapped**.

2. Select to map requests by custom criteria.

3. Enter the custom expression `${contexts.oauth2.accessToken.info.status}`.

4. In **Default Rate**, select **Edit** and change default rate to 1 request each 10 seconds.

5. In **Mapped Rates**, add the following rate for `gold` status:

■ **Match Value** : `gold`

■ **Number of requests** : 6

■ **Period** : 10 seconds

6. Add a different rate for `silver` status:

■ **Match Value** : `silver`

■ **Number of requests** : 3

■ **Period** : 10 seconds

7. Add a different rate for `bronze` status:

■ **Match Value** : `bronze`

■ **Number of requests** : 1

■ **Period** : 10 seconds

8. Save the rate policy.

6. Select  **Chain**, and change the order of the filters so  **Throttling** comes after  **Authorization**.

7. On the top-right of the screen, select  and  **Display** to review the route.

8. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

Scriptable throttling filter in Structured Editor

This section describes how to set up a scriptable throttling filter in the structured editor of Studio. For more information about how to set up throttling, refer to [Configure scriptable throttling](#).

1. Set up AM as described in [Validating PingAM access tokens with introspection](#). In addition, create an OAuth 2.0 Client authorized to introspect tokens with the following values:

- **Client ID:** `resource-server`
- **Client secret:** `password`
- **Scope(s):** `am-introspect-all-tokens`

2. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
2. Select **Structured** to use the structured editor.

3. Select **Advanced options** on the right, and create a route with the following options:

- **Base URI:** `http://app.example.com:8081`
- **Condition: Path:** `/home/throttle-scriptable-se`
- **Name:** `00-throttle-scriptable-se`

4. Configure authorization:

1. Select **Authorization > OAuth 2.0 Resource Server**, and then select the following options:

- **Token resolver configuration:**

- **Access token resolver:** `OAuth 2.0 introspection endpoint`
- **Introspection endpoint URI:** `http://am.example.com:8088/openam/oauth2/introspect`
- **Client name and Client secret:** `resource-server` and `password`

This is the name and password of the OAuth 2.0 client with the scope to examine (introspect) tokens, configured in AM.

- **Scope configuration:**

- **Evaluate scopes:** `Statically`
- **Scopes:** `mail`, `employeenumber`

- **OAuth 2.0 Authorization settings:**

- **Require HTTPS:** Deselect this option
- **Enable cache:** Deselect this option

Leave all other values as default.

5. Configure throttling:

1. Select and enable  **Throttling**.

2. Set up the grouping policy:

1. In **GROUPING POLICY**, apply the rate to independent groups of requests.

Requests are split into different groups according to criteria, and the throttling rate is applied to each group.

2. Select to group requests by custom criteria.

3. Enter `${contexts.oauth2.accessToken.info.mail}` as the custom expression.

3. Set up the rate policy:

1. In **RATE POLICY**, select **Scripted**.

2. Select to create a new script, and name it `X-User-Status`. So that you can easily identify the script, use a name that describes the content of the script.

3. Add the following argument/value pairs:

- **argument:** `status`, **value:** `gold`
- **argument:** `rate`, **value:** `6`
- **argument:** `duration`, **value:** `10 seconds`

- Replace the default script with the content of a valid Groovy script. For example, enter the following script:

```
if (contexts.oauth2.accessToken.info.status == status) {  
    return new ThrottlingRate(rate, duration)  
} else {  
    return null  
}
```

Alternatively, skip the step to define arguments, and add the following script instead:

```
if (contexts.oauth2.accessToken.info.status == 'gold') {  
    return new ThrottlingRate(6, '10 seconds')  
} else {  
    return null  
}
```



Note

Studio doesn't check the validity of the Groovy script.

4. Enable the default rate, and set it to 1 request each 10 seconds.

5. Save the rate policy. The script is added to the list of reference scripts available to use in scriptable throttling filters.

6. Select  **Chain**, and change the order of the filters so  **Throttling** comes after  **Authorization**.
7. On the top-right of the screen, select  and  **Display** to review the route.
8. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

Proxy for websocket traffic in Structured Editor

This section describes how to set up PingGateway to proxy WebSocket traffic, in the structured editor of Studio. For more information about how to set up proxying for WebSocket traffic, refer to [WebSocket traffic with PingAM](#).

1. In PingGateway Studio, create a route:
 1. Go to `http://ig.example.com:8085/studio`, and then select  **Create a route**.
 2. Select  **Structured** to use the structured editor.
2. Select **Advanced options** on the right, and create a route with the following options:
 - **Base URI**: `http://app.example.com:8081`
 - **Condition: Path**: `/websocket-se`
 - **Name**: `websocket-se`
 - **Enable WebSocket**: Select this option
 1. Select  **Authentication**.
 2. Select **Single Sign-On**, and enter the following information:
 - **AM service**: Configure an AM service to use for authentication:
 - **URI**: `http://am.example.com:8088/openam`
 - **Secrets Provider**: `SystemAndEnvSecretStore-1`
 - **Agent**:
 - **Username**: `ig_agent`
 - **Password Secret ID**: `password.secret.id`

Leave all other values as default.

3. On the top-right of the screen, select  and  **Display** to review the route.
4. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

Example routes created with Freeform Designer

The following sections give examples of how to use the templates provided by the FreeForm Designer:



Important

SecretsProviders can't be configured in Studio. Documentation examples generated with Studio might refer to SecretsProviders that must be configured separately in `config.json`.

Use a basic template in FreeForm Designer

This section describes how to use a basic template in FreeForm Designer to set up SSO. For more information about setting up and testing SSO, refer to [Authentication with PingAM](#).

1. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
2. Select  **Freeform** to use the FreeForm Designer.

2. Select  **Basic** to create a route from a blank template.

3. Select **Advanced options** on the right, and create a route with the following options:

- **Base URI:** `http://app.example.com:8081`
- **Condition: Path:** `/home/sso-ff`
- **Name:** `sso-ff`

The route is displayed on the  **Flow** tab of the canvas. Select the  **All Objects** tab to view a list of objects in the route.

Double-click on any object to review or edit it. After double-clicking on an object, select the **Decorations** tab to decorate it.

4. Configure authentication with a SingleSignOnFilter:

1. In the  **Flow** tab, delete the connector between **Start** and **ReverseProxyHandler**.
2. From the sidebar, drag a  **Chain** onto the canvas, and then drag a  **SingleSignOnFilter** into the chain.
3. In the **Edit SingleSignOnFilter** page, click **+**, and create an AM service, with the following values:

- **URI:** `http://am.example.com:8088/openam`
- **Secrets Provider:** `SystemAndEnvSecretStore-1`
- **Agent:**
 - **Username:** `ig_agent`
 - **Password Secret ID :** `agent.secret.id`

4. Connect **Start** to **Chain-1**, and **Chain-1** to **ReverseProxyHandler**.

5. On the top-right of the screen, select  and  **Display** to review the route.

```

{
  "name": "sso-ff",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/sso-ff')}",
  "handler": "Chain-1",
  "heap": [
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler"
    },
    {
      "type": "BaseUriDecorator",
      "name": "baseUri"
    },
    {
      "type": "TimerDecorator",
      "name": "timer",
      "config": {
        "timeUnit": "ms"
      }
    },
    {
      "type": "CaptureDecorator",
      "name": "capture",
      "config": {
        "captureEntity": false,
        "captureContext": false,
        "maxEntityLength": 524288
      }
    },
    {
      "name": "Chain-1",
      "type": "Chain",
      "config": {
        "handler": "ReverseProxyHandler",
        "filters": [
          "SingleSignOnFilter-1"
        ]
      }
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "url": "http://am.example.com:8088/openam",
        "realm": "/",
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "sessionCache": {
          "enabled": false
        }
      }
    },
    {
      "name": "SingleSignOnFilter-1",
      "type": "SingleSignOnFilter",
      "config": {

```

```

    "amService": "AmService-1"
  }
}
]
}

```

Source: [sso-ff.json](#)

6. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

Protect a web app with Freeform Designer

This section describes how to use FreeForm Designer to protect a web app, using AM for single sign-on and policy enforcement.

The generated route contains a chain of objects to authenticate the user, enforce an AM authorization policy, retrieve the user's profile, insert it into the request, and, finally, forward the request to the web app.

Before you start, set up AM as described in [Enforce AM policy decisions](#).

1. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio`, and then select **+ Create a route**.
2. Select  **Freeform** to use the FreeForm Designer.

2. Select  **Web SSO** to use the template for protecting web apps.

3. Select **Advanced options** on the right, and create a route with the following options:

- **Base URI** : `http://app.example.com:8081`
- **Condition: Path** : `/home/pep-sso-ff`
- **Name** : `pep-sso-ff`
- **AM Configuration** :
 - **URI** : `http://am.example.com:8088/openam`
 - **Secrets Provider**: `SystemAndEnvSecretStore-1`
 - **Username** : `ig_agent`
 - **Password Secret ID** : `agent.secret.id`

The route is displayed on the  **Flow** tab of the canvas. Select the  **All Objects** tab to view a list of objects in the route.

Double-click on any object to review or edit it. After double-clicking on an object, select the **Decorations** tab to decorate it.

4. On the  **Flow** tab, double-click the Policy Enforcement object, and add a policy set with the following values:

- **Policy set** : `PEP-SSO`

- **AM SSO token** : `${contexts.ssoToken.value}`

Leave all other values as default.

5. On the top-right of the screen, select  and **Display** to review the route.

```

{
  "name": "pep-sso-ff",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/pep-sso-ff')}",
  "handler": "Chain",
  "heap": [
    {
      "name": "Chain",
      "type": "Chain",
      "config": {
        "handler": "ReverseProxyHandler",
        "filters": [
          "SSO",
          "Policy Enforcement",
          "GetEmail",
          "InjectEmail"
        ]
      }
    },
    {
      "name": "SSO",
      "type": "SingleSignOnFilter",
      "config": {
        "amService": "AmService"
      }
    },
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler"
    },
    {
      "name": "AmService",
      "type": "AmService",
      "config": {
        "url": "http://am.example.com:8088/openam",
        "realm": "/",
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "sessionCache": {
          "enabled": false
        }
      }
    },
    {
      "name": "Policy Enforcement",
      "type": "PolicyEnforcementFilter",
      "config": {
        "amService": "AmService",
        "ssoTokenSubject": "${contexts.ssoToken.value}",
        "cache": {
          "enabled": false
        },
        "application": "PEP-SSO"
      }
    },
    {
      "name": "GetEmail",

```

```

    "type": "UserProfileFilter",
    "config": {
      "username": "${contexts.ssoToken.info.uid}",
      "userService": {
        "type": "UserProfileService",
        "config": {
          "amService": "AmService"
        }
      }
    }
  },
  {
    "name": "InjectEmail",
    "type": "HeaderFilter",
    "config": {
      "messageType": "REQUEST",
      "add": {
        "Email": [
          "${contexts.userProfile.username}"
        ]
      }
    }
  },
  {
    "type": "BaseUriDecorator",
    "name": "baseUri"
  },
  {
    "type": "TimerDecorator",
    "name": "timer",
    "config": {
      "timeUnit": "ms"
    }
  },
  {
    "type": "CaptureDecorator",
    "name": "capture",
    "config": {
      "captureEntity": false,
      "captureContext": false,
      "maxEntityLength": 524288
    }
  }
]
}

```

Source: [pep-sso-ff.json](#)

6. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

Protect an API with Freeform Designer

This section describes how to use FreeForm Designer to protect APIs, using AM as an OAuth 2.0 Authorization Server.

The generated route contains a chain of objects to authenticate the user, throttle the rate of requests to the API, and, finally, forward the request to the sample app.

Before you start, set up AM as described in [Validating PingAM access tokens with introspection](#). In addition, create an OAuth 2.0 Client authorized to introspect tokens with the following values:

- **Client ID** : `resource-server`
- **Client secret** : `password`
- **Scope(s)** : `am-introspect-all-tokens`

1. In PingGateway Studio, create a route:

1. Go to `http://ig.example.com:8085/studio` , and then select **+ Create a route**.
2. Select  **Freeform** to use the FreeForm Designer.

2. Select **API Security**.

3. Select **Advanced options** on the right, and create a route with the following options:

- **Base URI** : `http://app.example.com:8081`
- **Condition: Path** : `/home/rs-introspect-ff`
- **Name** : `rs-introspect-ff`
- **AM Configuration** :
 - **URI** : `http://am.example.com:8088/openam`
 - **Secrets Provider**: `SystemAndEnvSecretStore-1`
 - **Username** : `ig_agent`
 - **Password Secret ID** : `agent.secret.id`
 - **Scopes** : `mail` , `employeenumber`

The route is displayed on the  **Flow** tab of the canvas.

Notice that the **Start**, **Chain**, and **ReverseProxyHandler** objects are connected by solid lines, but other objects, such as **Authenticate to Am Chain**, are connected by a fading line. Objects connected by a fading line are used by other objects in the route.

Select the  **All Objects** tab to view a list of objects in the route. Double-click on any object to review or edit it. After double-clicking on an object, select the **Decorations** tab to decorate it.

4. On the  **Flow** tab, double-click the OAuth2RS object, and edit it as follows:

- **Require HTTPS** : Deselect this option
- **Realm** : `OpenIG`

Leave the other values as they are.

5. On the top-right of the screen, select  and  **Display** to review the route.

```

{
  "name": "rs-introspect-ff",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/rs-introspect-ff')}",
  "handler": "Chain",
  "properties": {
    "amSecretsProvider": "SystemAndEnvSecretStore-1",
    "amUsername": "ig_agent",
    "amPasswordSecretId": "agent.secret.id"
  },
  "heap": [
    {
      "name": "ClientHandler",
      "type": "ClientHandler"
    },
    {
      "name": "Chain",
      "type": "Chain",
      "config": {
        "handler": "ReverseProxyHandler",
        "filters": [
          "OAuth2RS",
          "Throttling"
        ]
      }
    },
    {
      "type": "OAuth2ResourceServerFilter",
      "name": "OAuth2RS",
      "config": {
        "requireHttps": false,
        "scopes": [
          "mail",
          "employeenumber"
        ],
        "accessTokenResolver": "TokenIntrospectionAccessTokenResolver"
      }
    },
    {
      "type": "TokenIntrospectionAccessTokenResolver",
      "name": "TokenIntrospectionAccessTokenResolver",
      "config": {
        "amService": "AmService",
        "providerHandler": "Authenticate to AM Chain"
      }
    },
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler"
    },
    {
      "name": "AmService",
      "type": "AmService",
      "config": {
        "url": "http://am.example.com:8088/openam",
        "realm": "/",
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        }
      }
    }
  ]
}

```



```

    },
    "sessionCache": {
      "enabled": false
    }
  },
  {
    "name": "Authenticate to AM Chain",
    "type": "Chain",
    "config": {
      "handler": "ClientHandler",
      "filters": [
        "Authenticate to AM Filter"
      ]
    }
  },
  {
    "name": "Authenticate to AM Filter",
    "type": "HttpBasicAuthenticationClientFilter",
    "config": {
      "username": "ig_agent",
      "passwordSecretId": "password.secret.id",
      "secretsProvider": "SystemAndEnvSecretStore-1"
    }
  },
  {
    "name": "Throttling",
    "type": "ThrottlingFilter",
    "config": {
      "requestGroupPolicy": "${contexts.oauth2.info.sub}",
      "rate": {
        "numberOfRequests": 60,
        "duration": "60 s"
      }
    }
  },
  {
    "type": "BaseUriDecorator",
    "name": "baseUri"
  },
  {
    "type": "TimerDecorator",
    "name": "timer",
    "config": {
      "timeUnit": "ms"
    }
  },
  {
    "type": "CaptureDecorator",
    "name": "capture",
    "config": {
      "captureEntity": false,
      "captureContext": false,
      "maxEntityLength": 524288
    }
  }
]
}

```

Source: [rs-introspect-ff.json](#)

6. Select  **Deploy** to push the route to the PingGateway configuration.

You can check the `$HOME/.openig/config/routes` folder to see that the route is there.

7. Test the setup:

1. In a terminal window, use a `curl` command similar to the following to retrieve an access token:

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=mail%20employeeenumber" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

2. Validate the access token returned in the previous step:

```
$ curl -v http://ig.example.com:8080/home/rs-introspect-ff --header "Authorization: Bearer ${mytoken}"
```

The HTML of the sample application is returned.

Summary of tasks, route status, and icons

The following tables summarize the basic tasks that you can do in Studio, and summarizes the icons and status displayed in Studio:

Task reference

To do this	Do this
Create a new route	Select  ROUTES , + Create a route .
Select a route	Select  ROUTES , and then select a route to view.
Display the config of a selected route	Select a route, and then select  and  Display .
Deploy a selected route	Select a route, and then select  Deploy .
Undeploy a selected route	Select a deployed route, and then select  and  Undeploy .
Change the basic config of a route	Select a route, and then select  Route settings . Edit the route and save the changes.

Route status

Status	Description	Action
! Undeployed	The route is saved in Studio but is not deployed to the backend.	Deploy the route. The status changes to Deployed .
Deployed	The route is saved in Studio and deployed to the backend.	None. The route has the same configuration in Studio and the backend.
! Changes pending	The route has been deployed and then subsequently changed in Studio.	Deploy the route. The status changes to Deployed .
⚠ Out of sync	The route has been deployed and then subsequently changed in the backend, or in both Studio and the backend.	Select Deploy. A message informs you that a different version of the route is deployed in the backend. Select an option: • Deploy: The version in Studio overwrites the backend. • Import a route: The version in the backend overwrites Studio. When you import a route into Studio you go into editor mode. You can use the JSON editor to manually edit the route, but can no longer use the full Studio interface to add or edit filters.
⚠ Compatibility update required	The route was created in Studio in an earlier version of PingGateway. Some information is needed to complete the upgrade.	Enter the information as prompted, and then select Deploy to deploy the route.

Icons

Icon	Mode	Description
	Structured editor	The route was created and edited using the menus and options of structured editor.
	Editor mode	The route was imported into Studio, or was created in Studio and then edited in editor mode.

Icon	Mode	Description
	Freeform designer	The route was created on the canvas of FreeForm Designer.

Maintaining PingGateway deployments

These pages describe tasks and configurations you repeat throughout the life cycle of a deployment in your organization. They're for people who maintain PingGateway services for their organization.

Auditing the PingGateway deployment

The following sections describe how to set up auditing for your deployment. You can find information on how to include user ID in audit logs in [Recording User ID in Audit Events](#).

You can find more information about configuring the JMS event handler in [PingGateway audit framework](#).

Record access audit events in CSV

This section describes how to record access audit events in a CSV file.



Important

The CSV handler doesn't sanitize messages when writing to CSV log files. Don't open CSV logs in spreadsheets or other applications that treat data as code.

Before you start, prepare PingGateway and the sample application as described in the [Getting started with PingGateway](#).

1. Set up PingGateway

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/30-csv.json
```

Windows

```
%appdata%\OpenIG\config\routes\30-csv.json
```

```

{
  "name": "30-csv",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/csv-audit')}",
  "heap": [
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.csv.CsvAuditEventHandler",
            "config": {
              "name": "csv",
              "logDirectory": "/tmp/logs",
              "topics": [
                "access"
              ]
            }
          }
        ],
        "config": { }
      }
    },
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.csv.CsvAuditEventHandler",
            "config": {
              "name": "csv",
              "logDirectory": "/tmp/logs",
              "topics": [
                "access"
              ]
            }
          }
        ],
        "config": { }
      }
    }
  ],
  "auditService": "AuditService",
  "handler": "ForgeRockClientHandler"
}

```

Source: [30-csv.json](#)

The route calls an audit service configuration for publishing log messages to the CSV file, `/tmp/logs/access.csv`.

When a request matches `audit`, audit events are logged to the CSV file.

The route uses the `ForgeRockClientHandler` as its handler, to send the `X-ForgeRock-TransactionId` header with its requests to external services.

2. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/csv-audit>.

The sample application displays the home page and PingGateway updates the `/tmp/logs/access.csv` file.

Record access audit events with a JMS audit event handler

Important

- The `JmsAuditEventHandler` is deprecated. Use an alternative audit event handler.
- This procedure is an example of how to record access audit events with a JMS audit event handler configured to use the ActiveMQ message broker. This example isn't tested on all configurations, and can be more or less relevant to your configuration.

Before you start, prepare PingGateway as described in the [Getting started with PingGateway](#).

1. Download the following files:

- [ActiveMQ binary](#). PingGateway is tested with ActiveMQ Classic 5.15.11.
- [ActiveMQ Client](#). Use a version that corresponds to your ActiveMQ version.
- [Apache Geronimo J2EE management bundle](#).
- [hawtbuf-1.11 JAR](#).

2. Add the files to the configuration:

- Create the directory `$HOME/.openig/extra`, where `$HOME/.openig` is the instance directory, and add .jar files to the directory.

3. Create a consumer that subscribes to the `audit` topic.

From the ActiveMQ installation directory, run the following command:

```
$ ./bin/activemq consumer --destination topic://audit
```

4. Set up PingGateway

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/30-jms.json
```

Windows

```
%appdata%\OpenIG\config\routes\30-jms.json
```



```

{
  "name": "30-jms",
  "MyCapture" : "all",
  "baseURI": "http://app.example.com:8081",
  "condition" : "${request.uri.path == '/activemq_event_handler'}",
  "heap": [
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers" : [
          {
            "class" : "org.forgerock.audit.handlers.jms.JmsAuditEventHandler",
            "config" : {
              "name" : "jms",
              "topics": [ "access" ],
              "deliveryMode" : "NON_PERSISTENT",
              "sessionMode" : "AUTO",
              "jndi" : {
                "contextProperties" : {
                  "java.naming.factory.initial" :
"org.apache.activemq.jndi.ActiveMQInitialContextFactory",
                  "java.naming.provider.url" : "tcp://am.example.com:61616",
                  "topic.audit" : "audit"
                },
                "topicName" : "audit",
                "connectionFactoryName" : "ConnectionFactory"
              }
            }
          }
        ],
        "config" : { }
      }
    },
    {
      "name": "auditService": "AuditService",
      "handler" : {
        "type" : "StaticResponseHandler",
        "config" : {
          "status" : 200,
          "headers" : {
            "Content-Type" : [ "text/plain; charset=UTF-8" ]
          },
          "entity" : "Message from audited route"
        }
      }
    }
  ]
}

```

Source: [30-jms.json](#)

When a request matches the `/activemq_event_handler` route, this configuration publishes JMS messages containing audit event data to an ActiveMQ managed JMS topic, and the `StaticResponseHandler` displays a message.

5. Test the setup:

1. In your browser's privacy or incognito mode, go to https://ig.example.com:8443/activemq_event_handler.

Depending on how ActiveMQ is configured, audit events are displayed on the ActiveMQ console or written to file.

Record access audit events with a JSON audit event handler

This section describes how to record access audit events with a JSON audit event handler. You can find more information about configuring the JSON event handler in [JsonAuditEventHandler](#).

1. Set up PingGateway

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/30-json.json
```

Windows

```
%appdata%\OpenIG\config\routes\30-json.json
```

```
{
  "name": "30-json",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/json-audit')}",
  "heap": [
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.json.JsonAuditEventHandler",
            "config": {
              "name": "json",
              "logDirectory": "/tmp/logs",
              "topics": [
                "access"
              ],
              "rotationRetentionCheckInterval": "1 minute",
              "buffering": {
                "maxSize": 100000,
                "writeInterval": "100 ms"
              }
            }
          }
        ]
      }
    }
  ],
  "auditService": "AuditService",
  "handler": "ReverseProxyHandler"
}
```

Source: [30-json.json](#) 

Notice the following features of the route:

- The route calls an audit service configuration for publishing log messages to the JSON file, `/tmp/audit/access.audit.json`. When a request matches `/home/json-audit`, a single line per audit event is logged to the JSON file.
- The route uses the `ForgeRockClientHandler` as its handler to send the `X-ForgeRock-TransactionId` header with its requests to external services.

2. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/json-audit>.

The home page of the sample application is displayed and the file `/tmp/logs/access.audit.json` is created or updated with a message. The following example message is formatted for easy reading, but it is produced as a single line for each event:

```
{
  "_id": "830...-41",
  "timestamp": "2019-...540Z",
  "eventName": "OPENIG-HTTP-ACCESS",
  "transactionId": "830...-40",
  "client": {
    "ip": "0:0:0:0:0:0:1",
    "port": 51666
  },
  "server": {
    "ip": "0:0:0:0:0:0:1",
    "port": 8080
  },
  "http": {
    "request": {
      "secure": false,
      "method": "GET",
      "path": "http://ig.example.com:8080/home/json-audit",
      "headers": {
        "accept": ["text/html,application/xhtml+xml,application/xml;q=0.9,/;q=0.8"],
        "host": ["ig.example.com:8080"],
        "user-agent": ["Mozilla/5.0 ... Firefox/66.0"]
      }
    }
  },
  "response": {
    "status": "SUCCESSFUL",
    "statusCode": "200",
    "elapsedTime": 212,
    "elapsedTimeUnits": "MILLISECONDS"
  },
  "ig": {
    "exchangeId": "b3f...-29",
    "routeId": "30-json",
    "routeName": "30-json"
  }
}
```

Record access audit events to standard output

This section describes how to record access audit events to standard output. You can find more information about the event handler in [JsonStdoutAuditEventHandler](#).

Before you start, prepare PingGateway and the sample application as described in the [Getting started with PingGateway](#).

1. Set up PingGateway

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/30-jsonstdout.json
```

Windows

```
%appdata%\OpenIG\config\routes\30-jsonstdout.json
```

```
{
  "name": "30-jsonstdout",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/jsonstdout-audit')}",
  "heap": [
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.json.stdout.JsonStdoutAuditEventHandler",
            "config": {
              "name": "jsonstdout",
              "elasticsearchCompatible": false,
              "topics": [
                "access"
              ]
            }
          }
        ]
      },
      "config": {}
    }
  ],
  "auditService": "AuditService",
  "handler": "ReverseProxyHandler"
}
```

Source: [30-jsonstdout.json](#) 

Notice the following features of the route:

- The route matches requests to `/home/jsonstdout-audit`.

- The route calls the audit service configuration for publishing access log messages to standard output. When a request matches `/home/jsonstdout-audit`, a single line per audit event is logged.

2. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/jsonstdout-audit>.

The home page of the sample application is displayed, and a message like this is published to standard output:

```
{
  "_id": "830...-61",
  "timestamp": "2019-...89Z",
  "eventName": "OPENIG-HTTP-ACCESS",
  "transactionId": "830...-60",
  "client": {
    "ip": "0:0:0:0:0:0:1",
    "port": 51876
  },
  "server": {
    "ip": "0:0:0:0:0:0:1",
    "port": 8080
  },
  "http": {
    "request": {
      "secure": false,
      "method": "GET",
      "path": "http://ig.example.com:8080/home/jsonstdout-audit",
      "headers": {
        "accept": ["text/html,application/xhtml+xml,application/xml;q=0.9,/;q=0.8"],
        "host": ["ig.example.com:8080"],
        "user-agent": ["Mozilla/5.0 ... Firefox/66.0"]
      }
    }
  },
  "response": {
    "status": "SUCCESSFUL",
    "statusCode": "200",
    "elapsedTime": 10,
    "elapsedTimeUnits": "MILLISECONDS"
  },
  "ig": {
    "exchangeId": "b3f...-41",
    "routeId": "30-jsonstdout",
    "routeName": "30-jsonstdout"
  },
  "source": "audit",
  "topic": "access",
  "level": "INFO"
}
```

Trust transaction IDs from other products

Each audit event is identified by a unique transaction ID that can be communicated across products and recorded for each local event. By using the transaction ID, requests can be tracked as they traverse the platform, making it easier to monitor activity and to enrich reports.

The `X-ForgeRock-TransactionId` header is automatically set in all outgoing HTTP calls from one ForgeRock product to another. Customers can also set this header themselves from their own applications or scripts that call into the Ping Identity Platform.

To reduce the risk of malicious attacks, by default PingGateway doesn't trust transaction ID headers from client applications.

If you trust the transaction IDs sent by your client applications, consider setting Java system property `org.forgerock.http.TrustTransactionHeader` to `true`.

Add the following system property in `env.sh`:

```
# Specify a JVM option
TX_HEADER_OPT="-Dorg.forgerock.http.TrustTransactionHeader=true"

# Include it into the JAVA_OPTS environment variable
export JAVA_OPTS="${TX_HEADER_OPT}"
```

All incoming `X-ForgeRock-TransactionId` headers are trusted, and monitoring or reporting systems that consume the logs can allow requests to be correlated as they traverse multiple servers.

Safelist audit event fields for the logs

To prevent logging of sensitive data for an audit event, the Common Audit Framework uses a safelist to specify which audit event fields appear in the logs.

By default, only safelisted audit event fields are included in the logs. You can find information about how to include non-safelisted audit event fields or exclude safelisted audit event fields in [Include or exclude audit event fields in logs](#).

Audit event fields use JSON pointer notation, and are taken from the JSON schema for the audit event content. The following event fields are safelisted:

- `/_id`
- `/timestamp`
- `/eventName`
- `/transactionId`
- `/trackingIds`
- `/userId`
- `/client`
- `/server`
- `/ig/exchangeId`
- `/ig/routeId`
- `/ig/routeName`
- `/http/request/secure`
- `/http/request/method`
- `/http/request/path`

- `/http/request/headers/accept`
- `/http/request/headers/accept-api-version`
- `/http/request/headers/content-type`
- `/http/request/headers/host`
- `/http/request/headers/user-agent`
- `/http/request/headers/x-forwarded-for`
- `/http/request/headers/x-forwarded-host`
- `/http/request/headers/x-forwarded-port`
- `/http/request/headers/x-forwarded-proto`
- `/http/request/headers/x-original-uri`
- `/http/request/headers/x-real-ip`
- `/http/request/headers/x-request-id`
- `/http/request/headers/x-requested-with`
- `/http/request/headers/x-scheme`
- `/request`
- `/response`

Include or exclude audit event fields in logs

The safelist is designed to prevent logging of sensitive data for audit events by specifying which audit event fields appear in the logs. You can add or remove messages from the logs as follows:

- To include audit event fields in logs that aren't safelisted, configure the `includeIf` property of AuditService.



Important

Before you include non-safelisted audit event fields in the logs, consider the impact on security. Including some headers, query parameters, or cookies in the logs could cause credentials or tokens to be logged, and allow anyone with access to the logs to impersonate the holder of these credentials or tokens.

- To exclude safelisted audit event fields from the logs, configure the `excludeIf` property of AuditService. You can find an example in [Exclude safelisted audit event fields from logs](#).

Exclude safelisted audit event fields from logs

Before you start, set up and test the example in [Recording access audit events in JSON](#). Note the audit event fields in the log file `access.audit.json`.

1. Replace `30-json.json` with the following route:

Linux

```
$HOME/.openig/config/routes/30-json-excludeif.json
```

Windows

```
%appdata%\OpenIG\config\routes\30-json-excludeif.json
```

```
{
  "name": "30-json-excludeif",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/json-audit-excludeif$')}",
  "heap": [
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "config": {
          "filterPolicies": {
            "field": {
              "excludeIf": [
                "/access/http/request/headers/host",
                "/access/http/request/path",
                "/access/server",
                "/access/response"
              ]
            }
          }
        },
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.json.JsonAuditEventHandler",
            "config": {
              "name": "json",
              "logDirectory": "/tmp/logs",
              "topics": [
                "access"
              ],
              "rotationRetentionCheckInterval": "1 minute",
              "buffering": {
                "maxSize": 100000,
                "writeInterval": "100 ms"
              }
            }
          }
        ]
      }
    }
  ],
  "auditService": "AuditService",
  "handler": "ReverseProxyHandler"
}
```

Source: [30-json-excludeif.json](#)

Notice that the AuditService is configured with an `excludeIf` property to exclude audit event fields from the logs.

2. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/json-audit-excludeif>.

The home page of the sample application is displayed and the file `/tmp/logs/access.audit.json` is updated:

```
{
  "_id": "830...-41",
  "timestamp": "2019-...540Z",
  "eventName": "OPENIG-HTTP-ACCESS",
  "transactionId": "830...-40",
  "client": {
    "ip": "0:0:0:0:0:0:1",
    "port": 51666
  },
  "http": {
    "request": {
      "secure": false,
      "method": "GET",
      "headers": {
        "accept": ["text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8"],
        "user-agent": ["Mozilla/5.0 ... Firefox/66.0"]
      }
    }
  },
  "ig": {
    "exchangeId": "b3f...-56",
    "routeId": "30-json-excludeif",
    "routeName": "30-json-excludeif"
  }
}
```

3. Compare the audit event fields in `access.audit.json` with those produced in [Recording access audit events in JSON](#), and note that the audit event fields specified by the `excludeIf` property no longer appear in the logs.

Record user ID in audit events

The following sections provide examples of how to capture the AM user ID in audit logs.

Sample scripts are available in the `openig-samples.jar` file, to capture the user ID after SSO, CDSSO, OpenID, or SAML authentication. The scripts inject the user ID into the RequestAuditContext so that it is available when the audit event is written.

Using the notes in the sample scripts, adapt the script for your deployment. For example, configure which `user_info` field to capture in the audit event.

The audit service in these examples use a `JsonStdoutAuditEventHandler`, which writes audit events to standard output, but can be any other audit service.

Record user ID in audit logs after SSO authentication

Before you start, set up and test the example in [Cross-domain single sign-on for PingAM](#).

1. Add the following script to PingGateway:

Linux

```
$HOME/.openig/scripts/groovy/InjectUserIdSso.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\InjectUserIdSso.groovy
```

```

package scripts.groovy

import org.forgerock.openig.openam.SsoTokenContext
import org.forgerock.services.context.RequestAuditContext

/**
 * Sample ScriptableFilter implementation to capture the user id from the session
 * and inject it into the RequestAuditContext for later use when the audit event
 * is written.
 *
 * This ScriptableFilter should be added in the filter chain at whatever point the
 * desired user id is available - e.g. on the session after SS0.
 *
 * "handler": {
 *   "type": "Chain",
 *   "config": {
 *     "filters": [ {
 *       "name": "SingleSignOnFilter-1",
 *       "type": "SingleSignOnFilter",
 *       "config": {
 *         "amService": "AmService-1"
 *       }
 *     }, {
 *       "type": "ScriptableFilter",
 *       "config": {
 *         "file": "InjectUserIdSso.groovy",
 *         "type": "application/x-groovy"
 *       }
 *     }
 *   ],
 *   "handler": "ReverseProxyHandler",
 * }
 *
 * When using the SS0/ CDSSO flow then the SsoTokenContext is guaranteed to exist and
 * be populated if there was no error. The RequestAuditContext is also guaranteed to
 * be available. Note also that if the SessionInfoFilter is present in the route then
 * a SessionInfoContext would be available in the context chain and could be queried
 * for user info.
 *
 * Implementors may decide which user id field to capture in the audit event:
 * - The sessionInfo universalId - 'universalId' - is always available as
 *   provided by AM and resembles -
 *   e.g. "id=bonnie,ou=user,o=myrealm,ou=services,dc=openam,dc=forgerock,dc=org".
 * - The sessionInfo username - mapped to 'username') resembles - e.g. "bonnie".
 *   Field 'username' should be preferred to 'uid', which also points to 'username'.
 *
 * Additional error handling may be required.
 *
 * @see RequestAuditContext
 * @see SsoTokenContext
 * @see org.forgerock.openig.openam.SessionInfoContext
 */

def requestAuditContext = context.asContext(RequestAuditContext.class)
def ssoTokenContext = context.asContext(SsoTokenContext.class)

```

```
// The sessionInfo 'universalId' is always available, though 'username' may be unknown
requestAuditContext.setUserId(ssoTokenContext.universalId)

// Propagate the request to the next filter/ handler in the chain
next.handle(context, request)
```

Source: [InjectUserIdSso.groovy](#)

The script captures the user ID after SSO or CDSSO authentication, and injects it into the RequestAuditContext so that it is available when the audit event is written.

2. Replace `sso.json` with the following route:

Linux

```
$HOME/.openig/config/routes/audit-sso.json
```

Windows

```
%appdata%\OpenIG\config\routes\audit-sso.json
```

```

{
  "name": "audit-sso",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/audit-sso$')}",
  "heap": [
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.json.stdout.JsonStdoutAuditEventHandler",
            "config": {
              "name": "jsonstdout",
              "elasticsearchCompatible": false,
              "topics": [
                "access"
              ]
            }
          }
        ],
        "config": {}
      }
    },
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "auditService": "AuditService",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "SingleSignOnFilter-1",
          "type": "SingleSignOnFilter",
          "config": {
            "amService": "AmService-1"
          }
        },
        {
          "type": "ScriptableFilter",
          "config": {
            "file": "InjectUserIdSso.groovy",
            "type": "application/x-groovy"
          }
        }
      ]
    }
  }
}

```

```
    ],  
    "handler": "ReverseProxyHandler"  
  }  
}  
}
```

Source: [audit-sso.json](#)

Notice the following features of the route compared to `sso.json`:

- The route matches requests to `/home/audit-sso`.
- An audit service is included to publish access log messages to standard output.
- The chain includes a scriptable filter that refers to `InjectUserIdSso.groovy`.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to <https://ig.example.com:8443/home/audit-sso>. The `SingleSignOnFilter` redirects the request to AM for authentication.
2. Log in to AM as user `demo`, password `Ch4ng31t`, and then allow the application to access user information.

The profile page of the sample application is displayed. The script captures the user ID from the session, and the audit service includes it with the audit event.

3. Search the standard output for a message like this, containing the user ID:

```
{
  "_id": "23a...-23",
  "timestamp": "...",
  "eventName": "OPENIG-HTTP-ACCESS",
  "transactionId": "23a...-22",
  "userId": "id=demo,ou=user,dc=openam,dc=forgerock,dc=org",
  "client": {
    "ip": "0:0:0:0:0:0:1",
    "port": 57843
  },
  "server": {
    "ip": "0:0:0:0:0:0:1",
    "port": 8080
  },
  "http": {
    "request": {
      "secure": false,
      "method": "GET",
      "path": "http://ig.example.com/home/audit-sso",
      "headers": {
        "accept": ["text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,/;q=0.8"],
        "host": ["ig.example.com:8080"],
        "user-agent": [...]
      }
    }
  },
  "response": {
    "status": "SUCCESSFUL",
    "statusCode": "200",
    "elapsedTime": 276,
    "elapsedTimeUnits": "MILLISECONDS"
  },
  "ig": {
    "exchangeId": "1dc...-26",
    "routeId": "audit-sso",
    "routeName": "audit-sso"
  },
  "source": "audit",
  "topic": "access",
  "level": "INFO"
}
```

Record user ID in audit logs after OpenID connect authentication

1. Set up and test the example in [AM as OIDC provider](#).
2. Make sure the token signature algorithm in the `oidc_client` profile uses HMAC with the client password as the symmetric key:
 1. In the AM admin UI, select **Applications > OAuth 2.0 > Clients > oidc_client**.
 2. Under **Signing and Encryption**, set **ID Token Signing Algorithm** to `HS256` and click **Save Changes**.
3. Set up the script:
 1. Add the following example script to PingGateway:

Linux

```
$HOME/.openig/scripts/groovy/InjectUserIdOpenId.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\InjectUserIdOpenId.groovy
```



```

package scripts.groovy

import org.forgerock.services.context.AttributesContext
import org.forgerock.services.context.RequestAuditContext

/**
 * Sample script implementation supporting user id injection in an OpenId scenario.
 * This sample captures the user id and injects it into the RequestAuditContext for
 * later use when the audit event is written.
 *
 * This ScriptableFilter should be added in the filter chain at whatever point the
 * desired user id is available - e.g. after OpenId client authentication (in the
 * OAuth2 authentication filter chain) - as follows:
 *
 * "handler" : {
 *   "type" : "Chain",
 *   "config" : {
 *     "filters" : [ {
 *       "type" : "OAuth2ClientFilter",
 *       "config" : {
 *         ...
 *         "target" : "${attributes.target}",
 *         "registrations" : [ "ClientRegistrationWithOpenIdScope" ],
 *       }
 *     }, {
 *       "type" : "ScriptableFilter",
 *       "config" : {
 *         "file" : "InjectUserIdOpenId.groovy",
 *         "type": "application/x-groovy"
 *       }
 *     } ],
 *     "handler" : "display-user-info-groovy-handler"
 *   }
 * }
 *
 * The ClientRegistration associated with the above OAuth2ClientFilter config will
 * require the 'openid' scope. The OAuth2SessionContext is guaranteed to exist and
 * be populated on successful authentication. The userinfo will then be populated
 * according to the OAuth2ClientFilter OpenId 'target' configuration (e.g. in this
 * sample, on the AttributesContext). The 'target' referenced will be populated
 * with a 'user_info' JSON value containing the userinfo. It should be noted that
 * the OAuth2ClientFilter 'target' config is a config-time expression, and cannot
 * be used in a ScriptableFilter to read runtime data. The RequestAuditContext is
 * also guaranteed to be available.
 *
 * Implementors may decide which 'user_info' field to capture in the audit event:
 * - The userinfo 'sub' field is the user's "complex" ID marked with a type - e.g.
 *   "(usr!bonnie)".
 * - The userinfo 'subName' field is the user's username (or resource name) - e.g.
 *   "bonnie".
 * - To capture the universalId (consistent with the session info universalId),
 *   it is necessary to configure AM to provide it as a claim in the id-token. To
 *   do this, edit the OIDC Claims Script to include the following line just prior
 *   to the UserInfoClaims creation:
 *     computedClaims["universalId"] = identity.universalId
 * - This will include 'universalId' in the userinfo which we can use with audit
 *   e.g. "id=bonnie,ou=user,o=myrealm,ou=services,dc=openam,dc=forgerock,dc=org"
 *
 * Additional error handling may be required.
 *

```

```

* @see RequestAuditContext
* @see AttributesContext
*/

def requestAuditContext = context.asContext(RequestAuditContext.class)
def attributesContext = context.asContext(AttributesContext.class)

// The OAuth2ClientFilter captures userinfo based on its 'target' configuration.
// In this sample 'target' is configured as the AttributesContext with key "target".
// We can query this for 'user_info' values: 'sub', 'subName' or anything else
// made available via the OIDC Claims Script (see above).
def oauth2UserInfo = attributesContext.getAttributes().get("target")
requestAuditContext.setUserId(oauth2UserInfo.get("user_info").get("sub"))

// Propagate the request to the next filter/ handler in the chain
next.handle(context, request)

```

Source: [InjectUserIdOpenId.groovy](#)

The script captures the user ID from the AuthorizationCodeOAuth2ClientFilter `target` object, by default at `{attributes.openid}`, and injects it into the RequestAuditContext so that it is available when the audit event is written.

2. Edit the script to get the attributes from the `openid` target:

Replace `attributesContext.getAttributes().get("target")`
with `attributesContext.getAttributes().get("openid")`.

4. Replace `07-openid.json` with the following route:

Linux

```
$HOME/.openig/config/routes/audit-oidc.json
```

Windows

```
%appdata%\OpenIG\config\routes\audit-oidc.json
```

```

{
  "name": "audit-oidc",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/id_token')}",
  "heap": [
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.json.stdout.JsonStdoutAuditEventHandler",
            "config": {
              "name": "jsonstdout",
              "elasticsearchCompatible": false,
              "topics": [
                "access"
              ]
            }
          ]
        ],
        "config": {}
      }
    },
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AuthenticatedRegistrationHandler-1",
      "type": "Chain",
      "config": {
        "filters": [
          {
            "name": "ClientSecretBasicAuthenticationFilter-1",
            "type": "ClientSecretBasicAuthenticationFilter",
            "config": {
              "clientId": "oidc_client",
              "clientSecretId": "oidc.secret.id",
              "secretsProvider": "SystemAndEnvSecretStore-1"
            }
          ]
        ],
        "handler": "ForgeRockClientHandler"
      }
    }
  ],
  "auditService": "AuditService",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "AuthorizationCode0Auth2ClientFilter-1",
          "type": "AuthorizationCode0Auth2ClientFilter",
          "config": {
            "clientEndpoint": "/home/id_token",
            "failureHandler": {
              "type": "StaticResponseHandler",
              "config": {

```

```

        "status": 500,
        "headers": {
          "Content-Type": [
            "text/plain"
          ]
        },
        "entity": "Error in OAuth 2.0 setup."
      }
    },
    "registrations": [
      {
        "name": "oidc-user-info-client",
        "type": "ClientRegistration",
        "config": {
          "clientId": "oidc_client",
          "issuer": {
            "name": "Issuer",
            "type": "Issuer",
            "config": {
              "wellKnownEndpoint": "http://am.example.com:8088/openam/oauth2/.well-known/openid-
configuration"
            }
          },
          "scopes": [
            "openid",
            "profile",
            "email"
          ],
          "authenticatedRegistrationHandler": "AuthenticatedRegistrationHandler-1",
          "clientSecretIdUsage": "ID_TOKEN_VALIDATION_ONLY",
          "clientSecretId": "oidc.secret.id",
          "secretsProvider": "SystemAndEnvSecretStore-1"
        }
      }
    ],
    "requireHttps": false,
    "cacheExpiration": "disabled"
  }
},
{
  "type": "ScriptableFilter",
  "config": {
    "file": "InjectUserIdOpenId.groovy",
    "type": "application/x-groovy"
  }
}
],
"handler": "ReverseProxyHandler"
}
}
}

```

Source: [audit-oidc.json](#)

Notice the following features of the route compared to `07-openid.json`:

- An audit service is included to publish access log messages to standard output.
- The chain includes a scriptable filter that refers to `InjectUserIdOpenId.groovy`.

5. Test the setup:

1. In your browser's privacy or incognito mode, go to https://ig.example.com:8443/home/id_token. The AM login page is displayed.
2. Log in to AM as user **demo**, password **Ch4ng31t**, and then allow the application to access user information.

The home page of the sample application is displayed. The script captures the user ID from the **openid** target, and the audit service includes it with the audit event.

3. Search the standard output for a message like this, containing the user ID:

```
{
  "_id": "<uuid>",
  "timestamp": "<timestamp>",
  "eventName": "OPENIG-HTTP-ACCESS",
  "transactionId": "<uuid>",
  "userId": "(usr!demo)",
  "client": {
    "ip": "127.0.0.1",
    "port": 62056
  },
  "server": {
    "ip": "127.0.0.1",
    "port": 8443
  },
  "http": {
    "request": {
      "secure": true,
      "method": "GET",
      "path": "https://ig.example.com:8443/home/id_token",
      "headers": {
        "accept": [
          "...",
        ],
        "user-agent": [
          "...",
        ]
      }
    },
    "response": {
      "status": "SUCCESSFUL",
      "statusCode": "200",
      "elapsedTime": 29,
      "elapsedTimeUnits": "MILLISECONDS"
    },
    "ig": {
      "exchangeId": "<uuid>",
      "routeId": "openid",
      "routeName": "audit-oidc"
    },
    "source": "audit",
    "topic": "access",
    "level": "INFO"
  }
}
```

Record user ID in audit logs after SAML authentication



Important

This example uses the deprecated `SamlFederationHandler`. The `SamlFederationHandler` is replaced by the `SamlFederationFilter` and will be removed in a future release.

Before you start, set up and test the `SamlFederationHandler` example under [SAML v2.0 and PingGateway](#).

1. Set up the script:

1. Add the following example script to PingGateway:

Linux

```
$HOME/.openig/scripts/groovy/InjectUserIdSaml.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\InjectUserIdSaml.groovy
```

```

package scripts.groovy

import org.forgerock.http.session.SessionContext
import org.forgerock.services.context.RequestAuditContext

/**
 * Sample ScriptableFilter implementation to capture the user id obtained from a
 * SAML assertion. The IG SamlFederationHandler captures this and locates it on
 * the SessionContext with the key as the configured SAML 2 user id key. We then
 * take this and inject it into the RequestAuditContext for later use when the
 * audit event is written.
 *
 * This ScriptableFilter should be added in the filter chain together with the
 * SamlFederationHandler, as follows. Note that the InjectUserIdSaml.groovy script
 * operates on the response, injecting the userId as captured by the handler.
 *
 * {
 *   "condition" : "${matches(request.uri.path, '^/api/saml')}",
 *   "handler" : {
 *     "type" : "Chain",
 *     "config" : {
 *       "filters" : [ {
 *         "type" : "ScriptableFilter",
 *         "config" : {
 *           "file" : "InjectUserIdSaml.groovy",
 *           "type": "application/x-groovy"
 *         }
 *       } ],
 *     "handler" : {
 *       "name" : "saml_handler_SPOne",
 *       "type" : "SamlFederationHandler",
 *       "config" : {
 *         "assertionMapping" : {
 *           "SPOne_userName" : "uid",
 *           "SPOne_password" : "mail"
 *         },
 *         "redirectURI" : "/api/home",
 *         "logoutURI" : "http://openig.example.com:8082/api/after_logout",
 *         "subjectMapping" : "SubjectName_SPOne",
 *         "authnContext" : "AuthnContext_SPOne",
 *         "sessionIndexMapping" : "SessionIndex_SPOne"
 *       }
 *     }
 *   }
 * }

* The SessionContext and RequestAuditContext are guaranteed to be available and the
* SessionContext will have been populated with userinfo on successful authentication.
*
* Implementors may decide which user id field to capture in the audit event:
* - This should be based on SAML attribute mappings and/ or the subject mapping (if
*   transient names are not used).
* - Other attributes are available, such as 'uid' and 'userName', though it must be
*   noted that there is an expectation that the IDP makes available the user id.
* - In this sample, 'SPOne_userName' maps to the 'uid'.
*
* Additional error handling may be required.
*
* @see RequestAuditContext

```

```

* @see SessionContext
*/

// Propagate the request to the next filter/ handler in the chain
next.handle(context, request)
    .then({ response ->
        def requestAuditContext = context.asContext(RequestAuditContext.class)
        def sessionContext = context.asContext(SessionContext.class)

        // Inject the user id as captured by the SamlFederationHandler
        requestAuditContext.setUserId(sessionContext.getSession().get("SPOne_userName"))
        return response
    })

```

Source: [InjectUserIdSaml.groovy](#)

The script captures the user ID from the SessionContext subject or attribute mappings, provided by the SamlFederationHandler from the inbound assertions. It injects the user ID into the RequestAuditContext so that it is available when the audit event is written.

2. Replace `get("SPOne_userName"))` with `get("username"))`.

The script captures the user ID from the assertionMapping `username`, which is mapped in the route to `cn`.

2. Replace `saml.json` with the following route:

Linux

```
$HOME/.openig/config/routes/audit-saml.json
```

Windows

```
%appdata%\OpenIG\config\routes\audit-saml.json
```



```

{
  "name": "audit-saml",
  "condition": "${find(request.uri.path, '^/saml')}",
  "heap": [
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.json.stdout.JsonStdoutAuditEventHandler",
            "config": {
              "name": "jsonstdout",
              "elasticsearchCompatible": false,
              "topics": [
                "access"
              ]
            }
          }
        ],
        "config": {}
      }
    }
  ],
  "auditService": "AuditService",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "ScriptableFilter",
          "config": {
            "file": "InjectUserIdSaml.groovy",
            "type": "application/x-groovy"
          }
        }
      ],
      "handler": {
        "type": "SamlFederationHandler",
        "config": {
          "useOriginalUri": true,
          "assertionMapping": {
            "username": "cn",
            "password": "sn"
          },
          "subjectMapping": "sp-subject-name",
          "redirectURI": "/home/federate"
        }
      }
    }
  }
}

```

Source: [audit-saml.json](#)

Notice the following features of the route compared to `saml.json`:

- An audit service is included to publish access log messages to standard output.

- The main Handler is a Chain that includes a scriptable filter to refer to `InjectUserIdSaml.groovy`.
- The script uses the assertionMapping `username` to capture the user ID.

3. Test the setup:

1. In your browser's privacy or incognito mode, go to [IdP-initiated SSO](#).
2. Log in to AM with username `demo` and password `Ch4ng31t`.

PingGateway returns the response page showing that the demo user has logged in. The script captures the user ID from the session, and the audit service includes it with the audit event.

3. Search the standard output for a message like this, containing the user ID:

```
{
  "_id": "82f...-14",
  "timestamp": "2021-...",
  "eventName": "OPENIG-HTTP-ACCESS",
  "transactionId": "82f...-13",
  "userId": "demo",
  "client": {
    "ip": "0:0:0:0:0:0:1",
    "port": 60655
  },
  "server": {
    "ip": "0:0:0:0:0:0:1",
    "port": 8080
  },
  "http": {
    "request": {
      "secure": false,
      "method": "POST",
      "path": "http://sp.example.com:8080/saml/fedletapplication/metaAlias/sp",
      "headers": {
        "accept": ["text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,/;q=0.8"],
        "content-type": ["application/x-www-form-urlencoded"],
        "host": ["sp.example.com:8080"],
        "user-agent": [...]
      }
    }
  },
  "response": {
    "status": "SUCCESSFUL",
    "statusCode": "302",
    "elapsedTime": 2112,
    "elapsedTimeUnits": "MILLISECONDS"
  },
  "ig": {
    "exchangeId": "1dc...-26",
    "routeId": "audit-saml",
    "routeName": "audit-saml"
  },
  "source": "audit",
  "topic": "access",
  "level": "INFO"
}
```

Monitoring services for PingGateway

This page describes how to set up and maintain monitoring in your deployment.

Health check endpoints

PingGateway implements health check endpoints for use as Kubernetes-style [Liveness, Readiness, and Startup Probes](#).

Use these endpoints to check PingGateway health:

- The liveness endpoint at `http://ig.example.com:8085/health/liveness` by default. (Interface stability: [Evolving](#).)

An `HTTP 200 OK` response means PingGateway is alive and operating normally.

An `HTTP 503 Service Unavailable` response means PingGateway isn't operating normally. Consider restarting PingGateway.

- The readiness endpoint at `http://ig.example.com:8085/health/readiness` by default. (Interface stability: [Evolving](#).)

An `HTTP 200 OK` response means PingGateway is ready to accept requests.

An `HTTP 503 Service Unavailable` response means PingGateway isn't ready to accept requests.

- The startup endpoint at `http://ig.example.com:8085/health/startup` by default.

An `HTTP 200 OK` response means PingGateway is running.

An `HTTP 503 Service Unavailable` response means PingGateway hasn't finished starting or is shutting down.

Push to an OpenTelemetry service

PingGateway can push traces to an [OpenTelemetry](#) Protocol (OTLP) endpoint over HTTP. When you use it with other applications with OpenTelemetry support, the service helps you analyze the flows through PingGateway and the other applications to understand performance and system behavior.

Important

This feature has [Evolving](#) interface stability. It is subject to change without notice, even in a minor or maintenance release.

OpenTelemetry support is disabled by default. Enable it with the `openTelemetry` setting in `admin.json`. Make sure the OTLP exporter targets the endpoint for the OpenTelemetry service in your deployment. The following example targets the default endpoint:

```

{
  "openTelemetry": {
    "tracing": {
      "enabled": true,
      "exporter": {
        "type": "otlp",
        "config": {
          "endpoint": "http://localhost:4318/v1/traces"
        }
      }
    }
  }
}

```

When tracing is enabled, traces always span requests entering PingGateway and any requests started by PingGateway; for example, proxied requests to the sample application. The span ends when PingGateway receives or returns a response or when an error arises during processing. The span captures the response status code. If a `ClientHandler` or `ReverseProxyHandler` has the retry feature enabled, PingGateway records the number of retries as a `http.request.resend_count` span attribute in the trace. If the original request is a websocket upgrade, PingGateway sets the `ig.websocket.upgrade.request` span attribute to `true` (default: `false`).

Trace sampling is `parentBasedAlwaysOn` by default, meaning PingGateway always samples if the parent span was sampled. Adjust this in the configuration settings as required for your deployment and traffic.

Use the `"tracing": true` decoration on other configuration objects or in `"globalDecorators"` to activate additional tracing points.

Access the monitoring endpoints

All ForgeRock products automatically expose a monitoring endpoint to expose metrics in a standard Prometheus format, and as a JSON format monitoring resource.

In PingGateway, metrics are available for each router, subrouter, and route in the configuration. When a `TimerDecorator` is configured, timer metrics are also available.

Learn more about PingGateway monitoring endpoints and available metrics in [PingGateway monitoring reference](#).

Monitor at the Prometheus Scrape Endpoint

Note

Prometheus metric names are deprecated and expected to be replaced with names ending in `_total`. The information provided by the metric is not deprecated. Other Prometheus metrics aren't affected.

All ForgeRock products automatically expose a monitoring endpoint where Prometheus can scrape metrics, in a standard Prometheus format.

When PingGateway is set up as described in the [Getting started with PingGateway](#), the Prometheus Scrape Endpoint is available by default at <http://ig.example.com:8085/metrics/prometheus/0.0.4>.

By default, no special setup or configuration is required to access metrics at these endpoints. The following example queries the Prometheus Scrape Endpoint for a route.

Tools such as Grafana are available to create customized charts and graphs based on the information collected by Prometheus. You can find more information on installing and running Grafana on [the Grafana website](#).

1. Set up PingGateway:

1. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/myroute1.json
```

Windows

```
%appdata%\OpenIG\config\routes\myroute1.json
```

```
{
  "name": "myroute1",
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/plain; charset=UTF-8" ]
      },
      "entity": "Hello world, from myroute1!"
    }
  },
  "condition": "${find(request.uri.path, '^/myroute1')}"
}
```

Source: [myroute1.json](#)

The route contains a StaticResponseHandler to display a simple message.

2. Test the setup:

1. Access the route a few times, on <https://ig.example.com:8443/myroute1>.

2. Query the Prometheus Scrape Endpoint:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
http://ig.example.com:8085/metrics/prometheus/0.0.4
```

Metrics for `myroute1` and `_router` are displayed.

Vert.x monitoring is enabled by default to provide additional metrics for HTTP, TCP, and the internal component pool. The metrics provide low-level information about requests and responses, such as the number of bytes, duration, and the number of concurrent requests.

Monitor the Common REST Monitoring Endpoint (deprecated)

All ForgeRock products expose a monitoring endpoint where metrics are exposed as a JSON format monitoring resource.

When PingGateway is set up as described in [Getting started with PingGateway](#), the Common REST Monitoring Endpoint is available at http://ig.example.com:8085/metrics/api?_prettyPrint=true&_sortKeys=_id&_queryFilter=true [↗](#).

By default, no special setup or configuration is required to access metrics at this endpoint. The following example queries the Common REST Monitoring Endpoint for a route, and restricts the query to specific metrics only.

Before you start, prepare PingGateway as described in the [Getting started with PingGateway](#).

1. Set up PingGateway and some example routes, as described in the first few steps of [Monitor the Prometheus Scrape Endpoint](#).
2. Query the Common REST Monitoring Endpoint:

```
$ curl "http://ig.example.com:8085/metrics/api?_prettyPrint=true&_sortKeys=_id&_queryFilter=true"
```

Metrics for `myroute1` and `_router` are displayed:

```

{
  "result" : [ {
    "_id" : "gateway._router.deployed-routes",
    "value" : 1.0,
    "_type" : "gauge"
  }, {
    "_id" : "gateway._router.route.default.request",
    "count" : 204,
    "_type" : "counter"
  }, {
    "_id" : "gateway._router.route.default.request.active",
    "value" : 0.0,
    "_type" : "gauge"
  }, {
    "...": "...",
    "_id" : "gateway._router.route.myroute1.response.status.unknown",
    "count" : 0,
    "_type" : "counter"
  }, {
    "_id" : "gateway._router.route.myroute1.response.time",
    "count" : 204,
    "max" : 0.420135,
    "mean" : 0.08624678327176545,
    "min" : 0.045079999999999995,
    "p50" : 0.070241,
    "p75" : 0.096049,
    "p95" : 0.178534,
    "p98" : 0.227217,
    "p99" : 0.242554,
    "p999" : 0.420135,
    "stddev" : 0.046611762381930474,
    "m15_rate" : 0.2004491450567003,
    "m1_rate" : 2.8726563452698075,
    "m5_rate" : 0.5974045160056258,
    "mean_rate" : 0.010877725092634833,
    "duration_units" : "milliseconds",
    "rate_units" : "calls/second",
    "total" : 17.721825,
    "_type" : "timer"
  } ],
  "resultCount" : 11,
  "pagedResultsCookie" : null,
  "totalPagedResultsPolicy" : "EXACT",
  "totalPagedResults" : 11,
  "remainingPagedResults" : -1
}

```

Vert.x monitoring is enabled by default to provide additional metrics for HTTP, TCP, and the internal component pool. The metrics provide low-level information about requests and responses, such as the number of bytes, duration, the number of concurrent requests, and so on.

3. Change the query to access metrics only for `myroute1` : [http://ig.example.com:8085/metrics/api?_prettyPrint=true&_sortKeys=_id&_queryFilter=_id+sw+\"gateway._router.route.myroute1\"](http://ig.example.com:8085/metrics/api?_prettyPrint=true&_sortKeys=_id&_queryFilter=_id+sw+\).

Note that metric for the router, `"_id" : "gateway._router.deployed-routes"`, is no longer displayed.

Monitor Vert.x metrics

Note

Vert.x metric names are deprecated and expected to be replaced with names ending in `_total`. The information provided by the metric is not deprecated. Other Prometheus metrics aren't affected.

Vert.x monitoring is enabled by default to provide metrics for HTTP, TCP, and the internal component pool. The metrics provide low-level information about requests and responses, such as the number of bytes, duration, the number of concurrent requests, and so on.

To disable Vert.x monitoring, add the following settings to `admin.json` and restart PingGateway:

```
{
  "vertx": {
    "metricsEnabled": false
  }
}
```

Protect monitoring endpoints

By default, no special credentials or privileges are required for read-access to the Prometheus Scrape Endpoint and Common REST Monitoring Endpoint.

To override this behavior, define an `"metricsProtectionFilter"` in `admin.json`. The following procedure gives an example of how to manage access to the monitoring endpoints.

1. Set up the procedure in [Monitor at the Prometheus Scrape Endpoint](#), query the Prometheus Scrape Endpoint, and note that metrics for `myroute1` and `_router` are displayed:

```
$ curl -v "http://ig.example.com:8085/metrics/prometheus/0.0.4"
```

2. Add the following script to the PingGateway configuration:

Linux

```
$HOME/.openig/scripts/groovy/BasicAuthResourceServerFilter.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\BasicAuthResourceServerFilter.groovy
```



```

/*
 * This script is a simple implementation of HTTP basic access authentication on
 * server side.
 * It expects the following arguments:
 * - realm: the realm to display when the user agent prompts for
 *   username and password if none were provided.
 * - username: the expected username
 * - passwordSecretId: the secretId to find the password
 * - secretsProvider: the SecretsProvider to query for the password
 */
import static org.forgerock.util.promise.Promises.newResultPromise;

import java.nio.charset.Charset;
import org.forgerock.util.encode.Base64;
import org.forgerock.secrets.Purpose;
import org.forgerock.secrets.GenericSecret;

String authorizationHeader = request.getHeaders().getFirst("Authorization");
if (authorizationHeader == null) {
    // No credentials provided, return 401 Unauthorized
    Response response = new Response(Status.UNAUTHORIZED);
    response.getHeaders().put("WWW-Authenticate", "Basic realm=\"" + realm + "\"");
    return newResultPromise(response);
}

return secretsProvider.getNamed(Purpose.PASSWORD, passwordSecretId)
    .thenAsync(password -> {
        // Build basic authentication string -> username:password
        StringBuilder basicAuthString = new StringBuilder(username).append(":");
        password.revealAsUtf8{ p -> basicAuthString.append(new String(p).trim()) };
        String expectedAuthorization = "Basic " +
Base64.encode(basicAuthString.toString().getBytes(Charset.defaultCharset()));
        // Incorrect credentials provided, return 403 forbidden
        if (!expectedAuthorization.equals(authorizationHeader)) {
            return newResultPromise(new Response(Status.FORBIDDEN));
        }
        // Correct credentials provided, continue.
        return next.handle(context, request);
    },
        noSuchSecretException -> { throw new RuntimeException(noSuchSecretException); });

```

Source: [BasicAuthResourceServerFilter.groovy](#)

The script is a simple implementation of the HTTP basic access authentication scheme. Learn more about scripting filters and handlers in [Extending PingGateway](#).

3. Add a `"metricsProtectionFilter"` setting in `admin.json`:

```
{
  ...,
  "heap": [
    {
      "name": "ClientHandler",
      "type": "ClientHandler"
    },
    {
      "name": "mySecretsProvider",
      "type": "Base64EncodedSecretStore",
      "config": {
        "secrets": {
          "password.secret.id": "cGFzc3dvcmQ="
        }
      }
    }
  ],
  "metricsProtectionFilter": {
    "type": "ScriptableFilter",
    "config": {
      "type": "application/x-groovy",
      "file": "BasicAuthResourceServerFilter.groovy",
      "args": {
        "realm": "/",
        "username": "myUsername",
        "passwordSecretId": "password.secret.id",
        "secretsProvider": "${heap['mySecretsProvider']}"
      }
    }
  },
  ...
}
```

Source: [admin_monitor.json](#)

Notice the following features of the configuration:

- The filter uses the script to protect the monitoring endpoint.
- The filter requires the username `myUsername` and a password provided by the SecretsProvider in the heap.

4. Restart PingGateway.

5. Query the Prometheus Scrape Endpoint without providing credentials, and note that an HTTP 401 Unauthorized is returned:

```
$ curl -v "http://ig.example.com:8085/metrics/prometheus/0.0.4"
```

6. Query the Prometheus Scrape Endpoint by providing correct credentials, and note that metrics are displayed:

```
$ curl -v "http://ig.example.com:8085/metrics/prometheus/0.0.4" -u myUsername:password
```

7. Query the Prometheus Scrape Endpoint by providing incorrect credentials, and note that an HTTP 403 Forbidden is returned:

```
$ curl -v "http://ig.example.com:8085/metrics/prometheus/0.0.4" -u myUsername:wrong-password
```

Managing PingGateway sessions

Learn about PingGateway sessions in [PingGateway sessions](#).

Change PingGateway session configurations using the "session" in the [AdminHttpApplication](#) (`admin.json`) for administrative requests and the [GatewayHttpApplication](#) (`config.json`) or individual [Route](#) for other requests:

- Change the default stateful session settings by configuring an [InMemorySessionManager](#).
- Switch to stateless sessions by configuring a [JwtSessionManager](#).

Managing PingGateway logs

Log messages in PingGateway and third-party dependencies are recorded using the Logback implementation of the Simple Logging Facade for Java (SLF4J) API. The following log levels are supported:

- TRACE
- DEBUG
- INFO
- WARN
- ERROR
- ALL
- OFF

You can find a full description of the options for logging in [the Logback website](#).

Default logging behavior

By default, log messages are recorded with the following configuration:

- When PingGateway starts, log messages for PingGateway and third-party dependencies, such as the ForgeRock Common Audit framework, are displayed on the console and written to `$HOME/.openig/logs/route-system.log`, where `$HOME/.openig` is the instance directory.
- When a capture point for the default CaptureDecorator is defined in a route, for example, when "capture: "all" is set as a top-level attribute of the JSON, log messages for requests and responses passing through the route are written to a log file in `$HOME/.openig/logs`.

When no capture point is defined in a route, only exceptions thrown during request or response processing are logged.

You can find more information in [Capturing log messages for routes](#) and [CaptureDecorator](#).

- By default, log messages with the level **INFO** or higher are recorded, with the titles and the top line of the stack trace. Messages on the console are highlighted with a color related to their log level.

The content and format of logs in PingGateway is defined by the reference `logback.xml` delivered with PingGateway. This file defines the following configuration items for logs:

- A root logger to set the overall log level, and to write all log messages to the **SIFT** and **STDOUT** appenders.
- A **STDOUT** appender to define the format of log messages on the console.
- A **SIFT** appender to separate log messages according to the key `routeId`, to define when log files are rolled, and to define the format of log messages in the file.
- An exception logger, called `LogAttachedExceptionFilter`, to write log messages for exceptions attached to responses.

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration>

  <!--
    Prevent log flow attacks, by limiting repeated log messages.

    Configuration properties:
    * AllowedRepetitions (int): Threshold above which repeated messages are no longer logged.
    * CacheSize (int): When CacheSize is reached, remove the oldest entry.
  -->
  <!--<turboFilter class="ch.qos.logback.classic.turbo.DuplicateMessageFilter" />-->

  <!-- Allow configuration of JUL loggers within this file, without performance impact -->
  <contextListener class="ch.qos.logback.classic.jul.LevelChangePropagator" />

  <appender name="STDOUT" class="ch.qos.logback.core.ConsoleAppender">
    <withJansi>true</withJansi>
    <encoder>
      <pattern>%nopex[%thread] %highlight(%-5level) %boldWhite(%logger{35}) @%mdc{routeId:-system} -
%replace(%message){'([\r\n])(.)', '$1[CONTINUED]$2'}%n%highlight(%replace(%rootException{short}){'(^|[\r\n])(.)',
'$1[CONTINUED]$2'})</pattern>
    </encoder>
  </appender>

  <appender name="SIFT" class="ch.qos.logback.classic.sift.SiftingAppender">
    <discriminator>
      <key>routeId</key>
      <defaultValue>system</defaultValue>
    </discriminator>
    <sift>
      <!-- Create a separate log file for each <key> -->
      <appender name="FILE-${routeId}" class="ch.qos.logback.core.rolling.RollingFileAppender">
        <file>${instance.dir}/logs/route-${routeId}.log</file>

        <rollingPolicy class="ch.qos.logback.core.rolling.SizeAndTimeBasedRollingPolicy">
          <!-- Rotate files daily -->
          <fileNamePattern>${instance.dir}/logs/route-${routeId}-%d{yyyy-MM-dd}.i.log</fileNamePattern>

          <!-- each file should be at most 100MB, keep 30 days worth of history, but at most 3GB -->
          <maxFileSize>100MB</maxFileSize>
          <maxHistory>30</maxHistory>
          <totalSizeCap>3GB</totalSizeCap>
        </rollingPolicy>

        <encoder>
          <pattern>%nopex%date{"yyyy-MM-dd'T'HH:mm:ss,SSSXXX", UTC} | %-5level | %thread | %logger{20} |
@%mdc{routeId:-system} | %replace(%message%n%xException){'([\r\n])(.)', '$1[CONTINUED]$2'}</pattern>
        </encoder>
      </appender>
    </sift>
  </appender>

  <!-- Disable logs of exceptions attached to responses by defining 'level' to OFF -->
  <logger name="org.forgerock.openig.filter.LogAttachedExceptionFilter" level="INHERITED" />

  <root level="${ROOT_LOG_LEVEL:-INFO}">
    <appender-ref ref="SIFT" />
    <appender-ref ref="STDOUT" />
  </root>
</configuration>

```

Source: [logback.xml](#)

Using a custom Logback file

To change the logging behavior, create a new logback file at `$HOME/.openig/config/logback.xml`, and restart PingGateway. The custom Logback file overrides the default configuration.

To take into account edits to `logback.xml`, stop and restart PingGateway, or edit the `configuration` parameter to add a scan and an interval:

```
<configuration scan="true" scanPeriod="5 seconds">
```

The `logback.xml` file is scanned after both of the following criteria are met:

- The specified number of logging operations have occurred, where the default is 16.
- The `scanPeriod` has elapsed.

If the custom `logback.xml` contains errors, messages like these are displayed on the console but log messages aren't recorded:

```
14:38:59,667 |-ERROR in ch.qos.logback.core.joran.spi.Interpreter@20:72 ...  
14:38:59,690 |-ERROR in ch.qos.logback.core.joran.action.AppenderRefAction ...
```

Change the global log level

The global log level is set by default to `INFO` by the following line of the default `logback.xml`:

```
<root level="${ROOT_LOG_LEVEL:-INFO}">
```

The log level set in `logback.xml` supercedes the log level set by environment variables. When the global log level is not set in `logback.xml`, set the global log level.

- To persist the log level for all future PingGateway instances:
 - Add an environment variable in `$HOME/.openig/bin/env.sh`, where `$HOME/.openig` is the instance directory:

```
export ROOT_LOG_LEVEL=DEBUG
```

- Alternatively, add a system property in `$HOME/.openig/bin/env.sh`, where `$HOME/.openig` is the instance directory:

```
export JAVA_OPTS="-DROOT_LOG_LEVEL=DEBUG"
```

If both an environment variable and system property is set, the system property takes precedence.

- To persist the log level for PingGateway instances launched from the same shell, add an environment variable in the shell before you start PingGateway:

Linux

```
$ export ROOT_LOG_LEVEL=DEBUG  
$ /path/to/identity-gateway-2025.6.1/bin/start.sh $HOME/.openig
```

Windows

```
C:\set ROOT_LOG_LEVEL=DEBUG  
C:\path\to\identity-gateway-2025.6.1\bin\start.bat %appdata%\OpenIG
```

- To persist the log level for a single PingGateway instance:

Linux

```
$ export ROOT_LOG_LEVEL=DEBUG /path/to/identity-gateway-2025.6.1/bin/start.sh $HOME/.openig
```

Windows

```
C:\set ROOT_LOG_LEVEL=DEBUG  
C:\path\to\identity-gateway-2025.6.1\bin\start.bat %appdata%\OpenIG
```

Change the log level for different object types

To change the log level for a single object type without changing it for the rest of the configuration, edit `logback.xml` to add a logger defined by the fully qualified class name or package name of the object and set its log level.

The following line in `logback.xml` sets the ClientHandler log level to `ERROR`, but doesn't change the log level of other classes or packages:

```
<logger name="org.forgerock.openig.handler.ClientHandler" level="ERROR" />
```

To facilitate debugging, in `logback.xml` add loggers defined by the fully qualified package name or class name of the object. For example, add loggers for the following feature:

Feature	Logger
OAuth 2.0 client authentication: • AuthorizationCodeOAuth2ClientFilter • ClientCredentialsOAuth2ClientFilter • ResourceOwnerOAuth2ClientFilter	<code>org.forgerock.secrets.oauth2</code>
Expression resolution	<code>org.forgerock.openig.el</code> <code>org.forgerock.openig.resolver</code>
WebSocket notifications	<code>org.forgerock.openig.tools.notifications.ws</code>
Stateless session management	<code>org.forgerock.openig.jwt</code>
OAuth 2.0 and OpenID Connect and token resolution and validation	<code>org.forgerock.openig.filter.oauth2</code>
AM policies, SSO, CDSSO, and user profiles	<code>org.forgerock.openig.openam</code> <code>org.forgerock.openig.tools</code>
SAML	<code>org.forgerock.openig.handler.saml</code>
UMA	<code>org.forgerock.openig.uma</code>
WebSocket tunnelling	<code>org.forgerock.openig.websocket</code>
Secret resolution	<code>org.forgerock.secrets.jwkset</code> <code>org.forgerock.secrets.keystore</code> <code>org.forgerock.secrets.oauth2</code> <code>org.forgerock.secrets.propertyresolver</code> <code>org.forgerock.openig.secrets.Base64EncodedSecretStore</code>
AllowOnlyFilter	<code>org.forgerock.openig.filter.allow.AllowOnlyFilter.<filter_name></code>
Condition of a route	<code>org.forgerock.openig.handler.router.RouterHandler</code>
Header field size	<code>io.vertx.core.http.impl.HttpServerImpl</code>

Change the character set and format of log messages

By default, logs use the system default character set where PingGateway is running.



Tip

If your logs might contain characters that aren't in your system character set, edit `logback.xml` to change the encoder part of the SIFT appender.

The following lines add the date to log messages and change the character set:

```
<encoder>
  <pattern>%d{yyyyMMdd-HH:mm:ss} | %-5level | %thread | %logger{20} | %message%n%xException</pattern>
  <charset>UTF-8</charset>
</encoder>
```

Learn more about what information you can include in the logs and its format in [PatternLayoutEncoder](#) and [Layouts](#) in the Logback documentation.

Log in scripts

The [logger](#) object provides access to a unique SLF4J logger instance for scripts. Events are logged as defined in by a dedicated logger in `logback.xml` and are included in the logs with the name of with the scriptable object.

To log events for scripts:

- Add logger objects to the script to enable logging at different levels. For example, add some of the following logger objects:

```
logger.error("ERROR")
logger.warn("WARN")
logger.info("INFO")
logger.debug("DEBUG")
logger.trace("TRACE")
```

- Add a logger to `logback.xml` to reference the scriptable object and set the log level. The logger is defined by the type and name of the scriptable object that references the script, as follows:

- ScriptableFilter: `org.forgerock.openig.filter.ScriptableFilter.filter_name`
- ScriptableHandler: `org.forgerock.openig.handler.ScriptableHandler.handler_name`
- ScriptableThrottlingPolicy: `org.forgerock.openig.filter.throttling.ScriptableThrottlingPolicy.throttling_policy_name`
- ScriptableAccessTokenResolver: `org.forgerock.openig.filter.oauth2.ScriptableAccessTokenResolver.access_token_resolver_name`

For example, the following logger logs trace-level messages for a ScriptableFilter named `cors_filter`:

```
<logger name="org.forgerock.openig.filter.ScriptableFilter.cors_filter" level="TRACE" />
```

The resulting messages in the logs contain the name of the scriptable object:

```
14:54:38:307 | TRACE | http-nio-8080-exec-6 | o.f.o.f.S.cors_filter | TRACE
```

Log the BaseUriDecorator

During setup and configuration, it can be helpful to display log messages from the BaseUriDecorator. To record a log message each time a request URI is rebased, edit `logback.xml` to add a logger defined by the fully qualified class name of the BaseUriDecorator appended by the name of the baseURI decorator:

```
<logger name="org.forgerock.openig.decoration.baseuri.BaseUriDecorator.baseURI" level="TRACE" />
```

Each time a request URI is rebased, a log message similar to this is created:

```
12:27:40| TRACE | http-nio-8080-exec-3 | o.f.o.d.b.B.b.{Router}/handler| Rebasing request to http://app.example.com:8081
```

Stop exception logging

To stop recording log messages for exceptions, edit `logback.xml` to set the level to `OFF` :

```
<logger name="org.forgerock.openig.filter.LogAttachedExceptionFilter" level="OFF" />
```

Reduce logging when propagating disconnections

When using HTTP/2 and propagating disconnections from the user-agent to the protected application, edit `logback.xml` to change the log level for the `DefaultHttp2ConnectionDecoder` to `WARN` :

```
<logger name="io.netty.handler.codec.http2.DefaultHttp2ConnectionDecoder" level="WARN" />
```

At the level of `INFO` , the logging for this component is noisy when PingGateway propagates disconnections.

Capture the context or entity of messages for routes

To capture the context or entity of inbound and outbound messages for a route or for an individual handler or filter in the route, configure a `CaptureDecorator`. Captured information is written to SLF4J logs.

Important

During debugging, consider using a `CaptureDecorator` to capture the entity and context of requests and responses. However, increased logging consumes resources, such as disk space, and can cause performance issues. In production, reduce logging by disabling the `CaptureDecorator` properties `captureEntity` and `captureContext`, or setting `maxEntityLength`.

You can find more information about the decorator configuration in [CaptureDecorator](#).

Studio provides an easy way to capture messages while developing your configuration. The following image illustrates the capture points where you can log messages on a route:




Figure 1. Capturing log messages for routes

Capture messages on a route in Studio

1. In Studio, select **ROUTES**, and then select a route with the **≡** icon.
2. On the left side of the screen, select **Capture**, and then select capture options. You can capture the body and context of messages passing to and from the user agent, the protected application, and the Ping Identity Platform.
3. Select **Deploy** to push the route to the PingGateway configuration.
You can check the `$HOME/.openig/config/routes` folder to see that the route is there.
4. Access the route, and then check `$HOME/.openig/logs` for a log file named by the route, where `$HOME/.openig` is the instance directory. The log file should contain the messages defined by your capture configuration.

Limit repetitive log messages

To keep log files clean and readable, and to prevent log flow attacks, limit the number of repeat log messages. Add a custom `logback.xml` with a `DuplicateMessageFilter`. This filter detects duplicate messages, and after the specified number of repetitions, drops repeated messages.

The following example allows five repetitions of a log message and holds the last 10 repeated messages in the cache:

```
<turboFilter class="ch.qos.logback.classic.turbo.DuplicateMessageFilter" allowedRepetitions="5" CacheSize="10" />
```

The DuplicateMessageFilter has the following limitations:

- Filters out **all** duplicate messages. It doesn't filter per logger, or logger instance, or logger name.
- Detects repetition of raw messages, meaning that the following example messages are considered as repetition:

```
logger.debug("Hello {}", name0);  
logger.debug("Hello {}", name1);
```

- Doesn't limit the lifespan of the cache. After the specified number of repetitions is reached, the repeated log messages never appear again, even if they're frequently hit.

Tuning PingGateway performance

Tune deployments in the following steps:

1. Consider the issues that impact the performance of a deployment. See [Define requirements and constraints](#).
2. Tune and test the downstream servers and applications:
 1. Tune the downstream web container and JVM to achieve performance targets.
 2. Test downstream servers and applications in a pre-production environment, under the expected load, and with common use cases.
3. Increase hardware resources as required, and then re-tune the deployment.

Define requirements and constraints

When you consider performance requirements, bear in mind the following points:

- The capabilities and limitations of downstream services or applications on your performance goals.
- The increase in response time due to the extra network hop and processing, when PingGateway is inserted as a proxy in front of a service or application.
- The constraint that downstream limitations and response times place on PingGateway.

Service level objectives

A service level objective (SLO) is a target that you can measure quantitatively. Where possible, define SLOs to set out what performance your users expect. Even if your first version of an SLO consists of guesses, it is a first step towards creating a clear set of measurable goals for your performance tuning.

When you define SLOs, bear in mind that PingGateway can depend on external resources that can impact performance, such as AM's response time for token validation, policy evaluation, and so on. Consider measuring remote interactions to take dependencies into account.

Consider defining SLOs for the following metrics of a route:

- Average response time for a route.

The response time is the time to process and forward a request, and then receive, process, and forward the response from the protected application.

The average response time can range from less than a millisecond, for a low latency connection on the same network, to however long it takes your network to deliver the response.

- Distribution of response times for a route.

Because applications set timeouts based on worst case scenarios, the distribution of response times can be more important than the average response time.

- Peak throughput.

The maximum rate at which requests can be processed at peak times. Because applications are limited by their peak throughput, this SLO is arguably more important than an SLO for average throughput.

- Average throughput.

The average rate at which requests are processed.

Metrics are returned at the monitoring endpoints. For information about monitoring endpoints, refer to [PingGateway monitoring reference](#). For examples of how to set up monitoring in PingGateway, refer to [Monitoring services for PingGateway](#).

Available resources

With your defined SLOs, inventory the server, networks, storage, people, and other resources. Estimate whether it is possible to meet the requirements, with the resources at hand.

Benchmarks

Before you can improve the performance of your deployment, establish an accurate benchmark of its current performance. Consider creating a deployment scenario that you can control, measure, and reproduce.

For information about running Ping Identity Platform benchmark tests, refer to the ForgeOps documentation on [benchmarks](#). Adapt the scenarios as necessary for your PingGateway deployment.

Tune PingGateway

Consider the following recommendations for improving performance, throughput, and response times. Adjust the tuning to your system workload and available resources, and then test suggestions before rolling them out into production.

Logs

Log messages in PingGateway and third-party dependencies are recorded using the Logback implementation of the Simple Logging Facade for Java (SLF4J) API. By default, logging level is INFO.

To reduce the number of log messages, consider setting the logging level to `error`. For information, refer to [Managing PingGateway logs](#).

Buffering message content

PingGateway creates a `TemporaryStorage` object to buffer content during processing. For information about this object and its default values, refer to [TemporaryStorage](#).

Messages bigger than the buffer size are written to disk, consuming I/O resources and reducing throughput.

The default size of the buffer is 64 KB. If the number of concurrent messages in your application is generally bigger than the default, consider allocating more heap memory or changing the initial or maximum size of the buffer.

To change the values, add a `TemporaryStorage` object named `TemporaryStorage`, and use non-default values.

Caches

When caches are enabled, PingGateway can reuse cached information without making additional or repeated queries for the information. This gives the advantage of higher system performance, but the disadvantage of lower trust in results.

When caches are disabled, PingGateway must query a data store each time it needs data. This gives the disadvantage of lower system performance, and the advantage of higher trust in results.

All caches provide similar configuration properties for timeout, defining the duration to cache entries. When the timeout is lower, the cache is evicted more frequently, and consequently, the performance is lower but the trust in results is higher.

When you configure caches in PingGateway, make choices to balance your required performance with your security needs.

Learn more about PingGateway caches in [PingGateway caches](#).

WebSocket notifications

By default, PingGateway receives WebSocket notifications from AM for the following events:

- When a user logs out of AM, or when the AM session is modified, closed, or times out. PingGateway can use WebSocket notifications to evict entries from the session cache. For an example of setting up session cache eviction, refer to [Session cache eviction with PingAM](#).
- When AM creates, deletes, or changes a policy decision. PingGateway can use WebSocket notifications to evict entries from the policy cache. For an example of setting up policy cache eviction, refer to [Notifications and the PingAM policy cache](#).
- When PingGateway automatically renews a WebSocket connection to AM. To configure WebSocket renewal, refer to the `notifications.renewalDelay` property of [AmService](#).

If the WebSocket connection is lost, during that time the WebSocket is not connected, PingGateway behaves as follows:

- Responds to session service calls with an empty `SessionInfo` result.

When the `SingleSignOn` filter receives an empty `SessionInfo` call, it concludes that the user is not logged in, and triggers a login redirect.

- Responds to policy evaluations with a deny policy result.

By default, PingGateway waits for five seconds before trying to reestablish the WebSocket connection. If it can't reestablish the connection, it keeps trying every five seconds.

To disable WebSocket notifications, or change any of the parameters, configure the `notifications` property in `AmService`. For information, refer to [AmService](#).

Tune the ClientHandler/ReverseProxyHandler

The ClientHandler/ReverseProxyHandler communicates as a client to a downstream third-party service or protected application. The performance of the communication is determined by the following parameters:

- The number of available connections to the downstream service or application.
- The connection timeout, which is the maximum time to connect to a server-side socket before timing out and abandoning the connection attempt.
- The socket timeout, which is the maximum time a request can take before a response is received after which the request is deemed to have failed.

Configure PingGateway in conjunction with PingGateway's first-class Vert.x configuration, and the `vertx` property of `admin.json`. For more information, refer to [AdminHttpApplication \(admin.json\)](#).

Vert.x options for tuning

Object	Vert.x Option	Description
PingGateway (first-class)	<code>gatewayUnits</code>	The number of deployed Vert.x Verticles. This setting is effectively the number of cores that PingGateway operates across, or in other words, the number of available threads. Each instance operates on the same port on its own event-loop thread. Default: Number of available cores. (This is the optimal value.)
root.vertx	<code>eventLoopPoolSize</code>	The size of the pool available to service Verticles for event-loop threads. To guarantee that a single thread handles all I/O events for a single request or response, PingGateway deploys a Verticle onto each event loop. Configure <code>eventLoopPoolSize</code> to be greater than or equal to <code>gatewayUnits</code> . Default: 2 * number of available cores. For more information, refer to Reactor and Multi-Reactor .
root.connectors.<connector>.vertx	<code>acceptBacklog</code>	The maximum number of connections to queue before refusing requests. Default: 1024

Object	Vert.x Option	Description
	<code>sendBufferSize</code>	The TCP connection send buffer size. Set this property according to the available RAM and required number of concurrent connections. Default: Use the Java TCP send buffer size default settings that Java inherits from the operating system.
	<code>receiveBufferSize</code>	The TCP receive buffer size. Set this property according to the available RAM and required number of concurrent connections. Default: Use the Java TCP receive buffer size default settings that Java inherits from the operating system.
	<code>maxHeaderSize</code>	Set this property when HTTP headers manage large values (such as JWT). Default: 8 KB (8,192 bytes)

Vert.x options for troubleshooting performance

Object	Vert.x Option	Description
root.vertx	<code>blockedThreadCheckInterval</code> and <code>blockedThreadCheckIntervalUnit</code>	The interval at which Vert.x checks for blocked threads and logs a warning. Default: 1 second
	<code>maxEventLoopExecuteTime</code> and <code>maxEventLoopExecuteTimeUnit</code>	The maximum execution time before Vert.x logs a warning. Default: 2 seconds
	<code>warningExceptionTime</code> and <code>warningExceptionTimeUnit</code>	The threshold at which warning logs are accompanied by a stack trace to identify cause. Default: 5 seconds
	<code>logActivity</code>	Whether to log network activity. Default: <code>false</code>

Set the maximum number of file descriptors and processes per user

Each PingGateway instance in your environment should have access to at least 65,536 file descriptors to handle multiple client connections.

Ensure that every PingGateway instance is allocated enough file descriptors. For example, use the `ulimit -n` command to check the limits for a particular user:


```
$ su - iguser
$ ulimit -n
```

It may also be necessary to increase the number of processes available to the user running the PingGateway processes.

For example, use the `ulimit -u` command to check the process limits for a user:

```
$ su - iguser
$ ulimit -u
```



Important

Before increasing the file descriptors for the PingGateway instance, ensure that the total amount of file descriptors configured for the operating system is higher than 65,536.

If the PingGateway instance uses all of the file descriptors, the operating system will run out of file descriptors. This may prevent other services from working, including those required for logging in the system.

Refer to your operating system's documentation for instructions on how to display and increase the file descriptors or process limits for the operating system and for a given user.

Tune PingGateway's JVM

Start tuning the JVM with default values, and monitor the execution, paying particular attention to memory consumption, and GC collection time and frequency. Incrementally adjust the configuration, and retest to find the best settings for memory and garbage collection.

Make sure there is enough memory to accommodate the peak number of required connections, and make sure timeouts in PingGateway and its container support latency in downstream servers and applications.

PingGateway makes low memory demands, and consumes mostly YoungGen memory. However, using caches, or proxying large resources, increases the consumption of OldGen memory. For information about how to optimize JVM memory, refer to the Oracle documentation.

Consider these points when choosing a JVM:

- Find out which version of the JVM is available. More recent JVMs usually contain performance improvements, especially for garbage collection.
- Choose a 64-bit JVM if you need to maximize available memory.

Consider these points when choosing a GC:

- Test GCs in realistic scenarios, and load them into a pre-production environment.
- Choose a GC that is adapted to your requirements and limitations. Consider comparing the *Garbage-First Collector (G1)* and *Parallel GC* in typical business use cases.

The G1 is targeted for multi-processor environments with large memories. It provides good overall performance without the need for additional options. The G1 is designed to reduce garbage collection, through low-GC latency. It is largely self-tuning, with an adaptive optimization algorithm.

The Parallel GC aims to improve garbage collection by following a high-throughput strategy, but it requires more full garbage collections.

Learn more in [Best practice for JVM Tuning with G1 GC](#).

Rotating PingGateway encryption and signing keys

The following sections give an overview of how to manage rotation of encryption keys and signing keys, and include examples for key rotation based on use cases from the [Gateway guide](#).

About key rotation

Key rotation is the process of generating a new version of a key, assigning that version as the *active* key to encrypt or sign new messages, or as a *valid* key to decrypt or validate messages, and then deprovisioning the old key.

Why and when to rotate keys

Regular key rotation is a security consideration that is sometimes required for internal business compliance. Regularly rotate keys to:

- Limit the amount of data protected by a single key.
- Reduce dependence on specific keys, making it easier to migrate to stronger algorithms.
- Prepare for when a key is compromised. The first time you try key rotation shouldn't be during a real-time recovery.

Key revocation is a type of key rotation, done exceptionally if you suspect that a key has been compromised. To decide when to revoke a key, consider the following points:

- If limited use of the old keys can be tolerated, provision the new keys and then deprovision the old keys. Messages produced before the new keys are provisioned are impacted.
- If use of the old keys cannot be tolerated, deprovision the old keys before you provision the new keys. The system is unusable until new keys are provisioned.

Steps for rotating symmetric keys

The following steps outline key rotation and revocation for symmetric keys managed by a KeyStoreSecretStore. For an example, refer to [Rotate keys in a shared JWT session](#).

1. Using OpenSSL, Keytool, or another key creation mechanism, create the new symmetric key. The keystore should contain the old key and the new key.
2. Provision the new key.
 1. In the `mappings` property of KeyStoreSecretStore, add the alias for the new key after the alias for the old key. The new key is now valid. Because the old key is the first key in the list, it is the active key.
 2. Move the new key to be the first key in the list. The new key is now the active key.
3. Deprovision the old key.

To ensure that no messages or users are impacted, wait until messages encrypted or signed with the old key are out of the system before you deprovision the old key.

1. In the `mappings` property of `KeyStoreSecretStore`, delete the alias for the old key. The old key can no longer be used.
2. Using OpenSSL, Keytool, or another key creation mechanism, delete the old symmetric key.

Steps for rotating asymmetric keys

The following steps outline the process for key rotation and revocation for asymmetric keys managed by a `KeyStoreSecretStore` or `HsmSecretStore`. For an example, refer to [Rotate keys for stateless access tokens signed with a KeyStoreSecretStore](#).

1. Create new asymmetric keys for signing and encryption, using OpenSSL, Keytool, or another key creation mechanism.
2. Provision the message consumer with the private portion of the new encryption key, and the public portion of the new signing key.

The message consumer can now decrypt and verify messages with the old key and the new key.

3. Provision the message producer, with the public portion of the new encryption key, and the private portion of the signing key. The message producer starts encrypting and signing messages with the new key, and stops using the old key.
4. Deprovision the message consumer with the private portion of the old encryption key, and the public portion of the old signing key. The message consumer can no longer decrypt and verify messages with the old key.

To ensure that no messages or users are impacted, wait until messages encrypted or signed with the corresponding old key are out of the system before you deprovision the old key.

5. Deprovision the message producer, with the public portion of the old encryption key, and the private portion of old signing key.

Key rotation for keys in a JWK set

When keys are provided by a JWK Set from AM, the key rotation is transparent to PingGateway. AM generates a key ID (`kid`) for each key it exposes at the `jwk_uri`. For more information, refer to [Mapping and rotating secrets](#) in AM's *Security guide*.

When PingGateway processes a request with a JWT containing a `kid`, PingGateway uses the `kid` to identify the key in the JWK Set. If the `kid` is available at the `jwk_uri` on AM, PingGateway processes the request. Otherwise, PingGateway tries all compatible secrets from the JWK Set. If none of the secrets work, the JWT is rejected.

Rotate keys for stateless access tokens signed with a KeyStoreSecretStore

This example extends the example in [Signed PingAM tokens with KeyStoreSecretStore](#) to rotate the keys that sign an access token and verify the signature.

Rotate Keys For Stateless Access Tokens Signed With a KeyStoreSecretStore

Before you start, set up and test the example in [Signed PingAM tokens with KeyStoreSecretStore](#).

1. Set up the new keys:
 1. Generate a new private key called `signature-key-new`, and a corresponding public certificate called `x509certificate-new.pem`:

```
$ openssl req -x509 \  
-newkey rsa:2048 \  
-nodes \  
-subj "/CN=ig.example.com/OU=example/O=com/L=fr/ST=fr/C=fr" \  
-keyout keystore_directory/signature-key-new.key \  
-out keystore_directory/x509certificate-new.pem \  
-days 365
```

Output

```
... writing new private key to 'keystore_directory/signature-key-new.key'
```

2. Convert the private key and certificate files into a new PKCS#12 keystore file:

```
$ openssl pkcs12 \  
-export \  
-in keystore_directory/x509certificate-new.pem \  
-inkey keystore_directory/signature-key-new.key \  
-out keystore_directory/keystore-new.p12 \  
-passout pass:password \  
-name signature-key-new
```

3. List the keys in the new keystore:

```
$ keytool -list \  
-keystore "keystore_directory/keystore-new.p12" \  
-storepass "password" \  
-storetype PKCS12
```

Output

```
...  
Your keystore contains 1 entry  
Alias name: signature-key-new
```

4. Import the new keystore into `keystore.p12`, so that `keystore.p12` contains both keys:

```
$ keytool -importkeystore  
-srckeystore keystore_directory/keystore-new.p12  
-srcstoretype pkcs12  
-srcstorepass password  
-destkeystore keystore_directory/keystore.p12  
-deststoretype pkcs12  
-deststorepass password
```

Output

Entry for alias signature-key-new successfully imported ...

5. List the keys in `keystore.p12`, to make sure it contains the new and old keys:

```
$ keytool -list \  
-keystore "keystore_directory/keystore.p12" \  
-storepass "password" \  
-storetype PKCS12
```

Output

```
...  
Your keystore contains 2 entries  
Alias name: signature-key  
Alias name: signature-key-new
```

2. Set up AM:

1. Copy the updated keystore to AM:

1. Copy `keystore.p12` to AM:

```
$ cp keystore_directory/keystore.p12 am_keystore_directory/AM_keystore.p12
```

2. List the keys in the updated AM keystore:

```
$ keytool -list \  
-keystore "am_keystore_directory/AM_keystore.p12" \  
-storepass "password" \  
-storetype PKCS12
```

Output

```
...  
Your keystore contains 2 entries  
Alias name: signature-key  
Alias name: signature-key-new
```

3. Restart AM to update the keystore cache.

2. Update the KeyStoreSecretStore on AM:

1. In AM, select  **Secret Stores** > keystoresecretstore.

2. Select the **Mappings** tab, and in `am.services.oauth2.stateless.signing.RSA` add the alias `signature-key-new`.

The mapping now contains two aliases, but the alias `signature-key` is still the active alias. AM still uses `signature-key` to sign tokens.

3. Drag `signature-key-new` above `signature-key`.

AM now uses `signature-key-new` to sign tokens.

3. Set up PingGateway:

1. Set up PingGateway for HTTPS, as described in [Configure PingGateway for TLS \(server-side\)](#).
2. Import the public certificate to the PingGateway keystore, with the alias `verification-key-new`:

```
$ keytool -import \  
-trustcacerts \  
-rfc \  
-alias verification-key-new \  
-file "keystore_directory/x509certificate-new.pem" \  
-keystore "ig_keystore_directory/IG_keystore.p12" \  
-storetype PKCS12 \  
-storepass "password"
```

Output

```
...  
Trust this certificate? [no]: yes  
Certificate was added to keystore
```

3. List the keys in the PingGateway keystore:

```
$ keytool -list \  
-keystore "ig_keystore_directory/IG_keystore.p12" \  
-storepass "password" \  
-storetype PKCS12
```

Output

```
...  
Your keystore contains 2 entries  
Alias name: verification-key  
Alias name: verification-key-new
```

4. In `rs-stateless-signed-ksss.json`, edit the `KeyStoreSecretStore` mapping with the new verification key:

```
"mappings": [
  {
    "secretId": "stateless.access.token.verification.key",
    "aliases": [ "verification-key", "verification-key-new" ]
  }
]
```

If the Router `scanInterval` is disabled, restart PingGateway to reload the route.

PingGateway can now check the authenticity of access tokens signed with `verification-key`, the old key, and `verification-key-new`, the new key. However, AM signs with the old key.

4. Test the setup:

1. Get an access token for the demo user, using the scope `myscope` :

```
$ mytoken=$(curl -s \
--user "client-application:password" \
--data "grant_type=password&username=demo&password=Ch4ng31t&scope=myscope" \
http://am.example.com:8088/openam/oauth2/access_token | jq -r ".access_token")
```

2. Display the token:

```
$ echo ${mytoken}
```

3. Access the route by providing the token returned in the previous step:

```
$ curl -v \
--cacert /path/to/secrets/ig.example.com-certificate.pem \
--header "Authorization: Bearer ${mytoken}" \
https://ig.example.com:8443/rs-stateless-signed-ksss
```

Output

```
...
Decoded access_token: {
  sub=demo,
  cts=OAUTH2_STATELESS_GRANT,
  ...
}
```

Deprovision Old Keys

1. Remove `signature-key` from the AM keystore:
1. Delete the key from the keystore:

```
$ keytool -delete \
-keystore "am_keystore_directory/AM_keystore.p12" \
-storepass "password" \
-alias signature-key
```

2. List the keys in the AM keystore to make sure `signature-key` is removed:

```
$ keytool -list \
-keystore "am_keystore_directory/AM_keystore-new.p12" \
-storepass "password" \
-storetype PKCS12
```

3. Restart AM.

2. Remove `verification-key` from the PingGateway keystore:

1. Delete the key from the keystore:

```
$ keytool -delete \
-keystore "ig_keystore_directory/IG_keystore.p12" \
-storepass "password" \
-alias verification-key
```

2. List the keys in the PingGateway keystore to make sure that `verification-key` is removed:

```
$ keytool -list \
-keystore "ig_keystore_directory/IG_keystore.p12" \
-storepass "password" \
-storetype PKCS12
```

3. In AM, delete the mapping for `signature-key` from `keystoresecretstore`.
4. In PingGateway, delete the mapping for `verification-key` from the route `rs-stateless-signed-ksss.json`. If the Router `scanInterval` is disabled, restart PingGateway to reload the route.

Rotate keys in a shared JWT session

This section builds on the example in [Share JWT session between multiple instances of PingGateway](#) to rotate a key used in a shared JWT session.

When a JWT session is shared between multiple instances of PingGateway, the instances are able to share the session information for load balancing and failover.

Before you start, set up the example in [Set up shared secrets for multiple instances of PingGateway](#), where three instances of PingGateway share stateless sessions and use the same authenticated encryption key. Instance 1 acts as a load balancer, and generates a session. Instances 2 and 3 access the session information.

1. Test the setup with the existing key, `symmetric-key`:

1. Access instance 1 to generate a session:

```
$ curl -v http://ig.example.com:8001/log-in-and-generate-session
```

Output

```
GET /log-in-and-generate-session HTTP/1.1
...

HTTP/1.1 200 OK
Content-Length: 84
Set-Cookie: IG=eyJ...HyI; Path=/; Domain=.example.com; HttpOnly
...
Sam Carter logged IN. (JWT session generated)
```

2. Using the JWT cookie returned in the previous step, access instance 2:

```
$ curl -v http://ig.example.com:8001/webapp/browsing?one --header "cookie:IG=<JWT cookie>"
```

Output

```
GET /webapp/browsing?one HTTP/1.1
...
cookie: IG=eyJ...QHyI
...
HTTP/1.1 200 OK
...
Hello, Sam Carter !! (instance2)
```

Note that instance 2 can access the session info.

3. Using the JWT cookie again, access instance 3:

```
$ curl -v http://ig.example.com:8001/webapp/browsing?two --header "Cookie:IG=<JWT cookie>"
```

Output

```
GET /webapp/browsing?two HTTP/1.1
...
cookie: IG=eyJ...QHyI
...
HTTP/1.1 200 OK
...
Hello, Sam Carter !! (instance3)
```

Note that instance 3 can access the session info.

2. Commission a new key:

1. Generate a new encryption key, called `symmetric-key-new`, in the existing keystore:

```
$ keytool \
-genseckey \
-alias symmetric-key-new
-keystore /path/to/secrets/jwtsessionkeystore.pkcs12 \
-storepass password \
-storetype PKCS12 \
-keyalg HmacSHA512 \
-keysize 512
```

2. Make sure the keystore contains the old key and the new key:

```
$ keytool \
-list \
-keystore /path/to/secrets/jwtsessionkeystore.pkcs12 \
-storepass password \
-storetype PKCS12
```

Output

```
...
Your keystore contains 2 entries
symmetric-key, ...
symmetric-key-new ...
```

3. Add the key alias to `instance1-loadbalancer.json`, `instance2-retrieve-session-username.json`, and `instance3-retrieve-session-username.json`, for each PingGateway instance, as follows:

```
"mappings": [{
  "secretId": "jwtsession.encryption.secret.id",
  "aliases": ["symmetric-key", "symmetric-key-new"]
}]
```

If the Router `scanInterval` is disabled, restart PingGateway to reload the route.

The active key is `symmetric-key`, and the valid key is `symmetric-key-new`.

4. Test the setup again, as described in step 1, and make sure instances 2 and 3 can still access the session information.

3. Make the new key the active key for generating sessions:

1. In `instance1-loadbalancer.json`, change the order of the keys to make `symmetric-key-new` the active key, and `symmetric-key` the valid key:

```
"mappings": [{
  "secretId": "jwtsession.encryption.secret.id",
  "aliases": ["symmetric-key-new", "symmetric-key"]
}]
```

Don't change `instance2-retrieve-session-username.json` or `instance3-retrieve-session-username.json`.

2. Test the setup again, as described in step 1, and make sure instances 2 and 3 can still access the session information.

Instance 1 creates the session using the new active key, `symmetric-key-new`.

Because `symmetric-key-new` is declared as a valid key in instances 2 and 3, the instances can still access the session. It isn't necessary to make `symmetric-key-new` the active key.

4. Decommission the old key:

1. Remove the old key from all of the routes, as follows:

```
"mappings": [{
  "secretId": "jwtsession.encryption.secret.id",
  "aliases": ["symmetric-key-new"]
}]
```

Key `symmetric-key-new` is the only key in the routes.

2. Remove the old key, `symmetric-key`, from the keystore:

1. Delete `symmetric-key`:

```
$ keytool \
  -delete \
  -alias symmetric-key \
  -keystore /path/to/secrets/jwtsessionkeystore.pkcs12 \
  -storepass password \
  -storetype PKCS12 \
  -keypass password
```

2. Make sure the keystore contains only `symmetric-key-new`:

```
$ keytool \  
-list \  
-keystore /path/to/secrets/jwtsessionkeystore.pkcs12 \  
-storepass password \  
-storetype PKCS12
```

Output

```
...  
Your keystore contains 1 entry  
symmetric-key-new ...
```

3. Test the setup again, as described in step 1, and make sure instances 2 and 3 can still access the session information.

Securing and hardening PingGateway

The following sections describe options for securing and hardening your deployment:

General security considerations

Consider the following settings in PingGateway to secure your deployment:

Switch to production mode.

Prevent changes to your configuration by setting the run mode to `production`. Learn more in [PingGateway operating modes](#).

Protect endpoints.

Restrict access to your monitoring data by protecting the Prometheus Scrape Endpoint and Common REST Monitoring Endpoint (deprecated). Learn more in [Protecting the monitoring endpoints](#).

Exclude sensitive data from logs.

- Prevent logging of sensitive data for audit events by excluding fields from the audit logs. Learn more in [Including or Excluding Audit Event Fields In Logs](#).
- When using a `CaptureDecorator`, mask captured header and attribute values to avoid disclosing information, such as token values or passwords. Learn more in [CaptureDecorator](#).

Limit the amount of information available to attackers during reconnaissance, the initial phase of an attack sequence.

- Reduce the global log level from `TRACE` or `DEBUG` to `INFO`. Learn more in [Changing Log Levels](#).
- Avoid using words that help to identify PingGateway in error messages, such as those produced by the entity in a `StaticResponseHandler`. Learn more in [StaticResponseHandler](#).

Secure responses from cross-site scripting.

- Sanitize any external input, such as the request, before incorporating it in the response.
- Specify `Content-Type` in the `headers` property of `StaticResponseHandler` when an entity is used. (Required by default, from PingGateway 7.)
- Set the response header `X-Content-Type-Options: nosniff` to prevent the user agent from interpreting the response entity as a different content type. (Set by default, from PingGateway 7.)
- Set a restrictive value in the `Cache-Control` response header. For example, setting `Cache-Control: private` indicates that all or part of the response message is intended for a single user and MUST NOT be cached by a shared cache.

Secure sessions.

Protect network traffic by using HTTPS where possible, and secure communications during stateless sessions by signing and encrypting JWTs. Learn more in [JwtSessionManager](#).

Secure cookies.

- Store a minimum amount of sensitive data in cookies, and only when necessary.
- Change the default name of cookies to prevent them from being easily associated with an application.
- Where possible, configure cookie properties to restrict how and where they can be used. Learn more about this in the reference documentation. Read about the `cookie` setting in [InMemorySessionManager](#) (stateful sessions) or in [JwtSessionManager](#) (stateless sessions). Read about the `authCookie` setting in [CrossDomainSingleSignOnFilter](#).

Limit HTTP request body size

HTTP doesn't define a limit for the body size in POST and PUT requests. By default, PingGateway also doesn't limit the HTTP request body size.

You can configure PingGateway to reject requests whose body exceeds a defined size. In the `admin.json` file, add these settings:

- `adminMaxBodyLength` : Maximum body size in bytes for HTTP requests to the administration port.
- `maxBodyLength` : Maximum body size in bytes for HTTP requests from client applications.

Consider the following general points to secure your deployment:

Keep up-to-date on patches.

Security vulnerabilities are the reason why you should keep your operating systems, web and application servers, and any other application in your environment up-to-date. Knowledge of vulnerabilities spreads fast across malicious users, who would not hesitate in trying to exploit them.

Ping Identity maintains a list of security advisories you should follow. You should also follow similar lists from all of your vendors.

Keep up-to-date on cryptographic methods and algorithms.

Different algorithms and methods are discovered and tested over time, and communities of experts decide which are the most secure for different uses. Do not use outdated algorithms for generating your keys.

Turn off unnecessary features.

The more features you have turned on, the greater the attack surface. If something is not being used, uninstall it, disable it, or protect access to it.

Limit access to the servers hosting PingGateway.

Make sure only authorized people can access your servers and applications through the appropriate network, using the appropriate ports, and presenting strong-enough credentials.

Ensure users connect to systems through the latest versions of TLS, and audit system access periodically.

Enforce security.

Don't expect your users to follow security practices on their own; enforce security when possible by requiring secure connections, password resets, and strong authentication methods.

Audit access and changes.

Audit logs record all events that have happened. Some applications store them with their engine logs, others use specific files or send the information to a different server for archiving. Operating systems have audit logs as well, to detect unauthorized login attempts and changes to the software.

PingGateway has its own audit logging service that adheres to the log structure common across the Ping Identity Platform. Learn more in [Auditing the PingGateway deployment](#).

Prevent log flow attacks.

Limit the number of repeat log messages by adding a custom `logback.xml` with a `DuplicateMessageFilter`. Learn more in [Limit Repetitive Log Messages](#).

Switch from development mode to production mode

After installation, PingGateway is by default in production mode. While you evaluate PingGateway or develop routes, it can be helpful to switch to development mode as described in [PingGateway operating modes](#). After deployment, it's essential to switch back to production mode to prevent unwanted changes to the configuration.

Troubleshooting PingGateway issues

Ping Identity provides support services, professional services, training, and partner services to help you set up and maintain your deployments.

Getting support

Ping Identity provides support services, professional services, training, and partner services to assist you in setting up and maintaining your deployments. For a general overview of these services, see <https://www.pingidentity.com>.

Ping Identity has staff members around the globe who support our international customers and partners. For details on Ping Identity's support offering, visit <https://www.pingidentity.com/support>.

Ping Identity publishes comprehensive documentation online:

- The Ping Identity [Knowledge Base](#) offers a large and increasing number of up-to-date, practical articles that help you deploy and manage Ping Identity Platform software.

While many articles are visible to everyone, Ping Identity customers have access to much more, including advanced information for customers using Ping Identity Platform software in a mission-critical capacity.

- Ping Identity product documentation, such as this document, aims to be technically accurate and complete with respect to the software documented. It is visible to everyone and covers all product features and examples of how to use them.

Getting info about the problem

When trying to solve a problem, save time by asking the following questions:

- How do you reproduce the problem?
- What behavior do you expect, and what behavior do you have?
- When did the problem start occurring?
- Are their circumstances in which the problem doesn't occur?
- Is the problem permanent, intermittent, getting better, getting worse, or staying the same?

If you contact ForgeRock for help, include the following information with your request:

- The product version and build information. This information is included in the logs when PingGateway starts up. If PingGateway is running in development mode, and set up as described in the [Getting started with PingGateway](#), access the information at `http://ig.example.com:8085/api/info`.
- Description of the problem, including when the problem occurs and its impact on your operation.
- Steps you took to reproduce the problem.
- Relevant access and error logs, stack traces, and core dumps.
- Description of the environment, including the following information:
 - Machine type
 - Operating system and version
 - Web server or container and version
 - Java version
 - Patches or other software that might affect the problem

Start up

If PingGateway doesn't restart or load routes after a first startup, search `route-system.log` for lines containing `Error while starting...` or `Unable to start ...` and use the error message to debug the issue.

If PingGateway shuts down without using the `stop.sh` or `stop.bat` script, the PID file isn't removed and PingGateway can't restart. This can happen when you use the PingGateway service to stop or restart PingGateway, or when PingGateway is deployed in Docker.

Remove the PID file or change the configuration as described in [Allow startup when there is an existing PID file](#).

Resources

By default, AM writes cookies to the fully qualified domain name of the server; for example, `am.example.com`. Therefore, a host-based cookie, rather than a domain-based cookie, is set.

Consequently, after authentication through PingAM, requests can be redirected to PingAM instead of to the resource.

To resolve this issue, add a cookie domain to the PingAM configuration. For example, in the AM admin UI, go to **Configure > Global Services > Platform**, and add the domain `example.com`.

When the sample application is used with PingGateway in the documentation examples, the sample application must serve static resources, such as the `.css`. Add the following route to the PingGateway configuration:

```
{
  "name" : "00-static-resources",
  "baseURI" : "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/css') or matchesWithRegex(request.uri.path, '^/.*\.\.ico$') or matchesWithRegex(request.uri.path, '^/.*\.\.gif$')}",
  "handler": "ReverseProxyHandler"
}
```

Source: [00-static-resources.json](#)

Define an entity for the response, as in the following example:

```
{
  "name": "AccessDeniedHandler",
  "type": "StaticResponseHandler",
  "config": {
    "status": 403,
    "headers": {
      "Content-Type": [ "text/html; charset=UTF-8" ]
    },
    "entity": "<html><body><p>User doesn't have permission</p></body></html>"
  }
}
```

Routes

Symptom

The following errors are in `route-system.log`:


```
... | ERROR | main | o.f.o.h.r.RouterHandler | no handler to dispatch to
```

```
08:22:54:974 | ERROR | http-... | o.f.o.h.DispatchHandler | no handler to dispatch to for URI 'http://ig.example.com/demo'
```

Cause

PingGateway is not configured to handle the incoming request or the request to the specified URI:

- "no handler to dispatch to": the router cannot find a route that accepts the incoming request. This error happens when none of the route conditions match the incoming request and there is no default route.
- "no handler to dispatch to for URI": the router cannot find a route that can handle the request to the specified URI because none of the route conditions match the request path (URI).

Solution

If the errors occur during the startup, they are safe to ignore. If the errors occur after the startup, do the following:

- Identify why the request matched none of the [Route](#) conditions, and adapt the conditions. You can find examples in [Example conditions and requests](#).
- Add a default handler to the [Router](#).
- [Add a default route](#) for when no condition is met.

If you have the following error, you have specified `"handler": "Router2"` in `config.json` or in the route, but no handler configuration object named Router2 exists:

```
org.forgerock.json.fluent.JsonValueException: /handler:
  object Router2 not found in heap
  at org.forgerock.openig.heap.HeapImpl.resolve(HeapImpl.java:351)
  at org.forgerock.openig.heap.HeapImpl.resolve(HeapImpl.java:334)
  at org.forgerock.openig.heap.HeapImpl.getHandler(HeapImpl.java:538)
```

Make sure you have added an entry for the handler, and that you have correctly spelled its name.

When the JSON for a route is not valid, PingGateway doesn't load the route. Instead, a description of the error appears in the log.

Use a JSON editor or JSON validation tool such as [JSONLint](#) to make sure your JSON is valid.

PingGateway loads all configurations at startup, and, by default, periodically reloads changed route configurations.

If you make changes to a route that result in an invalid configuration, PingGateway logs errors, but it keeps the previous, correct configuration, and continues to use the old route.

PingGateway only uses the new configuration after you save a valid version or when you restart PingGateway.

Of course, if you restart PingGateway with an invalid route configuration, then PingGateway tries to load the invalid route at startup and logs an error. In that case, if there is no default handler to accept any incoming request for the invalid route, then you have an error, `No handler to dispatch to`.

PingGateway returns an exception if it loads a route for which it can't resolve a requirement. For example, when you load a route that uses an `AmService` object, the object must be available in the AM configuration.

If you add routes to a configuration when the environment is not ready, rename the route to prevent PingGateway from loading it. For example, rename a route as follows:

```
$ mv $HOME/.openig/config/routes/03-sql.json $HOME/.openig/config/routes/03-sql.inactive
```

If necessary, restart PingGateway to reload the configuration. When you have configured the environment, change the file extension back to `.json`.

Studio

Studio deploys and undeploys routes through a main router named `_router`, which is the name of the main router in the default configuration. If you use a custom `config.json`, make sure it contains a main router named `_router`.

You can find more information about creating routes in Studio in [PingGateway Studio](#).

Timeout errors

Problem: After a request is sent to PingGateway, PingGateway seems to hang. An HTTP 502 Bad Gateway error is produced, and the PingGateway log is flushed with `SocketTimeoutException` warnings.

Possible cause: The `baseURI` configuration is missing or causes the request to return to PingGateway, so PingGateway can't produce a response to the request.

Possible solution: Configure the `baseURI` to use a different host and port to PingGateway.

Other problems

Make sure the user running PingGateway can read the flat file. Remember that values include spaces and tabs between the separator, so make sure the values aren't padded with spaces.

The following error can be encountered when using an `AssignmentFilter` as described in [AssignmentFilter](#) and setting a string value for one of the headers.

```
HTTP ERROR 500
Problem accessing /myURL . Reason:
java.lang.String cannot be cast to java.util.List
Caused by:
java.lang.ClassCastException: java.lang.String cannot be cast to java.util.List
```

All headers are stored in lists so the header must be addressed with a subscript. For example, rather than trying to set `request.headers['Location']` for a redirect in the response object, you should instead set `request.headers['Location'][0]`. A header without a subscript leads to the error above.

When a request is longer than 4096 bytes, it can cause an HTTP 414 URI Too Long response.

The default limit for request length is set by the Vert.x configuration `DEFAULT_MAX_INITIAL_LINE_LENGTH`. This default acts on the `connectors` property of [admin.json](#).

When working with requests constructed with parameters and query strings, such as for SAML or token transformation, where the request can become long consider setting the Vert.x property `getMaxInitialLineLength` to increase the limit.

The following example configuration in `admin.json` increases the request length limit to 9999 bytes:

```
"connectors": [  
  {  
    "vertx": {  
      "maxInitialLineLength": 9999,  
      ...  
    }  
  }  
]
```

The following log message indicates that the client or server side has disconnected and PingGateway has ignored the event.

```
[vert.x-eventloop-thread-2] DEBUG ... @system - Connection error. Ignored.  
[CONTINUED]java.nio.channels.ClosedChannelException: null
```

This type of error occurs when a network component closes the connection. This can occur when:

- A load balancer or firewall terminates or times out connections
- Third-party network changes prevent successful connections

Increase logging to provide more information, as described in [Managing PingGateway logs](#).

PingGateway security

Use this guide to reduce risk and mitigate threats to PingGateway security.



Threats

Understand and address security threats.



Operating systems

Secure your operating systems.



Connections

Secure network connections.



Access

Remove non-essential access and features, update patches, and manage cookies.



Keys and Secrets

Manage keys and secrets.



Audit Trails

Audit events in your deployment.

Access to PingGateway

The following sections describe how to prevent unwanted access to your deployment, and reduce the amount of non-essential information that it provides.

Use a PingGateway service account

Install and run PingGateway from a dedicated service account. This is optional when evaluating PingGateway, but essential in production installations. For more information, refer to [Create a PingGateway service account](#).

Remove non-essential access

Make sure only authorized people can access your servers and applications through the appropriate network, using the appropriate ports, and by presenting strong-enough credentials.

Apply the principle of least privilege to PingGateway logs and configuration directories. For more information, refer to [Configuration location](#).

Make sure that users connect to systems through the latest versions of TLS, and audit system access periodically.

Restrict access to your monitoring data by protecting the Prometheus Scrape Endpoint and Common REST Monitoring Endpoint (deprecated). Learn more from [Protecting the monitoring endpoints](#).

Prevent PingGateway from scanning for changes to routes. For information, see `scanInterval` in [Router](#).

Disable administration endpoints and Studio by setting the PingGateway run mode to `production`. For information, refer to [PingGateway operating modes](#).

Remove non-essential features

The more features you have turned on, the greater the attack surface. If something isn't used, uninstall it, disable it, or protect access to it.

Update patches

Prevent the exploitation of security vulnerabilities by using up-to-date versions of PingGateway and third-party software.

Review and follow the Ping Identity security advisories.

Follow similar lists from all of your vendors.

Manage sessions

Expire PingOne Advanced Identity Cloud and AM sessions

To minimize the time an attacker can attack an active session, set expiration timeouts for every PingOne Advanced Identity Cloud and AM session. Set timeouts according to context of the deployment, balancing security and usability so that the user can complete operations without the session frequently expiring.

Learn more in OWASP's [Session Management Cheat Sheet](#) .

Set a maximum session lifetime and idle time in PingOne Advanced Identity Cloud:

- In the Advanced Identity Cloud admin UI, select  **Native Consoles > Access Management**.
- In the AM admin UI, select **Services > Add a Service** and add a **Session** service.

- Specify the following properties in minutes:
 - **Maximum Session Time**
 - **Maximum Idle Time**

Set a maximum session lifetime and idle time in PingAM:

- In the AM admin UI, select **Services > Add a Service** and add a **Session** service.
- Specify the following properties in minutes:
 - **Maximum Session Time**
 - **Maximum Idle Time**

Validate the signature of PingOne Advanced Identity Cloud and AM session cookies

Always configure `verificationSecretId` in the [CrossDomainSingleSignOnFilter](#).

When `verificationSecretId` is not configured, PingGateway doesn't verify the signature of AM session tokens, increasing the risk of CDSO token tampering.

Manage cookies

Increase the security of cookies generated by PingGateway or the protected application in the following ways:

- Change the default name of cookies to prevent them from being easily associated with an application.
- Create cookies with the `secure` flag to ensure that browsers cannot transmit the cookie over non-SSL.

When cookies have the `secure` flag, the first hop of the connection between the user agent and protected application must be secure (over HTTPS); subsequent hops don't have to be secure. In this example, the first hop from the user agent to NGINX is secure, the subsequent hop to PingGateway is not secure:

```
User agent -> NGINX (https://acme.com) -> PingGateway (http://gateway:8080)-> protected application (https://internal.app:8081)
```

- Create cookies with the `httpOnly` flag, to ensure that the cookie cannot be accessed through client-side scripts, and to mitigate any cross-site scripting attacks.

Cookies are `httpOnly` by default in `admin.json`, `InMemorySessionManager`, `JwtSessionManager`, `CrossDomainSingleSignOnFilter`, and `FragmentFilter`.

- Set the `samesite` attribute of cookies to `STRICT` or `LAX`. Learn more in [SameSite cookies](#).
- Set a timeout for cookies to strike a good compromise between security and usability.

Harden a PingGateway configuration by configuring the following objects:

- Configure the `cookie` property of the [InMemorySessionManager](#) (stateful sessions) or [JwtSessionManager](#) (stateless sessions).
- For authentication results, configure the `authCookie` property of the [CrossDomainSingleSignOnFilter](#).

- For the fragment part of a URI when a request triggers a login redirect, configure the `cookie` property of [FragmentFilter](#).

Threats to PingGateway deployments

The following sections describe some of the possible threats to PingGateway, which you can mitigate by following the instructions in this guide.

Out-of-date software

Prevent the exploitation of security vulnerabilities by using up-to-date versions of PingGateway and third-party software.

Review and follow the Ping Identity security advisories.

Follow similar lists from all of your vendors.

Reconnaissance

The initial phase of an attack sequence is often reconnaissance. Limit the amount of information available to attackers during reconnaissance, as follows:

- Avoid using words that help to identify PingGateway in error messages, such as those produced by the entity in a `StaticResponseHandler`. For information, see [StaticResponseHandler](#).
- Use the lowest level of logging necessary. For example, consider logging at the `ERROR` or `WARNING` level, instead of `TRACE` or `MESSAGE`. For information, refer to [Changing the global log level](#).

Cross-site scripting

When using a `StaticResponseHandler`, secure responses from cross-site scripting attacks, as follows:

- Sanitize any external input, such as the request, before incorporating it in the response.
- Specify `Content-Type` in the `headers` property of `StaticResponseHandler` when an entity is used. (Required by default, from PingGateway 7.)
- Set the response header `X-Content-Type-Options: nosniff` to prevent the user agent from interpreting the response entity as a different content type. (Set by default, from PingGateway 7.)
- Set a restrictive value in the `Cache-Control` response header. For example, setting `Cache-Control: private` indicates that all or part of the response message is intended for a single user and MUST NOT be cached by a shared cache.

Compromised passwords

Despite efforts to improve how people manage passwords, users have more passwords than ever before, and many use weak passwords. You are strongly encouraged to use a password manager to generate secure passwords. You can use identity and access management services to avoid password proliferation, and you can ensure the safety of passwords that you cannot eliminate.

Manage passwords for server administration securely.

 Important

Put secrets like passwords and symmetric keys in secret stores or files, or enter them interactively. When you set file permissions correctly, the operating system grants access only to authorized accounts, such as the account to run a server process. Other accounts can't read the secret from a properly protected file. Don't put secrets in commands, environment variables, or Java system properties. Example commands in the documentation favor ease of use for evaluation, often including passwords. When you harden services for deployment, don't sacrifice security for ease of use. Including secrets in commands, environment variables, or Java system properties isn't secure:

- Operating system processes can access the full command to run another process. Those processes can read any secrets you set in the command to run a service, for example.
- Operating system processes can access the environment variables of a server process.
- Monitoring software, command-line tools, and support tools extract values of Java system properties and can share them with other systems.

Misconfiguration

Misconfiguration can arise from bad or mistaken configuration decisions, and from poor change management. Depending on the configuration error, features can stop working in obvious or subtle ways, and potentially introduce security vulnerabilities.

The following behaviour can be caused by misconfiguration:

- Routes fail to load, or succeed in loading but cause unexpected behaviour.

For example, if a configuration change prevents the server from making HTTPS connections, many applications can no longer connect, and the problem is detected immediately. However, if a configuration change allows insecure TLS protocol versions or cipher suites for HTTPS connections, some applications negotiate insecure TLS, but appear to continue to work properly.

- Access policy is not correctly enforced.

Incorrect parameters for secure connections and incorrect Access Control Instructions (ACI) can lead to overly permissive access to data, and potentially to a security breach.

- The server fails to restart.

Although failure to start a server is not directly a threat to security, it can affect service availability.

To guard against bad configuration decisions, implement good change management:

- For all enabled features, document why they are enabled and what your configuration choices mean. This implies a review of configuration settings, including default settings that you accept.
- Validate configuration decisions with thorough testing.
- Maintain a record of your configurations and the changes applied.

For example, use a filtered audit log. Use version control software for any configuration scripts and to record changes to configuration files.

- Maintain a record of external changes to the system, such as changes to operating system configuration, and updates to software, such as the JVM that introduces security changes.

Unauthorized access

Data theft can occur when access policies are too permissive, and when the credentials to gain access are too easily cracked. It can also occur when the data is not protected, when administrative roles are too permissive, and when administrative credentials are poorly managed.

Poor risk management

Threats can arise when plans fail to account for outside risks. To mitigate risk, develop appropriate answers to at least the following questions:

- What happens when a server or an entire data center becomes unavailable?
- How do you remedy a serious security issue in the service, either in the PingGateway software or the connected systems?
- How do you validate mitigation plans and remedial actions?
- How do client applications work when the PingGateway offline?

If client applications require always-on services, how do your operations ensure high availability, even when a server goes offline?

For critical services, test expected operation and disaster recovery operation.

Operating systems and PingGateway

When you deploy PingGateway, familiarize yourself with the recommendations for the host operating systems that you use. For comprehensive information about securing operating systems, refer to the [CIS Benchmark](#) documentation.

System updates

Over the lifetime of a deployment, the operating system might be subject to vulnerabilities. Some vulnerabilities require system upgrades, whereas others require only configuration changes. All updates require proactive planning and careful testing.

For the operating systems used in production, put a plan in place for avoiding and resolving security issues. The plan should answer the following questions:

- How does your organization become aware of system security issues early?

This could involve following bug reports, mailing lists, forums, and other sources of information.

- How do you test security fixes, including configuration changes, patches, service packs, and system updates?

Validate the changes first in development, then in one or more test environments, then in production in the same way you would validate other changes to the deployment.

- How do you roll out solutions for security issues?

In some cases, fixes might involve both changes to the service, and specific actions by those who use the service.

- What must you communicate about security issues?

- How must you respond to security issues?

Software providers often don't communicate what they know about a vulnerability until they have a way to mitigate or fix the problem. Once they do communicate about security issues, the information is likely to become public knowledge quickly. Make sure you can expedite resolution of security issues.

To resolve security issues quickly, make sure you are ready to validate any changes that must be made. When you validate a change, check that the fix resolves the security issue. Validate that the system and PingGateway software continue to function as expected in all the ways they are used.

System audits

System audit logs make it possible to uncover system-level security policy violations that aren't recorded in PingGateway, such as unauthorized access to PingGateway files. Such violations aren't recorded in PingGateway logs or monitoring information.

Also consider how to prevent or at least detect tampering. A malicious user violating security policy is likely to try to remove evidence of how security was compromised.

Unused features

By default, operating systems include many features, accounts, and services that PingGateway software doesn't require. Each optional feature, account, and service on the system brings a risk of additional vulnerabilities. To reduce the surface of attack, enable only required features, system accounts, and services. Disable or remove those that aren't needed for the deployment.

The features needed to run and manage PingGateway software securely include the following:

- A Java runtime environment, required to run PingGateway software.
- Software to secure access to service management tools; in particular, when administrators access the system remotely.
- Software to secure access for remote transfer of software updates, backup files, and log files.
- Software to manage system-level authentication, authorization, and accounts.
- Firewall software, intrusion-detection/intrusion-prevention software.
- Software to allow auditing access to the system.
- System update software to allow updates that you have validated previously.
- If required for the deployment, system access management software such as SELinux.
- Any other software that is clearly indispensable to the deployment.

Consider the minimal installation options for your operating system, and the options to turn off features.

Consider configuration options for system hardening to further limit access even to required services.

For each account used to run a necessary service, limit the access granted to the account to what is required. This reduces the risk that a vulnerability in access to one account affects multiple services across the system.

Make sure you validate the operating system behavior every time you deploy new or changed software. When preparing the deployment and when testing changes, maintain a full operating system with PingGateway software that is not used for any publicly available services, but only for troubleshooting problems that might stem from the system being *too* minimally configured.

Network connections and PingGateway

Protect network traffic by using HTTPS where possible, and secure communications during stateless sessions by signing and/or encrypting JWTs. For information about configuring PingGateway for HTTPS client-side and HTTPS server-side, refer to the [Installation guide](#).

Recommendations for incoming connections (from clients to PingGateway).

Protocol	Recommendations
HTTP	HTTP connections that aren't protected by SSL/TLS use cleartext messages. When you permit insecure connections, you cannot prevent client applications from sending sensitive data. For example, a client could send unprotected credentials in an HTTP Authorization header. Even if the server were to reject the request, the credentials would already be leaked to any eavesdroppers. Always use HTTPS for connections up to a load-balancer or proxy in front of the web application or server.
HTTPS	Follow industry-standard TLS recommendations for Security/Server Side TLS. Use a secure version of TLS/SSL to connect to TLS-protected endpoints with HTTP connection handlers, such as ClientHandler and ReverseProxyHandler. TLS protocols below 1.2 aren't considered secure. Some client applications require a higher level of trust, such as clients with additional privileges or access. Client application deployers might find it easier to manage public keys as credentials than to manage user name/password credentials. Client applications can use SSL client authentication. When using PingGateway REST to LDAP gateway, use HTTPS to protect client connections.
JMX	Secure JMX access with the SSL/TLS-related properties, such as <code>use-ssl</code> and others.
SSH	PingGateway administration tools can connect securely. Administrators should use SSH when changing the PingGateway configuration or binaries. The user account for running PingGateway should not be the same user account for connecting remotely. Secure Copy (SCP) uses SSH to transfer files securely. SCP is an appropriate protocol for copying backup data, for example.

Recommendations for outgoing connections (from PingGateway to another service.)

Client	Recommendations
Common Audit event handlers	Configure ForgeRock Common Audit event handlers to use HTTPS when connecting to external log services.

Client	Recommendations
OAuth 2.0-based HTTP authorization mechanisms	HTTP authorization can be based on OAuth 2.0, where PingGateway servers act as resource servers, and make requests to resolve OAuth 2.0 tokens. Use HTTPS to protect the connections to <code>OAuth2ResourceServerFilter</code> and <code>AuthorizationCodeOAuth2ClientFilter</code> . For information, refer to OAuth2ResourceServerFilter and AuthorizationCodeOAuth2ClientFilter .

Message-level security

Server protocols such as HTTP and JMX rely on TLS to protect connections. To enforce secure communication, configure TLS as follows:

- HTTPS server-side: Configure [admin.json](#), [Configure PingGateway for TLS \(server-side\)](#).
- HTTPS client-side: Configure trust managers and key managers, as described in [Configure PingGateway for TLS \(client-side\)](#).

When negotiating connection security, the server and client must use a common security protocol and cipher suite. In `ClientTlsOptions` and `ServerTlsOptions`, define lists of security protocols and cipher suites. For security, use the most recent protocols and ciphers that the client supports. Clients with older TLS implementations might not support the most recent protocols and ciphers.

PingGateway keys and secrets

PingGateway uses cryptographic keys for encryption, signing, and securing network connections, and passwords. The following sections describe how to secure keys and secrets in your deployment.

About secrets

PingGateway uses the Commons Secrets API to manage secrets, such as passwords and cryptographic keys.

Repositories of secrets are managed through secret stores, provided to the configuration by the `SecretsProvider` object or `secrets` object.

Learn more from:

- [PingGateway secrets](#)
- [SecretsProvider](#)

Secret types

PingGateway uses the following secret types:

GenericSecret

An opaque blob of bytes, such as a password or API key, without any metadata.

A `GenericSecret` cannot be used to perform cryptographic operations.

CryptoKey

A secret that contains either a private or shared key, and/or a public certificate. A `CryptoKey` contains the secret material itself and its metadata; for example, the associated algorithm or key type.

This secret type can be used for cryptographic operations. For example:

- A `Base64EncodedSecretStore` can only serve secrets of the `GenericSecret` type.
- An `HsmSecretStore` can only server secrets of the `CryptoKey` type.
- A `FileSystemSecretStore` can serve secrets of both types.

Secret terminology

PingGateway uses the following terms to describe secrets:

Secret ID

A label to indicate the purpose of a secret. A secret ID is generally associated with one or more aliases of a key in a keystore or HSM.

Stable ID

A label to identify a secret. The stable ID corresponds to the following values in each type of secret store:

- `Base64EncodedSecretStore`: The value of `secret-id` in the `"secret-id": "string"` pair.
- `FileSystemSecretStore`: The filename of a file in the specified directory, without the prefix/suffix defined in the store configuration.
- `HsmSecretStore`: The value of an `alias` in a `secret-id / aliases` mapping.
- `JwkSetSecretStore`: The value of the `kid` of a JWK stored in a `JwkSetSecretStore`.
- `KeyStoreSecretStore`: The value of an `alias` in a `secret-id / aliases` mapping.
- `SystemAndEnvSecretStore`: The name of a system property or environment. variable

Valid secret

A secret whose purpose matches the secret ID **and** any purpose constraints. Constraints can include requirements for the following:

- Secret type, such as signing key or encryption key
- Cryptographic algorithm, such as Diffie-Hellman and RSA
- Signature algorithm, such as ES256 and ES384

Constraints are defined when the secret is generated, and cannot be added after.

Named secret

A valid secret that a secret store can find by using a secret ID and stable ID.

Active secret

A valid secrets that's considered eligible at the time of use. The way that the active secret is chosen is determined by the type of secret store. For more information, refer to [PingGateway secrets](#),

About keys and certificates

The examples in this documentation use self-signed certificates, but your deployment is likely to use certificates issued by a certificate authority (CA certificates).

The way to obtain CA certificates depends on the certificate authority that you are using, and is not described in this document. As an example, refer to [Let's Encrypt](#).

Integrate CA certificates by using secret stores:

- For PEM files, use a [FileSystemSecretStore](#) and [PemPropertyFormat](#)
- For PKCS12 keystores, use a [KeyStoreSecretStore](#)

For examples, refer to [Serve the same certificate for TLS connections to all server names](#).

Note the following points about using secrets:

- When PingGateway starts up, it listens for HTTPS connections, using the `ServerTlsOptions` configuration in `admin.json`. The keys and certificates are fetched at startup.
- Keys and certificates must be present at startup.
- If keys or certificates change, you must to restart PingGateway.
- When the `autoRefresh` property of `FileSystemSecretStore` or `KeyStoreSecretStore` is enabled, the secret store is automatically reloaded when the filesystem or keystore is changed.

For information about secret stores provided in PingGateway, refer to [PingGateway secrets](#).

Validate the signature of signed tokens

PingGateway validates the signature of signed tokens as described here.

Named secret resolution

If a JWT contains a `kid`, PingGateway queries the secret stores declared in `secretsProvider` or `secrets` to find a named secret, identified by a secret ID and stable ID.

If a named secret is found, PingGateway then uses the named secret to try to validate the signature. If the named secret can't validate the signature, the token is considered as invalid.

If a named secret isn't found, PingGateway tries valid secret resolution.

Valid secret resolution

PingGateway uses the value of `verificationSecretId` as the secret ID, and queries the declared secret stores to find all secrets that match the provided secret ID.

All matching secrets are returned as valid secrets, in the order that the secret stores are declared, and for `KeyStoreSecretStore` and `HsmSecretStore`, in the order defined by the mappings.

PingGateway tries to verify the signature with each valid secret, starting with the first valid secret, and stopping when it succeeds.

If no valid secrets are returned, or if none of the valid secrets can verify the signature, the token is considered as invalid.

For examples where a `StatelessAccessTokenResolver` uses a secret store to validate the signature of signed tokens, refer to the example sections of [JwkSetSecretStore](#) and [KeyStoreSecretStore](#).

Algorithms for elliptic curve digital signatures

When the Elliptic Curve Digital Signature Algorithm (ECDSA) is used for signing, and both of the following conditions are met, JWTs are signed with a deterministic ECDSA:

- Bouncy Castle is installed.
- The system property `org.forgerock.secrets.preferDeterministicEcdsa` is `true`, which is its default value.

Otherwise, when ECDSA is used for signing, JWTs are signed with a non-deterministic ECDSA.

A non-deterministic ECDSA signature can be verified by the equivalent deterministic algorithm.

For information about deterministic ECDSA, refer to [RFC 6979](#). For information about Bouncy Castle, refer to [The Legion of the Bouncy Castle](#).

Update cryptography

Different algorithms and methods are discovered and tested over time, and communities of experts decide which are the most secure for different uses. Use up-to-date cryptographic methods and algorithms to generate keys.



Warning

Legacy keystore types such as JKS and JCEKS are supported but aren't secure. Consider using the PKCS#12 keystore type.

Use strong keys

Small keys are easily compromised. Use at least the [recommended key size](#).

In JVM, the default ephemeral Diffie-Hellman (DH) key size is 1024 bits. To support stronger ephemeral DH keys, and protect against weak keys, consider setting the following system property to increase the DH key size:

```
jdk.tls.ephemeralDHKeySize=2048
```

For more information, refer to [Customizing size of ephemeral Diffie-Hellman keys](#).

Rotate keys

Rotate keys regularly to:

- Limit the amount of data protected by a single key.
- Reduce dependence on specific keys, making it easier to migrate to stronger algorithms.

- Prepare for when a key is compromised. The first time you try key rotation shouldn't be during a real-time recovery.
- Conform to internal business compliance requirements.

For more information, refer to [Rotating PingGateway encryption and signing keys](#).

PingGateway audits and logs

Audit trails

Audits in PingGateway record access to a route. Audit logs in operating systems detect system login attempts and changes to the software.

The PingGateway audit logging service adheres to the log structure common across the Ping Identity Platform. For information, refer to [Auditing the PingGateway deployment](#).

Prevent logging of sensitive data for audit events by excluding fields from the audit logs. For information, refer to [Including or excluding audit event fields in logs](#).

Log files

Logs in PingGateway contain informational, error, and warning events, to troubleshoot and debug transactions and events that take place within the PingGateway instance.

Protect logs from unauthorised access, and make sure they contain a minimum of sensitive or personally identifiable information that could be used in attacks.

When using a `CaptureDecorator`, mask captured header and attribute values to avoid disclosing information, such as token values or passwords. For information, refer to [CaptureDecorator](#).

Limit the number of repeat log messages to prevent log flow attacks, by adding a custom `logback.xml` with a `DuplicateMessageFilter`. For information, refer to [Limit repetitive log messages](#).

PingGateway reference

This guide describes configuration options for PingGateway. It is for PingGateway designers, developers, and administrators.

For API specifications, refer to the appropriate [Javadoc](#).

The examples in this guide use some of the following third-party tools:

- `curl` : <https://curl.haxx.se>
- `HTTPie` : <https://httpie.org>
- `jq` : <https://stedolan.github.io/jq/>
- `keytool` : <https://docs.oracle.com/en/java/javase/21/docs/specs/man/keytool.html>

Reserved routes

By default, PingGateway reserves all paths starting with `/openig` for administrative use, and only local client applications can access resources exposed under `/openig`.

By default, PingGateway allows access to reserved routes only from the loopback address. To override this behavior, define an `"apiProtectionFilter"` in `admin.json`. Find an example in the documentation on [setting up UMA](#).

You can find more information about how to change the base for administrative routes in [Change the base location](#).

Reserved field names

PingGateway reserves all configuration field names that contain only alphanumeric characters.

If you must define your own field names, for example, in custom decorators, use names with dots, `.`, or dashes, `-`. Examples include `my-decorator` and `com.example.myDecorator`.

Field value conventions

PingGateway configuration uses [JSON](#) notation.

This reference uses the following terms when referring to values of configuration object fields:

array

[JSON](#) array.

boolean

Either `true` or `false`.

certificate

`java.security.cert.Certificate` instance.

configuration token

Configuration tokens introduce variables into the server configuration. They can take values from Java system properties, environment variables, JSON and Java properties files held in specified directories, and from properties configured in routes. Learn more in [JSON Evaluation](#).

duration

A duration is a lapse of time expressed in English, such as `23 hours 59 minutes and 59 seconds`. Durations aren't case-sensitive and negative durations aren't supported. Use the following units in durations:

- `indefinite`, `infinity`, `undefined`, `unlimited`: unlimited duration
- `zero`, `disabled`: zero-length duration
- `days`, `day`, `d`: days
- `hours`, `hour`, `h`: hours
- `minutes`, `minute`, `min`, `m`: minutes
- `seconds`, `second`, `sec`, `s`: seconds
- `milliseconds`, `millisecond`, `millisec`, `millis`, `milli`, `ms`: milliseconds
- `microseconds`, `microsecond`, `microsec`, `micros`, `micro`, `us`, `µs`: microseconds
- `nanoseconds`, `nanosecond`, `nanosec`, `nanos`, `nano`, `ns`: nanoseconds

enumeration

A collections of constants.

expression

See [Expressions](#).

configuration expression

Expression evaluated at configuration time, when routes are loaded. See [Configuration Expressions](#).

runtime expression

Expression evaluated at runtime, for each request and response. See [Runtime Expressions](#).

instant

An instantaneous point on the timeline, as a Java type. For more information, see [Class Instant](#) [↗](#).

JsonValue

An object (`JsonObject`), an array (`JsonArray`), a number (`JsonNumber`), a string (`JsonString`), true (`JsonValue.TRUE`), false (`JsonValue.FALSE`), or null (`JsonValue.NULL`).

lvalue-expression

Expression yielding an object whose value is to be set.

Properties whose format is `lvalue-expression` cannot consume streamed content. They must be written with `$` instead of `#`.

map

An object that maps keys to values. Keys must be unique, and can map to at most one value.

number

[JSON](#) number.

object

[JSON](#) object where the content depends on the object's type.

pattern

A regular expression according to the rules for the Java [Pattern](#) class.

pattern-template

Template for referencing capturing groups in a pattern by using `$n`, where `n` is the index number of the capturing group starting from zero.

For example, if the pattern is `\w+\s*=\s*(\w)+`, the pattern-template is `$1`, and the text to match is `key = value`, the pattern-template yields `value`.

reference

References an object in the following ways:

- An inline configuration object, where the name is optional.
- A configuration expression that is a string or contains variable elements that evaluate to a string, where the string is the name of an object declared in the heap.

For example, the following `temporaryStorage` object takes the value of the system property `storage.ref`, which must be a string equivalent to the name of an object defined in the heap:

```
{
  "temporaryStorage": "${system['storage.ref']}"
}
```

secret-id

String that references a secret managed by the Commons Secrets API, as described in [Secrets](#).

The secret ID must conform to the following regex pattern: `Pattern.compile("(\\.[a-zA-Z0-9])*");`

string

[JSON](#)  string.

url

String representation for a resource available via the Internet. For more information, refer to [Uniform Resource Locators \(URL\)](#) .

Required PingGateway configuration

PingGateway requires the following configuration:

- [AdminHttpApplication](#) (`admin.json`)
- [GatewayHttpApplication](#) (`config.json`)
- [Heap objects](#)
- [Configuration settings](#)
- [System properties](#)

AdminHttpApplication (admin.json)

The AdminHttpApplication serves requests on the administrative route, such as the creation of routes and the collection of monitoring information. The administrative route and its subroutes are reserved for administration endpoints.

The configuration is loaded from a JSON-encoded file, expected at `$HOME/.openig/config/admin.json`. Objects configured in `admin.json` cannot be used by `config.json` or any PingGateway routes.

Default objects

PingGateway provides default objects in `admin.json`. To override a default object, configure an object with the same name in `admin.json`.

Configure default objects in `admin.json` and `config.json` separately. An object configured in `admin.json` with the same name as an object configured in `config.json` isn't the same object.

AuditService

Records no audit events. The default AuditService is `NoOpAuditService`. Learn more from [NoOpAuditService](#).

CaptureDecorator

Captures requests and response messages. The default CaptureDecorator is named `capture`, and uses the default settings given in [CaptureDecorator](#).

When a capture point for the default CaptureDecorator is defined in a route, for example, when `"capture: "all"` is set as a top-level attribute of the JSON, log messages for requests and responses passing through the route are written to a log file in `$HOME/.openig/logs`.

When no capture point is defined in a route, only exceptions thrown during request or response processing are logged.

By default, request and response contexts and entities aren't captured. Do one of the following to capture information:

- Override the default capture decorator declaration, and set `captureEntity` to `true`.
- Declare another `CaptureDecorator` object with an appropriate configuration and use it at your capture points.

The capture decorator logs information about the HTTP request and response messages, along with their respective headers.

ClientHandler

Communicates with third-party services. Learn more from [ClientHandler](#).

ForgeRockClientHandler

Sends ForgeRock Common Audit transaction IDs when communicating with protected applications. The default `ForgeRockClientHandler` is a Chain, composed of a `TransactionIdOutboundFilter` and a `ClientHandler`.

IssuerRepository (deprecated)

A repository of Issuers declared in the heap. To overwrite the default issuer, configure a local `IssuerRepository` with the name `IssuerRepository`. To create a new `IssuerRepository` containing a subset of Issuers, configure a local `IssuerRepository` with a different name.



Important

The [IssuerRepository \(deprecated\)](#) is deprecated. For issuers known in advance, add their settings to the [ClientRegistration](#). For discovery, configure an [AuthorizationCodeOAuth2ClientFilter](#) "discoveryHandler".

ProxyOptions

A proxy to which a [ClientHandler](#) or [ReverseProxyHandler](#) can submit requests, and an [AmService](#) can submit Websocket notifications. For more information, refer to [ProxyOptions](#).

ReverseProxyHandler

Communicates with third-party services. For more information, refer to [ReverseProxyHandler](#).

ScheduledExecutorService

Specifies the number of threads in a pool.

TemporaryStorage

Manages temporary buffers. For more information, refer to [TemporaryStorage](#).

TimerDecorator

Records time spent within filters and handlers. The default `TimerDecorator` is named `timer`. For more information, refer to [TimerDecorator](#).

TracingDecorator

Pushes traces to an [OpenTelemetry](#) service.



Important

This feature has [Evolving](#) interface stability. It is subject to change without notice, even in a minor or maintenance release.

Use this to decorate the following:

- [PingGateway access token resolvers](#)
- [AmService](#)
- [AuditService](#)
- [PingGateway filters](#)
- [PingGateway handlers](#)

The default [TracingDecorator](#) is named `tracing`. PingGateway traces include Vert.x traces where applicable.

TransactionIdOutboundFilter

Inserts the ID of a transaction into the header of a request.

Provided objects (deprecated)

PingGateway creates the following objects when a filter with the name of the object is declared in `admin.json`.



Important

Overriding these objects by declaring objects with the same names in the heap is deprecated; define them [in the configuration](#) instead.

"ApiProtectionFilter"

A filter to protect administrative APIs on reserved routes. By default, only the loopback address can access reserved routes.

"MetricsProtectionFilter"

A filter to protect the monitoring endpoints. By default, the Prometheus Scrape Endpoint and Common REST Monitoring Endpoint (deprecated) are open and accessible; no special credentials or privileges are required to access the monitoring endpoints.

"StudioProtectionFilter"

A filter to protect the Studio endpoint when PingGateway is running in development mode. When PingGateway is running in development mode, by default, the Studio endpoint is open and accessible.

Usage



Important

Restart PingGateway after making configuration changes to load the new settings.

```

{
  "heap": [ object, ... ],
  "adminConnector": {
    "port": configuration expression<number>,
    "host": configuration expression<string>,
    "tls": ServerTlsOptions reference,
    "vertex": object,
    "maxTotalHeadersSize": configuration expression<integer>
  },
  "connectors": [ {
    "port": [ configuration expression<number>, ... ],
    "host": configuration expression<string>,
    "tls": ServerTlsOptions reference,
    "vertex": object,
    "maxTotalHeadersSize": configuration expression<integer>
  }, ... ],
  "vertex": object,
  "gatewayUnits": configuration expression<number>,
  "adminMaxBodyLength": configuration expression<number>,
  "maxBodyLength": configuration expression<number>,
  "mode": configuration expression<enumeration>,
  "prefix": configuration expression<string>, // deprecated
  "properties": object,
  "temporaryDirectory": configuration expression<string>,
  "temporaryStorage": TemporaryStorage reference,
  "pidFileMode": configuration expression<enumeration>,
  "preserveOriginalQueryString": configuration expression<boolean>,
  "session": AsyncSessionManager reference,
  "streamingEnabled": configuration expression<boolean>,
  "serveDeprecatedPrometheusEndpoint": configuration expression<boolean>,
  "openTelemetry": {
    "tracing": {
      "enabled": configuration expression<boolean>,
      "resourceAttributes": object,
      "exporter": {
        "type": "otlp",
        "config": {
          "endpoint": configuration expression<string>,
          "connectionTimeout": configuration expression<duration>,
          "headers": object,
          "proxyOptions": ProxyOptions reference,
          "retries": {
            "enabled": configuration expression<boolean>,
            "maxAttempts": configuration expression<number>,
            "maxBackoff": configuration expression<duration>,
            "initialBackoff": configuration expression<duration>,
            "backoffMultiplier": configuration expression<number>
          },
          "timeout": configuration expression<duration>,
          "tls": ClientTlsOptions reference
        },
      },
    },
    "batch": {
      "enabled": configuration expression<boolean>,
      "compressionMethod": configuration expression<enumeration>,
      "scheduleDelay": configuration expression<duration>,
      "maxQueueSize": configuration expression<number>,
      "maxExportBatchSize": configuration expression<number>,
      "exporterTimeout": configuration expression<duration>,
      "exportUnsampledSpans": configuration expression<boolean>
    }
  }
}

```

```
    },
    "sampler": {
      "type": configuration expression<string>,
      "ratio": configuration expression<number>
    },
    "spanLimits": {
      "maxNumberOfAttributesPerEvent": configuration expression<number>,
      "maxAttributeValueLength": configuration expression<number>,
      "maxNumberOfAttributes": configuration expression<number>,
      "maxNumberOfLinks": configuration expression<number>,
      "maxNumberOfEvents": configuration expression<number>,
      "maxNumberOfAttributesPerLink": configuration expression<number>
    }
  },
  "apiProtectionFilter": object,
  "metricsProtectionFilter": object,
  "studioProtectionFilter": object
}
```

Properties

heap

"heap" : array of *objects*, optional

The *heap* object configuration.

adminConnector

"adminConnector" : *object*, optional

Port configuration for administrative traffic.

The following example requires administrative connections over HTTPS on port 9443 from the same computer (*localhost*):

```
{
  "adminConnector": {
    "host": "localhost",
    "port": 9443,
    "tls": "ServerTlsOptions-1"
  }
}
```

By default, PingGateway reserves all paths starting with the (deprecated) prefix */openig* for administrative use. When you define an "adminConnector" , PingGateway no longer uses the prefix in paths to administrative endpoints:

Administrative endpoints

Default path	Path with "adminConnector" settings
<i>/openig/api/info</i>	<i>/api/info</i>

Default path	Path with "adminConnector" settings
/openig/health/liveness	/health/liveness
/openig/health/readiness	/health/readiness
/openig/health/startup	/health/startup
/openig/metrics/prometheus/0.0.4	/metrics/prometheus/0.0.4
/openig/ping	/ping

port: configuration expression<number>, required

The port where PingGateway listens for administrative connections.

Don't reuse this port when setting port numbers for "connectors" .

host: configuration expression<string>, optional

The hostname where PingGateway listens for administrative connections.

If this isn't "localhost" and you intend to permit connections from other systems, set an "apiProtectionFilter" in admin.json to allow access. For example, permit connections from systems in the private network address range 192.168.0.0 – 192.168.255.255 :

```

{
  "apiProtectionFilter": {
    "type": "AllowOnlyFilter",
    "config": {
      "rules": [
        {
          "name": "AdminAccessFromPrivateNetwork",
          "from": [
            {
              "ip": {
                "list": [
                  "192.168.0.0/16"
                ]
              }
            }
          ],
          "destination": [
            {
              "hosts": [
                "ig.example.com"
              ],
              "ports": [
                "9444"
              ],
              "methods": [
                "POST",
                "GET"
              ],
              "paths": [
                "/*"
              ]
            }
          ]
        }
      ]
    }
  },
  "failureHandler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 403,
      "headers": {
        "Content-Type": [
          "text/html; charset=UTF-8"
        ]
      },
      "entity": "<html><p>Administrative access denied</p></html>"
    }
  }
}

```

Default: **0.0.0.0** (listen on all network interfaces)

tls: *ServerTlsOptions* [reference](#), *optional*

Configure [ServerTlsOptions](#) for connections to TLS-protected endpoints. Define the object inline or in the heap.

Default: Connections to TLS-protected endpoints aren't configured.

vertx: *object, optional*

Vert.x-specific configuration for administrative connections.

Learn more about Vert.x options in [HttpServerOptions](#).

For properties where PingGateway provides its own first-class configuration, the PingGateway configuration option takes precedence over Vert.x options configured in `vertx`.

Vert.x values are evaluated as configuration expressions.

The following Vert.x configuration options are disallowed server-side:

- `port`
- `useAlpn`
- `ssl`
- `enabledCipherSuites`
- `enabledSecureTransportProtocols`
- `jdkSslEngineOptions`
- `keyStoreOptions`
- `openSslEngineOptions`
- `pemKeyCertOptions`
- `pemTrustOptions`
- `pfxKeyCertOptions`
- `pfxTrustOptions`
- `trustStoreOptions`
- `clientAuth`

The following Vert.x configuration options are deprecated server-side:

- `maxHeaderSize`
- `initialSettings:maxHeaderListSize`
- `host`

Use `adminConnector:maxTotalHeadersSize` instead of `vertx.maxHeaderSize` or `vertx.initialSettings.maxHeaderListSize`.

maxTotalHeadersSize: *integer, optional*

The maximum size in bytes for the sum of all request headers. When the request headers exceed this limit, PingGateway returns an HTTP 431 error.

Default: 8 192 bytes

connectors

"connectors" : array of [objects](#), required

Server port configuration, when PingGateway is acting *server-side*.

Note

When an application sends requests to or requests services from PingGateway, PingGateway is server-side. PingGateway serves the application acting as a client.

port: *array of configuration expression<[numbers](#)>, required*

One or more ports where PingGateway listens for client application connections.

When more than one port is defined, PingGateway listens on each port.

Don't reuse these ports when setting the [port for the](#) "adminConnector" .

host: *configuration expression<[string](#)>, optional*

The hostname where PingGateway listens for administrative connections.

Default: `0.0.0.0` (listen on all network interfaces)

tls: *[ServerTlsOptions reference](#), optional*

Configure options for connections to TLS-protected endpoints based on [ServerTlsOptions](#). Define the object inline or in the heap.

Default: Connections to TLS-protected endpoints aren't configured.

vertx: *[object](#), optional*

Vert.x-specific configuration for this connector when PingGateway is acting *server-side*. When PingGateway is acting *client-side*, configure the `vertx` property of a [ClientHandler](#) or [ReverseProxyHandler](#).

Learn more about Vert.x options in [HttpServerOptions](#) .

For properties where PingGateway provides its own first-class configuration, Vert.x configuration options are disallowed, and the PingGateway configuration option takes precedence over Vert.x options configured in `vertx` .

Vert.x values are evaluated as configuration expressions.

The following Vert.x configuration options are disallowed server-side:

- `port`
- `useAlpn`
- `ssl`
- `enabledCipherSuites`
- `enabledSecureTransportProtocols`

- `jdkSslEngineOptions`
- `keyStoreOptions`
- `openSslEngineOptions`
- `pemKeyCertOptions`
- `pemTrustOptions`
- `pfxKeyCertOptions`
- `pfxTrustOptions`
- `trustStoreOptions`
- `clientAuth`

The following Vert.x configuration options are deprecated server-side:

- `maxHeaderSize`
- `initialSettings:maxHeaderListSize`
- `host`

Use `connectors:maxTotalHeadersSize` instead of `vertx.maxHeaderSize` or `vertx.initialSettings.maxHeaderListSize`.

The following example configures connectors on ports 8080 and 8443 when PingGateway is acting server-side:

```
{
  "connectors": [{
    "port": 8080,
    "vertx": {
      "maxWebSocketFrameSize": 128000,
      "maxWebSocketMessageSize": 256000,
      "compressionLevel": 4
    }
  },
  {
    "port": 8443,
    "tls": "ServerTlsOptions-1"
  }
  ]
}
```

maxTotalHeadersSize: *integer, optional*

The maximum size in bytes of the sum of all request headers. When the request headers exceed this limit, PingGateway returns an HTTP 431 error.

The following example configures HTTP/2 connections on port 7070 when PingGateway is acting server-side. The configuration allows PingGateway to accept HTTP/2 requests with large headers:


```
{
  "connectors": [
    {
      "port": 7070,
      "maxTotalHeadersSize": 16384
    }
  ]
}
```

Default: 8 192 bytes

vertex

vertex : *object*, optional

This is the Vert.x-specific configuration used to more finely tune Vert.x instances. Vert.x values are evaluated as configuration expressions.

Use the Vert.x options described in [VertexOptions](#) with the following exceptions:

- **metricsOptions** : Not used
- **metricsEnabled** : Enable Vertx metrics. Default: `true`.

Learn more in [Monitor Vert.x metrics](#).

PingGateway proxies all WebSocket subprotocols by default. To proxy specific WebSocket subprotocols only, list them as follows:

```
"vertex": {
  "websocketSubProtocols": ["v1.notifications.forgerock.org", ... ]
}
```

gatewayUnits

"gatewayUnits" : *configuration expression<number>*, optional

The number of parallel instances of PingGateway to bind to an event loop. All instances listen on the same ports.

Default: The number of cores available to the JVM.

adminMaxBodyLength

"adminMaxBodyLength" : *configuration expression<number>*, optional

Maximum body size in bytes for HTTP requests to the administration port.

This takes effect only when **"streamingEnabled"** is `false`.

Default: `-1` (unlimited)

maxBodyLength

"maxBodyLength" : *configuration expression<number>*, optional

Maximum body size in bytes for HTTP requests from client applications.

This takes effect only when `"streamingEnabled"` is `false`.

Default: `-1` (unlimited)

mode

`mode` : configuration expression<enumeration>, optional

Set the PingGateway mode to `development` or `production`. The value is not case-sensitive.

If `mode` is not set, PingGateway resolves the provided configuration token `ig.run.mode` at startup to define the run mode.

Learn more in [PingGateway operating modes](#).

Default: `production`

prefix (deprecated)

`"prefix"` : configuration expression<string>, optional

The base of the route for administration requests. This route and its subroutes are reserved for administration endpoints.



Important

This property is deprecated. Define an `"adminConnector"` instead.

Default: `openig`

properties

`"properties"` : [object](#), optional

Configuration parameters declared as property variables for use in the configuration. Learn more in [PingGateway route properties](#).

Default: No properties are defined.

temporaryDirectory

`"temporaryDirectory"` : configuration expression<string>, optional

Directory containing temporary storage files.

Set this property to store temporary files in a different directory, for example:

```
{
  "temporaryDirectory": "/path/to/my/temporary/directory"
}
```

Default: `$HOME/.openig/tmp` (on Windows, `%appdata%\OpenIG\tmp`)

temporaryStorage

"temporaryStorage" : *TemporaryStorage* [reference](#), optional

The **TemporaryStorage** object to buffer content during processing.

Provide the name of a TemporaryStorage object defined in the heap or an inline TemporaryStorage configuration object.

Incoming requests use the temporary storage buffer as follows:

- Only used when **streamingEnabled** is **false**.
- The request is loaded into the PingGateway storage defined in **temporaryStorage** before it enters the chain.
- If the content length of the request is more than the buffer limit, PingGateway returns an **HTTP 413 Payload Too Large**.

Default: Use the heap object named **TemporaryStorage**. Otherwise, use an internally created TemporaryStorage object named **TemporaryStorage** with default settings for a TemporaryStorage object.

pidFileMode

"pidFileMode" : *configuration expression*<[enumeration](#)>, optional

Mode to allow or disallow startup if there is an existing PID file. Use one of the following values:

- **fail** : Startup fails if there is an existing PID file.
- **override** : Startup is allowed if there is an existing PID file. PingGateway removes the existing PID file and creates a new one during startup.

Default: **fail**

preserveOriginalQueryString

"preserveOriginalQueryString" : *configuration expression*<[boolean](#)>, optional

Process query strings in URLs by applying or not applying a decode/encode process to the whole query string.

The following characters are disallowed in query string URL components: `"`, `{`, `}`, `<`, `>`, (space), and `|`. Learn more about which query string characters require encoding in [Uniform Resource Identifier \(URI\): Generic Syntax](#).

- **true** : Preserve query strings as they are presented.

Select this option if the query string must not change during processing, for example, in signature verification.

If a query string contains a disallowed character, the request returns HTTP 400 Bad Request.

- **false** : Tolerate disallowed characters in query string URL components by applying a decode/encode process to the whole query string.

Select this option when a user agent or client produces query searches with disallowed characters. PingGateway transparently encodes the disallowed characters before forwarding requests to the protected application.

Characters in query strings are transformed as follows:

- Allowed characters aren't changed. For example, **sep=a** is not changed.

- Percent-encoded values are re-encoded when the decoded value is an allowed character. For example, `sep=%27` is changed to `sep='` because `'` is an allowed character.
- Percent-encoded values aren't changed when the decoded value is a disallowed character. For example, `sep=%22` is not changed because `"` is a disallowed character.
- Disallowed characters are encoded. For example, `sep="` is changed to `sep=%22` because `"` is a disallowed character.

Default: `false`

session

`"session"` : *AsyncSessionManager* [reference](#), optional

An [InMemorySessionManager](#) (stateful sessions) or [JwtSessionManager](#) (stateless sessions).

Learn more in [PingGateway sessions](#).

Default: [InMemorySessionManager](#) with default values

streamingEnabled

`"streamingEnabled"` : *configuration expression* [boolean](#), optional

A flag to manage content:

- `true` : PingGateway streams the content of HTTP requests and responses. The content is available for processing bit-by-bit, as soon as it is received.
- `false` : PingGateway buffers the content of HTTP requests and responses into the storage defined in `temporaryStorage`. The content is available for processing only after it has all been received.

When this property is `true`, consider the following requirements to prevent PingGateway from blocking an executing thread to wait for streamed content:

- Write runtime expressions that consume streamed content with `#` instead of `$`. Learn more in the section on [runtime expressions](#).
- In scripts and Java extensions, never use a `Promise` blocking method, such as `get()`, `getOrThrow()`, or `getOrThrowUninterruptibly()` to obtain the response. Learn more in [PingGateway scripts](#).

Note

When `"streamingEnabled": true`:

- A [CaptureDecorator](#) with `"captureEntity": true` decorating a component interrupts streaming for the captured request or response until the whole entity is captured.
- For a client sharing connections to PingGateway, for example, because the client uses HTTP pipelining, any error consuming a chunked response causes PingGateway to reset (close) the client connection. This affects all requests associated with the connection.

Default: `false`

serveDeprecatedPrometheusEndpoint

"serveDeprecatedPrometheusEndpoint": *configuration expression*<[boolean](#)>, optional

A flag to enable or disable the deprecated Prometheus metrics endpoint at `/metrics/prometheus`:

- `false` : Disable the deprecated Prometheus Scrape Endpoint
- `true` : Enable the deprecated Prometheus Scrape Endpoint

Default: `false`

openTelemetry

"openTelemetry": *object*, optional

Configure how to push traces to an [OpenTelemetry](#) service. When you use it with other applications with OpenTelemetry support, the service helps you analyze the flows through PingGateway and the other applications to understand performance and system behavior.



Important

This feature has [Evolving](#) interface stability. It is subject to change without notice, even in a minor or maintenance release.

"tracing": *object*, required

PingGateway can push traces to an OpenTelemetry Protocol (OTLP) endpoint over HTTP where you collect and analyze system trace data. By default, this optional feature is disabled. To push traces to an OpenTelemetry service, you must at least enable it and set the decoration `"tracing": true` on routes or objects of interest to enable additional traces.

The trace data and span content have [Evolving](#) interface stability. It is subject to change without notice, even in a minor or maintenance release.

The following configuration enables PingGateway to push traces to `http://localhost:4318/v1/traces`:

```
{
  "openTelemetry": {
    "tracing": {
      "enabled": true
    }
  }
}
```

"enabled": *configuration expression*<[boolean](#)>, optional

Set to `true` to enable OpenTelemetry tracing.

Default: `false`

"resourceAttributes": *object*, optional

A map of additional resource attributes for processing traces. Learn more in the OpenTelemetry documentation about [Semantic Attributes with SDK-provided Default Value](#).

For example, if there are multiple PingGateway instances in a deployment, set the `"service.instance.id"` resource attribute differently for each one to distinguish between them:

```
{
  "resourceAttributes": {
    "service.instance.id": "gateway1"
  }
}
```

"exporter": *object, optional*

Configuration for the exporter, which pushes traces to the OpenTelemetry service.

"type": *configuration expression<string>, optional*

Set to `otlp` for OpenTelemetry Protocol (OTLP) support, which is the only supported protocol at this time.

Default: `otlp`

"config": *object, optional*

Endpoint and timeout configuration:

- **"endpoint" : *configuration expression<string>, optional***

The endpoint to publish traces to.

For HTTPS, PingGateway trusts the default JVM CAs. To override this, set the `-Djavax.net.ssl.trustStore` and associated JVM settings when starting PingGateway. Learn more about the optional settings in the [Java Secure Socket Extension \(JSSE\) Reference Guide](#).

PingGateway doesn't support TLS configuration for the tracing endpoint at this time.

Default: `http://localhost:4318/v1/traces`

- **"connectionTimeout" : *configuration expression<duration>, optional***

Time out a connection to the endpoint after this duration.

Default: 10 seconds.

- **"headers" : *object, optional***

Map of additional headers to include in the export span request.

The following example sets the authorization header, `Authorization: Bearer ${bearer.token}`:

```
"headers": { "Authorization": "Bearer ${bearer.token}" }
```

- **"proxyOptions" : *ProxyOptions reference, optional***

A [proxy](#) to send traces to.

Default: Use the system proxy settings.

- **"retries"** : *object, optional*

This defines a retry policy for the export span requests.

Default: Enabled

- **"enabled"** : *configuration expression<[boolean](#)>, optional*

Retry failed requests.

Default: `true`

- **"maxAttempts"** : *configuration expression<[number](#)>, optional*

Maximum number of retries.

Default: 5

- **"initialBackoff"** : *configuration expression<[duration](#)>, optional*

How long to wait before the first retry.

Default: 1 second

- **"maxBackoff"** : *configuration expression<[duration](#)>, optional*

Maximum wait time between retries.

Default: 5 seconds

- **"backoffMultiplier"** : *configuration expression<[number](#)>, optional*

Multiplier for the backoff wait time before retries.

Default: 1.5

- **"timeout"** : *configuration expression<[duration](#)>, optional*

Time out a request to publish data to the endpoint after this duration.

Default: 10 seconds.

- **"tls"** : *ClientTlsOptions [reference](#), optional*

Configure [ClientTlsOptions](#) for connections to a TLS-protected OpenTelemetry service. Define the object inline or in the heap.

Default: Rely on the JVM settings to trust server certificates.

"batch": object, optional

Enable and configure batch processing for trace data.

- **"enabled"** : *configuration expression<[boolean](#)>, optional*

Leave batch processing enabled in deployment.

Default: `true`

- `"compressionMethod"` : *configuration expression<enumeration>, optional*

Method used to compress trace data; either `gzip` or `none`.

Default: `gzip`

- `"scheduleDelay"` : *configuration expression<duration>, optional*

Maximum interval between sending batches of trace data.

Default: 50 seconds

- `"maxQueueSize"` : *configuration expression<number>, optional*

Maximum number of spans to queue before dropping them.

Default: 1024

- `"maxExportBatchSize"` : *configuration expression<number>, optional*

Maximum number of spans in a batch.

Default: 256

- `"exporterTimeout"` : *configuration expression<duration>, optional*

Time out a data exporter after this duration.

Default: 30 seconds

- `"exportUnsampledSpans"` : *configuration expression<boolean>, optional*

Whether to report on unsampled spans.

Default: `false`

`"sampler"`: object, optional

Configuration for sampling spans.

`"type"`: configuration expression<string>, optional

The sampler strategy to use is one of the following:

- `"alwaysOn"` : Send every span for processing.
- `"alwaysOff"` : Never send any span for processing.
- `"traceIdRatio"` : Sample the specified ratio of spans, deterministically based on the trace IDs of the spans.
- `"parentBasedAlwaysOn"` : Always send the span for processing if the parent span was sampled. (Default)
- `"parentBasedAlwaysOff"` : Never send the span for processing if the parent span was sampled.

- `"parentBasedTraceIdRatio"` : Send the specified ratio of spans for processing if the parent span was sampled.

"ratio": *configuration expression*<number>, optional

For ratio-based types, a percentage of spans to process.

Default: 50 (percent)

"spanLimits": *object*, optional

Configuration for limits enforced when recording spans.

"maxNumberOfAttributesPerEvent": *configuration expression*<number>, optional

The maximum number of metadata items (attributes) attached to a span per event. An event is an annotation to span at a particular, meaningful point in time during the span's duration.

Default: 256

"maxAttributeValueLength": *configuration expression*<number>, optional

The maximum number of characters in a string attribute value.

Default: 256

"maxNumberOfAttributes": *configuration expression*<number>, optional

The maximum number of attributes per span.

Default: 256

"maxNumberOfLinks": *configuration expression*<number>, optional

The maximum number of links per span. Links associate the current span with one or more other spans.

Default: 256

"maxNumberOfEvents": *configuration expression*<number>, optional

The maximum number of events per span.

Default: 256

"maxNumberOfAttributesPerLink": *configuration expression*<number>, optional

The maximum number of attributes per link.

Default: 256

apiProtectionFilter

"apiProtectionFilter" : *object*, optional

A filter to protect administrative APIs on reserved routes.

Learn more in the section on [setting up UMA](#) and in [Reserved routes](#).

Default: only the loopback address can access reserved routes

metricsProtectionFilter

"metricsProtectionFilter" : *object, optional*

A filter to protect the monitoring endpoints.

Default: the Prometheus Scrape Endpoint and Common REST Monitoring Endpoint (deprecated) are open and accessible; no special credentials or privileges are required to access the monitoring endpoints.

Find an example in [Protect monitoring endpoints](#).

studioProtectionFilter

"studioProtectionFilter" : *object, optional*

A filter to protect the Studio endpoint when PingGateway is running in development mode.

Learn more in [Restrict access to Studio](#).

Default: the Studio endpoint is open and accessible when running PingGateway in development mode

Default configuration

When your configuration doesn't include an `admin.json` file, PingGateway provides the following `admin.json` by default:

```
{
  "connectors": [ { "port" : 8080 } ]
}
```

Source: [admin-sa.json](#)

By default, PingGateway implicitly defines 8085 as the `adminConnector` port, which is equivalent to `"adminConnector": { "port": 8085 }`. Also, by default, PingGateway no longer uses the (deprecated) prefix in paths to administrative endpoints. Learn more in [adminConnector](#).

More information

[org.forgerock.openig.http.AdminHttpApplication](#)

config.json)">

GatewayHttpApplication (config.json)

The GatewayHttpApplication is the entry point for all incoming gateway requests. It is responsible for initializing a heap of objects, described in [Heap objects](#), and providing the main Handler that receives all the incoming requests.

The configuration is loaded from a JSON-encoded file, expected by default at `$HOME/.openig/config/config.json`. Objects configured in `config.json` can be used by `config.json` and any PingGateway route. They cannot be used by `admin.json`.

If you provide a `config.json`, the PingGateway configuration is loaded from that file. If there is no file, the default configuration is loaded.

Routes endpoint

The endpoint is defined by the presence and content of `config.json`, as follows:

- When `config.json` isn't provided, the routes endpoint includes the name of the main router in the default configuration, `_router`.
- When `config.json` is provided with an unnamed main router, the routes endpoint includes the main router name `router-handler`.
- When `config.json` is provided with a named main router, the routes endpoint includes the provided name or the transformed, URL-friendly name.

Studio deploys and undeploys routes through a main router named `_router`, which is the name of the main router in the default configuration. If you use a custom `config.json`, make sure it contains a main router named `_router`.

Default objects

PingGateway creates objects by default in `config.json`. To override a default object, configure an object with the same name in `config.json`.

Configure default objects in `config.json` and `admin.json` separately. An object configured in `config.json` with the same name as an object configured in `admin.json` isn't the same object.

BaseUriDecorator

A decorator to override the scheme, host, and port of the existing request URI. The default BaseUriDecorator is named `baseURI`. Learn more in [BaseUriDecorator](#).

AuditService

Records no audit events. The default AuditService is `NoOpAuditService`. Learn more from [NoOpAuditService](#).

CaptureDecorator

Captures requests and response messages. The default CaptureDecorator is named `capture`, and uses the default settings given in [CaptureDecorator](#).

When a capture point for the default CaptureDecorator is defined in a route, for example, when `"capture: "all"` is set as a top-level attribute of the JSON, log messages for requests and responses passing through the route are written to a log file in `$HOME/.openig/logs`.

When no capture point is defined in a route, only exceptions thrown during request or response processing are logged.

By default, request and response contexts and entities aren't captured. Do one of the following to capture information:

- Override the default capture decorator declaration, and set `captureEntity` to `true`.
- Declare another CaptureDecorator object with an appropriate configuration and use it at your capture points.

The capture decorator logs information about the HTTP request and response messages, along with their respective headers.

ClientHandler

Communicates with third-party services. Learn more from [ClientHandler](#).

ForgeRockClientHandler

Sends ForgeRock Common Audit transaction IDs when communicating with protected applications. The default ForgeRockClientHandler is a Chain, composed of a TransactionIdOutboundFilter and a ClientHandler.

IssuerRepository (deprecated)

A repository of Issuers declared in the heap. To overwrite the default issuer, configure a local IssuerRepository with the name `IssuerRepository`. To create a new IssuerRepository containing a subset of Issuers, configure a local IssuerRepository with a different name.



Important

The [IssuerRepository \(deprecated\)](#) is deprecated. For issuers known in advance, add their settings to the [ClientRegistration](#). For discovery, configure an [AuthorizationCodeOAuth2ClientFilter](#) "discoveryHandler".

ProxyOptions

A proxy to which a [ClientHandler](#) or [ReverseProxyHandler](#) can submit requests, and an [AmService](#) can submit Websocket notifications. For more information, refer to [ProxyOptions](#).

ReverseProxyHandler

Communicates with third-party services. For more information, refer to [ReverseProxyHandler](#).

ScheduledExecutorService

Specifies the number of threads in a pool.

TemporaryStorage

Manages temporary buffers. For more information, refer to [TemporaryStorage](#).

TimerDecorator

Records time spent within filters and handlers. The default TimerDecorator is named `timer`. For more information, refer to [TimerDecorator](#).

TracingDecorator

Pushes traces to an [OpenTelemetry](#)  service.



Important

This feature has [Evolving](#)  interface stability. It is subject to change without notice, even in a minor or maintenance release.

Use this to decorate the following:

- [PingGateway access token resolvers](#)

- [AmService](#)
- [AuditService](#)
- [PingGateway filters](#)
- [PingGateway handlers](#)

The default [TracingDecorator](#) is named `tracing`. PingGateway traces include Vert.x traces where applicable.

TransactionIdOutboundFilter

Inserts the ID of a transaction into the header of a request.

Usage



Important

Restart PingGateway after making configuration changes to load the new settings.

```
{
  "handler": Handler reference,
  "heap": [ object, ... ],
  "properties": object,
  "session": AsyncSessionManager reference,
  "temporaryStorage": TemporaryStorage reference
}
```

Properties

"handler": *Handler [reference](#), required*

The [Handler](#) to which PingGateway dispatches requests.

Provide the name of a Handler object defined in the heap or an inline Handler configuration object.

"heap": *array of [objects](#), optional*

The [heap object configuration](#).

"properties": *[object](#), optional*

Configuration parameters declared as property variables for use in the configuration. Learn more in [PingGateway route properties](#).

Default: No properties are defined.

"session": *AsyncSessionManager [reference](#), optional*

An [InMemorySessionManager](#) (stateful sessions) or [JwtSessionManager](#) (stateless sessions).

Default: [InMemorySessionManager](#) with default values

Learn more in [PingGateway sessions](#).

"temporaryStorage": *TemporaryStorage* [reference](#), optional

The `TemporaryStorage` object to buffer content during processing.

Provide the name of a `TemporaryStorage` object defined in the heap or an inline `TemporaryStorage` configuration object.

Incoming requests use the temporary storage buffer as follows:

- Only used when `streamingEnabled` is `false`.
- The request is loaded into the PingGateway storage defined in `temporaryStorage` before it enters the chain.
- If the content length of the request is more than the buffer limit, PingGateway returns an `HTTP 413 Payload Too Large`.

Default: Use the heap object named `TemporaryStorage`. Otherwise, use an internally created `TemporaryStorage` object named `TemporaryStorage` with default settings for a `TemporaryStorage` object.

Example configuration files**Default configuration**

When your configuration doesn't include a `config.json` file, the following configuration is provided by default.

```

{
  "heap": [
    {
      "name": "_router",
      "type": "Router",
      "config": {
        "scanInterval": "&{ig.router.scan.interval|10 seconds}",
        "directory": "${openig.configDirectory}/routes",
        "defaultHandler": {
          "type": "DispatchHandler",
          "config": {
            "bindings": [
              {
                "condition": "${request.method == 'GET' and request.uri.path == '/'}",
                "handler": {
                  "type": "WelcomeHandler"
                }
              },
              {
                "condition": "${request.uri.path == '/'}",
                "handler": {
                  "type": "StaticResponseHandler",
                  "config": {
                    "status": 405,
                    "reason": "Method Not Allowed"
                  }
                }
              },
              {
                "handler": {
                  "type": "StaticResponseHandler",
                  "config": {
                    "status": 404,
                    "reason": "Not Found"
                  }
                }
              }
            ]
          }
        }
      }
    },
    {
      "handler": "_router"
    }
  ]
}

```

Source: [default-config.json](#)

Notice the following features of the default configuration:

- The handler contains a main router named `_router`. When PingGateway receives an incoming request, `_router` routes the request to the first route in the configuration whose condition is satisfied.
- If the request doesn't satisfy the condition of any route, it is routed to the defaultHandler. If the request is to access the PingGateway welcome page, PingGateway dispatches the request. Otherwise, PingGateway returns an HTTP status 404 (Resource not found), because the requested resource doesn't exist.

Example config.json used in the documentation

The following example of `config.json` is used in many of the examples in the documentation:

```
{
  "handler": {
    "type": "Router",
    "name": "_router",
    "capture": "all"
  },
  "heap": [
    {
      "name": "capture",
      "type": "CaptureDecorator",
      "config": {
        "captureEntity": true,
        "_captureContext": true
      }
    }
  ],
  "session": {
    "type": "JwtSessionManager"
  }
}
```

Source: [config.json](#)

Notice the following features of the file:

- The handler contains a main router named `_router`. When PingGateway receives an incoming request, `_router` routes the request to the first route in the configuration whose condition is satisfied.
- The `capture` captures the body of the HTTP request and response.
- The configuration uses stateless sessions. Learn more about session management in [PingGateway sessions](#).

More information

[org.forgerock.openig.http.GatewayHttpApplication](#)

Heap objects

An array of objects created and initialized by heaplet objects. Learn more about the configuration in [Inline and heap objects](#).

Usage

```
{
  "heap": [
    {
      "name": string,
      "type": string,
      "config": {
        type-specific configuration
      }
    }
  ]
}
```

Properties

"name": *string*, *required*

A unique name for an object in the heap.

Routes and other configurations must refer to heap objects by their `name` property.

"type": *string*, *required*

The class name of the heap object.

"config": *object*, *required unless all the fields are optional and the configuration uses only default settings*

The configuration of the heap object. The object configuration must conform to the object class.

More information

[org.forgerock.openig.heap.Heap](https://github.com/forgerock/openig.heap.Heap) 

Configuration settings

Filters, handlers, and other objects whose configuration settings are defined by strings, integers, or booleans, can alternatively be defined by expressions that match the expected type.

For information about expressions, refer to [Expressions](#).

System properties

PingGateway supports the following reserved system properties. The names have special meanings in PingGateway. Use them only for their stated purpose:

`ig.instance.dir`, `IG_INSTANCE_DIR`

The full path to the directory containing configuration and data for the PingGateway instance.

Default: Linux, `$HOME/.openig`; Windows, `%appdata%\OpenIG`

For information about how to use a different location, refer to [Configuration location](#).

org.forgerock.http.TrustTransactionHeader

When this property is `true`, PingGateway trusts all incoming `X-ForgeRock-TransactionId` headers. Monitoring and reporting systems consuming the logs can correlate requests as they traverse multiple servers.

Default: `false`

org.forgerock.http.util.ignoreFormParamDecodingError

When this property is `true`, PingGateway ignores form encoding errors caused by invalid characters and uses encoded values instead.

Default: `false`

org.forgerock.json.jose.jwe.compression.max.decompressed.size.bytes

The maximum size in bytes to which a compressed JWT can be decompressed.

Default: 32 KBytes

org.forgerock.secrets.preferDeterministicEcdsa

When this property is `true` and the following conditions are met, PingGateway signs JWTs with a deterministic Elliptic Curve Digital Signature Algorithm (ECDSA):

- ECDSA is used for signing
- Bouncy Castle is installed

Default: `true`

PingGateway handlers

Handler objects process a request and context and return a response. The way the response is created depends on the type of handler.

- [Chain](#)
- [ClientHandler](#)
- [DispatchHandler](#)
- [ForgeRockClientHandler](#)
- [IdentityAssertionHandler](#)
- [JwkSetHandler](#)
- [PingOneProtectThreatLevelRoutingHandler](#)
- [ResourceHandler](#)
- [ReverseProxyHandler](#)

- [Route](#)
- [Router](#)
- [SamlFederationHandler \(deprecated\)](#)
- [ScriptableHandler](#)
- [SequenceHandler](#)
- [StaticResponseHandler](#)

Chain

Dispatches a request and context to an ordered list of filters, and then finally to a handler.

Filters process the incoming request and context, pass it on to the next filter, and then to the handler. After the handler produces a response, the filters process the outgoing response and context as it makes its way to the client. Note that the same filter can process both the incoming request and the outgoing response but most filters do one or the other.

A Chain can be placed in a configuration anywhere that a handler can be placed.

Unlike ChainOfFilters, Chain finishes by dispatching the request to a handler. For more information, refer to [ChainOfFilters](#).

Usage

```
{
  "name": string,
  "type": "Chain",
  "config": {
    "filters": [ Filter reference, ... ],
    "handler": Handler reference
  }
}
```

Properties

"filters": array of [Filter references](#), required

An array of names of filter objects defined in the heap, and inline filter configuration objects.

The chain dispatches the request to these filters in the order they appear in the array.

See also [PingGateway filters](#).

"handler": [Handler reference](#), required

The [Handler](#) to which the Chain dispatches the request after it has traversed the specified filters.

Provide the name of a Handler object defined in the heap or an inline Handler configuration object.

Example

```
{
  "name": "LoginChain",
  "type": "Chain",
  "config": {
    "filters": [ "LoginFilter" ],
    "handler": "ReverseProxyHandler"
  }
}
```

More information

[org.forgerock.openig.filter.ChainHandlerHeaplet](#)

ClientHandler

Sends requests to third-party services that are accessible through HTTP, and reconstructs the response from the received bytes. A third-party service is one that PingGateway calls for data, such as an HTTP API or AM, or one to which PingGateway submits data. When PingGateway relays a request to a third-party service, PingGateway is acting as a client of the service. PingGateway is *client-side*.

Consider the following comparison of the ClientHandler and ReverseProxyHandler:

	ClientHandler	ReverseProxyHandler
Use this handler to ...	Send requests to third-party services accessed within a route. The service can be AM or an HTTP API. The service can be an HTTP endpoint, such as AM, IDM, PingOne Advanced Identity Cloud, or any custom HTTP API.	Send requests to the final service accessed by a route. The service can be the final downstream application.
If the service doesn't respond in time, this handler ...	Propagates the error through the Promise flow. If the error is not handled within the route, for example, by a FailureHandler, the handler returns a 500 Internal Server Error response.	Stops processing the request, and returns a 502 Bad Gateway response.

When uploading or downloading large files, prevent timeout issues by increasing the value of `soTimeout`, and using a streaming mode, as follows:

Configure the `streamingEnabled` property of [AdminHttpApplication](#).

Usage

```
{
  "name": string,
  "type": "ClientHandler",
  "config": {
    "vertex": object,
    "connections": configuration expression<number>,
    "waitQueueSize": configuration expression<number>,
    "soTimeout": configuration expression<duration>,
    "connectionTimeout": configuration expression<duration>,
    "connectionTimeToLive": configuration expression<duration>,
    "connectionShutdownGracePeriod": configuration expression<duration>,
    "protocolVersion": configuration expression<enumeration>,
    "http2PriorKnowledge": configuration expression<boolean>,
    "proxyOptions": ProxyOptions reference,
    "propagateDisconnection": configuration expression<boolean>,
    "temporaryStorage": TemporaryStorage reference,
    "tls": ClientTlsOptions reference,
    "retries": {
      "enabled": configuration expression<boolean>,
      "condition": runtime expression<boolean>,
      "executor": ScheduledExecutorService reference,
      "count": configuration expression<number>,
      "delay": configuration expression<duration>,
      "runtimeExceptionCondition": runtime expression<boolean>
    },
    "circuitBreaker": {
      "enabled": configuration expression<boolean>,
      "maxFailures": configuration expression<integer>,
      "slidingCounter": {
        "size": configuration expression<number>
      },
      "openDuration": configuration expression<duration>,
      "openHandler": Handler reference,
      "executor": ScheduledExecutorService reference
    }
  }
}
```

Properties

vertex

"vertex": *object*, optional

Vert.x-specific configuration for the handler when PingGateway is *client-side*. When PingGateway is acting server-side, configure the `connectors.vertex` property of `admin.json`.

Note

When PingGateway sends requests to a proxied application or requests services from a third-party application, PingGateway is client-side. PingGateway is acting as a client of the application. The application is acting as a server.

Learn more about Vert.x options in [HttpClientOptions](#).

The `vertx` object is read as a map, and values are evaluated as configuration expressions.

For properties where PingGateway provides its own first-class configuration, Vert.x configuration options are disallowed. The PingGateway configuration option takes precedence over Vert.x options configured in `vertx`. The following Vert.x configuration options are disallowed client-side:

- `alpnVersions`
- `connectTimeout`
- `enabledCipherSuites`
- `enabledSecureTransportProtocols`
- `http2ClearTextUpgrade`
- `idleTimeout`
- `idleTimeoutUnit`
- `keyCertOptions`
- `keyStoreOptions`
- `maxWaitQueueSize`
- `pemKeyCertOptions`
- `pemTrustOptions`
- `pfxKeyCertOptions`
- `pfxTrustOptions`
- `port`
- `protocolVersion`
- `proxyOptions`
- `ssl`
- `trustOptions`
- `trustStoreOptions`
- `useAlpn`
- `verifyHost`

The following example configures the Vert.x configuration when PingGateway is acting client-side:

```
{
  "vertx": {
    "maxWebSocketFrameSize": 128000,
    "maxWebSocketMessageSize": 256000,
    "compressionLevel": 4,
    "maxHeaderSize": 16384
  }
}
```

The following example configures HTTP/2 connections when PingGateway is acting client-side. The configuration allows PingGateway to make HTTP/2 requests with large headers:

```
{
  "vertx": {
    "initialSettings": {
      "maxHeaderListSize": 16384
    }
  }
}
```

connections

"connections" : *configuration expression<number>, optional*

The maximum number of concurrent HTTP connections in the client connection pool.

Default: 64

waitQueueSize

"waitQueueSize": *configuration expression<number>, optional*

The maximum number of outbound requests allowed to queue when no downstream connections are available. Outbound requests received when the queue is full are rejected.

Use this property to limit memory use when there is a backlog of outbound requests, for example, when the protected application or third-party service is slow.

Configure **waitQueueSize** as follows:

- Not set (default): The wait queue is calculated as the square of **connections** .
 - If **connections** isn't configured, then its default of **64** is used, giving the **waitQueueSize** of **4096** .
 - If the square of **connections** exceeds the maximum integer value for the Java JVM, the maximum integer value for the Java JVM is used.
- **-1** : The wait queue is unlimited. Requests received when there are no available connections are queued without limit.
- **0** : There is no wait queue. Requests received when there are no available connections are rejected.
- A value that is less than the square of **connections** :

When the configuration is loaded, the configured value is used. PingGateway generates a warning that the `waitQueueSize` is too small for the `connections` size and recommends a different value.

- A value where `waitQueueSize` plus `connections` exceeds the maximum integer value for the Java JVM:

When the configuration is loaded, the `waitQueueSize` is reduced to the maximum integer value for the Java JVM minus the value of `connections`. PingGateway logs a warning.

Consider the following example configuration of `connections` and `waitQueueSize`:

```
{
  "handler" : {
    "name" : "proxy-handler",
    "type" : "ReverseProxyHandler",
    "MyCapture" : "all",
    "config": {
      "soTimeout": "10 seconds",
      "connectionTimeout": "10 seconds",
      "connections": 64,
      "waitQueueSize": 100
    }
  },
  "baseURI" : "https://app.example.com:8444",
  "condition" : "${find(request.uri.path, '/')}"
}
```

PingGateway can propagate the request to the sample application using 64 connections. When the connections are consumed, up to 100 requests are queued until a connection is freed. Effectively PingGateway can accommodate 164 requests, although user concurrency delay means more may be handled. Requests received when the waitQueue is full are rejected.

Default: Not set

connectionTimeout

`"connectionTimeout"` : *configuration expression<duration>, optional*

Time to wait to establish a connection, expressed as a duration.

Default: 10 seconds

connectionTimeToLive

`"connectionTimeToLive"` : *configuration expression<duration>, optional*

Time before a connection is closed, expressed as a duration.

Default: no limit

connectionShutdownGracePeriod

`"connectionShutdownGracePeriod"` : *configuration expression<duration>, optional*

Time to wait beyond `"connectionTimeToLive"` before shutting down the connection, expressed as a duration.

Default: The value of `"soTimeout"` (default: 10 seconds)

protocolVersion

"protocolVersion" : *configuration expression*<enumeration>, optional

The version of HTTP protocol to use when processing requests:

- HTTP/2 :
 - For HTTP, process requests using HTTP/1.1.
 - For HTTPS, process requests using HTTP/2.
- HTTP/1.1 :
 - For HTTP and HTTPS, process requests using HTTP/1.1.
- Not set (default):
 - For HTTP, process requests using HTTP/1.1.
 - For HTTPS with `alpn` enabled in `ClientTlsOptions`, process requests using HTTP/1.1 with an HTTP/2 upgrade request. If the targeted server can use HTTP/2, the client uses HTTP/2.
 - For HTTPS with `alpn` disabled in `ClientTlsOptions`, process requests using HTTP/1.1 without an HTTP/2 upgrade request.

By default, `alpn` is enabled in `ClientTlsOptions`.

Default: Not set

Note

In HTTP/1.1 request messages, a `Host` header is required to specify the host and port number of the requested resource. In HTTP/2 request messages, the `Host` header isn't available. In scripts or custom extensions that use HTTP/2, use `UriRouterContext.originalUri.host` or `UriRouterContext.originalUri.port` in requests.

http2PriorKnowledge

"http2PriorKnowledge" : *configuration expression*<boolean>, optional

A flag for whether the client should have prior knowledge that the server supports HTTP/2. This property is for cleartext (non-TLS requests) only and is used only when `protocolVersion` is HTTP/2.

- `false` : The client checks whether the server supports HTTP/2 by sending an HTTP/1.1 request to upgrade the connection to HTTP/2:
 - If the server supports HTTP/2, the server upgrades the connection to HTTP/2 and later requests are processed over HTTP/2.
 - If the server doesn't support HTTP/2, the connection isn't upgraded and later requests are processed over HTTP/1.
- `true` : The client doesn't check that the server supports HTTP/2. The client sends HTTP/2 requests to the server, assuming that the server supports HTTP/2.

Default: `false`

proxyOptions

"proxyOptions" : *ProxyOptions* [reference](#), optional

A proxy server to which requests can be submitted. Use this property to relay requests to other parts of the network. For example, use it to submit requests from an internal network to the internet.

Provide the name of a [ProxyOptions](#) object defined in the heap or an inline configuration.

Default: A heap object named `ProxyOptions`.

propagateDisconnection

"propagateDisconnection" : *configuration expression*<[boolean](#)>, optional

Use this setting to stop streaming content to a browser that disconnects.

When "propagateDisconnection": `true`, PingGateway disconnects from the remote application when:

- The user-agent disconnects from PingGateway.
- [Streaming is enabled](#) for PingGateway.
- The response includes the header `Transfer-Encoding: chunked`.

When changing this setting, also consider [reducing logging when propagating disconnections](#).

Default: `false`

soTimeout

"soTimeout" : *configuration expression*<[duration](#)>, optional

Socket timeout, after which stalled connections are destroyed, expressed as a duration.



Tip

If PingGateway logs `SocketTimeoutException` errors when you try to upload or download large files, increase `soTimeout`.

Default: 10 seconds

temporaryStorage

"temporaryStorage" : *TemporaryStorage* [reference](#), optional

The [TemporaryStorage](#) object to buffer the request and response when the `streamingEnabled` property of `admin.json` is `false`.

Default: A heap object named `TemporaryStorage`.

tls

tls : *ClientTlsOptions* [reference](#), optional

Configure options for connections to TLS-protected endpoints with a [ClientTlsOptions](#) configuration. Define the object inline or in the heap.

Default: Connections to TLS-protected endpoints aren't configured.

retries

"retries": *object, optional*

Enable and configure retry for requests.

During the execution of a request to a remote server, if a condition is met, a runtime exception occurs, or a matching runtime exception condition is met, PingGateway waits for a delay, then schedules a new execution of the request. PingGateway tries until the allowed number of retries is reached or the execution succeeds.

A warning-level entry is logged if all retry attempts fail; a debug-level entry is logged if a retry succeeds.

The following example configures a retry when a downstream component returns a **502 Bad Gateway** response code:

```
{
  "retries": {
    "enabled": true,
    "condition": "${response.status.code == 502}"
  }
}
```

The following example configures the handler to retry the request only once, after a 1-minute delay:

```
{
  "retries": {
    "count": 1,
    "delay": "1 minute"
  }
}
```

The following example configures the handler to retry the request at most 20 times per second:

```
{
  "retries": {
    "count": 20,
    "delay": "1 second"
  }
}
```

The following example retries the request only when a runtime expression for an HTTP/2 GOAWAY error occurs:

```
{
  "retries": {
    "enabled": true,
    "runtimeExceptionCondition": "${exception.message.contains(\"GOAWAY\")}"
  }
}
```

The following example configures the handler to retry the request 5 times every 10 seconds (default values) with a dedicated executor:

```
{
  "retries": {
    "executor": {
      "type": "ScheduledExecutorService",
      "config": {
        "corePoolSize": 20
      }
    }
  }
}
```

"enabled": configuration expression<[boolean](#)>, optional

Enable retries.

Default: `true`

"condition": runtime expression<[boolean](#)>, optional

An inline PingGateway [expression](#) to define a condition based on the response, such as an error code.

The condition is evaluated as follows:

- If `true`, PingGateway retries the request until the `count` is reached.
- If `false`, PingGateway retries the request only if a runtime exception occurs until the `count` is reached.

Default: `${false}`

"executor": *ScheduledExecutorService* [reference](#), optional

The [ScheduledExecutorService](#) to use for scheduling delayed execution of the request.

Default: `ScheduledExecutorService`

"count": configuration expression<[number](#)>, optional

The maximum number of retries to perform. After this threshold is passed and if the request is still not successful, the ClientHandler propagates the failure.

Retries caused by any runtime exception or triggered condition are included in the count.

Default: `5`

"delay": configuration expression<duration>, optional

The time to wait before retrying the request.

After a failure to send the request, if the number of retries is below the threshold, a new attempt is scheduled with the executor service after this delay.

Default: 10 seconds

"runtimeExceptionCondition": runtime expression<boolean>, optional

An inline [expression](#) to define a condition when a runtime exception occurs. The `context`, `request`, and `exception` are available in the expression.

- If `true`, PingGateway retries the request until the value in `count` is reached.
- If `false`, PingGateway doesn't retry the request.

Default: When this isn't set, retry when any runtime exception occurs.

circuitBreaker

"circuitBreaker": [object](#), optional

Enable and configure a circuit breaker to trip when the number of failures exceeds a configured threshold. Calls to downstream services are stopped and a runtime exception is returned. The circuit breaker is reset after the configured delay.

"enabled": configuration expression<boolean>, optional

A flag to enable the circuit breaker.

Default: `true`

"maxFailures": configuration expression<number>, required

The maximum number of failed requests allowed in the window given by `size`, before the circuit breaker trips. The value must be greater than zero.

**Important**

When `retries` is set, the circuit breaker doesn't count retried requests as failures. Keep this in mind when you set `maxFailures`.

In the following example, a request can fail and then be retried three times. If it fails the third retry, the request has failed four times, but the circuit breaker counts only one failure.

```
{
  "retries": {
    "count": 3,
    "delay": "1 second"
  }
}
```


"openDuration": configuration expression<duration>, required

The duration for which the circuit stays open after the circuit breaker trips. The `executor` schedules the circuit to be closed after this duration.

"slidingCounter": object, required

A sliding window error counter. The circuit breaker trips when the number of failed requests in the number of requests given by `size` reaches `maxFailures`.

The following image illustrates how the sliding window counts failed requests:

**"size": configuration expression<number>, required**

The size of the sliding window in which to count errors.

The value of `size` must be greater than zero and greater than the value of `maxFailures`, otherwise PingGateway throws an exception.

"openHandler": Handler reference, optional

The `Handler` to call when the circuit is open.

Default: A handler that throws a `RuntimeException` with a "circuit-breaker open" message.

"executor": ScheduledExecutorService reference, optional

A `ScheduledExecutorService` to schedule closure of the circuit after the duration given by `openDuration`.

Default: The default `ScheduledExecutorService` in the heap

Close connections gracefully

By default, PingGateway doesn't explicitly set a time limit for closing idle connections.

You can set `"connectionTimeToLive"` and `"connectionShutdownGracePeriod"` to choose how long to keep idle connections and how long a grace period to allow before closing them.

When configuring PingGateway to close idle connections, keep the following in mind:

- When [streaming is enabled](#) and the client application shares connections to PingGateway, closing a connection affects all the requests that share it.
- When PingGateway closes a connection to a protected application, the closure affects multiple requests even when PingGateway isn't pipelining any requests. Closing one connection from PingGateway to an application results in the closure of one or more connections from the client application to PingGateway. This affects multiple client requests.

More information

org.forgerock.openig.handler.ClientHandlerHeaplet 

DispatchHandler

When a request is handled, the first condition in the list of conditions is evaluated. If the condition expression yields `true`, the request is dispatched to the associated handler with no further processing. Otherwise, the next condition in the list is evaluated.

Usage

```
{
  "name": string,
  "type": "DispatchHandler",
  "config": {
    "bindings": [
      {
        "condition": runtime expression<boolean>,
        "handler": Handler reference,
        "baseURI": runtime expression<url>,
      }, ...
    ]
  }
}
```

Properties

"bindings": array of [objects](#), required

One or more condition and handler bindings.

"condition": runtime expression<[boolean](#)>, optional

A flag to indicate that a condition is met. The condition can be based on the request, context, or PingGateway runtime environment, such as system properties or environment variables.

Conditions are defined using PingGateway expressions, as described in [Expressions](#), and are evaluated as follows:

- `true`: The request is dispatched to the associated handler.
- `false`: The next condition in the list is evaluated.

You can find examples in [Example conditions and requests](#).

Default: `${true}`

"handler": *Handler reference, required*

The [Handler](#) to which PingGateway dispatches the request if the associated condition yields `true`.

Provide the name of a Handler object defined in the heap or an inline Handler configuration object.

"baseURI": *runtime expression<url>, optional*

A base URI that overrides the existing request URI. Only scheme, host, and port are used in the supplied URI.

The result of the expression must be a string that represents a valid URI, but isn't a real `java.net.URI` object. For example, it would be incorrect to use `${request.uri}`, which isn't a String but a MutableUri.

In the following example, the binding condition looks up the hostname of the request. If it finds a match, the value is used for the `baseURI`. Otherwise, the default value is used:

```
{
  "properties": {
    "uris": {
      "app1.example.com": {
        "baseURI": "https://backend1:8443/"
      },
      "app2.example.com": {
        "baseURI": "https://backend2:8443/"
      },
      "default": {
        "baseURI": "https://backend3:8443/"
      }
    }
  },
  "handler": {
    "type": "DispatchHandler",
    "config": {
      "bindings": [
        {
          "condition": "${not empty uris[contexts.router.originalUri.host]}",
          "baseURI": "${uris[contexts.router.originalUri.host].baseURI}",
          "handler": "ReverseProxyHandler"
        },
        {
          "baseURI": "${uris['default'].baseURI}",
          "handler": "ReverseProxyHandler"
        }
      ]
    }
  }
}
```

Default: No change to the base URI

Example

You can find an example that uses a DispatchHandler in [With a DispatchHandler](#).

More information

Expressions

ForgeRockClientHandler

The ForgeRockClientHandler is a Handler available by default on the heap that chains a default [ClientHandler](#) with a [TransactionIdOutboundFilter](#).

This Handler supports ForgeRock audit by supporting the initiation or propagation of audit information from PingGateway to the audit framework. For more information, see [AuditService](#).

The following default ForgeRockClientHandler is available as a default object on the heap, and can be referenced by the name ForgeRockClientHandler.

```
{
  "name": "ForgeRockClientHandler",
  "type": "Chain",
  "config": {
    "filters": [ "TransactionIdOutboundFilter" ],
    "handler": "ClientHandler"
  }
}
```

Example

For an example that uses ForgeRockClientHandler to log interactions between PingGateway and AM, see [Decorating PingGateway's interactions with AM](#).


More information

org.forgerock.openig.heap.Keys [↗](#)

IdentityAssertionHandler

Use in a PingOne Advanced Identity Cloud authentication journey with the IdentityAssertionNode node. The node is available in PingOne Advanced Identity Cloud and from AM 7.5. Learn more in the documentation for PingOne Advanced Identity Cloud's [Identity Assertion node](#) [↗](#) and AM's [Identity Assertion node](#) [↗](#).

The following image shows the flow of information when an Identity Assertion node authenticates internal accesses:



As part of a PingOne Advanced Identity Cloud journey, the IdentityAssertionHandler uses an identityAssertionPlugin to manage local authentication as follows:

1. The PingOne Advanced Identity Cloud authentication journey redirects a user to PingGateway for local authentication, providing an **identity request JWT**.
2. PingGateway validates the identity request JWT.
3. The identityAssertionPlugin accesses the **IdentityRequestJwtContext** generated from the identity request JWT. It then performs local processing and returns the principal and identity claims in an **identity assertion JWT**.
4. PingGateway redirects the user back to PingOne Advanced Identity Cloud authentication journey, providing the identity assertion JWT. If an exception prevents PingGateway from returning a valid identity assertion JWT, PingGateway returns an HTTP 500.

The following table lists the claims contained in identity request JWT and identity assertion JWT:

Claim	Description	Identity request JWT	Identity assertion JWT (successful plugin processing)	Identity assertion JWT (plugin processing error)
iss	Issuer	✓	✓	✓

Claim	Description	Identity request JWT	Identity assertion JWT (successful plugin processing)	Identity assertion JWT (plugin processing error)
aud	Audience	✓	✓	✓
iat	Issued at	✓	✓	✓
exp	Expiration time	✓	✓	✓
nonce	Unique ID generated by the IdentityGatewayAssertionNode and returned in the identity assertion JWT	✓	✓	✓
redirect	URL on which to send the identity assertion JWT	✓	✗	✗
version	JWT version; only v1 is supported	✓	✗	✗
data	Map of claims items that can be required by a plugin	Optional	✗	✗
principal	The user for whom the identity assertion JWT is issued	✗	✓	✗
identity	Map of additional identity claims returned by the plugin	✗	✓	✗
error	Error message of the plugin processing failure	✗	✗	✓

Usage

```
{
  "name": string,
  "type": "IdentityAssertionHandler",
  "config": {
    "identityAssertionPlugin": IdentityAssertionPlugin reference,
    "selfIdentifier": configuration expression<string>,
    "peerIdentifier": configuration expression<string>,
    "encryptionSecretId": configuration expression<secret-id>,
    "secretsProvider": Secrets Provider reference,
    "expiry": configuration expression<duration>,
    "skewAllowance": configuration expression<duration>
  }
}
```

"identityAssertionPlugin": configuration expression<string>, required

An implementation of [org.forgerock.openig.assertion.plugin.IdentityAssertionPlugin](#), such as a [KerberosIdentityAssertionPlugin](#) to use Kerberos or a [ScriptableIdentityAssertionPlugin](#) to support use cases that aren't covered by a PingGateway plugin.

This plugin is called after the IdentityAssertionHandler validates the identity request JWT from PingOne Advanced Identity Cloud. The handler then passes the [IdentityRequestJwtContext](#) in the context chain to the plugin.

"selfIdentifier": configuration expression<string>, required

An identifier to validate that this PingGateway instance is the correct audience for the identity request from PingOne Advanced Identity Cloud.

This identifier is the value of:

- `aud` claim in the identity request JWT
- `iss` claim in the identity assertion JWT

Can't be null.

"peerIdentifier": configuration expression<string>, required

An identifier to validate that the expected PingOne Advanced Identity Cloud tenant issued the identity request.

This identifier is the value of the:

- `iss` claim in the identity request JWT
- `aud` claim in the identity assertion JWT

Can't be null.

"encryptionSecretId": configuration expression<secret-id>, required

The secret ID for the secret to decrypt the identity request JWT and encrypt the returned identity assertion JWT. The secret ID must point to a [CryptoKey](#). Decryption and encryption is with AES GCM using a 256-bit key.

"secretsProvider": SecretsProvider reference, required

The [SecretsProvider](#) to resolve encryption and decryption keys.

"expiry": configuration expression<duration>, optional

The expiry time of the identity assertion JWT.

Default: 30 seconds

"skewAllowance": configuration expression<duration>, optional

The duration to add to the validity period of a JWT to allow for clock skew between different servers.

A `skewAllowance` of 2 minutes affects the validity period as follows:

- A JWT with an `iat` of 12:00 is valid from 11:58 on the PingGateway clock.

- A JWT with an `exp` 13:00 is expired after 13:02 on the PingGateway clock.

Default: To support a zero-trust policy, the skew allowance is by default `zero`.

Example

The following route is an Identity Assertion service route for use with the IdentityAssertionNode.

Learn how to set up the example in the documentation for PingOne Advanced Identity Cloud's [Identity Assertion node](#) and AM's [Identity Assertion node](#).

```

{
  "name": "IdentityAssertion",
  "condition": "${find(request.uri.path, '^/idassert')}",
  "properties": {
    "amIdcPeer": "myTenant.forgeblocks.com"
  },
  "handler": "IdentityAssertionHandler-1",
  "heap": [
    {
      "name": "IdentityAssertionHandler-1",
      "type": "IdentityAssertionHandler",
      "config": {
        "identityAssertionPlugin": "BasicAuthScriptablePlugin",
        "selfIdentifier": "https://ig.ext.com:8443",
        "peerIdentifier": "&{amIdcPeer}",
        "secretsProvider": [
          "secrets-pem"
        ],
        "encryptionSecretId": "idassert"
      }
    },
    {
      "name": "BasicAuthScriptablePlugin",
      "type": "ScriptableIdentityAssertionPlugin",
      "config": {
        "type": "application/x-groovy",
        "source": [
          "import org.forgerock.openig.assertion.IdentityAssertionClaims",
          "import org.forgerock.openig.assertion.plugin.IdentityAssertionPluginException",
          "logger.info('Running ScriptableIdentityAssertionPlugin')",
          "return new IdentityAssertionClaims('demo')"
        ]
      }
    },
    {
      "name": "pemPropertyFormat",
      "type": "PemPropertyFormat"
    },
    {
      "name": "secrets-pem",
      "type": "FileSystemSecretStore",
      "config": {
        "directory": "&{ig.instance.dir}/secrets/igfs",
        "suffix": ".pem",
        "format": "pemPropertyFormat",
        "mappings": [
          {
            "secretId": "idassert",
            "format": "pemPropertyFormat"
          }
        ]
      }
    }
  ]
}

```

Source: [identity-assertion.json](#)

More information

[org.forgerock.openig.assertion.plugin.IdentityAssertionPlugin](#) 

JwkSetHandler

Expose cryptographic keys as a JWK set. Use this handler to reuse exposed keys for their assigned purpose in a downstream application.

Consider the following limitations:

- When the public key isn't available, the corresponding private key can't be exposed.



Caution

You aren't recommended to expose private keys as a JWK.

- Keys in secure storage, such as a Hardware Security Module (HSM) or remote server, can't be exposed.

You can find a description of how secrets are managed in [About secrets](#).

You can find more information about JWKs and JWK Sets in [JSON Web Key \(JWK\)](#) .

Usage

```
{
  "name": string,
  "type": "JwkSetHandler",
  "config": {
    "secretsProvider": SecretsProvider reference,
    "purposes": [ object, ... ],
    "exposePrivateSecrets": configuration expression<boolean>
  }
}
```

"secretsProvider": *SecretsProvider* [reference](#), **required**

The [SecretsProvider](#) containing secrets to expose in the JwkSet.

"purposes": *array of objects*, **required**

One or more purposes for the JwkSet key.

```
{
  "purposes": [
    {
      "secretId": configuration expression<secret-id>,
      "keyUsage": configuration expression<enumeration>
    },
    ...
  ]
}
```

"secretId": configuration expression<[secret-id](#)>, required

The secret ID of the key to be exposed in the JwkSet.

This secret ID must point to a [CryptoKey](#).

"keyUsage": configuration expression<[enumeration](#)>, required

The allowed use of the key:

- **AGREE_KEY** : Export the private key used in the key agreement protocol, for example, Diffie-Hellman.
- **ENCRYPT** : Export the public key used to encrypt data.
- **DECRYPT** : Export the private key used to decrypt data.
- **SIGN** : Export the private key used to sign data.
- **VERIFY** : Export the public key used to verify signature data.
- **WRAP_KEY** : Export the public key used to encrypt (wrap) other keys.
- **UNWRAP_KEY** : Export the private key used to decrypt (unwrap) other keys.

exposePrivateSecrets: configuration expression<[boolean](#)>, optional

A flag indicating whether to publish private keys in a JWK set. As a security safeguard, this property is **false** by default to prevent the accidental exposure of private keys.

true : Publish both public and private keys in the JWK set **false** : Publish only public keys in the JWK set

Default: **false**

Examples

This example uses a JwkSetHandler to expose a signing key used by the JwtBuilderFilter:

1. Set an environment variable for the base64-encoded secret to sign the JWT:

```
$ export SIGNING_KEY_SECRET_ID='cGFzc3dvcnQ='
```

2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/jwksethandler.json
```

Windows

```
%appdata%\OpenIG\config\routes\jwksethandler.json
```

```

{
  "name": "jwksethandler",
  "condition": "${find(request.uri.path, '/jwksethandler')}",
  "heap": [
    {
      "name": "SecretKeyPropertyFormat-1",
      "type": "SecretKeyPropertyFormat",
      "config": {
        "format": "BASE64",
        "algorithm": "AES"
      }
    },
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore",
      "config": {
        "mappings": [{
          "secretId": "signing.key.secret.id",
          "format": "SecretKeyPropertyFormat-1"
        }]
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "JwtBuilderFilter-1",
          "type": "JwtBuilderFilter",
          "config": {
            "template": {
              "name": "${contexts.userProfile.commonName}",
              "email": "${contexts.userProfile.rawInfo.mail[0]}"
            },
            "secretsProvider": "SystemAndEnvSecretStore-1",
            "signature": {
              "secretId": "signing.key.secret.id",
              "algorithm": "HS256"
            }
          }
        }
      ]
    }
  },
  "handler": {
    "type": "JwkSetHandler",
    "config": {
      "secretsProvider": "SystemAndEnvSecretStore-1",
      "purposes": [{
        "secretId": "signing.key.secret.id",
        "keyUsage": "SIGN"
      }]
    }
  }
}

```

Source: [jwksethandler.json](#)

Notice the following features of the route:

- The route matches requests to `/jwksethandler`.
- The JWT signing key is managed by the `SysEnvStoreSecretStore` in the heap, which refers to the `SecretKeyPropertyFormat` for the secret's format.
- The `JwtBuilderFilter` `signature` property refers to the JWT signing key in the `SysEnvStoreSecretStore`.
- The `JwkSetHandler` refers to the JWT signing key.

3. Go to <https://ig.example.com:8443/jwksethandler>.

The signing key is displayed as an array, as follows:

```
{
  "keys": [
    {
      "k": "cGFzc3dvcmQ",
      "kid": "signing.key.secret.id",
      "kty": "oct",
      "use": "sig"
    }
  ]
}
```

The JWK set secret is ULR base64-encoded. Although the secret is set with the value `cGFzc3dvcmQ=`, the value `cGFzc3dvcmQ` is exposed.

More information

org.forgerock.openig.handler.JwkSetHandler

PingOneProtectThreatLevelRoutingHandler

Uses a [PingOneProtectEvaluationContext](#) representing a risk evaluation to route the inbound request according to the risk level.

You use a `PingOneProtectEvaluationFilter` to make a risk assessment request to PingOne Protect. The filter records the evaluation in a [PingOneProtectEvaluationContext](#) object. The `PingOneProtectThreatLevelRoutingHandler` acts on the risk level set in the context.

After completing additional actions to verify the identity of a user following a risk evaluation, record the outcome using a [PingOneProtectFeedbackSuccessFilter](#) or a [PingOneProtectFeedbackFailureFilter](#).

For complex scenarios where you don't want to base the decision on the risk level, you can [use a DispatcherHandler instead](#).

Usage

```
{
  "name": string,
  "type": "PingOneProtectThreatLevelRoutingHandler",
  "config": {
    "levels": {
      "low": Handler reference,
      "medium": Handler reference,
      "high": Handler reference
    }
  }
}
```

Configuration

"levels": *array of objects, required*

Object mapping a risk level to a handler.

"low": *Handler reference, required*

The handler responsible for low-risk requests.

"medium": *Handler reference, required*

The handler responsible for medium-risk requests.

"high": *Handler reference, required*

The handler responsible for high-risk requests.

Example

Threat-level routing handler

The following example sends low-risk requests straight through, medium-risk requests to a handler for additional authentication, for example, and high-risk requests to a handler that denies access and takes additional action:

```
{
  "name": "PingOneProtectThreatLevelRoutingHandler-1",
  "type": "PingOneProtectThreatLevelRoutingHandler",
  "config": {
    "levels": {
      "low": "passthroughHandler",
      "medium": "mediumRiskHandler",
      "high": "highRiskHandler"
    }
  }
}
```

Alternative with dispatch handler

This example uses a [DispatchHandler](#) to route requests based on the risk evaluation score rather than the levels:

```
{
  "name": "scoreBasedRoutingHandler",
  "type": "DispatchHandler",
  "config": {
    "bindings": [
      {
        "condition": "${contexts.pingOneProtect.score <= 30}",
        "handler": "passthroughHandler"
      },
      {
        "condition": "${contexts.pingOneProtect.score > 30 && contexts.pingOneProtect.score <= 70}",
        "handler": "mediumRiskHandler"
      },
      {
        "condition": "${contexts.pingOneProtect.score > 70}",
        "handler": "highRiskHandler"
      }
    ]
  }
}
```

The conditions depend on the [PingOne Protect risk evaluation response API](#) and the [PingOneProtectEvaluationContext](#).

More information

[org.forgerock.openig.ping.protect.PingOneProtectThreatLevelRoutingHandler](https://forgerock.org/openig/ping/protect/PingOneProtectThreatLevelRoutingHandler)

ResourceHandler

Serves static content from a directory.

Usage

```
{
  "name": string,
  "type": "ResourceHandler",
  "config": {
    "directories": [ configuration expression<string>, ... ],
    "basePath": configuration expression<string>,
    "welcomePages": [ configuration expression<string>, ... ],
    "temporaryStorage": TemporaryStorage reference
  }
}
```

Properties

"directories": *array of configuration expression<strings>, required*

A list of one or more directories in which to search for static content.

When multiple directories are specified in an array, the directories are searched in the listed order.

"basePath": *_configuration expression<string>, required if the route isn't /*

The base path of the incoming request for static content.

To specify no base path, leave this property out of the configuration, or specify it as `"basePath": ""` or

`"basePath": "/"`.

Default: `""`.

"welcomePages": *array of configuration expression<strings>, optional*

A set of static content to serve from one of the specified directories when no specific resource is requested.

When multiple sets of static content are specified in an array, the sets are searched for in the listed order. The first set that is found is used.

Default: Empty

"temporaryStorage": *TemporaryStorage reference, optional*

A [TemporaryStorage](#) object for the static content.

Default: `TemporaryStorage` heap object

Example

The following example serves requests to `https://ig.example.com:8443` with the static file `index.html` from `/path/to/static/pages/`:

```
{
  "name": "StaticWebsite",
  "type": "ResourceHandler",
  "config": {
    "directories": ["/path/to/static/pages"],
    "welcomePages": ["index.html"]
  }
}
```

When the `basePath` is `/website`, the example serves requests to `https://ig.example.com:8443/website`:

```
{
  "name": "StaticWebsite",
  "type": "ResourceHandler",
  "config": {
    "directories": ["/path/to/static/pages"],
    "basePath": "/website",
    "welcomePages": ["index.html"]
  }
}
```

More information

[org.forgerock.openig.handler.resources.ResourceHandler](#)

[org.forgerock.http.protocol.Entity](#)

ReverseProxyHandler

Proxy requests to protected applications. When PingGateway relays the request to the protected application, PingGateway is acting as a client of the application. PingGateway is *client-side*.

Consider the following comparison of the ClientHandler and ReverseProxyHandler:

	ClientHandler	ReverseProxyHandler
Use this handler to ...	Send requests to third-party services accessed within a route. The service can be AM or an HTTP API. The service can be an HTTP endpoint, such as AM, IDM, PingOne Advanced Identity Cloud, or any custom HTTP API.	Send requests to the final service accessed by a route. The service can be the final downstream application.
If the service doesn't respond in time, this handler ...	Propagates the error through the Promise flow. If the error is not handled within the route, for example, by a FailureHandler, the handler returns a 500 Internal Server Error response.	Stops processing the request, and returns a 502 Bad Gateway response.

When uploading or downloading large files, prevent timeout issues by increasing the value of `soTimeout` , and using a streaming mode, as follows:

Configure the `streamingEnabled` property of [AdminHttpApplication](#).

Usage

```
{
  "name": string,
  "type": "ReverseProxyHandler",
  "config": {
    "vertex": object,
    "connections": configuration expression<number>,
    "waitQueueSize": configuration expression<number>,
    "soTimeout": configuration expression<duration>,
    "connectionTimeout": configuration expression<duration>,
    "connectionTimeToLive": configuration expression<duration>,
    "connectionShutdownGracePeriod": configuration expression<duration>,
    "protocolVersion": configuration expression<enumeration>,
    "http2PriorKnowledge": configuration expression<boolean>,
    "proxyOptions": ProxyOptions reference,
    "propagateDisconnection": configuration expression<boolean>,
    "temporaryStorage": TemporaryStorage reference,
    "tls": ClientTlsOptions reference,
    "retries": {
      "enabled": configuration expression<boolean>,
      "condition": runtime expression<boolean>,
      "executor": ScheduledExecutorService reference,
      "count": configuration expression<number>,
      "delay": configuration expression<duration>,
      "runtimeExceptionCondition": runtime expression<boolean>
    },
    "circuitBreaker": {
      "enabled": configuration expression<boolean>,
      "maxFailures": configuration expression<integer>,
      "slidingCounter": {
        "size": configuration expression<number>
      },
      "openDuration": configuration expression<duration>,
      "openHandler": Handler reference,
      "executor": ScheduledExecutorService reference
    },
    "websocket": {
      "enabled": configuration expression<boolean>,
      "connectionTimeout": configuration expression<duration>,
      "soTimeout": configuration expression<duration>,
      "numberOfSelectors": configuration expression<number>,
      "tls": ClientTlsOptions reference,
      "proxyOptions": ProxyOptions reference
    }
  }
}
```

Properties

vertex

"vertex": *object*, optional

Vert.x-specific configuration for the handler where PingGateway doesn't provide its own first-class configuration. Learn more about Vert.x options in [HttpClientOptions](#).

The `vertx` object is read as a map, and values are evaluated as configuration expressions.

For properties where PingGateway provides its own first-class configuration, Vert.x configuration options are disallowed and the PingGateway configuration option takes precedence over Vert.x options configured in `vertx`. The following Vert.x configuration options are disallowed client-side:

- `alpnVersions`
- `connectTimeout`
- `enabledCipherSuites`
- `enabledSecureTransportProtocols`
- `http2ClearTextUpgrade`
- `idleTimeout`
- `idleTimeoutUnit`
- `keyCertOptions`
- `keyStoreOptions`
- `maxWaitQueueSize`
- `pemKeyCertOptions`
- `pemTrustOptions`
- `pfxKeyCertOptions`
- `pfxTrustOptions`
- `port`
- `protocolVersion`
- `proxyOptions`
- `ssl`
- `trustOptions`
- `trustStoreOptions`
- `useAlpn`
- `verifyHost`

The following example configures the Vert.x configuration when PingGateway is acting client-side:

```
{
  "vertx": {
    "maxWebSocketFrameSize": 128000,
    "maxWebSocketMessageSize": 256000,
    "compressionLevel": 4,
    "maxHeaderSize": 16384
  }
}
```

The following example configures HTTP/2 connections when PingGateway is acting client-side. The configuration allows PingGateway to make HTTP/2 requests with large headers:

```
{
  "vertx": {
    "initialSettings": {
      "maxHeaderListSize": 16384
    }
  }
}
```

connections

"connections" : *configuration expression*<number>, optional

The maximum number of concurrent HTTP connections in the client connection pool.

This setting interacts with the [waitQueueSize](#).

Default: 64

waitQueueSize

"waitQueueSize" : *configuration expression*<number>, optional

The maximum number of outbound requests allowed to queue when no downstream connections are available. Outbound requests received when the queue is full are rejected.

Use this property to limit memory use when there is a backlog of outbound requests; for example, when the protected application or third-party service is slow.

Configure **waitQueueSize** in accord with the [connections](#) setting:

- Not set (default): The wait queue is calculated as the square of **connections** .
 - If **connections** isn't configured, then its default of **64** is used, giving the **waitQueueSize** of **4096** .
 - If the square of **connections** exceeds the maximum integer value for the Java JVM, the maximum integer value for the Java JVM is used.
- **-1** : The wait queue is unlimited. Requests received when there are no available connections are queued without limit.
- **0** : There is no wait queue. Requests received when there are no available connections are rejected.
- A value that is less than the square of **connections** :

When the configuration is loaded, the configured value is used. PingGateway generates a warning that the `waitQueueSize` is too small for the `connections` size and recommends a different value.

- A value where `waitQueueSize` plus `connections` exceeds the maximum integer value for the Java JVM:

When the configuration is loaded, the `waitQueueSize` is reduced to the maximum integer value for the Java JVM minus the value of `connections`. PingGateway logs a warning.

Consider the following example configuration with `connections` and `waitQueueSize`:

```
{
  "handler" : {
    "name" : "proxy-handler",
    "type" : "ReverseProxyHandler",
    "MyCapture" : "all",
    "config": {
      "soTimeout": "10 seconds",
      "connectionTimeout": "10 seconds",
      "connections": 64,
      "waitQueueSize": 100
    }
  },
  "baseURI" : "https://app.example.com:8444",
  "condition" : "${find(request.uri.path, '/')}"
}
```

PingGateway can propagate the request to the sample application using 64 connections. When the connections are consumed, up to 100 requests are queued until a connection is freed. Effectively PingGateway can accommodate 164 requests, although user concurrency delay means more may be handled. Requests received when the waitQueue is full are rejected.

Default: Not set

connectionTimeout

`"connectionTimeout"` : *configuration expression*<duration>, optional

Time to wait to establish a connection, expressed as a duration

Default: 10 seconds

connectionTimeToLive

`"connectionTimeToLive"` : *configuration expression*<duration>, optional

Time before a connection is closed, expressed as a duration.

Default: no limit

connectionShutdownGracePeriod

`"connectionShutdownGracePeriod"` : *configuration expression*<duration>, optional

Time to wait beyond `"connectionTimeToLive"` before shutting down the connection, expressed as a duration.

Default: The value of `"soTimeout"` (default: 10 seconds)

protocolVersion

"protocolVersion" : *configuration expression*<enumeration>, optional

The version of HTTP protocol to use when processing requests:

- HTTP/2 :
 - For HTTP, process requests using HTTP/1.1.
 - For HTTPS, process requests using HTTP/2.
 - HTTP/1.1 :
 - For HTTP and HTTPS, process requests using HTTP/1.1.
 - Not set:
 - For HTTP, process requests using HTTP/1.1.
 - For HTTPS with `alpn` enabled in `ClientTlsOptions`, process requests using HTTP/1.1 with an HTTP/2 upgrade request. If the targeted server can use HTTP/2, the client uses HTTP/2.
 - For HTTPS with `alpn` disabled in `ClientTlsOptions`, process requests using HTTP/1.1 without an HTTP/2 upgrade request.
- Note that `alpn` is enabled by default in `ClientTlsOptions`.

Default: Not set

Note

In HTTP/1.1 request messages, a `Host` header is required to specify the host and port number of the requested resource. In HTTP/2 request messages, the `Host` header isn't available. In scripts or custom extensions that use HTTP/2, use `UriRouterContext.originalUri.host` or `UriRouterContext.originalUri.port` in requests.

http2PriorKnowledge

"http2PriorKnowledge" : *configuration expression*<boolean>, optional

A flag for whether the client should have prior knowledge that the server supports HTTP/2. This property is for cleartext (non-TLS requests) only and is used only when `protocolVersion` is HTTP/2.

- `false` : The client checks whether the server supports HTTP/2 by sending an HTTP/1.1 request to upgrade the connection to HTTP/2:
 - If the server supports HTTP/2, the server upgrades the connection to HTTP/2 and later requests are over HTTP/2.
 - If the server doesn't support HTTP/2, the connection isn't upgraded and later requests are over HTTP/1.1.
- `true` : The client doesn't check that the server supports HTTP/2. The client sends HTTP/2 requests to the server, assuming that the server supports HTTP/2.

Default: `false`

proxyOptions

"proxyOptions" : *ProxyOptions* [reference](#), optional

A proxy server to which requests can be submitted. Use this property to relay requests to other parts of the network. For example, use it to submit requests from an internal network to the internet.

Provide the name of a [ProxyOptions](#) object defined in the heap or an inline configuration.

Default: A heap object named `ProxyOptions`.

propagateDisconnection

"propagateDisconnection" : *configuration expression*<[boolean](#)>, optional

Use this setting to stop streaming content to a browser that disconnects.

When "propagateDisconnection": `true`, PingGateway disconnects from the protected application when:

- The user-agent disconnects from PingGateway.
- [Streaming is enabled](#) for PingGateway.
- The response includes the header `Transfer-Encoding: chunked`.

When changing this setting, also consider [reducing logging when propagating disconnections](#).

Default: `false`

soTimeout

"soTimeout" : *configuration expression*<[duration](#)>, optional

Socket timeout, after which stalled connections are destroyed, expressed as a duration.



Tip

If `SocketTimeoutException` errors occur in the logs when you upload or download large files, increase `soTimeout`.

Default: 10 seconds

temporaryStorage

"temporaryStorage" : *TemporaryStorage* [reference](#), optional

The [TemporaryStorage](#) object to buffer the request and response when the `streamingEnabled` property of [admin.json](#) is `false`.

Default: A heap object named `TemporaryStorage`

tls

tls : *ClientTlsOptions* [reference](#), optional

Configure [ClientTlsOptions](#) for connections to TLS-protected endpoints.

Define the object inline or in the heap.

Default: Connections to TLS-protected endpoints aren't configured.

retries

`"retries"` : *object*, *optional*

Enable and configure retry for requests.

During the execution of a request to a remote server, if a condition is met, a runtime exception occurs, or a matching runtime exception condition is met, PingGateway waits for a delay, then schedules a new execution of the request. PingGateway tries until the allowed number of retries is reached or the execution succeeds.

A warning-level entry is logged if all retry attempts fail. A debug-level entry is logged if a retry succeeds.

The following example configures a retry when a downstream component returns HTTP 502 Bad Gateway:

```
"retries": {
  "enabled": true,
  "condition": "${response.status.code == 502}"
}
```

The following example configures the handler to retry the request only once after a 1-minute delay:

```
{
  "retries": {
    "count": 1,
    "delay": "1 minute"
  }
}
```

The following example configures the handler to retry the request at most 20 times per second:

```
{
  "retries": {
    "count": 20,
    "delay": "1 second"
  }
}
```

The following example retries the request only when a runtime expression for an HTTP/2 GOAWAY error occurs:

```
{
  "retries": {
    "enabled": true,
    "runtimeExceptionCondition": "${exception.message.contains(\"GOAWAY\")}"
  }
}
```

The following example configures the handler to retry the request 5 times every 10 seconds (default values) with a dedicated executor:

```
{
  "retries": {
    "executor": {
      "type": "ScheduledExecutorService",
      "config": {
        "corePoolSize": 20
      }
    }
  }
}
```

"enabled": configuration expression<boolean>, optional

Enable retries.

Default: `true`

"condition": runtime expression<boolean>, optional

An inline PingGateway [expression](#) to define a condition based on the response, such as an error code.

The condition is evaluated as follows:

- If `true`, PingGateway retries the request until the `count` is reached.
- If `false`, PingGateway retries the request only if a runtime exception occurs until the `count` is reached.

Default: `${false}`

"executor": ScheduledExecutorService [reference](#), optional

The [ScheduledExecutorService](#) to use for scheduling delayed execution of the request.

Default: `ScheduledExecutorService`

"count": configuration expression<number>, optional

The maximum number of retries to perform. After this threshold is passed and if the request is still not successful, the handler propagates the failure.

Retries caused by any runtime exception or triggered condition are included in the count.

Default: `5`

"delay": configuration expression<duration>, optional

The time to wait before retrying the request.

After a failure to send the request, if the number of retries is below the threshold, a new attempt is scheduled with the executor service after this delay.

Default: `10 seconds`

"runtimeExceptionCondition": *runtime expression*<boolean>, optional

An inline **expression** to define a condition when a runtime exception occurs. The **context**, **request**, and **exception** are available in the expression.

- If **true**, PingGateway retries the request until the **count** is reached.
- If **false**, PingGateway doesn't retry the request.

Default: When this isn't set, retry when any runtime exception occurs.

circuitBreaker

"circuitBreaker": *object*, optional

Enable and configure a circuit breaker to trip when the number of failures exceeds a configured threshold. Calls to downstream services are stopped and a runtime exception is returned. The circuit breaker is reset after the configured delay.

"enabled": *configuration expression*<boolean>, optional

A flag to enable the circuit breaker.

Default: **true**

"maxFailures": *configuration expression*<number>, required

The maximum number of failed requests allowed in the window given by **size**, before the circuit breaker trips. The value must be greater than zero.

**Important**

When **retries** is set, the circuit breaker doesn't count retried requests as failures. Keep this in mind when you set **maxFailures**.

In the following example, a request can fail and then be retried three times. If it fails the third retry, the request has failed four times, but the circuit breaker counts only one failure.

```
{
  "retries": {
    "count": 3,
    "delay": "1 second"
  }
}
```


"openDuration": *configuration expression*<duration>, required

The duration for which the circuit stays open after the circuit breaker trips. The **executor** schedules the circuit to be closed after this duration.

"slidingCounter": *object*, required

A sliding window error counter. The circuit breaker trips when the number of failed requests in the number of requests given by **size** reaches **maxFailures**.

The following image illustrates how the sliding window counts failed requests:



"size": configuration expression<number>, required

The size of the sliding window in which to count errors.

The value of `size` must be greater than zero and greater than the value of `maxFailures`, otherwise PingGateway throws an exception.

"openHandler": Handler reference, optional

The [Handler](#) to call when the circuit is open.

Default: A handler that throws a `RuntimeException` with a "circuit-breaker open" message

"executor": ScheduledExecutorService reference, optional

A [ScheduledExecutorService](#) to schedule closure of the circuit after the duration given by `openDuration`.

Default: The default `ScheduledExecutorService` in the heap

websocket

"websocket": object, optional

Object to configure upgrade from HTTP or HTTPS protocol to [The WebSocket Protocol](#).

Every key/value of the `websocket` object is evaluated as a configuration expression.

List the subprotocols proxied by PingGateway in the `vertx` property of [AdminHttpApplication](#) (`admin.json`). Learn more in [WebSocket traffic with PingAM](#).

"enabled": configuration expression<boolean>, optional

Enable upgrade from HTTP protocol and HTTPS protocol to WebSocket protocol.

Default: `false`

"connectionTimeout": configuration expression<duration>, optional

The maximum time allowed to establish a WebSocket connection.

Default: The value of handler's main `connectionTimeout`.

"soTimeout": *configuration expression*<duration>, optional

The time after which stalled connections are destroyed.

**Tip**

If there can be long delays between messages, consider increasing this value. Alternatively, keep the connection active by using WebSocket ping messages in your application.

Default: The value of handler's main `soTimeout`.

"numberOfSelectors": *configuration expression*<number>, optional

The maximum number of worker threads.

In deployments with a high number of simultaneous connections, consider increasing the value of this property.

Default: 2

"tls": *ClientTlsOptions* *reference*, optional

An [ClientTlsOptions](#) reference to configure connections to TLS-protected endpoints.

Default: Use ClientTlsOptions defined for the handler

"proxyOptions": *ProxyOptions* *reference*, optional

A proxy server to which requests can be submitted. Use this property to relay requests to other parts of the network. For example, use it to submit requests from an internal network to the internet.

Provide the name of a [ProxyOptions](#) object defined in the heap or an inline configuration.

Default: A heap object named `ProxyOptions`.

Close connections gracefully

By default, PingGateway doesn't explicitly set a time limit for closing idle connections.

You can set "[connectionTimeToLive](#)" and "[connectionShutdownGracePeriod](#)" to choose how long to keep idle connections and how long a grace period to allow before closing them.

When configuring PingGateway to close idle connections, keep the following in mind:

- When [streaming is enabled](#) and the client application shares connections to PingGateway, closing a connection affects all the requests that share it.
- When PingGateway closes a connection to a protected application, the closure affects multiple requests even when PingGateway isn't pipelining any requests. Closing one connection from PingGateway to an application results in the closure of one or more connections from the client application to PingGateway. This affects multiple client requests.

More information

[org.forgerock.openig.handler.ReverseProxyHandlerHeaplet](#) 

Route

Routes are JSON-encoded configuration files that you add to PingGateway to manage requests. You can add routes in the following ways:

- Manually into the filesystem.
- Through Common REST commands. Learn more in [PingGateway routes and common REST](#).
- Through Studio. Learn more in [PingGateway Studio](#).

Routes handle requests and their context, and then hand off any request they accept to a [Handler](#).

When a route has a condition, it handles only requests that meet the condition. When a route has no condition, it handles any request.

Routes inherit settings from their parent configuration. This means that you can configure global objects in the `config.json` heap, for example, and then reference the objects by name in any other PingGateway configuration.

Learn about Route metrics:

- [Metrics at the Prometheus Scrape Endpoint](#)
- [Route metrics at the Common REST Monitoring Endpoint \(deprecated\)](#)

Usage

```
{
  "handler": Handler reference,
  "heap": [ object, ... ],
  "condition": runtime expression<boolean>,
  "name": string,
  "session": AsyncSessionManager reference,
  "auditService": AuditService reference,
  "globalDecorators": map,
  "decorator name": Decorator object
}
```

(*)Deprecated

Properties

"handler": *Handler reference, required*

The [Handler](#) to which PingGateway dispatches requests.

Provide the name of a Handler object defined in the heap or an inline Handler configuration object.

"heap": *array of objects, optional*

Heap object configuration for objects local to this route.

Objects referenced but not defined here are inherited from the parent.

You can omit an empty array. If you only have one object in the heap, you can inline it as the handler value.

Refer to [Heap objects](#).

"condition": *runtime expression*<*boolean*>, optional

A condition based on the request, context, or PingGateway runtime environment, such as system properties or environment variables.

- **true**: The request is dispatched to the route.
- **false**: The condition for the next route in the configuration is evaluated.
- No condition: the request is dispatched unconditionally to the route.

Tip

For debugging, log the routes for which PingGateway evaluates a condition, and the route that matches a condition. Add the following line to a custom `$HOME/.openig/config/logback.xml`, and restart PingGateway:

```
<logger name="org.forgerock.openig.handler.router.RouterHandler" level="trace" />
```

For information, refer to [Managing PingGateway logs](#).

An external request can never match a condition that uses the reserved administrative route. Therefore, routes that use these conditions are effectively ignored even if you configure PingGateway to use the same ports for all requests.

Default: `${true}`

You can find an example conditions and requests that match them in [Example](#).

"name": *string*, optional

Route name.

The Router uses the `name` property to order the routes in the configuration. If the route doesn't have a `name` property, the Router uses the route ID.

The route ID is managed as follows:

- When you add a route manually to the routes folder, the route ID is the value of the `_id` field. If there is no `_id` field, the route ID is the filename of the added route.
- When you add a route through the Common REST endpoint, the route ID is the value of the mandatory `_id` field.
- When you add a route through Studio, you can edit the default route ID.

CAUTION: The filename of a route cannot be `default.json`. The route `name` property or route ID cannot be `default`.

Default: route ID

"session": *AsyncSessionManager reference*. *reference*, optional

An [InMemorySessionManager](#) (stateful sessions) or [JwtSessionManager](#) (stateless sessions).

When a request enters the route, PingGateway builds a new session object for the route. The session content is available to the route's downstream handlers and filters. Session content available in the parent route or `config.json` isn't available in the new session.

Default: [InMemorySessionManager](#) with default values

Learn more in [PingGateway sessions](#).

"auditService": *AuditService* [reference](#), optional

An audit service for the route. Provide either the name of an AuditService object defined in the heap or an inline AuditService configuration object.

Default: No auditing of a configuration. The NoOpAuditService provides an empty audit service to the top-level heap and its child routes.

"globalDecorators": *map*, optional

A map of one or more data pairs with the format `Map<String, JsonValue>`, where:

- The key is a decorator name
- The value is a decorator configuration, passed *as is* to the decorator

The following format is required:

```
{
  "globalDecorators": {
    "decorator name": "decoration configuration",
    ...
  }
}
```

All compatible objects in a route are decorated with the mapped decorator value. For more information, refer to [PingGateway decorators](#).

In the following example, the property decorates all compatible objects in the route with capture, timer, and tracing decorators:

```
"globalDecorators": {
  "capture": "all",
  "timer": true,
  "tracing": true
}
```

Default: Empty

"decorator name": *Decorator object*, optional

Decorate the main handler of this route with a decorator referred to by the decorator name, and provide the configuration as described in [PingGateway decorators](#).

Default: No decoration.

Example

The following table gives examples of route conditions and matching requests.

Condition	Requests that meet the condition
<code>"\${true}"</code>	All requests, because this expression always evaluates to <code>true</code> .
<code>"\${find(request.uri.path, '^/login')}}"</code>	<code>https://app.example.com/login</code> , ...
<code>"\${request.uri.host == 'api.example.com'}"</code>	<code>https://api.example.com/</code> , <code>https://api.example.com/home</code> , <code>https://api.example.com:8444/home</code> , ...
<code>"\${find(contexts.client.remoteAddress, '127.0.0.1')}}"</code>	<code>https://localhost:8443/keygen</code> , <code>https://127.0.0.1:8443/keygen</code> , ... Where <code>/keygen</code> isn't mandatory and could be anything else.
<code>"\${find(request.uri.query, 'demo=simple')}}"</code>	<code>https://ig.example.com:8443/login?demo=simple</code> , ... You can find more information about URI query parameters in URI .
<code>"\${request.uri.scheme == 'https'}"</code>	<code>https://ig.example.com:8443</code> , ...
<code>"\${find(request.uri.path, '^/dispatch') or find(request.uri.path, '^/mylogin')}}"</code>	<code>https://ig.example.com:8443/dispatch</code> , <code>https://ig.example.com:8443/mylogin</code> , ...
<code>"\${request.uri.host == 'sp1.example.com' and not find(request.uri.path, '^/saml')}}"</code>	<code>https://sp1.example.com:8443/</code> , <code>https://sp1.example.com/mypath</code> , ... Not <code>https://sp1.example.com:8443/saml</code> , <code>https://sp1.example.com/saml</code> , ...

Condition	Requests that meet the condition
<pre>"condition": "\${find (request.uri.path, '&{uriPath}')}"</pre>	<code>https://ig.example.com:8443/hello</code> , when the following property is configured: <pre>{ "properties": { "uriPath": "hello" }}</pre> For information about including properties in the configuration, refer to PingGateway route properties.
<pre>"condition": "\${request.headers['X-Forwarded-Host'] [0] == 'service.example.com'}"</pre>	Requests with the header <code>X-Forwarded-Host</code> , whose first value is <code>service.example.com</code> .
<pre>"condition": "#{find(request.uri.path, '^/openam/oauth2/access_token') && request.entity.form['client_id'][0] == 'client-service'}"</pre>	Requests where an OAuth 2.0 client named <code>client-service</code> issues the original access token request.
<pre>"condition": "#{find(request.uri.path, '^/openam/oauth2/access_token') && request.entity.form['grant_type'][0] == 'client_credentials'}"</pre>	Requests using the client credentials grant-type.

Router

A [Handler](#) that performs the following tasks:

- Defines the routes directory and loads routes into the configuration.
- Depending on the scanning interval, periodically scans the routes directory and updates the PingGateway configuration when routes are added, removed, or changed. The router updates the PingGateway configuration without needing to restart PingGateway or access the route.
- Manages an internal list of routes, where routes are ordered lexicographically by route name. If a route isn't named, then the route ID is used instead. Learn more in [Route](#).
- Routes requests to the first route in the internal list of routes, whose condition is satisfied.

Because the list of routes is ordered lexicographically by route name, name your routes with this in mind:

- If a request satisfies the condition of more than one route, it is routed to the first route in the list whose condition is met.

- Even if the request matches a later route in the list, it might never reach that route.

If a request doesn't satisfy the condition of any route, it is routed to the default handler if one is configured.

The router doesn't have to know about specific routes in advance - you can configure the router first and then add routes while PingGateway is running.



Important

Studio deploys and undeploys routes through a main router named `_router`, which is the name of the main router in the default configuration. If you use a custom `config.json`, make sure it contains a main router named `_router`.

Learn about Router metrics:

- [Metrics at the Prometheus Scrape Endpoint](#)
- [Router metrics at the Common REST Monitoring Endpoint \(deprecated\)](#)

Usage

```
{
  "name": string,
  "type": "Router",
  "config": {
    "defaultHandler": Handler reference,
    "directory": configuration expression<string>,
    "scanInterval": configuration expression<duration>,
    "delayRouteMetrics": configuration expression<boolean>
  }
}
```

An alternative value for type is RouterHandler.

Properties

"defaultHandler": *Handler [reference](#), optional*

Handler to use when a request doesn't satisfy the condition of any route.

Provide either the name of a handler object defined in the heap or an inline handler configuration object.

Default: If no default route is set either here or in the route configurations, PingGateway aborts the request with an internal error.

See also [Handlers](#).

"directory": *configuration expression<[string](#)>, optional*

Directory from which to load route configuration files. If this isn't an existing directory PingGateway can read, PingGateway creates the directory.

Default: The default directory for route configuration files, at `$HOME/.openig` (on Windows, `%appdata%\OpenIG`).

**Important**

The default setting is deprecated. Setting the "directory" will be required in a future release.

With the following example, route configuration files are loaded from `/path/to/safe/routes` instead of from the default directory:

```
{
  "type": "Router",
  "config": {
    "directory": "/path/to/safe/routes"
  }
}
```

**Important**

If you define multiple routers, configure directory so that the routers load route configuration files from different directories.

An infinite route-loading sequence is triggered when a router starts a route that, directly or indirectly, starts another router, which then loads route configuration files from the same directory.

Learn more in [PingGateway expressions](#).

"scanInterval": configuration expression<duration>, optional

Time interval at which PingGateway scans the specified directory for changes to routes. When a route is added, removed, or changed, the router updates the PingGateway configuration without needing to restart PingGateway or access the route.

When an integer is used for the `scanInterval`, the time unit is seconds.

To load routes at startup only, and prevent changes to the configuration if the routes are changed, set the scan interval to `disabled`.

Default: 10 seconds

"delayRouteMetrics": configuration expression<boolean>, optional

Whether to delay creation of route metrics until the first request passes through the route.

If you have many routes, consider setting `"delayRouteMetrics": true` to improve PingGateway startup time.

Default: `false`

Example

The following `config.json` file configures a Router:

```
{
  "handler": {
    "type": "Router",
    "name": "_router",
    "capture": "all"
  },
  "heap": [
    {
      "name": "capture",
      "type": "CaptureDecorator",
      "config": {
        "captureEntity": true,
        "_captureContext": true
      }
    }
  ],
  "session": {
    "type": "JwtSessionManager"
  }
}
```

Source: [config.json](#)

All requests pass with the default settings to the Router. The Router scans `$HOME/.openig/config/routes` at startup, and rescans the directory every 10 seconds. If routes have been added, deleted, or changed, the router applies the changes.

The main router and any subrouters build the monitoring endpoints. Learn more about information about monitoring endpoints in [PingGateway monitoring reference](#).

More information

[org.forgerock.openig.handler.router.RouterHandler](#)

SamIFederationHandler (deprecated)



Important

This handler is deprecated. Use the [SamIFederationFilter](#) instead.

A handler to play the role of SAML 2.0 Service Provider (SP).

Consider the following requirements for SamIFederationHandler:

- This handler doesn't support filtering; don't use it as the handler for a chain, which can include filters.
- Don't use this handler when its use depends on something in the response. The response can be handled independently of PingGateway, and can be `null` when control returns to PingGateway. For example, don't use this handler in a `SequenceHandler` where the `postcondition` depends on the response.
- Requests to the SamIFederationHandler must not be rebased, because the request URI must match the endpoint in the SAML metadata.

SAML in deployments with multiple instances of PingGateway

When PingGateway acts as a SAML service provider, session information is stored in the fedlet not the session cookie. In deployments with multiple instances of PingGateway as a SAML service provider, it is necessary to set up sticky sessions so that requests always hit the instance where the SAML interaction was started.

For information, refer to [Session state considerations](#) in AM's *SAML v2.0 guide*.

Usage

```
{
  "name": string,
  "type": "SamlFederationHandler",
  "config": {
    "assertionMapping": map or configuration expression<map>,
    "redirectURI": configuration expression<url>,
    "secretsProvider": SecretsProvider reference,
    "assertionConsumerEndpoint": configuration expression<url>,
    "authnContext": configuration expression<string>,
    "authnContextDelimiter": configuration expression<string>,
    "logoutURI": configuration expression<url>,
    "sessionIndexMapping": configuration expression<string>,
    "singleLogoutEndpoint": configuration expression<url>,
    "singleLogoutEndpointSoap": configuration expression<url>,
    "SPinitiatedSLOEndpoint": configuration expression<url>,
    "SPinitiatedSSOEndpoint": configuration expression<url>,
    "useOriginalUri": configuration expression<boolean>,
    "subjectMapping": configuration expression<string>
  }
}
```

Properties

"assertionMapping": *map or configuration expression<map>, required*

A map with the format `Map<String, String>`, where:

- Key: Session name, `localName`
- Value: SAML assertion name, `incomingName`, or a configuration expression that evaluates to the name

The following formats are allowed:

```
{
  "assertionMapping": {
    "string": "configuration expression<string>",
    ...
  }
}

{
  "assertionMapping": "configuration expression<map>"
}
```

In the following example, the session names `username` and `password` are mapped to SAML assertion names `mail` and `mailPassword` :

```
{
  "assertionMapping": {
    "username": "mail",
    "password": "mailPassword"
  }
}
```

If an incoming SAML assertion contains the following statement:

```
mail = demo@example.com
mailPassword = demopassword
```

Then the following values are set in the session:

```
username[0] = demo@example.com
password[0] = demopassword
```

For this to work, edit the `<Attribute name="attributeMap">` element in the SP extended metadata file, `$HOME/.openid/SAML/sp-extended.xml`, so that it matches the assertion mapping configured in the SAML 2.0 Identity Provider (IdP) metadata.

Because the dot character (`.`) serves as a query separator in expressions, don't use dot characters in the `localName`.

To prevent different handlers from overwriting each others' data, use unique `localName` settings when protecting multiple service providers.

"redirectURI": *configuration expression*[<url>](#), *required*

The page that the filter used to HTTP POST a login form recognizes as the login page for the protected application.

This is how PingGateway and the Federation component work together to provide SSO. When PingGateway detects the login page of the protected application, it redirects to the Federation component. Once the Federation handler validates the SAML exchanges with the IdP, and sets the required session attributes, it redirects back to the login page of the protected application. This allows the filter used to HTTP POST a login form to finish the job by creating a login form to post to the application based on the credentials retrieved from the session attributes.

"secretsProvider": *SecretsProvider* [reference](#), *optional*

The [SecretsProvider](#) to query for keys when AM provides signed or encrypted SAML assertions.

+ When this property isn't set, the keys are provided by direct keystore look-ups based on entries in the SP extended metadata file, `sp-extended.xml`.

+ Default: Empty.

"assertionConsumerEndpoint": *configuration expression*[<string>](#), *optional*

Default: `fedletapplication` (same as the Fedlet)

If you modify this attribute, change the metadata to match.

"authnContext": configuration expression<string>, optional

Name of the session field to hold the value of the authentication context. Because the dot character (.) serves as a query separator in expressions, don't use dot characters in the field name.

Use this setting when protecting multiple service providers, as the different configurations must not map their data into the same fields of `session`. Otherwise different handlers can overwrite each others' data.

As an example, if you set `"authnContext": "myAuthnContext"`, then PingGateway sets `session.myAuthnContext` to the authentication context specified in the assertion. When the authentication context is password over protected transport, then this results in the session containing `"myAuthnContext": "urn:oasis:names:tc:SAML:2.0:ac:classes:PasswordProtectedTransport"`.

Default: map to `session.authnContext`

"authnContextDelimiter": configuration expression<string>, optional

The authentication context delimiter used when there are multiple authentication contexts in the assertion.

Default: |

"logoutURI": configuration expression<string>, optional

Set this to the URI to visit after the user is logged out of the protected application.

You only need to set this if the application uses the single logout feature of the Identity Provider.

"sessionIndexMapping": configuration expression<string>, optional

Name of the session field to hold the value of the session index. Because the dot character (.) serves as a query separator in expressions, don't use dot characters in the field name.

Use this setting when protecting multiple service providers, as the different configurations must not map their data into the same fields of `session`. Otherwise different handlers can overwrite each others' data.

As an example, if you set `"sessionIndexMapping": "mySessionIndex"`, then PingGateway sets `session.mySessionIndex` to the session index specified in the assertion. This results in the session containing something like `"mySessionIndex": "s24ccbbffe2bfd761c32d42e1b7a9f60ea618f9801"`.

Default: map to `session.sessionIndex`

"singleLogoutEndpoint": configuration expression<string>, optional

Default: `fedletSLORedirect` (same as the Fedlet)

If you modify this attribute, change the metadata to match.

"singleLogoutEndpointSoap": configuration expression<string>, optional

Default: `fedletSloSoap` (same as the Fedlet)

If you modify this attribute, change the metadata to match.

"SPInitiatedSLOEndpoint": configuration expression<string>, optional

Default: `SPInitiatedSLO`

If you modify this attribute, change the metadata to match.

"SPInitiatedSSOEndpoint": *configuration expression*<string>, optional

Default: `SPInitiatedSSO`

If you modify this attribute, change the metadata to match.

"useOriginalUri": *configuration expression*<boolean>, optional

When `true`, use the original URI instead of a rebased URI when validating RelayState and Assertion Consumer Location URLs. Use this property if a `baseUri` decorator is used in the route or in `config.json`.

Default: `false`

"subjectMapping": *configuration expression*<string>, optional

Name of the session field to hold the value of the subject name. Because the dot character (`.`) serves as a query separator in expressions, don't use dot characters in the field name.

Use this setting when protecting multiple service providers, as the different configurations must not map their data into the same fields of `session`. Otherwise different handlers can overwrite each others' data.

As an example, if you set `"subjectMapping": "mySubjectName"`, then PingGateway sets `session.mySubjectName` to the subject name specified in the assertion. If the subject name is an opaque identifier, then this results in the session containing something like `"mySubjectName": "vt0k+APj1s9Rr4yCka6V9pGUuzUL"`.

Default: map to `session.subjectName`

Example

You can find an example of how to set up PingGateway as a SAML service provider in [SAML v2.0 and PingGateway](#).

In the following example, PingGateway receives a SAML 2.0 assertion from the IdP, and then logs the user in to the protected application using the username and password from the assertion:

```
{
  "name": "SamlFederationHandler",
  "type": "SamlFederationHandler",
  "config": {
    "assertionMapping": {
      "username": "mail",
      "password": "mailPassword"
    },
    "redirectURI": "/login",
    "logoutURI": "/logout"
  }
}
```

More information

org.forgerock.openig.handler.saml.SamlFederationHandlerHeaplet 

ScriptableHandler

Creates a response to a request by executing a script.

Scripts must return either a [Promise<Response, NeverThrowsException>](#) or a [Response](#).

This section describes the usage of ScriptableHandler. For information about script properties, available global objects, and automatically imported classes, see [PingGateway scripts](#).

Usage

```
{
  "name": string,
  "type": "ScriptableHandler",
  "config": {
    "type": configuration expression<string>,
    "file": configuration expression<string>, // Use either "file"
    "source": [ string, ... ],                // or "source", but not both
    "args": map,
    "clientHandler": Handler reference
  }
}
```

Properties

For information about properties for ScriptableHandler, refer to [PingGateway scripts](#).

More information

org.forgerock.openig.handler.ScriptableHandler

SequenceHandler

Processes a request through a sequence of handlers and post conditions, as follows:

- A request is treated by `handler1`, and then `postcondition1` is evaluated.
- If `postcondition1` is true, the request is then treated by `handler2`, and so on.

```
{
  "handler": handler1,
  "postcondition": expression1
},
{
  "handler": handler2,
  "postcondition": expression2
},
...
```

Use this handler for multi-request processing, such as retrieving a form, extracting form content (for example, a nonce), and then submitting it in a subsequent request.

Usage

```
{
  "name": string,
  "type": "SequenceHandler",
  "config": {
    "bindings": [
      {
        "handler": Handler reference,
        "postcondition": runtime expression<boolean>
      }
    ]
  }
}
```

Properties

"bindings": *array of [objects](#), required*

A list of handler and postcondition bindings.

"handler": *Handler [reference](#), required*

The [handler](#) to dispatch the request to when it is the first handler in the bindings, or for subsequent handlers when their previous `postcondition` yields `true`.

Provide the name of a Handler object defined in the heap or an inline Handler configuration object.

"postcondition": *runtime expression<[boolean](#)>, optional*

A flag to indicate that a post condition is met:

- `true` : The request is dispatched to the next handler in `bindings`.
- `false` : The sequence stops.

Postconditions are defined using PingGateway expressions, as described in [Expressions](#).

Default: `${true}`

StaticResponseHandler

Creates a response to a request statically, or based on something in the context.

Usage

```
{
  "name": string,
  "type": "StaticResponseHandler",
  "config": {
    "status": configuration expression<number>,
    "reason": configuration expression<string>,
    "headers": {
      configuration expression<string>: [ runtime expression<string>, ... ], ...
    },
    "trailers": {
      configuration expression<string>: [ runtime expression<string>, ... ], ...
    },
    "entity": runtime expression<string> or [ runtime expression<string>, ... ]
  }
}
```

Properties

"status": *Status object*

The response status. Learn more in [Status](#).

"reason": *configuration expression<string>, optional*

Used only for custom HTTP status codes. Learn more in [Response Status Codes](#) and [Status Code Registry](#).

"headers": *map, optional*

One or more headers to set for a response, with the format `name: [ value, ... ]`, where:

- *name* is a configuration expression<string> for a header name. If multiple expressions resolve to the same final string, *name* has multiple values.
- *value* one or more a runtime expression<strings> for header values.

When the property `entity` is used, set a `Content-Type` header with the correct content type value. The following example sets the content type of a message entity in the response:

```
"headers": {
  "Content-Type": [ "text/html; charset=UTF-8" ]
}
```

The following example redirects the original URI from the request:

```
"headers": {
  "Location": [
    "https://sp.example.com:8443/saml/SPInitiatedSSO"
  ]
}
```

Default: Empty

"trailers": *map, optional*

One or more trailers to set for a response, with the format `name: [ value, ... ]`, where:

- *name* is a configuration expression<[string](#)> for a trailer name. If multiple expressions resolve to the same string, *name* has multiple values.

The following trailer names aren't allowed:

- Message framing headers (for example, `Transfer-Encoding` and `Content-Length`)
- Routing headers (for example, `Host`)
- Request modifiers (for example, controls and conditionals such as `Cache-Control`, `Max-Forwards`, and `TE`)
- Authentication headers (for example, `Authorization` and `Set-Cookie`)
- `Content-Encoding`
- `Content-Type`
- `Content-Range`
- `Trailer`

- *value* is one or more runtime expression<[strings](#)> for trailer values.

Default: Empty

"entity": *runtime expression<string> or array of runtime expression<string>, optional*

The message entity body to include in a response.

If a `Content-Type` header is present, the entity must conform to the header and set the content length header automatically.

Methods are provided for accessing the entity as byte, string, or JSON content. Learn more in [Entity](#).



Important

Attackers during reconnaissance can use response messages to identify information about a deployment. For security, limit the amount of information in messages, and avoid using words that help identify PingGateway.

Default: Empty

Example

```
{
  "name": "ErrorHandler",
  "type": "StaticResponseHandler",
  "config": {
    "status": 500,
    "headers": {
      "Content-Type": [ "text/html; charset=UTF-8" ]
    },
    "entity": "<html><h2>Epic #FAIL</h2></html>"
  }
}
```

```
{
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "content-type": [ "text/html" ]
      },
      "entity": [
        "<html>",
        "  <body>",
        "    <h1>Request Details</h1>",
        "    <p>The path was: ${request.uri.path}</p>",
        "    <p>The query params were: ${toString(request.queryParams)}</p>",
        "    <p>The headers were: ${toString(request.headers.entrySet())}</p>",
        "  </body>",
        "</html>"
      ]
    }
  }
}
```

PingGateway filters

Filters intercept requests and responses during processing and change them as follows:

- Leave the request, response, and contexts unchanged; for example, log the context as it passes through the filter.
- In the request flow, change any aspect of the request, such as the URL, headers, or entity, or replace the request with a new [Request](#).
- In the response flow, change any aspect of the response, such as the status, headers, or entity, or return a new [Response](#).

PingGateway provides these filters:

- [AllowOnlyFilter](#)
- [AmSessionIdleTimeoutFilter](#)
- [AssignmentFilter](#)

- [AuthorizationCodeOAuth2ClientFilter](#)
- [CapturedUserPasswordFilter](#)
- [CertificateThumbprintFilter](#)
- [ChainOfFilters](#)
- [CircuitBreakerFilter](#)
- [ClientCredentialsOAuth2ClientFilter](#)
- [ClientSecretBasicAuthenticationFilter](#)
- [ClientSecretPostAuthenticationFilter](#)
- [ConditionEnforcementFilter](#)
- [ConditionalFilter](#)
- [CookieFilter](#)
- [CorsFilter](#)
- [CrossDomainSingleSignOnFilter](#)
- [CsrfFilter](#)
- [DataPreservationFilter](#)
- [DateHeaderFilter](#)
- [EncryptedPrivateKeyJwtClientAuthenticationFilter](#)
- [EntityExtractFilter](#)
- [FapiInteractionIdFilter](#)
- [FileAttributesFilter](#)
- [ForwardedRequestFilter](#)
- [FragmentFilter](#)
- [GrantSwapJwtAssertionOAuth2ClientFilter](#)
- [HeaderFilter](#)
- [HttpBasicAuthFilter](#)
- [HttpBasicAuthenticationClientFilter](#)
- [IdTokenValidationFilter](#)
- [JwtBuilderFilter](#)
- [JwtValidationFilter](#)
- [LocationHeaderFilter](#)

- [OAuth2ResourceServerFilter](#)
- [OAuth2TokenExchangeFilter](#)
- [PasswordReplayFilter](#)
- [PingOneApiAccessManagementFilter](#)
- [PingOneProtectEvaluationFilter](#)
- [PingOneProtectFeedbackFailureFilter](#)
- [PingOneProtectFeedbackSuccessFilter](#)
- [PolicyEnforcementFilter](#)
- [PrivateKeyJwtClientAuthenticationFilter](#)
- [ResourceOwnerOAuth2ClientFilter](#)
- [SamlFederationFilter](#)
- [ScriptableFilter](#)
- [SessionInfoFilter](#)
- [SetCookieUpdateFilter](#)
- [SingleSignOnFilter](#)
- [SqlAttributesFilter](#)
- [StaticRequestFilter](#)
- [SwitchFilter](#)
- [ThrottlingFilter](#)
- [TokenTransformationFilter](#)
- [TransactionIdOutboundFilter](#)
- [UmaFilter](#)
- [UriPathRewriteFilter](#)
- [UserProfileFilter](#)

AllowOnlyFilter

Authorizes a request to continue processing if it satisfies at least one of the configured rules. Otherwise, passes the request to the FailureHandler or returns an HTTP 401 Unauthorized, with an empty response body.

This filter manages requests from the *last request sender*, otherwise called the *request from the last hop*, or the *request from a direct client*.

For debugging, configure the AllowOnlyFilter `name`, and add the following logger to `logback.xml`, replacing `filter_name` with the name:

```
org.forgerock.openig.filter.allow.AllowOnlyFilter.filter_name
```

For more information, see [Managing PingGateway logs](#).

Usage

```
{
  "name": string,
  "type": "AllowOnlyFilter",
  "config": {
    "rules": [ object, ... ],
    "failureHandler": Handler reference
  }
}
```

Properties

"rules": array of *objects*, required

An array of one or more `rules` configuration objects to specify criteria for the request.

When more than one `rules` configuration object is included in the array, the request must match at least one of the configuration objects.

When more than one property is specified in the `rules` configuration (for example, `from` and `destination`) the request must match criteria for each property.

```
{
  "rules": [
    {
      "name": configuration expression<string>,
      "from": [ object, ... ],
      "destination": [ object, ... ],
      "when": configuration expression<boolean>
    },
    ...
  ]
}
```

"name": configuration expression<*string*>, optional

A name for the `rules` configuration. When logging is configured for the AllowOnlyFilter, the rule name appears in the logs.

"from": array of *objects*, required

An array of one or more `from` configuration objects to specify criteria about the last request sender (the direct client).

When more than one **from** configuration object is included in the array, the last request sender must match at least one of the configuration objects.

When both **ip** and **certificate** properties are included in the configuration, the last request sender must match criteria for both properties.

```
"from": [
  {
    "ip": {
      "list": [configuration expression<string>, ...],
      "resolver": runtime expression<string>
    },
    "certificate": {
      "subjectDNs" : Pattern[]
    }
  },
  ...
]
```

"ip": *object, optional*

Criteria about the IP address of the last request sender.

"list": *array of configuration expression<strings>, required:*

An array of IP addresses or IP address ranges, using IPv4 or IPv6, and CIDR notation. The following example includes different formats:

```
"list": ["127.0.0.1", "::1", "192.168.0.0/16", "1234::/16"]
```

The IP address of the last request sender must match at least one of the specified IP addresses or IP address ranges.

"resolver": *runtime expression<string>, optional:*

An expression that returns an IP address as a string.

The following example returns an IP address from the first item in the first **X-Forwarded-For** [header](#):

```
"resolver": "${split(request.headers['X-Forwarded-For'][0], ',')[0]}"
```

Default: Resolve the IP address from the following items, in the following order:

1. If there is a **Forwarded** header, use the IP address of the last hop.
2. Otherwise, if there is an **X-Forwarded-For** header, use the IP address of the last hop.
3. Otherwise, use the IP address of the connection.

"certificate": *object, optional*

A `certificate` configuration object specifying criteria about the certificate of the last request sender.

"subjectDNs": *array of patterns, required:*

An array of patterns to represent the expected distinguished name of the certificate subject, the `subjectDN`. The `subjectDN` of the last request sender must match at least one of the patterns.

"destination": *array of objects, optional*

An array of `destination` configuration objects to specify criteria about the request destination.

When more than one `destination` configuration object is included in the array, the request destination must match at least one of the configuration objects.

When more than one property is specified in the `destination` configuration, for example `hosts` and `ports`, the request destination must match criteria for each property.

```
"destination": [
  {
    "hosts": [pattern, ... ],
    "ports": [configuration expression<string>, ... ],
    "methods": [configuration expression<string>, ... ],
    "paths": [pattern, ... ]
  },
  ...
]
```

"hosts": *array of patterns, optional*

An array of *case-insensitive* patterns to match the `request.host` attribute. Patterns are matched with the Java [Pattern](#) class.

When this property is configured, the request destination must match at least one host pattern in the array.

Default: Any host is allowed.

"ports": *array of configuration expression<strings>, optional*

An array of strings to match the `request.port` attribute. Specify values in the array as follows:

- Array of single ports, for example `["80", "90"]`.
- Array of port ranges, for example `["100:200"]`.
- Array of single ports and port ranges, for example `["80", "90", "100:200"]`.

When this property is configured, the destination port must match at least one entry in the array.

Default: Any port is allowed.

"methods": *array of configuration expression<strings>, optional*

An array of HTTP methods to match the `request.method` attribute.

When this property is configured, the request method must match at least one method in the array.

Default: Any method is allowed.

"paths": array of *patterns*, optional

An array of *case-sensitive* patterns to match the `request.url_path` attribute. Patterns are matched with the Java [Pattern](#) class.

When this property is configured, the destination path must match at least one path in the array.

Default: Any path is allowed.

"when": runtime expression<*boolean*>, optional

A flag to indicate that the request meets a condition. When `true`, the request is allowed.

The following condition is met when the first value of `h1` is `1`:

```
"when": "${request.headers['h1'][0] == '1'}"
```

Default: `${true}`

"failureHandler": Handler *reference*, optional

Handler to treat the request if none of the declared rules are satisfied.

Provide either the name of a Handler object defined in the heap or an inline Handler configuration object.

Default: HTTP 401 Unauthorized, with an empty response body.

See also [PingGateway handlers](#).

Examples

Certificate and IP address conditions

In the following example, a request is authorized if the last request sender satisfies *either* of the following conditions:

- Certificate subject DN matches `.*CN=test$` or `CN=me`, and the IP address is in the range 1.2.3.0/24.
- IP address is 123.43.56.8.

```
"from": [
  {
    "certificate": {
      "subjectDNs": [".*CN=test$", "CN=me"]
    },
    "ip": {
      "list": ["1.2.3.0/24"]
    }
  },
  {
    "ip": {
      "list": ["123.43.56.8"]
    }
  }
]
```

Destination conditions

In the following example, a request is authorized if the request destination satisfies *all* of the following conditions:

- The host is `myhost1.com` or `www.myhost1.com`
- The port is `80`.
- The method is `POST` or `GET`
- The path matches `/user/*`.

```
"destination": [
  {
    "hosts": ["myhost1.com", "www.myhost1.com"],
    "ports": ["80"],
    "methods": ["POST", "GET"],
    "paths": ["/user/*"]
  }
]
```

Multiple rules

The following example authorizes a request to continue processing if the requests meets the conditions set by *either* `rule1` or `rule2`:

```

{
  "type": "AllowOnlyFilter",
  "config": {
    "rules": [
      {
        "name": "rule1",
        "from": [
          {
            "certificate": {
              "subjectDNs": [".*CN=test$", "CN=me"]
            },
            "ip": {
              "list": ["1.2.3.0/24"]
            }
          }
        ],
        "destination": [
          {
            "hosts": ["myhost1.com", "www.myhost1.com"],
            "ports": ["80"],
            "methods": ["POST", "GET"],
            "paths": ["/user/*"]
          }
        ],
        "when": "${request.headers['h1'][0] == '1'}"
      },
      {
        "name": "rule2",
        "when": "${request.headers['h1'][0] == '2'}"
      }
    ]
  }
}

```

More information

org.forgerock.openig.filter.allow.AllowOnlyFilter 

AmSessionIdleTimeoutFilter

Forces the revocation of AM sessions that have been idle for a specified duration. The AmSessionIdleTimeoutFilter issues an authenticated and encrypted JWT to track activity on the AM session and conveys it within a persistent cookie.

To help honor timeout, the persistent cookie is configured to expire at the same time as the tracking token. Without a persistent cookie, the browser is more likely to clear the side-car cookie and PingGateway is more likely to consider the session as timed out.

The tracking token contains the following parts:


- The time when the user was last active
- A hash of the AM session cookie, used to bind the tracking token to the AM session cookie
- The idle timeout

Multiple filter instances can share the same tracking token, for example, in a clustered PingGateway configuration, or when a federation of applications protected by authentication filters need to have a flexible idle timeout strategy.

AmSessionIdleTimeoutFilter requires the following configuration:

- In AM, client-side sessions must be enabled for the realm in which the tracking token operates. See [Configure client-side sessions](#) in AM's *Sessions Guide*.
- In AM, client-side session denylisting must be enabled. See [Configure client-side session denylisting](#) in AM's *Sessions Guide*.
- The AmSessionIdleTimeoutFilter must be placed in a route before a filter that uses the AM session token, such as a SingleSignOnFilter or PolicyEnforcementFilter.
- In production environments, and when multiple AmSessionIdleTimeoutFilters use the same tracking token, the encryption must not rely on the default configuration. It must be configured identically on each filter that uses the tracking token.

The following image shows the flow of information when an AmSessionIdleTimeoutFilter sits in front of a CrossDomainSingleSignOnFilter, to manage AM session timeout.



[1-5] When the AmSessionIdleTimeoutFilter receives an unauthenticated request, it passes the request along the chain, and the CrossDomainSingleSignOnFilter manages authentication.

[6-8] When the AmSessionIdleTimeoutFilter receives an authenticated request, it checks that the AM session token is valid, and then passes the request along the chain.

[9-10] If the AM session was valid, the `AmSessionIdleTimeoutFilter` issues a tracking token on the response flow, containing the following information:

- Hash of the AM session token
- Current timestamp
- Idle timeout of the current filter

If the AM session was not valid, the `AmSessionIdleTimeoutFilter` does nothing on the response flow.

[11-12] The `AmSessionIdleTimeoutFilter` places the tracking token in persistent tracking cookie, and sends it with the response, to be used in the next request.

[13-15] When the same or another `AmSessionIdleTimeoutFilter` receives an authenticated request with a tracking token, it checks that the AM session token is valid, and checks that tracking token hash is bound to the AM session.

[16] Depending on the strategy set by `idleTimeoutUpdate`, the `AmSessionIdleTimeoutFilter` selects the value for `idleTimeout` from the tracking token (set by the `AmSessionIdleTimeoutFilter` in a previous request) or from its own value of `idleTimeout` (if this is a different instance of `AmSessionIdleTimeoutFilter`).

The `AmSessionIdleTimeoutFilter` checks for AM session timeout. If the last activity time plus the idle timeout is before the current time, the session has timed out. For example, a session with the following values has timed out:

- last activity time: 15h30 today
- idle timeout: 5 mins
- current time: 15h40

[17-21] The AM session has timed out, so the `AmSessionIdleTimeoutFilter` does the following:

- Forces AM to revoke the session.
- Passes the request along the chain.
- Expires the tracking cookie on the response flow, and sends it with the response.

[22-26] The session has not timed out, so the `AmSessionIdleTimeoutFilter` does the following:

- Passes the request along the chain.
- Updates the tracking token on the response flow based on the `idleTimeoutUpdate` strategy.
- Places the tracking token in a persistent tracking cookie, and sends it with the response, to be used in the next request.

Usage

```
{
  "name": string,
  "type": "AmSessionIdleTimeoutFilter",
  "config": {
    "amService": AmService reference,
    "idleTimeout": configuration expression<duration>,
    "sessionToken": runtime expression<string>,
    "removeAmSessionFilter": Filter reference,
    "idleTimeoutUpdate": configuration expression<enumeration>,
    "secretsProvider": SecretsProvider reference,
    "encryptionSecretId": configuration expression<secret-id>,
    "encryptionMethod": configuration expression<string>,
    "cookie": object
  }
}
```

Properties

"amService": *AmService* [reference](#), *required*

The AmService that refers to the AM instance that issue tracked session token.

"idleTimeout": *configuration expression*<[duration](#)>, *required*

The time a session can be inactive before it is considered as idle.

When an AmSessionIdleTimeoutFilter creates the tracking token, the token's value for `idleTimeout` is set by this property. When a different AmSessionIdleTimeoutFilter accesses the same tracking token, depending on the strategy set by `idleTimeoutUpdate`, the token's value for `idleTimeout` can be updated by the second AmSessionIdleTimeoutFilter.

"sessionToken": *runtime expression*<[string](#)>, *optional*

The location of the AM session token in the request. The following example accesses the first value of the request cookie `iPlanetDirectoryPro`:

```
"sessionToken": "${request.cookies['iPlanetDirectoryPro']}[0].value}"
```

You can find more information in [Find the AM session cookie name](#).

Default: `${request.cookies['<cookie name defined in the referenced AmService>']}[0].value}`

"removeAmSessionFilter": *Filter* [reference](#), *optional*

A filter to remove the AM session details from the request when the session is no longer valid.

This helps in load-balanced AM deployments with client-side sessions where AM servers aren't necessarily in sync regarding expired client-side sessions. Set this to a custom filter if the AM session token isn't in the AM session cookie.

Default: a filter that removes the AM session token based on the AM session cookie name.

"idleTimeoutUpdate": configuration expression<enumeration>, required

When multiple AmSessionIdleTimeoutFilters use the same tracking token, this property defines what idle timeout to use for the request and how to set the idle timeout for the tracking token in the response.

Use one of the following values:

- **ALWAYS** : Enforce the idle timeout from this filter; in the response, set the new tracking token idle timeout to the idle timeout of this filter.
- **DECREASE_ONLY** : Enforce the shortest idle timeout from either this filter or the tracking token; in the response, set the new tracking token idle timeout to the shortest of the two.
- **INCREASE_ONLY** : Enforce the longest idle timeout from either this filter or the tracking token; in the response, set the new tracking token idle timeout to the longest of the two.
- **INCREASE_ONLY_THEN_ALWAYS** : Enforce the longest idle timeout from either this filter or the tracking token; in the response, set the new tracking token idle timeout to the idle timeout of this filter.
- **NEVER** : Enforce the idle timeout from the tracking token; in the response, set the new tracking token idle timeout to the idle timeout of the old tracking token.

PingGateway uses the new tracking token on the next interaction with an AmSessionIdleTimeoutFilter.

Default: **ALWAYS**

"secretsProvider": SecretsProvider reference, optional

The [SecretsProvider](#) to query for secrets to encrypt the tracking token.

"encryptionSecretId": configuration expression<secret-id>, optional

The secret ID of the encryption key used to encrypt the tracking cookie.

This secret ID must point to a [CryptoKey](#).

In production environments, and when multiple AmSessionIdleTimeoutFilters use the same tracking cookie, the encryption must not rely on the default configuration. It must be configured identically on each filter that uses the cookie.

Authenticated encryption is achieved with a symmetric encryption key. Therefore, the secret must refer to a symmetric key.

For more information, refer to [RFC 5116](#).

Default: When no **secretsProvider** is provided, PingGateway generates a random symmetric key for authenticated encryption.

"encryptionMethod": configuration expression<string>, optional

The algorithm to use for authenticated encryption. For information about allowed encryption algorithms, refer to [RFC 7518: "enc" \(Encryption Algorithm\) Header Parameter Values for JWE](#).

Default: A256GCM

"cookie": *object*, optional

Configuration of the activity tracking cookie.

```
{
  "name": configuration expression<string>,
  "domain": configuration expression<string>,
  "httpOnly": configuration expression<boolean>,
  "path": configuration expression<string>,
  "sameSite": configuration expression<enumeration>,
  "secure": configuration expression<boolean>
}
```

"name": *configuration expression*<string>, optional

The cookie name.

Default: `x-ig-activity-tracker`

"domain": *configuration expression*<string>, optional

Domain to which the cookie applies.

Default: The fully qualified hostname of the PingGateway host.

"httpOnly": *configuration expression*<boolean>, optional

Flag to mitigate the risk of client-side scripts accessing protected cookies.

Default: `true`

"path": *configuration expression*<string>, optional

Path to apply to the cookie.

Default: `/`

"sameSite": *configuration expression*<enumeration>, optional

Options to manage the circumstances in which a cookie is sent to the server. Use one of the following values to reduce the risk of CSRF attacks:

- **STRICT** : Send the cookie only if the request was initiated from the cookie domain. Not case-sensitive. Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.
- **LAX** : Send the cookie only with GET requests in a first-party context, where the URL in the address bar matches the cookie domain. Not case-sensitive. Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.
- **NONE** : Send the cookie whenever a request is made to the cookie domain. With this setting, consider setting `secure` to `true` to prevent browsers from rejecting the cookie. For more information, refer to [SameSite cookies](#).

Default: Null

"secure": *configuration expression*<*boolean*>, *optional*

Flag to limit the scope of the cookie to secure channels.

Default: `false`

Example

```
{
  "type": "AmSessionIdleTimeoutFilter",
  "config": {
    "sessionToken": "${request.cookies['iPlanetDirectoryPro'][0].value}",
    "amService": "AmService",
    "idleTimeout": "1 minute",
    "idleTimeoutUpdate": "ALWAYS",
    "cookie": {
      "name": "x-ig-activity-tracker",
      "domain": null,
      "path": "/",
      "secure": false,
      "httpOnly": true,
      "sameSite": null
    },
    "secretsProvider": "secrets-provider-ref",
    "encryptionMethod": "A256GCM",
    "encryptionSecretId": "crypto.key.secret.id"
  }
}
```

More information

org.forgerock.openig.openam.session.AmSessionIdleTimeoutFilter 

AssignmentFilter

Verifies that a specified condition is met. If the condition is met or if no condition is specified, the value is assigned to the target. Values can be assigned before the request is handled and after the response is handled.

Usage

```
{
  "name": string,
  "type": "AssignmentFilter",
  "config": {
    "onRequest": [
      {
        "condition": runtime expression<boolean>,
        "target": lvalue-expression,
        "value": runtime expression
      }, ...
    ],
    "onResponse": [
      {
        "condition": runtime expression<boolean>,
        "target": lvalue-expression,
        "value": runtime expression
      }, ...
    ]
  }
}
```

Properties

"onRequest": *array of [objects](#), optional*

Defines a list of assignment bindings to evaluate before the request is handled.

"onResponse": *array of [objects](#), optional*

Defines a list of assignment bindings to evaluate after the response is handled.

"condition": *runtime expression<[boolean](#)>, optional*

If the expression evaluates `true`, the value is assigned to the target.

Default: `${true}`

"target": *<[lvalue-expression](#)>, required*

Expression that yields the target object whose value is to be set.

"value": *runtime expression<[object](#)>, optional*

The value to be set in the target. The value can be a string, information from the context, or even a whole map of information.

Examples

Add info to a session

The following example assigns a value to a session to keep empty stateless session cookies:

```
{
  "type": "AssignmentFilter",
  "config": {
    "onRequest": [{
      "target": "${session.authUsername}",
      "value": "I am root"
    }]
  }
}
```

Capture and store login credentials

The following example captures credentials and stores them in the PingGateway session during a login request. Notice that the credentials are captured on the request but aren't marked as valid until the response returns a positive 302. The credentials could then be used to log a user in to a different application:

```
{
  "name": "PortalLoginCaptureFilter",
  "type": "AssignmentFilter",
  "config": {
    "onRequest": [
      {
        "target": "${session.authUsername}",
        "value": "${request.queryParams['username']}"
      },
      {
        "target": "${session.authPassword}",
        "value": "${request.queryParams['password']}"
      },
      {
        "comment": "Authentication has not yet been confirmed.",
        "target": "${session.authConfirmed}",
        "value": "${false}"
      }
    ],
    "onResponse": [
      {
        "condition": "${response.status.code == 302}",
        "target": "${session.authConfirmed}",
        "value": "${true}"
      }
    ]
  }
}
```

AuthorizationCodeOAuth2ClientFilter

Uses OAuth 2.0 delegated authorization to authenticate end users. The filter can act as an OpenID Connect relying party or as an OAuth 2.0 client.

AuthorizationCodeOAuth2ClientFilter performs the following tasks:

- Allows the user to select an Authorization Server from one or more static client registrations or by discovery and dynamic registration.

In static client registration, Authorization Servers are provided by [Issuer](#), and registrations are provided by [ClientRegistration](#).

- Redirects the user through the authentication and authorization steps of an OAuth 2.0 authorization code grant, which results in the Authorization Server returning an access token to the filter.
- When an authorization grant succeeds, injects the access token data into a configurable target in the context so that subsequent filters and handlers can access the access token. Subsequent requests can use the access token without authenticating again.
- When an authorization grant fails, the filter injects information about the failure into the [OAuth2FailureContext](#), which is provided to the `failureHandler` object.

Service URIs

Service URIs are constructed from the `clientEndpoint`, as follows:

`clientEndpoint/login/?discovery=user-input&goto=url`

Discover and register dynamically with the end user's OpenID Provider or with the client registration endpoint as described in RFC 7591, using the value of user-input.

After successful registration, redirect the end user to the provider for authentication and authorization consent. Then redirect the user agent back to the callback client endpoint, and then the goto URL.

The goto URL must use the same scheme, host, and port as the original URI, or be a relative URI (just the path). Otherwise, the request fails with an error.

To redirect a request to a site that doesn't meet the goto URL criteria, change the original URI by using a `ForwardedRequestFilter`.

`clientEndpoint/login?registration=clientId&issuer=issuerName&goto=url`

Redirect the end user for authorization with a registration defined by the [ClientRegistration](#) properties `clientId` and `issuerName`.

The provider corresponding to the registration then authenticates the end user and obtains authorization consent before redirecting the user agent back to the callback client endpoint.

If successful, the filter saves the authorization state in the session and redirects the user agent to the goto URL.

The goto URL must use the same scheme, host, and port as the original URI, or be a relative URI (just the path). Otherwise, the request fails with an error.

To redirect a request to a site that doesn't meet the goto URL criteria, change the original URI by using a `ForwardedRequestFilter`.

`clientEndpoint/logout?goto=url`

Remove the authorization state for the end user, and redirect the request to the goto URL.

The goto URL must use the same scheme, host, and port as the original URI, or be a relative URI (just the path). Otherwise, the request fails with an error.

To redirect a request to a site that doesn't meet the goto URL criteria, change the original URI by using a `ForwardedRequestFilter`.

If no goto URL is specified in the request, use `defaultLogoutGoto`.

clientEndpoint/callback

Handle the callback from the OAuth 2.0 Authorization Server occurring as part of the authorization process.

If the callback is handled successfully, the filter saves the authorization state in the context at the specified target location and redirects to the URL provided to the login endpoint during login.

Other request URIs

Restore the authorization state in the specified target location, and call the next filter or handler in the chain.

Usage

```
{
  "name": string,
  "type": "AuthorizationCodeOAuth2ClientFilter",
  "config": {
    "clientEndpoint": runtime expression<uri string>,
    "failureHandler": Handler reference,
    "loginHandler": Handler reference,
    "registrations": [ ClientRegistration reference, ... ],
    "metadata": object,
    "cacheExpiration": configuration expression<duration>,
    "executor": ScheduledExecutorService reference,
    "target": lvalue-expression,
    "defaultLoginGoto": runtime expression<url>,
    "defaultLogoutGoto": runtime expression<url>,
    "requireHttps": configuration expression<boolean>,
    "requireLogin": configuration expression<boolean>,
    "revokeOAuth2TokenOnLogout": configuration expression<boolean>,
    "openIdEndSessionOnLogout": configuration expression<boolean>,
    "prompt": configuration expression<string>,
    "issuerRepository": IssuerRepository reference, // deprecated
    "useDeprecatedIssuerRepository": configuration expression<boolean>, // deprecated
    "discoveryHandler": Handler reference,
    "discoverySecretId": configuration expression<secret-id>,
    "tokenEndpointAuthMethod": configuration expression<enumeration>,
    "tokenEndpointAuthSigningAlg": configuration expression<string>,
    "oAuth2SessionKey": configuration expression<string>,
    "secretsProvider": SecretsProvider reference
  }
}
```

Properties

clientEndpoint

`"clientEndpoint"` : *runtime expression<url>, required*

The URI to the client endpoint.

So that routes can accept redirects from the Authorization Server to the callback endpoint, the `clientEndpoint` must be the same as the route condition or a sub path of the route condition:

- The same as the route condition:

```
"condition": "${find(request.uri.path, '^/discovery')}"
```

```
"clientEndpoint": "/discovery"
```

- As a sub path of the route condition:

```
"condition": "${find(request.uri.path, '^/home/id_token')}"
```

```
"clientEndpoint": "/home/id_token/sub-path"
```

Service URIs are constructed from the `clientEndpoint`. For example, when `clientEndpoint` is `openid`, the service URIs are `/openid/login`, `/openid/logout`, and `/openid/callback`. These endpoints are implicitly reserved and attempts to access them directly can cause undefined errors.

The result of the expression must be a string that represents a valid URI, but isn't a real `java.net.URI` object. For example, it would be incorrect to use `${request.uri}`, which isn't a String but a `MutableUri`. Learn more in [PingGateway expressions](#).

failureHandler

`"failureHandler"`: *Handler [reference](#), optional*

An inline handler configuration object or the name of a handler object defined in the heap.

When the OAuth 2.0 Resource Server denies access to a resource, the failure handler can only be invoked if the error response contains a WWW-Authenticate header, which means there was a problem with the OAuth 2.0 exchange. All other responses are forwarded to the user agent without invoking the failure handler.

If the value of the WWW-Authenticate header is `invalid_token`, the `AuthorizationCodeOAuth2ClientFilter` tries to refresh the access token:

- If the token is refreshed, the `AuthorizationCodeOAuth2ClientFilter` tries again to access the protected resource.
- If the token isn't refreshed, or if the second attempt to access the protected resource fails, the `AuthorizationCodeOAuth2ClientFilter` invokes the failure handler.

You can configure the handler to access information in [OAuth2FailureContext](#).

Default: Fail with an HTTP 500 Internal Server error and log an exception with the failure context.

loginHandler

`"loginHandler"`: *Handler [reference](#), required if there are zero or multiple client registrations, optional if there is one client registration*

The handler to invoke when the user must select a registered identity provider for login. When `registrations` contains only one client registration, this handler is optional but is displayed if specified.

Provide the name of a [Handler](#) object defined in the heap or an inline handler configuration object.

When you use `loginHandler` in `AuthorizationCodeOAuth2ClientFilter`, retrieve the original target URI for the request from one of the following contexts:

- `originalUri` in [IdpSelectionLoginContext](#)
- `originalUri` in [UriRouterContext](#) (deprecated)
- `request.uri` (deprecated)

registrations

`"registrations"` : array of [ClientRegistration references](#) optional

List of client registrations to authenticate PingGateway to the Authorization Server.

The value represents a static [ClientRegistration](#) with an Authorization Server.

metadata

`"metadata"` : [object](#), required for dynamic client registration and ignored otherwise

The values of the object are evaluated as configuration expression [strings](#).

This object holds the client metadata described in [OpenID Connect Dynamic Client Registration 1.0](#) and optionally a list of scopes.

This object can also hold the client metadata described in RFC 7591, [OAuth 2.0 Dynamic Client Registration Protocol](#).

The following partial list of metadata fields isn't exhaustive. It includes metadata that is useful with AM as OpenID Provider:

`"redirect_uris"` : array of configuration expression [url](#), required

The array of redirection URIs to use when dynamically registering this client.

One of the registered values **must** match the `clientEndpoint`.

`"client_name"` : configuration expression [string](#), optional

Name of the client to present to the end user.

`"scope"` : [configuration expression string](#), optional

Space-separated string of scopes to request of the OpenID Provider, for example:

```
"scope" : "openid profile"
```

This property is available for dynamic client registration with AM and with Authorization Servers that support RFC 7591, [OAuth 2.0 Dynamic Client Registration Protocol](#).

"pkce_method": *configuration expression*<string>, optional

The [Proof Key for Code Exchange \(PKCE\)](#) code challenge method; one of:

- **S256** : Use a SHA256-based encoding of the code verifier.
- **none** : Disable PKCE.

Default: **S256**

cacheExpiration

"cacheExpiration" : *configuration expression*<duration>, optional

Duration for which to cache user-info resources.

PingGateway lazily fetches user info from the OpenID provider. In other words, PingGateway only fetches the information when a downstream Filter or Handler uses the user info. Caching allows PingGateway to avoid repeated calls to OpenID providers when reusing the information over a short period.

Set this to disabled or zero to disable caching. When caching is disabled, user info is still lazily fetched.

Default: 10 minutes

executor

"executor" : *ScheduledExecutorService* [reference](#), optional

A [ScheduledExecutorService](#) to schedule the execution of tasks, such as the eviction of entries in the OpenID Connect user information cache.

Default: **ScheduledExecutorService**

target

"target" : *lvalue-expression*, optional

An expression that yields the target object. Downstream filters and handlers can use data in the target to enrich the existing request or create a new request.

When the **target** is **openid**, the following information can be provided in **\${attributes.openid}**:

- **access_token** : Value of the OAuth 2.0 access token
- **scope** : Scopes associated with the OAuth 2.0 access token
- **token_type** : Authentication token type; for example, **Bearer**
- **expires_in** : Number of milliseconds until the OAuth 2.0 access token expires
- **id_token** : Value of the OpenID Connect token
- **id_token_claims** : Claims used in the OpenID Connect token
- **client_endpoint** : URL to the client endpoint

- **client_registration**: Client ID of the OAuth 2.0 client that enables PingGateway to communicate as an OAuth 2.0 client with an authorization server
- **user_info**: Profile attributes of an authenticated user; for example, **sub**, **name**, **family_name**

Data is provided to the target as follows:

- If the authorization process completes successfully, the `AuthorizationCodeOAuth2ClientFilter` injects the authorization state data into the target. In the following example, a downstream `StaticRequestFilter` retrieves the username and password from the target to log the user in to the sample application.

```
{
  "type": "StaticRequestFilter",
  "config": {
    "method": "POST",
    "uri": "https://app.example.com:8444/login",
    "form": {
      "username": [
        "${attributes.openid.user_info.sub}"
      ],
      "password": [
        "${attributes.openid.user_info.family_name}"
      ]
    }
  }
}
```

Learn about setting up this example in [Authenticate automatically to the sample application](#).

- If the **"failureHandler"** is invoked, the target can be populated with information such as the exception, client registration, and error.

Learn more in [PingGateway expressions](#).

Default: `${attributes.openid}`

defaultLoginGoto

"defaultLoginGoto": *runtime expression<url>, optional*

After successful authentication and authorization, if the user accesses the `clientEndpoint/login` endpoint without providing a landing page URL in the `goto` parameter, the request is redirected to this URI.

The goto URL must use the same scheme, host, and port as the original URI, or be a relative URI (just the path). Otherwise, the request fails with an error.

To redirect a request to a site that doesn't meet the goto URL criteria, change the original URI with a [ForwardedRequestFilter](#).

The result of the expression must be a string that represents a valid URI, but isn't a real `java.net.URI` object. For example, it would be incorrect to use `${request.uri}`, which is not a String but a `MutableUri`.

Default: return an empty page.

defaultLogoutGoto

`"defaultLogoutGoto" : runtime expression<url>, optional`

If the user accesses the `clientEndpoint/logout` endpoint without providing a goto URL, the request is redirected to this URI.

The goto URL must use the same scheme, host, and port as the original URI, or be a relative URI (just the path). Otherwise, the request fails with an error.

To redirect a request to a site that doesn't meet the goto URL criteria, change the original URI with a [ForwardedRequestFilter](#).

The result of the expression must be a string that represents a valid URI, but is not a real `java.net.URI` object. For example, it would be incorrect to use `${request.uri}`, which is not a String but a MutableUri.

Default: return an empty page.

requireHttps

`"requireHttps" : configuration expression<boolean>, optional`

Whether to require that original target URI of the request uses the HTTPS scheme.

If the received request doesn't use HTTPS, it is rejected.

Default: `true`

requireLogin

`"requireLogin" : configuration expression<boolean>, optional`

Whether to require authentication for all incoming requests.

Default: `true`

revokeOauth2TokenOnLogout

`"revokeOauth2TokenOnLogout" : configuration expression<boolean>, optional`

When `true`, call the `revocationEndpoint` defined in [Issuer](#) to revoke the access token or refresh token issued by the Authorization Server during login.

If this property is `false` or if `revocationEndpoint` in Issuer isn't defined, PingGateway doesn't revoke the tokens.

Processing errors generate warnings in the logs but don't break the logout flow.

Default: `false`

openIdEndSessionOnLogout

`"openIdEndSessionOnLogout" : configuration expression<boolean>, optional`

When `true`, redirect the user to the `endSessionEndpoint` defined in [Issuer](#) to log the user out of the Authorization Server. Use this property to initiate logout from an OpenID Connect resource provider.

If this property is `false` or if `endSessionEndpoint` in Issuer isn't defined, PingGateway doesn't redirect the user to log the user out of the Authorization Server.

If the user accesses the `endSessionEndpoint` endpoint without providing a goto URL, PingGateway redirects the request to the `defaultLogoutGoto`.

Learn more in [OpenID Connect Session Management](#).

Default: `false`

prompt

`"prompt"` : *configuration expression<string>, optional*

A space-separated, case-sensitive list of strings that indicate whether to prompt the end user for authentication and consent. Use in [OIDC flows](#) only.

Read the Authorization Server documentation for information about supported `prompt` values. For example, learn more in [prompt](#) in the PingOne Advanced Identity Cloud documentation or [prompt](#) in the AM documentation.

PingGateway provides the following values:

- `none` : Don't display authentication or consent pages. Don't use this value in the same list as `login`, `consent`, or `select_account`.
- `login` : Prompt the end user to reauthenticate even if they have a valid session on the Authorization Server.
- `consent` : Prompt the end user to consent before returning information to the client, even if they have already consented in the session.
- `select_account` : Prompt the end user to select a user account.

Prompt the end user to reauthenticate

```
"prompt": "login"
```

Prompt the end user to reauthenticate and consent

```
"prompt": "login consent"
```

issuerRepository (deprecated)

`"issuerRepository"` : *Issuer repository [reference](#), optional*

A repository of OAuth 2.0 issuers, built from discovered issuers and the PingGateway configuration.



Important

The `IssuerRepository` (deprecated) is deprecated.
 For issuers known in advance, add their settings to the `ClientRegistration`.
 For discovery, if the `IssuerRepository` had an `"issuerHandler"`, configure an `AuthorizationCodeOAuth2ClientFilter` `"discoveryHandler"` instead.

Provide the name of an `IssuerRepository` object defined in the heap.

Default: Look up an issuer repository named `IssuerRepository` in the heap. If none is explicitly defined, a default one named `IssuerRepository` is created in the current route.

`useDeprecatedIssuerRepository` (deprecated)

`"useDeprecatedIssuerRepository"` : *configuration expression* `<boolean>`, optional

Whether to use the deprecated default `"IssuerRepository"` from the heap.



Important

This property is deprecated.

- `true` : When the `"issuerRepository"` isn't set, use the deprecated default `"IssuerRepository"` from the heap.
- `false` : When the `"issuerRepository"` isn't set, don't use the deprecated default `"IssuerRepository"` and don't share registered or discovered issues with any `AuthorizationCodeOAuth2ClientFilters`.

Default: `false`

`discoveryHandler`

`"discoveryHandler"` : *Handler reference*, optional

Use this property for discovery and dynamic registration of OpenID Connect clients.

Provide either the name of a Handler object defined in the heap or an inline `Handler` configuration object. Usually, set this to the name of a `ClientHandler` configured in the heap or a `Chain` that ends in a `ClientHandler`.

Default: The default `ClientHandler`.

`discoverySecretId`

`"discoverySecretId"` : *configuration expression* `<secret-id>`, required for discovery and dynamic registration

Use this property for discovery and dynamic registration of OAuth 2.0 clients.

This secret ID must point to a `CryptoKey`.

This specifies the secret ID of the secret used to sign a JWT before the JWT is sent to the Authorization Server.

If `discoverySecretId` is used, then the `tokenEndpointAuthMethod` is always `private_key_jwt`.

tokenEndpointAuthMethod

"tokenEndpointAuthMethod" : *configuration expression* [<enumeration>](#), optional

Use this property for discovery and dynamic registration of OAuth 2.0 clients.

The authentication method with which a client authenticates to the authorization server or OpenID provider at the token endpoint. Learn about client authentication methods in the OpenID document on [Client Authentication](#).

The following client authentication methods are allowed:

- **client_secret_basic** : Clients that have received a **client_secret** value from the Authorization Server authenticate with the Authorization Server with HTTP basic access authentication:

```
POST /oauth2/token HTTP/1.1
Host: as.example.com
Authorization: Basic ....
Content-Type: application/x-www-form-urlencoded

grant_type=authorization_code&
code=...
```

- **client_secret_post** : Clients that have received a **client_secret** value from the Authorization Server authenticate with the Authorization Server with the client credentials in the request body:

```
POST /oauth2/token HTTP/1.1
Host: as.example.com
Content-Type: application/x-www-form-urlencoded

grant_type=authorization_code&
client_id=...&
client_secret=...&
code=...
```

- **private_key_jwt** : Clients send a signed JSON Web Token (JWT) to the Authorization Server. PingGateway builds and signs the JWT and prepares the request:

```
POST /token HTTP/1.1
Host: as.example.com
Content-Type: application/x-www-form-urlencoded

grant_type=authorization_code&
code=...&
client_id=<clientregistration_id>&
client_assertion_type=urn%3Aietf%3Aparams%3Aoauth%3Aclient-assertion-type%3Ajwt-bearer&
client_assertion=PHNhbWxwO1 ... ZT
```

If the Authorization Server doesn't support **private_key_jwt**, the dynamic registration falls back on the method returned by the Authorization Server; for example, **client_secret_basic** or **client_secret_post**.

If **tokenEndpointAuthSigningAlg** is not configured, the **RS256** signing algorithm is used for **private_key_jwt**.

Consider these points for identity providers:

- Some providers accept more than one authentication method.
- If a provider strictly enforces how the client must authenticate, align the authentication method with the provider.
- If a provider doesn't support the authentication method, the provider sends an HTTP 400 Bad Request response with an `invalid_client` error message, according to [RFC 6749: Error Response](#).
- If the authentication method is invalid, the provider sends an `IllegalArgumentException`.

Default: If `discoverySecretId` is used, then the `tokenEndpointAuthMethod` is always `private_key_jwt`. Otherwise, it is `client_secret_basic`.

tokenEndpointAuthSigningAlg

`"tokenEndpointAuthSigningAlg"` : *configuration expression<string>, optional*

The JSON Web Algorithm (JWA) used to sign the JWT that is used to authenticate the client at the token endpoint. The property is used when `private_key_jwt` is used for authentication.

If the Authorization Server sends a notification to use a different algorithm to sign the JWT, that algorithm is used.

Default: If `discoverySecretId` is used, then the `tokenEndpointAuthSigningAlg` is `RS256`. Otherwise, it is not used.

oAuth2SessionKey

`"oAuth2SessionKey"` : *configuration expression<string>, optional*

A key to identify an OAuth 2.0 session. The key can be any character string.

To share the same OAuth 2.0 session when a user accesses different applications protected by PingGateway, use the same key in each filter.

Default: The complete client endpoint URI. `AuthorizationCodeOAuth2ClientFilters` don't share OAuth 2.0 sessions.

secretsProvider

`"secretsProvider"` : *SecretsProvider [reference](#), required if `discoverySecretId` is used*

The [SecretsProvider](#) to query for passwords and cryptographic keys.

Examples

You can find more information in the following pages:

- [AM as OIDC provider](#)
- [Multiple OIDC providers using PingAM and PingOne Advanced Identity Cloud](#)
- [Discovery and dynamic registration with PingAM](#)

More information

[org.forgerock.openig.filter.oauth2.client.AuthorizationCodeOAuth2ClientFilter](#)

Issuer

ClientRegistration

The OAuth 2.0 Authorization Framework

The OAuth 2.0 Authorization Framework: Bearer Token Usage

[OpenID Connect](#) site, in particular the list of standard OpenID Connect 1.0 [scope values](#).

CapturedUserPasswordFilter

Makes an AM password available to PingGateway in the following steps:

- Checks for the presence of the SessionInfoContext context, at `contexts.amSession`.
 - If the context isn't present, or if `sunIdentityUserPassword` is `null`, the CapturedUserPasswordFilter collects session info and properties from AM.
 - If the context is present and `sunIdentityUserPassword` isn't `null`, the CapturedUserPasswordFilter uses that value for the password.
- The CapturedUserPasswordFilter decrypts the password and stores it in the CapturedUserPasswordContext, at `contexts.capturedPassword`.

Note

In PingOne Advanced Identity Cloud and from AM 7.5, the password capture and replay feature can optionally manage the replay password through AM's secret service. The secret label for the replay password must be `am.authentication.replaypassword.key`. For backward compatibility, if a secret isn't defined, is empty, or can't be resolved, AM manages the replay password through the AM system property `am.authentication.replaypassword.key`.

Usage

```
{
  "name": string,
  "type": "CapturedUserPasswordFilter",
  "config": {
    "amService": AmService reference,
    "keySecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference,
    "ssoToken": runtime expression<string>
  }
}
```

Properties

"amService": *AmService* [reference](#), *required*

The AmService heap object to use for the password. See also, [AmService](#).

"keySecretId": configuration expression<[secret-id](#)>, required

The secret ID for the key required decrypt the AM password.

This secret ID must point to a [CryptoKey](#) whose algorithm is AES.

**Important**

Although secrets of type `GenericSecret` are accepted, their usage is deprecated in this filter. Learn more in the [Deprecated](#) section of the *Release Notes*.

"secretsProvider": [SecretsProvider](#) reference, required

The [SecretsProvider](#) to query for secrets to decrypt the user password.

"ssoToken": runtime expression<[string](#)>, required

Location of the AM SSO token.

Default: `${request.cookiesAmService-ssoTokenHeader' ][0].value}`, where `AmService-ssoTokenHeader` is the name of the header or cookie where the AmService expects to find SSO tokens.

More information

[org.forgerock.openig.openam.CapturedUserPasswordFilter](#)

[org.forgerock.openig.openam.CapturedUserPasswordContext](#)

[CapturedUserPasswordContext](#)

[SessionInfoFilter](#)

CertificateThumbprintFilter

Extracts a Java certificate from a trusted header or from a TLS connection, computes the SHA-256 thumbprint of that certificate, and makes the thumbprint available for the `ConfirmationKeyVerifierAccessTokenResolver`. Use this filter to enable verification of certificate-bound access tokens.

`CertificateThumbprintFilter` computes and makes available the SHA-256 thumbprint of a client certificate as follows:

- Evaluates a runtime expression and yields a `java.security.cert.Certificate`
- Hashes the certificate using SHA-256
- Base64url-encodes the result
- Stores the result in the contexts chain

The runtime expression can access or build a client certificate from any information present at runtime, such as a PEM in a header, or a pre-built certificate.

Use `CertificateThumbprintFilter` with `ConfirmationKeyVerifierAccessTokenResolver` when the PingGateway instance is behind the TLS termination point, for example, when PingGateway is running behind a load balancer or other ingress point.

Usage

```
{
  "name": string,
  "type": "CertificateThumbprintFilter",
  "config": {
    "certificate": runtime expression<certificate>,
    "failureHandler": Handler reference,
  }
}
```

Properties

"certificate": runtime expression<certificate>, required

An EL expression which, when evaluated, yields an instance of a `java.security.cert.Certificate`.

Use the following [PingGateway functions](#) in the expression to define the hash, decoding, and certificate:

- `digestSha256`, to calculate the SHA-256 hash of the certificate.
- `decodeBase64url`, to decode an incoming base64url-encoded string.
- `derCertificate`, to convert a base64-encoded DER-format string into a certificate.
- `pemCertificate`, to convert a PEM-format string into a certificate.

Refer to [Examples](#).

"failureHandler": Handler reference, optional

Handler to treat the request on failure.

Provide an inline handler configuration object or the name of a handler object declared in the heap. See also [PingGateway handlers](#).

Default: HTTP 403 Forbidden, the request stops being executed.

Examples

Certificate from HTTPS

When PingGateway terminates TLS, use the certificate associated with the incoming HTTPS connection:

```
{
  "name": "CertificateThumbprintFilter-1",
  "type": "CertificateThumbprintFilter",
  "config": {
    "certificate": "${contexts.client.certificates[0]}"
  }
}
```

From an NGINX trusted header

When NINGX fronts PingGateway and terminates TLS, it can send the client certificate in a trusted header.

The following example uses `x-ssl-cert` as the trusted header. NGINX encodes the certificate in PEM format and URL-encodes the result:

```
{
  "name": "CertificateThumbprintFilter-2",
  "type": "CertificateThumbprintFilter",
  "config": {
    "certificate": "${pemCertificate(urlDecode(request.headers['x-ssl-cert'][0]))}"
  }
}
```

For details, refer to the NGINX [Module ngx_http_ssl_module](#) documentation.

From an Envoy or Istio trusted header

When Envoy or Istio fronts PingGateway and terminates TLS, it can send the client certificate in a field in a trusted header.

The following example uses `x-forwarded-client-cert` as the trusted header. Envoy puts the client certificate in the `Cert` field of the header value. Envoy encodes the certificate in PEM format and URL-encodes the result:

```
{
  "name": "CertificateThumbprintFilter-3",
  "type": "CertificateThumbprintFilter",
  "config": {
    "certificate": "${pemCertificate(urlDecode(findGroups(request.headers['x-forwarded-client-cert'][0], 'Cert=([^\n;]+);?')[1]))}"
  }
}
```

For details, refer to the Envoy [x-forwarded-client-cert](#) documentation.

More information

[org.forgerock.openig.filter.oauth2.cnf.CertificateThumbprintFilter](#)

ChainOfFilters

Dispatches a request to an ordered list of filters. Use this filter to assemble a list of filters into a single filter that you can then use in different places in the configuration.

A ChainOfFilters can be placed in a configuration anywhere that a filter can be placed.

Unlike `Chain`, `ChainOfFilters` doesn't finish by dispatching the request to a handler. Learn more in [Chain](#).

Usage

```
{
  "name": string,
  "type": "ChainOfFilters",
  "config": {
    "filters": [ Filter reference, ... ]
  }
}
```

Properties

"filters": array of *Filter references*, required

An array of names of filter objects defined in the heap, and inline filter configuration objects.

The chain dispatches the request to these filters in the order they appear in the array.

Learn more in [Filters](#).

Example

```
{
  "name": "MyChainOfFilters",
  "type": "ChainOfFilters",
  "config": {
    "filters": [ "Filter1", "Filter2" ]
  }
}
```

More information

org.forgerock.openig.filter.ChainFilterHeaplet 

CircuitBreakerFilter

Monitors failures. When the number of failures reaches a configured failure threshold, the circuit breaker trips, and the circuit is considered *open*. Calls to downstream filters are stopped, and a runtime exception is returned.

After a configured delay, the circuit breaker is reset, and is the circuit considered *closed*. Calls to downstream filters are restored.

Usage

```
{
  "name": string,
  "type": "CircuitBreakerFilter",
  "config": {
    "maxFailures": configuration expression<integer>,
    "openDuration": configuration expression<duration>,
    "slidingCounter": object,
    "openHandler": Handler reference,
    "executor": ScheduledExecutorService reference
  }
}
```

Properties

"maxFailures": *configuration expression<number>, required*

The maximum number of failed requests allowed in the window given by `size`, before the circuit breaker trips. The value must be greater than zero.


"openDuration": *configuration expression<duration>, required*

The duration for which the circuit stays open after the circuit breaker trips. The `executor` schedules the circuit to be closed after this duration.

"slidingCounter": *object, required*

A sliding window error counter. The circuit breaker trips when the number of failed requests in the number of requests given by `size` reaches `maxFailures`.

The following image illustrates how the sliding window counts failed requests:



```
{
  "slidingCounter": {
    "size": configuration expression<number>
  }
}
```

"size": *configuration expression*<number>, required

The size of the sliding window in which to count errors.

The value of `size` must be greater than zero, and greater than the value of `maxFailures`, otherwise an exception is thrown.

"openHandler": *Handler reference*, optional

The `Handler` to call when the circuit is open.

Default: A handler that throws a `RuntimeException` with a "circuit-breaker open" message.

"executor": *ScheduledExecutorService reference*, optional

A `ScheduledExecutorService` to schedule closure of the circuit after the duration given by `openDuration`.

Default: The default `ScheduledExecutorService` in the heap

Example

In the following example, the circuit breaker opens after 11 failures in the previous 100 requests, throwing a runtime exception with a "circuit-breaker open" message. The default `ScheduledExecutorService` in the heap closes the circuit-breaker after 10 seconds.

```
{
  "type": "CircuitBreakerFilter",
  "config": {
    "maxFailures": 10,
    "openDuration": "10 seconds",
    "openHandler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 500,
        "headers": {
          "Content-Type": [ "text/plain" ]
        },
        "entity": "Too many failures; circuit opened to protect downstream services."
      },
    },
    "slidingCounter": {
      "size": 100
    }
  }
}
```

More information

org.forgerock.openig.filter.circuitbreaker.CircuitBreakerFilter 

ClientCredentialsOAuth2ClientFilter

Authenticates OAuth 2.0 clients by using the client's OAuth 2.0 credentials to obtain an access token from an Authorization Server, and injecting the access token into the inbound request as a Bearer Authorization header. The access token is valid for the configured scopes.

The ClientCredentialsOAuth2ClientFilter obtains the client's access token by using the `client_credentials` grant type. Client authentication is provided by the `endpointHandler` property, which uses a client authentication filter, such as [ClientSecretBasicAuthenticationFilter](#). When a previous access token expires, the filter requests a new access token.

Use the ClientCredentialsOAuth2ClientFilter in a service-to-service context, where services need to access resources protected by OAuth 2.0.

Usage

```
{
  "name": string,
  "type": "ClientCredentialsOAuth2ClientFilter",
  "config": {
    "secretsProvider": SecretsProvider reference,
    "tokenEndpoint": configuration expression<url>,
    "scopes": [ configuration expression<string>, ... ],
    "endpointHandler": Handler reference
  }
}
```

Properties

"secretsProvider": *SecretsProvider* [reference](#), required

The [SecretsProvider](#) to query for passwords and cryptographic keys.

"tokenEndpoint": *configuration expression<url>*, required

The URL to the Authorization Server's OAuth 2.0 token endpoint.

"scopes": *array of configuration expression<strings>*, optional

Array of scope strings to request from the Authorization Server.

Default: Empty, request no scopes.

"endpointHandler": *Handler* [reference](#), optional

The Handler to exchange tokens on the authorization endpoint.

Configure this property as a [Chain](#), using one of the following client authentication filters:

- [ClientSecretBasicAuthenticationFilter](#)
- [ClientSecretPostAuthenticationFilter](#)
- [PrivateKeyJwtClientAuthenticationFilter](#)

```
{
  "name": "myHandler",
  "type": "Chain",
  "config": {
    "handler": "ForgeRockClientHandler",
    "filters": [
      {
        "type": "ClientSecretBasicAuthenticationFilter",
        "config": {
          "clientId": "myConfidentialClient",
          "clientSecretId": "my.client.secret.id",
          "secretsProvider": "mySystemAndEnvSecretStore",
        }
      }
    ]
  }
}
```

Default: ForgeRockClientHandler

Examples

For an example, refer to [Client credentials grant with PingAM](#).

More information

[org.forgerock.openig.filter.oauth2.client.ClientCredentialsOAuth2ClientFilterHeaplet](#)

[org.forgerock.openig.filter.oauth2.OAuth2ResourceServerFilterHeaplet](#)

[OAuth2ResourceServerFilter](#)

[The OAuth 2.0 Authorization Framework](#)

[The OAuth 2.0 Authorization Framework: Bearer Token Usage](#)

ClientSecretBasicAuthenticationFilter

Supports client authentication with the method `client_secret_basic`. Clients that have received a `client_secret` value from the Authorization Server authenticate through the HTTP basic access authentication scheme, as in the following example:

```
POST /oauth2/token HTTP/1.1
Host: as.example.com
Authorization: Basic ....
Content-Type: application/x-www-form-urlencoded

grant_type=authorization_code&
code=...
```

Use this filter with an endpoint `Handler` that requires `client_secret_basic` authentication. For example, `endpointHandler` in the [OAuth2TokenExchangeFilter](#) or [ClientCredentialsOAuth2ClientFilter](#).

Usage

```
{
  "name": string,
  "type": "ClientSecretBasicAuthenticationFilter",
  "config": {
    "clientId": configuration expression<string>,
    "clientSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference
  }
}
```

Configuration

"clientId": *configuration expression*<string>, required

The OAuth 2.0 client ID to use for authentication.

"clientSecretId": *configuration expression*<secret-id>, required

The OAuth 2.0 client secret to use for authentication.

This secret ID must point to a [GenericSecret](#).

"secretsProvider": *SecretsProvider reference*, required

The [SecretsProvider](#) to query for passwords and cryptographic keys.

Example

```
{
  "name": "ExchangeHandler",
  "type": "Chain",
  "config": {
    "handler": "ForgeRockClientHandler",
    "filters": [
      {
        "type": "ClientSecretBasicAuthenticationFilter",
        "config": {
          "clientId": "serviceConfidentialClient",
          "clientSecretId": "client.secret.id",
          "secretsProvider": "SystemAndEnvSecretStore-1"
        }
      }
    ]
  }
}
```

ClientSecretPostAuthenticationFilter

Supports client authentication with the method `client_secret_post`. Clients that have received a `client_secret` value from the Authorization Server authenticate by including the client credentials in the request body, as in the following example:


```
POST /oauth2/token HTTP/1.1
Host: as.example.com
Content-Type: application/x-www-form-urlencoded

grant_type=authorization_code&
client_id=...&
client_secret=...&
code=...
```

Use this filter with an endpoint `Handler` that requires `client_secret_post` authentication. For example, `endpointHandler` in the [OAuth2TokenExchangeFilter](#) or [ClientCredentialsOAuth2ClientFilter](#).

Usage

```
{
  "name": string,
  "type": "ClientSecretPostAuthenticationFilter",
  "config": {
    "clientId": configuration expression<string>,
    "clientSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference
  }
}
```

Configuration

"clientId": configuration expression<[string](#)>, required

The OAuth 2.0 client ID to use for authentication.

"clientSecretId": configuration expression<[secret-id](#)>, required

The OAuth 2.0 client secret to use for authentication.

This secret ID must point to a [GenericSecret](#).

"secretsProvider": *SecretsProvider* [reference](#), required

The [SecretsProvider](#) to query for passwords and cryptographic keys.

ConditionEnforcementFilter

Verifies that a specified condition is met. If the condition is met, the request continues to be executed. Otherwise, the request is referred to a failure handler, or PingGateway returns 403 Forbidden and the request is stopped.

Usage

```
{
  "name": string,
  "type": "ConditionEnforcementFilter",
  "config": {
    "condition": runtime expression<boolean>,
    "failureHandler": Handler reference
  }
}
```

Properties

"condition": runtime expression<boolean>, required

If the expression evaluates to `true`, the request continues to be executed.

"failureHandler": Handler reference, optional

Handler to treat the request if the condition expression evaluates as `false`.

Provide an inline handler configuration object or the name of a handler object declared in the heap. See also [PingGateway handlers](#).

Default: HTTP 403 Forbidden, the request stops being executed.

Example

The following example tests whether a request contains a session username. If it does, the request continues to be executed. Otherwise, the request is dispatched to the `ConditionFailedHandler` failure handler.

```
{
  "name": "UsernameEnforcementFilter",
  "type": "ConditionEnforcementFilter",
  "config": {
    "condition": "${not empty (session.username)}",
    "failureHandler": "ConditionFailedHandler"
  }
}
```

More information

[org.forgerock.openig.filter.ConditionEnforcementFilter](https://pingidentity.com/docs/forgerock/openig/filter/ConditionEnforcementFilter)

ConditionalFilter

Verifies that a specified condition is met. If the condition is met, the request is dispatched to a delegate Filter. Otherwise, the delegate Filter is skipped.

Use `ConditionalFilter` to easily use or skip a Filter depending on whether a condition is met. To easily use or skip a set of Filters, use a `ChainOfFilters` as the delegate Filter and define a set of Filters. For information, refer to [ChainOfFilters](#).

Usage

```
{
  "name": string,
  "type": "ConditionalFilter",
  "config": {
    "condition": runtime expression<boolean>,
    "delegate": Filter reference
  }
}
```

Properties

"condition": runtime expression<boolean>, required

If the expression evaluates to `true`, the request is dispatched to the delegate Filter. Otherwise the delegate Filter is skipped.

"delegate": Filter reference, required

Filter to treat the request when the condition expression evaluates as `true`.

See also [Filters](#).

Example

The following example tests whether a request finishes with `.js` or `.jpg`:

```
{
  "type": "Chain",
  "config": {
    "filters": [{
      "type": "ConditionalFilter",
      "config": {
        "condition": "${not (find(request.uri.path, '.js$') or find(request.uri.path, '.jpg$'))}",
        "delegate": "mySingleSignOnFilter"
      }
    }],
    "handler": "ReverseProxyHandler"
  }
}
```

If the request is to access a `.js` file or `.jpg` file, it skips the delegate `SingleSignOnFilter` filter declared in the heap, and passes straight to the `ReverseProxyHandler`.

If the request is to access another type of resource, it must pass through the delegate `SingleSignOnFilter` for authentication with AM before it can pass to the `ReverseProxyHandler`.

More information

[org.forgerock.openig.filter.ConditionalFilter](https://forgerock.org/openig/filter/ConditionalFilter)

CookieFilter

Manages, suppresses, and relays cookies for [stateful sessions](#). This filter isn't currently compatible with [stateless sessions](#).

Usage

```
{
  "name": string,
  "type": "CookieFilter",
  "config": {
    "managed": [ configuration expression<string>, ... ],
    "suppressed": [ configuration expression<string>, ... ],
    "relayed": [ configuration expression<string>, ... ],
    "defaultAction": configuration expression<enumeration>
  }
}
```

Properties

"managed": array of configuration expression<strings>, optional

A list of the names of cookies to be managed.

PingGateway stores cookies from the protected application in the session and manages them as follows:

- Requests with a `Cookie` header: PingGateway removes managed cookies so that protected applications cannot see them.
- Responses with a `Set-Cookie` header: PingGateway removes managed cookies and keeps a copy of them. PingGateway then adds the managed cookies in a `Cookie` header to future requests that traverse the CookieFilter.

"suppressed": array of configuration expression<strings>, optional

A list of the names of cookies to be suppressed.

PingGateway removes cookies from the request and response. Use this option to hide domain cookies, such as the AM session cookie, that are used by PingGateway but aren't usually used by protected applications.

"relayed": array of configuration expression<strings>, optional

A list of the names of cookies to be relayed.

PingGateway transmits cookies freely from the user agent to the remote server, and vice versa.

"defaultAction": configuration expression<enumeration>, optional

Action to perform for cookies that don't appear in one of the above lists. Set to `MANAGE`, `SUPPRESS`, or `RELAY`.

If a cookie appears in more than one of the above lists, it is treated in the following order of precedence: `managed`, `suppressed`, `relayed`. For example, if a cookie is in both the `managed` and `relayed` lists, the cookie is managed.

Default: `"MANAGE"`.

More information

org.forgerock.openig.filter.CookieFilter 

CorsFilter

Configures policies for cross-origin resource sharing (CORS), to allow cross-domain requests from user agents.

Usage

```
{
  "name": string,
  "type": "CorsFilter",
  "config": {
    "policies": [ {
      "acceptedOrigins": [ configuration expression<url>, ... ] or "*",
      "acceptedMethods": [ configuration expression<string>, ... ] or "*",
      "acceptedHeaders": [ configuration expression<string>, ... ] or "*",
      "exposedHeaders": [ configuration expression<string>, ... ],
      "maxAge": configuration expression<duration>,
      "allowCredentials": configuration expression<boolean>
    }, ... ],
    "failureHandler": Handler reference
  }
}
```

Properties

policies

"policies": array of *objects*, required

One or more policies to apply to the request. A policy is selected when the origin of the request matches the accepted origins of the policy.

When multiple policies are declared, PingGateway tries them in the order they are declared. PingGateway selects the first matching policy.

"acceptedOrigins": array of configuration expression<urls> or "*", required

A comma-separated list of *origins* to match the origin of the CORS request. Alternatively, use `*` to allow requests from any URL.

If the request origin isn't in the list of accepted origins, PingGateway invokes the failure handler or returns an HTTP 403 Forbidden response and stops processing the request.

Origins are URLs with a scheme, hostname, and optionally a port number; for example, `https://www.example.com`. If a port number isn't defined, origins with no port number or with the default port number (80 for HTTP, 443 for HTTPS) are accepted.

Examples:

```
{
  "acceptedOrigins": [
    "https://www.example.com",
    "https://example.org:8433"
  ]
}
```

```
{
  "acceptedOrigins": "*"
}
```

"acceptedMethods": array of configuration expression<strings> or "*", optional

A comma-separated list of case-sensitive HTTP method names allowed when making CORS requests. Alternatively, use `*` to allow requests with any method.

In preflight requests, browsers use the `Access-Control-Request-Method` header to let the server know which HTTP method might be used in the actual request.

- If all requested methods are allowed, the requested methods are returned in the preflight response, in the `Access-Control-Allow-Methods` header.
- If any requested method isn't allowed, the `Access-Control-Allow-Methods` header is omitted. The failure handler isn't invoked, but the user agent interprets the preflight response as a CORS failure.

Examples:

```
{
  "acceptedMethods": [
    "GET",
    "POST",
    "PUT",
    "MyCustomMethod"
  ]
}
```

```
{
  "acceptedMethods": "*"
}
```

Default: All methods are rejected.

"acceptedHeaders": array of configuration expression<strings> or "*", optional

A comma-separated list of case-insensitive request header names allowed when making CORS requests. Alternatively, use `*` to allow requests with any header.

In preflight requests, browsers use the `Access-Control-Request-Headers` header to let the server know which HTTP headers might be used in the actual request.

- If all requested headers are allowed, the requested headers are returned in the preflight response, in the `Access-Control-Allow-Headers` header.
- If any requested header isn't allowed, the `Access-Control-Allow-Headers` header is omitted. The failure handler isn't invoked, but the user agent interprets the preflight response as a CORS failure.

Examples:

```
{
  "acceptedHeaders": [
    "iPlanetDirectoryPro",
    "X-OpenAM-Username",
    "X-OpenAM-Password",
    "Accept-API-Version",
    "Content-Type",
    "If-Match",
    "If-None-Match"
  ]
}
```

```
{
  "acceptedHeaders": "*"
}
```

Default: Reject all requested headers.

"exposedHeaders": *list of configuration expression*<string>, optional

A comma-separated list of case-insensitive response header names returned in the `Access-Control-Expose-Headers` header.

Only headers in this list, safe headers, and these simple response headers are exposed to frontend JavaScript code:

- `Cache-Control`
- `Content-Language`
- `Expires`
- `Last-Modified`
- `Pragma`
- `Content-Type`

Example:

```
{
  "exposedHeaders": [
    "Access-Control-Allow-Origin",
    "Access-Control-Allow-Credentials",
    "Set-Cookie"
  ]
}
```

Default: No headers are exposed.

"maxAge": *configuration expression*<duration>, optional

The maximum duration for which a browser is allowed to cache a preflight response. The value is included in the `Access-Control-Max-Age` header of preflight responses.

When this `maxAge` is greater than the browser's maximum internal value, the browser value takes precedence.

Default: 5 seconds

"allowCredentials": *configuration expression*<boolean>, optional

A flag to allow requests that use credentials, such as cookies, authorization headers, or TLS client certificates.

Set to `true` to set the `Access-Control-Allow-Credentials` header to `true` and allow browsers to expose the response to frontend JavaScript code.

Default: `false`

failureHandler

"failureHandler" : *Handler reference*, optional

Handler invoked during the preflight request when the request origin doesn't match any of the `acceptedOrigins` defined in [policies](#).

The failure handler isn't invoked when requested headers or requested methods aren't allowed.

Provide an inline [Handler](#) configuration object or the name of a handler object declared in the heap.

Default: PingGateway returns HTTP 403 Forbidden and stops processing the request.

More information

org.forgerock.http.filter.cors.CorsFilter [↗](#)

org.forgerock.openig.filter.CorsFilterHeaplet [↗](#)

<https://fetch.spec.whatwg.org/#http-cors-protocol> [↗](#)

CrossDomainSingleSignOnFilter

When PingGateway and AM are running in the same domain, the [SingleSignOnFilter](#) can be used for SSO. When PingGateway and AM are running in different domains, AM cookies aren't visible to PingGateway because of the same-origin policy. The `CrossDomainSingleSignOnFilter` provides a mechanism to push tokens issued by AM to PingGateway running in a different domain.

When this filter processes a request, it injects the CDSSO token, the session user ID, and the full claims set into the [CdSsoContext](#). If an error occurs during authentication, information is captured in the [CdSsoFailureContext](#).

You can find an example of how to configure CDSSO and information about the CDSSO data flow in [Cross-domain single sign-on for PingAM](#).

WebSocket notifications for sessions

When WebSocket notifications are set up for sessions, PingGateway receives a notification from AM when a user logs out of AM, or when the AM session is modified, closed, or times out. PingGateway then evicts entries that are related to the event from the `sessionCache`.

For information about setting up WebSocket notifications, using them to clear the session cache, and including them in the server logs, refer to [WebSocket notifications](#).

Usage

```
{
  "name": string,
  "type": "CrossDomainSingleSignOnFilter",
  "config": {
    "amService": AmService reference,
    "redirectEndpoint": configuration expression<url>,
    "authenticationService": configuration expression<string>,
    "authCookie": {
      "name": configuration expression<string>,
      "domain": configuration expression<string>,
      "httpOnly": configuration expression<boolean>,
      "path": configuration expression<string>,
      "sameSite": configuration expression<enumeration>,
      "secure": configuration expression<boolean>
    },
    "redirectionMarker": {
      "enabled": configuration expression<boolean>,
      "name": configuration expression<string>
    },
    "defaultLogoutLandingPage": configuration expression<url>,
    "logoutExpression": runtime expression<boolean>,
    "failureHandler": Handler reference,
    "verificationSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference,
    "lifetime": configuration expression<duration>
  }
}
```

Properties

amService

"amService" : *AmService* [reference](#), required

The [AmService](#) to use.

redirectEndpoint

"redirectEndpoint" : *configuration expression*[<url>](#), required

The URI to which AM redirects the browser with the authentication token or an authentication error. The filter checks that the authentication was initiated by PingGateway.

Configure this URI to be the same as that in AM.

To make sure the redirect is routed back to the CrossDomainSingleSignOnFilter, include the endpoint in the route condition in one of the following ways:

- As a sub-path of the condition path.

For example, use the following route condition with the following endpoint:

```
"condition": "${find(request.uri.path, '^/home/cdsso')}"
```

```
"redirectEndpoint": "/home/cdsso/callback"
```

- To match the route condition.

For example, use the following route condition with the following endpoint:

```
"condition": "${find(request.uri.path, '^/home/cdsso')}"
```

```
"redirectEndpoint": "/home/cdsso"
```

With this route condition, all POST requests on the condition path are treated as AM CDSO callbacks. Any POST requests that aren't the result of an AM CDSO callback fail.

- As a specific path that isn't related to the condition path.

To make sure the redirect is routed back to this filter, include the redirect endpoint as a path in the filter condition.

For example, use the following route condition with the following endpoint:

```
"condition": "${find(request.uri.path, '^/home/cdsso/redirect') || find(request.uri.path, '^/ig/cdssoRedirectUri')}"
```

```
"redirectEndpoint": "/ig/cdssoRedirectUri"
```

authenticationService

"authenticationService" : *configuration expression*<string>, optional

The name of an AM authentication tree/journey to use for authentication. Learn more about trees in the AM documentation on [authentication nodes and trees](#).

Default: AM's default authentication tree.

authCookie

"authCookie" : *object*, optional

The configuration of the cookie used to store the authentication.

"name" : *configuration expression*<string>, optional

Name of the cookie containing the authentication token from AM.

For security, change the default name of cookies.

Default: `ig-token-cookie`

"domain" : *configuration expression*<string>, optional

Domain to which the cookie applies.

Set a domain only if the user agent is able to reemit cookies on that domain on its next hop. For example, to reemit a cookie on the domain `example.com`, the user agent must be able to access that domain on its next hop.

Default: The fully qualified hostname of the user agent's next hop.

"httpOnly" : *configuration expression*<boolean>, optional

Flag to mitigate the risk of client-side scripts accessing protected cookies.

Default: `true`

"path" : *configuration expression*<string>, optional

Path protected by this authentication.

Set a path only if the user agent is able to reemit cookies on the path. For example, to reemit a cookie on the path `/home/cdsso`, the user agent must be able to access that path on its next hop.

Default: The path of the request that got the `Set-Cookie` in its response.

"sameSite": configuration expression<enumeration>, optional

Options to manage the circumstances in which a cookie is sent to the server. Use one of the following values to reduce the risk of CSRF attacks:

- **STRICT** : Send the cookie only if the request was initiated from the cookie domain. Not case-sensitive.

Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.

- **LAX** : Send the cookie only with GET requests in a first-party context, where the URL in the address bar matches the cookie domain. Not case-sensitive.

Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.

- **NONE** : Send the cookie whenever a request is made to the cookie domain. Not case-sensitive.

With this setting, set **"secure": true** to prevent browsers from rejecting the cookie. Learn more in [SameSite cookies](#).

**Note**

For CDSSO, set **"sameSite": "none"** and **"secure": "true"**.

For security reasons, many browsers require a secure browser connection (HTTPS) for **"sameSite": "none"**. If the connection used by the browser isn't secure (HTTP), the browser won't supply cookies with **"sameSite": "none"**.

Learn more in [Cross-domain single sign-on for PingAM](#).

Default: **LAX**

"secure": configuration expression<boolean>, optional

Flag to limit the scope of the cookie to secure channels.

Set this flag only if the user agent is able to reemit cookies over HTTPS on its next hop. For example, to reemit a cookie with the **secure** flag, the user agent must be connected to its next hop by HTTPS.

Default: **false**

redirectionMarker**"redirectionMarker": configuration expression<object>, optional**

A redirect marker for the CDSSO flow. If the marker is present in the CDSSO flow, the request isn't redirected for authentication.

This feature is on by default to prevent redirect loops when the session cookie isn't present in the CDSSO flow. The cookie can be absent from the flow if it doesn't include PingGateway's domain.

"enabled": configuration expression<boolean>, optional

- **true** : When the session is empty or invalid, PingGateway checks the request **goto** query parameter for the presence of the redirection marker:
 - If the redirection marker is present, PingGateway fails the request.
 - If the redirection marker isn't present, PingGateway redirects the user-agent for login.

- `false`: PingGateway never checks the request `goto` query parameter for the presence of a redirection marker.

Default: `true`

"name": *configuration expression*<string>, optional

The name of the redirection marker query parameter to use when `enabled` is `true`.

Default: `_ig`

defaultLogoutLandingPage

"defaultLogoutLandingPage" : *configuration expression*<url>, optional

The URL to which a request is redirected if `logoutExpression` is evaluated as true.

If this property isn't an absolute URL, the request is redirected to the PingGateway domain name.

This parameter is effective only when `logoutExpression` is specified.

Default: None, processing continues.

logoutExpression

A flag to indicate whether a request initiates logout processing before reaching the protected application.

- `false`: The request doesn't initiate logout processing:
 - If a valid AM session is found, the request is forwarded to the protected application.
 - If a valid AM session isn't found, the request triggers login.
- `true`: The request initiates logout processing:
 - If a valid AM session is found, the session is revoked, and the request is forwarded as follows:
 - If `defaultLogoutLandingPage` is defined, the request is forwarded to the specified logout page.
 - If `defaultLogoutLandingPage` isn't defined, the request is forwarded to the protected application without any other validation.
 - If a valid session isn't found, the request is forwarded to the protected application without any other validation.

Important

To prevent unwanted access to the protected application, use `logoutExpression` with extreme caution as follows:

- Define a `defaultLogoutLandingPage`.
- If you don't define a `defaultLogoutLandingPage`, specify `logoutExpression` to resolve to **true only** for requests that target dedicated logout pages of the protected application.

Consider the following examples when a `defaultLogoutLandingPage` isn't configured:

- This expression resolves to **true only** for requests with `/app/logout` in their path:

```
"logoutExpression": ${startsWith(request.uri.rawPath, '/app/logout')}
```

When a request matches the expression, the AM session is revoked, and the request is forwarded to the `/app/logout` page.

- This expression resolves to **true** for **all** requests that contain `logOff=true` in their query parameters:

```
"logoutExpression": ${find(request.uri.query, 'logOff=true')}
```

When a request matches the expression, the AM session is revoked, and the request is forwarded to the protected application without any other validation. In this example, an attacker can bypass PingGateway's security mechanisms by adding `?logOff=true` to a request.

Default: `${false}`

failureHandler

`"failureHandler"`: *Handler [reference](#), optional*

[Handler](#) to treat the request if an error occurs during authentication.

If an error occurs during authentication, PingGateway populates a [CdSsoFailureContext](#) with details of the error and any associated [Throwable](#). This is available to the failure handler so it can respond appropriately.

Be aware the failure handler doesn't play a direct role in user authentication. It is only invoked if there is a problem that prevents user authentication from taking place.

A number of circumstances may cause the failure handler to be invoked, including:

- The redirect endpoint is invalid.
- The redirect endpoint is invoked without a valid CDSSO token.
- The redirect endpoint is invoked inappropriately.
- An error was reported by AM during authentication.

If no failure handler is configured, the default failure handler is used.

Default: HTTP 200 OK. The response entity contains details of the error.

verificationSecretId

`"verificationSecretId"` : configuration expression<[secret-id](#)>, required if PingGateway can't discover and use a JWK set specified by ``amservice``

The secret ID for the secret to verify the signature of AM session tokens. This secret ID must point to a [CryptoKey](#).

PingGateway verifies the token as follows:

- If `verificationSecretId` is NOT set, PingGateway validates the JWT against the JWKs provided by the AM service. There is no fallback.
- If `verificationSecretId` is set with a `secretsProvider`, PingGateway validates the JWT signature with a named or valid secrets strategy:
 - First, PingGateway uses a secret obtained with the secret ID:
 - For JWK sets, the secret ID should map to a `kid` of one of the JWKs.
 - For keystores, the secret ID should map to an alias of one of the keys associated with the secret ID.
 - If PingGateway finds no named secrets, it tries with all valid secrets mapped to the secret ID.

Learn more in [Validate the signature of signed tokens](#) and [Secrets](#).

secretsProvider

`"secretsProvider"` : [SecretsProvider reference](#), required when `verificationSecretId` is set

The [SecretsProvider](#) to query for passwords and cryptographic keys.

lifetime

`"lifetime"` : configuration expression<[duration](#)>, optional

When more than one authentication happens during the lifetime of the session, this sets the duration after which PingGateway removes the initial CDSSO authentication session state.

Default: 5 minutes

Example

You can find an example that uses the `CrossDomainSingleSignOnFilter` in [Cross-domain single sign-on for PingAM](#).

More information

[org.forgerock.openig.openam.CrossDomainSingleSignOnFilter](#) 

[CdSsoContext](#)

[CdSsoFailureContext](#)

[SsoTokenContext](#)

CsrfFilter

Prevent Cross Site Request Forgery (CSRF) attacks when using cookie-based authentication, as follows:

- When a session is created or updated for a client, generate a CSRF token as a hash of the session cookie.
- Send the token in a response header to the client, and require the client to provide that header in subsequent requests.
- In subsequent requests, compare the provided token to the generated token.
- If the token isn't provided or can't be validated, reject the request and return a valid CSRF token transparently in the response header.

Rogue websites that attempt CSRF attacks operate in a different website domain to the targeted website. Because of same-origin policy, rogue websites can't access a response from the targeted website, and cannot, therefore, access the CSRF token.

Usage

```
{
  "name": string,
  "type": "CsrfFilter",
  "config": {
    "cookieName": configuration expression<string>,
    "headerName": configuration expression<string>,
    "excludeSafeMethods": configuration expression<boolean>,
    "failureHandler": Handler reference
  }
}
```

Properties

"cookieName": *configuration expression<string>, required*

The name of the HTTP session cookie used to store the session ID. For example, use the following cookie names for the following processes:

- SSO with the [SingleSignOnFilter](#): Use the name of the AM session cookie. You can find more information in [Find the AM session cookie name](#).
- CDSO with the [CrossDomainSingleSignOnFilter](#): Use the name configured in `authCookie.name`.
- OpenID Connect with the [AuthorizationCodeOAuth2ClientFilter](#): Use the name of the PingGateway HTTP session cookie (default, `IG_SESSIONID`). You can find more information about the PingGateway session cookie in [admin.json](#).
- SAML: Use the name of the PingGateway HTTP session cookie (default, `IG_SESSIONID`). You can find more information about the PingGateway session cookie in [admin.json](#).

"headerName": *configuration expression<string>, optional*

The name of the header that carries the CSRF token. The same header is used to create and verify the token.

Default: `X-CSRF-Token`

"excludeSafeMethods": *configuration expression*<boolean>, optional

Whether to exclude GET, HEAD, and OPTION methods from CSRF testing. In most cases, these methods are assumed as safe from CSRF.

Default: `true`

"failureHandler": *Handler reference*, optional

Handler to treat the request if the CSRF the token isn't provided or can't be validated. Provide an inline handler declaration, or the name of a handler object defined in the heap.

Although PingGateway returns the CSRF token transparently in the response header, this handler cannot access the CSRF token.

Default: Handler that generates `HTTP 403 Forbidden`.

Example

You can find an example of how to harden protection against CSRF attacks in [CSRF protection with PingGateway](#).

```
{
  "name": "CsrfFilter-1",
  "type": "CsrfFilter",
  "config": {
    "cookieName": "openig-jwt-session",
    "headerName": "X-CSRF-Token",
    "excludeSafeMethods": true
  }
}
```

More information

[org.forgerock.openig.filter.CsrfFilterHeaplet](https://github.com/forgerock/openig/blob/master/docs/forgerock.org/openig/filter/CsrfFilterHeaplet) 

DataPreservationFilter

The [DataPreservationFilter](#) triggers POST data preservation when an unauthenticated client posts HTML form data to a protected resource.

When an authentication redirect is triggered, the filter stores the data in the HTTP session, and redirects the client for authentication. After authentication, the filter generates an empty self-submitting form POST to emulate the original POST. It then replays the stored data into the request before passing it along the chain.

The data can be any POST content, such as HTML form data or a file upload.

Learn more in [POST data preservation](#).

Usage

```
{
  "type": "DataPreservationFilter",
  "config": {
    "noJavaScriptMessage": configuration expression<string>,
    "maxContentLength": configuration expression<positive integer>,
    "lifetime": configuration expression<duration>
  }
}
```

Properties

"noJavaScriptMessage": *configuration expression<string>, optional*

JavaScript is used to replay the preserved data from the original POST that triggered the login redirect. This property configures a message to display if the user-agent doesn't support JavaScript.

Default: Javascript is disabled in your browser, click on this button to replay the preserved original request

"maxContentLength": *configuration expression<positive integer>, optional*

The maximum number of bytes of POST data the filter can preserve. The size is taken from the [Content-Length](#) header.

Default: 4096

"lifetime": *configuration expression<duration>, optional*

The maximum time that the filter can store POST data in an HTTP session.

The filter deletes stored POST data when the following events occur:

- The `lifetime` has expired.
- The POST data preservation process from an earlier request hasn't completed.
- A new request arrives that triggers a new POST data preservation process.

Stored POST data is also deleted when the session expires.

Default: 5 minutes

Example

You can find an example of use in [POST data preservation](#).

More information

[org.forgerock.openig.filter.DataPreservationFilter](#)

[AuthRedirectContext](#)

DateHeaderFilter

Inserts the server date in an HTTP `Date` header on the response, if the `Date` header isn't present.

Usage

```
{
  "type": "DateHeaderFilter"
}
```

Properties

There are no configuration properties for this filter.

Example

The following example includes a `DateHeaderFilter` in a chain:

```
{
  "condition": "...",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [{
        ...
      }],
      {
        "type": "DateHeaderFilter"
      }
    ],
    "handler": {
      "name": "StaticResponseHandler-1",
      ...
    }
  }
}
```

More information

You can find more information about Date format in [RFC 7231 - Date](#).

This filter is also available to support Financial-Grade API. Learn more in [Financial-grade API Security Profile 1.0 - Part 1: Baseline](#).

org.forgerock.openig.filter.DateHeaderFilter

EncryptedPrivateKeyJwtClientAuthenticationFilter

Supports client authentication with the `private_key_jwt` client-assertion, using a signed and encrypted JWT.

Clients send a signed and encrypted JWT to the Authorization Server. PingGateway builds, signs and encrypts the JWT, and prepares the request as in the following example:

```
POST /token HTTP/1.1
Host: as.example.com
Content-Type: application/x-www-form-urlencoded

grant_type=authorization_code&
code=...&
client_id=<clientregistration_id>&
client_assertion_type=urn%3Aietf%3Aparams%3Aoauth%3Aclient-assertion-type%3Ajwt-bearer&
client_assertion=PHNhbWxwO1 ... ZT
```

Use this filter with an endpoint `Handler` that requires authentication with the `private_key_jwt` client-assertion, using an encrypted JWT. For example, the `endpointHandler` handler in the [OAuth2TokenExchangeFilter](#).

Usage

```
{
  "name": string,
  "type": "EncryptedPrivateKeyJwtClientAuthenticationFilter",
  "config": {
    "encryptionAlgorithm": configuration expression<enumeration>,
    "encryptionMethod": configuration expression<string>,
    "encryptionSecretId": configuration expression<secret-id>,
    "clientId": configuration expression<string>,
    "tokenEndpoint": configuration expression<url>,
    "secretsProvider": SecretsProvider reference,
    "signingSecretId": configuration expression<string>,
    "signingAlgorithm": configuration expression<string>,
    "jwtExpirationTimeout": configuration expression<duration>,
    "claims": map or configuration expression<map>
  }
}
```

Configuration

"encryptionAlgorithm": configuration expression<string>, required

The algorithm name used for encryption and decryption. Use algorithm names from [Java Security Standard Algorithm Names](#).

"encryptionMethod": configuration expression<string>, optional

The algorithm method to use for encryption. Use algorithms from [RFC 7518, section-5.1](#).

"encryptionSecretId": configuration expression<secret-id>, required

The secret-id of the keys used to encrypt the JWT.

This secret ID must point to a [CryptoKey](#).

"clientId": configuration expression<string>, required

The `client_id` obtained when registering with the Authorization Server.

"tokenEndpoint": configuration expression<url>, required

The URL to the Authorization Server's OAuth 2.0 token endpoint.

"secretsProvider": SecretsProvider reference, required

The [SecretsProvider](#) to query for passwords and cryptographic keys.

"signingSecretId": configuration expression<string>, required

Reference to the keys used to sign the JWT.

This secret ID must point to a [CryptoKey](#).

"signingAlgorithm": configuration expression<string>, optional

The JSON Web Algorithm (JWA) used to sign the JWT, such as:

- `RS256` : RSA using SHA-256
- `ES256` : ECDSA with SHA-256 and NIST standard P-256 elliptic curve
- `ES384` : ECDSA with SHA-384 and NIST standard P-384 elliptic curve
- `ES512` : ECDSA with SHA-512 and NIST standard P-521 elliptic curve

Default: `RS256`

"jwtExpirationTimeout": configuration expression<duration>, optional

The duration for which the JWT is valid.

Default: 1 minute

"claims": map or configuration expression<map>, optional

A map of one or more data pairs with the format `Map<String, Object>`, where:

- The key is the name of a claim used in authentication
- The value is the value of the claim, or a configuration expression that evaluates to the value

The following formats are allowed:

```
{
  "args": {
    "string": "configuration expression<string>",
    ...
  }
}
```

```
{
  "args": "configuration expression<map>"
}
```

Default: Empty

EntityExtractFilter

Extracts regular expression patterns from a message entity, and stores their values in a **target** object. Use this object in password replay, to find a login path or extract a nonce.

If the message **type** is **REQUEST**, the pattern is extracted before the request is handled. If the message **type** is **RESPONSE**, the pattern is extracted out of the response body.

Each pattern can have an associated template, which is applied to its match result.

For information, see [Patterns and PingGateway](#).

Usage

```
{
  "name": string,
  "type": "EntityExtractFilter",
  "config": {
    "messageType": configuration expression<enumeration>,
    "charset": configuration expression<string>,
    "target": lvalue-expression,
    "bindings": [
      {
        "key": configuration expression<string>,
        "pattern": pattern,
        "template": pattern
      }, ...
    ]
  }
}
```

Properties

"messageType": *configuration expression<enumeration>, required*

The message type to extract patterns from.

Must be **REQUEST** or **RESPONSE**.

"charset": *configuration expression<string>, optional*

Overrides the character set encoding specified in message.

Default: The message encoding is used.

"target": *<value-expression>*, required

Expression that yields the target object that contains the extraction results.

The bindings determine what type of object is stored in the target location.

The object stored in the target location is a `Map<String, String>`. You can then access its content with `${target.key}` or `${target['key']}`.

Learn more in [PingGateway expressions](#).

"key": *configuration expression<string>*, required

Name of the element in the target object to contain an extraction result.

"pattern": *pattern*, required

The regular expression pattern to find in the entity.

See also [Patterns and PingGateway](#).

"template": *pattern-template*, optional

The template to apply to the pattern, and store in the named target element.

Default: store the match result itself.

See also [Patterns and PingGateway](#).

Examples

Extracts a nonce from the response, which is typically a login page, and sets its value in the attributes context to be used by the downstream filter posting the login form. The nonce value would be accessed using the following expression: `${attributes.extract.wpLoginToken}`.

The pattern finds all matches in the HTTP body of the form `wpLogintokenvalue="abc"`. Setting the template to `$1` assigns the value `abc` to `attributes.extract.wpLoginToken`:

```
{
  "name": "WikiNoncePageExtract",
  "type": "EntityExtractFilter",
  "config": {
    "messageType": "response",
    "target": "${attributes.extract}",
    "bindings": [
      {
        "key": "wpLoginToken",
        "pattern": "wpLoginToken\\s.*value=\"(.*)\"",
        "template": "$1"
      }
    ]
  }
}
```

The following example reads the response looking for the AM login page. When found, it sets `isLoginPage = true` to be used in a SwitchFilter to post the login credentials:

```
{
  "name": "FindLoginPage",
  "type": "EntityExtractFilter",
  "config": {
    "messageType": "response",
    "target": "${attributes.extract}",
    "bindings": [
      {
        "key": "isLoginPage",
        "pattern": "OpenAM\\s\\(Login\\)",
        "template": "true"
      }
    ]
  }
}
```

FapiInteractionIdFilter

Tracks the interaction ID of requests, according to the [Financial-grade API \(FAPI\) WG](#), as follows:

- If a FAPI header is provided in a client request, this filter includes the interaction ID in the `x-fapi-interaction-id` property of the response header.
- If a FAPI header isn't provided in the request, this filter includes a new Universally Unique Identifier (UUID) in the `x-fapi-interaction-id` property of the response header.
- This filter logs the value of `x-fapi-interaction-id`.

Usage

```
{
  "name": string,
  "type": "FapiInteractionIdFilter"
}
```

Properties

There are no configuration properties for this filter.

Example

The following example is based on [Mutual TLS with PingAM](#) and adds a FapiInteractionIdFilter to the end of the chain:


```
{
  "name": "mtls",
  "condition": "${find(request.uri.path, '/mtls')}",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [ {
        "name": "OAuth2ResourceServerFilter-1",
        ...
      },
      {
        "type": "FapiInteractionIdFilter"
      }
    ],
    "handler": {
      "name": "StaticResponseHandler-1",
      ...
    }
  }
}
```

More information

[org.forgerock.openig.filter.finance.FapiInteractionIdFilter](#)

[Financial-grade API - Part 1: Read-Only API Security Profile](#)

FileAttributesFilter

Retrieves and exposes a record from a delimiter-separated file. PingGateway looks up the record with the keys specified in the `fields` setting.

PingGateway populates the `FileAttributesContext` and the optional `target` (deprecated) with key-value pairs from the record. If no matching record is found, the context and optional `target` are empty.

When the deprecated `target` setting is configured, PingGateway lazy loads the record on the first attempt to access one of its values. This defers the overhead of file operations and text processing until a value is first required. PingGateway doesn't evaluate the `value` expression until the data is first accessed. PingGateway reads the file synchronously, potentially impacting performance.

When `target` isn't set, PingGateway reads the file asynchronously when calling this filter. In this case, place this filter immediately before the entity reading the data from the context.

Usage

```
{
  "name": string,
  "type": "FileAttributesFilter",
  "config": {
    "file": configuration expression<string>,
    "charset": configuration expression<string>,
    "separator": configuration expression<enumeration>,
    "header": configuration expression<boolean>,
    "fields": [ configuration expression<string>, ... ],
    "target": lvalue-expression, // deprecated
    "key": configuration expression<string>,
    "value": runtime expression<string>,
    "executorService": ScheduledExectutorService reference
  }
}
```

You can find an example in [Password replay from a file](#).

Properties

"file": configuration expression<string>, required

The file containing the record to be read.

"charset": configuration expression<string>, optional

The character set in which the file is encoded.

Default: "UTF-8" .

"separator": configuration expression<enumeration>, optional

The separator character, which is one of the following:

COLON

Unix-style colon-separated values, with backslash as the escape character.

COMMA

Comma-separated values, with support for quoted literal strings.

TAB

Tab-separated values, with support for quoted literal strings.

Default: COMMA

"header": configuration expression<boolean>, optional

A flag to treat the first row of the file as a header row.

When the first row of the file is treated as a header row, the data in that row is disregarded and cannot be returned by a lookup operation.

Default: `true`.

"fields": *array of configuration expression*<strings>, optional

A list of keys in the order they appear in a record.

If `fields` isn't set, the keys are assigned automatically by the column numbers of the file.

"target": *<value-expression>*, optional



Important

This property is deprecated. Use the [FileAttributesContext](#) instead. Learn more in the [Deprecated](#) section of the *Release Notes*.

Expression that yields the target object to contain the record.

The target object is a `Map<String, String>`, where the fields are the keys. For example, if the target is `${attributes.file}` and the record has `username` and `password` fields mentioned in the "fields" list, access the username as `${attributes.file.username}` and the password as `${attributes.file.password}`.

Learn more in [PingGateway expressions](#).

"key": *configuration expression*<string>, required

The key used for the lookup operation.

"value": *runtime expression*<string>, required

The value to find in the file.

Learn more in [PingGateway expressions](#).

"executorService": *ScheduledExecutorService* [reference](#), optional

A [ScheduledExecutorService](#) to read the file.

Default: The default `ScheduledExecutorService` in the heap

More information

[org.forgerock.openig.filter.FileAttributesFilter](#)

ForwardedRequestFilter

Rebase the request URI to a computed scheme, host name, and port.

Use this filter to configure redirects when a request is forwarded by an upstream application such as a TLS offloader.

Usage

```
{
  "name": string,
  "type": "ForwardedRequestFilter",
  "config": {
    "scheme": runtime expression<string>,
    "host": runtime expression<string>,
    "port": runtime expression<number>
  }
}
```

Properties

At least one of `scheme`, `host`, or `port` must be configured.

"scheme": runtime expression<string>, optional

The scheme to which the request is rebased, for example, `https`.

Default: Not rebased to a different scheme

"host": runtime expression<string>, optional

The host to which the request is rebased.

Default: Not rebased to a different host

"port": runtime expression<number>, optional

The port to which the request is rebased.

Default: Not rebased to a different port

Example

In the following configuration, PingGateway runs behind an AWS load balancer, to perform a login page redirect to an authentication party, using the original URI requested by the client.

PingGateway can access the URI used by the load balancer to reach PingGateway, but can't access the original request URI.

The load balancer breaks the original request URI into the following headers, and adds them to the incoming request:

- `X-Forwarded-Proto` : Scheme
- `X-Forwarded-Port` : Port
- `Host` : Original host name, and possibly the port.

```
{
  "type": "ForwardedRequestFilter",
  "config": {
    "scheme": "${request.headers['X-Forwarded-Proto']}",
    "host": "${split(request.headers['Host'], ':')[0]}",
    "port": "${integer(request.headers['X-Forwarded-Port'])}"
  }
}
```

More information

[org.forgerock.openig.filter.ForwardedRequestFilter](https://github.com/pingidentity/pinggateway/blob/master/src/main/java/org/forgerock/openig/filter/ForwardedRequestFilter.java)

FragmentFilter

Tracks the fragment part of a URI when a request triggers a login redirect, as follows:

- Before authentication, the filter captures the URI fragment information and stores it in a cookie.
- After authentication, when the request is issued again to the original URI, the filter redirects the browser to the original URI, including any URI fragment.

The full fragment capture process is described in [URI fragments in redirect](#).

The FragmentFilter doesn't handle multiple fragment captures in parallel. If a fragment capture is in progress while PingGateway performs another login redirect, a second fragment capture process isn't triggered and the fragment is lost.

When a browser request loads a favicon, it can cause the fragment part of a URI to be lost. Prevent problems by serving static resources with a separate route. As an example, use the route in [Serve static resources](#).

Use this filter with SingleSignOnFilter, CrossDomainSingleSignOnFilter, AuthorizationCodeOAuth2ClientFilter, and PolicyEnforcementFilter. This filter is not required for SAML because the final redirect is done with a Dispatcher and a StaticResponseFilter.

Usage

```
{
  "name": string,
  "type": "FragmentFilter",
  "config": {
    "fragmentCaptureEndpoint": configuration expression<string>,
    "noJavaScriptMessage": configuration expression<string>,
    "cookie": object
  }
}
```

"fragmentCaptureEndpoint": configuration expression<string>, required

The PingGateway endpoint used to capture the fragment form data.

Configure the endpoint to match the condition of the route in which the filter is used.

"noJavaScriptMessage": configuration expression<string>, optional

A message to display on the fragment form when JavaScript isn't enabled.

Default: No message

"cookie": object, optional

The configuration of the cookie used to store the fragment information.

```
{
  "name": configuration expression<string>,
  "domain": configuration expression<string>,
  "httpOnly": configuration expression<boolean>,
  "path": configuration expression<string>,
  "sameSite": configuration expression<enumeration>,
  "secure": configuration expression<boolean>,
  "maxAge": configuration expression<duration>
}
```

"name": configuration expression<string>, optional

Cookie name.

Default: `ig-fragment-cookie`

"domain": configuration expression<string>, optional

Domain to which the cookie applies.

Default: The fully qualified hostname of the PingGateway host.

"httpOnly": configuration expression<boolean>, optional

Flag to mitigate the risk of client-side scripts accessing protected cookies.

Default: `true`

"path": configuration expression<string>, optional

Path to apply to the cookie.

Default: `/`

"sameSite": configuration expression<enumeration>, optional

Options to manage the circumstances in which a cookie is sent to the server. Use one of the following values to reduce the risk of CSRF attacks:

- **STRICT** : Send the cookie only if the request was initiated from the cookie domain. Not case-sensitive.
Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.
- **LAX** : Send the cookie only with GET requests in a first-party context, where the URL in the address bar matches the cookie domain. Not case-sensitive.

Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.

- **NONE** : Send the cookie whenever a request is made to the cookie domain. Not case-sensitive.

With this setting, set **"secure": true** to prevent browsers from rejecting the cookie. Learn more in [SameSite cookies](#).

Default: **LAX**

"secure": configuration expression<boolean>, optional

Flag to limit the scope of the cookie to secure channels.

Default: **false**

"maxAge": configuration expression<duration>, optional

The maximum duration for which the FragmentFilter cookie can be valid.

When this **maxAge** is greater than the browser's maximum internal value, the browser value takes precedence.

Default: 1 hour

Example

You can find an example of how the FragmentFilter is used in an SSO flow in [URI fragments in redirect](#).

More information

[org.forgerock.openig.filter.FragmentFilter](#)

[URI Fragment](#)

[RFC 3986: Fragment](#)

[AuthRedirectContext](#)

GrantSwapJwtAssertionOAuth2ClientFilter

Transforms requests for OAuth 2.0 access tokens into secure [JWT bearer grant type](#) requests. Propagates transformed requests to PingOne Advanced Identity Cloud or AM to obtain an access token.

Use this filter with PingOne Advanced Identity Cloud or AM to increase the security of less-secure grant-type requests, such as [Client credentials grant](#) requests or [Resource owner password credentials grant](#) requests.

⚠ Caution

The GrantSwapJwtAssertionOAuth2ClientFilter obtains access tokens from the `/oauth2/access_token` endpoint. To prevent unwanted or malicious access to the endpoint, make sure only a well-defined set of clients can use this filter. Consider the following options to secure access to the GrantSwapJwtAssertionOAuth2ClientFilter:

- Deploy PingGateway on a trusted network.
- Use mutual TLS (mTLS) and X.509 certificates for authentication between clients and PingGateway. For more information, refer to [OAuth 2.0 Mutual TLS Client Authentication and Certificate Bound Access Tokens](#).
- Configure an [AllowOnlyFilter](#) in front of the GrantSwapJwtAssertionOAuth2ClientFilter to control access within a route.
- Define restrictive [Route](#) conditions to allow access only for expected grant-type requests. For example, define a route condition that requires a specific client ID, grant-type, or scope.
- Configure a [ScriptableFilter](#) in front of the GrantSwapJwtAssertionOAuth2ClientFilter to validate requests.

Usage

```
{
  "name": string,
  "type": "GrantSwapJwtAssertionOAuth2ClientFilter",
  "config": {
    "clientId": configuration expression<string>,
    "scopes": [ runtime expression<string>, ... ] or ResourceAccess reference,
    "assertion": {
      "issuer": runtime expression<string>,
      "subject": runtime expression<string>,
      "audience": runtime expression<string>,
      "expiryTime": runtime expression<duration>,
      "otherClaims": map<string, runtime expression<string>>
    },
    "secretsProvider": SecretsProvider reference,
    "signature": {
      "secretId": configuration expression<secret-id>,
      "includeKeyId": configuration expression<boolean>
    },
    "encryption": {
      "secretId": secret-id,
      "algorithm": configuration expression<string>,
      "method": configuration expression<enumeration>
    },
    "failureHandler": Handler reference
  }
}
```

Properties

clientId

`"clientId"`: configuration expression<[string](#)>, optional

The OAuth 2.0 client ID to use for authentication.

scopes

"scopes" : array of runtime expression<[strings](#)> or ResourceAccess <[reference](#)>, required

A list of one or more scopes required by the OAuth 2.0 access token. Provide the scopes as strings or through a ResourceAccess configuration, such as a RequestFormResourceAccess or ScriptableResourceAccess:

Array of runtime expression<[strings](#)>, required if a [ResourceAccess](#) isn't used

A string, array of strings, runtime expression string, or array of runtime expression strings to represent one or more scopes.

RequestFormResourceAccess <[reference](#)>

A ResourceAccess that transfers scopes from the inbound request to a JWT bearer grant-type request.

In the following example request, the ResourceAccess extracts scopes from the request:

```
$ curl --request POST 'https://am.example.com:8888/am/oauth2/access_token'
header 'Content-Type: application/x-www-form-urlencoded'
urlencoded form-data 'grant_type=client_credentials'
urlencoded form-data 'client_id=service-account'
urlencoded form-data 'scope=fr:idm:*'
```

Default: Empty

ScriptableResourceAccess <[reference](#)>

A script that evaluates each request dynamically and returns the scopes that the request needs to access the protected resource. The script must return a `Set<String>`.

Learn about the properties of ScriptableResourceAccess in [PingGateway scripts](#).

```
{
  "name": string,
  "type": "ScriptableResourceAccess",
  "config": {
    "type": configuration expression<string>,
    "file": configuration expression<string>, // Use either "file"
    "source": [ string, ... ],                // or "source", but not both.
    "args": object,
    "clientHandler": Handler reference
  }
}
```

Default: Empty

assertion

"assertion" : [object](#), required

The JWT claims. The `GrantSwapJwtAssertionOAuth2ClientFilter` checks that all mandatory fields are present and sets the JWT expiry. The filter doesn't check the fields in `otherClaims`.

"issuer": *string, required*

The JWT `iss` claim. Can't be null.

"subject": *string, required*

The JWT `sub` claim. Can't be null.

"audience": *string, required*

The JWT `aud` claim. Can't be null.

"expiryTime": *duration, required*

The JWT `exp` claim. Can't be `zero` or `unlimited`.

Default: 2 minutes

"otherClaims": *map or map, optional*

A map of additional JWT claims with the format `Map<String, RuntimeExpression<String>>`, where:

- Key: Claim name
- Value: Claim value

Use the following format:

```
{
  "otherClaims": {
    "string": "runtime expression<string>",
    ...
  }
}
```

The filter doesn't check `otherClaims` in the JWT.

secretsProvider

"secretsProvider": *SecretsProvider reference, required*

The [SecretsProvider](#) to query for passwords and cryptographic keys.

signature

"signature": *_object*, "signature" and/or "encryption" is required

A JWT signature to validate the authenticity of claims and data.

"secretId": configuration expression<[secret-id](#)>, required if signature is used

The secret ID of the key to sign the JWT. The secret ID must point to a [CryptoKey](#).

"includeKeyId": configuration expression<[boolean](#)>, optional

A flag to include the ID of the signature key in the JWT header:

- `true` : Include the flag
- `false` : Don't include the flag

Default: `true`

encryption

"encryption" : [object](#), "signature" and/or "encryption" is required

Configuration to encrypt the JWT.

This property takes precedence over the [signature](#) setting.

"secretId": [secret-id](#), optional

The secret ID of the key used to encrypt the JWT. The value is mapped to key `aliases` in [KeyStoreSecretStore](#).

This secret ID must point to a [CryptoKey](#).

"algorithm": configuration expression<[string](#)>, required

The algorithm used to encrypt the JWT.

Learn about available algorithms in [RFC 7518: "alg" \(Algorithm\) Header Parameter Values for JWE](#) [↗](#).

"method": configuration expression<[enumeration](#)>, required

The method used to encrypt the JWT.

Learn about available methods in [RFC 7518: "enc" \(Encryption Algorithm\) Header Parameter Values for JWE](#) [↗](#).

failureHandler

"failureHandler" : *Handler* <[reference](#)>, optional

[Handler](#) to manage a failed request.

Provide an inline handler configuration object or the name of a handler object declared in the heap.

Default: PingGateway returns HTTP 500 Internal Server Error and stops processing the request.

Example

You can find an example that uses this filter in [Securing the OAuth 2.0 access token endpoint with PingOne Advanced Identity Cloud](#).

More information

[org.forgerock.openig.filter.oauth2.client.GrantSwapJwtAssertionOAuth2ClientFilter](#)

HeaderFilter

Removes, adds, or replaces headers in request or response messages.

Usage

```
{
  "name": string,
  "type": "HeaderFilter",
  "config": {
    "messageType": configuration expression<enumeration>,
    "remove": [ configuration expression<string>, ... ],
    "add": {
      string: [ runtime expression<string>, ... ], ...
    }
    "replace": {
      string: [ runtime expression<string>, ... ], ...
    }
  }
}
```

Properties

"messageType": configuration expression<[enumeration](#)>, required

The type of message for which to filter headers. Must be either "REQUEST" or "RESPONSE".

"remove": array of configuration expression<[strings](#)>, optional

The names of header fields to remove.

"add": [object](#), optional

One or more headers to add with the format `name: [ value, ... ]`:

- *name* is a string for a header name.
- *value* is a runtime expression that resolves to one or more header values.

"replace": [object](#), optional

One or more headers to replace with the format `name: [ value, ... ]`

- *name* is a string for a header name.
- *value* is a runtime expression that resolves to one or more header values.

PingGateway removes current values for the *name* headers and adds the specified values.

Examples

Replace host header on an incoming request

The following example replaces the host header on the incoming request with the value `myhost.com`:

```
{
  "name": "ReplaceHostFilter",
  "type": "HeaderFilter",
  "config": {
    "messageType": "REQUEST",
    "replace": {
      "host": [ "myhost.com" ]
    }
  }
}
```

Add a header to a response

The following example adds a `Set-Cookie` header to the response:

```
{
  "name": "SetCookieFilter",
  "type": "HeaderFilter",
  "config": {
    "messageType": "RESPONSE",
    "add": {
      "Set-Cookie": [ "mysession=12345" ]
    }
  }
}
```

Add headers to a request

The following example adds the headers `custom1` and `custom2` to the request:

```
{
  "name": "SetCustomHeaders",
  "type": "HeaderFilter",
  "config": {
    "messageType": "REQUEST",
    "add": {
      "custom1": [ "12345", "6789" ],
      "custom2": [ "abcd" ]
    }
  }
}
```

Add a token value to a response

The following example adds the value of session's policy enforcement token to the `pef_sso_token` header in the response:

```
{
  "type": "HeaderFilter",
  "config": {
    "messageType": "RESPONSE",
    "add": {
      "pef_sso_token": ["${session.pef_token}"]
    }
  }
}
```

Add headers and logging results

The following example adds a message to the request and response as it passes through the Chain and the `capture` on the ReverseProxyHandler logs the result.

```

{
  "condition": "${find(request.uri.path, '^/home/chain')}",
  "handler": {
    "type": "Chain",
    "comment": "Base configuration defines the capture decorator",
    "config": {
      "filters": [
        {
          "type": "HeaderFilter",
          "comment": "Add a header to all requests",
          "config": {
            "messageType": "REQUEST",
            "add": {
              "MyHeaderFilter_request": [
                "Added by HeaderFilter to request"
              ]
            }
          }
        },
        {
          "type": "HeaderFilter",
          "comment": "Add a header to all responses",
          "config": {
            "messageType": "RESPONSE",
            "add": {
              "MyHeaderFilter_response": [
                "Added by HeaderFilter to response"
              ]
            }
          }
        }
      ]
    },
    "handler": {
      "type": "ReverseProxyHandler",
      "config": {
        "tls": {
          "type": "ClientTlsOptions",
          "comment": "Blindly trust the sample app certificate",
          "config": {
            "trustManager": {
              "type": "TrustAllManager"
            },
            "hostnameVerifier": "ALLOW_ALL"
          }
        },
        "comment": "Log request, pass it to the sample app, log response",
        "capture": "all",
        "baseURI": "https://app.example.com:8444"
      }
    }
  }
}

```

Source: [chain.json](#)

The chain receives the request and context and processes it as follows:

- The first **HeaderFilter** adds a header to the incoming request.

- The second `HeaderFilter` manages responses not requests, so it simply passes the request and context to the handler.
- The `ReverseProxyHandler` captures (logs) the request.
- The `ReverseProxyHandler` forwards the transformed request to the protected application.
- The protected application passes a response to the `ReverseProxyHandler`.
- The `ReverseProxyHandler` captures (logs) the response.
- The second `HeaderFilter` adds a header added to the response.
- The first `HeaderFilter` is configured to manage requests, not responses, so it simply passes the response back to PingGateway.

The following example lists some of the HTTP requests and responses captured as they flow through the chain. You can search the log files for `MyHeaderFilter_request` and `MyHeaderFilter_response`.

```
# Original request from user-agent
GET https://ig.example.com:8443/home/chain HTTP/1.1
Accept: /
Host: ig.example.com:8443

# Add a header to the request (inside PingGateway) and direct it to the protected application
GET https://app.example.com:8444/home/chain HTTP/1.1
Accept: /
Host: ig.example.com:8443
MyHeaderFilter_request: Added by HeaderFilter to request

# Return the response to the user-agent
HTTP/1.1 200 OK
Content-Length: 1809
Content-Type: text/html; charset=ISO-8859-1

# Add a header to the response (inside PingGateway)
HTTP/1.1 200 OK
Content-Length: 1809
MyHeaderFilter_response: Added by HeaderFilter to response
```

HttpBasicAuthFilter

Authenticate clients by providing the client credentials as a basic authorization header in the request. The credentials are base64-encoded.

This filter performs HTTP basic access authentication, described in [RFC 2617](#).

Use this filter primarily for password replay scenarios, where the password is stored externally in clear text.

If challenged for authentication via a `401 Unauthorized` status code by the server, this filter retries the request with credentials attached. After an HTTP authentication challenge is issued from the remote server, all subsequent requests to that remote server that pass through the filter include the user credentials.

If authentication fails (including the case where no credentials are yielded from expressions), then processing is diverted to the specified authentication failure handler.

Usage

```
{
  "name": string,
  "type": "HttpBasicAuthFilter",
  "config": {
    "username": runtime expression<string>,
    "password": runtime expression<string>,
    "failureHandler": Handler reference,
    "cacheHeader": configuration expression<boolean>
  }
}
```

Properties

"username": runtime expression<string>, required

The username to supply during authentication.

Learn more in [PingGateway expressions](#).

"password": runtime expression<string>, required

The password to supply during authentication.

Learn more in [PingGateway expressions](#).

"failureHandler": Handler reference, required

Dispatch to this Handler if authentication fails.

Provide either the name of a Handler object defined in the heap or an inline Handler configuration object.

See also [PingGateway handlers](#).

"cacheHeader": configuration expression<boolean>, optional

Whether or not to cache credentials in the session after the first successful authentication, and then replay those credentials for subsequent authentications in the same session.

With `"cacheHeader": false`, the filter generates the header for each request. This is useful, for example, when users change their passwords during a browser session.

Default: `true`

Example

```
{
  "name": "MyAuthenticator",
  "type": "HttpBasicAuthFilter",
  "config": {
    "username": "demo",
    "password": "password",
    "failureHandler": "AuthFailureHandler",
    "cacheHeader": false
  }
}
```

More information

[org.forgerock.openig.filter.HttpBasicAuthFilter](#) 

HttpBasicAuthenticationClientFilter

Authenticates clients according to the HTTP basic access authentication scheme.

HTTP basic access authentication is a simple challenge and response mechanism, where a server requests credentials from a client, and the client passes them to the server in an **Authorization** header. The credentials are base-64 encoded. To protect them, use SSL encryption for the connections between the server and client. For more information, refer to [RFC 2617](#) .

Tip

Compare the purpose of this filter with that of the following filters:

- [ClientCredentialsOAuth2ClientFilter](#), which authenticates clients by their OAuth 2.0 credentials to obtain an access token from an Authorization Server.
- [ClientSecretBasicAuthenticationFilter](#), which fulfils the same role of transforming OAuth 2.0 credentials to an **Authorization** header, but is more strict for OAuth 2.0 requirements.

Use `HttpBasicAuthenticationClientFilter` in a service-to-service context, where services need to access resources protected by HTTP basic access authentication.

Usage

```
{
  "name": string,
  "type": "HttpBasicAuthenticationClientFilter",
  "config": {
    "username": configuration expression<string>,
    "passwordSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference,
    "urlEncodeCredentials": configuration expression<boolean>
  }
}
```

Properties

"username": configuration expression<string>, required

The username of the client to authenticate.

"passwordSecretId": configuration expression<string>, required

The secret ID required to obtain the client password.

This secret ID must point to a [GenericSecret](#).

"secretsProvider": SecretsProvider reference, required

The [SecretsProvider](#) to query for the `passwordSecretId`.


"urlEncodeCredentials": configuration expression<boolean>, optional

Set to `true` to URL-encoded credentials before base64-encoding them.

Default: `false`

Example

The following example shows the flow of information when a client service accesses a resource protected by HTTP basic access authentication:



Set Up the Example

1. Add the following script to the PingGateway configuration:

Linux

```
$HOME/.openig/scripts/groovy/BasicAuthResourceServerFilter.groovy
```

Windows

```
%appdata%\OpenIG\scripts\groovy\BasicAuthResourceServerFilter.groovy
```

```
/*
 * This script is a simple implementation of HTTP basic access authentication on
 * server side.
 * It expects the following arguments:
 * - realm: the realm to display when the user agent prompts for
 *   username and password if none were provided.
 * - username: the expected username
 * - passwordSecretId: the secretId to find the password
 * - secretsProvider: the SecretsProvider to query for the password
 */
import static org.forgerock.util.promise.Promises.newResultPromise;

import java.nio.charset.Charset;
import org.forgerock.util.encode.Base64;
import org.forgerock.secrets.Purpose;
import org.forgerock.secrets.GenericSecret;

String authorizationHeader = request.getHeaders().getFirst("Authorization");
if (authorizationHeader == null) {
    // No credentials provided, return 401 Unauthorized
    Response response = new Response(Status.UNAUTHORIZED);
    response.getHeaders().put("WWW-Authenticate", "Basic realm=\"" + realm + "\"");
    return newResultPromise(response);
}

return secretsProvider.getNamed(Purpose.PASSWORD, passwordSecretId)
    .thenAsync(password -> {
        // Build basic authentication string -> username:password
        StringBuilder basicAuthString = new StringBuilder(username).append(":");
        password.revealAsUtf8{ p -> basicAuthString.append(new String(p).trim()) };
        String expectedAuthorization = "Basic " +
Base64.encode(basicAuthString.toString().getBytes(Charset.defaultCharset()));
        // Incorrect credentials provided, return 403 forbidden
        if (!expectedAuthorization.equals(authorizationHeader)) {
            return newResultPromise(new Response(Status.FORBIDDEN));
        }
        // Correct credentials provided, continue.
        return next.handle(context, request);
    },
    noSuchSecretException -> { throw new RuntimeException(noSuchSecretException); });
```

Source: [BasicAuthResourceServerFilter.groovy](#)

The script is a simple implementation of the HTTP basic access authentication scheme. Learn more about scripting filters and handlers in [Extending PingGateway](#).

2. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/http-basic-access.json
```

Windows

%appdata%\OpenIG\config\routes\http-basic-access.json

```
{
  "name": "http-basic-access",
  "baseURI": "http://ig.example.com:8080",
  "condition": "${find(request.uri.path, '^/http-basic-access')}",
  "heap": [
    {
      "name": "httpBasicAuthEnabledClientHandler",
      "type": "Chain",
      "capture": "all",
      "config": {
        "filters": [
          {
            "type": "HttpBasicAuthenticationClientFilter",
            "config": {
              "username": "myclient",
              "passwordSecretId": "password.secret.id",
              "secretsProvider": {
                "type": "Base64EncodedSecretStore",
                "config": {
                  "secrets": {
                    "password.secret.id": "cGFzc3dvcmQ="
                  }
                }
              }
            }
          }
        ]
      },
      "handler": "ForgeRockClientHandler"
    }
  ],
  "handler": {
    "type": "ScriptableHandler",
    "config": {
      "type": "application/x-groovy",
      "clientHandler": "httpBasicAuthEnabledClientHandler",
      "source": [
        "request.uri.path = '/http-basic-protected-resource'",
        "return http.send(context, request);"
      ]
    }
  }
}
```

Source: [http-basic-access.json](#)

Note the following features of the route:

- The route matches requests to `/http-basic-access`.
- The `ScriptableHandler` rewrites the request to target it to `/http-basic-protected-resource` and calls the HTTP client that uses the `httpBasicAuthEnabledClientHandler`.

- The `httpBasicAuthEnabledClientHandler` calls the `HttpBasicAuthenticationClientFilter` to authenticate the client using the client's credentials.

3. Add the following route to PingGateway:

Linux

```
$HOME/.openig/config/routes/http-basic-protected-resource.json
```

Windows

```
%appdata%\OpenIG\config\routes\http-basic-protected-resource.json
```

```

{
  "heap": [
    {
      "name": "mySecretsProvider",
      "type": "Base64EncodedSecretStore",
      "config": {
        "secrets": {
          "password.secret.id": "cGFzc3dvcmQ="
        }
      }
    }
  ],
  "name": "http-basic-protected-resource",
  "condition": "${find(request.uri.path, '^/http-basic-protected-resource')}",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "HttpBasicAuthResourceServerFilter",
          "type": "ScriptableFilter",
          "config": {
            "type": "application/x-groovy",
            "file": "BasicAuthResourceServerFilter.groovy",
            "args": {
              "realm": "IG Protected Area",
              "username": "myclient",
              "passwordSecretId": "password.secret.id",
              "secretsProvider": "${heap['mySecretsProvider']}"
            }
          }
        }
      ]
    },
    "handler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 200,
        "headers": {
          "Content-Type": [ "text/html; charset=UTF-8" ]
        },
        "entity": "<html><body><h2>Access Granted</h2></body></html>"
      }
    }
  }
}

```

Source: [http-basic-protected-resource.json](#)

Notice the following features of the route:

- The route matches requests to `/http-basic-protected-resource`.
- The ScriptableFilter provides a script to implement a simple HTTP basic access authentication scheme that compares the provided credentials with the expected credentials.
- When the client is authenticated, the StaticResponseHandler returns a message that access is granted.

4. Access the route on <http://ig.example.com:8080/http-basic-access>.

Because the expected credentials were provided in the request, a message shows that access is granted.

More information

org.forgerock.openig.filter.HttpBasicAuthenticationClientFilterHeaplet

IdTokenValidationFilter

Validates an ID token by checking the standard claims, `aud`, `exp`, and `iat`. If specified in the configuration, this filter also checks the ID token issuer and signature.

This filter passes data into the context as follows:

- If the JWT is validated, the request continues down the chain. The data is provided in the [JwtValidationContext](#).
- If the JWT isn't validated, data is provided in the [JwtValidationErrorContext](#).

If a failure handler is configured, the request passes to the failure handler. Otherwise, an HTTP 403 Forbidden is returned.

The `iat` claim is required, and the `iat` minus the `skewAllowance` must be before the current time on the PingGateway clock. For information, see [OpenID Connect Core 1.0 incorporating errata set 1](#).

Usage

```
{
  "name": string,
  "type": "IdTokenValidationFilter",
  "config": {
    "idToken": runtime expression<string>,
    "audience": configuration expression<string>,
    "issuer": configuration expression<string>,
    "skewAllowance": configuration expression<duration>,
    "verificationSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference,
    "customizer": JwtValidatorCustomizer reference,
    "failureHandler": Handler reference
  }
}
```

Properties

"idToken": runtime expression<string>, required

The ID token as an expression representing the JWT or signed JWT in the request. Cannot be null.

"audience": configuration expression<string>, required

One `aud` claim to check on the JWT. Cannot be null.

"issuer": configuration expression<string>, optional

One `iss` claim to check on the JWT. Can be null.

"skewAllowance": *configuration expression*<duration>, optional

The duration to add to the validity period of a JWT to allow for clock skew between different servers.

A `skewAllowance` of 2 minutes affects the validity period as follows:

- A JWT with an `iat` of 12:00 is valid from 11:58 on the PingGateway clock.
- A JWT with an `exp` 13:00 is expired after 13:02 on the PingGateway clock.

Default: To support a zero-trust policy, the skew allowance is by default `zero`.

"verificationSecretId": *configuration expression*<secret-id>, required to verify the signature of signed tokens

The secret ID for the secret to verify the signature of signed tokens.

This secret ID must point to a [CryptoKey](#).

If configured, the token must be signed. If not configured, PingGateway doesn't verify the signature.

For information about how signatures are validated, refer to [Validate the signature of signed tokens](#). For information about how each type of secret store resolves named secrets, refer to [Secrets](#).

"secretsProvider": *SecretsProvider reference*, required

The [SecretsProvider](#) to query for passwords and cryptographic keys.

"customizer": *JwtValidatorCustomizer reference*, optional

A set of validation constraints for JWT claims and sub-claims. These constraints are in addition to internally-defined constraints, such as `aud`, `iss`, `exp`, and `iat`. If a claim isn't validated against a constraint, the JWT isn't validated.

The customizer doesn't override existing constraints. Defining a new constraint on an already constrained claim has an impact only if the new constraint is more restrictive.

`JwtValidatorCustomizer` provides a `ScriptableJwtValidatorCustomizer` to enrich a `builder` object by using its methods. Get more information about the following items:

- The `builder` object, at [Available Objects](#).
- Transformer methods, to enrich the builder object, at [org.forgerock.openig.util.JsonValues](#) [↗](#).
- Constraints, at [org.forgerock.openig.tools.jwt.validation.Constraints](#) [↗](#).
- Other properties for `ScriptableJwtValidatorCustomizer`, at [PingGateway scripts](#).

The following examples provide checks:

Check that the value of the claim greaterThan5 is greater than 5

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "builder.claim('/greaterThan5', JsonValue::asInteger, isGreaterThan(5))"
    ]
  }
}
```

Check that the value of the claim sub is george

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "builder.claim('subname', JsonValue::asString, isEqualTo('george'))"
    ]
  }
}
```

Check that the value of the custom sub-claim is ForgeRock

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "builder.claim('customclaim/subclaim', JsonValue::asString, isEqualTo('ForgeRock'));"
    ]
  }
}
```

Check the value of multiple claims

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "builder.claim('aud', listOf(JsonValue::asString), contains('My App'))",
      "      .claim('iat', instant(), isInThePast())",
      "      .claim('exp', instant(), isInTheFuture());",
      "builder.claim('iss', JsonValue::asString, isEqualTo('ForgeRock AM'));"
    ]
  }
}
```

Check that the value of `val1` is greater than `val2`

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [ "builder.claim('/val1', JsonValue::asInteger, isGreaterThan(claim('/val2').asInteger()))" ]
  }
}
```

Check that the value of `val1` is greater than `val2`, when both are `YYYY-MM-DD` dates

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "Function<JsonValue, java.time.LocalDate, Exception> asDate() {",
      "  return (jsonValue) -> java.time.LocalDate.parse(jsonValue.asString());",
      "}",
      "builder.claim('claim1', asDate(), isGreaterThan(claim('claim2').as(asDate())));"
    ]
  }
}
```

Check that the claim issuer matches the regex pattern

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [ "builder.claim('iss', JsonValue::asString, find(~/.am\\.example\\.(com|org)/))" ]
  }
}
```

Default: Claims aren't validated

"failureHandler": *Handler [reference](#), optional*

Handler to treat the request on failure.

Provide an inline handler configuration object or the name of a handler object declared in the heap. See also [PingGateway handlers](#).

Default: HTTP 403 Forbidden, the request stops being executed.

Example

Find an example of how the `IdTokenValidationFilter` is used in [ID token validation with PingAM](#).

More information

[org.forgerock.openig.filter.oauth2.client.IdTokenValidationFilterHeaplet](https://forgerock.org/openig/filter/oauth2/client/IdTokenValidationFilterHeaplet) [↗](#)

[org.forgerock.openig.filter.jwt.JwtValidationContext](#)

[org.forgerock.openig.filter.jwt.JwtValidationErrorContext](#)

[OpenID Connect Core 1.0 incorporating errata set 1](#)

JwtBuilderFilter

Collects data at runtime, packs it in a JSON Web Token (JWT), and places the resulting JWT into the [JwtBuilderContext](#).

Configure JwtBuilderFilter to create a signed JWT, a signed then encrypted JWT, or an encrypted JWT:

- Sign the JWT so that an application can validate the authenticity of the claims/data. The JWT can be signed with a shared secret or private key, and verified with a shared secret or corresponding public key.
- Encrypt the JWT to reduce the risk of a data breach.

For a flexible way to pass identity or other runtime information to the protected application, use this filter with a [HeaderFilter](#).

To enable downstream filters and handlers to verify signed and/or encrypted JWTs built by this filter, use this filter with a [JwkSetHandler](#).

Usage

```
{
  "name": string,
  "type": "JwtBuilderFilter",
  "config": {
    "template": map or runtime expression<map>,
    "secretsProvider": SecretsProvider reference,
    "signature": {
      "secretId": configuration expression<secret-id>,
      "includeKeyId": configuration expression<secret-id>,
      "algorithm": configuration expression<string>,
      "encryption": {
        "secretId": configuration expression<secret-id>,
        "algorithm": configuration expression<string>,
        "method": configuration expression<string>
      }
    },
    "encryption": {
      "secretId": secret-id,
      "algorithm": configuration expression<string>,
      "method": configuration expression<enumeration>
    }
  }
}
```

Properties

template

"template": *map or runtime expression<map>, required*

A map of one or more data pairs with the format `Map<String, Object>`, where:

- The key is the name of a data field
- The value is a data object, or a runtime expression that evaluates to a data object

The following formats are allowed:

```
{
  "template": {
    "string": "runtime expression<object>",
    ...
  }
}
```

```
{
  "template": "runtime expression<map>"
}
```

In the following example, the property is a map whose values are runtime [expressions](#) that evaluate to objects in the context:

```
{
  "template": {
    "name": "${contexts.userProfile.commonName}",
    "email": "${contexts.userProfile.rawInfo.mail[0]}",
    "address": "${contexts.userProfile.rawInfo.postalAddress[0]}",
    "phone": "${contexts.userProfile.rawInfo.telephoneNumber[0]}"
  }
}
```

In the following example, the property is a runtime expression that evaluates to a `Map<String, Object>`:

```
{
  "template": "${contexts.attributes}"
}
```

Use the [now dynamic binding](#) to dynamically set the value of an attribute that represents time. For example, set the value of attributes to a defined time after the expressions are evaluated:

```
{
  "name": "JwtBuilderFilter-1",
  "type": "JwtBuilderFilter",
  "config": {
    "template": {
      "iat": "${now.epochSeconds}",
      "nbf": "${now.plusSeconds(10).epochSeconds}",
      "exp": "${now.plusSeconds(20).epochSeconds}"
    },
    "secretsProvider": "FileSystemSecretStore-1",
    "signature": {
      "secretId": "id.key.for.signing.jwt",
      "algorithm": "RS512"
    }
  }
}
```

secretsProvider

"secretsProvider": *SecretsProvider* [reference](#), required

The [SecretsProvider](#) to query for JWT signing or encryption keys.

signature

"signature": *object*, "signature" and/or "encryption" is required

A JWT signature to allow the authenticity of the claims/data to be validated. A signed JWT can be encrypted.

The [encryption](#) settings take precedence over this property.

"secretId": configuration expression<[secret-id](#)>, required if signature is used

The secret ID of the key to sign the JWT.

This secret ID must point to a [CryptoKey](#).

"includeKeyId": configuration expression<[boolean](#)>, optional

When `true`, include the ID of the signature key in the JWT header.

Default: `true`

"algorithm": configuration expression<[string](#)>, optional

The algorithm to sign the JWT.

The following algorithms are supported but not necessarily tested in PingGateway:

- Algorithms described in [RFC 7518: Cryptographic Algorithms for Digital Signatures and MACs](#).
For RSASSA-PSS, you must install Bouncy Castle. Learn more from [The Legion of the Bouncy Castle](#).
- Ed25519 described in [CFRG Elliptic Curve Diffie-Hellman \(ECDH\) and Signatures in JSON Object Signing and Encryption \(JOSE\)](#).

Default: RS256

"encryption": *object, optional*

Configuration to encrypt the JWT signature.

"secretId": *configuration expression<secret-id>, optional*

The secret ID of the key used to encrypt the JWT signature. The value is mapped to key `aliases` in `KeyStoreSecretStore`.

This secret ID must point to a `CryptoKey`.

"algorithm": *configuration expression<string>, required*

The algorithm used to encrypt the JWT signature.

Learn about available algorithms in [RFC 7518: "alg" \(Algorithm\) Header Parameter Values for JWE](#).

"method": *configuration expression<string>, required*

The method used to encrypt the JWT signature.

Learn about available methods in [RFC 7518: "enc" \(Encryption Algorithm\) Header Parameter Values for JWE](#).

encryption

"encryption" : *object, "signature" and/or "encryption" is required*

Configuration to encrypt the JWT.

This property takes precedence over the `signature` settings.

"secretId": *secret-id, optional*

The secret ID of the key used to encrypt the JWT. The value is mapped to key `aliases` in `KeyStoreSecretStore`.

This secret ID must point to a `CryptoKey`.

"algorithm": *configuration expression<string>, required*

The algorithm used to encrypt the JWT.

Learn about available algorithms in [RFC 7518: "alg" \(Algorithm\) Header Parameter Values for JWE](#).

"method": *configuration expression<enumeration>, required*

The method used to encrypt the JWT.

Learn about available methods in [RFC 7518: "enc" \(Encryption Algorithm\) Header Parameter Values for JWE](#).

Examples

You can find examples in [Passing PingAM data along the chain](#)

More information

[org.forgerock.openig.filter.JwtBuilderFilter](#)

[org.forgerock.openig.filter.JwtBuilderContext](#)

JwtValidationFilter

Validates an unsigned, signed, encrypted, or signed and encrypted JWT. The order of signing and encryption isn't important; a JWT can be signed and then encrypted, or encrypted and then signed.

If the JWT is validated, the request continues down the chain and data is provided in the [JwtValidationContext](#).

If the JWT isn't validated, data is provided in the [JwtValidationErrorContext](#). If a failure handler is configured, the request passes to the failure handler. Otherwise, an HTTP 403 Forbidden is returned.

Usage

```
{
  "name": string,
  "type": "JwtValidationFilter",
  "config": {
    "jwt": runtime expression<string>,
    "verificationSecretId": configuration expression<secret-id>,
    "decryptionSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference,
    "skewAllowance": configuration expression<duration>,
    "customizer": JwtValidatorCustomizer reference,
    "failureHandler": Handler reference
  }
}
```

Properties

jwt

"jwt" : *runtime expression<[string](#)>, required* The value of the JWT in the request. Cannot be null.

verificationSecretId

"verificationSecretId" : *configuration expression<[secret-id](#)>, required* to verify the signature of signed tokens

The secret ID used for the secret to verify the signature of signed tokens.

This secret ID must point to a [CryptoKey](#).

If configured, the token must be signed. If not configured, PingGateway doesn't verify the signature.

Learn more in [Validate the signature of signed tokens](#).

Learn how each type of secret store resolves named secrets in [Secrets](#).

decryptionSecretId

`"decryptionSecretId"` : configuration expression [secret-id](#), required if AM secures access tokens with encryption

The secret ID for the secret to verify the encryption of tokens.

This secret ID must point to a [CryptoKey](#).

If configured, the token must be encrypted. If not configured, PingGateway doesn't verify the encryption.

Learn how each type of secret store resolves named secrets in [Secrets](#).

secretsProvider

`"secretsProvider"` : [SecretsProvider](#) [reference](#), required

The [SecretsProvider](#) to query for passwords and cryptographic keys.

customizer

`"customizer"` : [JwtValidatorCustomizer](#) [reference](#), optional

A set of validation constraints for JWT claims and sub-claims. These constraints are in addition to internally defined constraints, such as `aud`, `iss`, `exp`, and `iat`. If a claim isn't validated against a constraint, the JWT isn't validated.

The customizer doesn't override existing constraints. Defining a new constraint on an already constrained claim has an impact only if the new constraint is more restrictive.

`JwtValidatorCustomizer` provides a `ScriptableJwtValidatorCustomizer` to enrich a `builder` object by using its methods. Get more information about:

- The `builder` object in [Available Objects](#).
- Transformer methods to enrich the builder object in [org.forgerock.openig.util.JsonValues](#) [↗](#).
- Constraints in [org.forgerock.openig.tools.jwt.validation.Constraints](#) [↗](#).
- Other properties for `ScriptableJwtValidatorCustomizer` in [PingGateway scripts](#).

The following examples verify claims:

Check the value of the claim `greaterThan5` is greater than 5

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "builder.claim('/greaterThan5', JsonValue::asInteger, isGreaterThan(5))"
    ]
  }
}
```

Check the value of the claim sub is george

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "builder.claim('subname', JsonValue::asString, isEqualTo('george'))"
    ]
  }
}
```

Check the value of the custom sub-claim is Ping Identity

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "builder.claim('customclaim/subclaim', JsonValue::asString, isEqualTo('Ping Identity'));"
    ]
  }
}
```

Check the values of multiple claims

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "builder.claim('aud', listOf(JsonValue::asString), contains('My App'))",
      "      .claim('iat', instant(), isInThePast())",
      "      .claim('exp', instant(), isInTheFuture());",
      "builder.claim('iss', JsonValue::asString, isEqualTo('PingAM'));"
    ]
  }
}
```

Check the value of val1 is greater than val2

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [ "builder.claim('/val1', JsonValue::asInteger, isGreaterThan(claim('/val2').asInteger()))" ]
  }
}
```

Check the value of `va11` is greater than `va12`, when both are YYYY-MM-DD dates

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "Function<JsonValue, java.time.LocalDate, Exception> asDate() {",
      "  return (jsonValue) -> java.time.LocalDate.parse(jsonValue.asString());",
      "}",
      "builder.claim('claim1', asDate(), isGreaterThan(claim('claim2').as(asDate())));"
    ]
  }
}
```

Check the claim issuer matches the regex pattern

```
"customizer": {
  "type": "ScriptableJwtValidatorCustomizer",
  "config": {
    "type": "application/x-groovy",
    "source": [ "builder.claim('iss', JsonValue::asString, find(~/.am\\.example\\.(com|org)/))" ]
  }
}
```

Default: Claims aren't validated

skewAllowance

"skewAllowance" : *configuration expression*<duration>, optional

The duration to add to the validity period of a JWT to allow for clock skew between different servers.

A **skewAllowance** of 2 minutes affects the validity period as follows:

- A JWT with an **iat** of 12:00 is valid from 11:58 on the PingGateway clock.
- A JWT with an **exp** 13:00 is expired after 13:02 on the PingGateway clock.

Default: To support a zero-trust policy, the default skew allowance is **zero**.

failureHandler

"failureHandler" : *Handler* [reference](#), optional

A [Handler](#) to process the request on failure.

Provide an inline handler configuration object or the name of a handler object declared in the heap.

Default: PingGateway returns HTTP 403 Forbidden and stops processing the request.

Example

You can find an example of using `JwtValidationFilter` in [JWT validation with PingAM](#).

More information

[org.forgerock.openig.filter.jwt.JwtValidationFilter](#) 

[org.forgerock.openig.filter.jwt.JwtValidationContext](#) 

[org.forgerock.openig.filter.jwt.JwtValidationErrorContext](#) 

[OpenID Connect Core 1.0 incorporating errata set 1](#) 

LocationHeaderFilter

For a response that generates a redirect to the proxied application, this filter rewrites the Location header on the response to redirect the user to PingGateway.

Usage

```
{
  "name": string,
  "type": "LocationHeaderFilter",
  "config": {
    "baseURI": runtime expression<url>
  }
}
```

Properties

"baseURI": runtime expression<url>, optional

The base URI of the PingGateway instance. This is used to rewrite the Location header on the response.

The result of the expression must be a string that represents a valid URI, but isn't a real `java.net.URI` object. For example, it would be incorrect to use `${request.uri}`, which isn't a String but a `MutableUri`.

Default: Redirect to the original URI specified in the request.

Learn more in [PingGateway expressions](#).

Example

In the following example, PingGateway listens on <https://ig.example.com:8443>  and the application it protects listens on <https://app.example.com:8444>. The filter rewrites redirects that would normally take the user to locations under <https://app.example.com:8444> to go instead to locations under <https://ig.example.com:8443>.

```
{
  "name": "LocationRewriter",
  "type": "LocationHeaderFilter",
  "config": {
    "baseURI": "https://ig.example.com:8443"
  }
}
```

OAuth2ResourceServerFilter

Validates a request containing an OAuth 2.0 access token. The filter expects an OAuth 2.0 token from the HTTP Authorization header of the request, such as the following example header, where the OAuth 2.0 access token is 1fc...ec9 :

```
Authorization: Bearer 1fc...ec9
```

The filter performs the following tasks:

- Extracts the access token from the request header.
- Uses the configured access token resolver to resolve the access token against an Authorization Server, and validate the token claims.
- Checks that the token has the scopes required by the filter configuration.
- Injects the access token info into the [OAuth2Context](#).

The following errors can occur during access token validation:

Error	Response from the filter to the user agent
Combination of the filter configuration and access token result in an invalid request to the Authorization Server.	HTTP 400 Bad Request
There is no access token in the request header.	HTTP 401 Unauthorized
The access token isn't valid, for example, because it has expired.	
The access token doesn't have all the scopes required in the OAuth2ResourceServerFilter configuration.	HTTP 403 Forbidden

Usage

```
{
  "name": string,
  "type": "OAuth2ResourceServerFilter",
  "config": {
    "accessTokenResolver": AccessTokenResolver reference,
    "cache": {
      "enabled": configuration expression<boolean>,
      "defaultTimeout": configuration expression<duration>,
      "maxTimeout": configuration expression<duration>,
      "amService": AmService reference,
      "onNotificationDisconnection": configuration expression<enumeration>
    },
    "executor": Executor service reference,
    "requireHttps": configuration expression<boolean>,
    "realm": configuration expression<string>,
    "scopes": [ runtime expression<string>, ... ] or ScriptableResourceAccess reference
  }
}
```

An alternative value for type is OAuth2RSFilter.

Properties

accessTokenResolver

"accessTokenResolver": *AccessTokenResolver* [reference](#), *required*

Resolves an access token against an Authorization Server. Configure one of the following access token resolvers:

- [TokenIntrospectionAccessTokenResolver](#)
- [StatelessAccessTokenResolver](#)
- [ConfirmationKeyVerifierAccessTokenResolver](#)
- [ScriptableAccessTokenResolver](#)

To decorate an AccessTokenResolver, add the decoration at the `accessTokenResolver` level. The following example uses the default timer decorator to record the time that a TokenIntrospectionAccessTokenResolver takes to process a request:

```
{
  "accessTokenResolver": {
    "type": "TokenIntrospectionAccessTokenResolver",
    "config": {
      ...
    },
    "timer": true
  }
}
```

cache

"cache" : *object*, optional

Configuration of caching for OAuth 2.0 access tokens. By default, access tokens aren't cached. For an alternative way to cache OAuth 2.0 access tokens, configure a [CacheAccessTokenResolver](#).

When an access token is cached, PingGateway can reuse the token information without repeatedly asking the Authorization Server to verify the access token. When caching is disabled, PingGateway must ask the Authorization Server to verify the access token for each request.

When an access_token is revoked on AM, the CacheAccessTokenResolver can delete the token from the cache when both of the following conditions are true:

- The `notification` property of AmService is enabled.
- The delegate AccessTokenResolver provides the token metadata required to update the cache.

When a refresh_token is revoked on AM, all associated access tokens are automatically and immediately revoked.

enabled: *configuration expression*<*boolean*>, optional

Enable or disable caching.

Default: `false`

defaultTimeout: *configuration expression*<*duration*>, optional

The duration for which to cache an OAuth 2.0 access token if it doesn't provide a valid expiry value.

If an access token provides an expiry value that falls *before* the current time plus the `maxTimeout`, PingGateway uses the token expiry value.

The following example caches access tokens for these times:

- One hour, if the access token doesn't provide a valid expiry value.
- The duration specified by the token expiry value, when the token expiry value is shorter than one day.
- One day, when the token expiry value is longer than one day.

```
"cache": {  
  "enabled": true,  
  "defaultTimeout": "1 hour",  
  "maxTimeout": "1 day"  
}
```

Default: `1 minute`

maxTimeout: *configuration expression*<*duration*>, optional

The maximum duration for which to cache OAuth 2.0 access tokens.

If an access token provides an expiry value that falls *after* the current time plus the `maxTimeout`, PingGateway uses the `maxTimeout`.

The duration cannot be `zero` or `unlimited`.

"amService": *AmService* [reference](#), optional

The [AmService](#) to use for the WebSocket notification service. To evict revoked access tokens from the cache, enable the `notifications` property of AmService.

onNotificationDisconnection: *configuration expression*<[enumeration](#)>, optional

An `amService` must be configured for this property to have effect.

The strategy to manage the cache when the WebSocket notification service is disconnected and PingGateway receives no notifications for AM events. If the cache isn't cleared, it can become outdated, and PingGateway can allow requests on revoked sessions or tokens.

Cached entries that expire naturally while the notification service is disconnected are removed from the cache.

Use one of the following values:

- `NEVER_CLEAR`
 - When the notification service is disconnected:
 - Continue to use the existing cache.
 - Deny access for requests that aren't cached and don't update the cache with these requests.
 - When the notification service is reconnected:
 - Continue to use the existing cache.
 - Query AM for incoming requests that aren't found in the cache and update the cache with these requests.
- `CLEAR_ON_DISCONNECT`
 - When the notification service is disconnected:
 - Clear the cache.
 - Deny access to all requests and don't update the cache with these requests.
 - When the notification service is reconnected:
 - Query AM for all requests that aren't found in the cache. (Because the cache was cleared, the cache is empty after reconnection.)
 - Update the cache with these requests.
- `CLEAR_ON_RECONNECT`
 - When the notification service is disconnected:
 - Continue to use the existing cache.
 - Deny access for requests that aren't cached and don't update the cache with these requests.

- When the notification service is reconnected:
 - Query AM for all requests that aren't found in the cache. (Because the cache was cleared, the cache is empty after reconnection.)
 - Update the cache with these requests.

Default: `CLEAR_ON_DISCONNECT`

executor

`"executor"` : Executor service [reference](#), optional

An [executor service](#) to schedule the execution of tasks, such as the eviction of entries in the access token cache.

Default: `ScheduledExecutorService`

requireHttps

`"requireHttps"` : configuration expression<[boolean](#)>, optional

Whether to require that original target URI of the request uses the HTTPS scheme.

If the received request doesn't use HTTPS, it is rejected.

Default: `true`

realm

`"realm"` : configuration expression<[string](#)>, optional

The HTTP authentication realm PingGateway includes in the WWW-Authenticate response header field when returning an HTTP 401 Unauthorized status to a user-agent that needs to authenticate.

Default: No realm is specified.

scopes

`"scopes"` : array of runtime expression<[strings](#)> or ResourceAccess <[reference](#)>, required

A list of one or more scopes required by the OAuth 2.0 access token. Provide the scopes as strings or through a ResourceAccess such as a ScriptableResourceAccess:

Array of runtime expression<[strings](#)>, required if a [ResourceAccess](#) isn't used

A string, array of strings, runtime expression string, or array of runtime expression strings to represent one or more scopes.

ScriptableResourceAccess <[reference](#)>

A script that evaluates each request dynamically and returns the scopes the request needs to access the protected resource. The script must return a `Set<String>`.

Learn about the properties of ScriptableResourceAccess in [PingGateway scripts](#).

```
{
  "name": string,
  "type": "ScriptableResourceAccess",
  "config": {
    "type": configuration expression<string>,
    "file": configuration expression<string>, // Use either "file"
    "source": [ string, ... ],                // or "source", but not both.
    "args": object,
    "clientHandler": Handler reference
  }
}
```

Default: Empty

Examples

Learn more in [PingGateway as an OAuth 2.0 resource server](#).

More information

[org.forgerock.openig.filter.oauth2.OAuth2ResourceServerFilterHeaplet](#)

[org.forgerock.http.oauth2.OAuth2Context](#)

[org.forgerock.http.oauth2.AccessTokenInfo](#)

[OAuth2Context](#)

[ConfirmationKeyVerifierAccessTokenResolver](#)

[TokenIntrospectionAccessTokenResolver](#)

[StatelessAccessTokenResolver](#)

[ScriptableAccessTokenResolver](#)

[The OAuth 2.0 Authorization Framework](#)

[The OAuth 2.0 Authorization Framework: Bearer Token Usage](#)

OAuth2TokenExchangeFilter

Identifies a client's access token or ID token (a *subject token*), and communicates with an authorization service, such as AM, to exchange it for a new token (an *issued token*):

- When the OAuth2TokenExchangeFilter successfully exchanges a token, it injects the issued token and its scopes into the [OAuth2TokenExchangeContext](#).
- When the OAuth2TokenExchangeFilter fails to exchange a token, it injects information about the failure into the [OAuth2FailureContext](#), which is provided to the `failureHandler`.

The scopes for issued token can be *restricted* or *expanded* by the authorization services:

- Restricted when the token scopes are a subset of those available to the subject token.

- Expanded when they have scopes that aren't included in the subject token.

Use this filter in the *impersonation* use case. Learn more in the AM documentation on [Token Exchange](#).

Usage

```
{
  "name": string,
  "type": "OAuth2TokenExchangeFilter",
  "config": {
    "subjectToken": runtime expression<string>,
    "amService": AmService reference,
    "endpoint": configuration expression<url>,
    "subjectTokenType": configuration expression<string>,
    "requestedTokenType": configuration expression<string>,
    "scopes": [ runtime expression<string>, ... ] or ScriptableResourceAccess reference,
    "resource": configuration expression<url>,
    "audience": configuration expression<string>,
    "endpointHandler": Handler reference,
    "failureHandler": Handler reference
  }
}
```

Configuration

"subjectToken": runtime expression<string>, required

The location of the subject token in the inbound request.

"amService": AmService reference, required if endpoint isn't configured

The AmService to use as the authorization service.

Configure either 'amService' or 'endpoint'. If both are configured, 'amService' takes precedence.

"endpoint": configuration expression<url>, required if amService isn't configured

The URI for the authorization service.

Configure either 'amService' or 'endpoint'. If both are configured, 'amService' takes precedence.

"subjectTokenType": configuration expression<string>, optional

The subject token type.

Default: URN_ACCESS_TOKEN

"requestedTokenType": configuration expression<string>, optional

The type of token being requested.

Default: URN_ACCESS_TOKEN

"scopes": array of runtime expression<strings> or ResourceAccess <reference>, required

A list of one or more scopes required by the OAuth 2.0 access token. Provide the scopes as strings or through a ResourceAccess such as a ScriptableResourceAccess:

Array of runtime expression<strings>, required if a ResourceAccess [isn't used](#)

A string, array of strings, runtime expression<string>, or array of runtime expression<string> to represent one or more scopes.

ScriptableResourceAccess <reference>

A script that evaluates each request dynamically and returns the scopes that the request needs to access the protected resource. The script must return a `Set<String>`.

For information about the properties of ScriptableResourceAccess, refer to [PingGateway scripts](#).

```
{
  "name": string,
  "type": "ScriptableResourceAccess",
  "config": {
    "type": configuration expression<string>,
    "file": configuration expression<string>, // Use either "file"
    "source": [ string, ... ],                // or "source", but not both.
    "args": object,
    "clientHandler": Handler reference
  }
}
```

Default: Empty

"resource": configuration expression<url>, optional

The target service URI where the issued token is intended to be used.

"audience": configuration expression<url>, optional

The target service name where the token is intended to be used.

"endpointHandler": Handler [reference](#), optional

The handler to exchange tokens on the authorization endpoint.

Configure this property as a [Chain](#), using one of the following filters for client authentication:

- [ClientSecretBasicAuthenticationFilter](#)
- [ClientSecretPostAuthenticationFilter](#)
- [EncryptedPrivateKeyJwtClientAuthenticationFilter](#)
- [PrivateKeyJwtClientAuthenticationFilter](#)

```
{
  "name": "EndpointHandler",
  "type": "Chain",
  "config": {
    "handler": "ForgeRockClientHandler",
    "filters": [
      {
        "type": "ClientSecretBasicAuthenticationFilter",
        "config": {
          "clientId": "serviceConfidentialClient",
          "clientSecretId": "client.secret.id",
          "secretsProvider": "SystemAndEnvSecretStore-1",
        }
      }
    ]
  }
}
```

Default: ForgeRockClientHandler

"failureHandler": *Handler* <[reference](#)>, optional

Handler to manage a failed request.

Provide an inline handler configuration object or the name of a handler object declared in the heap. The handler can access information in the [OAuth2FailureContext](#).

Default: `500 Internal Server Error`, the request stops being executed.

Example

You can find an example of how this filter is used in [OAuth 2.0 token exchange with PingAM](#).

More information

[org.forgerock.http.oauth2.OAuth2TokenExchangeFilter](#) [↗](#)

[OAuth2TokenExchangeContext](#)

[OAuth2FailureContext](#)

[The OAuth 2.0 Authorization Framework](#) [↗](#)

PasswordReplayFilter

Replays credentials to a login page or to the next filter or handler in the chain. The PasswordReplayFilter doesn't retry failed authentication attempts.

Usage

```
{
  "name": string,
  "type": "PasswordReplayFilter",
  "config": {
    "request": object,
    "loginPage": runtime expression<boolean>,
    "loginPageContentMarker": pattern,
    "credentials": Filter reference,
    "loginPageExtractions": [ object, ... ]
  }
}
```

Properties

"request": <object>, required

The HTTP request message that replays the credentials.

```
{
  "request": object,
  "method": config expression<string>,
  "uri": runtime expression<string>,
  "version": configuration expression<string>,
  "entity": runtime expression<string>,
  "headers": map,
  "form": map
}
```

For information about the properties of `request`, refer to [Request](#).

The JSON object of `request` is the `config` content of a [StaticRequestFilter](#).

"loginPage": runtime expression<boolean>, required unless loginPageContentMarker is defined

`true`: Direct the request to a login page, extract credentials, and replay them.

`false`: Pass the request unchanged to the next filter or handler in the chain.

The following example expression resolves to `true` when the request is an HTTP GET, and the request URI path is `/login`:

```
${find(request.uri.path, '/login') and (request.method == 'GET')}
```

"loginPageContentMarker": pattern, required unless loginPage is defined

A [Patterns and PingGateway](#) that matches when a response entity is a login page.

You can find an example route that uses this property in [Login form with password replay and cookie filters](#).

"credentials": *Filter reference, optional*

[Filter](#), such as a [FileAttributesFilter](#) or [SqlAttributesFilter](#), that injects credentials, making them available for replay.

When this isn't specified, credentials must be made available to the request by other means.

"loginPageExtractions": *array of <objects>, optional*

Objects to extract values from the login page entity.

```
{
  "loginPageExtractions": [
    {
      "name": string,
      "pattern": pattern
    },
    ...
  ]
}
```

The extract configuration array is a series of configuration objects. To extract multiple values, use multiple extract configuration objects. Each object has the following fields:

"name": *string, required*

Name of the field where the extracted value is put.

The names are mapped into `attributes.extracted`.

For example, if the name is `nonce`, the value can be obtained with the expression `${attributes.extracted.nonce}`.

The name `isLoginPage` is reserved to hold a boolean that indicates whether the response entity is a login page.

"pattern": *pattern, required*

The regular expression pattern to find in the entity.

The pattern must contain one capturing group. (If it contains more than one, only the value matching the first group is placed into `attributes.extracted`.)

For example, suppose the login page entity contains a nonce required to authenticate, and the nonce in the page looks like `nonce='n-0S6_WzA2Mj'`. To extract `n-0S6_WzA2Mj`, set `"pattern": " nonce='(.*)'"`.

Example

The following example authenticates requests using static credentials when the request URI path is `/login`. This `PasswordReplayFilter` example doesn't include any mechanism for remembering when authentication has already been successful, it simply replays the authentication every time that the request URI path is `/login`:

```

{
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [{
        "type": "PasswordReplayFilter",
        "config": {
          "loginPage": "${request.uri.path == '/login'}",
          "request": {
            "method": "POST",
            "uri": "https://www.example.com:8444/login",
            "form": {
              "username": [
                "MY_USERNAME"
              ],
              "password": [
                "MY_PASSWORD"
              ]
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

Additional examples:

- [Password replay and PingOne Advanced Identity Cloud](#) with PingOne Advanced Identity Cloud
- [Password replay with AM](#)
- [Password replay from a database](#)
- [Password replay from a file](#)

More information

org.forgerock.openig.filter.PasswordReplayFilterHeaplet 

PingOneApiAccessManagementFilter

Use the PingOneApiAccessManagementFilter with PingOne Authorize's API Access Management capability, where the PingOne API moderates requests and responses as follows:

- Allows requests, optionally instructing PingGateway to edit the requests.
- Rejects requests, instructing PingGateway on how to respond to the client, such as with an HTTP 403 and a custom message.
- Instructs PingGateway to update responses from the backend; for example, instructions to remove content from the response body or to add or remove headers.

The filter sends the following elements to the PingOne API for the request:

- Client IP address
- Client port
- HTTP method used
- URL targeted
- HTTP version used
- HTTP headers
- HTTP content (if the content matches any of the optional `includeBodyContentTypes`)

The filter sends the following elements to the PingOne API for the response:

- Original URL queried
- Original method called
- HTTP status code
- HTTP status message
- HTTP version
- HTTP headers
- HTTP content (if the content matches any of the optional `includeBodyContentTypes`)

Usage

```
{
  "name": string,
  "type": "PingOneApiAccessManagementFilter",
  "config": {
    "gatewayServiceUri": configuration expression<url>,
    "secretsProvider": SecretsProvider reference,
    "gatewayCredentialSecretId": configuration expression<secret-id>,
    "includeBodyContentTypes": [ configuration expression<string> ] || configuration expression<string>,
    "sidebandHandler": Handler reference,
    "accessToken": runtime expression<string>
  }
}
```

Configuration

"gatewayServiceUri": *configuration expression<url>*, required

The URL of the API gateway in the PingOne API.

To find the URL, go to your PingOne Authorize environment, select **Authorization > API gateways**, and note the value of the **Service URL**.

"secretsProvider": *SecretsProvider* [reference](#), required

The [SecretsProvider](#) to query for the credential to access the PingOne API.

"gatewayCredentialSecretId": *configuration expression*<[secret-id](#)>, required

The secret ID of the PingOne API credential.

The secret ID must point to a [GenericSecret](#) in the `secretsProvider`.

To add the credential, go to your PingOne Authorize environment, select **Authorization > API gateways**, and select your gateway.

"includeBodyContentTypes": *array of configuration expression*<[string](#)>, optional

If any of these content types are present, include the body of the request or response in the request to the PingOne API.

** Note**

Including the body in every request and response can impact the HTTP exchange latency.

Default: Don't send the request body to the PingOne API.

"sidebandHandler": *Handler* [reference](#), optional

An HTTP client handler to use to contact the PingOne API.

The handler sends requests and responses to the HTTP Access Policy service. It then processes authorization decisions to accept, reject, or rewrite requests and responses.

Default: `ForgeRockClientHandler`

"accessToken": *runtime expression*<[string](#)>, optional

The location of the access token to send to the PingOne API.

Default: none, the token is expected to be present in the request's "Authorization" header.

More information

org.forgerock.openig.ping.PingOneApiAccessManagementFilter[↗](#)

PingOneProtectEvaluationFilter

Passes data to PingOne Protect and gets a risk evaluation for an incoming request.

PingGateway makes a risk evaluation request to PingOne Protect. The PingOne Protect response returns a risk evaluation including the following items PingGateway retains in the evaluation context:

- Risk level (`low`, `medium`, or `high`)
- Risk score, a single aggregated numerical value

The `PingOneProtectEvaluationFilter` records the evaluation in a `PingOneProtectEvaluationContext` object. Configure a `PingOneProtectThreatLevelRoutingHandler` to act on the risk level set in the context. As an alternative, use a `DispatchHandler` to act on the risk score.

Usage

```
{
  "name": string,
  "type": "PingOneProtectEvaluationFilter",
  "config": {
    "pingOneService": PingOneService reference,
    "failureHandler": Handler reference,
    "userId": runtime expression<string>,
    "policySet": configuration expression<string>,
    "lowRiskEvaluationThrottlePeriod": configuration expression<duration>,
    "nonEvaluatedUrls": configuration expression<boolean>,
    "deviceProfile": {
      "callbackEndpoint": configuration expression<string>,
      "enabled": configuration expression<boolean>,
      "lifetime": configuration expression<duration>,
      "cookieName": configuration expression<string>,
      "noJavaScriptMessage": configuration expression<string>,
      "timeout": configuration expression<duration>,
      "failureAction": configuration expression<string>
    }
  }
}
```

Properties

pingOneService

"pingOneService" : *Handler [reference](#), required*

The `PingOneService` to access the evaluation endpoint in the PingOne environment.

failureHandler

"failureHandler" : *Handler [reference](#), optional*

The `Handler` PingGateway calls when an error occurs.

Default: Return an HTTP 403 Forbidden response; if the request to the evaluation endpoint fails, PingGateway denies access by default.

userId

"userId" : *runtime expression<[string](#)>, optional*

An expression setting the user identifier, if available; for example, if the user has already authenticated in the route.

PingGateway raises an error if the expression resolves to `null`.

Default: A UUID that remains the same for the lifetime of the session

policySet

`"policySet"` : *configuration expression*<string>, optional

The PingOne Protect policy set to use.

Default: The default policy set for the evaluation service

lowRiskEvaluationThrottlePeriod

`"lowRiskEvaluationThrottlePeriod"` : *configuration expression*<duration>, optional

When PingOne Protect returns a low risk level for an incoming request, PingGateway waits until this period expires before making another risk evaluation request for the same session.

Set this to zero to make a risk evaluation request for every incoming request.

Default: 2 minutes

nonEvaluatedUrls

`"nonEvaluatedUrls"` : *configuration expression*<boolean>, optional

A boolean conditional expression matching request URLs to exclude from risk evaluation.

This setting exists for intermediate flows, such as CDSSO requests, that PingGateway shouldn't evaluate for risk. Don't use it to exclude ordinary request URLs from risk evaluation.

Default: `false` (evaluate risk for all request URLs)

deviceProfile

`"deviceProfile"` : *object*, optional

The settings governing collection and use of device profile data from the user-agent.

After PingGateway collects device profile data, it stores the data in cookies on the user-agent. The user-agent returns these to PingGateway in the `Cookie` request header. Set the `maxTotalHeadersSize` for the PingGateway server ports large enough to avoid HTTP 431 Request Header Fields Too Large errors; for example:

```
"connectors": [  
  {  
    "port": 8080,  
    "maxTotalHeadersSize": 32768  
  },  
  {  
    "port": 8443,  
    "maxTotalHeadersSize": 32768,  
    "tls": "TlsConf"  
  }  
],
```

Default: Don't collect device profile data.

"callbackEndpoint": configuration expression<string>, required

PingGateway endpoint to transform and manage the collected device profile data.

This endpoint must:

- Match the `"condition"` for the route so PingGateway routes the device profile callback correctly.
- Be different from the callback or redirect endpoints for any other filters in the route, such as a [CrossDomainSingleSignOnFilter](#), a [DataPreservationFilter](#), or a [FragmentFilter](#).

For example, if the route has `"condition": "${find(request.uri.path, '^/home/cdsso')}"`, and a [CrossDomainSingleSignOnFilter](#) with `"redirectEndpoint": "/home/cdsso/redirect"`, choose a different path under the base request URI path like `"callbackEndpoint": "/home/cdsso/profilecallback"`.

"enabled": configuration expression<boolean>, optional

Enable device profiling.

Default: `true`

"lifetime": configuration expression<duration>, optional

How long to keep collected device profile data before forcing it to be collected again.

Default: 5 minutes

"cookieName": configuration expression<string>, optional

PingGateway stores collected device profile data on the user-agent in one or more cookies with this name. If the device profile cookie data exceeds 4 KBytes, PingGateway automatically splits it into multiple cookies each with a numeric suffix to determine the order.

Default: `ig_profile`

"noJavaScriptMessage": configuration expression<string>, optional

PingGateway collects device profile data on the user-agent by sending it a self-submitting form page that uses JavaScript to retrieve the profile information.

When the user-agent won't run the script, the page displays this message to the end user.

Default: `Javascript is disabled in your browser`

"timeout": configuration expression<duration>, optional

How long to wait for the user-agent to respond with device profile data.

Default: 500 milliseconds

"failureAction": configuration expression<string>, optional

Action to take when this filter fails to collect device profile data or collection times out; one of:

- `deny` : Deny the request without further risk evaluation.
- `proceed` : Allow risk evaluation to continue without device profile data.

Default: `deny`

Example

The following example prepares PingGateway to make requests to PingOne Protect for risk evaluation. It doesn't request risk evaluation for CDSO redirect requests to `/home/cdsso/redirect`. The policy set identifier depends on your PingOne Protect deployment:

```
{
  "name" : "PingOneProtectEvaluationFilter-1",
  "type" : "PingOneProtectEvaluationFilter",
  "config" : {
    "pingOneService" : "PingOneService-1",
    "policySet" : "47447388-fa5a-40f7-b3f1-24fbbbbc30",
    "userId" : "${contexts.cdsso.claimsSet.subject}",
    "nonEvaluatedUrls" : "${find(request.uri.path, '/home/cdsso/redirect')}",
    "deviceProfile": {
      "callbackEndpoint": "/home/cdsso/profilecallback"
    }
  }
}
```

More information

org.forgerock.openig.ping.protect.PingOneProtectEvaluationFilter

PingOneProtectFeedbackFailureFilter

Provides a feedback mechanism for actions that failed following risk evaluation with PingOne Protect. This filter registers its completion status (`failure`) with PingOne Protect.

Put this filter at a point in the route where PingGateway knows the definitive result of post-evaluation actions is failure. For example, add it to a chain just before the handler that runs on failure as shown in [PingOne Protect integration with PingGateway](#).

Usage

```
{
  "name": string,
  "type": "PingOneProtectFeedbackFailureFilter",
  "config": {
    "pingOneService": PingOneService reference,
    "postEvaluationAssumedRiskLevel": configuration expression<string>
  }
}
```

Configuration

"pingOneService": *Handler reference, required*

The [PingOneService](#) to access the feedback endpoint in the PingOne environment.

If an error occurs with the request to the feedback endpoint, PingGateway passes to the next handler. The optional `"postEvaluationAssumedRiskLevel"` setting applies as configured.

"postEvaluationAssumedRiskLevel": *configuration expression*<string>, optional

A string to override the assumed risk level managed in the local session state.

PingGateway uses this during the `"lowRiskEvaluationThrottlePeriod"` defined in the [PingOneProtectEvaluationFilter](#) for the route to decide whether to make a risk evaluation request to PingOne Protect for the next incoming request.

One of:

- `low`
- `medium`
- `high`

Default: don't override the risk level in the session state.

PingOneProtectFeedbackSuccessFilter

Provides a feedback mechanism for actions that completed successfully following risk evaluation with PingOne Protect. This filter registers its completion status (`success`) with PingOne Protect.

Put this filter at a point in the route where PingGateway knows the definitive result of post-evaluation actions is success. For example, add it to a chain just before the handler that runs on successful completion as shown in [PingOne Protect integration with PingGateway](#).

Usage

```
{
  "name": string,
  "type": "PingOneProtectFeedbackSuccessFilter",
  "config": {
    "pingOneService": PingOneService reference,
    "postEvaluationAssumedRiskLevel": configuration expression<string>
  }
}
```

Configuration

"pingOneService": *Handler reference*, required

The [PingOneService](#) to access the feedback endpoint in the PingOne environment.

If an error occurs with the request to the feedback endpoint, PingGateway passes to the next handler. The optional `"postEvaluationAssumedRiskLevel"` setting applies as configured.

"postEvaluationAssumedRiskLevel": *configuration expression*<string>, optional

A string to override the assumed risk level managed in the local session state.

PingGateway uses this during the `"lowRiskEvaluationThrottlePeriod"` defined in the [PingOneProtectEvaluationFilter](#) for the route to decide whether to make a risk evaluation request to PingOne Protect for the next incoming request.

One of:

- `low`
- `medium`
- `high`

Default: don't override the risk level in the session state.

PolicyEnforcementFilter

Requests and enforces policy decisions from AM. For more information, refer to PingGateway's [PingAM policy enforcement](#) and AM's [Authorization guide](#).

AM can deny access with *advice* in the policy decision response. The advice indicates how to authenticate the user for access to the resource. PingGateway stores attributes and advices in the `policyDecision` context. For information, refer to [PolicyDecisionContext](#).

When you precede a PolicyEnforcementFilter in a [Chain](#) with a [SingleSignOnFilter](#) or [CrossDomainSingleSignOnFilter](#), PingGateway reacts to AM advices in the policy decision:

- `AuthLevelConditionAdvice` : Authenticate the user to reach the specified authentication level.
- `AuthSchemeConditionAdvice` : Authenticate the user based on the details of the specified scheme.
- `AuthenticateToRealmConditionAdvice` : Authenticate the user to the specified realm.
- `AuthenticateToServiceConditionAdvice` : Authenticate the user with the specified authentication journey or chain. (AM has deprecated authentication chains.)
- `TransactionConditionAdvice` : Perform additional actions to authenticate the user for one-time access to the protected resource.

To respond to advices from AM:

- Use the PolicyEnforcementFilter in a Chain.
- Add a SingleSignOnFilter or CrossDomainSingleSignOnFilter before the PolicyEnforcementFilter.

If you don't precede it with an SSO filter, the PolicyEnforcementFilter ignores the advice. When AM returns advice, the PolicyEnforcementFilter denies access with HTTP 403 Forbidden by default.

If you can't use a SingleSignOnFilter or CrossDomainSingleSignOnFilter before the PolicyEnforcementFilter, it's still possible to enable PingGateway to respond to advices:

- Write a script to respond to advice from AM.

For details about the advice types AM returns, refer to [Policy decision advice](#) in the AM documentation.

- Use a scriptable filter or handler in the `"failureHandler"` of the PolicyEnforcementFilter to trigger the script.

Notes on configuring policies in AM

In the AM policy, remember to configure the **Resources** parameter with the URI of the protected application.

The request URI from PingGateway must match the **Resources** parameter defined in the AM policy. If the URI of the incoming request is changed before it enters the policy filter (for example, by rebasing or scripting), remember to change the **Resources** parameter in AM policy accordingly.

WebSocket notifications for policy changes

When WebSocket notifications are set up for changes to policies, PingGateway receives a notification from AM when a policy decision is created, deleted, or updated.

You can find more information about setting up WebSocket notifications, using them to clear the policy cache, and including them in the server logs in [WebSocket Notifications](#).

Usage

```
{
  "name": string,
  "type": "PolicyEnforcementFilter",
  "config": {
    "amService": AmService reference,
    "pepRealm": configuration expression<string>,
    "ssoTokenSubject": runtime expression<string>,
    "jwtSubject": runtime expression<string>,
    "claimsSubject": map or runtime expression<map>,
    "cache": {
      "enabled": configuration expression<boolean>,
      "defaultTimeout": configuration expression<duration>,
      "executor": Executor service reference,
      "maximumSize": configuration expression<number>,
      "maximumTimeToCache": configuration expression<duration>,
      "onNotificationDisconnection": configuration expression<enumeration>
    },
    "application": configuration expression<string>,
    "environment": map or runtime expression<map>,
    "failureHandler": Handler reference,
    "resourceUriProvider": ResourceUriProvider reference,
    "authenticateResponseRequestHeader": configuration expression<string>,
    "useLegacyAdviceEncoding": configuration expression<boolean> //deprecated
  }
}
```

Properties

amService

"amService" : *AmService* [reference](#), *required*

The AM instance to use for policy decisions.

pepRealm

"pepRealm" : *configuration expression<string>*, *optional*

The AM realm where the policy set is located.

Default: The realm declared for `amService`.

ssoTokenSubject

`"ssoTokenSubject"` : runtime expression<string>, required if neither of the following properties are present: `jwtSubject`, `claimsSubject`

The AM token ID string for the subject making the request to the protected resource.

`ssoTokenSubject` can take the value of the session token from the following sources:

- When the `PolicyEnforcementFilter` is preceded by a `SingleSignOnFilter`, `${contexts.ssoToken.value}`.
- When the `PolicyEnforcementFilter` is preceded by a `CrossDomainSingleSignOnFilter`, `${contexts.ssoToken.value}` or `${contexts.cdsso.token}`.
- When the `PolicyEnforcementFilter` isn't preceded by a `SingleSignOnFilter` or `CrossDomainSingleSignOnFilter`, `ssoTokenSubject` usually points to the token value.

The token value can be in the request message, a header, or a cookie. For example, the `ssoTokenSubject` can point to a header value, such as `${request.headers.cookie name}`, where `cookie name` is the AM session cookie name.

Requests that return a policy decision with advices fail with an HTTP 403 and no advice handling.

jwtSubject

`"jwtSubject"` : runtime expression<string>, required if neither of the following properties are present: `ssoTokenSubject`, `claimsSubject`

The JWT string for the subject making the request to the protected resource.

To use the raw `id_token` (base64, not decoded) returned by the OpenID Connect Provider during authentication, place an [AuthorizationCodeOAuth2ClientFilter](#) before the PEP filter and use `${attributes.openid.id_token}` as the `expression` value.

claimsSubject

`"claimsSubject"` : `map` or runtime expression<map>, required if neither of the following properties are present: `jwtSubject`, `ssoTokenSubject`

A map of one or more data pairs with the format `Map<String, Object>`, where:

- The key is the name of a claim.
- The value is a claim object or a runtime expression that evaluates to a claims object.

The following formats are allowed:

```
{
  "claimsSubject": {
    "string": "runtime expression<object>",
    ...
  }
}
```

```
{
  "claimsSubject": "runtime expression<map>"
}
```

The claim `"sub"` must be specified; other claims are optional.

In the following example, the property is a map whose first value is a runtime [expression](#) that evaluates to a JWT claim for the subject, and whose second value is a JWT claim for the subject:

```
"claimsSubject": {
  "sub": "${attributes.subject_identifier}",
  "iss": "am.example.com"
}
```

In the following example, the property is a runtime [expression](#) that evaluates to a map with the format `Map<String, Object>`:

```
"claimsSubject": "${attributes.openid.id_token_claims}"
```

Learn more in the example of [policy enforcement using claimsSubject](#).

cache

`"cache"` : *object, optional*

Enable and configure caching of policy decisions from AM based on [Caffeine](#).

When a request matches a cached policy decision, PingGateway can reuse the decision without asking AM for a new decision. When caching is disabled, PingGateway must ask AM to make a decision for each request.

```
{
  "cache": {
    "enabled": configuration expression<boolean>,
    "defaultTimeout": configuration expression<duration>,
    "executor": Executor service reference,
    "maximumSize": configuration expression<number>,
    "maximumTimeToCache": configuration expression<duration>,
    "onNotificationDisconnection": configuration expression<enumeration>
  }
}
```

Note

Policy decisions that contain advices are never cached.

The following code example caches AM policy decisions without advices for these times:

- One hour, when the policy decision doesn't provide a `ttl` value.
- The duration specified by the `ttl`, when `ttl` is shorter than one day.

- One day, when `ttl` is longer than one day.

```
"cache": {  
  "enabled": true,  
  "defaultTimeout": "1 hour",  
  "maximumTimeToCache": "1 day"  
}
```

Default: Policy decisions aren't cached.

"enabled": configuration expression<boolean>, optional

Enable or disable caching of policy decisions.

Default: `false`

"defaultTimeout": configuration expression<duration>, optional

The default duration for which to cache AM policy decisions.

If an AM policy decision provides a valid `ttl` value to specify the time the policy decision remains valid, PingGateway uses that value or the `maxTimeout`.

Default: `1 minute`

"executor": Executor service reference, optional

An executor service to schedule the execution of tasks, such as the eviction of entries in the cache.

Default: `ForkJoinPool.commonPool()`

"maximumSize": configuration expression<number>, optional

The maximum number of entries the cache can contain.

Default: Unlimited/unbound.

"maximumTimeToCache": configuration expression<duration>, optional

The maximum duration for which to cache AM policy decisions.

If the `ttl` value provided by the AM policy decision is after the current time plus the `maximumTimeToCache`, PingGateway uses the `maximumTimeToCache`.

The duration cannot be `zero` or `unlimited`.

"onNotificationDisconnection": configuration expression<enumeration>, optional

The strategy to manage the cache when the WebSocket notification service is disconnected and PingGateway receives no notifications for AM events. If the cache isn't cleared it can become outdated and PingGateway can allow requests on revoked sessions or tokens.

Cached entries that expire naturally while the notification service is disconnected are removed from the cache.

Use one of the following values:

- **NEVER_CLEAR**
 - When the notification service is disconnected:
 - Continue to use the existing cache.
 - Deny access for requests that aren't cached, but don't update the cache with these requests.
 - When the notification service is reconnected:
 - Continue to use the existing cache.
 - Query AM for incoming requests that aren't found in the cache and update the cache with these requests.
- **CLEAR_ON_DISCONNECT**
 - When the notification service is disconnected:
 - Clear the cache.
 - Deny access to all requests, but don't update the cache with these requests.
 - When the notification service is reconnected:
 - Query AM for all requests that aren't found in the cache. (Because the cache was cleared, the cache is empty after reconnection.)
 - Update the cache with these requests.
- **CLEAR_ON_RECONNECT**
 - When the notification service is disconnected:
 - Continue to use the existing cache.
 - Deny access for requests that aren't cached, but don't update the cache with these requests.
 - When the notification service is reconnected:
 - Query AM for all requests that aren't found in the cache. (Because the cache was cleared, the cache is empty after reconnection.)
 - Update the cache with these requests.

Default: **CLEAR_ON_DISCONNECT**

application

"application" : *configuration expression*<string>, optional

The ID of the AM policy set to use when requesting policy decisions.

Default: **iPlanetAMWebAgentService**, provided by AM's default policy set

environment

"environment" : *map* or runtime expression<map>, optional

A map of one or more data pairs with the format `Map<String, Object>`, where:

- The key is the name of a field in the request environment or context, such as a request header.
- The value is the object to forward to AM with a policy decision request or a runtime expression that evaluates to the object.

The following formats are allowed:

```
{
  "claimsSubject": {
    "string": "runtime expression<object>",
    ...
  }
}
```

```
{
  "claimsSubject": "runtime expression<map>"
}
```

AM uses environment conditions to set the circumstances where a policy applies. For example, environment conditions can specify the policy applies only during working hours or only when accessing from a specific IP address.

Forward any HTTP header or any value that the AM policy definition can use.

In the following example, the property is a map whose values are runtime [expressions](#) that evaluate to request headers, an ID token, and the IP address of the subject making the request:

```
"environment": {
  "H-Via": "${request.headers['Via']}",
  "H-X-Forwarded-For": "${request.headers['X-Forwarded-For']}",
  "H-myHeader": "${request.headers['myHeader']}",
  "id_token": [
    "${attributes.openid.id_token}"
  ],
  "IP": [
    "${contexts.client.remoteAddress}"
  ]
}
```

failureHandler

"failureHandler" : *Handler reference*, optional

Handler to treat the request if it is denied by the policy decision.

In the following example, the `failureHandler` passes the request to a `StaticResponseHandler` to display a message:

```

"failureHandler": {
  "type": "StaticResponseHandler",
  "config": {
    "status": 403,
    "headers": {
      "Content-Type": [
        "text/plain; charset=UTF-8"
      ]
    },
    "entity": "Restricted area. You don't have sufficient privileges."
  }
}

```

Default: HTTP 403 Forbidden, the request stops being executed.

resourceUriProvider

"resourceUriProvider": *ResourceUriProvider* [reference](#), optional

Use one of the following providers to return a resource URL to include in policy decision requests to AM:

- [RequestResourceUriProvider](#)
- [ScriptableResourceUriProvider](#)

The PolicyEnforcementFilter uses the returned resource URL to identify the policy decision in the policy cache.

When a request matches a cached policy decision, PingGateway can reuse the decision without asking AM for a new decision. When caching is disabled, PingGateway must ask AM to make a decision for each request.

Default: `RequestResourceUriProvider` configured to use the request URI with all query parameters included.

Maximize the cache hit ratio by managing the returned resource URL in conjunction with AM policies:

Strip all query parameters from the returned resource URL

Consider the following AM policy that matches requests on the specified path. The policy ignores query parameters:

```
https://ig.example.com:8443/app
```

The following requests match the path but have additional query parameters:

```

https://ig.example.com:8443/app?day=monday
https://ig.example.com:8443/app?day=monday&place=london
https://ig.example.com:8443/app?day=monday&place=london&building=x

```

When `includeQueryParams` in `RequestResourceUriProvider` is `true`, the `ResourceUriProvider` includes all query parameters in requests for policy decisions. The `PolicyEnforcementFilter` requests a policy decision for the first request `/app?day=monday` and caches the decision. The second request `app?day=monday&place=london` doesn't match the cached decision, so the `PolicyEnforcementFilter` requests another policy decision and adds it to the cache. Similarly for the third request.

When `includeQueryParams` in `RequestResourceUriProvider` is `false`, the `ResourceUriProvider` strips all query parameters from the requests. The `PolicyEnforcementFilter` requests a policy decision for the first request without query parameters and caches the policy decision. The following two requests without query parameters match the cached decision and PingGateway uses the cached decision without consulting AM.

Include only specified query parameters in the returned resource URL

Consider a similar example where an AM policy matches requests on the specified path and having a specified query parameter:

```
https://ig.example.com:8443/app?day=monday
```

The following requests match the path and query parameter, but two of them have additional query parameters:

```
https://ig.example.com:8443/app?day=monday
https://ig.example.com:8443/app?day=monday&place=london
https://ig.example.com:8443/app?day=monday&place=london&building=x
```

Because the policy requires a query parameter, you can't use `RequestResourceUriProvider` to strip all query parameters from the requests.

Instead, use a `ScriptableResourceUriProvider` to include the `?day=monday` query parameter but strip all other query parameters.

Note

Query order is important. The following queries are semantically the same but don't match: `?day=monday&place=london` and `?place=london&day=monday`.

```
"resourceUriProvider": {
  "type": "ScriptableResourceUriProvider",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "// Define a list of parameters to keep",
      "def keepOnly = { [ 'place', 'day' ].contains(it.key) }",
      "// Build a new URI based on the original request URI",
      "return new MutableUri(request.uri).with { uri ->",
      "  // Build a filtered and normalized query string",
      "  uri.rawQuery = new Form().with { form ->",
      "    // Keep only the wanted parameters and sort by name",
      "    form.addAll(request.queryParams.findAll(keepOnly).sort())",
      "    return form.toQueryString()",
      "  }",
      "  // Return the full modified URI",
      "  return uri.toASCIIString()",
      "}"
    ]
  }
}
```


authenticateResponseRequestHeader

`authenticateResponseRequestHeader` : configuration expression<[string](#)>, optional

A header to include in a request to manage the way PingGateway handles policy advices from AM. The header name and value is case-insensitive. The header value can be set as follows:

- `HEADER` : Return policy advices in a `WWW-Authenticate` header as base64-encoded JSON in a parameter called `advices` .
- Any other value: Return policy advices as parameters in a redirect response (default).

Learn more in the example showing how to [deny requests with advice in a header](#).

Default: `x-authenticate-response`

useLegacyAdviceEncoding (deprecated)

`useLegacyAdviceEncoding` : configuration expression<[boolean](#)>, optional



Important

This property is deprecated and should be used only to support SDK in legacy installations. Learn more in the [Deprecated](#) section of the *Release Notes*.

- `true` : Don't encode advices.
- `false` : Encode advices with the encoder used by the AM version.

Default: `false`

Examples

You can find examples of policy enforcement in [PingAM policy enforcement](#).

More information

[org.forgerock.openig.openam.PolicyEnforcementFilter](#)

[org.forgerock.openig.openam.PolicyDecisionContext](#)

[PolicyDecisionContext](#)

AM's [Authorization guide](#)

PrivateKeyJwtClientAuthenticationFilter

Supports client authentication with the `private_key_jwt` client-assertion, using an unencrypted JWT.

Clients send a signed JWT to the Authorization Server. PingGateway builds and signs the JWT, and prepares the request as in the following example:

```
POST /token HTTP/1.1
Host: as.example.com
Content-Type: application/x-www-form-urlencoded

grant_type=authorization_code&
code=...&
client_id=<clientregistration_id>&
client_assertion_type=urn%3Aietf%3Aparams%3Aoauth%3Aclient-assertion-type%3Ajwt-bearer&
client_assertion=PHNhbwXw01 ... ZT
```

Use this filter with an endpoint handler that requires authentication with the with the `private_key_jwt` client-assertion, using an unencrypted JWT. For example, the `endpointHandler` handler in the [OAuth2TokenExchangeFilter](#).

Usage

```
{
  "name": string,
  "type": "PrivateKeyJwtClientAuthenticationFilter",
  "config": {
    "clientId": configuration expression<string>,
    "tokenEndpoint": configuration expression<url>,
    "secretsProvider": SecretsProvider reference,
    "signingSecretId": configuration expression<secret-id>,
    "signingAlgorithm": configuration expression<string>,
    "jwtExpirationTimeout": configuration expression<duration>,
    "claims": map or configuration expression<map>
  }
}
```

Configuration

"clientId": configuration expression<string>, required

The `client_id` obtained when registering with the Authorization Server.

"tokenEndpoint": configuration expression<url>, required

The URL to the Authorization Server's OAuth 2.0 token endpoint.

"secretsProvider": SecretsProvider reference, required

The [SecretsProvider](#) to query for passwords and cryptographic keys.

"signingSecretId": configuration expression<string>, required

Reference to the keys used to sign the JWT.

This secret ID must point to a [CryptoKey](#).

"signingAlgorithm": configuration expression<string>, optional

The JSON Web Algorithm (JWA) used to sign the JWT, such as:

- RS256 : RSA using SHA-256

- **ES256** : ECDSA with SHA-256 and NIST standard P-256 elliptic curve
- **ES384** : ECDSA with SHA-384 and NIST standard P-384 elliptic curve
- **ES512** : ECDSA with SHA-512 and NIST standard P-521 elliptic curve

Default: **RS256**

"jwtExpirationTimeout": *configuration expression*<duration>, optional

The duration for which the JWT is valid.

Default: 1 minute

"claims": *map* or *configuration expression*<map>, optional

A map of one or more data pairs with the format `Map<String, Object>`, where:

- The key is the name of a claim used in authentication
- The value is the value of the claim, or a configuration expression that evaluates to the value

The following formats are allowed:

```
{
  "args": {
    "string": "configuration expression<string>",
    ...
  }
}
```

```
{
  "args": "configuration expression<map>"
}
```

Default: Empty

ResourceOwnerOAuth2ClientFilter



Important

This filter uses the *Resource Owner Password Credentials* grant type. According to information in the [The OAuth 2.0 Authorization Framework](#), minimize use of this grant type and utilize other grant types whenever possible. Use this filter in a service-to-service context, where services need to access resources protected by OAuth 2.0.

Authenticates OAuth 2.0 clients by using the resource owner's OAuth 2.0 credentials to obtain an access token from an Authorization Server, and injecting the access token into the inbound request as a Bearer Authorization header.

Client authentication is provided by the `endpointHandler` property, which uses a client authentication filter.

The ResourceOwnerOAuth2ClientFilter refreshes the access token as required.

For more information, refer to [RFC 6749 - Resource Owner Password Grant](#).

Usage

```
{
  "name": string,
  "type": "ResourceOwnerOAuth2ClientFilter",
  "config": {
    "username": configuration expression<string>,
    "passwordSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference,
    "tokenEndpoint": configuration expression<url>,
    "scopes": [ configuration expression<string>, ... ],
    "endpointHandler": Handler reference
  }
}
```

Properties

"username": configuration expression<string>, required

The resource owner username to supply during authentication.

"passwordSecretId": configuration expression<secret-id>, required

The secret ID to obtain the resource owner password.

This secret ID must point to a [GenericSecret](#).

"secretsProvider": SecretsProvider reference, required

The [SecretsProvider](#) to query for passwords and cryptographic keys.

"tokenEndpoint": configuration expression<url>, required

The URL to the Authorization Server's OAuth 2.0 token endpoint.

"scopes": array of configuration expression<strings>, optional

Array of scope strings to request from the Authorization Server.

Default: Empty, request no scopes.

"endpointHandler": Handler reference, optional

The Handler to exchange tokens on the authorization endpoint.

Configure this property as a [Chain](#), using one of the following client authentication filters:

- [ClientSecretBasicAuthenticationFilter](#)
- [ClientSecretPostAuthenticationFilter](#)
- [PrivateKeyJwtClientAuthenticationFilter](#)

```
{
  "name": "myHandler",
  "type": "Chain",
  "config": {
    "handler": "ForgeRockClientHandler",
    "filters": [
      {
        "type": "ClientSecretBasicAuthenticationFilter",
        "config": {
          "clientId": "myConfidentialClient",
          "clientSecretId": "my.client.secret.id",
          "secretsProvider": "mySystemAndEnvSecretStore",
        }
      }
    ]
  }
}
```

Default: ForgeRockClientHandler

Examples

For an example, refer to [Resource owner password credentials grant with PingAM](#).

More information

[org.forgerock.openig.filter.oauth2.client.ResourceOwnerOAuth2ClientFilterHeaplet](#) [↗](#)

[org.forgerock.openig.filter.oauth2.OAuth2ResourceServerFilterHeaplet](#) [↗](#)

[OAuth2ResourceServerFilter](#)

[The OAuth 2.0 Authorization Framework](#) [↗](#)

[The OAuth 2.0 Authorization Framework: Bearer Token Usage](#) [↗](#)

SamlFederationFilter

Initiates the login or logout of a SAML 2.0 Service Provider (SP) with a SAML 2.0 Identity Provider (IdP). Login is initiated for requests that don't:

- Trigger a logout expression
- Match a SAML endpoint
- Include a valid session

Requests with a valid session are passed along the chain.

SAML in deployments with multiple instances of PingGateway

When PingGateway acts as a SAML service provider, session information is stored in the fedlet not the session cookie. In deployments with multiple instances of PingGateway as a SAML service provider, it is necessary to set up sticky sessions so that requests always hit the instance where the SAML interaction was started.

For information, refer to [Session state considerations](#) in AM's *SAML v2.0 guide*.

Usage

```
{
  "name": string,
  "type": "SamlFederationFilter",
  "config": {
    "redirectURI": configuration expression<url>,
    "assertionMapping": map or configuration expression<map>,
    "subjectMapping": configuration expression<string>,
    "sessionIndexMapping": configuration expression<string>,
    "authnContext": configuration expression<string>,
    "authnContextDelimiter": configuration expression<string>,
    "assertionConsumerEndpoint": configuration expression<url>,
    "SPinitiatedSSOEndpoint": configuration expression<url>,
    "SPinitiatedSLOEndpoint": configuration expression<url>,
    "singleLogoutEndpoint": configuration expression<url>,
    "singleLogoutEndpointSoap": configuration expression<url>,
    "useOriginalUri": configuration expression<boolean>,
    "logoutExpression": runtime expression<boolean>,
    "logoutURI": configuration expression<url>,
    "redirectionMarker": {
      "enabled": configuration expression<boolean>,
      "name": configuration expression<string>
    },
    "secretsProvider": SecretsProvider reference,
    "spEntityId": configuration expression<string>,
    "idpEntityId": configuration expression<string>,
    "failureHandler": Handler reference
  }
}
```

Properties

redirectURI

"redirectURI" : *configuration expression<url>, required*

The URI to use if there is no RelayState value.

assertionMapping

"assertionMapping" : *map or configuration expression<map>, required*

A map with the format `Map<String, String>`, where:

- Key: Session name, `localName`
- Value: SAML assertion name, `incomingName`, or a configuration expression that evaluates to the name

The following formats are allowed:

```
{
  "assertionMapping": {
    "string": "configuration expression<string>",
    ...
  }
}
```

```
{
  "assertionMapping": "configuration expression<map>"
}
```

In the following example, the session names `username` and `password` map to SAML assertion names `mail` and `mailPassword`:

```
{
  "assertionMapping": {
    "username": "mail",
    "password": "mailPassword"
  }
}
```

If an incoming SAML assertion contains the following statement:

```
mail = demo@example.com
mailPassword = demopassword
```

Then the following values are set in the session:

```
username[0] = demo@example.com
password[0] = demopassword
```

For this to work, edit the `<Attribute name="attributeMap">` element in the SP extended metadata file, `$HOME/.openig/SAML/sp-extended.xml` so that it matches the assertion mapping configured in the SAML 2.0 Identity Provider (IdP) metadata.

Because the dot character (`.`) serves as a query separator in expressions, don't use dot characters in the `localName`.

To prevent different handlers from overwriting each other's data, use unique `localName` settings when protecting multiple service providers.

subjectMapping

`"subjectMapping"` : *configuration expression<string>, optional*

Name of the session field to hold the value of the subject name. Because the dot character (`.`) serves as a query separator in expressions, don't use dot characters in the field name.

Use this setting when protecting multiple service providers, as the different configurations must not map their data into the same fields of `session`. Otherwise, different handlers can overwrite each other's data.

As an example, if you set `"subjectMapping": "mySubjectName"`, PingGateway sets `session.mySubjectName` to the subject name specified in the assertion. If the subject name is an opaque identifier, this results in the session containing something like `"mySubjectName": "vt0...zuL"`.

Default: Map to `session.subjectName`

sessionIndexMapping

`"sessionIndexMapping": configuration expression<string>, optional`

Name of the session field to hold the value of the session index. Because the dot character (`.`) serves as a query separator in expressions, don't use dot characters in the field name.

Use this setting when protecting multiple service providers, as the different configurations must not map their data into the same fields of `session`. Otherwise, different handlers can overwrite each other's data.

As an example, if you set `"sessionIndexMapping": "mySessionIndex"`, PingGateway sets `session.mySessionIndex` to the session index specified in the assertion. This results in the session containing something like `"mySessionIndex": "s24c...801"`.

Default: Map to `session.sessionIndex`

authnContext

`"authnContext": configuration expression<string>, optional`

Name of the session field to hold the value of the authentication context. Because the dot character (`.`) serves as a query separator in expressions, don't use dot characters in the field name.

Use this setting when protecting multiple service providers, as the different configurations must not map their data into the same fields of `session`. Otherwise, different handlers can overwrite each other's data.

As an example, if you set `"authnContext": "myAuthnContext"`, PingGateway sets `session.myAuthnContext` to the authentication context specified in the assertion. When the authentication context is password over protected transport, this results in the session containing `"myAuthnContext": "urn:oasis:names:tc:SAML:2.0:ac:classes:PasswordProtectedTransport"`.

Default: Map to `session.authnContext`

authnContextDelimiter

`"authnContextDelimiter": configuration expression<string>, optional`

The authentication context delimiter used when there are multiple authentication contexts in the assertion.

Default: `|`

assertionConsumerEndpoint

`"assertionConsumerEndpoint": configuration expression<string>, optional`

Part of the URI that designates the consumer endpoint as defined in the SP metadata shared with the IdP.

If you modify this attribute, change the metadata to match.

Default: `fedletapplication`

SPInitiatedSSOEndpoint

`"SPInitiatedSSOEndpoint"` : *configuration expression*<string>, optional

Part of the URI that designates the SP initiated SSO endpoint.

If you modify this attribute, change the metadata to match.

Default: `SPInitiatedSSO`

SPInitiatedSLOEndpoint

`"SPInitiatedSLOEndpoint"` : *configuration expression*<string>, optional

Part of the URI that designates the SP initiated SLO endpoint.

If you modify this attribute, change the metadata to match.

Default: `SPInitiatedSLO`

singleLogoutEndpoint

`"singleLogoutEndpoint"` : *configuration expression*<string>, optional

Part of the URI that designates the SP SLO endpoint as defined in the SP metadata shared with the IdP.

If you modify this attribute, change the metadata to match.

Default: `fedletSLORedirect` (same as the Fedlet)

singleLogoutEndpointSoap

`"singleLogoutEndpointSoap"` : *configuration expression*<string>, optional

Part of the URI that designates the SP SLO SOAP endpoint as defined in the SPs metadata shared with the IdP.

If you modify this attribute, change the metadata to match.

Default: `fedletSloSoap` (same as the Fedlet)

useOriginalUri

`"useOriginalUri"` : *configuration expression*<boolean>, optional

When `true`, use the original URI instead of a rebased URI to validate RelayState and Assertion Consumer Location URLs. Use this property if a `baseUri` decorator is used in the route or in `config.json`.

Default: `true`

logoutExpression

`"logoutExpression"` : *runtime expression*<boolean>, optional

A flag to indicate whether a request initiates logout processing before reaching the protected application.

- **false** : The request doesn't initiate logout processing:
 - If a valid SAML session is found, the request is forwarded to the protected application.
 - If a valid SAML session is not found, the request triggers the SAML login flow.
- **true** : The request initiates logout processing:
 - If a valid SAML session is found, the request triggers the SAML logout flow:
 - If there is a RelayState URL parameter, the request is forwarded to that URL. RelayState provides backwards compatibility for SamlFederationHandler.
 - If there is no RelayState URL parameter and **logoutURI** is defined, the request is forwarded to the logout page.
 - If there is no RelayState URL parameter and **logoutURI** is not defined, the request is forwarded to the protected application without any other validation.
 - If a valid session is not found, the request is forwarded to the protected application without any other validation.



Important

To prevent unwanted access to the protected application, use **logoutExpression** with extreme caution as follows:

- Define a **logoutURI** .
- If you don't define a **logoutURI** , specify **logoutExpression** to resolve to **true only** for requests that target dedicated logout pages of the protected application.

Consider the following examples when a **logoutURI** is not defined:

- This expression resolves to **true only** for requests with `/app/logout` in their path:

```
"logoutExpression": "${startsWith(request.uri.rawPath, '/app/logout')}"
```

When a request matches the expression, the SAML session is revoked and the request is forwarded to the `/app/logout` page.

- This expression resolves to **true** for **all** requests that contain **logOff=true** in their query parameters:

```
"logoutExpression": "${find(request.uri.query, 'logOff=true')}"
```

When a request matches the expression, the SAML session is revoked and the request is forwarded to the protected application without any other validation. In this example, an attacker can bypass PingGateway's security mechanisms by adding `?logOff=true` to a request.

Default: `${false}`

logoutURI

"logoutURI": configuration expression<string>, optional

The URL to which a request is redirected if `logoutExpression` is evaluated as `true` or when the protected application uses the single logout feature of the Identity Provider.

Default: None, processing continues.

redirectionMarker

"redirectionMarker" : configuration expression<object>, optional

A redirect marker for the SAML flow. If the marker is present in the flow, the request isn't redirected for authentication.

This feature is on by default to prevent redirect loops when the session cookie isn't present in the SAML flow. The cookie can be absent from the flow if it doesn't include PingGateway's domain.

"enabled": configuration expression<boolean>, optional

- `true` : When the session is empty or invalid, PingGateway checks the request `goto` query parameter for the presence of the redirection marker:
 - If the redirection marker is present, PingGateway fails the request.
 - If the redirection marker isn't present, PingGateway redirects the user agent for login.
- `false`: PingGateway never checks the request `goto` query parameter for the presence of a redirection marker.

Default: `true`

"name": configuration expression<string>, optional

The name of the redirection marker query parameter to use when `enabled` is `true`.

Default: `_ig`

secretsProvider

"secretsProvider" : SecretsProvider [reference](#), optional

The [SecretsProvider](#) to query for keys when AM provides signed or encrypted SAML assertions.

When this property isn't set, the keys are provided by direct keystore lookups based on entries in the SP extended metadata file, `sp-extended.xml`.

spEntityId

"spEntityId" : configuration expression<string>, optional

The entity ID that this SP represents. Configure this property when more than one SP is defined in the metadata.

Default:

- When no SPs are defined in the metadata an error is generated.

- When one SP is defined in the metadata the filter uses that SP.
- When there is more than one SP defined in the metadata the filter uses the first SP in the list of discovered metadata and logs a warning. Because ordering is not deterministic, the discovered SP can be the wrong SP.

idpEntityId

`"idpEntityId"` : *configuration expression* `<string>`, optional

The entity ID this IdP represents. Configure this property when more than one IdP is defined in the metadata.

Default:

- When no IdPs are defined in the metadata an error is generated.
- When one IdP is defined in the metadata the filter uses that IdP.
- When there is more than one IdP defined in the metadata the filter uses the first IdP in the list of discovered metadata and logs a warning. Because ordering is not deterministic, the discovered IdP can be the wrong IdP.

failureHandler

`"failureHandler"` : *Handler* [reference](#), optional

[Handler](#) to invoke when SAML processing fails.

Provide an inline handler configuration object or the name of a handler object declared in the heap.

Default: Return an error response containing a SAML processing error.

ScriptableFilter

Processes requests and responses by executing a Groovy script. Executed scripts must return one of the following:

- [Promise<Response, NeverThrowsException>](#) 
- [Response](#) 

To execute the next element in a chain (a filter or a handler), the script must call the expression `next.handle(context, request)`. If the script doesn't call `next.handle(context, request)`, the chain flow breaks and the script has to build and return its own response by calling one of the following expressions:

- `return myResponse`
- `return newResultPromise(myResponse)`

Actions on the response returned from the downstream flow must be performed in the Promise's callback methods.

You can find more information about script properties, available global objects, and automatically imported classes in [PingGateway scripts](#). You can find more information about creating scriptable objects in Studio in [Scripts in Studio](#) and [Configure scriptable throttling](#).

Usage

```
{
  "name": string,
  "type": "ScriptableFilter",
  "config": {
    "type": configuration expression<string>,
    "file": configuration expression<string>, // Use either "file"
    "source": [ string, ... ],                // or "source", but not both.
    "args": map,
    "clientHandler": Handler reference
  }
}
```

Properties

You can find more information about properties for ScriptableFilter in [PingGateway scripts](#).

Examples

You can find an example scriptable filter that recovers policy advices from AM in the `failureHandler` property of [PolicyEnforcementFilter](#).

More information

[PingGateway scripts](#)

org.forgerock.openig.filter.ScriptableFilter 

SessionInfoFilter

Calls the AM endpoint for session information, and makes the data available as a new context to downstream PingGateway filters and handlers. Learn more in [SessionInfoContext](#).

Note

When using a SessionInfoFilter with a [CrossDomainSingleSignOnFilter](#) (CDSSO filter) or [SingleSignOnFilter](#) (SSO filter):

- Include the SessionInfoFilter *after* the CDSSO or SSO filter in the chain.
- Do *not* use the raw CDSSO or SSO token in the SessionInfoFilter configuration. Use the token the CDSSO or SSO filter adds to the context, such as `${contexts.ssoToken.value}` .

WebSocket notifications for sessions

When WebSocket notifications are set up for sessions, PingGateway receives a notification from AM when a user logs out of AM, or when the AM session is modified, closed, or times out. PingGateway then evicts entries that are related to the event from the `sessionCache` .

For information about setting up WebSocket notifications, using them to clear the session cache, and including them in the server logs, refer to [WebSocket notifications](#).

Usage

```
{
  "name": string,
  "type": "SessionInfoFilter",
  "config": {
    "amService": AmService reference,
    "ssoToken": runtime expression<string>
  }
}
```

Properties

"amService": *AmService* [reference](#), *required*

The [AmService](#) object to use for communication with AM.

The following `sessionProperties`, are retrieved from AM:

- When `sessionProperties` in AmService is configured, listed session properties with a value.
- When `sessionProperties` in AmService isn't configured, all session properties with a value.
- Properties with a value that are required by PingGateway but not specified by `sessionProperties` in AmService. For example, when the session cache is enabled, session properties related to the cache are automatically retrieved.

Properties with a value are returned, properties with a null value aren't returned.

"ssoToken": *runtime expression*<[string](#)>, *optional*

Location of the AM SSO or CDSSO token.

This property can take the following values:

- `${contexts.ssoToken.value}`, when the SingleSignOnFilter is used for authentication
- `${contexts.ssoToken.value}` or `${contexts.cdsso.token}`, when the CrossDomainSingleSignOnFilter is used for authentication
- `${request.headers['mySsoToken']}[0]}`, where the SSO or CDSSO token is the first value of the `mySsoToken` header in the request.

Default: `${request.cookies['AmService-ssoTokenHeader']}[0].value}`, where `AmService-ssoTokenHeader` is the name of the header or cookie where the AmService expects to find SSO or CDSSO tokens.

Examples

You can find an example that uses this filter in [Retrieve a Username From the sessionInfo Context](#).

More information

[org.forgerock.openig.openam.SessionInfoFilter](#) 

[org.forgerock.openig.openam.SessionInfoContext](#) 

SessionInfoContext

AM's [Authorization guide](#)

SetCookieUpdateFilter

Updates the attribute values of Set-Cookie headers in a cookie. This filter facilitates the transition to the SameSite and secure cookie settings required by newer browsers. Use SetCookieUpdateFilter at the beginning of a chain to guarantee security along the chain.

Set-Cookie headers must conform to grammar in [RFC 6265: Set-Cookie](#).

Usage

```
{
  "name": string,
  "type": "SetCookieUpdateFilter",
  "config": {
    "cookies": {
      "cookie-name": {
        "attribute-name": "attribute-value",
        ...
      }
      ...
    }
  }
}
```

Properties

"cookies": *map*, *required*

Configuration that matches case-sensitive cookie names to response cookies, and specifies how matching cookies attribute values should be updated. Each cookie begins with a name-value pair, where the value is one or more attribute-value pairs.

cookie-name: *pattern*, *required*

The name of a cookie contained in the `Set-Cookie` header, as a pattern.

To change the attribute value on all existing cookies, specify `.*`.

If a cookie is named more than once, either explicitly or by the wildcard (`*`), the rules are applied to the cookie in the order they appear in the map.

In the following example, the SameSite attribute of the CSRF cookie first takes the value `none`, and then that value is overwritten by the value `LAX`.

```

"cookies": {
  "CSRF": {
    "value": "myValue",
    "secure": ${true},
    "SameSite": "none"
  }
  ".*": {
    "SameSite": "LAX"
  }
}

```

attribute-name: *enumeration, required*

A case-insensitive enumeration of a Set-Cookie attribute name.

Attribute names include `SameSite`, `secure`, `http-only`, `value`, `expires`, `Max-Age`, `path`, and `domain`. For more information, refer to [RFC 6265: Set-Cookie](#).

Use the `now` [dynamic binding](#) to dynamically set the value of a cookie attribute that represents time. For example, set the value of the attribute `expires` to one day after the expression is evaluated, as follows:

```

{
  "type": "SetCookieUpdateFilter",
  "config": {
    "cookies": {
      ".*": {
        "expires": "${now.plusDays(1).rfc1123}",
        ...

```

attribute-value: *runtime expression<string, boolean, or integer>, required*

The replacement value for the named attribute. The value must conform to the expected type for the attribute name:

- `secure`: runtime expression<boolean>. Required if `SameSite` is `none`.
- `http-only`: runtime expression<boolean>.
- `Max-Age`: runtime expression<number>.
- `SameSite`, and all other attribute names: runtime expression<string>.

For all values except `expires`, specify `${previous}` to reuse the existing value for the attribute. The following example adds five seconds to the `Max-Age` attribute:

```

"Max-Age": "${integer(previous+5)}",

```

If the named the Set-Cookie header doesn't contain the named attribute, `${previous}` returns null.

Examples

The following example updates attributes of all existing Set-Cookie headers:


```
{
  "name": "SetCookieUpdateFilter",
  "condition": "${find(request.uri.path, '/home')}",
  "baseURI": "https://app.example.com:8444",
  "heap": [],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [{
        "type": "SetCookieUpdateFilter",
        "config": {
          "cookies": {
            ".*": {
              "SameSite": "LAX",
              "domain": "ig.example.com",
              "Max-Age": "${session.maxAge}",
              "Secure": "${true}",
              "expires": 155...833
            }
          }
        }
      }],
      "handler": "ReverseProxyHandler"
    }
  }
}
```

More information

[org.forgerock.openig.filter.SetCookieUpdateFilter](https://forgerock.org/openig/filter/SetCookieUpdateFilter)

SingleSignOnFilter

When this filter processes a request, it injects the SSO token, the session user ID, and the full claims set into the [SsoTokenContext](#).

You can find an example of how to configure SSO and information about the SSO data flow in [Single sign-on with PingAM](#).

Tip

To prevent issues with performance when accessing large resources, such as .jpg and .js files, consider using the SingleSignOnFilter with the following options:

- The `sessionCache`, so that PingGateway can reuse session token information without repeatedly asking AM to verify the session token.
- A ConditionalFilter, so that requests to access large resources skip the SingleSignOnFilter. For an example configuration, see the example in [ConditionalFilter](#).

Note

When AM is using CTS-based sessions, it doesn't monitor idle time for client-side sessions, and so refresh requests are ignored.

When the SingleSignOnFilter is used for authentication with AM, after a time AM can view the session as idle even though the user continues to interact with PingGateway. The user session can eventually time out.

When AM is using CTS-based sessions, use the `sessionIdleRefresh` property of `AmService` to refresh idle sessions, and prevent unwanted timeouts.

WebSocket notifications for sessions

When WebSocket notifications are set up for sessions, PingGateway receives a notification from AM when a user logs out of AM, or when the AM session is modified, closed, or times out. PingGateway then evicts entries that are related to the event from the `sessionCache`.

For information about setting up WebSocket notifications, using them to clear the session cache, and including them in the server logs, refer to [WebSocket notifications](#).

Usage

```
{
  "name": string,
  "type": "SingleSignOnFilter",
  "config": {
    "amService": AmService reference,
    "authenticationService": configuration expression<string>,
    "redirectionMarker": {
      "enabled": configuration expression<boolean>,
      "name": configuration expression<string>
    },
    "defaultLogoutLandingPage": configuration expression<url>,
    "loginEndpoint": runtime expression<url>,
    "logoutExpression": runtime expression<boolean>
  }
}
```

Properties

amService

"amService": *AmService* [reference](#), required

An [AmService](#) object to use for the following properties:

- `agent`: the credentials of the PingGateway agent in AM. When the agent is authenticated, PingGateway can use the token to get the user's profile, make policy evaluations, and connect to the AM notification endpoint.
- `realm`: Realm of the PingGateway agent in AM.
- `url`: the URL of an AM service to use for session token validation and authentication when `loginEndpoint` isn't specified.
- `ssoTokenHeader`: the name of the cookie that contains the session token created by AM.
- `amHandler`: the handler to use when communicating with AM to validate the token in the incoming request.

- `sessionCache` : the configuration of a cache for session information from AM.
- `version` : The version of the AM server.

The AM version is derived as follows, in order of precedence:

- Discovered value: The AmService discovers the AM version. If `version` is configured with a different value, the AmService ignores the value of `version` and logs a warning.
- Value in `version` : The AmService cannot discover the AM version and `version` is configured.
- Default value of AM 7.3: AmService cannot discover the AM version and `version` isn't configured.

authenticationService

`"authenticationService"` : *configuration expression<string>, optional*

The name of an AM authentication tree to use for authentication. Learn more in the AM documentation on [Authentication nodes and trees](#).

Default: AM's default authentication tree.

redirectionMarker

`redirectionMarker` : *object, optional*

A redirect marker for the SSO flow. If the marker is present in the SSO flow, the request isn't redirected for authentication.

This feature is on by default to prevent redirect loops when the session cookie isn't present in the SSO flow. The cookie can be absent from the flow if it doesn't include PingGateway's domain.

`"enabled"` : *configuration expression<boolean>, optional*

- `true` : When the session is empty or invalid, PingGateway checks the request `goto` query parameter for the presence of the redirection marker:
 - If the redirection marker is present, PingGateway fails the request.
 - If the redirection marker isn't present, PingGateway redirects the user agent for login.
- `false` : PingGateway never checks the request `goto` query parameter for the presence of a redirection marker.

Default: `true`

`"name"` : *configuration expression<string>, optional*

The name of the redirection marker query parameter to use when `enabled` is `true`.

Default: `_ig`

defaultLogoutLandingPage

`"defaultLogoutLandingPage"` : *configuration expression<url>, optional*

The URL to which a request is redirected if `logoutExpression` is evaluated as true.

If this property isn't an absolute URL, the request is redirected to the PingGateway domain name.

This parameter is effective only when `logoutExpression` is specified.

Default: None, processing continues.

loginEndpoint

`"loginEndpoint"` : runtime expression<[url](#)>, optional

The URL of a service instance for the following tasks:

- Manage authentication and the location to which the request is redirected after authentication.
- Process policy advices after an AM policy decision denies a request with supported advices. The `PolicyEnforcementFilter` redirects the request to this URL with information about how to meet the conditions in the advices.

PingGateway can perform authentication in the following ways:

- Directly through AM, with optional authentication parameters in the query string, such as `service` and `realm`. Learn more about authentication query parameters in the AM documentation on [authenticating browsers](#).

The value must include a redirect with a `goto` parameter.

The following example uses AM as the authentication service and includes the `service` authentication parameter:

```
"loginEndpoint": "https://am.example.com/openam?service=TwoFactor&goto=${urlEncodeQueryParameterNameOrValue(contexts.router.originalUri)}"
```

- Through the URL of another application with optional authentication parameters in the query string, such as `service` and `realm`. The application must create a session with AM to set an SSO token, and return the request to the redirect location.

The value can optionally include a redirect with a `goto` parameter or different parameter name.

The following example uses an authentication service that isn't AM and includes a redirect parameter:

```
"loginEndpoint": "https://authservice.example.com/auth?redirect=${urlEncodeQueryParameterNameOrValue(contexts.router.originalUri)}"
```

When using this option, review the cookie domains to make sure cookies set by the authentication server are properly conveyed to the PingGateway instance.

Learn more in [PolicyEnforcementFilter](#) and the AM [authorization documentation](#).

Default: The value of `url` in `amService`

logoutExpression

`"logoutExpression"` : runtime expression<[boolean](#)>, optional

A flag to indicate whether a request initiates logout processing before reaching the protected application.

- **false** : The request doesn't initiate logout processing:
 - If a valid AM session is found, the request is forwarded to the protected application.
 - If a valid AM session isn't found, the request triggers login.
- **true** : The request initiates logout processing:
 - If a valid AM session is found, the session is revoked and the request is forwarded as follows:
 - If `defaultLogoutLandingPage` is defined, the request is forwarded to the specified logout page.
 - If `defaultLogoutLandingPage` isn't defined, the request is forwarded to the protected application without any other validation.
 - If a valid session isn't found, the request is forwarded to the protected application without any other validation.

Important

To prevent unwanted access to the protected application, use `logoutExpression` with extreme caution as follows:

- Define a `defaultLogoutLandingPage`.
- If you don't define a `defaultLogoutLandingPage`, specify `logoutExpression` to resolve to **true only** for requests that target dedicated logout pages of the protected application.

Consider the following examples when a `defaultLogoutLandingPage` isn't configured:

- This expression resolves to **true only** for requests with `/app/logout` in their path:

```
"logoutExpression": ${startsWith(request.uri.rawPath, '/app/logout')}
```

When a request matches the expression, the AM session is revoked and the request is forwarded to the `/app/logout` page.

- This expression resolves to **true** for **all** requests that contain `logOff=true` in their query parameters:

```
"logoutExpression": ${find(request.uri.query, 'logOff=true')}
```

When a request matches the expression, the AM session is revoked and the request is forwarded to the protected application without any other validation. In this example, an attacker can bypass PingGateway's security mechanisms by adding `?logOff=true` to a request.

Default: `${false}`

More information

[org.forgerock.openig.openam.SingleSignOnFilter](#) 

[org.forgerock.openig.openam.SsoTokenContext](#) 

[SsoTokenContext](#)

SqlAttributesFilter

! Caution

This filter uses synchronous architecture by default. Accessing the filter `target` triggers a call to the database that blocks the executing thread until the database responds. Consider the performance impact of this filter, especially for deployments with a small number of gateway units (therefore, a small number of executing threads) and a long execution time for the JDBC call.

Executes an SQL query through a prepared statement and collects the first result. Parameters in the prepared statement are derived from expressions.

PingGateway populates the [SqlAttributesContext](#) and the optional `target` (deprecated) with key-value pairs from the query. If no matching row is found, the context and optional `target` are empty.

When the deprecated `target` setting is configured, PingGateway executes the query lazily on the first attempt to access its results. This defers the overhead of connection pool, network, and database query processing until a value is first required. PingGateway doesn't evaluate the `parameters` expression until the results are first accessed. PingGateway executes the query synchronously, potentially impacting performance.

When `target` isn't set, PingGateway executes the query asynchronously when calling this filter. In this case, place this filter immediately before the entity reading the data from the context.

Usage

```
{
  "name": string,
  "type": "SqlAttributesFilter",
  "config": {
    "dataSource": JdbcDataSource reference,
    "preparedStatement": configuration expression<string>,
    "parameters": [ runtime expression<string>, ... ],
    "target": lvalue-expression, // deprecated
    "executorService": ScheduledExectutorService reference
  }
}
```

Properties

"dataSource": *JdbcDataSource* [reference](#), required

The JdbcDataSource to use for connections. Configure JdbcDataSource as described in [JdbcDataSource](#).

"preparedStatement": *configuration expression<string>*, required

The parameterized SQL query to execute, with `?` parameter placeholders.

"parameters": *array of runtime expressions<strings>*, optional

The parameters to evaluate and include in the execution of the prepared statement.

Learn more in [PingGateway expressions](#).

"target": *<value-expression>, optional*



Important

This property is deprecated. Use the [SqlAttributesContext](#) instead. For more information, refer to the [Deprecated](#) section of the *Release Notes*.

Expression that yields the target object containing the query results; for example, `${target.sql.queryresult}`.

Access to `target` triggers a call to the database that blocks the executing thread until the database responds.

Also refer to [Expressions](#).

"executorService": *ScheduledExecutorService reference, optional*

A [ScheduledExecutorService](#) to execute the query.

Default: The default `ScheduledExecutorService` in the heap

Example

Using the user's session ID from a cookie, query the database to find the user and set the profile attributes in the `SqlAttributesContext`:

```
{
  "name": "SqlAttributesFilter",
  "type": "SqlAttributesFilter",
  "config": {
    "dataSource": "java:comp/env/jdbc/mysql",
    "preparedStatement": "SELECT f.value AS 'first', l.value AS 'last', u.mail AS 'email',
GROUP_CONCAT(CAST(r.rid AS CHAR)) AS 'roles' FROM sessions s INNER JOIN users u ON ( u.uid = s.uid AND u.status = 1 )
LEFT OUTER JOIN profile_values f ON ( f.uid = u.uid AND f.fid = 1 ) LEFT OUTER JOIN profile_values l ON ( l.uid =
u.uid AND l.fid = 2 ) LEFT OUTER JOIN users_roles r ON ( r.uid = u.uid ) WHERE (s.sid = ? AND s.uid <> 0) GROUP BY
s.sid;",
    "parameters": [ "${request.cookies[keyMatch(request.cookies, 'JSESSION1234')][0].value}" ]
  }
}
```

Lines are folded for readability in this example. In your JSON, keep the values for `"preparedStatement"` and `"parameters"` on one line.

More information

org.forgerock.openig.sql.SqlAttributesFilter

StaticRequestFilter

Creates a new request, replacing any existing request. The request can include an entity specified in the `entity` parameter. Alternatively, the request can include a form, specified in the `form` parameter, which is included in an entity encoded in `application/x-www-form-urlencoded` format if request method is `POST`, or otherwise as (additional) query parameters in the URI. The `form` and `entity` parameters cannot be used together when the `method` is set to `POST`.

Usage

```
{
  "name": string,
  "type": "StaticRequestFilter",
  "config": {
    "method": configuration expression<string>,
    "uri": runtime expression<url>,
    "version": configuration expression<string>,
    "headers": {
      configuration expression<string>: [ runtime expression<string>, ... ], ...
    },
    "form": {
      configuration expression<string>: [ runtime expression<string>, ... ], ...
    },
    "entity": runtime expression<string>
  }
}
```

Properties

"method": *configuration expression*<string>, *required*

The HTTP method to be performed on the resource; for example, `GET`.

"uri": *runtime expression*<url>, *required*

The fully-qualified URI of the resource being accessed; for example, `https://www.example.com/resource.txt`.

The result of the expression must be a string that represents a valid URI, but isn't a real `java.net.URI` object. For example, it would be incorrect to use `${request.uri}`, which is not a string but a mutable URI.

"version": *configuration expression*<string>, *optional*

Protocol version.

Default: `"HTTP/1.1"`

"headers": *map*, *optional*

One or more headers to set for a request, with the format `name: [ value, ... ]`, where:

- *name* is a configuration expression<string> that resolve to a header name. If multiple expressions resolve to the same final string, *name* has multiple values.
- *value* is one or more runtime expression<strings> that resolve to header values.

In the following example, the header name is the value of the system variable defined in `cookieHeaderName`. The header value is stored in `contexts.ssoToken.value`:


```
"headers": {
  "${application['header1Name']}": [
    "${application['header1Value']}"
  ]
}
```

Default: Empty

"form": *map, optional*

A form to include in the request and/or `application/x-www-form-urlencoded` entity, as name-value pairs, where:

- *name* is a configuration expression<string> that resolves to a form parameter name.
- *value* is one or more runtime expression<strings> that resolve to form parameter values.

When a Request `method` is `POST`, `form` is mutually exclusive with `entity`.

Examples:

- In the following example, the field parameter names and values are hardcoded in the form:

```
"form": {
  "username": [
    "demo"
  ],
  "password": [
    "password"
  ]
}
```

- In the following example, the values take the first value of `username` and `password` provided in the session:

```
"form": {
  "username": [
    "${session.username[0]}"
  ],
  "password": [
    "${session.password[0]}"
  ]
}
```

- In the following example, the name of the first field parameter takes the value of the expression `${application['formName']}` when it is evaluated at startup. The values take the first value of `username` and `password` provided in the session:

```
"form": {
  "${application['formName']}": [
    "${session.username[0]}"
  ],
  "${application['formPassword']}": [
    "${session.password[0]}"
  ]
}
```

Default: Empty

"entity": runtime expression<string>, optional

The message entity body to include in a request.

When a Request `method` is `POST`, `entity` is mutually exclusive with `form`.

Methods are provided for accessing the entity as byte, string, or JSON content. Learn more in [Entity](#).



Important

Attackers during reconnaissance can use messages to identify information about a deployment. For security, limit the amount of information in messages, and avoid using words that help identify PingGateway.

Default: Empty

Example

In the following example, PingGateway replaces the browser's original HTTP GET request with an HTTP POST login request containing credentials to authenticate to the sample application. You can find more information about how to set up and test this example in [Getting started with PingGateway](#).

```
{
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "StaticRequestFilter",
          "config": {
            "method": "POST",
            "uri": "http://app.example.com:8081/login",
            "form": {
              "username": [
                "demo"
              ],
              "password": [
                "Ch4ng31t"
              ]
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  },
  "condition": "${find(request.uri.path, '^/static')}"
}
```

Source: [01-static.json](#)

SwitchFilter

Verifies that a specified condition is met. If the condition is met or no condition is specified, the request is diverted to the associated handler, with no further processing by the switch filter.

Usage

```
{
  "name": string,
  "type": "SwitchFilter",
  "config": {
    "onRequest": [
      {
        "condition": runtime expression<boolean>,
        "handler": Handler reference
      },
      ...
    ],
    "onResponse": [
      {
        "condition": runtime expression<boolean>,
        "handler": Handler reference
      },
      ...
    ]
  }
}
```

Properties

"onRequest": array of *objects*, optional

Conditions to test (and handler to dispatch to, if `true`) before the request is handled.

"onResponse": array of *objects*, optional

Conditions to test (and handler to dispatch to, if `true`) after the response is handled.

"condition": runtime expression<*boolean*>, optional

A flag to indicate that a condition is met:

- `true`: The request is dispatched to the handler.
- `false`: The request is not dispatched to the handler, and the next condition in the list is tried.

When the last condition in the list returns `false`, the request is passed to the next filter or handler in the chain.

Default: `${true}`

"handler": *Handler reference*, required

The [Handler](#) to which PingGateway dispatches the request if the associated condition yields `true`.

Provide the name of a Handler object defined in the heap or an inline Handler configuration object.

Example

This example intercepts the response if it is equal to 200 and executes the `LoginRequestHandler`. This filter might be used in a login flow where the request for the login page must go through to the target, but the response should be intercepted in order to send the login form to the application. This is typical for scenarios where there is a hidden value or cookie returned in the login page, which must be sent in the login form:

```
{
  "name": "SwitchFilter",
  "type": "SwitchFilter",
  "config": {
    "onResponse": [
      {
        "condition": "${response.status.code == 200}",
        "handler": "LoginRequestHandler"
      }
    ]
  }
}
```

ThrottlingFilter

Limits the rate that requests pass through a filter. The maximum number of requests that a client is allowed to make in a defined time is called the *throttling rate*.

When the throttling rate is reached, PingGateway issues an HTTP status code 429 `Too Many Requests` and a `Retry-After` header, whose value is rounded up to the number of seconds to wait before trying the request again.

```
GET https://ig.example.com:8443/home/throttle-scriptable HTTP/1.1
...
HTTP/1.1 429 Too Many Requests
Retry-After: 10
```

Usage

```
{
  "name": string,
  "type": "ThrottlingFilter",
  "config": {
    "requestGroupingPolicy": runtime expression<string>,
    "throttlingRatePolicy": ThrottlingPolicy reference, //Use either "throttlingRatePolicy"
    "rate": {                                           //or "rate", but not both.
      "numberOfRequests": configuration expression<number>,
      "duration": configuration expression<duration>
    },
    "cleaningInterval": configuration expression<duration>,
    "executor": ScheduledExecutorService reference
  }
}
```

Properties

"requestGroupingPolicy": *runtime expression*<string>, optional

An expression to identify the partition to use for the request. In many cases the partition identifies an individual client that sends requests, but it can also identify a group that sends requests. The expression can evaluate to the client IP address or user ID, or an OpenID Connect subject/issuer.

The value for this expression must not be null.

Default: Empty string; all requests share the same partition

Learn more in [PingGateway expressions](#).

"throttlingRatePolicy": *ThrottlingPolicy* [reference](#), required if rate isn't used

A reference to, or inline declaration of, a policy to apply for throttling rate. The following policies can be used:

- [MappedThrottlingPolicy](#)
- [ScriptableThrottlingPolicy](#)
- [DefaultRateThrottlingPolicy](#)

This value for this parameter must not be null.

"rate": *object*, required if throttlingRatePolicy isn't used

The throttling rate to apply to requests. The rate is calculated as the number of requests divided by the duration:

"numberOfRequests": *configuration expression*<integer>, required

The number of requests allowed through the filter in the time specified by "duration".

"duration": *configuration expression*<duration>, required

A time interval during which the number of requests passing through the filter is counted.

"cleaningInterval": *configuration expression*<duration>, optional

The time to wait before cleaning outdated partitions. The value must be more than zero but not more than one day.

"executor": *ScheduledExecutorService* [reference](#), optional

An executor service to schedule the execution of tasks, such as the clean up of partitions that are no longer used.

Default: `ScheduledExecutorService`

Learn more in [ScheduledExecutorService](#).

Examples

- [Example of a mapped throttling policy](#)
- [Example of a scriptable throttling policy](#)

The following route defines a throttling rate of 6 requests/10 seconds to requests. You can find more information about how to set up and test this example in [Configure simple throttling](#).

```
{
  "name": "00-throttle-simple",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/throttle-simple')}",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "ThrottlingFilter",
          "name": "ThrottlingFilter-1",
          "config": {
            "requestGroupingPolicy": "",
            "rate": {
              "numberOfRequests": 6,
              "duration": "10 s"
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}
```

Source: [00-throttle-simple.json](#)

More information

[org.forgerock.openig.filter.throttling.ThrottlingFilterHeaplet](#)

TokenTransformationFilter

Transforms a token issued by AM to another token type.

The TokenTransformationFilter makes the result of the token transformation available to downstream handlers in the `sts` context. Learn more in [StsContext](#).

The current implementation uses REST Security Token Service (STS) APIs to transform an OpenID Connect ID Token (`id_token`) into a SAML 2.0 assertion. The subject confirmation method is Bearer, as described in [Profiles for the OASIS Security Assertion Markup Language \(SAML\) V2.0](#).

The TokenTransformationFilter makes the result of the token transformation available to downstream handlers in the `issuedToken` property of the `${contexts.sts}` context.

The TokenTransformationFilter configuration references a REST STS instance that must be set up in AM before the TokenTransformationFilter can be used. The REST STS instance exposes a preconfigured transformation under a specific REST endpoint.

Errors that occur during the token transformation cause a error response to be returned to the client and an error message to be logged for the PingGateway administrator.

Usage

```
{
  "name": "string",
  "type": "TokenTransformationFilter",
  "config": {
    "amService": AmService reference,
    "idToken": runtime expression<string>,
    "instance": configuration expression<string>,
    "username": configuration expression<string>, //deprecated
    "password": configuration expression<string> //deprecated
  }
}
```

Properties

"amService": *AmService* [reference](#), *required*

The [AmService](#) heap object to use for the following properties:

- **agent**, the credentials of the PingGateway agent in AM, to authenticate PingGateway as an AM REST STS client, and to communicate WebSocket notifications from AM to PingGateway. This credentials are evaluated when the route is initialized
- **url**, the URL of an AM service to use for session token validation and authentication. Authentication and REST STS requests are made to this service.
- **realm**, the AM realm containing the following information:
 - The AM application that can make the REST STS request and whose credentials are the username and password.
 - The STS instance described by the instance field.
- **ssoTokenHeader**, the name of the HTTP header that provides the SSO token for the REST STS client subject.
- **amHandler**, the handler to use for authentication and STS requests to AM.

"idToken": *runtime expression*<[string](#)>, *required*

The value of the OpenID Connect ID token. The expected value is a string that is the JWT encoded `id_token`.

"instance": *configuration expression*<[string](#)>, *required*

An expression evaluating to the name of the REST STS instance.

This expression is evaluated when the route is initialized, so the expression cannot refer to `request` or `contexts`.

"username": *string*, *required*



Important

The use of this property is deprecated. Use the AmService property agent instead.

The username to authenticate PingGateway as an AM REST STS client.

"password": *expression, required***Important**

The use of this property is deprecated. Use the AmService property agent instead.

The password to authenticate PingGateway as an AM REST STS client.

Example

The following example shows a configuration for a TokenTransformationFilter:

```
{
  "type": "TokenTransformationFilter",
  "config": {
    "amService": "MyAmService",
    "idToken": "${attributes.openid.id_token}",
    "instance": "openid"
  }
}
```

You can find an example of how to set up and test the TokenTransformationFilter in [OIDC ID tokens to SAML assertions with PingAM](#).

More information

[org.forgerock.openig.openam.TokenTransformationFilter](#)

[org.forgerock.openig.openam.StsContext](#)

[StsContext](#)

TransactionIdOutboundFilter

Inserts the ID of a transaction into the header of a request.

The default TransactionIdOutboundFilter is created by PingGateway, and used in [ForgeRockClientHandler](#), as follows:

```
{
  "name": "ForgeRockClientHandler",
  "type": "ForgeRockClientHandler",
  "config": {
    "filters": [ "TransactionIdOutboundFilter" ],
    "handler": "ClientHandler"
  }
}
```

More information

[org.forgerock.http.filter.TransactionIdOutboundFilter](#)

UmaFilter

This filter acts as a policy enforcement point, protecting access as a User-Managed Access (UMA) resource server. Specifically, this filter ensures that a request for protected resources includes a valid requesting party token with appropriate scopes before allowing the response to flow back to the requesting party.

Usage

```
{
  "name": string,
  "type": "UmaFilter",
  "config": {
    "protectionApiHandler": Handler reference,
    "umaService": UmaService reference,
    "realm": configuration expression<string>
  }
}
```

Properties

"protectionApiHandler": *Handler* [reference](#), *required*

The handler to use when interacting with the UMA Authorization Server for token introspection and permission requests, such as a ClientHandler capable of making an HTTPS connection to the server.

Learn more in [PingGateway handlers](#).

"umaService": *UmaService* [reference](#), *required*

The UmaService to use when protecting resources.

Learn more in [UmaService](#).

"realm": *configuration expression*<[string](#)>, *optional*

The UMA realm set in the response to a request for a protected resource that doesn't include a requesting party token enabling access to the resource.

Default: `uma`

More information

[User-Managed Access \(UMA\) Profile of OAuth 2.0](#) 

[org.forgerock.openig.uma.UmaResourceServerFilter](#) 

UriPathRewriteFilter

Rewrite a URL path, using a bidirectional mapping:

- In the request flow, `fromPath` is mapped to `toPath`.

- In the response flow, `toPath` is mapped to `fromPath`.

PingGateway overwrites a response header only when all of the following conditions are true:

- The response includes a header such as `Location` or `Content-Location`
- The URI of the response header matches the mapping
- The value of response header is a relative path or its `scheme://host:port` value matches the base URI.

Usage

```
{
  "name": string,
  "type": "UriPathRewriteFilter",
  "config": {
    "mappings": object,
    "failureHandler": Handler reference
  }
}
```

Properties

"mappings": *object, required*

One or more bidirectional mappings between URL paths. You can find example mappings, request scenarios, and an example route in [Examples](#).

```
{
  "mappings": {
    "/fromPath1": "/toPath1",
    "/fromPath2": "/toPath2",
    ...
  }
}
```

Paths are given by a `configuration expression<string>`. Consider the following points when you define paths:

- The incoming URL must start with the mapping path.
- When more than one mapping applies to a URL, the most specific mapping is used.
- Duplicate `fromPath` values are removed without warning.
- Trailing slashes `/` are removed from path values.
- If the response includes a `Location` or `Content-Location` header with a `toPath` in its URL, the response is rewritten with `fromPath`.

"failureHandler": *handler reference, optional*

Failure handler to be invoked if an invalid URL is produced when the request path is mapped, or when the response `Location` or `Content-Location` header URI path is reverse-mapped.

Provide an inline handler declaration, or the name of a handler object defined in the heap. See also [PingGateway handlers](#).

Default: HTTP 500

Examples

Valid and invalid mapping examples

The following mapping examples are valid:

- Single `fromPath` and `toPath`

```
"mappings": {  
  "/fromPath1": "/toPath1",  
  "/fromPath2": "/toPath2"  
}
```

- Expressions in the `fromPath` and `toPath`

```
"mappings": {  
  "/${join(array(`fromPath`, 'path1'), `/`)}": "/${join(array(`toPath`, 'path2'), `/`)}"  
}
```

- Expressions in the `fromPath` and `toPath` that use predefined heap properties

```
"mappings": {  
  "${fromPath}": "${toPath}"  
}
```

- No mappings—the configuration is valid, but has no effect

```
"mappings": { }
```

- Duplicate `toPath`

```
"mappings": {  
  "/fromPath1": "/toPath",  
  "/fromPath2": "/toPath"  
}
```

- Duplicate `fromPath`—the configuration is overwritten without warning

```
"mappings": {  
  "/fromPath": "/toPath1",  
  "/fromPath": "/toPath2"  
}
```

The following mapping examples aren't valid

- No **toPath**

```
"mappings": {  
  "/fromPath": ""  
}
```

```
"mappings": {  
  "/fromPath": "${unknown}"  
}
```

- Invalid **toPath**

```
"mappings": {  
  "/fromPath": "${invalidExpression}"  
}
```

- No **fromPath**

```
"mappings": {  
  "": "/toPath"  
}
```

```
"mappings": {  
  "${unknown}": "/toPath"  
}
```

- Invalid **fromPath**

```
"mappings": {  
  "${invalidExpression}": "/toPath"  
}
```

Example request scenarios

Description	Mapping	Inbound URI	Rewritten URI
Basic path	<pre>"mappings": { "/fromPath": "/toPath" }</pre>	https://example.com/ fromPath/remainder	https://example.com/ toPath/remainder
Root context, where the inbound request URI has a / path segment	<pre>"mappings": { "/": "/rootcontext" }</pre>	https://example.com/	https://example.com/ rootcontext/
Root context, where the inbound URI has a / path segment	<pre>"mappings": { "/rootcontext": "/" }</pre>	https://example.com/ rootcontext/	https://example.com/
Root context, where the inbound request URI has an empty path	<pre>"mappings": { "/": "/rootcontext" }</pre>	https://example.com	https://example.com/ rootcontext
Root context, where the rewritten URI has an empty path	<pre>"mappings": { "/rootcontext": "/" }</pre>	https://example.com/ rootcontext	https://example.com
Root context, with path remainder	<pre>"mappings": { "/": "/rootcontext" }</pre>	https://example.com/ remainder	https://example.com/ rootcontext/remainder
Root context, with path remainder	<pre>"mappings": { "/rootcontext": "/" }</pre>	https://example.com/ rootcontext/remainder	https://example.com/ remainder
Root context, where the trailing / on toPath is ignored	<pre>"mappings": { "/": "/rootcontext/" }</pre>	https://example.com/ remainder	https://example.com/ rootcontext/remainder

Description	Mapping	Inbound URI	Rewritten URI
Path with dot-segments:	<pre>"mappings": { "/fromPath": "/toPath1/../ toPath2" }</pre>	https://example.com/ fromPath	https://example.com/ toPath1/../toPath2
Path with syntax:	<pre>"mappings": { "/fromPath;v=1.1": "/toPath, 1.1" }</pre>	https://example.com/ fromPath;v=1.1	https://example.com/ toPath,1.1
Path with syntax:	<pre>"mappings": { "/\$fromPath": "/\$toPath" }</pre>	https://example.com/ \$fromPath	https://example.com/ \$toPath
Path with query parameters	<pre>"mappings": { "/fromPath": "/toPath" }</pre>	https://example.com/ fromPath? param1&param2=2	https://example.com/ toPath? param1&param2=2
Path with fragment	<pre>"mappings": { "/fromPath": "/toPath" }</pre>	https://example.com/ fromPath#fragment	https://example.com/ toPath#fragment

Example route

The example route changes a request URL as follows:

- The `baseURI` overrides the scheme, host, and port of a request URL.
- The `UriPathRewriteFilter` remaps the path of a request URL.

Requests to `https://ig.example.com:8443/mylogin` are mapped to `https://app.example.com:8444/login`.

Requests to `https://ig.example.com:8443/welcome` are mapped to `https://app.example.com:8444/home`.

Requests to `https://ig.example.com:8443/other` are mapped to `https://app.example.com:8444/not-found`, and result in an HTTP 404.

Requests to `https://ig.example.com:8443/badurl` are mapped to the invalid URL `https://app.example.com:8444[`, and invoke the failure handler.

```

{
  "name": "UriPathRewriteFilter",
  "baseURI": "https://app.example.com:8444",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "UriPathRewriteFilter",
          "config": {
            "mappings": {
              "/mylogin": "/login",
              "/welcome": "/home",
              "/other": "/not-found",
              "/badurl": "["
            },
            "failureHandler": {
              "type": "StaticResponseHandler",
              "config": {
                "status": 500,
                "headers": {
                  "Content-Type": [
                    "text/plain"
                  ]
                },
              },
              "entity": "Invalid URL produced"
            }
          }
        }
      ]
    },
    "handler": {
      "type": "ClientHandler",
      "config": {
        "tls": {
          "type": "ClientTlsOptions",
          "comment": "Blindly trust the gateway certificate",
          "config": {
            "trustManager": {
              "type": "TrustAllManager"
            },
            "hostnameVerifier": "ALLOW_ALL"
          }
        }
      }
    }
  }
}

```

Source: [UriPathRewriteFilter.json](#)

More information

[org.forgerock.openig.filter.UriPathRewriteFilter](#)

[RFC 3986: Path](#)

UserProfileFilter

Queries AM to retrieve the profile attributes of an user identified by their `username`.

Only profile attributes that are enabled in AM can be returned by the query. The `roles` field isn't returned.

The data is made available to downstream PingGateway filters and handlers, in the context [UserProfileContext](#).

Usage

```
{
  "name": string,
  "type": "UserProfileFilter",
  "config": {
    "username": runtime expression<string>,
    "userProfileService": UserProfileService reference
  }
}
```

Properties

"username": *runtime expression<string>*, required

The username of an AM subject. This filter retrieves profile attributes for the subject.

"userProfileService": *UserProfileService reference*, required

The service to retrieve profile attributes from AM, for the subject identified by `username`.

```
"userProfileService": {
  "type": "UserProfileService",
  "config": {
    "amService": AmService reference,
    "cache": object,
    "profileAttributes": [ configuration expression<string>, ... ],
    "realm": configuration expression<string>
  }
}
```

"amService": *AmService reference*, required

The AmService heap object to use for the following properties:

- `agent`, the credentials of the PingGateway agent in AM. When the agent is authenticated, the token can be used for tasks such as getting the user's profile, making policy evaluations, and connecting to the AM notification endpoint.
 - `url`: URL of the AM server where the user is authenticated.
 - `amHandler`: Handler to use when communicating with AM to fetch the requested user's profile.
- `realm`: Realm of the PingGateway agent in AM.
- `version`: The version of the AM server.

The AM version is derived as follows, in order of precedence:

- Discovered value: AmService discovers the AM version. If `version` is configured with a different value, AmService ignores the value of `version` and issues a warning.
- Value in `version`: AmService cannot discover the AM version, and `version` is configured.
- Default value of AM 7.3: AmService cannot discover the AM version, and `version` is not configured.

"cache": *object*, optional

Caching of AM user profiles, based on *Caffeine*. For more information, see the GitHub entry, [Caffeine](#).

When caching is enabled, PingGateway can reuse cached profile attributes without repeatedly querying AM. When caching is disabled, PingGateway must query AM for each request, to retrieve the required user profile attributes.

Default: No cache.

```
"cache": {
  "enabled": configuration expression<boolean>,
  "executor": Executor reference,
  "maximumSize": configuration expression<number>,
  "maximumTimeToCache": configuration expression<duration>,
}
```

enabled: *configuration expression*<*boolean*>, optional

Enable or disable caching of user profiles. When `false`, the cache is disabled but the cache configuration is maintained.

Default: `true` when `cache` is configured

executor: *Executor reference*, optional

An executor service to schedule the execution of tasks, such as the eviction of entries in the cache.

Default: `ForkJoinPool.commonPool()`

"maximumSize": *configuration expression*<*number*>, optional

The maximum number of entries the cache can contain.

Default: Unlimited/unbound

maximumTimeToCache: *configuration expression*<*duration*>, required

The maximum duration for which to cache user profiles.

The duration cannot be `zero`.

profileAttributes: *array of configuration expression*<*strings*>, optional

List of one or more fields to return and store in UserProfileContext.

Field names are defined by the underlying repository in AM. When AM is installed with the default configuration, the repository is PingDS.

The following convenience accessors are provided for commonly used fields:

- `cn`: Retrieved through `${contexts.userProfile.commonName}`
- `dn`: Retrieved through `${contexts.userProfile.distinguishedName}`
- `realm`: Retrieved through `${contexts.userProfile.realm}`
- `username`: Retrieved through `${contexts.userProfile.username}`

All other available fields can be retrieved through `${contexts.userProfile.rawInfo}` and `${contexts.userProfile.asJsonValue()}`.

When `profileAttributes` is configured, the specified fields **and** the following fields are returned: `username`, `_id`, and `_rev`.

Default: All available fields are returned.

"realm": *configuration expression*<string>, optional

The AM realm where the subject is authenticated.

Default: The realm declared for `amService`.

Example

For examples that use the `UserProfileFilter`, see [Pass profile data downstream](#).

More information

[org.forgerock.openig.openam.UserProfileFilter](#) 

[org.forgerock.openig.tools.userprofile.UserProfileService](#) 

[org.forgerock.openig.openam.UserProfileContext](#) 

[UserProfileContext](#)

AM's [Authorization guide](#) 

PingGateway decorators

Decorators are heap objects to extend what other objects can do. PingGateway defines default `baseURI`, `capture`, `timer`, and `tracing` decorators you can use without explicitly defining them.

For more information, refer to [PingGateway decorators](#).

- [BaseUriDecorator](#)
- [CaptureDecorator](#)
- [TimerDecorator](#)
- [TracingDecorator](#)

BaseUriDecorator

Overrides the scheme, host, and port of the existing request URI, rebasing the URI and so making requests relative to a new base URI. Rebasing changes only the scheme, host, and port of the request URI. Rebasing doesn't affect the path, query string, or fragment.

Decorator Usage

```
{
  "name": string,
  "type": "BaseUriDecorator"
}
```

A BaseUriDecorator doesn't have configurable properties.

PingGateway creates a default BaseUriDecorator named baseURI at startup time in the top-level heap, so you can use baseURI as the decorator name without adding the decorator declaration

Decorated Object Usage

```
{
  "name": string,
  "type": string,
  "config": object,
  decorator name: runtime expression<url>
}
```

"name": *string*, required except for inline objects

The unique name of the object, just like an object that isn't decorated.

"type": *<string>*, required

The class name of the decorated object, which must be either a [PingGateway filters](#) or a [PingGateway handlers](#).

"config": *object* required unless empty

The configuration of the object, just like an object that isn't decorated

decorator name: runtime expression<url>, required

The scheme, host, and port of the new base URI. The port is optional when using the defaults (80 for HTTP, 443 for HTTPS).

The value of the string must not contain underscores, and must conform to the syntax specified in [RFC 3986](#).

Examples

Add a custom decorator to the heap named myBaseUri:

```
{
  "name": "myBaseUri",
  "type": "BaseUriDecorator"
}
```

Set a Router's base URI to <https://www.example.com:8443>:

```
{
  "name": "Router",
  "type": "Router",
  "myBaseUri": "https://www.example.com:8443/"
}
```

More information

[org.forgerock.openig.decoration.baseuri.BaseUriDecorator](#)

CaptureDecorator

Captures request and response messages in SLF4J logs, named in this format:

```
org.forgerock.openig.decoration.capture.CaptureDecorator.<decoratorName>.<decoratedObjectName>
```

If the decorated object isn't named, the object path is used in the log.

Important

During debugging, consider using a CaptureDecorator to capture the entity and context of requests and responses. However, increased logging consumes resources, such as disk space, and can cause performance issues. In production, reduce logging by disabling the CaptureDecorator properties `captureEntity` and `captureContext`, or setting `maxEntityLength`.

You can find more information about using default or custom logging in [Managing PingGateway logs](#).

Decorator Usage

```
{
  "name": string,
  "type": "CaptureDecorator",
  "config": {
    "captureEntity": configuration expression<boolean>,
    "captureContext": configuration expression<boolean>,
    "maxEntityLength": configuration expression<number>,
    "masks": object
  }
}
```

"captureEntity": configuration expression<boolean>, optional

A flag for capture of the message entity:

- **true** : Capture the request and response message entity and write it to the logs. The message entity is the body of the HTTP message, which can be a JSON document, XML, HTML, image, or other information.

When the message is binary, PingGateway writes a `[binary entity]` .

When streaming is enabled in `admin.json`, the decorator interrupts streaming for the captured request or response until the whole entity is captured.

- **false** : Don't capture the message entity.

If the `Content-Type` header is set for a request or response, the decorator uses it to decode the request or response messages, and then writes them to the logs. If the `Content-Type` header isn't set, the decorator doesn't write the request or response messages to the logs.

Default: `false`

"captureContext": configuration expression<boolean>, optional

A flag for capture of contextual data about the handled request, such as client, session, authentication identity, authorization identity, or any other state information associated with the request:

- **true** : Capture contextual data about the handled request.

The context is captured as JSON. The context chain is used when processing the request inside PingGateway in the filters and handlers.

- **false** : Don't capture contextual data about the handled request.

Default: `false`

"maxEntityLength": configuration expression<number>, optional

The maximum number of bytes that can be captured for an entity. This property is used when `captureEntity` is `true` .

If the captured entity is bigger than `maxEntityLength` , everything up to `maxEntityLength` is captured, and an `[entity truncated]` message is written in the log.

Set `maxEntityLength` to be big enough to allow capture of normal entities, but small enough to prevent excessive memory use or `OutOfMemoryError` errors. Setting `maxEntityLength` to 2 GB or more causes an exception at startup.

Default: 524 288 bytes (512 KB)

"masks": object, optional

The configuration to mask the values of headers and attributes in the logs.

```
{
  "masks": {
    "headers": [ pattern, ... ],
    "trailers": [ pattern, ... ]
    "attributes": [ pattern, ... ]
    "mask": [ configuration expression<string>, ... ]
  }
}
```

"headers": array of *patterns*, optional

The case-insensitive name of one or more headers whose value to mask in the logs.

The following value masks headers called `X-OpenAM-Username`, `X-OpenAM-Password` and `x-openam-token`:

```
"headers": [ "X-OpenAM-.*" ]
```

Default: None

"trailers": array of *patterns*, optional

The case-insensitive name of one or more trailers whose value to mask in the logs.

The following value masks trailers called `Expires`:

```
"trailers": [ "Expires" ]
```

Default: None

"attributes": array of *patterns*, optional

The case-insensitive name of one or more attributes whose value to mask in the logs.

Default: None

"mask": configuration expression<*string*>, optional

Text to replace the masked header value or attribute value in the logs.

Default: `*****`

Decorated Object Usage

```
{
  "name": string,
  "type": string,
  "config": object,
  decorator name: capture point(s)
}
```

"name": *string, required except for inline objects*

The unique name of the decorated object.

"type": *string, required except for inline objects, required_*

The class name of the decorated object, which must be either a Filter or a Handler. See also [PingGateway filters](#) and [PingGateway handlers](#).

"config": *object required unless empty*

The configuration of the decorated object, as documented in the object reference page.

decorator name: capture point(s), optional

The decorator name must match the name of the CaptureDecorator. For example, if the CaptureDecorator has **"name" : "capture"**, then decorator name is **capture**.

The capture point(s) are either a single string, or an array of strings. The strings are documented here in lowercase, but aren't case-sensitive:

"all"

Capture at all available capture points.

"none"

Disable capture. If **none** is configured with other capture points, **none** takes precedence.

"request"

Capture the request as it enters the Filter or Handler.

"filtered_request"

Capture the request as it leaves the Filter. Only applies to Filters.

"response"

Capture the response as it enters the Filter or leaves the Handler.

"filtered_response"

Capture the response as it leaves the Filter. Only applies to Filters.

Examples

Log the entity

The following example decorator is configured to log the entity:


```
{
  "name": "capture",
  "type": "CaptureDecorator",
  "config": {
    "captureEntity": true
  }
}
```

Don't log the entity

The following example decorator is configured not to log the entity:

```
{
  "name": "capture",
  "type": "CaptureDecorator"
}
```

Log the context

The following example decorator is configured to log the context in JSON format, excluding the request and the response:

```
{
  "name": "capture",
  "type": "CaptureDecorator",
  "config": {
    "captureContext": true
  }
}
```

Log requests and responses with the entity

The following example decorator is configured to log requests and responses with the entity, before sending the request and before returning the response:

```
{
  "heap": [
    {
      "name": "capture",
      "type": "CaptureDecorator",
      "config": {
        "captureEntity": true
      }
    },
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "capture": [
        "request",
        "response"
      ]
    }
  ],
  "handler": "ReverseProxyHandler"
}
```

Capture transformed requests and responses

The following example uses the default CaptureDecorator to capture transformed requests and responses, as they leave filters:

```

{
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [{
        "type": "HeaderFilter",
        "config": {
          "messageType": "REQUEST",
          "add": {
            "X-RequestHeader": [
              "Capture at filtered_request point",
              "And at filtered_response point"
            ]
          }
        }
      }],
      {
        "type": "HeaderFilter",
        "config": {
          "messageType": "RESPONSE",
          "add": {
            "X-ResponseHeader": [
              "Capture at filtered_response point"
            ]
          }
        }
      }
    ],
    "handler": {
      "type": "StaticResponseHandler",
      "config": {
        "status": 200,
        "headers": {
          "Content-Type": [ "text/html; charset=UTF-8" ]
        },
        "entity": "<html><body><p>Hello world!</p></body></html>"
      }
    }
  },
  "capture": [
    "filtered_request",
    "filtered_response"
  ]
}

```

Capture the context as JSON

The following example captures the context as JSON, excluding the request and response, before sending the request and before returning the response:

```
{
  "heap": [
    {
      "name": "capture",
      "type": "CaptureDecorator",
      "config": {
        "captureContext": true
      }
    },
    {
      "name": "ReverseProxyHandler",
      "type": "ReverseProxyHandler",
      "capture": [
        "request",
        "response"
      ]
    }
  ],
  "handler": "ReverseProxyHandler"
}
```

More information

[org.forgerock.openig.decoration.capture.CaptureDecorator](https://github.com/forgerock/openig-decoration-capture/CaptureDecorator) 

TimerDecorator

Records time to process filters, handlers, and access token resolvers.

Decorator usage

```
{
  "name": string,
  "type": "TimerDecorator",
  "config": {
    "timeUnit": configuration expression<string>
  }
}
```

PingGateway configures a default TimerDecorator named `timer`. Use `timer` as the decorator name without explicitly declaring a decorator named timer.

"timeUnit": *configuration expression*<*string*>, optional

Unit of time used in the decorator output. The unit of time can be any unit allowed in the <[duration](#)> field.

Default: `ms`

Decorated object usage

```
{
  "name": string,
  "type": string,
  "config": object,
  decorator name: boolean
}
```

"name": *string*, required except for inline objects

The unique name of the object to decorate.

"type": *string*, required

The class name of the object to decorate, which must be a [Filter](#), [Handler](#), or the `accessTokenResolver` property of [OAuth2ResourceServerFilter](#).

"config": *object*, optional

The configuration of the object, just like an object that isn't decorated.

Default: Empty

decorator name: *configuration expression<boolean>*, required

PingGateway looks for the presence of the decorator name field for the TimerDecorator:

- `true` : Activate the timer
- `false` : Deactivate the TimerDecorator

Timer metrics

Learn about Timer metrics:

- [Metrics at the Prometheus Scrape Endpoint](#)
- [Timer metrics at the Common REST Monitoring Endpoint \(deprecated\)](#)

Timer metrics in SLF4J logs are named in this format:

```
<className>.<decoratorName>.<decoratedObjectName>
```

If the decorated object isn't named, the object path is used in the log.

When a route's top-level handler is decorated, the timer decorator records the elapsed time for operations traversing the whole route:

```
2018-09-04T12:16:08,994Z | INFO | I/O dispatcher 17 | o.f.o.d.t.T.t.top-level-handler | @myroute | Elapsed time: 13 ms
```

When an individual handler in the route is decorated, the timer decorator records the elapsed time for operations traversing the handler:

```
2018-09-04T12:44:02,161Z | INFO | http-nio-8080-exec-8 | o.f.o.d.t.T.t.StaticResponseHandler-1 | @myroute | Elapsed time: 1 ms
```

Examples

The following example uses the default timer decorator to record the time that `TokenIntrospectionAccessTokenResolver` takes to process a request:

```
{
  "accessTokenResolver": {
    "name": "TokenIntrospectionAccessTokenResolver-1",
    "type": "TokenIntrospectionAccessTokenResolver",
    "config": {
      "amService": "AmService-1",
      ...
    },
    "timer": true
  }
}
```

The following example defines a customized timer decorator in the heap, and uses it to record the time that the `SingleSignOnFilter` takes to process a request:

```

{
  "heap": [
    {
      "name": "mytimerdecorator",
      "type": "TimerDecorator",
      "config": {
        "timeUnit": "nano"
      }
    },
    ...
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "SingleSignOnFilter",
          "config": {
            ...
          }
        },
        "mytimerdecorator": true
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}

```

More information

[org.forgerock.openig.decoration.timer.TimerDecorator](https://github.com/pingidentity/pinggateway/blob/main/doc/org.forgerock.openig.decoration.timer.TimerDecorator)

TracingDecorator

PingGateway can push traces to an [OpenTelemetry](#) service. You set up OpenTelemetry tracing in the [AdminHttpApplication](#) (`admin.json`) configuration.

Important

This feature has [Evolving](#) interface stability. It is subject to change without notice, even in a minor or maintenance release.

The span content of traces, such as attached metadata like request details, aren't supported. Compatibility isn't guaranteed.

Decorator Usage

```

{
  "name": string,
  "type": "TracingDecorator"
}

```

A TracingDecorator doesn't have configurable properties.

PingGateway creates a default TracingDecorator named `tracing` at startup time in the top-level heap. You can use the `tracing` decorator without additional configuration.

Decorated Object Usage

```
{
  "name": string,
  "type": string,
  "<decorator-name>": configuration expression<boolean>
}
```

"name": *string*, required except for inline objects

The unique name of the object, just like an object that isn't decorated.

"type": *<string>*, required

The class name of the decorated object.

<decorator-name>: *configuration expression<boolean>*, required

- `true` : Activate tracing
- `false` : Deactivate tracing

More information

org.forgerock.openig.decoration.tracing.TracingDecorator 

PingGateway audit framework

PingGateway uses the common audit framework to record audit events.

Audit logs use timestamps in UTC format, for example, `2024-07-10T09:35:12.335Z`, a unified standard not affected by time changes for daylight savings. The timestamp format isn't configurable.

The following objects are available for auditing:

- [AuditService](#)
- [CsvAuditEventHandler](#)
- [JdbcAuditEventHandler](#)
- [JmsAuditEventHandler](#)
- [JsonAuditEventHandler](#)
- [JsonStdoutAuditEventHandler](#)
- [NoOpAuditService](#)
- [SyslogAuditEventHandler](#)

AuditService

The audit service uses the common audit event framework to record `access` and `notifications` audit events. Learn how to record other types of audit events in [Record custom audit events](#).

By default, no routes in a configuration are audited; the `NoOpAuditService` object type provides an empty audit service to the top-level heap and its child routes. PingGateway provides a default empty service based on the `NoOpAuditService` type. The top-level heap and child routes inherit from the setting and use a service equivalent to the following declaration:

```
{
  "name": "AuditService",
  "type": "NoOpAuditService"
}
```

Configure auditing in the following ways:

Override the NoOpAuditService for all routes in the configuration

Define an `AuditService` object named `AuditService` in `config.json`. No other configuration is required; all routes use the same `AuditService`.

Configure an audit service that can be optionally used by all routes in the configuration

Do both of the following:

- In `config.json` in the top-level heap, define an `AuditService` object that is **not** named `AuditService`.
- In a route, configure the `Route` property `auditService` to refer to the name of the declared `AuditService` heaplet.

Configure an audit service specifically for a route

Do one of the following:

- Define an `AuditService` object named `AuditService` in the route heap.
- In the route heap or a parent heap, define an `AuditService` object that is **not** named `AuditService`; configure the `Route` property `auditService` to refer to the name of the declared `AuditService` heaplet.
- Configure the `Route` property `auditService` with an inline `AuditService` object.

One configuration can contain multiple `AuditServices`.

When you define multiple `AuditServices` that use `JsonAuditEventHandler` or `CsvAuditEventHandler`, configure each of the event handlers with a different `logDirectory`. This prevents the `AuditServices` from logging to the same audit logging file.

Usage

```
{
  "name": string,
  "type": "AuditService",
  "config": {
    "config": object,
    "eventHandlers": [ object, ...],
    "topicSchemasDirectory": configuration_expression<string>
  }
}
```

Properties

"config": *object*, *required*

Configures the audit service itself, rather than event handlers. If the configuration uses only default settings, you can omit the field instead of including an empty object as the field value.

```
{
  "config": {
    "handlerForQueries": configuration_expression<string>,
    "availableAuditEventHandlers": [configuration_expression<string>, ...],
    "caseInsensitiveFields": [configuration_expression<string>, ...],
    "filterPolicies": {
      "field": {
        "includeIf": [configuration_expression<string>, ...],
        "excludeIf": [configuration_expression<string>, ...]
      }
    }
  }
}
```

"handlerForQueries": *configuration expression<string>*, *optional*

The name of the event handler to use when querying audit event messages over REST.

"availableAuditEventHandlers": *array of configuration expression<strings>*, *optional*

A list of fully qualified event handler class names for event handlers available to the audit service.

"caseInsensitiveFields": *array of configuration expression<strings>*, *optional*

A list of audit event fields to be considered as case-insensitive for filtering. The fields are referenced using JSON pointer syntax. The list can be `null` or empty.

Default: `/access/http/request/headers` and `/access/http/response/headers` fields are considered case-insensitive for filtering. All other fields are considered case-sensitive.

"filterPolicies": *object*, *optional*

To prevent logging of sensitive data for an event, the Common Audit implementation uses a safelist to specify which event fields appear in the logs. By default, only event fields that are safelisted are included in the audit event logs. For more information about safelisting, refer to [Safelisting audit event fields for the logs](#).

"field": *object*, optional

This property specifies non-safelisted event fields to include in the logs, and safelisted event fields to exclude from the logs.

If `includeIf` and `excludeIf` are specified for the same field, `excludeIf` takes precedence.

Audit event fields use JSON pointer notation, and are taken from the JSON schema for the audit event content.

Default: Include only safelisted event fields in the logs.

"includeIf": *array of configuration expression<strings>*, optional:

A list of non-safelisted audit event fields to include in the logs. Specify the topic and the hierarchy to the field. Any child fields of the specified field are encompassed.

**Important**

Before you include non-safelisted event fields in the logs, consider the impact on security. Including some headers, query parameters, or cookies in the logs could cause credentials or tokens to be logged, and allow anyone with access to the logs to impersonate the holder of these credentials or tokens.

"excludeIf": *array of configuration expression<strings>*, optional:

A list of safelisted audit event fields to exclude from the logs. Specify the topic and the hierarchy to the field. Any child fields of the specified field are encompassed.

The following example excludes fields for the `access` topic:

```
{
  "field": {
    "excludeIf": [
      "/access/http/request/headers/host",
      "/access/http/request/path",
      "/access/server",
      "/access/response"
    ]
  }
}
```

For an example route that excludes fields, see [Exclude safelisted audit event fields from logs](#).

"eventHandlers": *array of Event Handler objects*, required

An array of one or more audit event handler configuration objects to deal with audit events.

The configuration of the event handler depends on type of event handler. PingGateway supports the event handlers listed in [AuditFramework](#).

"topicSchemasDirectory": *configuration expression*<string>, optional

Directory containing the JSON schema for the topic of a custom audit event. The schema defines which fields are included in the topic. For information about the syntax, see [JSON Schema](#).

Default: `$HOME/.openig/audit-schemas` (Windows, `%appdata%\OpenIG\audit-schemas`)

For an example of how to configure custom audit events, see [Record custom audit events](#).

The following example schema includes the mandatory fields, `_id`, `timestamp`, `transactionId`, and `eventName`, and an optional `customField`:

```
{
  "schema": {
    "$schema": "http://json-schema.org/draft-04/schema#",
    "id": "/",
    "type": "object",
    "properties": {
      "_id": {
        "type": "string"
      },
      "timestamp": {
        "type": "string"
      },
      "transactionId": {
        "type": "string"
      },
      "eventName": {
        "type": "string"
      },
      "customField": {
        "type": "string"
      }
    }
  }
}
```

Source: [customTopic.json](#)

Example

The following example audit service logs access event messages in a comma-separated variable file, named `/path/to/audit/logs/access.csv`:

```
{
  "name": "AuditService",
  "type": "AuditService",
  "config": {
    "config": {},
    "eventHandlers": [
      {
        "class": "org.forgerock.audit.handlers.csv.CsvAuditEventHandler",
        "config": {
          "name": "csv",
          "logDirectory": "/path/to/audit/logs",
          "topics": [
            "access"
          ]
        }
      }
    ]
  }
}
```

The following example route uses the audit service:

```
{
  "handler": "ReverseProxyHandler",
  "auditService": "AuditService"
}
```

More information

[NoOpAuditService](#)

[org.forgerock.audit.AuditService](#) 

CsvAuditEventHandler

An audit event handler that responds to events by logging messages to files in comma-separated variable (CSV) format.

Declare the configuration in an audit service, as described in [AuditService](#).



Important

The CSV handler doesn't sanitize messages when writing to CSV log files.
Don't open CSV logs in spreadsheets or other applications that treat data as code.

Usage

```
{
  "class": "org.forgerock.audit.handlers.csv.CsvAuditEventHandler",
  "config": {
    "name": configuration expression<string>,
    "logDirectory": configuration expression<string>,
    "topics": [ configuration expression<string>, ... ],
    "enabled": configuration expression<boolean>,
    "formatting": {
      "quoteChar": configuration expression<string>,
      "delimiterChar": configuration expression<string>,
      "endOfLineSymbols": configuration expression<string>
    },
    "buffering": {
      "enabled": configuration expression<boolean>,
      "autoFlush": configuration expression<boolean>
    },
    "fileRotation": {
      "rotationEnabled": configuration expression<boolean>,
      "maxFileSize": configuration expression<number>,
      "rotationFilePrefix": configuration expression<string>,
      "rotationFileSuffix": configuration expression<string>,
      "rotationInterval": configuration expression<duration>,
      "rotationTimes": [ configuration expression<duration>, ... ]
    },
    "fileRetention": {
      "maxDiskSpaceToUse": configuration expression<number>,
      "maxNumberOfHistoryFiles": configuration expression<number>,
      "minFreeSpaceRequired": configuration expression<number>
    },
    "rotationRetentionCheckInterval": configuration expression<duration>
  }
}
```

The values in this configuration object can use expressions as long as they resolve to the correct types for each field. Learn more about expressions in [Expressions](#).

Configuration

"name": configuration expression<string>, required

The name of the event handler.

"logDirectory": configuration expression<string>, required

The file system directory where this event handler writes log files.

When multiple `AuditServices` are defined in the deployment, prevent them from logging to the same audit logging file by setting different values for `logDirectory`.

"topics": array of configuration expression<strings>, required

One or more topics that this event handler intercepts. PingGateway can record the following audit event topics:

- `access`: Log access audit events.

Access audit events occur at the system boundary. They include the arrival of the initial HTTP request and departure of the final HTTP response.

To record `access` audit events, configure the `AuditService` inline in a route or in the heap.

- `notifications`: Log AM WebSocket notifications.

To record `notifications` audit events, configure the `AuditService` inline in a route or in the heap.

- `customTopic`: Log custom audit events.

To create a topic for a custom audit event, include a JSON schema for the topic in your PingGateway configuration.

To record custom audit events, configure the `AuditService` in the heap and refer to it from the route or subroutes.

For an example of how to set up custom audit events, refer to [Record custom audit events](#).

"enabled": configuration expression<*boolean*>, optional

Whether this event handler is active.

Default: true

"formatting": *object*, optional

Formatting settings for CSV log files.

The formatting object has the following fields:

"quoteChar": configuration expression<*string*>, optional

A single character to quote CSV entries.

Default: `"`

"delimiterChar": configuration expression<*string*>, optional

A single character to delimit CSV entries.

Default: `,`

"endOfLineSymbols": configuration expression<*string*>, optional

A character or characters to separate a line.

Default: System-dependent line separator defined for the JVM

"buffering": *object*, optional

Buffering settings for writing CSV log files. The default is for messages to be written to the log file for each event.

The buffering object has the following fields:

"enabled": configuration expression<*boolean*>, optional

Whether log buffering is enabled.

Default: false

"autoFlush": configuration expression<boolean>, optional

Whether events are automatically flushed after being written.

Default: true

"fileRotation": object, optional

File rotation settings for log files.

"rotationEnabled": configuration expression<boolean>, optional

A flag to enable rotation of log files.

Default: false.

"maxFileSize": configuration expression<number>, optional

The maximum file size of an audit log file in bytes. A setting of 0 or less indicates that the policy is disabled.

Default: 0.

"rotationFilePrefix": configuration expression<string>, optional

The prefix to add to a log file on rotation. This has an effect when time-based file rotation is enabled.

"rotationFileSuffix": configuration expression<string>, optional

The suffix to add to a log file on rotation, possibly expressed in [SimpleDateFormat](#).

This has an effect when time-based file rotation is enabled.

Default: `-yyyy.MM.dd-HH.mm.ss`, where yyyy characters are replaced with the year, MM characters are replaced with the month, dd characters are replaced with the day, HH characters are replaced with the hour (00-23), mm characters are replaced with the minute (00-60), and ss characters are replaced with the second (00-60).

"rotationInterval": configuration expression<duration>, optional

The time interval after which to rotate log files. This duration must not be zero. This has the effect of enabling time-based file rotation.

"rotationTimes": array of configuration expression<durations>, optional

The durations, counting from midnight UTC, after which to rotate files.

The following example schedules rotation six and twelve hours after midnight:

```
"rotationTimes": [ "6 hours", "12 hours" ]
```

This has the effect of enabling time-based file rotation.

"fileRetention": object, optional

File retention settings for log files.

"maxNumberOfHistoryFiles": configuration expression<number>, optional

The maximum number of historical audit files that can be stored. If the number exceeds this maximum, older files are deleted. A value of `-1` disables purging of old log files.

Default: 0.

"maxDiskSpaceToUse": configuration expression<number>, optional

The maximum disk space in bytes that can be used for audit files. If the audit files use more than this space, older files are deleted. A negative or zero value indicates that this policy is disabled, and historical audit files can use unlimited disk space.

Default: 0

"minFreeSpaceRequired": configuration expression<string>, optional

The minimum free disk space in bytes required on the system that houses the audit files. If the free space drops below this minimum, older files are deleted. A negative or zero value indicates that this policy is disabled, and no minimum space requirements apply.

Default: 0

"rotationRetentionCheckInterval": configuration expression<string>, optional

Interval at which to periodically check file rotation and retention policies. The interval must be a duration, for example, 5 seconds, 5 minutes, or 5 hours.

PingGateway checks whether to rotate the current audit file at each interval. If so, it also checks whether to retain old audit files.

Default: 5 seconds

Example

You can find more information about how to record audit events in a CSV file in [Recording Access Audit Events in CSV](#).

The following example configures a CSV audit event handler to write a log file `/path/to/audit/logs/access.csv`:

```
{
  "name": "csv",
  "topics": [
    "access"
  ],
  "logDirectory": "/path/to/audit/logs/"
}
```

More information

[org.forgerock.audit.handlers.csv.CsvAuditEventHandler](#) 

JdbcAuditEventHandler

An audit event handler that responds to events by logging messages to an appropriately configured relational database table.

Declare the configuration in an audit service, as described in [AuditService](#).

To configure PingGateway to use the database, add the database .jar file containing the Driver as follows:

- Create the directory `$HOME/.openig/extra`, where `$HOME/.openig` is the instance directory, and add .jar files to the directory.

The JDBC handler library is in the `lib` directory.

Unpack the library, then find the examples under the `db/` folder.

Usage

```
{
  "class": "org.forgerock.audit.handlers.jdbc.JdbcAuditEventHandler",
  "config": {
    "name": configuration expression<string>,
    "topics": [ configuration expression<string>, ... ],
    "databaseType": configuration expression<string>,
    "enabled": configuration expression<boolean>,
    "buffering": {
      "enabled": configuration expression<boolean>,
      "writeInterval": configuration expression<duration>,
      "autoFlush": configuration expression<boolean>,
      "maxBatchedEvents": configuration expression<number>,
      "maxSize": configuration expression<number>,
      "writerThreads": configuration expression<number>
    },
    "connectionPool": {
      "driverClassName": configuration expression<string>,
      "dataSourceClassName": configuration expression<string>,
      "jdbcUrl": configuration expression<string>,
      "username": configuration expression<string>,
      "password": configuration expression<string>,
      "autoCommit": configuration expression<boolean>,
      "connectionTimeout": configuration expression<number>,
      "idleTimeout": configuration expression<number>,
      "maxLifetime": configuration expression<number>,
      "minIdle": configuration expression<number>,
      "maxPoolSize": configuration expression<number>,
      "poolName": configuration expression<string>
    },
    "tableMappings": [
      {
        "event": configuration expression<string>,
        "table": configuration expression<string>,
        "fieldToColumn": map or configuration expression<map>
      }
    ]
  }
}
```

Configuration

"name": configuration expression<string>, required

The name of the event handler.

"topics": array of configuration expression<strings>, required

One or more topics that this event handler intercepts. PingGateway can record the following audit event topics:

- **access** : Log access audit events.

Access audit events occur at the system boundary. They include the arrival of the initial HTTP request and departure of the final HTTP response.

To record **access** audit events, configure the `AuditService` inline in a route or in the heap.

- **notifications** : Log AM WebSocket notifications.

To record **notifications** audit events, configure the `AuditService` inline in a route or in the heap.

- **customTopic**: Log custom audit events.

To create a topic for a custom audit event, include a JSON schema for the topic in your PingGateway configuration.

To record custom audit events, configure the `AuditService` in the heap and refer to it from the route or subroutes. For an example of how to set up custom audit events, refer to [Record custom audit events](#).

"databaseType": configuration expression<string>, required

The database type name.

Built-in support is provided for `oracle`, `mysql`, and `h2`.

"enabled": configuration expression<boolean>, optional

Whether this event handler is active.

Default: true.

"buffering": object, optional

Buffering settings for sending messages to the database. The default is for messages to be written to the log file for each event.

The buffering object has the following fields:

"enabled": configuration expression<boolean>, optional

Whether log buffering is enabled.

Default: false.

"writeInterval": configuration expression<duration>, required

The interval at which to send buffered event messages to the database.

This interval must be greater than 0 if buffering is enabled.

"autoFlush": *configuration expression*<boolean>, optional

Whether the events are automatically flushed after being written.

Default: true.

"maxBatchedEvents": *configuration expression*<number>, optional

The maximum number of event messages batched into a [PreparedStatement](#).

Default: 100.

"maxSize": *configuration expression*<number>, optional

The maximum size of the queue of buffered event messages.

Default: 5000.

"writerThreads": *configuration expression*<number>, optional

The number of threads to write buffered event messages to the database.

Default: 1.

"connectionPool": *object*, required

When a `JdbcDataSource` object named `AuditService` is defined in the route heap. This configuration isn't required.

Connection pool settings for sending messages to the database.

"driverClassName": *configuration expression*<string>, optional

The class name of the driver to use for the JDBC connection. For example, with MySQL Connector/J, the class name is `com.mysql.jdbc.Driver`.

"dataSourceClassName": *configuration expression*<string>, optional

The class name of the data source for the database.

"jdbcUrl": *configuration expression*<string>, required

The JDBC URL to connect to the database.

"username": *configuration expression*<string>, required

The username identifier for the database user with access to write the messages.

"password": *configuration expression*<number>, optional

The password for the database user with access to write the messages.

"autoCommit": *configuration expression*<boolean>, optional

Whether to commit transactions automatically when writing messages.

Default: true.

"connectionTimeout": configuration expression<number>, optional

The number of milliseconds to wait for a connection from the pool before timing out.

Default: 30000.

"idleTimeout": configuration expression<number>, optional

The number of milliseconds to allow a database connection to remain idle before timing out.

Default: 600000.

"maxLifetime": configuration expression<number>, optional

The number of milliseconds to allow a database connection to remain in the pool.

Default: 1800000.

"minIdle": configuration expression<number>, optional

The minimum number of idle connections in the pool.

Default: 10.

"maxPoolSize": configuration expression<number>, optional

The maximum number of connections in the pool.

Default: 10.

"poolName": configuration expression<string>, optional

The name of the connection pool.

"tableMappings": array of objects, required

Table mappings for directing event content to database table columns.

A table mappings object has the following fields:

"event": configuration expression<string>, required

The audit event that the table mapping is for.

Set this to `access`.

"table": configuration expression<string>, required

The name of the database table that corresponds to the mapping.

"fieldToColumn": map or configuration expression<map>, required

A map of one or more data pairs with the format `Map<String, String>`, where:

- The key is the name of an audit event field

- The value is the name of a database column, or a configuration expression that evaluates to the name of a database column

The following formats are allowed:

```
{
  "fieldToColumn": {
    "string": "configuration expression<string>",
    ...
  }
}
```

```
{
  "fieldToColumn": "configuration expression<map>"
}
```

Audit event fields use JSON pointer notation, and are taken from the JSON schema for the audit event content.

In the following example, the property is a map whose keys and values are strings representing the names of audit event fields and database columns:

```
{
  "fieldToColumn": {
    "_id": "id",
    "timestamp": "timestamp_",
    ...
  }
}
```

Example

Examples including statements to create tables are provided in the JDBC handler library, `forgerock-audit-handler-jdbc-version.jar`.

For an example of using `JdbcAuditEventHandler`, refer to [Recording access audit events in a database](#).

In the following example, PingGateway events are logged to an h2 database:

```

{
  "name": "audit-jdbc",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/audit-jdbc')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AuditDataSource",
      "type": "JdbcDataSource",
      "config": {
        "dataSourceClassName" : "org.h2.jdbcx.JdbcDataSource",
        "username" : "sa",
        "passwordSecretId" : "database.password",
        "secretsProvider" : "SystemAndEnvSecretStore-1",
        "properties" : {
          "url" : "jdbc:h2:tcp://localhost/~/test"
        }
      }
    },
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.jdbc.JdbcAuditEventHandler",
            "config": {
              "databaseType": "h2",
              "name": "jdbc",
              "topics": [
                "access"
              ],
              "tableMappings": [
                {
                  "event": "access",
                  "table": "audit.auditaccess",
                  "fieldToColumn": {
                    "_id": "id",
                    "timestamp": "timestamp",
                    "eventName": "eventname",
                    "transactionId": "transactionid",
                    "userId": "userid",
                    "trackingIds": "trackingids",
                    "server/ip": "server_ip",
                    "server/port": "server_port",
                    "client/ip": "client_ip",
                    "client/port": "client_port",
                    "request/protocol": "request_protocol",
                    "request/operation": "request_operation",
                    "request/detail": "request_detail",
                    "http/request/secure": "http_request_secure",
                    "http/request/method": "http_request_method",
                    "http/request/path": "http_request_path",
                    "http/request/queryParameters": "http_request_queryparameters",
                    "http/request/headers": "http_request_headers",
                    "http/request/cookies": "http_request_cookies",
                    "http/response/headers": "http_response_headers",

```

```

        "response/status": "response_status",
        "response/statusCode": "response_statuscode",
        "response/elapsedTime": "response_elapsedtime",
        "response/elapsedTimeUnits": "response_elapsedtimeunits"
      }
    ]
  }
}
],
"auditService": "AuditService",
"handler": "ReverseProxyHandler"
}

```

Source: [audit-jdbc.json](#)

More information

[org.forgerock.audit.handlers.jdbc.JdbcAuditEventHandler](#)

JmsAuditEventHandler



Important

This object is deprecated. Use an alternative audit event handler.

The Java Message Service (JMS) is a Java API for sending asynchronous messages between clients. It wraps audit events in JMS messages and publishes them in a JMS broker, which then delivers the messages to the appropriate destination.

The JMS API architecture includes a *JMS provider* and *JMS clients*, and supports the *publish/subscribe* messaging pattern. Learn more in [Basic JMS API Concepts](#).

The JMS audit event handler doesn't support queries. To support queries, also enable a second handler that supports queries.

The ForgeRock JMS audit event handler supports JMS communication, based on the following components:

- JMS message broker .jar files, to provide clients with connectivity, message storage, and message delivery functionality.
Add the .jar files to the configuration as follows:
- Create the directory `$HOME/.openig/extra`, where `$HOME/.openig` is the instance directory, and add .jar files to the directory.
- JMS messages.
- Destinations, maintained by a message broker. A destination can be a JMS topic, using [publish/subscribe](#) to take the ForgeRock JSON for an audit event, wrap it into a JMS TextMessage, and send it to the broker.
- JMS clients, to produce and/or receive JMS messages.

Depending on the configuration, some or all of these components are included in JMS audit log messages.

Important

The example in this section is based on [Apache ActiveMQ](#), but you can choose a different JMS message broker.

Declare the configuration in an audit service, as described in [AuditService](#).

Usage

```
{
  "name": string,
  "type": "AuditService",
  "config": {
    "config": {},
    "eventHandlers": [
      {
        "class": "org.forgerock.audit.handlers.jms.JmsAuditEventHandler",
        "config": {
          "name": configuration expression<string>,
          "topics": [ configuration expression<string>, ... ],
          "deliveryMode": configuration expression<string>,
          "sessionMode": configuration expression<string>,
          "jndi": {
            "contextProperties": map,
            "topicName": configuration expression<string>,
            "connectionFactoryName": configuration expression<string>
          }
        }
      }
    ]
  }
}
```

The values in this configuration object can use configuration expressions, as described in [Configuration and Runtime Expressions](#).

Configuration

You can find a list of properties in the "config" object in [JMS Audit Event Handler](#) in the IDM documentation.

"name": configuration expression<string>, required

The name of the event handler.

"topics": array of configuration expression<strings>, required

One or more topics that this event handler intercepts. PingGateway can record the following audit event topics:

- **access**: Log access audit events.

Access audit events occur at the system boundary. They include the arrival of the initial HTTP request and departure of the final HTTP response.

To record **access** audit events, configure the AuditService inline in a route or in the heap.

- **notifications**: Log AM WebSocket notifications.

To record `notifications` audit events, configure the `AuditService` inline in a route or in the heap.

- `customTopic`: Log custom audit events.

To create a topic for a custom audit event, include a JSON schema for the topic in your PingGateway configuration.

To record custom audit events, configure the `AuditService` in the heap and refer to it from the route or subroutes.

For an example of how to set up custom audit events, refer to [Record custom audit events](#).

"deliveryMode": configuration expression<string>, required

Delivery mode for messages from a JMS provider. Set to `PERSISTENT` or `NON_PERSISTENT`.

"sessionMode": configuration expression<string>, required

Acknowledgement mode in sessions without transactions. Set to `AUTO`, `CLIENT`, or `DUPS_OK`.

"contextProperties": *map*, optional

Settings with which to populate the initial context.

The map values are evaluated as configuration expression<strings>.

The following properties are required when ActiveMQ is used as the message broker:

- `java.naming.factory.initial`

For example, `"org.apache.activemq.jndi.ActiveMQInitialContextFactory"`.

To substitute a different JNDI message broker, change the JNDI context properties.

- `java.naming.provider.url`

For example, `"tcp://127.0.0.1:61616"`.

To configure the message broker on a remote system, substitute the associated IP address.

To set up SSL, set up keystores and truststores, and change the value of the `java.naming.provider.url` to:

```
ssl://127.0.0.1:61617?
daemon=true&socket.enabledCipherSuites=SSL_RSA_WITH_RC4_128_SHA,SSL_DH_anon_WITH_3DES_EDE_CBC_SHA
```

- `topic.audit`

For example, `"audit"`.

To use the JMS resources provided by your application server, leave this field empty. The values for `topicName` and `connectionFactoryName` are then JNDI names that depend on the configuration of your application server.

"topicName": configuration expression<string>, required

JNDI lookup name for the JMS topic.

For ActiveMQ, this property must be consistent with the value of `topic.audit` in `contextProperties`.

"connectionFactoryName": *configuration expression*<string>, required

JNDI lookup name for the JMS connection factory.

Example

In the following example, a JMS audit event handler delivers audit events in batches. The handler is configured to use the ActiveMQ JNDI message broker, on port 61616. You can find an example of setting up and testing this configuration in [Recording Access Audit Events in JMS](#).

```
{
  "name": "30-jms",
  "MyCapture" : "all",
  "baseURI": "http://app.example.com:8081",
  "condition" : "${request.uri.path == '/activemq_event_handler'}",
  "heap": [
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers" : [
          {
            "class" : "org.forgerock.audit.handlers.jms.JmsAuditEventHandler",
            "config" : {
              "name" : "jms",
              "topics": [ "access" ],
              "deliveryMode" : "NON_PERSISTENT",
              "sessionMode" : "AUTO",
              "jndi" : {
                "contextProperties" : {
                  "java.naming.factory.initial" : "org.apache.activemq.jndi.ActiveMQInitialContextFactory",
                  "java.naming.provider.url" : "tcp://am.example.com:61616",
                  "topic.audit" : "audit"
                },
                "topicName" : "audit",
                "connectionFactoryName" : "ConnectionFactory"
              }
            }
          }
        ]
      },
      "config" : { }
    }
  ],
  "auditService": "AuditService",
  "handler" : {
    "type" : "StaticResponseHandler",
    "config" : {
      "status" : 200,
      "headers" : {
        "Content-Type" : [ "text/plain; charset=UTF-8" ]
      },
      "entity" : "Message from audited route"
    }
  }
}
```

Source: [30-jms.json](#)

More information

[org.forgerock.audit.handlers.json.JsonAuditEventHandler](#)

JsonAuditEventHandler

Logs events as JSON objects to a set of JSON files. There is one file for each topic defined in `topics`, named with the format `topic.audit.json`.

The `JsonAuditEventHandler` is the preferred file-based audit event handler.

Declare the configuration in an audit service, as described in [AuditService](#).

Usage

```
{
  "name": string,
  "type": "AuditService",
  "config": {
    "config": {},
    "eventHandlers": [
      {
        "class": "org.forgerock.audit.handlers.json.JsonAuditEventHandler",
        "config": {
          "name": configuration expression<string>,
          "topics": [ configuration expression<string>, ... ],
          "logDirectory": configuration expression<string>,
          "elasticsearchCompatible": configuration expression<boolean>,
          "fileRotation": {
            "rotationEnabled": configuration expression<boolean>,
            "maxFileSize": configuration expression<number>,
            "rotationFilePrefix": configuration expression<string>,
            "rotationFileSuffix": configuration expression<string>,
            "rotationInterval": configuration expression<duration>,
            "rotationTimes": [ configuration expression<duration>, ... ]
          },
          "fileRetention": {
            "maxNumberOfHistoryFiles": configuration expression<number>,
            "maxDiskSpaceToUse": configuration expression<number>,
            "minFreeSpaceRequired": configuration expression<number>
          },
          "rotationRetentionCheckInterval": configuration expression<duration>,
          "buffering": {
            "writeInterval": configuration expression<duration>,
            "maxSize": configuration expression<number>
          }
        }
      }
    ]
  }
}
```

Configuration

"name": configuration expression<string>, required

The event handler name. This property is used only to refer to the event handler, but isn't used to name the generated log file.

"topics": array of configuration expression<strings>, required

One or more topics that this event handler intercepts. PingGateway can record the following audit event topics:

- **access** : Log access audit events.

Access audit events occur at the system boundary. They include the arrival of the initial HTTP request and departure of the final HTTP response.

To record **access** audit events, configure the `AuditService` inline in a route or in the heap.

- **notifications** : Log AM WebSocket notifications.

To record **notifications** audit events, configure the `AuditService` inline in a route or in the heap.

- **customTopic**: Log custom audit events.

To create a topic for a custom audit event, include a JSON schema for the topic in your PingGateway configuration.

To record custom audit events, configure the `AuditService` in the heap and refer to it from the route or subroutes. For an example of how to set up custom audit events, refer to [Record custom audit events](#).

"logDirectory": configuration expression<string>, required

The file system directory where this event handler writes log files.

When multiple `AuditServices` are defined in the deployment, prevent them from logging to the same audit logging file by setting different values for **logDirectory**.

elasticsearchCompatible: configuration expression<boolean>, optional

Set to **true** to enable compatibility with ElasticSearch JSON format.

Learn more in the [ElasticSearch](#) documentation.

Default: **false**

"fileRotation": object, optional

File rotation settings for log files.

"rotationEnabled": configuration expression<boolean>, optional

A flag to enable rotation of log files.

Default: **false**.

"maxFileSize": configuration expression<number>, optional

The maximum file size of an audit log file in bytes. A setting of 0 or less indicates that the policy is disabled.

Default: 0.

"rotationFilePrefix": *configuration expression*<string>, optional

The prefix to add to a log file on rotation. This has an effect when time-based file rotation is enabled.

"rotationFileSuffix": *configuration expression*<string>, optional

The suffix to add to a log file on rotation, possibly expressed in [SimpleDateFormat](#).

This has an effect when time-based file rotation is enabled.

Default: `-yyyy.MM.dd-HH.mm.ss`, where yyyy characters are replaced with the year, MM characters are replaced with the month, dd characters are replaced with the day, HH characters are replaced with the hour (00-23), mm characters are replaced with the minute (00-60), and ss characters are replaced with the second (00-60).

"rotationInterval": *configuration expression*<duration>, optional

The time interval after which to rotate log files. This duration must not be zero. This has the effect of enabling time-based file rotation.

"rotationTimes": *array of configuration expression*< durations>, optional

The durations, counting from midnight UTC, after which to rotate files.

The following example schedules rotation six and twelve hours after midnight:

```
"rotationTimes": [ "6 hours", "12 hours" ]
```

This has the effect of enabling time-based file rotation.

"fileRetention": *object*, optional

File retention settings for log files.

"maxNumberOfHistoryFiles": *configuration expression*<number>, optional

The maximum number of historical audit files that can be stored. If the number exceeds this maximum, older files are deleted. A value of `-1` disables purging of old log files.

Default: 0.

"maxDiskSpaceToUse": *configuration expression*<number>, optional

The maximum disk space in bytes that can be used for audit files. If the audit files use more than this space, older files are deleted. A negative or zero value indicates that this policy is disabled, and historical audit files can use unlimited disk space.

Default: 0

"minFreeSpaceRequired": *configuration expression*<string>, optional

The minimum free disk space in bytes required on the system that houses the audit files. If the free space drops below this minimum, older files are deleted. A negative or zero value indicates that this policy is disabled, and no minimum space requirements apply.

Default: 0

"rotationRetentionCheckInterval": *configuration expression*<string>, optional

Interval at which to periodically check file rotation and retention policies. The interval must be a duration, for example, 5 seconds, 5 minutes, or 5 hours.

PingGateway checks whether to rotate the current audit file at each interval. If so, it also checks whether to retain old audit files.

Default: 5 seconds

"buffering": *object*, optional

Settings for buffering events and batch writes.

"writeInterval": *configuration expression*<duration>, optional

The interval at which to send buffered event messages. If buffering is enabled, this interval must be greater than 0.

Default: 1 second

"maxSize": *configuration expression*<number>, optional

The maximum number of event messages in the queue of buffered event messages.

Default: 10000

Examples

You can find an example of setting up and testing this configuration in [Recording Access Audit Events in JSON](#).

This example rotates the log at midnight UTC and retains files for 60 days:

```
{
  "name": "AuditService",
  "type": "AuditService",
  "config": {
    "eventHandlers": [
      {
        "class": "org.forgerock.audit.handlers.json.JsonAuditEventHandler",
        "config": {
          "name": "json",
          "logDirectory": "/tmp/logs",
          "topics": [ "access" ],
          "fileRotation": {
            "rotationEnabled": true,
            "rotationTimes": [ "0 hours" ]
          },
          "fileRetention": {
            "maxNumberOfHistoryFiles": 60
          }
        }
      }
    ]
  }
}
```

This example rotates logs at 2:00 AM UTC and retains five files:

```
{
  "name": "AuditService",
  "type": "AuditService",
  "config": {
    "eventHandlers": [
      {
        "class": "org.forgerock.audit.handlers.json.JsonAuditEventHandler",
        "config": {
          "name": "json",
          "logDirectory": "/tmp/logs",
          "topics": [ "access" ],
          "fileRotation": {
            "rotationEnabled": true,
            "rotationTimes": [ "2 hours" ]
          },
          "fileRetention": {
            "maxNumberOfHistoryFiles": 5
          }
        }
      }
    ]
  }
}
```

More information

[org.forgerock.audit.handlers.json.JsonAuditEventHandler](#) 

JsonStdoutAuditEventHandler

Logs events to JSON standard output (stdout).

Declare the configuration in an audit service, as described in [AuditService](#).

Usage

```
{
  "name": string,
  "type": "AuditService",
  "config": {
    "config": {},
    "eventHandlers": [
      {
        "class": "org.forgerock.audit.handlers.json.stdout.JsonStdoutAuditEventHandler",
        "config": {
          "name": configuration expression<string>,
          "topics": [ configuration expression<string>, ... ],
          "elasticsearchCompatible": configuration expression<boolean>
        }
      }
    ]
  }
}
```

Configuration

"name": configuration expression<string>, required

The name of the event handler.

"topics": array of configuration expression<strings>, required

One or more topics that this event handler intercepts. PingGateway can record the following audit event topics:

- **access** : Log access audit events.

Access audit events occur at the system boundary. They include the arrival of the initial HTTP request and departure of the final HTTP response.

To record **access** audit events, configure the AuditService inline in a route or in the heap.

- **notifications** : Log AM WebSocket notifications.

To record **notifications** audit events, configure the AuditService inline in a route or in the heap.

- **customTopic**: Log custom audit events.

To create a topic for a custom audit event, include a JSON schema for the topic in your PingGateway configuration.

To record custom audit events, configure the AuditService in the heap and refer to it from the route or subroutes. For an example of how to set up custom audit events, refer to [Record custom audit events](#).

elasticsearchCompatible: *configuration expression* <boolean>, optional

Set to **true** to enable compatibility with ElasticSearch JSON format. For more information, refer to the [ElasticSearch](#) documentation.

Default: **false**

Example

In the following example, a `JsonStdoutAuditEventHandler` logs audit events. For an example of setting up and testing this configuration, refer to [Recording access audit events to standard output](#).

```
{
  "name": "30-jsonstdout",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/jsonstdout-audit')}",
  "heap": [
    {
      "name": "AuditService",
      "type": "AuditService",
      "config": {
        "eventHandlers": [
          {
            "class": "org.forgerock.audit.handlers.json.stdout.JsonStdoutAuditEventHandler",
            "config": {
              "name": "jsonstdout",
              "elasticsearchCompatible": false,
              "topics": [
                "access"
              ]
            }
          }
        ]
      }
    },
    {
      "config": {}
    }
  ],
  "auditService": "AuditService",
  "handler": "ReverseProxyHandler"
}
```

Source: [30-jsonstdout.json](#)

More information

[org.forgerock.audit.handlers.json.stdout.JsonStdoutAuditEventHandler](#)

NoOpAuditService

Provides an empty audit service to the top-level heap and its child routes. Use `NoOpAuditService` to prevent routes from using the parent audit service, when an `AuditService` isn't explicitly defined.

You can find more information about how to override the default audit service in [PingGateway audit framework](#).

Usage

```
{
  "name": "AuditService",
  "type": "NoOpAuditService"
}
```

```
"auditService": "NoOpAuditService"
```

More information

[AuditService](#)

[org.forgerock.openig.audit.NoOpAuditService](#) 

SyslogAuditEventHandler

An audit event handler that responds to events by logging messages to the UNIX system log as governed by RFC 5424, [The Syslog Protocol](#) .

Declare the configuration in an audit service, as described in [AuditService](#).

Usage

```
{
  "class": "org.forgerock.audit.handlers.syslog.SyslogAuditEventHandler",
  "config": {
    "name": configuration expression<string>,
    "topics": [ configuration expression<string>, ... ],
    "protocol": configuration expression<string>,
    "host": configuration expression<string>,
    "port": configuration expression<number>,
    "connectTimeout": configuration expression<number>,
    "facility": configuration expression<string>,
    "buffering": {
      "enabled": configuration expression<boolean>,
      "maxSize": configuration expression<number>
    },
    "severityFieldMappings": [
      {
        "topic": configuration expression<string>,
        "field": configuration expression<string>,
        "valueMappings": {
          "field-value": object
        }
      }
    ]
  }
}
```

The values in this configuration object can use expressions as long as they resolve to the correct types for each field. For details about expressions, refer to [Expressions](#).

Configuration

"name": configuration expression<string>, required

The name of the event handler.

"topics": array of configuration expression<strings>, required

One or more topics that this event handler intercepts. PingGateway can record the following audit event topics:

- **access** : Log access audit events.

Access audit events occur at the system boundary. They include the arrival of the initial HTTP request and departure of the final HTTP response.

To record **access** audit events, configure the `AuditService` inline in a route or in the heap.

- **notifications** : Log AM WebSocket notifications.

To record **notifications** audit events, configure the `AuditService` inline in a route or in the heap.

- **customTopic**: Log custom audit events.

To create a topic for a custom audit event, include a JSON schema for the topic in your PingGateway configuration.

To record custom audit events, configure the `AuditService` in the heap and refer to it from the route or subroutes.

For an example of how to set up custom audit events, refer to [Record custom audit events](#).

"protocol": configuration expression<string>, required

The transport protocol used to send event messages to the Syslog daemon.

Set this to **TCP** for Transmission Control Protocol, or to **UDP** for User Datagram Protocol.

"host": configuration expression<string>, required

The hostname of the Syslog daemon to which to send event messages. The hostname must resolve to an IP address.

"port": configuration expression<number>, required

The port of the Syslog daemon to which to send event messages.

The value must be between 0 and 65535.

"connectTimeout": configuration expression<number>, required when using TCP

The number of milliseconds to wait for a connection before timing out.

"facility": configuration expression<enumeration>, required

The Syslog facility to use for event messages. Set to one of the following values:

- **kern** : Kernel messages

- `user` : User-level messages
- `mail` : Mail system
- `daemon` : System daemons
- `auth` : Security/authorization messages
- `syslog` : Messages generated internally by `syslogd`
- `lpr` : Line printer subsystem
- `news` : Network news subsystem
- `uucp` : UUCP subsystem
- `cron` : Clock daemon
- `authpriv` : Security/authorization messages
- `ftp` : FTP daemon
- `ntp` : NTP subsystem
- `logaudit` : Log audit
- `logalert` : Log alert
- `clockd` : Clock daemon
- `local0` : Local use 0
- `local1` : Local use 1
- `local2` : Local use 2
- `local3` : Local use 3
- `local4` : Local use 4
- `local5` : Local use 5
- `local6` : Local use 6
- `local7` : Local use 7

"buffering": *object, optional*

Buffering settings for writing to the system log facility. The default is for messages to be written to the log for each event.

"enabled": *configuration expression<boolean>, optional*

Whether log buffering is enabled.

Default: false.

"maxSize": *configuration expression<number>, optional*

The maximum number of buffered event messages.

Default: 5000.

"severityFieldMappings": *object, optional*

Severity field mappings set the correspondence between audit event fields and Syslog severity values.

The severity field mappings object has the following fields:

"topic": *configuration expression<string>, required*

The audit event topic to which the mapping applies.

Set this to a value configured in `topics`.

"field": *configuration expression<string>, required*

The audit event field to which the mapping applies.

Audit event fields use JSON pointer notation, and are taken from the JSON schema for the audit event content.

"valueMappings": *object, required*

The map of audit event values to Syslog severities, where both the keys and the values are strings.

Syslog severities are one of the following values:

- `emergency` : System is unusable.
- `alert` : Action must be taken immediately.
- `critical` : Critical conditions.
- `error` : Error conditions.
- `warning` : Warning conditions.
- `notice` : Normal but significant condition.
- `informational` : Informational messages.
- `debug` : Debug-level messages.

Example

The following example configures a Syslog audit event handler that writes to the system log daemon on `syslogd.example.com`, port `6514` over TCP with a timeout of 30 seconds. The facility is the first one for local use, and response status is mapped to Syslog informational messages:

```
{
  "class": "org.forgerock.audit.handlers.syslog.SyslogAuditEventHandler",
  "config": {
    "name": "MySyslogAuditEventHandler",
    "topics": ["access"],
    "protocol": "TCP",
    "host": "https://syslogd.example.com",
    "port": 6514,
    "connectTimeout": 30000,
    "facility": "local0",
    "severityFieldMappings": [
      {
        "topic": "access",
        "field": "response/status",
        "valueMappings": {
          "FAILED": "INFORMATIONAL",
          "SUCCESSFUL": "INFORMATIONAL"
        }
      }
    ]
  }
}
```

More information

[org.forgerock.audit.handlers.syslog.SyslogAuditEventHandler](#) 

PingGateway monitoring reference

PingGateway exposes the following monitoring information.

Learn how to configure monitoring in [Monitoring services for PingGateway](#).

- [Monitoring types](#)
- [Metrics at the Prometheus Scrape Endpoint](#)
- [Metrics at the Common REST Monitoring Endpoint \(deprecated\)](#)

Monitoring types

This section describes the data types used in monitoring:

Counter

Cumulative metric for a numerical value that only increases.

Gauge

Metric for a numerical value that can increase or decrease.

Summary

Metric that samples observations, providing a count of observations, sum total of observed amounts, average rate of events, and moving average rates across a sliding time window.

The Prometheus view doesn't provide time-based statistics, because rates can be calculated from the time-series data. Instead, the Prometheus view includes summary metrics whose names have the following suffixes or labels:

- `_count` : number of recorded events
- `_sum` : total sum of recorded events
- `{quantile="0.5"}` : 50% at or below this value
- `{quantile="0.75"}` : 75% at or below this value
- `{quantile="0.95"}` : 95% at or below this value
- `{quantile="0.98"}` : 98% at or below this value
- `{quantile="0.99"}` : 99% at or below this value
- `{quantile="0.999"}` : 99.9% at or below this value

Timer

Metric combining time-series summary statistics.

Common REST views show summaries as JSON objects. JSON summaries have the following fields:

```
{
  "max": number,           // maximum duration recorded
  "mean": number,          // total/count, or 0 if count is 0
  "min": number,           // minimum duration recorded for this metric
  "mean_rate": number,     // average rate
  "p50": number,           // 50% at or below this value
  "p75": number,           // 75% at or below this value
  "p95": number,           // 95% at or below this value
  "p98": number,           // 98% at or below this value
  "p99": number,           // 99% at or below this value
  "p999": number,          // 99.9% at or below this value
  "stddev": number,        // standard deviation of recorded durations
  "m15_rate": number,      // fifteen-minute average rate
  "m5_rate": number,       // five-minute average rate
  "m1_rate": number,       // one-minute average rate
  "duration_units": string, // time unit used in durations
  "rate_units": string,    // event count unit and time unit used in rate
  "seconds_count": number,  // events recorded for this metric
  "count": number,         // events recorded for this metric (deprecated)
  "seconds_total": number   // sum of the durations of events recorded
  "total": number          // sum of the durations of events recorded (deprecated)
}
```


Metrics at the Prometheus Scrape Endpoint

PingGateway exposes a monitoring endpoint where Prometheus can scrape metrics in a standard Prometheus format. Learn more from the [Prometheus website](#).

When PingGateway is set up as described in the [Getting started with PingGateway](#), the Prometheus Scrape Endpoint is available by default at <http://ig.example.com:8085/metrics/prometheus/0.0.4>.

Learn to query the Prometheus Scrape Endpoint in [Monitor the Prometheus Scrape Endpoint](#).



Note

Some `ig_jvm_*` metrics depend on the JVM version and configuration. In particular, GC-related metrics depend on the garbage collector that the server uses. The GC metric names are *unstable* and can change even in a minor JVM release.

Name	Type	Description
<code>ig_cache_evictions_count{cause,content,fully_qualified_name,heap,name,route,router}</code>	Summary	Distribution of 'COLLECTED' eviction events
<code>ig_cache_evictions_sum{cause,content,fully_qualified_name,heap,name,route,router}</code>	Summary	Distribution of 'COLLECTED' eviction events
<code>ig_cache_gets_total{content,fully_qualified_name,heap,name,result,route,router}</code>	Counter	Number of times the cache has been asked for a value and a value was found
<code>ig_cache_loads_seconds_count{content,fully_qualified_name,heap,name,result,route,router}</code>	Summary	Track time spent loading entries unsuccessfully; the 'content' label is one of: 'access_token', 'policy_decision', 'session', 'user_profile'
<code>ig_cache_loads_seconds_sum{content,fully_qualified_name,heap,name,result,route,router}</code>	Summary	Track time spent loading entries unsuccessfully; the 'content' label is one of: 'access_token', 'policy_decision', 'session', 'user_profile'
<code>ig_cache_loads_seconds{content,fully_qualified_name,heap,name,result,route,router,quantile}</code>	Summary	Track time spent loading entries unsuccessfully; the 'content' label is one of: 'access_token', 'policy_decision', 'session', 'user_profile'
<code>ig_http_client_active_connections{local,remote}</code>	Gauge	Number of connections to the remote host currently open
<code>ig_http_client_active_requests{local,method,remote}</code>	Gauge	Number of requests waiting for a response
<code>ig_http_client_active_ws_connections{local,remote}</code>	Gauge	Number of websockets currently open
<code>ig_http_client_bytes_read_total{local,remote}</code>	Counter	Number of bytes received from the remote host

Name	Type	Description
<code>ig_http_client_bytes_read{local, remote}</code>	Counter	[Deprecated] Number of bytes received from the remote host
<code>ig_http_client_bytes_written_total{local, remote}</code>	Counter	Number of bytes sent to the remote host
<code>ig_http_client_bytes_written{local, remote}</code>	Counter	[Deprecated] Number of bytes sent to the remote host
<code>ig_http_client_queue_pending{local, remote}</code>	Gauge	Number of pending elements in queue [DEPRECATED]
<code>ig_http_client_queue_time_seconds_count{local, remote}</code>	Summary	Time spent in queue before being processed
<code>ig_http_client_queue_time_seconds_sum{local, remote}</code>	Summary	Time spent in queue before being processed
<code>ig_http_client_queue_time_seconds{local, remote, quantile}</code>	Summary	Time spent in queue before being processed [DEPRECATED]
<code>ig_http_client_request_bytes_count{local, method, remote}</code>	Summary	Size of requests in bytes
<code>ig_http_client_request_bytes_sum{local, method, remote}</code>	Summary	Size of requests in bytes
<code>ig_http_client_requests_total{local, method, remote}</code>	Counter	Number of requests sent
<code>ig_http_client_requests{local, method, remote}</code>	Counter	[Deprecated] Number of requests sent
<code>ig_http_client_response_bytes_count{code, local, method, remote}</code>	Summary	Size of responses in bytes
<code>ig_http_client_response_bytes_sum{code, local, method, remote}</code>	Summary	Size of responses in bytes
<code>ig_http_client_response_time_seconds_count{code, local, method, remote}</code>	Summary	Response time
<code>ig_http_client_response_time_seconds_sum{code, local, method, remote}</code>	Summary	Response time
<code>ig_http_client_response_time_seconds{code, local, method, remote, quantile}</code>	Summary	Response time

Name	Type	Description
<code>ig_http_client_responses_total{code, local, method, remote}</code>	Counter	Response count with codes
<code>ig_http_client_responses{code, local, method, remote}</code>	Counter	[Deprecated] Response count with codes
<code>ig_http_server_active_connections{local}</code>	Gauge	Number of open connections to the server
<code>ig_http_server_active_requests{local}</code>	Gauge	Number of requests being processed
<code>ig_http_server_active_ws_connections{local}</code>	Gauge	Number of websockets currently open
<code>ig_http_server_bytes_read_total{local}</code>	Counter	Number of bytes received by the server
<code>ig_http_server_bytes_read{local}</code>	Counter	[Deprecated] Number of bytes received by the server
<code>ig_http_server_bytes_written_total{local}</code>	Counter	Number of bytes sent by the server
<code>ig_http_server_bytes_written{local}</code>	Counter	[Deprecated] Number of bytes sent by the server
<code>ig_http_server_request_bytes_count{local, method}</code>	Summary	Size of requests in bytes
<code>ig_http_server_request_bytes_sum{local, method}</code>	Summary	Size of requests in bytes
<code>ig_http_server_request_resets_total{local, method}</code>	Counter	Number of request resets
<code>ig_http_server_request_resets{local, method}</code>	Counter	[Deprecated] Number of request resets
<code>ig_http_server_requests_total{local, method}</code>	Counter	Number of processed requests
<code>ig_http_server_requests{local, method}</code>	Counter	[Deprecated] Number of processed requests
<code>ig_http_server_response_bytes_count{code, local, method}</code>	Summary	Size of responses in bytes
<code>ig_http_server_response_bytes_sum{code, local, method}</code>	Summary	Size of responses in bytes
<code>ig_http_server_response_time_seconds_count{code, local, method}</code>	Summary	Request processing time
<code>ig_http_server_response_time_seconds_sum{code, local, method}</code>	Summary	Request processing time

Name	Type	Description
<code>ig_http_server_response_time_seconds{code, local, method, quantile}</code>	Summary	Request processing time
<code>ig_jvm_available_cpus</code>	Gauge	Number of processors available to the Java virtual machine
<code>ig_jvm_class_loading_loaded_total</code>	Counter	Number of classes loaded since the Java virtual machine started
<code>ig_jvm_class_loading_unloaded_total</code>	Counter	Number of classes unloaded since the Java virtual machine started
<code>ig_jvm_free_memory_bytes</code>	Gauge	Bytes of free memory allocated to the Java virtual machine
<code>ig_jvm_garbage_collector_count_total{name}</code>	Counter	Total number of garbage collections since startup
<code>ig_jvm_garbage_collector_time_total{name}</code>	Counter	Approximate accumulated garbage collection elapsed time in milliseconds
<code>ig_jvm_max_memory_bytes</code>	Gauge	Maximum amount of memory that the Java virtual machine will attempt to use
<code>ig_jvm_memory_usage_committed{location}</code>	Gauge	Amount of memory guaranteed to be available to the Java virtual machine
<code>ig_jvm_memory_usage_init{location}</code>	Gauge	Amount of memory the Java virtual machine requested during startup
<code>ig_jvm_memory_usage_max{location}</code>	Gauge	Maximum amount of memory the Java virtual machine can use for memory management
<code>ig_jvm_memory_usage_pools_committed{name}</code>	Gauge	Amount of memory guaranteed to be available to this memory pool
<code>ig_jvm_memory_usage_pools_init{name}</code>	Gauge	Amount of memory the memory pool requested during startup
<code>ig_jvm_memory_usage_pools_max{name}</code>	Gauge	Maximum amount of memory the memory pool can use for memory management
<code>ig_jvm_memory_usage_pools_used_after_gc{name}</code>	Gauge	Amount of memory the memory pool uses after the most recent garbage collection
<code>ig_jvm_memory_usage_pools_used{name}</code>	Gauge	Amount of memory the memory pool currently uses
<code>ig_jvm_memory_usage_used{location}</code>	Gauge	Maximum amount of memory the Java virtual machine currently uses

Name	Type	Description
<code>ig_jvm_thread_state_daemon</code>	Gauge	Number of live daemon threads
<code>ig_jvm_thread_state{state}</code>	Gauge	Number of threads in the specified state
<code>ig_jvm_used_memory_bytes</code>	Gauge	Amount of memory used by the Java virtual machine
<code>ig_pool_completed_total{pool_name,pool_type}</code>	Counter	Number of elements done with the resource
<code>ig_pool_completed{pool_name,pool_type}</code>	Counter	[Deprecated] Number of elements done with the resource
<code>ig_pool_in_use{pool_name,pool_type}</code>	Gauge	Number of resources used
<code>ig_pool_max_size{pool_name,pool_type}</code>	Gauge	Number of resources used
<code>ig_pool_queue_pending{pool_name,pool_type}</code>	Gauge	Number of pending elements in queue
<code>ig_pool_queue_time_seconds_count{pool_name,pool_type}</code>	Summary	Time spent in queue before being processed
<code>ig_pool_queue_time_seconds_sum{pool_name,pool_type}</code>	Summary	Time spent in queue before being processed
<code>ig_pool_queue_time_seconds{pool_name,pool_type, quantile}</code>	Summary	Time spent in queue before being processed
<code>ig_pool_ratio{pool_name,pool_type}</code>	Gauge	Pool usage ratio, only meaningful if maximum pool size could be determined
<code>ig_pool_usage_seconds_count{pool_name,pool_type}</code>	Summary	Time using a resource
<code>ig_pool_usage_seconds_sum{pool_name,pool_type}</code>	Summary	Time using a resource
<code>ig_pool_usage_seconds{pool_name,pool_type, quantile}</code>	Summary	Time using a resource
<code>ig_reverseproxyhandler_ws_proxy_application_side_read_total{frame_type,fully_qualified_name,heap,name,route,router}</code>	Counter	Number of application side websocket proxy frames received ¹
<code>ig_reverseproxyhandler_ws_proxy_application_side_read_total{frame_type,fully_qualified_name,heap,name}</code>	Counter	Number of application side websocket proxy frames received ¹

Name	Type	Description
<code>ig_reverseproxyhandler_ws_proxy_application_side_write_total{frame_type, fully_qualified_name, heap, name, route, router}</code>	Counter	Number of application side websocket proxy frames sent ¹
<code>ig_reverseproxyhandler_ws_proxy_application_side_write_total{frame_type, fully_qualified_name, heap, name}</code>	Counter	Number of application side websocket proxy frames sent ¹
<code>ig_reverseproxyhandler_ws_proxy_client_side_read_total{frame_type, fully_qualified_name, heap, name, route, router}</code>	Counter	Number of client side websocket proxy frames received ¹
<code>ig_reverseproxyhandler_ws_proxy_client_side_read_total{frame_type, fully_qualified_name, heap, name}</code>	Counter	Number of client side websocket proxy frames received ¹
<code>ig_reverseproxyhandler_ws_proxy_client_side_write_total{frame_type, fully_qualified_name, heap, name, route, router}</code>	Counter	Number of client side websocket proxy frames sent ¹
<code>ig_reverseproxyhandler_ws_proxy_client_side_write_total{frame_type, fully_qualified_name, heap, name}</code>	Counter	Number of client side websocket proxy frames sent ¹
<code>ig_reverseproxyhandler_ws_proxy_tunnels_active{fully_qualified_name, heap, name, route, router}</code>	Gauge	Number of active websocket proxy tunnels ¹
<code>ig_reverseproxyhandler_ws_proxy_tunnels_active{fully_qualified_name, heap, name}</code>	Gauge	Number of active websocket proxy tunnels ¹
<code>ig_reverseproxyhandler_ws_proxy_tunnels_created_total{fully_qualified_name, heap, name, route, router}</code>	Counter	Number of created websocket proxy tunnels ¹
<code>ig_reverseproxyhandler_ws_proxy_tunnels_created_total{fully_qualified_name, heap, name}</code>	Counter	Number of created websocket proxy tunnels ¹
<code>ig_route_request_active{name, route, router}</code>	Gauge	Number of requests being processed
<code>ig_route_request_total{name, route, router}</code>	Counter	Number of requests processed by the router or route since it was deployed
<code>ig_route_response_error_total{name, route, router}</code>	Counter	Number of responses that threw an exception
<code>ig_route_response_null_total{name, route, router}</code>	Counter	Number of responses that were not handled by the route

Name	Type	Description
<code>ig_route_response_status_total{family, name, route, router}</code>	Counter	Number of responses by HTTP status code family. The 'family' label depends on the HTTP status code
<code>ig_route_response_time_seconds_count{name, route, router}</code>	Summary	Response time observations
<code>ig_route_response_time_seconds_sum{name, route, router}</code>	Summary	Response time observations
<code>ig_route_response_time_seconds{name, route, router, quantile}</code>	Summary	Response time observations
<code>ig_router_deployed_routes{fully_qualified_name, heap, name}</code>	Gauge	Number of routes deployed in the configuration
<code>ig_startup_seconds_count{class, id, kind, level, parentId, parentKind, parent_id, parent_kind}</code>	Summary	Top-level startup metrics ²
<code>ig_startup_seconds_count{id, kind, level, parentId, parentKind, parent_id, parent_kind}</code>	Summary	Top-level startup metrics ²
<code>ig_startup_seconds_sum{class, id, kind, level, parentId, parentKind, parent_id, parent_kind}</code>	Summary	Top-level startup metrics ²
<code>ig_startup_seconds_sum{id, kind, level, parentId, parentKind, parent_id, parent_kind}</code>	Summary	Top-level startup metrics ²
<code>ig_startup_seconds{class, id, kind, level, parentId, parentKind, parent_id, parent_kind, quantile}</code>	Summary	Top-level startup metrics ²
<code>ig_startup_seconds{id, kind, level, parentId, parentKind, parent_id, parent_kind, quantile}</code>	Summary	Top-level startup metrics ²
<code>ig_timerdecorator_filter_downstream_seconds_count{decorated_object, heap, name}</code>	Summary	Time to process the request and response in the decorated filter (downstream time)
<code>ig_timerdecorator_filter_downstream_seconds_sum{decorated_object, heap, name}</code>	Summary	Time to process the request and response in the decorated filter (downstream time)
<code>ig_timerdecorator_filter_downstream_seconds{decorated_object, heap, name, quantile}</code>	Summary	Time to process the request and response in the decorated filter (downstream time)
<code>ig_timerdecorator_filter_elapsed_seconds_count{decorated_object, heap, name}</code>	Summary	Time to process the request and response in the decorated filter (elapsed time)
<code>ig_timerdecorator_filter_elapsed_seconds_sum{decorated_object, heap, name}</code>	Summary	Time to process the request and response in the decorated filter (elapsed time)

Name	Type	Description
<code>ig_timerdecorator_filter_elapsed_seconds{decorated_object,heap,name,quantile}</code>	Summary	Time to process the request and response in the decorated filter (elapsed time)
<code>ig_timerdecorator_filter_internal_seconds_count{decorated_object,heap,name}</code>	Summary	Time to process the request and response in the decorated filter (internal time)
<code>ig_timerdecorator_filter_internal_seconds_sum{decorated_object,heap,name}</code>	Summary	Time to process the request and response in the decorated filter (internal time)
<code>ig_timerdecorator_filter_internal_seconds{decorated_object,heap,name,quantile}</code>	Summary	Time to process the request and response in the decorated filter (internal time)
<code>ig_timerdecorator_handler_elapsed_seconds_count{decorated_object,heap,name}</code>	Summary	Time to process the request and response in the decorated handler
<code>ig_timerdecorator_handler_elapsed_seconds_sum{decorated_object,heap,name}</code>	Summary	Time to process the request and response in the decorated handler
<code>ig_timerdecorator_handler_elapsed_seconds{decorated_object,heap,name,quantile}</code>	Summary	Time to process the request and response in the decorated handler

¹ The "reverseproxyhandler" in the metric name reflects the name of the ReverseProxyHandler component in the PingGateway configuration.

² The present implementation includes the deprecated `parentId` and `parentKind` dimensions. Use the equivalent `parent_id` and `parent_kind` dimensions instead.

Metrics at the Common REST Monitoring Endpoint (deprecated)

The Common REST Monitoring Endpoint exposes metrics as a JSON format monitoring resource.

When PingGateway is set up as described in the documentation, the endpoint is `http://ig.example.com:8085/metrics/api?_queryFilter=true`.

For an example that queries the Common REST Monitoring Endpoint, refer to [Monitor the Common REST Monitoring Endpoint](#).

Route metrics at the Common REST Monitoring Endpoint (deprecated)

Route metrics at the Common REST Monitoring Endpoint are published with an `_id` in the following pattern:

- `heap.router-name.route.route-name.metric`

The following table summarizes the recorded metrics:

Name	Monitoring type	Description
<code>request</code>	Counter	Number of requests processed by the router or route since it was deployed.
<code>request.active</code>	Gauge	Number of requests being processed by the router or route at this moment.
<code>response.error</code>	Counter	Number of responses that threw an exception.
<code>response.null</code>	Counter	Number of responses that were not handled by PingGateway.
<code>response.status.client_error</code>	Counter	Number of responses with an HTTP status code <code>400 - 499</code> , indicating client error.
<code>response.status.informational</code>	Counter	Number of responses with an HTTP status code <code>100 - 199</code> , indicating that they are provisional responses.
<code>response.status.redirection</code>	Counter	Number of responses with an HTTP status code <code>300 - 399</code> , indicating a redirect.
<code>response.status.server_error</code>	Counter	Number of responses with an HTTP status code <code>500 - 599</code> , indicating server error.
<code>response.status.successful</code>	Counter	Number of responses with an HTTP status code <code>200 - 299</code> , indicating success.
<code>response.status.unknown</code>	Counter	Number of responses with an HTTP status code <code>600 - 699</code> , indicating that a request failed and was not executed.
<code>response.time</code>	Timer	Time-series summary statistics.

Router metrics at the Common REST Monitoring Endpoint (deprecated)

Router metrics at the Common REST Monitoring Endpoint are JSON objects, with the following form:

- `[heap name].[router name].deployed-routes`

The following table summarizes the recorded metrics:

Name	Monitoring type	Description
<code>deployed-routes</code>	Gauge	Number of routes deployed in the configuration.

Timer metrics at the Common REST Monitoring Endpoint (deprecated)

This section describes the metrics recorded at the Common REST Monitoring Endpoint.

When PingGateway is set up as described in the documentation, the endpoint is `http://ig.example.com:8085/metrics/api?_queryFilter=true`.

Metrics are published with an `_id` in the following pattern:

```
heap.router-name.route-name.decorator-name.object
```

Timer metrics at the Common REST Monitoring Endpoint

Name	Monitoring type	Description
<code>elapsed</code>	Timer	Time to process the request and response in the decorated handler, or in the decorated filter and its downstream filters and handler.
<code>internal</code>	Timer	Time to process the request and response in the decorated filter.
<code>downstream</code>	Timer	Time to process the request and response in filters and handlers that are downstream of the decorated filter.

Throttling policies

To protect applications from being overused by clients, use a [ThrottlingFilter](#) with one of the following policies to limit how many requests clients can make in a defined time.

- [DefaultRateThrottlingPolicy](#)
- [MappedThrottlingPolicy](#)
- [ScriptableThrottlingPolicy](#)

DefaultRateThrottlingPolicy

Provides a default throttling rate if the delegating throttling policy returns `null`.

Usage

```
{
  "name": string,
  "type": "ThrottlingFilter",
  "config": {
    "requestGroupingPolicy": expression,
    "throttlingRatePolicy": {
      "type": "DefaultRateThrottlingPolicy",
      "config": {
        "delegateThrottlingRatePolicy": ThrottlingRatePolicy reference,
        "defaultRate": {
          "numberOfRequests": configuration expression<number>,
          "duration": configuration expression<duration>
        }
      }
    }
  }
}
```

Properties

"delegateThrottlingRatePolicy": *ThrottlingRatePolicy* [reference](#), required

The policy to which the default policy delegates the throttling rate. The `DefaultRateThrottlingPolicy` delegates management of throttling to the policy specified by `delegateThrottlingRatePolicy`.

If `delegateThrottlingRatePolicy` returns `null`, the `defaultRate` is used.

For information about policies to use, refer to [MappedThrottlingPolicy](#) and [ScriptableThrottlingPolicy](#).

"defaultRate": *object*, required

The default throttling rate to apply if the delegating policy returns `null`.

"numberOfRequests": *configuration expression<integer>*, required

The number of requests allowed through the filter in the time specified by `"duration"`.

"duration": *configuration expression<duration>*, required

A time interval during which the number of requests passing through the filter is counted.

Example

For an example of how this policy is used, refer to [Example of a scriptable throttling policy](#).

More information

[org.forgerock.openig.filter.throttling.DefaultRateThrottlingPolicyHeaplet](https://github.com/forgereck/openig.filter.throttling.DefaultRateThrottlingPolicyHeaplet) [↗](#)

MappedThrottlingPolicy

Maps different throttling rates to different groups of requests, according to the evaluation of `throttlingRateMapper`.

Usage

```
{
  "name": string,
  "type": "ThrottlingFilter",
  "config": {
    "requestGroupingPolicy": runtime expression<string>,
    "throttlingRatePolicy": {
      "type": "MappedThrottlingPolicy",
      "config": {
        "throttlingRateMapper": runtime expression<string>,
        "throttlingRatesMapping": {
          "mapping1": {
            "numberOfRequests": configuration expression<number>,
            "duration": configuration expression<duration>
          },
          "mapping2": {
            "numberOfRequests": configuration expression<number>,
            "duration": configuration expression<duration>
          }
        },
        "defaultRate": {
          "numberOfRequests": configuration expression<number>,
          "duration": configuration expression<duration>
        }
      }
    }
  }
}
```

Properties

"throttlingRateMapper": *runtime expression<string>, required*

An expression to categorize requests for mapping to a throttling rate in the `throttlingRatesMapping`.

If this parameter is null or doesn't match any specified mappings, the default throttling rate is applied.

"throttlingRatesMapping": *object, required*

A map of throttling rate by request group. Requests are categorized into groups by the evaluation of the expression `"throttlingRateMapper"`.

"mapping1" and "mapping2": *string, required*

The evaluation of the expression `"throttlingRateMapper"`.

The number of mappings isn't limited to two.

"numberOfRequests": *configuration expression<integer>, required*

The number of requests allowed through the filter in the time specified by `"duration"`.

"duration": *configuration expression<duration>, required*

A time interval during which the number of requests passing through the filter is counted.

"defaultRate": *object*, required

The default throttling rate to apply if the evaluation of the expression `"throttlingRateMapper"` is null or isn't mapped to a throttling rate.

"numberOfRequests": *configuration expression<integer>*, required

The number of requests allowed through the filter in the time specified by `"duration"`.

"duration": *configuration expression<duration>*, required

A time interval during which the number of requests passing through the filter is counted.

Example of a mapped throttling policy

In the following example, requests from users with different statuses are mapped to different throttling rates. For information about how to set up and test this example, see [Configure Mapped Throttling](#).

```

{
  "name": "00-throttle-mapped",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/throttle-mapped')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [
              "mail",
              "employeenumber"
            ],
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "token-resolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "amService": "AmService-1",
                "providerHandler": {
                  "type": "Chain",
                  "config": {
                    "filters": [
                      {
                        "type": "HttpBasicAuthenticationClientFilter",
                        "config": {
                          "username": "ig_agent",
                          "passwordSecretId": "agent.secret.id",
                          "secretsProvider": "SystemAndEnvSecretStore-1"
                        }
                      }
                    ],
                    "handler": "ForgeRockClientHandler"
                  }
                }
              }
            }
          }
        }
      ]
    }
  }
},

```

```

{
  "name": "ThrottlingFilter-1",
  "type": "ThrottlingFilter",
  "config": {
    "requestGroupingPolicy": "${contexts.oauth2.accessToken.info.mail}",
    "throttlingRatePolicy": {
      "name": "MappedPolicy",
      "type": "MappedThrottlingPolicy",
      "config": {
        "throttlingRateMapper": "${contexts.oauth2.accessToken.info.status}",
        "throttlingRatesMapping": {
          "gold": {
            "numberOfRequests": 6,
            "duration": "10 s"
          },
          "silver": {
            "numberOfRequests": 3,
            "duration": "10 s"
          },
          "bronze": {
            "numberOfRequests": 1,
            "duration": "10 s"
          }
        },
        "defaultRate": {
          "numberOfRequests": 1,
          "duration": "10 s"
        }
      }
    }
  }
},
"handler": "ReverseProxyHandler"
}

```

Source: [00-throttle-mapped.json](#)

More information

[org.forgerock.openig.filter.throttling.MappedThrottlingPolicyHeaplet](#)

ScriptableThrottlingPolicy

Uses a script to look up the throttling rates to apply to groups of requests.

The script can store the mapping for the throttling rate in memory, and can use a more complex mapping mechanism than that used in the `MappedThrottlingPolicy`. For example, the script can map the throttling rate for a range of IP addresses. The script can also query an external database or read the mapping from a file.

Scripts must return a `Promise<ThrottlingRate, Exception>` or a `ThrottlingRate`.

For information about script properties, available global objects, and automatically imported classes, refer to [PingGateway scripts](#).

- For an example of how to create a ScriptableThrottlingPolicy in Studio, refer to [Configure scriptable throttling](#).

Usage

```
{
  "type": "ThrottlingFilter",
  "config": {
    "requestGroupingPolicy": runtime expression<string>,
    "throttlingRatePolicy": {
      "name": string,
      "type": "ScriptableThrottlingPolicy",
      "config": {
        "type": configuration expression<string>,
        "file": configuration expression<string>, // Use either "file"
        "source": [ string, ... ],                // or "source", but not both
        "args": map,
        "clientHandler": Handler reference
      }
    }
  }
}
```

Properties

For information about properties for ScriptableThrottlingPolicy, refer to [PingGateway scripts](#).

Example of a scriptable throttling policy

In the following example, the `DefaultRateThrottlingPolicy` delegates the management of throttling to the scriptable throttling policy. For information about how to set up and test this example, refer to [Configure scriptable throttling](#).


```

{
  "name": "00-throttle-scriptable",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/throttle-scriptable')}",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam/"
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "name": "OAuth2ResourceServerFilter-1",
          "type": "OAuth2ResourceServerFilter",
          "config": {
            "scopes": [
              "mail",
              "employeenumber"
            ],
            "requireHttps": false,
            "accessTokenResolver": {
              "name": "token-resolver-1",
              "type": "TokenIntrospectionAccessTokenResolver",
              "config": {
                "amService": "AmService-1",
                "providerHandler": {
                  "type": "Chain",
                  "config": {
                    "filters": [
                      {
                        "type": "HttpBasicAuthenticationClientFilter",
                        "config": {
                          "username": "ig_agent",
                          "passwordSecretId": "agent.secret.id",
                          "secretsProvider": "SystemAndEnvSecretStore-1"
                        }
                      }
                    ],
                    "handler": "ForgeRockClientHandler"
                  }
                }
              }
            }
          }
        }
      ]
    }
  }
},

```

```

{
  "name": "ThrottlingFilter-1",
  "type": "ThrottlingFilter",
  "config": {
    "requestGroupingPolicy": "${contexts.oauth2.accessToken.info.mail}",
    "throttlingRatePolicy": {
      "type": "DefaultRateThrottlingPolicy",
      "config": {
        "delegateThrottlingRatePolicy": {
          "name": "ScriptedPolicy",
          "type": "ScriptableThrottlingPolicy",
          "config": {
            "type": "application/x-groovy",
            "source": [
              "if (contexts.oauth2.accessToken.info.status == status) {",
              "  return new ThrottlingRate(rate, duration)",
              "} else {",
              "  return null",
              "}"
            ],
            "args": {
              "status": "gold",
              "rate": 6,
              "duration": "10 seconds"
            }
          }
        },
        "defaultRate": {
          "numberOfRequests": 1,
          "duration": "10 s"
        }
      }
    }
  },
  "handler": "ReverseProxyHandler"
}

```

Source: [00-throttle-scriptable.json](#)

More information

org.forgerock.openig.filter.throttling.ScriptableThrottlingPolicy.Heaplet

Miscellaneous PingGateway configuration objects

- [AmService](#)
- [ClientRegistration](#)
- [ClientTlsOptions](#)
- [Delegate](#)

- [InMemorySessionManager](#)
- [Issuer](#)
- [IssuerRepository \(deprecated\)](#)
- [JdbcDataSource](#)
- [JwtSession \(deprecated\)](#)
- [JwtSessionManager](#)
- [KerberosIdentityAssertionPlugin](#)
- [KeyManager \(deprecated\)](#)
- [KeyStore \(deprecated\)](#)
- [PingOneService](#)
- [ProxyOptions](#)
- [RequestResourceUriProvider](#)
- [ScheduledExecutorService](#)
- [ScriptableIdentityAssertionPlugin](#)
- [ScriptableResourceUriProvider](#)
- [ServerTlsOptions](#)
- [TemporaryStorage](#)
- [TrustAllManager](#)
- [UmaService](#)

AmService

Holds information about the configuration of an instance of AM. The AmService is available to PingGateway filters that communicate with that instance.

When PingGateway uses an AmService, PingGateway is positioned as the client of the service. By default, PingGateway is subscribed to Websocket notifications from AM, and the WebSocket connection can be secured by ClientTlsOptions.

Usage

```
{
  "name": string,
  "type": "AmService",
  "config": {
    "agent": {
      "username": configuration expression<string>,
      "passwordSecretId": configuration expression<secret-id>,
      "journey": configuration expression<string>
    },
    "secretsProvider": SecretsProvider reference,
    "url": configuration expression<url>,
    "realm": configuration expression<string>,
    "amHandler": Handler reference,
    "notifications": {
      "audit": {
        "auditService": AuditService reference,
        "auditIgnoredNotifications": configuration expression<boolean>
      },
      "enabled": configuration expression<boolean>,
      "initialConnectionAttempts": configuration expression<number>,
      "reconnectDelay": configuration expression<duration>,
      "renewalDelay": configuration expression<duration>,
      "heartbeatInterval": configuration expression<duration>,
      "connectionTimeout": configuration expression<duration>,
      "idleTimeout": configuration expression<duration>,
      "tls": ClientTlsOptions reference,
      "proxyOptions": ProxyOptions reference,
      "vertx": object
    },
    "sessionCache": {
      "enabled": configuration expression<boolean>,
      "executor": Executor service reference,
      "maximumSize": configuration expression<number>,
      "maximumTimeToCache": configuration expression<duration>,
      "onNotificationDisconnection": configuration expression<enumeration>
    },
    "sessionIdleRefresh": {
      "enabled": configuration expression<boolean>,
      "interval": configuration expression<duration>
    },
    "sessionProperties": [ configuration expression<string>, ... ],
    "ssoTokenHeader": configuration expression<string>,
    "version": configuration expression<string>
  }
}
```

Properties

agent

"agent": *object*, required

An PingGateway agent profile. When the agent is authenticated, PingGateway can use the token for tasks, such as getting the user profile, making policy evaluations, and connecting to the AM notification endpoint.

"username": configuration expression<string>, required

Name of the AM agent profile.

"passwordSecretId": configuration expression<secret-id>, required

The secret ID of the AM agent password.

This secret ID must point to a [GenericSecret](#).

"journey": configuration expression<string>, required

The authentication journey (tree) to use when authenticating to AM.

Default: `Agent`

secretsProvider

`"secretsProvider"` : *SecretsProvider* [reference](#), required

The [SecretsProvider](#) to query for the agent password.

url

`"url"` : configuration expression<url>, required

The URL of the AM service.

When AM is running locally, this value could be `https://am.example.com/openam`. When AM is running in PingOne Advanced Identity Cloud, this value could be `https://myTenant.forgeblocks.com/am`.

realm

`"realm"` : configuration expression<string>, optional

The AM realm in which the PingGateway agent is created.

Default: `/` (top level realm).

amHandler

`"amHandler"` : *Handler* [reference](#), optional

The [Handler](#) to use for communicating with AM. In production, use a [ClientHandler](#) capable of making an HTTPS connection to AM.

AmService doesn't use `amHandler` to subscribe to WebSocket notifications from AM. To subscribe to WebSocket notifications from AM, configure a [ClientTlsOptions](#) object in the heap and refer to it from the `amHandler` object and `notifications.tls`.

For auditing, use a [ForgeRockClientHandler](#) to send a Common Audit transaction ID when communicating with protected applications. Alternatively, configure this handler as a chain with a [TransactionIdOutboundFilter](#):

```
"amHandler": {  
  "type": "Chain",  
  "config": {  
    "handler": "MySecureClientHandler",  
    "filters": [ "TransactionIdOutboundFilter" ]  
  }  
}
```

Default: `ForgeRockClientHandler`

notifications

"notifications": *object, optional*

Configure a WebSocket notification service to subscribe to WebSocket notifications from AM.

To subscribe to WebSocket notifications from AM, configure a `ClientTlsOptions` object in the heap and refer to it from the `amHandler` object and `notifications.tls`. Alternatively, use `proxyOptions` to share a proxy configuration between the `amHandler` and the notification service.

Learn more in [WebSocket notifications](#).

"audit": *object, optional*

Audit service settings.

"auditService": *Handler reference, optional*

The `AuditService` to use for notifications.

This audit service must enable the `notifications` topic as in the following example:

```

{
  "name": "JsonAuditService",
  "type": "AuditService",
  "config": {
    "config": {
      "filterPolicies": {
        "field": {
          "_comment": "Optionally hide specific items; here, the universalId:",
          "excludeIf": [
            "/notifications/notification/body/universalId"
          ]
        }
      }
    },
    "eventHandlers": [
      {
        "class": "org.forgerock.audit.handlers.json.JsonAuditEventHandler",
        "config": {
          "name": "json",
          "logDirectory": "&{ig.instance.dir}/auditLogs",
          "topics": [
            "notifications"
          ]
        }
      }
    ]
  }
}

```

The file suffix depends on the audit service implementation. For this example, the file's named `notifications.audit.json`.

With tracing enabled as in the example, the traces include an additional attribute in the span to indicate the topic triggered, `code.namespace`, containing either `access` or `notifications`.

The `transactionId` in an audit event doesn't come from AM. PingGateway generates a new `transactionId` for each event. At present, you can't link the AM event that generated the notification with the PingGateway audit event.

Default: the `AuditService` defined in the heap

"auditIgnoredNotifications": *configuration expression*<boolean>, optional

If `true`, audit all notifications. If `false` audit only notifications that trigger a change in state, such as a removing an item from a cache.

If the notification triggered something to change, PingGateway records `"triggered":true` in the audit log entry. Otherwise, it records `"triggered":false`.

Default: `false`

"enabled": *configuration expression*<boolean>, optional

A flag to enable WebSocket notifications. Set to `false` to disable WebSocket notifications.

Default: `true`

"initialConnectionAttempts": configuration expression<number>, optional

The maximum number of times PingGateway attempts to open a WebSocket connection before failing to deploy a route. For no limit, set this property to `-1`.

If the WebSocket connection fails **after** it has been opened and the route is deployed, PingGateway attempts to reconnect to it an unlimited number of times.

Default: `5`

"reconnectDelay": configuration expression<duration>, optional

The time between attempts to reestablish a lost WebSocket connection.

When a WebSocket connection is lost, PingGateway waits for this delay and attempts to reestablish the connection. If subsequent attempts fail, PingGateway waits and tries again an unlimited number of times.

Default: `5 seconds`

"renewalDelay": configuration expression<duration>, optional

The time before automatically renewing a WebSocket connection between PingGateway and AM. PingGateway renews connections transparently.

PingOne Advanced Identity Cloud closes WebSocket connections every 60 minutes. This property is set by default to prevent connection closure by automatically renewing connections every 50 minutes.

Set to `0` or `unlimited` to never automatically renew connections.

Default: `50 minutes`

"heartbeatInterval": configuration expression<duration>, optional

The interval at which the AmService issues a heartbeat on WebSocket connections. When activity on the connection is low, the heartbeat prevents middleware or policies situated between PingGateway and AM from closing the connection for timeout.

Set to zero or unlimited to disable heartbeats.

Default: `1 minute`

"connectionTimeout": configuration expression<duration>, optional

The time PingGateway waits to establish a Websocket connection to AM before it considers the attempt as failed.

Default: `60 seconds`

"idleTimeout": configuration expression<duration>, optional

The time that a WebSocket connection to AM can be inactive before PingGateway closes it.

Default: `unlimited`

"tls": ClientTlsOptions [reference](#), optional

Configure options for WebSocket connections to TLS-protected endpoints.

Define a [ClientTlsOptions](#) object inline or in the heap.

Default: Connections to TLS-protected endpoints aren't configured.

"proxyOptions": *ProxyOptions* [reference](#)>, optional

A proxy server to which requests can be submitted. Use this property to relay requests to other parts of the network. For example, use it to submit requests from an internal network to the internet.

Provide the name of a [ProxyOptions](#) object defined in the heap or an inline configuration.

Default: A heap object named `ProxyOptions`.

"vertx": *object*, optional

Vert.x-specific configuration for WebSocket connections to AM. Vert.x values are evaluated as configuration expressions.

Use the Vert.x options described in [VertxOptions](#) [↗](#).

sessionCache

"sessionCache" : *object*, optional

In AM, if the realm includes a customized session property safelist, include `AMCtxId` in the list of properties. The customized session property safelist overrides the global session property safelist.

Enable and configure caching of session information from AM based on [Caffeine](#) [↗](#).

When `sessionCache` is enabled, PingGateway can reuse session token information without repeatedly asking AM to verify the token. Each instance of AmService has an independent cache content. The cache isn't shared with other AmService instances, either in the same or different routes and is not distributed among clustered PingGateway instances.

When `sessionCache` is disabled, PingGateway must ask AM to verify the token for each request.

PingGateway evicts session info entries from the cache for the following reasons:

- AM cache timeout, based on whichever of the following events occur first:
 - `maxSessionExpirationTime` from SessionInfo
 - `maxSessionTimeout` from the AmService configuration

When PingGateway evicts session info entries from the cache, the next time the token is presented, PingGateway must ask AM to verify the token.

- If WebSocket notifications are enabled, AM session revocation; for example, when a user logs out of AM.

When WebSocket notifications are enabled, PingGateway evicts a cached token almost as soon as it is revoked on AM, and in this way, stays synchronized with AM. Later requests to PingGateway that present the revoked token are rejected.

When WebSocket notifications are disabled, the token remains in the cache after it is revoked on AM. Later requests to PingGateway that present the revoked token are considered as valid and can cause incorrect authentication and authorization decisions until its natural eviction from the cache.

"enabled": configuration expression<boolean>, optional

Enable caching.

Default: `false`

"executor": Executor service reference, optional

An executor service to schedule the execution of tasks, such as the eviction of entries in the cache.

Default: `ForkJoinPool.commonPool()`

"maximumSize": configuration expression<number>, optional

The maximum number of entries the cache can contain.

Default: Unlimited/unbound

"maximumTimeToCache": configuration expression<duration>, optional

The maximum duration for which to cache session info. Set this duration to be less than the idle timeout of AM.

If `maximumTimeToCache` is longer than `maxSessionExpirationTime` from `SessionInfo`, `maxSessionExpirationTime` is used.

Default:

- When `sessionIdleRefresh` is set, idle timeout of AM minus 30 seconds.
- When `sessionIdleRefresh` is not set, `maxSessionExpirationTime`, from `SessionInfo`.

"onNotificationDisconnection": configuration expression<enumeration>, optional

The strategy to manage the cache when the WebSocket notification service is disconnected, and PingGateway receives no notifications for AM events. If the cache is not cleared it can become outdated, and PingGateway can allow requests on revoked sessions or tokens.

Cached entries that expire naturally while the notification service is disconnected are removed from the cache.

Use one of the following values:

- `NEVER_CLEAR`
 - When the notification service is disconnected:
 - Continue to use the existing cache.
 - Deny access for requests that aren't cached, but don't update the cache with these requests.
 - When the notification service is reconnected:
 - Continue to use the existing cache.
 - Query AM for incoming requests that aren't found in the cache, and update the cache with these requests.

- `CLEAR_ON_DISCONNECT`

- When the notification service is disconnected:
 - Clear the cache.
 - Deny access to all requests, but don't update the cache with these requests.
- When the notification service is reconnected:
 - Query AM for all requests that aren't found in the cache. (Because the cache was cleared, the cache is empty after reconnection.)
 - Update the cache with these requests.

- `CLEAR_ON_RECONNECT`

- When the notification service is disconnected:
 - Continue to use the existing cache.
 - Deny access for requests that aren't cached, but don't update the cache with these requests.
- When the notification service is reconnected:
 - Query AM for all requests that aren't found in the cache. (Because the cache was cleared, the cache is empty after reconnection.)
 - Update the cache with these requests.

Default: `CLEAR_ON_DISCONNECT`

sessionIdleRefresh

`"sessionIdleRefresh"`: *object*, optional

Enable and configure periodic refresh of idle sessions. When this property is enabled, PingGateway requests session refresh:

- The first time PingGateway gets an SSO token from AM, irrespective of the age of the token.
- When `sessionIdleRefresh.interval` has elapsed.

Use this property when AM is using CTS-based sessions. AM doesn't monitor idle time for client-side sessions and so refresh requests are ignored.

When the `SingleSignOnFilter` is used for authentication with AM, AM can view a session as idle even though a user continues to interact with PingGateway. The user session eventually times out, and the user must reauthenticate.

When the `SingleSignOnFilter` filter is used with the `PolicyEnforcementFilter`, the session is refreshed each time PingGateway requests a policy decision from AM. The session is less likely to become idle, and this property isn't required.

"enabled": configuration expression<boolean>, optional

Enable refresh of idle sessions.

Default: `false`

"interval": configuration expression<duration>, optional

Duration to wait after a session becomes idle before requesting a session refresh.

Set the refresh interval in line with the latest access time update frequency of AM. For example, if PingGateway requests a refresh every 60 seconds, but the update frequency of AM is 5 minutes, AM ignores most of the PingGateway requests.

**Important**

Each session refresh must be reflected in the AM core token service. Setting the interval to a duration lower than one minute can adversely impact AM performance.

Default: 5 minutes

sessionProperties

"sessionProperties" : array of configuration expression<strings>, optional

The list of user session properties to retrieve from AM by the [SessionInfoFilter](#).

Default: All available session properties are retrieved from AM.

ssoTokenHeader

"ssoTokenHeader" : configuration expression<string>, optional

The header name or cookie name where this AM server expects to find SSO tokens.

If a value for **ssoTokenHeader** is provided, PingGateway uses that value. Otherwise, PingGateway queries the AM **/serverinfo/*** endpoint for the header or cookie name.

Default: Empty. PingGateway queries AM for the cookie name.

version

"version" : configuration expression<string>, optional

The version number of the AM server. PingGateway uses the AM version to establish endpoints for its interaction with AM.

The AM version is derived as follows, in order of precedence:

- Discovered value: The AmService discovers the AM version.
If **"version"** is configured with a different value, the AmService ignores the value of **"version"** and logs a warning.
- Value in **"version"** : The AmService cannot discover the AM version and **"version"** is configured.
- Default value of AM 7.3: When the AmService cannot discover the AM version and **"version"** is not configured.

If you use a feature that is supported only in a higher AM version than discovered or specified, PingGateway logs a message or throws an error.

Default: AM 7.3.

More information

org.forgerock.openig.tools.am.AmService 

ClientRegistration

A ClientRegistration holds information about registration with an OAuth 2.0 Authorization Server or OpenID Provider.

The configuration includes the client credentials that are used to authenticate to the identity provider. The client credentials can be included directly in the configuration, or retrieved in some other way using an expression, described in [Expressions](#).

Usage

```
{
  "name": string,
  "type": "ClientRegistration",
  "config": {
    "clientId": configuration expression<string>,
    "issuer": Issuer reference,
    "pkceMethod": configuration expression<string>,
    "scopes": [ configuration expression<string>, ...],
    "registrationHandler": Handler reference,
    "authenticatedRegistrationHandler": Handler reference,
    "clientSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference,
    "skipSignatureVerification": configuration expression<boolean>
  }
}
```

Properties

clientId

`"clientId"` : configuration expression<[string](#)>, required

The `client_id` obtained when registering with the Authorization Server. [PingGateway expressions](#) describes alternatives to setting this to a literal string.

When using a login page with an [AuthorizationCodeOAuth2ClientFilter](#), the link to the `/login` endpoint must refer to a valid `clientId` identified by this property.

issuer

`"issuer"` : Issuer [reference](#), required

The provider configuration to use for this client registration. Provide the name of an [Issuer](#) defined in the heap or an inline Issuer configuration object.

pkceMethod

`"pkceMethod"` : configuration expression<[string](#)>, optional

The [Proof Key for Code Exchange \(PKCE\)](#) code challenge method; one of:

- `S256` : Use a SHA256-based encoding of the code verifier.
- `none` : Disable PKCE.

Default: `S256`

scopes

`"scopes"` : array of configuration expression<strings>, optional

Array of scope strings to present to the user for approval and to include in tokens for decisions about access to protected resources.

Default: Empty

registrationHandler

`"registrationHandler"` : Handler [reference](#), optional

HTTP client handler to invoke during client registration, to access endpoints that don't require client authentication. Provide either the name of a [Handler](#) defined in the heap or an inline Handler configuration object.

Usually set this to the name of a [ClientHandler](#) configured in the heap or a [Chain](#) that ends in a ClientHandler.

Default: [ClientHandler](#)

authenticatedRegistrationHandler

`"authenticatedRegistrationHandler"` : Handler [reference](#), optional

HTTP client handler to invoke during client registration to access endpoints that require client authentication. Configure this property as a [Chain](#) with one of the following filters for client authentication:

- [ClientSecretBasicAuthenticationFilter](#)
- [ClientSecretPostAuthenticationFilter](#)
- [EncryptedPrivateKeyJwtClientAuthenticationFilter](#)
- [PrivateKeyJwtClientAuthenticationFilter](#)

The following example relies on server-side TLS to protect the client credentials:

```
{
  "name": "AuthenticatedRegistrationHandler",
  "type": "Chain",
  "config": {
    "filters": [
      {
        "type": "ClientSecretBasicAuthenticationFilter",
        "config": {
          "clientId": "service-client",
          "clientSecretId": "client.secret.id",
          "secretsProvider": "SystemAndEnvSecretStore-1"
        }
      }
    ],
    "handler": "ForgeRockClientHandler"
  }
}
```

The following example uses a [ClientSecretBasicAuthenticationFilter](#) with a [ClientHandler](#) to add transaction IDs to requests and configure mutual TLS (mTLS). In the [ClientTlsOptions](#) configuration, the `SecretsKeyManager` holds the client keys and the `SecretsTrustManager` trusts the server CA certificates.

```

{
  "name": "AuthenticatedRegistrationHandler",
  "type": "Chain",
  "config": {
    "filters": [
      {
        "type": "ClientSecretBasicAuthenticationFilter",
        "config": {
          "clientId": "service-client",
          "clientSecretId": "client.secret.id",
          "secretsProvider": "SystemAndEnvSecretStore-1"
        }
      }
    ],
    "handler": {
      "name": "mTlsClientHandler",
      "type": "Chain",
      "config": {
        "filters": [ "TransactionIdOutboundFilter" ],
        "handler": {
          "type": "ClientHandler",
          "config": {
            "tls": {
              "type": "ClientTlsOptions",
              "config": {
                "keyManager": [ "SecretsKeyManager" ],
                "trustManager": [ "SecretsTrustManager" ]
              }
            }
          }
        }
      }
    }
  }
}

```

Default: `registrationHandler` with no authentication filter

clientSecretId

`"clientSecretId"` : *configuration expression<secret-id>, required to verify ID tokens with HMAC-based signatures*

The secret ID of the client secret.

Set this for ID token validation when the OpenID provider signs ID tokens using an HMAC algorithm. In addition, use a `"secretsProvider"` to access the client secret.

This secret ID must point to a [GenericSecret](#).

secretsProvider

`"secretsProvider"` : *SecretsProvider reference, required to verify ID tokens with HMAC-based signatures*

The [SecretsProvider](#) to query for the client's [GenericSecret](#).

When the OpenID provider signs ID tokens using an HMAC algorithm, use this provider to access the `"clientSecretId"`.

skipSignatureVerification

"skipSignatureVerification" : *configuration expression* [<boolean>](#), *optional*

A flag for signature validation of OpenID Connect ID tokens:

- `true` : Don't validate signatures.



Important

Before using the value `true`, consider the security impact on your deployment. Use only when the connection between the Issuer and Client is direct and well secured.

- `false` : Validate signatures.

Default: `false`

Example

Learn more in [AM as OIDC provider](#).

More information

[org.forgerock.openig.filter.oauth2.client.ClientRegistration](#) 

[Issuer](#)

[The OAuth 2.0 Authorization Framework](#) 

[The OAuth 2.0 Authorization Framework: Bearer Token Usage](#) 

[OpenID Connect](#) 

ClientTlsOptions

Configures connections to the TLS-protected endpoint of servers, when PingGateway is client-side.

When PingGateway is *client-side*, PingGateway sends requests to a proxied application, or requests services from a third-party application. PingGateway is acting as a client of the application, and the application is acting as a server.

Use ClientTlsOptions in [ClientHandler](#), [ReverseProxyHandler](#), and [AmService](#).

Usage

```
{
  "name": string,
  "type": "ClientTlsOptions",
  "config": {
    "keyManager": [ Key manager reference, ...],
    "trustManager": [ Trust manager reference, ...],
    "sslCipherSuites": [ configuration expression<string>, ...],
    "sslContextAlgorithm": configuration expression<string>,
    "sslEnabledProtocols": [ configuration expression<string>, ...],
    "alpn": object,
    "hostnameVerifier": configuration expression<enumeration>,
    "offloadHandshake": configuration expression<boolean>
  }
}
```

Properties

"keyManager": array of key manager [references](#), optional

One or more of the following objects to serve the same secret key and certificate pair for TLS connections to all server names in the deployment:

- [SecretsKeyManager](#)
- [KeyManager \(deprecated\)](#)

Key managers are used to prove the identity of the local peer during TLS handshake, as follows:

- When `ServerTlsOptions` is used in an HTTPS connector configuration (server-side), the key managers to which `ServerTlsOptions` refers are used to prove this PingGateway's identity to the remote peer (client-side). This is the usual TLS configuration setting (without mTLS).
- When `ClientTlsOptions` is used in a `ClientHandler` or `ReverseProxyHandler` configuration (client-side), the key managers to which `ClientTlsOptions` refers are used to prove this PingGateway's identity to the remote peer (server-side). This configuration is used in mTLS scenarios.

Default: None

"trustManager": array of trust manager [references](#), optional

One or more of the following objects to manage PingGateway's public key certificates:

- [SecretsTrustManager](#)
- [TrustAllManager](#)
- [TrustManager \(deprecated\)](#)



Important

When the `TrustManager` object is configured, only certificates accessible through that `TrustManager` are trusted. Default and system certificates are no longer trusted.

Trust managers verify the identity of a peer by using certificates, as follows:

- When `ServerTlsOptions` is used in an HTTPS connector configuration (server-side), `ServerTlsOptions` refers to trust managers that verify the remote peer's identity (client-side). This configuration is used in mTLS scenarios.
- When `ClientTlsOptions` is used in a `ClientHandler` or a `ReverseProxyHandler` configuration (client-side), `ClientTlsOptions` refers to trust managers that verify the remote peer's identity (server-side). This is the usual TLS configuration setting (without mTLS).

If `trustManager` is not configured, PingGateway uses the default Java truststore to verify the remote peer's identity. The default Java truststore depends on the Java environment. For example, `$JAVA_HOME/lib/security/cacerts`.

Default: No `trustManager` is set, and PingGateway uses the default and system certificates

"sslCipherSuites": array of configuration expression<strings>, optional

Array of cipher suite names, used to restrict the cipher suites allowed when negotiating transport layer security for an HTTPS connection.

For information about the available cipher suite names, refer to the documentation for the Java virtual machine (JVM) where you run PingGateway. For Oracle Java, refer to the list of [JSSE Cipher Suite Names](#).

Default: Allow any cipher suite supported by the JVM.

"sslContextAlgorithm": configuration expression<string>, optional

The `SSLContext` algorithm name, as listed in the table of [SSLContext Algorithms](#) for the Java Virtual Machine (JVM).

Default: `TLS`

"sslEnabledProtocols": array of configuration expression<strings>, optional

The Java Virtual Machine (JVM) security setting `jdk.tls.disabledAlgorithms` restricts the Transport Layer Security (TLS) algorithms Java applications like PingGateway can use. The JVM `java.security` file defines the default list of `jdk.tls.disabledAlgorithms`.

This PingGateway setting takes an array of protocol names. Use it to further restrict the protocols allowed when negotiating TLS for an HTTPS connection.

Learn more about the protocol names in the JVM documentation, [Additional JSSE Standard Names](#).

Follow these protocol recommendations:

- Use TLSv1.3 when it is supported by client applications, otherwise use TLSv1.2.
- Don't use algorithms listed in `jdk.tls.disabledAlgorithms` and don't remove algorithms from the list.

If applications require disabled algorithms for backwards compatibility, enable them only with express approval from enterprise security.

Default: `TLSv1.3, TLSv1.2`

"alpn": object, optional

A flag to enable the Application-Layer Protocol Negotiation (ALPN) extension for TLS connections.

```
{
  "alpn": {
    "enabled": configuration expression<boolean>
  }
}
```

enabled: *configuration expression*<*boolean*>, *optional*

- `true` : Enable ALPN. Required for HTTP/2 connections over TLS
- `false` : Disable ALPN.

Default: `true`

"hostnameVerifier": *configuration expression*<*enumeration*>, *optional*

The method to handle hostname verification for outgoing SSL connections.

Use one of the following values:

- `ALLOW_ALL` : Allow a certificate issued by a trusted CA for any hostname or domain to be accepted for a connection to any domain.

If the SSL endpoint uses a raw IP address rather than a fully-qualified hostname, you must configure this property as `ALLOW_ALL`.

To prevent the compromise of TLS connections, use `ALLOW_ALL` in development mode only. In production, use `STRICT`.

Caution

The `ALLOW_ALL` setting allows a certificate issued for one company to be accepted as a valid certificate for another company.

- `STRICT` : Match the hostname either as the value of the the first CN, or any of the subject-alt names.

A wildcard can occur in the CN, and in any of the subject-alt names. Wildcards match one domain level, so `*.example.com` matches `www.example.com` but not `some.host.example.com`.

Default: `STRICT`

"offloadHandshake": *configuration expression*<*boolean*>, *optional*

Whether to offload the handshake processing to a worker thread.

When processing a TLS handshake with revocation checks enabled, the handshake process can take an extended amount of time, blocking the event thread from processing other requests. When this option is `true`, PingGateway processes the TLS handshake in a separate worker thread. The event thread continues to process other requests.

Default: `false`

Example

For an example that uses ClientTlsOptions, refer to [Configure PingGateway for TLS \(client-side\)](#).

Delegate

Delegates all method calls to a referenced handler, filter, or any object type.

Use a Delegate to decorate referenced objects differently when they are used multiple times in a configuration.

Usage

```
{
  "filter or handler": {
    "type": "Delegate",
    [decorator reference, ...],
    "config": {
      "delegate": object
    }
  }
}
```

Example

For an example of how to delegate tasks to `ForgeRockClientHandler`, and capture PingGateway's interaction with AM, refer to [Decorating PingGateway's interactions with AM](#).

More information

org.forgerock.openig.decoration.DelegateHeaplet 

InMemorySessionManager

Configures the session cookie and timeout settings for stateful sessions.

Set this as the `"session"` in the [AdminHttpApplication](#) (`admin.json`) for administrative requests and the [GatewayHttpApplication](#) (`config.json`) or individual [Route](#) for other requests. PingGateway stores the session data and sets a session cookie on the user-agent to reference the session.

Learn more about session management in [PingGateway sessions](#).

Usage

```
{
  "name": string,
  "type": "InMemorySessionManager",
  "config": {
    "timeout": configuration expression<duration>,
    "cookie": {
      "name": configuration expression<string>,
      "domain": configuration expression<string>,
      "httpOnly": configuration expression<boolean>,
      "path": configuration expression<string>,
      "sameSite": configuration expression<enumeration>,
      "secure": configuration expression<boolean>
    }
  }
}
```

Properties

"timeout": configuration expression<duration>, optional

The duration of a valid session. The cookie expires after this duration.

Default: 30 minutes

"cookie": object, optional

The cookie used to store the reference to the session.

A cookie with default settings.

"name" configuration expression<string>, optional

The name of the cookie stored on the user-agent. Change the default name to improve security.

Default: `IG_SESSIONID`

"domain" configuration expression<string>, optional

The domain name for servers that can access the cookie.

Only set the domain if the user-agent can return cookies to servers in the domain on its next hop.

Default: The fully qualified hostname of the user-agent's next hop.

"httpOnly": configuration expression<boolean>, optional

Set to `true` to mitigate the risk of client-side scripts accessing protected cookies.

Default: `true`

"path" configuration expression<string>, optional

The URL path that must exist in the requested URL for PingGateway to use the cookie.

Default: `/`

"sameSite": *configuration expression*<enumeration>, optional

Options to manage the circumstances in which a cookie is sent to the server. Use one of the following values to reduce the risk of CSRF attacks:

- **STRICT** : Send the cookie only if the request was initiated from the cookie domain. Not case-sensitive.

Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.

- **LAX** : Send the cookie only with GET requests in a first-party context, where the URL in the address bar matches the cookie domain. Not case-sensitive.

Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.

- **NONE** : Send the cookie whenever a request is made to the cookie domain. Not case-sensitive.

With this setting, set `"secure": true` to prevent browsers from rejecting the cookie. Learn more in [SameSite cookies](#).

Default: **LAX**

"secure": *configuration expression*<boolean>, optional

Set to **true** to limit the scope of the cookie to secure channels.

When **true**, the user-agent can return cookies only over HTTPS. The user-agent must be connected to its next hop by HTTPS.

Default: **false**

More information

org.forgerock.openig.session.cookie.InMemorySessionManagerHeaplet

Issuer

Describes an OAuth 2.0 Authorization Server or an OpenID Provider that PingGateway can use as a OAuth 2.0 client or OpenID Connect relying party.

The Issuer requires OpenID Connect ID Token signature validation. It doesn't support ID Token encryption.

An Issuer is usually referenced from a [ClientRegistration](#).

Usage

```
{
  "name": string,
  "type": "Issuer",
  "config": {
    "wellKnownEndpoint": configuration expression<url>,
    "idTokenVerificationSecretId": configuration expression<string>,
    "secretsProvider": SecretsProvider reference,
    "authorizeEndpoint": configuration expression<url>,
    "registrationEndpoint": configuration expression<url>,
    "tokenEndpoint": configuration expression<url>,
    "userInfoEndpoint": configuration expression<url>,
    "endSessionEndpoint": configuration expression<url>,
    "revocationEndpoint": configuration expression<url>,
    "issuer": configuration expression<string>,
    "issuerHandler": Handler reference,
    "issuerRepository": IssuerRepository reference, // deprecated
    "useDeprecatedIssuerRepository": configuration expression<boolean>, // deprecated
    "supportedDomains": [ pattern, ... ],
    "idTokenSkewAllowance": configuration expression<duration>
  }
}
```

Properties

If the provider has a well-known configuration URL as defined for [OpenID Connect 1.0 Discovery](#) that returns JSON with at least authorization and token endpoint URLs, you can specify that URL in the provider configuration. Otherwise, you must specify at least the provider authorization and token endpoint URLs, and optionally, the registration endpoint and user info endpoint URLs.

For token signature validation, if you don't specify the well-known configuration URL, do specify the expected issuer and how to access the secret. For HMAC-based signature validation, PingGateway must have access to the symmetric key, such as the client secret it uses to connect to the OpenID provider. The verification secret ID expects a [CryptoKey](#). The OAuth2 client secret ID to registering the client is a [GenericSecret](#). At present, you can't reuse the same secrets provider for both the client secret and signature validation.

wellKnownEndpoint

"wellKnownEndpoint" : *configuration expression<url>, required unless authorizeEndpoint and tokenEndpoint are configured*

The URL to the well-known configuration resource described in OpenID Connect 1.0 Discovery.

idTokenVerificationSecretId

"idTokenVerificationSecretId" : *configuration expression<string>, optional*

When OpenID Connect ID token signature validation is enabled on the [ClientRegistration](#) and no **"wellKnownEndpoint"** is set, set this to reference the provider's public key for *asymmetric* ID token signature validation.

If the OpenID provider uses a *symmetric* (HMAC-based) signature algorithm, the symmetric key is the client secret. Configure the client secret ID in the [ClientRegistration](#) instead.

This secret ID must point to a [CryptoKey](#) in the **"secretsProvider"**.

Default: Use the `jwt_uri` in the well-known configuration to get the asymmetric signature validation keys and ignore this setting.

secretsProvider

`"secretsProvider"` : *SecretsProvider [reference](#), required when `idTokenVerificationSecretId` is set*

The [SecretsProvider](#) to query for the signature validation secret.

Default: Use the `jwt_uri` in the well-known configuration to get the asymmetric signature validation keys and ignore this setting.

authorizeEndpoint

`"authorizeEndpoint"` : *configuration expression<[url](#)>, required unless obtained through `wellKnownEndpoint`*

The URL to the provider's OAuth 2.0 authorization endpoint.

registrationEndpoint

`"registrationEndpoint"` : *configuration expression<[url](#)>, optional*

The URL to the provider's OpenID Connect dynamic registration endpoint.

tokenEndpoint

`"tokenEndpoint"` : *configuration expression<[url](#)>, required unless obtained through `wellKnownEndpoint`*

The URL to the provider's OAuth 2.0 token endpoint.

userInfoEndpoint

`"userInfoEndpoint"` : *configuration expression<[url](#)>, optional*

The URL to the provider's OpenID Connect UserInfo endpoint.

Default: no UserInfo is obtained from the provider.

endSessionEndpoint

`"endSessionEndpoint"` : *configuration expression<[url](#)>, optional*

The URL to the Authorization Server's `end_session_endpoint`. In OpenID Connect, when a request accesses this endpoint, PingGateway kills the user session in AM.

Example endpoint: `https://am.example.com:8443/openam/oauth2/realms/root/realms/alpha/connect/endSession`

Learn more in [OpenID Connect Session Management](#).

Default: No endpoint

revocationEndpoint

`"revocationEndpoint"` : *configuration expression<[url](#)>, optional*

The URL to the Authorization Server's `revocation_endpoint`. When a request accesses this endpoint, PingGateway revokes access tokens or refresh tokens associated with the current user session in AM.

Example endpoint: `https://am.example.com:8443/openam/oauth2/realms/root/realms/alpha/token/revoke`

Default: No endpoint

issuer

`"issuer"` : configuration expression<string>, required for OIDC unless obtained through the `wellKnownEndpoint`

The identifier of the issuer for OpenID Connect ID tokens. This must match the `iss` claim value in the ID tokens.

Default: Use the `issuer` in the well-known configuration.

issuerHandler

`"issuerHandler"` : Handler [reference](#), optional

Invoke this HTTP client [Handler](#) to communicate with the Authorization Server.

Provide the name of a Handler object defined in the heap or an inline handler configuration object.

Set this to the name of a [ClientHandler](#) configured in the heap or a [Chain](#) that ends in a ClientHandler.

Default: PingGateway uses the default ClientHandler.

issuerRepository (deprecated)

`"issuerRepository"` : Issuer repository [reference](#), optional

A repository of OAuth 2.0 issuers, built from discovered issuers and the PingGateway configuration.



Important

The [IssuerRepository \(deprecated\)](#) is deprecated.

For issuers known in advance, add their settings to the [ClientRegistration](#).

For discovery, if the `IssuerRepository` had an `"issuerHandler"`, configure an `AuthorizationCodeOAuth2ClientFilter` `"discoveryHandler"` instead.

Provide the name of an IssuerRepository object defined in the heap.

Default: Look up an issuer repository named `IssuerRepository` in the heap. If none is explicitly defined, PingGateway creates a default one named `IssuerRepository` in the current route.

useDeprecatedIssuerRepository (deprecated)

`"useDeprecatedIssuerRepository"` : configuration expression<boolean>, optional

Whether to use the deprecated default `"IssuerRepository"` from the heap.



Important

This property is deprecated.

- `true` : When the `"issuerRepository"` isn't set, use the deprecated default `"IssuerRepository"` from the heap.
- `false` : When the `"issuerRepository"` isn't set, don't add this issuer to any IssuerRepository.

Default: `false`

supportedDomains

`"supportedDomains"` : array of [patterns](#), optional

One or more domain patterns to match domain names that are handled by this issuer used as a shortcut for [OpenID Connect discovery](#) before performing [OpenID Connect dynamic registration](#).

When the OpenID Provider isn't known in advance, PingGateway can discover the OpenID Provider Issuer based on information provided by the user, such as an email address. The OpenID Connect discovery specification explains how to use [WebFinger](#) to discover the issuer. PingGateway can discover the issuer in this way. As a shortcut, PingGateway can also use the supported domains to find issuers already described in the PingGateway configuration.

To use this shortcut, PingGateway extracts the domain from the user input and looks for an issuer whose supported domains list contains a match.

Supported domains patterns match host names with optional port numbers. Don't specify a URI scheme such as HTTP. PingGateway adds the scheme. For instance, `*.example.com` matches any host in the `example.com` domain. You can specify the port number as well as in `host.example.com:8443`. Patterns must be valid regular expression patterns according to the rules for the Java [Pattern](#) class.

idTokenSkewAllowance

`"idTokenSkewAllowance"` : configuration expression<[duration](#)>, optional

Acceptable clock skew when validating OpenID Connect ID Tokens.

Default: `zero`

Examples

The following example shows an AM issuer configuration for AM. AM exposes a well-known endpoint for the provider configuration, but this example demonstrates use of the other fields:

```
{
  "name": "openam",
  "type": "Issuer",
  "config": {
    "authorizeEndpoint":
      "https://am.example.com:8443/openam/oauth2/authorize",
    "registration_endpoint":
      "https://am.example.com:8443/openam/oauth2/connect/register",
    "tokenEndpoint":
      "https://am.example.com:8443/openam/oauth2/access_token",
    "userInfoEndpoint":
      "https://am.example.com:8443/openam/oauth2/userinfo",
    "supportedDomains": [ "mail.example.*", "docs.example.com:8443" ]
  }
}
```

The following example shows an issuer configuration for Google:

```
{
  "name": "google",
  "type": "Issuer",
  "config": {
    "wellKnownEndpoint":
      "https://accounts.google.com/.well-known/openid-configuration",
    "supportedDomains": [ "gmail.*", "googlemail.com:8052" ]
  }
}
```

More information

- [org.forgerock.openig.filter.oauth2.client.Issuer](#) 

IssuerRepository (deprecated)

Stores OAuth 2 issuers that are discovered or built from the configuration.



Important

This object is deprecated. For issuers known in advance, add their settings to the [ClientRegistration](#). For discovery, if the IssuerRepository had an "issuerHandler", configure an [AuthorizationCodeOAuth2ClientFilter](#) "discoveryHandler".

It isn't normally necessary to change this object. Change it only for the following tasks:

- To isolate different repositories in the same route.
- To view the interactions of the well-known endpoint, for example, if the `issuerHandler` is delegating to another handler.

Usage

```
{
  "name": string,
  "type": "IssuerRepository",
  "config": {
    "issuerHandler": Handler reference
  }
}
```

Properties

"issuerHandler": *Handler reference, optional*

The default handler to fetch OAuth2 issuer configurations from the well-known endpoint.

Provide the name of a Handler object defined in the heap or an inline Handler configuration object.

Default: ForgeRockClientHandler

More information

[org.forgerock.openig.filter.oauth2.client.IssuerRepository](https://pingidentity.com/docs/pinggateway/4.12.0/org.forgerock.openig.filter.oauth2.client.IssuerRepository) 

JdbcDataSource

Manages connections to a JDBC data source.

To configure the connection pool, add a JdbcDataSource object named `AuditService` in the route heap.

Usage

```
{
  "name": string,
  "type": "JdbcDataSource",
  "config": {
    "dataSourceClassName": configuration expression<string>,
    "driverClassName": configuration expression<string>,
    "executor": ScheduledExectutorService reference,
    "jdbcUrl": configuration expression<url>,
    "passwordSecretId": configuration expression<secret-id>,
    "poolName": configuration expression<string>,
    "properties": object,
    "secretsProvider": SecretsProvider reference,
    "username": configuration expression<string>
  }
}
```

Properties

"dataSourceClassName": configuration expression<string>, optional

The data source class name to use to connect to the database.

Depending on the underlying data source, use either `jdbcUrl`, or `dataSourceClassName` with `url`.

"driverClassName": configuration expression<string>, optional

Class name of the JDBC connection driver. The following examples can be used:

- MySQL Connector/J: `com.mysql.jdbc.Driver`
- H2: `org.h2.Driver`

This property is optional, but required for older JDBC drivers.

"executor": ScheduledExecutorService reference, optional

A `ScheduledExecutorService` for maintenance tasks.

Default: [ScheduledExecutorService](#).

"jdbcUrl": configuration expression<url>, optional

The JDBC URL to use to connect to the database.

Depending on the underlying data source, use either `jdbcUrl`, or `dataSourceClassName` with `url`.

"passwordSecretId": configuration expression<secret-id>, required if the database is password-protected

The secret ID of the password to access the database.

This secret ID must point to a [GenericSecret](#).

"poolName": configuration expression<string>, optional

The connection pool name. Use to identify a pool easily for maintenance and monitoring.

"properties": object, optional

Server properties specific to the type of data source being used. The values of the object are evaluated as configuration expression<strings>.

You can find information about available options in the data source documentation.

"secretsProvider": SecretsProvider reference, required

The [SecretsProvider](#) to query for passwords and cryptographic keys.

"username": configuration expression<string>, optional

The username to access the database.

Example

You can find an example that uses `JdbcDataSource` in [Password replay from a database](#).

The following example configures a `JdbcDataSource` with a `dataSourceClassName` and `url`:

```
"config": {
  "username": "testUser",
  "dataSourceClassName": "org.h2.jdbcx.JdbcDataSource",
  "properties": {
    "url": "jdbc:h2://localhost:3306/auth"
  },
  "passwordSecretId": "database.password",
  "secretsProvider": "MySecretsProvider"
}
```

The following example configures a `JdbcDataSource` with `jdbcUrl` alone:

```
"config": {
  "username": "testUser",
  "jdbcUrl": "jdbc:h2://localhost:3306/auth",
  "passwordSecretId": "database.password",
  "secretsProvider": "MySecretsProvider"
}
```

The following example configures a `JdbcDataSource` with `jdbcUrl` and `driverName`. Use this format for older drivers, where `jdbcUrl` doesn't provide enough information:

```
"config": {
  "username": "testUser",
  "jdbcUrl": "jdbc:h2://localhost:3306/auth",
  "driverName": "org.h2.Driver",
  "passwordSecretId": "database.password",
  "secretsProvider": "MySecretsProvider"
}
```

More information

org.forgerock.openig.sql.JdbcDataSourceHeaplet 

JwtSession (deprecated)

Configures settings for stateless sessions.



Important

This object is [deprecated](#) ; instead, set the "session" in the [AdminHttpApplication \(admin.json\)](#) for administrative requests and the [GatewayHttpApplication \(config.json\)](#) or individual [Route](#) for other requests.

Session information is serialized as a secure JWT, that is encrypted and signed, and optionally compressed. The resulting JWT string is placed in one or more JWT session cookies. The cookies contain session attributes as JSON, and a marker for the session timeout.

Use `JwtSession` to configure stateless sessions as follows:

- Configure a `JwtSession` object named `Session` in the heap of `config.json`.

Stateless sessions are created when a request traverses any route or subroute in the configuration. No routes can create stateful sessions.

- Configure a `JwtSession` object in the `session` property of a `Route` object.

When a request enters the route, PingGateway builds a new session object for the route. Any child routes inherit the session. The session information is saved/persisted when the response exits the route.

- Configure a `JwtSession` object in the `session` property of multiple sibling routes in the configuration, using an identical cookie name and cryptographic properties. Sibling routes are in the same configuration, with no ascending hierarchy to each other.

When a `JwtSession` object is declared in a route, the session content is available only within that route. With this configuration, sibling routes can read/write in the same session.

Consider the following points when you configure `JwtSession`:

- Only JSON-compatible types can be serialized into a JWT and included in JWT session cookies. Compatible types include primitive JSON structures, lists, arrays, and maps. Learn more in [JSON.org](https://www.json.org/).
- The maximum size of the JWT session cookie is 4 KBytes, as defined by the browser. If the cookie exceeds this size, PingGateway automatically splits it into multiple cookies.
- If an empty session is serialized, the supporting cookie is marked as expired and is effectively discarded.

To prevent PingGateway from cleaning up empty session cookies, consider adding some information to the session context by using an `AssignmentFilter`. You can find an example in [Adding info to a session](#).

- When HTTP clients perform multiple requests in a session that modify the content, the session information can become inconsistent.

Learn more about session management in [PingGateway sessions](#).

Usage

```
{
  "name": string,
  "type": "JwtSession",
  "config": {
    "authenticatedEncryptionSecretId": configuration expression<secret-id>,
    "encryptionMethod": configuration expression<string>,
    "cookie": object,
    "sessionTimeout": configuration expression<duration>,
    "persistentCookie": configuration expression<boolean>,
    "secretsProvider": SecretsProvider reference,
    "skewAllowance": configuration expression<duration>,
    "useCompression": configuration expression<boolean>
  }
}
```

Properties

"authenticatedEncryptionSecretId": *configuration expression*<[secret-id](#)>, optional

The secret ID of the encryption key used to perform authenticated encryption on a JWT. Authenticated encryption encrypts data and then signs it with HMAC, in a single step.

This secret ID must point to a [CryptoKey](#).

Authenticated encryption is achieved with a symmetric encryption key. Therefore, the secret must refer to a symmetric key.

For more information, refer to [RFC 5116](#).

Default: PingGateway generates a default symmetric key for authenticated encryption. Consequently, PingGateway instances cannot share the JWT session.

"encryptionMethod": *configuration expression*<[string](#)>, optional

The algorithm to use for authenticated encryption. For information about allowed encryption algorithms, refer to [RFC 7518: "enc" \(Encryption Algorithm\) Header Parameter Values for JWE](#).

Default: A256GCM

"cookie": *object*, optional

The configuration of the cookie used to store the encrypted JWT.

The maximum size of the JWT session cookie is 4 KBytes, as defined by the browser. If the cookie exceeds this size, PingGateway automatically splits it into multiple cookies.

Default: The cookie is treated as a host-based cookie.

```
{
  "name": configuration expression<string>,
  "domain": configuration expression<string>,
  "httpOnly": configuration expression<boolean>,
  "path": configuration expression<string>,
  "sameSite": configuration expression<enumeration>,
  "secure": configuration expression<boolean>
}
```

"name" configuration expression<string>, optional

Name of the JWT cookie stored on the user agent. For security, change the default name of cookies.

Default: `openig-jwt-session`

"domain" configuration expression<string>, optional

Domain from which the JWT cookie can be accessed. When the domain is specified, a JWT cookie can be accessed from different hosts in that domain.

Set a domain only if the user agent is able to reemit cookies on that domain on its next hop. For example, to reemit a cookie on the domain `.example.com`, the user agent must be able to access that domain on its next hop.

Default: The fully qualified hostname of the user agent's next hop.

"httpOnly": configuration expression<boolean>, optional

Flag to mitigate the risk of client-side scripts accessing protected cookies.

Default: `true`

"path": configuration expression<string>, optional

Path protected by this session.

Set a path only if the user agent is able to reemit cookies on the path. For example, to reemit a cookie on the path `/home/cdsso`, the user agent must be able to access that path on its next hop.

Default: The path of the request that got the `Set-Cookie` in its response.

"sameSite": configuration expression<enumeration>, optional

Options to manage the circumstances in which a cookie is sent to the server. Use one of the following values to reduce the risk of CSRF attacks:

- **STRICT** : Send the cookie only if the request was initiated from the cookie domain. Not case-sensitive.
Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.
- **LAX** : Send the cookie only with GET requests in a first-party context, where the URL in the address bar matches the cookie domain. Not case-sensitive.
Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.
- **NONE** : Send the cookie whenever a request is made to the cookie domain. Not case-sensitive.

With this setting, set `"secure": true` to prevent browsers from rejecting the cookie. Learn more in [SameSite cookies](#).

Default: `LAX`

"secure": configuration expression<boolean>, optional

Flag to limit the scope of the cookie to secure channels.

Set this flag only if the user agent is able to reemit cookies over HTTPS on its next hop. For example, to reemit a cookie with the `secure` flag, the user agent must be connected to its next hop by HTTPS.

Default: `false`

"sessionTimeout": configuration expression<duration>, optional

The duration for which a JWT session is valid. If the supporting cookie is persistent, this property also defines the expiry of the cookie.

The value must be above zero. The maximum value is 3650 days (approximately 10 years). If you set a longer duration, PingGateway truncates the duration to 3650 days.

Default: 30 minutes

"persistentCookie": configuration expression<boolean>, optional

Whether or not the supporting cookie is persistent:

- `true`: the supporting cookie is a persistent cookie. Persistent cookies are reemitted by the user agent until their expiration date or until they are deleted.
- `false`: the supporting cookie is a session cookie. PingGateway doesn't specify an expiry date for session cookies. The user agent is responsible for deleting them when it considers that the session is finished (for example, when the browser is closed).

Default: `false`

"secretsProvider": SecretsProvider reference, required

The [SecretsProvider](#) to query for the JWT session signing or encryption keys.

"skewAllowance": configuration expression<duration>, optional

The duration to add to the validity period of a JWT to allow for clock skew between different servers.

A `skewAllowance` of 2 minutes affects the validity period as follows:

- A JWT with an `iat` of 12:00 is valid from 11:58 on the PingGateway clock.
- A JWT with an `exp` 13:00 is expired after 13:02 on the PingGateway clock.

Default: To support a zero-trust policy, the skew allowance is by default `zero`.

"useCompression": configuration expression boolean, optional

When `true`, PingGateway compresses the session JWT before setting it in a cookie.



Important

Compression can undermine the security of encryption. Evaluate this threat according to your use case before you enable compression.

Default: `false`

Example

You can find more information about configuring a `JwtSession` with authenticated encryption in [Encrypt JWT sessions](#).

You can find more information about managing multiple instances of PingGateway in the same deployment in [Installing PingGateway](#).

More information

Learn more about PingGateway sessions in [PingGateway sessions](#).

org.forgerock.openig.session.jwt.JwtSessionManagerHeaplet 

JwtSessionManager

Configures session cookie and timeout settings for stateless sessions. Set this as the `"session"` in the [AdminHttpApplication](#) (`admin.json`) for administrative requests and the [GatewayHttpApplication](#) (`config.json`) or individual [Route](#) for other requests.

The user-agent stores the session data, and PingGateway puts the session data in a JWT stored as one or more session cookies on the user-agent.

Learn more about session management in [PingGateway sessions](#).

Usage

```
{
  "name": string,
  "type": "JwtSessionManager",
  "config": {
    "authenticatedEncryptionSecretId": configuration expression<secret-id>,
    "encryptionMethod": configuration expression<string>,
    "cookie": {
      "name": configuration expression<string>,
      "domain": configuration expression<string>,
      "httpOnly": configuration expression<boolean>,
      "path": configuration expression<string>,
      "sameSite": configuration expression<enumeration>,
      "secure": configuration expression<boolean>
    },
    "sessionTimeout": configuration expression<duration>,
    "persistentCookie": configuration expression<boolean>,
    "secretsProvider": SecretsProvider reference,
    "skewAllowance": configuration expression<duration>,
    "useCompression": configuration expression<boolean>
  }
}
```

Properties

authenticatedEncryptionSecretId

"authenticatedEncryptionSecretId" : *configuration expression<[secret-id](#)>, optional*

The secret ID of the encryption key used to perform authenticated encryption on a JWT. Authenticated encryption encrypts data and signs it with HMAC in a single step.

This secret ID must point to a [CryptoKey](#).

Authenticated encryption is achieved with a symmetric encryption key. The secret must refer to a symmetric key. Learn more in [RFC 5116](#).

Default: PingGateway generates a default symmetric key for authenticated encryption. Consequently, PingGateway instances cannot share the JWT session.

encryptionMethod

"encryptionMethod" : *configuration expression<[string](#)>, optional*

The algorithm to use for authenticated encryption. Learn about allowed encryption algorithms in [RFC 7518: "enc" \(Encryption Algorithm\) Header Parameter Values for JWE](#).

Default: A256GCM

cookie

"cookie" : *[object](#), optional*

The cookie used to store the secure JWT.

Default: The cookie is treated as a host-based cookie.

"name": configuration expression<string>, optional

The name of the cookie stored on the user-agent. Change the default name to improve security.

Default: `openig-jwt-session`

"domain": configuration expression<string>, optional

The domain name for servers that can access the JWT cookie.

Only set the domain if the user-agent can return cookies to servers in the domain on its next hop.

Default: The fully qualified hostname of the user-agent's next hop.

"httpOnly": configuration expression<boolean>, optional

Set to `true` to mitigate the risk of client-side scripts accessing protected cookies.

Default: `true`

"path": configuration expression<string>, optional

The URL path that must exist in the requested URL for PingGateway to use the cookie.

Only set the path if the user-agent can return cookies for the path on its next hop.

Default: `/`

"sameSite": configuration expression<enumeration>, optional

Options to manage the circumstances in which a cookie is sent to the server. Use one of the following values to reduce the risk of CSRF attacks:

- **STRICT** : Send the cookie only if the request was initiated from the cookie domain. Not case-sensitive.

Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.

- **LAX** : Send the cookie only with GET requests in a first-party context, where the URL in the address bar matches the cookie domain. Not case-sensitive.

Use this value to reduce the risk of cross-site request forgery (CSRF) attacks.

- **NONE** : Send the cookie whenever a request is made to the cookie domain. Not case-sensitive.

With this setting, set `"secure": true` to prevent browsers from rejecting the cookie. Learn more in [SameSite cookies](#).

Default: `LAX`

"secure": configuration expression<boolean>, optional

Set to `true` to limit the scope of the cookie to secure channels.

When `true`, the user-agent can return cookies only over HTTPS. The user-agent must be connected to its next hop by HTTPS.

Default: `false`

sessionTimeout

`"sessionTimeout"` : configuration expression<[duration](#)>, optional

The duration of a valid JWT session. The cookie expires after this duration.

The value must be greater than zero and at most 3650 days (approximately 10 years). If you set a longer duration, PingGateway truncates the duration to 3650 days.

Default: 30 minutes

persistentCookie

`"persistentCookie"` : configuration expression<[boolean](#)>, optional

Whether the supporting cookie is persistent:

- `true` : the supporting cookie is a persistent cookie. The user-agent returns persistent cookies until their expiration date or until they are deleted.
- `false` : the supporting cookie is a session cookie. PingGateway doesn't specify an expiry date for session cookies. The user-agent deletes them when it considers the session terminated; for example, when the user closes the browser.

Default: `false`

secretsProvider

`"secretsProvider"` : *SecretsProvider* [reference](#), required

The [SecretsProvider](#) to query for the JWT session signing or encryption keys.

skewAllowance

`"skewAllowance"` : configuration expression<[duration](#)>, optional

The duration to add to the validity period of a JWT to allow for clock skew between different servers.

A `skewAllowance` of 2 minutes affects the validity period as follows:

- A JWT with an `iat` of 12:00 is valid from 11:58 on the PingGateway clock.
- A JWT with an `exp` 13:00 is expired after 13:02 on the PingGateway clock.

Default: To support a zero-trust policy, the default skew allowance is `zero`.

useCompression

`"useCompression"` : configuration expression [boolean](#), optional

When `true`, PingGateway compresses the session JWT before setting it in a cookie.



Important

Compression can undermine the security of encryption. Evaluate this threat according to your use case before you enable compression.

Default: `false`

Example

Learn more in [Encrypt JWT sessions](#).

More information

org.forgerock.openig.session.jwt.JwtSessionManagerHeaplet[↗](#)

KerberosIdentityAssertionPlugin

Use with an [IdentityAssertionHandler](#) to validate Kerberos authentication tickets locally.

The KerberosIdentityAssertionPlugin doesn't support Windows New Technology LAN Manager (NTLM) tokens.

Usage

```
{
  "name": string,
  "type": "KerberosIdentityAssertionPlugin",
  "config": {
    "serviceLogin": ServiceLogin reference,
    "trustedRealms": [configuration_expression<string>, ...],
    "unauthorizedResponseHandler": Handler reference
  }
}
```

Properties

"serviceLogin": *ServiceLogin* [reference](#), *required*

A service account object to log PingGateway in to the Kerberos server so that PingGateway can act on user tokens. PingGateway will be able to validate user tokens, for example.

PingGateway provides the following service account objects for the KerberosIdentityAssertionPlugin:

UsernamePasswordServiceLogin

Log PingGateway in to the Kerberos server by using a service account username and password.


```
{
  "type": "UsernamePasswordServiceLogin",
  "config": {
    "username": configuration_expression<string>,
    "passwordSecretId": configuration_expression<secret-id>,
    "secretsProvider": SecretsProvider reference
  }
}
```

"username": *configuration expression<string>, required*

Service username.

"passwordSecretId": *configuration expression<secret-id>, required if the proxy requires authentication*

The secret ID of the service account password.

"secretsProvider": *SecretsProvider reference, required*

The [SecretsProvider](#) to query for the password.

KeytabServiceLogin

Log PingGateway in to the Kerberos server by using a Keytab file.



Important

This service account object is less secure than UsernamePasswordServiceLogin; use it only for testing or to ease migration. In production environments, always use the most secure options available.

```
{
  "type": "KeytabServiceLogin",
  "config": {
    "username": configuration_expression<string>,
    "keytabFile": configuration_expression<secret-id>,
    "executor": ScheduledExecutorService reference
  }
}
```

"username": *configuration expression<string>, required*

Service username.

"keytabFile": *configuration expression<string>, required*

Path to the keytab file. Both the username and keytabFile are required for login.

"executor": *ScheduledExecutorService [reference](#), optional*

An executor service to schedule the execution of tasks during a keytab service login.

Default: [ScheduledExecutorService](#) or an executor service declared in the heap.

"trustedRealms": array of configuration expression<strings>, optional

A list of one or more Kerberos realms that are expected to match the principal's realm from the user's Kerberos ticket.

Kerberos tickets are accepted only if the principal's realm matches a realm in the list.

Default: Empty

"unauthorizedResponseHandler": handler reference, optional

Override the default unauthorized handler.

When a browser can't supply a Kerberos token and isn't configured to deal appropriately with HTTP 401 Unauthorized, the default response can leave the user stuck on an unauthorized page. Use the `unauthorizedResponseHandler` provide an appropriate response, such as the following:

```
{
  "unauthorizedResponseHandler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 401,
      "headers": {
        "Content-Type": [
          "text/html; charset=UTF-8"
        ]
      },
      "entity": "<!DOCTYPE html><html><head><title>401 Unauthorized</title></head><body><form
method=\"POST\"><input type=\"submit\" value=\"Return to Sign In\" /></form></body></html>"
    }
  }
}
```

When you use a custom handler, PingGateway overrides the response status to set it to HTTP 401 Unauthorized and overrides `WWW-Authenticate` header to set it to `Negotiate`.

Default: Return an empty HTTP 401 Unauthorized response with a `WWW-Authenticate` header set to `Negotiate`.

Kerberos configuration

When using this plugin, you can use Java system properties or a Kerberos configuration file to provide information about the Kerberos installation.

The following examples use system properties to set the default realm and Key Distribution Center (KDC). The system property settings override any settings found in a Kerberos configuration file:

Linux

```
export IG_OPTS="-Djava.security.krb5.realm=example.com -Djava.security.krb5.kdc=kdc.example.com"
```

Windows

```
set "IG_OPTS=-Djava.security.krb5.realm=example.com -Djava.security.krb5.kdc=kdc.example.com"
```

The following examples reference a Kerberos configuration file for advanced configuration options like encryption types:

Linux

```
export IG_OPTS="-Djava.security.krb5.conf=/path/to/krb5.conf"
```

Windows

```
set "IG_OPTS=-Djava.security.krb5.conf=\path\to\krb5.conf"
```

Learn more in [Define environment variables for startup, runtime, and stop](#) and in the *Java Security Developer's Guide* [Kerberos Requirements](#).

Examples

```
{
  "type": "KerberosIdentityAssertionPlugin",
  "config": {
    "serviceLogin": "UsernamePasswordServiceLogin",
    "trustedRealms": ["EXAMPLE.COM"]
  }
}
```

```
{
  "type": "UsernamePasswordServiceLogin",
  "config": {
    "username": "igsa",
    "passwordSecretId": "igsa.id",
    "secretsProvider": "mySecretsProvider"
  }
}
```

Both types require a Service Principal Name (SPN) for the PingGateway service account. The following commands add and view a Service Principal Name (SPN) for the PingGateway service account, **igsa**. Run the commands as the Windows Administrator to ensure you have access to everything necessary:

```
# Add the SPN for the service account:
PS C:\path\to> setspn -s HTTP/ig.example.com igsa

# View the SPN for the service account:
PS C:\path\to> setspn -l igsa
Registered ServicePrincipalNames for CN=igsa,CN=Users,DC=example,DC=com:
HTTP/ig.example.com
```

When using a Kerberos keytab file, generate it for PingGateway with the Windows **ktpass** command. The following command generates a keytab file for PingGateway in the **example.com** realm mapped to the **igsa** service account username. Run the command as the Windows Administrator to ensure you have access to everything necessary:

```
PS C:\path\to> ktpass -out keytab.file -princ HTTP/ig.example.com@EXAMPLE.COM -pass `
+rndPass -maxPass 256 -mapuser igsa -crypto All -ptype KRB5_NT_PRINCIPAL -kvno 0
```

In the PingGateway configuration, you can use the Kerberos principal as the username:

```
{
  "type": "KeytabServiceLogin",
  "config": {
    "username": "HTTP/ig.example.com@EXAMPLE.COM",
    "keytabFile": "/path/to/keytab.file"
  }
}
```

More information

[org.forgerock.openig.assertion.plugin.kerberos.KerberosIdentityAssertionPlugin](#)

[org.forgerock.openig.assertion.plugin.IdentityAssertionPlugin](#)

[org.forgerock.openig.assertion.IdentityAssertionClaims](#)

The following APIs are used in this class:

- [Kerberos: The Network Authentication Protocol](#)
- [Kerberos Authentication Overview](#)
- [Kerberos Requirements](#)
- [Single Sign-on Using Kerberos in Java](#)
- [Java Troubleshooting](#)
- [How do I enable debug logging for troubleshooting Kerberos and WDSO issues in AM \(All versions\)?](#)

KeyManager (deprecated)

Important

This object is deprecated. Use [SecretsKeyManager](#) instead.

The configuration of a Java Secure Socket Extension [KeyManager](#) to manage private keys for PingGateway. The configuration references the keystore that holds the keys.

When PingGateway acts as a server, it uses a KeyManager to prove its identity to the client. When PingGateway acts as a client, it uses a KeyManager to prove its identity to the server.

Usage

```
{
  "name": string,
  "type": "KeyManager",
  "config": {
    "keystore": KeyStore reference,
    "passwordSecretId": configuration expression<secret-id>,
    "alg": configuration expression<string>,
    "secretsProvider": SecretsProvider reference
  }
}
```

Properties

"keystore": *KeyStore* [reference](#), *required*

The [KeyStore \(deprecated\)](#) object that references the store for key certificates. When `keystore` is used in a KeyManager, it queries for private keys; when `keystore` is used in a TrustManager, it queries for certificates.

Provide either the name of the keystore object defined in the heap or an inline keystore configuration object.

"passwordSecretId": *configuration expression*<[secret-id](#)>, *required*

The secret ID of the password required to read private keys from the keystore.

This secret ID must point to a [GenericSecret](#).

"alg": *configuration expression*<[string](#)>, *optional*

The certificate algorithm to use.

Default: the default for the platform, such as `SunX509`.

Learn more in [PingGateway expressions](#).

"secretsProvider": *SecretsProvider* [reference](#), *required*

The [SecretsProvider](#) to query for the keystore password.

Example

The following example configures a KeyManager that depends on a [KeyStore \(deprecated\)](#) configuration. The KeyManager and KeyStore passwords are provided by Java system properties or environment variables, and retrieved by the SystemAndEnvSecretStore. By default, the password values must be base64-encoded.

```
{
  "name": "MyKeyManager",
  "type": "KeyManager",
  "config": {
    "keystore": {
      "type": "KeyStore",
      "config": {
        "url": "file://${env['HOME']}/keystore.p12",
        "passwordSecretId": "keymanager.keystore.secret.id",
        "secretsProvider": "SystemAndEnvSecretStore"
      }
    },
    "passwordSecretId": "keymanager.secret.id",
    "secretsProvider": "SystemAndEnvSecretStore"
  }
}
```

More information

[org.forgerock.openig.security.KeyManagerHeaplet](#)

[JSSE Reference](#)

[KeyStore](#)

[TrustManager \(deprecated\)](#)

KeyStore (deprecated)



Important

This object is deprecated. Use [KeyStoreSecretStore](#) instead.

The configuration for a Java [KeyStore](#), which stores cryptographic private keys and public key certificates.



Warning

Legacy keystore types such as JKS and JCEKS are supported but aren't secure. Consider using the PKCS#12 keystore type.

Usage

```
{
  "name": name,
  "type": "KeyStore",
  "config": {
    "url": configuration expression<url>,
    "passwordSecretId": configuration expression<secret-id>,
    "type": configuration expression<string>,
    "secretsProvider": SecretsProvider reference
  }
}
```

Properties

"url": configuration expression<url>, required

URL to the keystore file.

Learn more in [PingGateway expressions](#).

"passwordSecretId": configuration expression<secret-id>, optional

The secret ID of the password required to read private keys from the KeyStore.

This secret ID must point to a [GenericSecret](#).

If the KeyStore is used as a truststore to store only public key certificates of peers and no password is required to do so, then you don't have to specify this field.

Default: No password is set.

Learn more in [PingGateway expressions](#).

"type": configuration expression<string>, optional

The secret store type.

"secretsProvider": SecretsProvider reference, required

The [SecretsProvider](#) to query for the keystore password.

Example

The following example configures a KeyStore that references the Java KeyStore file `$HOME/keystore.p12`. The KeyStore password is provided by a Java system property or environment variable, and retrieved by the `SystemAndEnvSecretStore`. By default, the password value must be base64-encoded.

```
{
  "name": "MyKeyStore",
  "type": "KeyStore",
  "config": {
    "url": "file://${env['HOME']}/keystore.p12",
    "passwordSecretId": "keystore.secret.id",
    "secretsProvider": "SystemAndEnvSecretStore"
  }
}
```

More information

[org.forgerock.openig.security.KeyStoreHeaplet](#) 

[JSSE Reference](#) 

[KeyManager \(deprecated\)](#)

[TrustManager \(deprecated\)](#)

PingOneService

Holds information about a PingOne environment. Filters using the environment reference a PingOneService.

Usage

```
{
  "name": string,
  "type": "PingOneService",
  "config": {
    "serviceEndpoint": configuration expression<url>,
    "endpointHandler": Handler reference
  }
}
```

Properties

"serviceEndpoint": *configuration expression<url>*, *required*

The PingOne root service endpoint for the environment from which PingGateway derives other service endpoints.

Example: `https://api.pingone.eu/v1/environments/{envId}`.

"endpointHandler": *Handler reference*, *optional*

The handler to make requests to the service endpoints.

Make sure this handler can obtain the PingOne access tokens for the services it makes requests to.

Default: ForgeRockClientHandler as defined in the heap

Example

The following example shows a PingOneService using the default endpoint handler to access the environment:

```
{
  "name": "PingOneService-1",
  "type": "PingOneService",
  "config": {
    "serviceEndpoint": "https://api.pingone.eu/v1/environments/eeff3566-2e5a-4d35-a48d-19090fceb5e"
  }
}
```

In your environment, get the ID from **Settings > Environment Properties > Environment ID**.

ProxyOptions

A proxy to which a [ClientHandler](#) or [ReverseProxyHandler](#) can submit requests, and an [AmService](#) can submit Websocket notifications.

Use this object to configure a proxy for AM notifications, and use it in a `ClientHandler` or `ReverseProxyHandler`, and again in an `AmService` notifications block.

Usage

Use one of the following `ProxyOption` types with the `proxyOptions` option of [ClientHandler](#), [ReverseProxyHandler](#), and [AmService](#):

- No proxy.

```
{
  "name": string,
  "type": "NoProxyOptions"
}
```

- System defined proxy options.

```
{
  "name": string,
  "type": "SystemProxyOptions"
}
```

- Custom proxy

```
{
  "name": string,
  "type": "CustomProxyOptions",
  "config": {
    "uri": configuration expression<url>,
    "username": configuration expression<string>,
    "passwordSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference
  }
}
```

Default: `NoProxyOptions`

Properties

"uri": configuration expression<[url](#)>, required

URI of a server to use as a proxy for outgoing requests.

The result of the expression must be a string that represents a valid URI, but isn't a real `java.net.URI` object.

"username": configuration expression<[string](#)>, required if the proxy requires authentication

Username to access the proxy server.

"passwordSecretId": configuration expression <secret-id>, required if the proxy requires authentication

The secret ID of the password to access the proxy server.

This secret ID must point to a [GenericSecret](#).

"secretsProvider": _ SecretsProvider <reference>, required

The [SecretsProvider](#) to query for the proxy's password.

Example

In the following example, the handler passes outgoing requests to the proxy server, which requires authentication:

```
"handler": {
  "type": "ClientHandler" or "ReverseProxyHandler",
  "config": {
    "proxyOptions": {
      "type": "CustomProxyOptions",
      "config": {
        "uri": "https://proxy.example.com:3128",
        "username": "proxyuser",
        "passwordSecretId": "myproxy.secret.id",
        "secretsProvider": "SystemAndEnvSecretStore"
      }
    }
  }
}
```

In the following example, the AmService notification service passes Websocket notifications to the proxy server, which requires authentication:

```
"type": "AmService",
"config": {
  ...
  "notifications": {
    "proxyOptions": {
      "type": "CustomProxyOptions",
      "config": {
        "uri": "https://proxy.example.com:3128",
        "username": "proxyuser",
        "passwordSecretId": "myproxy.secret.id",
        "secretsProvider": "SystemAndEnvSecretStore"
      }
    }
  }
}
```

RequestResourceUriProvider

Return a resource URL to include in policy decision requests to AM. The [PolicyEnforcementFilter](#) uses the returned resource URL as a key to identify cached policy decisions.

To increase performance, use `RequestResourceUriProvider` in conjunction with AM policies to maximize the the cache hit ratio.

When a request matches a cached policy decision, PingGateway can reuse the decision without asking AM for a new decision. When caching is disabled, PingGateway must ask AM to make a decision for each request.

Usage

```
"resourceUriProvider": {
  "type": "RequestResourceUriProvider",
  "config": {
    "useOriginalUri": configuration expression<boolean>,
    "includeQueryParams": configuration expression<boolean>
  }
}
```

Properties

useOriginalUri: configuration expression<boolean>, optional

When `true`, use the value of `UriRouterContext.originalUri` as the resource URL when requesting policy decisions from AM.

When `false`, use the current `Request.uri` value. Consider that the value might have been modified by the `baseURI` of the route or by any other filter executed before the `PolicyEnforcementFilter`.

Default: `false`

includeQueryParams: configuration expression<boolean>, optional

When `true`, include query parameters in the resource URL when requesting a policy decision from AM.

When `false`, strip **all** query parameters from the resource URL when requesting a policy decision from AM. To strip some but not all query parameters, use [ScriptableResourceUriProvider](#).

Default: `true`

ScheduledExecutorService

An executor service to schedule tasks for execution after a delay or for repeated execution with a fixed interval of time in between each execution. You can configure the number of threads in the executor service and how the executor service is stopped.

The `ScheduledExecutorService` is shared by all downstream components that use an executor service.

Usage

```
{
  "name": string,
  "type": "ScheduledExecutorService",
  "config": {
    "corePoolSize": configuration expression<number>,
    "gracefulStop": configuration expression<boolean>,
    "gracePeriod": configuration expression<duration>
  }
}
```

Properties

"corePoolSize": configuration expression<number>, optional

The minimum number of threads to keep in the pool. If this property is an expression, the expression is evaluated as soon as the configuration is read.

The value must be an integer greater than zero.

Default: 1

"gracefulStop": configuration expression<boolean>, optional

Defines how the executor service stops.

If true, the executor service does the following:

- Blocks the submission of new jobs.
- If a grace period is defined, waits for up to that maximum time for submitted and running jobs to finish.
- Removes submitted jobs without running them.
- Attempts to end running jobs.

If false, the executor service does the following:

- Blocks the submission of new jobs.
- If a grace period is defined, ignores it.
- Removes submitted jobs without running them.
- Attempts to end running jobs.

Default: true

"gracePeriod": configuration expression<duration>, optional

The maximum time that the executor service waits for running jobs to finish before it stops. If this property is an expression, the expression is evaluated as soon as the configuration is read.

If all jobs finish before the grace period, the executor service stops without waiting any longer. If jobs are still running after the grace period, the executor service removes the scheduled tasks, and notifies the running tasks for interruption.

When `gracefulStop` is `false`, the grace period is ignored.

Default: 10 seconds

Example

The following example creates a thread pool to execute tasks. When the executor service is instructed to stop, it blocks the submission of new jobs, and waits for up to 10 seconds for submitted and running jobs to complete before it stops. If any jobs are still submitted or running after 10 seconds, the executor service stops anyway and prints a message.

```
{
  "name": "ExecutorService",
  "comment": "Default service for executing tasks in the background.",
  "type": "ScheduledExecutorService",
  "config": {
    "corePoolSize": 5,
    "gracefulStop": true,
    "gracePeriod": "10 seconds"
  }
}
```

More information

org.forgerock.openig.thread.ScheduledExecutorServiceHeaplet

ScriptableIdentityAssertionPlugin

An out-of-the box implementation of [IdentityAssertionPlugin](#) to support use-cases that aren't provided by a PingGateway plugin.

Use with an [IdentityAssertionHandler](#) for local processing, such as authentication. The plugin returns [IdentityAssertionClaims](#) to include in the identity assertion JWT PingGateway sends to PingOne Advanced Identity Cloud.

The script does the following:

1. Validates the identity request JWT.
2. (Optional) Takes a single String that represents the principal or a principal and a map of additional claims from the [IdentityRequestJwtContext](#).
3. If a `PreProcessingFilter` is configured, triggers the filter.
4. Returns principal and identity claims in the identity assertion JWT.

If script execution fails, the plugin creates an `IdentityAssertionPluginException`.

Usage

```
{
  "name": string,
  "type": "ScriptableIdentityAssertionPlugin",
  "config": {
    "preProcessingFilter": Filter reference,
    "type": configuration expression<string>,
    "file": configuration expression<string>, // Use either "file"
    "source": [ string, ... ],                // or "source", but not both
    "args": map,
    "clientHandler": Handler reference
  }
}
```

Properties

For information about other properties for ScriptableIdentityAssertionPlugin, refer to [PingGateway scripts](#).

"preProcessingFilter": *_Filter reference, optional*

A [Filter](#) to perform user defined actions, such as local authentication and/or authorization.

Default: Pass the request without pre-processing.

Example

The following example applies a `preProcessingFilter` that uses a ScriptableFilter to test whether the user is authenticated. If a Basic Authorization Header isn't found, a response is generated to trigger a Basic Authentication.

```

{
  "name": "BasicAuthScriptablePlugin",
  "type": "ScriptableIdentityAssertionPlugin",
  "config": {
    "type": "application/x-groovy",
    "source": [
      "import org.forgerock.openig.handler.assertion.IdentityAssertionClaims",
      "import org.forgerock.openig.handler.assertion.IdentityAssertionException",
      "if (request.headers.authorization != null && request.headers.authorization.values[0] == 'Basic
user:password') {",
        return new IdentityAssertionClaims("iguser", Map.of("auth", "basic")),
      "}",
      "return newExceptionPromise(new IdentityAssertionException('Invalid authentication'))",
    ],
    "preProcessingFilter": {
      "type": "ScriptableFilter",
      "config": {
        "type": "application/x-groovy",
        "source": [
          "if (request.headers.authorization == null) {",
            "    Response response = new Response(Status.UNAUTHORIZED)",
            "    response.headers['WWW-Authenticate'] = \"Basic\"",
            "    return response",
          "}",
          "return next.handle(context, request)",
        ],
      },
    },
  },
}

```

More information

[org.forgerock.openig.assertion.plugin.IdentityAssertionPlugin](#)

[org.forgerock.openig.assertion.IdentityAssertionClaims](#)

ScriptableResourceUriProvider

Use a script to return a resource URL to include in policy decision requests to AM. The result of the script must be a string that represents a resource URL. The [PolicyEnforcementFilter](#) uses the returned resource URL as a key to identify cached policy decisions.

To increase performance, use `ScriptableResourceUriProvider` in conjunction with AM policies to maximize the the cache hit ratio.

When a request matches a cached policy decision, PingGateway can reuse the decision without asking AM for a new decision.

When caching is disabled, PingGateway must ask AM to make a decision for each request.

Usage

```
"resourceUriProvider": {
  "type": "ScriptableResourceUriProvider",
  "config": {
    "type": configuration expression<string>,
    "file": configuration expression<string>, // Use either "file"
    "source": [ string, ... ],                // or "source", but not both.
    "args": object,
    "clientHandler": Handler reference
  }
}
```

Properties

For information about properties, refer to [PingGateway scripts](#).

ServerTlsOptions

When PingGateway is *server-side*, applications send requests to PingGateway or request services from PingGateway. PingGateway is acting as a server of the application, and the application is acting as a client.

ServerTlsOptions configures the TLS-protected endpoint when PingGateway is server-side. Use ServerTlsOptions in `admin.json`.

Usage

```
{
  "type": "ServerTlsOptions",
  "config": {
    // Use keyManager or sni, not both:
    "keyManager": [ Key manager reference, ...],
    "sni": {
      "serverNames": map,
      "defaultSecretId": configuration expression<secret-id>,
      "secretsProvider": SecretsProvider reference
    },
    "trustManager": [ Trust manager reference, ...],
    "sslCipherSuites": [ configuration expression<string>, ...],
    "sslContextAlgorithm": configuration expression<string>,
    "sslEnabledProtocols": [ configuration expression<string>, ...],
    "alpn": {
      "enabled": configuration expression<boolean>
    },
    "clientAuth": configuration expression<enumeration>,
    "offloadHandshake": configuration expression<boolean>
  }
}
```

Properties

Configure either [keyManager](#) or [sni](#), not both.

- When both are configured, `sni` takes precedence and PingGateway logs a warning.

- When neither is configured, PingGateway logs a warning and throws an exception.

keyManager

"keyManager" : array of key manager [references](#), required if `sni` isn't configured

One or more of the following objects to serve the same secret key and certificate pair for TLS connections to all server names in the deployment:

- [SecretsKeyManager](#)
- [KeyManager \(deprecated\)](#)

Key managers are used to prove the identity of the local peer during TLS handshake, as follows:

- When `ServerTlsOptions` is used in an HTTPS connector configuration (server-side), the key managers to which `ServerTlsOptions` refers are used to prove this PingGateway's identity to the remote peer (client-side). This is the usual TLS configuration setting (without mTLS).
- When `ClientTlsOptions` is used in a `ClientHandler` or `ReverseProxyHandler` configuration (client-side), the key managers to which `ClientTlsOptions` refers are used to prove this PingGateway's identity to the remote peer (server-side). This configuration is used in mTLS scenarios.

Default: None

sni

"sni" : [object](#), required if `keyManager` isn't configured

[Server Name Indication](#) (SNI) is an extension of the TLS handshake to serve different secret key and certificate pairs to the TLS connections on different server names. Use this property to host multiple domains on the same machine.

During a TLS handshake, vert.x accesses secret key and certificate pairs synchronously; PingGateway loads them in memory at startup, and they **must** be present. You must restart PingGateway to update a secret key and certificate pair.

Learn more in [Serve different certificates for TLS connections to different server names](#).

serverNames: [map](#), required

A map of one or more data pairs with the format `Map<String, String>`, where:

- The key is the server name provided during TLS handshake or a configuration expression that evaluates to the name.
- The value is a string representing the secret ID of the servers' secret key/certificate pair. Alternatively, it can be a configuration expression that evaluates to that string.

The following format is required:

```
{
  "serverNames": {
    "configuration expression<string>": "configuration expression<string>",
    ...
  }
}
```

In the following example, the keys and values in the map are strings:

```
"serverNames": {
  "app1.example.com": "my.app1.secretId",
  "app2.example.com": "my.app2.secretId",
  "*.test.com": "my.wildcard.test.secretId"
}
```

In the following example, the keys and values in the map are configuration expressions:

```
"serverNames": {
  "${server.name.available.at.config.time}" : "${secret.id.available.at.config.time}"
}
```

Note the following points:

- **One server cannot be mapped to multiple certificates.**

PingGateway cannot provide multiple certificates for the same server name, as is allowed by Java's key managers.

- **Multiple servers can be mapped to one certificate.**

Map server names individually. In the following configuration, both server names use the same certificate:

```
"serverNames": {
  "cat.com" : "my.secret.id",
  "dog.org" : "my.secret.id"
}
```

Use the `*` wildcard in the server name to map groups of server names. In the following configuration, `app1.example.com` and `app2.example.com` use the same certificate:

```
"serverNames": {
  "*.example.com": "my.wildcard.secret.id"
}
```

"defaultSecretId": configuration expression<secret-id>, required

The secret ID representing the certificate to use when an unmapped server name is provided during TLS handshake.

This secret ID must point to a [CryptoKey](#).

Learn more in [About secrets](#).

"secretsProvider": *SecretsProvider* [reference](#), required

The [SecretsProvider](#) to query for each secret ID.

trustManager

"trustManager" : array of trust manager [references](#), optional

One or more of the following objects to manage PingGateway's public key certificates:

- [SecretsTrustManager](#)
- [TrustAllManager](#)
- [TrustManager](#) (deprecated)



Important

When the TrustManager object is configured, PingGateway only trusts certificates in that TrustManager. Default and system certificates are no longer trusted.

Trust managers verify the identity of a peer by using certificates, as follows:

- When ServerTlsOptions is used in an HTTPS connector configuration (server-side), ServerTlsOptions refers to trust managers that verify the remote peer's identity (client-side). This configuration is used in mTLS scenarios.
- When ClientTlsOptions is used in a ClientHandler or a ReverseProxyHandler configuration (client-side), ClientTlsOptions refers to trust managers that verify the remote peer's identity (server-side). This is the usual TLS configuration setting (without mTLS).

If `trustManager` isn't configured, PingGateway uses the default Java truststore to verify the remote peer's identity. The default Java truststore depends on the Java environment; for example, `$JAVA_HOME/lib/security/cacerts`.

Default: No `trustManager` is set; PingGateway uses the default and system certificates

sslCipherSuites

"sslCipherSuites" : array of configuration expression<[strings](#)>, optional

Array of cipher suite names, used to restrict the cipher suites allowed when negotiating transport layer security for an HTTPS connection.

Learn about the available cipher suite names in the Java documentation on [JSSE Cipher Suite Names](#).

Default: Allow any cipher suite supported by the JVM.

sslContextAlgorithm

"sslContextAlgorithm" : configuration expression<[string](#)>, optional

The `SSLContext` algorithm name, as listed in the table of [SSLContext Algorithms](#) for the Java Virtual Machine (JVM).

Default: `TLS`

sslEnabledProtocols

`"sslEnabledProtocols"` : *array of configuration expression<strings>, optional*

The Java Virtual Machine (JVM) security setting `jdk.tls.disabledAlgorithms` restricts the Transport Layer Security (TLS) algorithms Java applications like PingGateway can use. The JVM `java.security` file defines the default list of `jdk.tls.disabledAlgorithms`.

This PingGateway setting takes an array of protocol names. Use it to further restrict the protocols allowed when negotiating TLS for an HTTPS connection.

Learn more about the protocol names in the JVM documentation, [Additional JSSE Standard Names](#).

Follow these protocol recommendations:

- Use TLSv1.3 when it is supported by client applications, otherwise use TLSv1.2.
- Don't use algorithms listed in `jdk.tls.disabledAlgorithms` and don't remove algorithms from the list.

If applications require disabled algorithms for backwards compatibility, enable them only with express approval from enterprise security.

Default: `TLSv1.3, TLSv1.2`

alpn

`"alpn"` : *object, optional*

A flag to enable the Application-Layer Protocol Negotiation (ALPN) extension for TLS connections.

"enabled": *configuration expression<boolean>, optional*

- `true` : Enable ALPN. (Required for HTTP/2 connections over TLS)
- `false` : Disable ALPN.

Default: `true`

clientAuth

`"clientAuth"` : *configuration expression<enumeration>, optional*

The authentication expected from the client; one of:

- `REQUIRED` : Require the client to present authentication. If it isn't presented, then decline the connection.
- `REQUEST` : Request the client to present authentication. If it isn't presented, then accept the connection anyway.
- `NONE` : Accept the connection without requesting or requiring the client to present authentication.

Default: `NONE`

offloadHandshake

"offloadHandshake" : *configuration expression*<boolean>, optional

Whether to offload the handshake processing to a worker thread.

When processing a TLS handshake with revocation checks enabled, the handshake process can take an extended amount of time, blocking the event thread from processing other requests. When this option is **true**, PingGateway processes the TLS handshake in a separate worker thread. The event thread continues to process other requests.

Default: **false**

TemporaryStorage

Allocates temporary buffers for caching streamed content during request processing. Initially uses memory; when the memory limit is exceeded, switches to a temporary file.

Usage

```
{
  "name": string,
  "type": "TemporaryStorage",
  "config": {
    "initialLength": configuration expression<number>,
    "memoryLimit": configuration expression<number>,
    "fileLimit": configuration expression<number>,
    "directory": configuration expression<string>
  }
}
```

Properties

"initialLength": *configuration expression*<number>, optional

Initial size of the memory buffer.

Default: 8 192 bytes (8 KB). Maximum: The value of **"memoryLimit"**.

"memoryLimit": *configuration expression*<number>, optional

Maximum size of the memory buffer. When the memory buffer is full, the content is transferred to a temporary file.

Default: 65 536 bytes (64 KB). Maximum: 2 147 483 647 bytes (2 GB).

"fileLimit": *configuration expression*<number>, optional

Maximum size of the temporary file. If the file is bigger than this value, PingGateway responds with an `OverflowException`.

Default: 1 073 741 824 bytes (1 GB). Maximum: 2 147 483 647 bytes (2 GB).

"directory": *configuration expression*<string>, optional

The directory where temporary files are created.

Default: `$HOME/.openig/tmp` (on Windows, `%appdata%\OpenIG\tmp`)

More information

[org.forgerock.openig.io.TemporaryStorageHeaplet](https://org.forgerock.openig.io/TemporaryStorageHeaplet) 

TrustAllManager

Blindly trusts all server certificates presented the servers for protected applications. Use this instead of a [TrustManager \(deprecated\)](#) only in tests where you can trust server certificates that were not signed by a well-known CA, such as self-signed certificates.



Important

The TrustAllManager isn't safe for production use. Use a properly configured [TrustManager \(deprecated\)](#) instead.

Usage

```
{
  "name": string,
  "type": "TrustAllManager"
}
```

Example

The following example configures a handler that blindly trusts server certificates and doesn't verify hostnames when PingGateway connects to servers over HTTPS:

```
{
  "name": "BlindTrustReverseProxyHandler",
  "type": "ReverseProxyHandler",
  "config": {
    "tls": {
      "type": "ClientTlsOptions",
      "config": {
        "trustManager": {
          "type": "TrustAllManager"
        },
        "hostnameVerifier": "ALLOW_ALL"
      }
    }
  }
}
```

More information

org.forgerock.openig.security.TrustAllManager 

UmaService

The UmaService includes a list of resource patterns and associated actions that define the scopes for permissions to matching resources. When creating a share using the REST API described below, you specify a path matching a pattern in a resource of the UmaService.

Usage

```
{
  "name": string,
  "type": "UmaService",
  "config": {
    "protectionApiHandler": Handler reference,
    "amService": AmService reference,           // Use either "amService"
    "wellKnownEndpoint": configuration expression<url>, // or "wellKnownEndpoint", but not both.
    "resources": [ object, ... ]
  }
}
```

Properties

"protectionApiHandler": *Handler [reference](#), required*

The handler to use when interacting with the UMA Authorization Server to manage resource sets, such as a ClientHandler capable of making an HTTPS connection to the server.

For more information, refer to [PingGateway handlers](#).

"amService": *AmService [reference](#), required if wellKnownEndpoint is not configured*

The AmService heap object to use for the URI to the well-known endpoint for this UMA Authorization Server. The endpoint is extrapolated from the `url` property of the AmService, and takes the realm into account.

If the UMA Authorization Server is AM, use this property to define the endpoint.

If `amService` is configured, it takes precedence over `wellKnownEndpoint`.

For more information, refer to [UMA discovery](#) in AM's *User-Managed Access (UMA) 2.0 guide*.

See also [AmService](#).

"wellKnownEndpoint": *configuration expression<[url](#)>, required if amService is not configured*

The URI to the well-known endpoint for this UMA Authorization Server.

If the UMA Authorization Server is not AM, use this property to define the endpoint.

If `amService` is configured, it takes precedence over `wellKnownEndpoint`.

Examples:

- In this example, the UMA configuration is in the default realm of AM:

```
https://am.example.com:8088/openam/uma/.well-known/uma2-configuration
```

- In this example, the UMA configuration is in a European customer realm:

```
https://am.example.com:8088/openam/uma/realms/root/realms/customer/realms/europe/.well-known/uma2-configuration
```

For more information, refer to [AM as UMA Authorization Server](#) in AM's *User-Managed Access (UMA) 2.0 guide*.

"resources": array of *objects*, required

Resource objects matching the resources the resource owner wants to share.

Each resource object has the following form:

```
{
  "pattern": resource pattern,
  "actions": [
    {
      "scopes": [ scope string, ... ],
      "condition": runtime expression<boolean>
    },
    {
      ...
    }
  ]
}
```

Each resource pattern can represent an application, or a consistent set of endpoints that share scope definitions. The actions map each request to the associated scopes. This configuration serves to set the list of scopes in the following ways:

1. When registering a resource set, PingGateway uses the list of actions to provide the aggregated, exhaustive list of all scopes that can be used.
2. When responding to an initial request for a resource, PingGateway derives the scopes for the ticket based on the scopes that apply according to the request.
3. When verifying the RPT, PingGateway checks that all required scopes are encoded in the RPT.

A description of each field follows:

"pattern": *pattern*, required

A pattern matching resources to be shared by the resource owner, such as `.*` to match any resource path, and `/photos/.*` to match paths starting with `/photos/`.

See also [Patterns and PingGateway](#).

"actions": array of *objects*, optional

A set of scopes to authorize when the corresponding condition evaluates to `true`.


```

"actions": [
  {
    "scopes": [ "#read" ],
    "condition": "${request.method == 'GET'}"
  },
  {
    "scopes": [ "#create" ],
    "condition": "${request.method == 'POST'}"
  }
]

```

"scopes": array of configuration expression<[strings](#)>, optional

One or more scopes that are authorized when the corresponding condition evaluates to `true`.

For example, the scope `#read` grants read-access to a resource.

"condition": runtime expression<[boolean](#)>, required

When the condition evaluates to `true`, the corresponding scope is authorized.

For example, the condition `${request.method == 'GET'}` is true when reading a resource.

REST API for shares

The REST API for UMA shares is exposed at a registered endpoint. PingGateway logs the paths to registered endpoints when the log level is `INFO` or finer. Look for messages such as the following in the log:

UMA Share endpoint available at
`'/api/system/objects/_router/routes/00-uma/objects/umaservice/share'`

To access the endpoint over HTTP, prefix the path with the PingGateway scheme, host, and port to obtain a full URL, such as http://localhost:8085/api/system/objects/_router/routes/00-uma/objects/umaservice/share.

The UMA REST API supports create (POST only), read, delete, and query (`_queryFilter=true` only). You can find an introduction to common REST APIs in [About Common REST](#).

In the present implementation, PingGateway doesn't have a mechanism for persisting shares. When PingGateway stops, the shares are discarded.

Learn more about API descriptors for the UMA share endpoint in [PingGateway API descriptors](#).

A share object has the following form:

```

{
  "path": pattern,
  "pat": UMA protection API token (PAT) string,
  "id": unique identifier string,
  "resource_id": unique identifier string,
  "user_access_policy_uri": URI string
}

```

"path": *pattern, required*

A pattern matching the path to protected resources, such as `/photos/*.*`.

This pattern must match a pattern defined in the UmaService for this API.

See also [Patterns and PingGateway](#).

"pat": *PAT string, required*

A PAT granted by the UMA Authorization Server given consent by the resource owner.

In the present implementation, PingGateway has access only to the PAT, not to any refresh tokens.

"id": *unique identifier string, read-only*

This uniquely identifies the share. This value is set by the service when the share is created, and can be used when reading or deleting a share.

"resource_id": *unique identifier string, read-only*

This uniquely identifies the UMA resource set registered with the authorization server. This value is obtained by the service when the resource set is registered, and can be used when setting access policy permissions.

"user_access_policy_uri": *URI string, read-only*

This URI indicates the location on the UMA Authorization Server where the resource owner can set or modify access policies. This value is obtained by the service when the resource set is registered.

More information

[User-Managed Access \(UMA\) 2.0 Grant for OAuth 2.0 Authorization](#) 

[org.forgerock.openig.uma.UmaSharingService](#) 

PingGateway property value substitution

In an environment with multiple PingGateway servers, use property value substitution for similar but different configurations across the servers.

Property value substitution enables you to:

- Define a configuration specific to a single instance; for example, setting the location of the keystore on a particular host.
- Define a configuration whose parameters vary between different environments; for example, the URLs and passwords for test, development, and production environments.
- Disable certain capabilities on specific nodes.

Property value substitution uses *configuration tokens* for variables in the server configuration. The substitution follows a process of token resolution, JSON evaluation, and data transformation. The following pages describe this in detail.

- [Configuration Tokens](#)

- [Token Resolution](#)
- [JSON Evaluation](#)
- [Transformations](#)

Configuration Tokens

A configuration token is a simple reference to a value. When configuration tokens are resolved, the result is always a string. Transformation described in [Transformations](#) can be used to coerce the output type.

Configuration Tokens for File System

PingGateway provides `ig.instance.dir` and `ig.instance.url` to define the file system directory and URL for configuration files.

Their values are computed at startup, and evaluate to a directory such as `$HOME/.openig` (`%appdata%\OpenIG`). You can use these tokens in your configuration without explicitly setting their values.

For information about how to change the default values, refer to [Configuration location](#).

Syntax

Configuration tokens follow the syntax `&{token[|default]}`, as follows:

- Are preceded by an ampersand, `&`
- Are enclosed in braces, `{ }`
- Define default values with a vertical bar (`|`) after the configuration token
- Are in lowercase
- Use the period as a separator, `.`

When a configuration token is supplied in a configuration parameter, it is always inside a string enclosed in quotation marks, as shown in the following example:

```
"&{listen.port|8080}"
```

To escape a string with the syntax of a configuration token, use a backslash (`\`). The following string is treated as normal text:

```
"\&{listen.port|8080}"
```

A configuration property can include a mix of static values and expressions, as shown in the following example:

```
"&{hostname}.example.com"
```

Configuration tokens can be nested inside other configuration tokens as shown in the following example:

```
"&{{protocol.scheme}.port}"
```

Default values or values in the property resolver chain can be nested, as shown in the following example:

```
"&{{protocol.scheme|http}.port|8080}"
```

Token Resolution

At startup, the bootstrap resolver builds a chain of resolvers to resolve configuration tokens included in `config.json` and `admin.json`. When a route is deployed, *route resolvers* build on the chain to add resolvers for the route.

Route Token Resolvers

When a route is deployed in PingGateway a route resolver is created to resolve the configuration tokens for the route. The resolver uses token values defined in the `properties` section of the route.

If the token can't be resolved locally, the route resolver accesses token values recursively in a parent route.

Learn more about route properties in [PingGateway route properties](#).

Environment Variables Resolver

When the bootstrap resolver resolves a configuration token to an environment variable, it replaces the lowercase and periods (`.`) in the token to match the convention for environment variables.

Environment variable keys are transformed as follows:

- Periods (`.`) are converted to underscores
- All characters are transformed to uppercase

The following example sets the value of an environment variable for the port number:

```
$ export LISTEN_PORT=8080
```

In the following PingGateway configuration, the value of `port` is `8080`:

```
{  
  "port": "&{{listen.port}}"  
}
```

System Properties Resolver

The system property name must match a configuration token exactly. The following example sets a system property for a port number:

```
$ java -Dlisten.port=8080 -jar start.jar
```

In the following PingGateway configuration, the value of `port` is `8080`:

```
{
  "port": "${listen.port}"
}
```

Token Source File Resolvers

Token source files have the `.json` or `.properties` extension. The bootstrap resolver uses the files to add file resolvers to the chain of resolvers:

• JSON file resolvers

Token source files with the `.json` extension take a JSON format. The token name is mapped either to the JSON attribute name or to the JSON path.

Each of the following `.json` files set the value for the configuration token `product.listen.port`:

```
{
  "product.listen.port": 8080
}
```

```
{
  "product.listen": {
    "port": 8080
  }
}
```

```
{
  "product": {
    "listen": {
      "port": 8080
    }
  }
}
```

• Properties file resolvers

Token source files with the `.properties` extension are Java properties files. They contain a flat list of key/value pairs, and keys must match tokens exactly.

The following `.properties` file also sets the value for the tokens `listen.port` and `listen.address`:

```
listen.port=8080
listen.address=192.168.0.10
```

Token source files are stored in one or more directories defined by the environment variable `IG_ENVCONFIG_DIRS` or the system property `ig.envconfig.dirs`.

If token source files are in multiple directories, each directory must be specified in a comma-separated list. PingGateway doesn't scan subdirectories. The following example sets an environment variable to define two directories that hold token source files:

```
$ export IG_ENVCONFIG_DIRS="/myconfig/directory1,/myconfig/directory2"
```

At startup, the bootstrap resolver scans the directories in the specified order, and adds a resolver to the chain of resolvers for each token source file in the directories.

Although the bootstrap resolver scans the directories in the specified order, within a directory it scans the files in a nondeterministic order.

Note the following constraints for using the same configuration token more than once:

- Don't define the same configuration token more than once in a single file. There is no error, but you won't know which token is used.
- Don't define the same configuration token in more than one file in a single directory. An error occurs.



Important

This constraint implies that you can't have backup `.properties` and `.json` files in a single directory if they define the same tokens.

- You can define the same configuration token once in several files that are located in different directories, but the first value that PingGateway reads during JSON evaluation is used.



Note

When logging is enabled at the DEBUG level for token resolvers, the origin of the token value is logged. If you are using the default logback implementation, add the following line to your `logback.xml` to enable logging:

```
<logger name="org.forgerock.config.resolvers" level="DEBUG" />
```

JSON Evaluation

JSON evaluation is the process of substituting configuration tokens and transforming JSON nodes for an entire JSON configuration. After JSON evaluation, all configuration tokens and transformations in the configuration are replaced by values.

At startup, PingGateway evaluates the configuration tokens in `config.json` and `admin.json`. When routes are deployed, PingGateway evaluates the configuration tokens in the route.

Configuration tokens are matched with tokens available in the chain of resolvers, and the configuration token is substituted with the value available in the resolver. For information about each of the resolvers mentioned in the following section, refer to [Token Resolution](#).

PingGateway searches for matching tokens in the chain of resolvers, using the following order of precedence:

1. Local resolver:

The route resolver for the route being deployed

2. Intermediate resolver:

All intermediate route resolvers (for example, for parent routes to the route being deployed) up to the bootstrap resolver

3. Bootstrap resolver:

1. Environment variables resolver
2. System properties resolver
3. Token source file resolvers
4. Hardcoded default values

The first resolver that matches the token returns the value of the token.

If the token can't be resolved, PingGateway uses the default value defined with the configuration token. If there is no default value, the token can't be resolved and an error occurs:

- If the configuration token is in `config.json` or `admin.json`, PingGateway fails to start up.
- If the configuration token is in a route, the route fails to load.

When configuration tokens are nested inside other configuration tokens, the tokens are evaluated bottom-up, or leaf-first. For example, if the following configuration token takes only the default values, it is resolved as follows:

1. `"&{{protocol.scheme|http}.port|8080}"`
2. `"&{http.port|8080}"`

When `&{protocol.scheme|http}` takes the default value `http`.

3. `"8080"`

When `&{http.port|8080}` takes the default value `8080`.

If the configuration includes a transformation, PingGateway applies the transformation after the token is substituted. When transformations are nested inside other transformations, the transformations are applied bottom-up, or leaf-first. For more information, refer to [Transformations](#).

Transformations

A set of built-in transformations are available to coerce strings to other data types. The transformations can be applied to any string, including strings resulting from the resolution of configurations tokens.

After transformation, the JSON node representing the transformation is replaced by the result value.

The following sections describe how to use transformations, and describe the transformations available:

Usage

```
{
  "$transformation": string or transformation
}
```

A transformation is a JSON object with a required main attribute, starting with a `$`. The following example transforms a string to an integer:

```
{"$int": string}
```

The value of a transformation value can be a JSON string or another transformation that results in a string. The following example shows a nested transformation:

```
{
  "$array": {
    "$base64:decode": string
  }
}
```

The input string must match the format expected by the transformation. In the previous example, because the final transformation is to an array, the input string must be a string that represents an array, such as `"[ \"one\", \"two\" ]"`.

In the first transformation, the encoded string is transformed to a base64-decoded string. In the second, the string is transformed into a JSON array, for example, `[ "one", "two" ]`.

array

```
{"$array": string}
```

Returns a JSON array of the argument.

Argument	Returns
string String representing a JSON array.	array JSON array of the argument.

The following example transformation results in the JSON array `[ "one", "two" ]`:

```
{"$array": "[ \"one\", \"two\" ]"}
```


bool

```
{ "$bool": string }
```

Returns `true` if the input value equals `"true"` (ignoring case). Otherwise, returns `false`.

Argument	Returns
string String containing the boolean representation.	boolean Boolean value represented by the argument.

If the configuration token `&{capture.entity}"` resolves to `"true"`, the following example transformation results in the value `true`:

```
{ "$bool": "&{capture.entity}" }
```

decodeBase64

```
{
  "$base64:decode": string,
  "$charset": "charset"
}
```

Transforms a base64-encoded string into a decoded string. If `$charset` is specified, the decoded value is interpreted with the character set.

Argument	Parameters	Returns
string Base64-encoded string.	\$charset The name of a Java character set, as described in Class Charset .	string Base64-decoded string in the given character set.

The following example transformation returns the `Hello` string:

```
{
  "$base64:decode": "SGVsbG8=",
  "$charset": "UTF-8"
}
```

encodeBase64

```
{
  "$base64:encode": string,
  "$charset": "charset"
}
```

Transforms a string into a base64-encoded string. Transforms to `null` if the string is `null`.

If `$charset` is specified, the string is encoded with the character set.

Argument	Parameters	Returns
string String to encode with the given character set.	\$charset The name of a Java character set, as described in Class Charset .	string Base64-encoded string.

int

```
{"$int": string}
```

Transforms a string into an integer.

If the parameter isn't a valid number in radix 10, returns `null`.

Argument	Returns
string String containing the integer representation.	int Integer value represented by the argument.

The following example transformation results in the integer `1234`:

```
{"$int": "1234"}
```

list

```
{"$list": string}
```

Transforms a comma-separated list of strings into a JSON array of strings

Argument	Returns
string A string representing a comma-separated list of strings.	array The JSON array of the provided argument. Values aren't trimmed of leading spaces.

The following example transformation results in the array of strings `["Apple", "Banana", "Orange", "Strawberry"]`:

```
{ "$list": "Apple,Banana,Orange,Strawberry" }
```

The following example transformation results in the array of strings `["Apple", " Banana", " Orange", " Strawberry"]`, including the untrimmed spaces:

```
{ "$list": "Apple, Banana, Orange, Strawberry" }
```

The following example transformation results in the array of strings `["1", "2", "3", "4"]`, and not an array of JSON numbers `[1,2,3,4]`:

```
{ "$list": "1,2,3,4" }
```

number

```
{ "$number": string }
```

Transform a string into a Java number, as defined in [Class Number](#).

Argument	Returns
strings A string containing the number representation.	number The number value represented by the argument.

The following example transformation results in the number `0.999`:

```
{ "$number": ".999" }
```

object

```
{ "$object": string }
```

Transforms a string representation of a JSON object into a JSON object.

Argument	Returns
string String representation of a JSON object.	object JSON object of the argument.

The following example transformation

```
{ "$object": "{ \"ParamOne\": { \"InnerParamOne\": \"InnerParamOneValue\", \"InnerParamTwo\": false } }" }
```

results in the following JSON object:

```
{
  "ParamOne": {
    "InnerParamOne": "myValue",
    "InnerParamTwo": false
  }
}
```

string

```
{ "$string": placeholder string }
```

Transforms a string representation of a JSON object into a placeholder string. Placeholder strings aren't encrypted.

Use this transformation for placeholder strings that that must not be encrypted.

Argument	Returns
string String representation of a JSON object.	placeholder string Placeholder string.

This example transformation:

```
{
  "someAttributeExpectingString": { "$string": "&{ig.instance.dir}" }
}
```

results in this JSON object:

```
{
  "someAttributeExpectingString": "/path/to/ig"
}
```

PingGateway expressions

Use expressions that conform to the Unified Expression Language in [JSR-245](#) to specify configuration parameters as expressions in routes. The result of an expression must match the expected type. For examples of expressions used in routes, refer to [Examples](#).

Use expressions in routes for the following tasks:

Evaluate object properties

The following example returns the URI of the incoming request:

```
${request.uri}
```

Call functions described in [PingGateway functions](#)

Functions can be operands for operations and can yield parameters for other function calls.

The following example uses the function `find` to test whether the request URI is on the `/home` path:

```
${find(request.uri.path, '^/home')}
```

Call Java methods

The following example uses the method Java `String.startsWith()` to test whether the request starts with `/home`:

```
${request.uri.path.startsWith("/home")}
```

Retrieve Java system properties

The following example yields the home directory of the user executing the PingGateway process:

```
${system['user.home']}
```

Retrieve environment variables

The following example yields the home directory of the user executing the PingGateway process:

```
${env['HOME']}
```

The following example yields the path value of the `keystore.p12` file in the user's home directory. The result is just a String concatenation, there is no verification that the file actually exists:

```
${env['HOME']}/keystore.p12`
```

Perform logical operations such as and, or, and not

The following expression uses the operators `and` and `or` to determine where to dispatch a request. The expression is used in [Share JWT sessions between multiple instances of PingGateway](#):

```
${find(request.uri.path, '/webapp/browsing') and (contains(request.uri.query, 'one') or empty(request.uri.query))}
```

Perform arbitrarily complex arithmetic, such as addition, subtraction, division, and multiplication

The following expression yields the URI port number incremented by four:

```
${request.uri.port + 4}
```

Perform relational operations, such as numerical equality and inequality

The following example is for a `DispatchHandler` condition, where the request is dispatched if it contains a form field with the attribute `answer` whose value is greater than `42`:

```
"bindings": [
  {
    "condition": "${request.entity.form['answer'] > 42}",
    "handler": ...
  }
]
```

Perform conditional operations of this form <condition> ? <if-true> : <if-false>

The following example tests whether the request path starts with `/home`. If so, the request is directed to `home`; otherwise, it is directed to `not-home`:

```
${request.uri.path.startsWith('/home') ? 'home' : 'not-home' }
```

Consume evaluated configuration tokens described in [JSON Evaluation](#) (runtime expressions only)

The following example returns `true` if the configuration token `my.status.code` resolves to `200`:

```
${integer(&{my.status.code|404}) == 200}
```

Expressions access the environment through the implicit object `openig`. The object has the following properties:

- `instanceDirectory` : Path to the base location for PingGateway files.

The default location is:

Linux

```
$HOME/.openig
```

Windows

```
%appdata%\OpenIG\config
```

- `configDirectory` : Path to the PingGateway configuration files.

The default location is:

Linux

```
$HOME/.openig/config
```

Windows

```
%appdata%\OpenIG\config
```

- `temporaryDirectory` : Path to the PingGateway temporary files.

The default location is:

Linux

```
$HOME/.openig/tmp
```

Windows

```
%appdata%\OpenIG\tmp
```

Learn how to change default values in [Change the base location of the PingGateway configuration](#).

Syntax

Expression syntax must conform to Unified Expression Language described in [JSR-245](#).

Route syntax

Expressions in routes are enclosed in quotation marks, for example: `"${request.method}"` and `"#{expression}"`.

Immediate and deferred evaluation syntax

Use the `${}` syntax for expressions to be evaluated at startup or when a route loads or reloads.

Use the `#{}` syntax for expressions to be evaluated later, when the evaluation result requires the request or response to be fully loaded.

Operator syntax

AM uses the `.` and `[]` operators to access properties:

- Use `.` for the following tasks:
 - Access object properties, such as public fields and Java bean properties.
 - Invoke methods on an object.
 - Access map entries when the specified entry name doesn't contain reserved characters.
- Use `[]` to access indexed elements:
 - If the object is a collection, such as an array, set, or list, use `[i]` to access an element at position `i`.
 - If the object isn't a collection, such as an array, set, or list, use `['prop']` to access the property `'prop'`. This is equivalent to `.` notation. The following expressions are equivalent:

```
${request.method}
```

```
${request['method']}
```

- If the object is a map, use `['name']` to access the entry with name `'name'`.

Tip

To access map entries containing characters that are also expression operators, prevent parsing exceptions by using `[]` instead of `.`

For example, to access a map field containing a dash `-`, such as `dash-separated-name`, write the expression as:

```
${data['dash-separated-name']}
```

instead of:

```
${data.dash-separated-name}
```

In the second example, the dash `-` is interpreted as part of the String instead of as an expression operator.

Array syntax

The index of an element in an array is expressed as a number in brackets. For example, the following expression refers to the first `Content-Type` header value in a request:

```
${request.headers['Content-Type'][0]}
```

Map syntax

The map key is expressed in brackets. For example, the following expression is an example of Map entry access:

```
system['prop.name']
```


If a property doesn't exist, the index reference yields a `null` (empty) value.

Function syntax

Expressions can call built-in functions described in [PingGateway functions](#).

Use the syntax `${function(parameter, ...)}`, supplying one or more parameters to the function. For examples, refer to [Expressions that use functions](#).

Functions can be operands for operations and can yield parameters for other function calls.

Method syntax

Use the syntax `${object.method()}` to call a method on the object instance.

If the object resolves to a String, then all methods in the `java.lang.String` class are usable.

For examples, refer to [Expressions that use functions](#).

Escape syntax

The character `\` is treated as an escape character when followed by `${` or `\#{`.

For example, the expression `${true}` normally evaluates to `true`. To include the string `${true}` in an expression, write `\${true}`.

When `\` is followed by any other character sequence, it isn't treated as an escape character.

Configuration expressions

PingGateway evaluates configuration expressions at startup and when a route loads or reloads. Configuration expressions are always evaluated immediately and use the `${}` syntax.

Configuration expressions can refer to the following information:

- System heap properties
- Built-in functions listed in [PingGateway functions](#)
- Environment variables, `${env['variable']}`
- System properties, `${system['property']}`
- [ExpressionInstant](#)

Because configuration expressions are evaluated before requests are made, they can't refer to the runtime properties `request`, `response`, `context`, or `contexts`.

Runtime expressions

PingGateway evaluates runtime expressions for each request and response, as follows:

Immediate evaluation of runtime expressions

If the expression consumes streamed content, for example, the content of a request or response, PingGateway blocks the executing thread until all the content is available.

Runtime expressions whose evaluation is immediate are written with the `${}` syntax.

Deferred evaluation of runtime expressions

PingGateway waits until all streamed content is available before it evaluates the expression. Deferred evaluation doesn't block executing threads.

Runtime expressions whose evaluation is deferred are written with the `#{}` syntax.

When the `streamingEnabled` property in `admin.json` is `true`, expressions that consume streamed content **must** be written with `#` instead of `$`.

Runtime expressions can refer to the following information:

- System heap properties
- Built-in functions listed in [PingGateway functions](#)
- Environment variables
- System properties
- [ExpressionInstant](#)
- `attributes`: [org.forgerock.services.context.AttributesContext](#) [↗](#) `Map<String, Object>`, obtained from `AttributesContext.getAttributes()`. For information, refer to [AttributesContext](#).
- `context`: [org.forgerock.services.context.Context](#) [↗](#) object.
- `contexts`: `map<string, context>` object. For information, refer to [PingGateway context reference](#).
- `request`: [org.forgerock.http.protocol.Request](#) [↗](#) object. For information, refer to [Request](#).
- `response`: [org.forgerock.http.protocol.Response](#) [↗](#) object, available only when the expression is intended to be evaluated on the response flow. For information, refer to [Response](#).
- `session`: [org.forgerock.http.session.Session](#) [↗](#) object, available only when the expression is intended to be evaluated for both request and response flow. For information, refer to [SessionContext](#).

Embedded expressions

Consider the following points when embedding expressions:

- System properties, environment variables, or function expressions can be embedded within expressions.

The following example embeds an environment variable in the argument for a `read()` function. The value of `entity` is set to the contents of the file `$HOME/.openid/html/defaultResponse.html`, where `$HOME/.openid` is the instance directory:

```
"entity": "${read('&{ig.instance.dir}/html/defaultResponse.html')}"
```

- Expressions can't be embedded inside other expressions, as `${expression}`.
- Embedded elements can't be enclosed in `${}`.

Extensions

PingGateway offers a plugin interface for extending expressions. See [Key extension points](#).

L-value expressions

L-value expressions assign a value to the expression scope. For example, `"${session.gotoURL}"` assigns a value to the session attribute named `gotoURL`.

PingGateway ignores attempts to write to read-only values.

L-value expressions must be specified using immediate evaluation syntax; use `$` instead of `#`.

Operators

The following operators are provided by Unified Expression Language:

- Index property value: `[]`, `.`
- Change precedence: `()`
- Arithmetic: `+` (binary), `-` (binary), `*`, `/`, `div`, `%`, `mod`, `-` (unary)
- Logical: `and`, `&&`, `or`, `||`, `not`, `!`
- Relational: `==`, `eq`, `!=`, `ne`, `<`, `lt`, `>`, `gt`, `<=`, `le`, `>=`, `ge`
- Empty: `empty`
Use this prefix operator to determine whether a value is null or empty.
- Conditional: `?`, `:`

Operators have the following precedence, from highest to lowest, and from left to right:

- `[]` `.`
- `()`
- `-` (unary) `not` `!` `empty`
- `*` `/` `div` `%` `mod`
- `+` (binary) `-` (binary)
- `<` `>` `<=` `>=` `lt` `gt` `le` `ge`
- `==` `!=` `eq` `ne`

- `&&` and
- `||` or
- `?` :

Dynamic bindings

Configuration and runtime expressions can use [ExpressionInstant](#).

The current instant is `${now.epochSeconds}`.

To add or subtract a period of time to the instant, add one or more of the following time periods to the binding:

- `plusMillis(integer)`, `minusMillis(integer)`
- `plusSeconds(integer)`, `minusSeconds(integer)`
- `plusMinutes(integer)`, `minusMinutes(integer)`
- `plusHours(integer)`, `minusHours(integer)`
- `plusDays(integer)`, `minusDays(integer)`

The following example binding refers to 30 minutes after the current instant:

```
${now.plusMinutes(30).epochSeconds}
```

The following example binding accesses the instant in RFC 1123 date format one day after the current instant:

```
${now.plusDays(1).rfc1123}
```

For more examples, refer to the `template` property of [JwtBuilderFilter](#) and the `attribute-name` property of [SetCookieUpdateFilter](#).

Examples

Immediate evaluation of configuration expressions

The following example yields the value of a secret from a system property.

```
{
  "passwordSecretId": "${system['keypass']}"
}
```

The following example yields a file from the home directory of the user running the PingGateway application server.

```
{
  "url": "file://${env['HOME']}/keystore.p12"
}
```

The following example of a `temporaryStorage` object takes the value of the system property `storage.ref`, which must be a string equivalent to the name of an object defined in the heap:

```
{
  "temporaryStorage": "${system['storage.ref']}"
}
```

Deferred evaluation of runtime expressions

The following example is a Route condition, where the Route is accessed if the request contains json with the attribute `answer`, whose value is `42`.

PingGateway defers evaluation of the expression until it receives the entire body of the request, transforms it to JSON view, and then introspects it for the attribute `answer`.

```
{
  "condition": "#{request.entity.json['answer'] == 42}",
  "handler": ...
}
```

The following example expression is for a `JwtBuilderFilter` that uses the content of the request mapped as a string. PingGateway defers evaluation of the expression until it receives the entire body of the request:

```
{
  "template": {
    "content": "#{request.entity.string}"
  }
}
```

Immediate and deferred evaluation of runtime expressions

The following example expressions are for an `AssignmentFilter` that consumes an ID captured from a response.

PingGateway evaluates the first expression immediately to define the target.

It then defers evaluation of the second expression until it receives the entire body of the response.

```
"onResponse": [
  {
    "target": "${response.headers['X-IG-FooBar']}",
    "value": "#{toString(response.entity.json['userId'])}"
  }
]
```

Expressions that use functions

In the following example, `"timer"` is defined by an expression that recovers the environment variable `"ENABLE_TIMER"` and transforms it into a boolean. Similarly, `"numberOfRequests"` is defined by an expression that recovers the system property `"requestsPerSecond"` and transforms it into an integer:

```
{
  "name": "throttle-simple-expressions1",
  "timer": "${bool(env['ENABLE_TIMER'])}",
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/throttle-simple-expressions1')}",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "ThrottlingFilter",
          "name": "ThrottlingFilter-1",
          "config": {
            "requestGroupingPolicy": "",
            "rate": {
              "numberOfRequests": "${integer(system['requestsPerSecond'])}",
              "duration": "10 s"
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}
```

Source: [00-throttle-simple-expressions1.json](#)

If `"requestsPerSecond"=6` and `"ENABLE_TIMER"=true`, after the expressions are evaluated PingGateway views the example route as follows:

```
{
  "name": "throttle-simple-expressions2",
  "timer": true,
  "baseURI": "http://app.example.com:8081",
  "condition": "${find(request.uri.path, '^/home/throttle-simple-expressions2')}",
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "ThrottlingFilter",
          "name": "ThrottlingFilter-1",
          "config": {
            "requestGroupingPolicy": "",
            "rate": {
              "numberOfRequests": 6,
              "duration": "10 s"
            }
          }
        }
      ]
    },
    "handler": "ReverseProxyHandler"
  }
}
```

Source: [00-throttle-simple-expressions2.json](#)

PingGateway functions

A set of built-in functions to call in [PingGateway expressions](#).

array

`array(strings...)`

Returns an array of the strings given as argument.

Parameters

strings

Strings to put in the array.

Returns

array

Resulting array containing the given strings.

boolean

`bool(string)`

Returns a Boolean with a value represented by the specified string.

The returned Boolean represents a true value if the string argument isn't `null` and is equal to the string `"true"`, ignoring case.

Parameters

string

String containing the boolean representation.

Returns

Boolean

Boolean value represented by the string.

contains

`contains(object, value)`

Returns `true` if the object contains the specified value. If the object is a string, a substring is searched for the value. If the object is a collection or array, its elements are searched for the value.

Parameters

object

Object to search for.

value

Value to search for.

Returns

true

If the object contains the specified value.

decodeBase64

`decodeBase64(string)`

Returns the base64-decoded string, or `null` if the string isn't valid base64.

Parameters

string

Base64-encoded string to decode.

Returns

string

Base64-decoded string.

decodeBase64url

decodeBase64url(string)

Returns the decoded value of the provided base64url-encoded string, or `null` if the string was not valid base64url.

Parameters

string

Base64url-encoded string to decode.

Returns

string

Base64url-decoded string.

derCertificate

derCertificate(string)

Convert the incoming character sequence into a certificate.

Parameters

string

Character sequence representing a base64-encoded DER-format (binary) certificate.

The string begins and ends with `:`. Learn more in RFC 9440 [Appendix A](#).

Returns

string

A `Certificate` instance or `null` if the function failed to load a certificate from the incoming object.

digestSha256

digestSha256(byte array or string)

Calculates the SHA-256 hash of an incoming object.

Parameters

byte array or string

The bytes to be hashed. If a string is provided, this function uses the UTF-8 charset to get the bytes from the string.

Returns

byte array

SHA-256 hash as a byte array, or null if the hash could not be calculated.

encodeBase64

encodeBase64(string)

Returns the base64-encoded string, or `null` if the string is `null`.

Parameters

string

String to encode into base64.

Returns

string

Base64-encoded string.

encodeBase64url

encodeBase64url(string)

Returns the base64url-encoded string, or `null` if the string is `null`.

Parameters

string

String to encode into base64url.

Returns

string

Base64url-encoded string.

fileToUrl

fileToUrl(file)

Converts a `java.io.File` into a string representation for the URL of the file or directory.

Parameters

file

File or directory for which to build the URL.

For example, `${fileToUrl(openig.configDirectory)}/myProperties.json`.

Returns

file

String representation for the URL of the file or directory, or `null` if the file or directory is `null`.

For example, <file:///home/gcostanza/.openig/config/myProperties.json>.

find

`find(string, pattern)`

Attempts to find the next subsequence of the input string that matches the pattern.

Parameters

string

The input string.

pattern

A [regular expression pattern](#).

Returns

boolean

- `true` if a subsequence of the input string matches the regular expression pattern.
- `false` if the input string is null, or a subsequence of it doesn't match the regular expression pattern.

findGroups

`findGroups(string, pattern)`

Attempts to find a string that matches the regular expression or groups specified in the regular expression.

Parameters

string

The input on which the regular expression is applied.

pattern

A [regular expression pattern](#).

Returns

array

An array containing the result of a find on the regular expression against the input string, or null if no result is found.

The first element of the array is the entire match, and each subsequent element correlates to a capture group specified in the regular expression.

formDecodeParameterNameOrValue

`formDecodeParameterNameOrValue(string)`

Returns the string that results from decoding the provided form encoded parameter name or value as per `application/x-www-form-urlencoded`, which can be `null` if the input is `null`.

Parameters

string

Parameter name or value.

Returns

string

String resulting from decoding the provided form encoded parameter name or value as per `application/x-www-form-urlencoded`.

formEncodeParameterNameOrValue

`formEncodeParameterNameOrValue(string)`

Returns the string that results from form encoding the provided parameter name or value as per `application/x-www-form-urlencoded`, which can be `null` if the input is `null`.

Parameters

string

Parameter name or value.

Returns

string

String resulting from form encoding the provided parameter name or value as per `application/x-www-form-urlencoded`.

indexOf

`indexOf(string, substring)`

Returns the index of the first instance of a specified substring inside a string.

Characters in the provided string are UTF-16, based on 16-bit code units. Each character is encoded as at least two bytes, and some extended characters are encoded as four bytes.

When this function processes a 2-byte character, it counts it as one 16-bit character. When it processes a 4-byte character, it counts it as two 16-bit characters.

Examples:

- The unicode character `a` (U+0061) has the UTF-16 value `0x0061`. The function `{{indexOf('afooBar', 'Bar')}}` evaluates to `4`.
- The unicode character `ü` (U+0075) has the UTF-16 value `0x0075`. The function `{{indexOf('fooBar', 'Bar')}}` evaluates to `5`.

Parameters

string

String in which to search for the specified substring.

substring

Value to search for within the string.

Returns

number

Index of the first instance of the substring, or -1 if not found.

The index count starts from 1, not 0.

integer

`integer(string)`

Transforms the string parameter into an integer. If the parameter isn't a valid number in radix 10, returns null.

Parameters

string

String containing the integer representation.

Returns

integer

Integer value represented by the string.

integerWithRadix

`integer(string, radix)`

Uses the radix as the base for the string, and transforms the string into a base-10 integer. For example:

- `("20", 8)` : Transforms `20` in base `8`, and returns `16`.
- `("11", 16)` Transforms `11` in base `16`, and returns `17`.

If either parameter isn't a valid number, returns null.

Parameters

string

String containing the integer representation, and an integer containing the radix representation.

Returns

integer

Integer value in base-10.

ipMatch

`ipMatch(string, string)`

Returns `true` if the IP address matches the range provided by the Classless Inter-Domain Routing (CIDR), `false` otherwise.

Parameters

string

IP address of a request sender, in IPv4 or IPv6

string

CIDR defining an IP address range

Returns

Boolean

`true` or `false`

join

`join(values, separator)`

Returns a string joined with the given separator, using either of the following values:

- Array of strings (`String[]`)
- Iterable value (`Iterable<String>`)

The function uses the `toString` result from each value.

Parameters

separator

Separator to place between joined values.

strings

Array of values to be joined.

Returns

string

String containing the joined values.

keyMatch

keyMatch(map, pattern)

Returns the first key found in a map that matches the specified [regular expression pattern](#), or `null` if no such match is found.

Parameters

map

Map whose keys are to be searched.

pattern

String containing the regular expression pattern to match.

Returns

string

First matching key, or `null` if no match found.

lastElement

lastElement(object)

Returns the last element of the collection or array in `object` or `null` if `object` is empty.

Returns

object

The last element or `null` if empty.

length

length(object)

Returns the number of items in a collection, or the number of characters in a string.

Characters in the provided string are UTF-16, based on 16-bit code units. Each character is encoded as at least two bytes, and some extended characters are encoded as four bytes.

When this function processes a 2-byte character, it counts it as one 16-bit character. When it processes a 4-byte character, it counts it as two 16-bit characters.

Examples:

- The unicode character `a` (U+0061) has the UTF-16 value `0x0061`. The function `{{length('a')}}` evaluates to `1`.
- The unicode character (U+10057) has the UTF-16 value `0xD800 0xDC57`. The function `{{length(' '}}` evaluates to `2`.

Parameters

object

A collection or string, whose length is to be determined.

Returns

number

Length of the collection or string, or 0 if length could not be determined.

matchesWithRegex

```
matchesWithRegex(string, pattern)
```

Attempts to match the entire input string against the regular expression pattern.

Parameters

string

The input string.

pattern

A [regular expression pattern](#).

Returns

boolean

- **true** if the entire input string matches the regular expression pattern.
- **false** if the input string is null, or the entire input string doesn't match the regular expression pattern.

pathToUrl

```
pathToUrl(path)
```

Converts the given path into the string representation of its URL.

Parameters

path

Path of a file or directory as a string.

For example, `${pathToUrl(system['java.io.tmpdir'])}`.

Returns

string

String representation for the URL of the path or **null** if the path is **null**.

For example, [file:///var/tmp](#).

pemCertificate

pemCertificate(string)

Convert the incoming character sequence into a certificate.

Parameters

string

Character sequence representing a PEM-formatted certificate

Returns

string

A `Certificate` instance or null if the function failed to load a certificate from the incoming object.

read

read(string)

Takes a file name as a string, interprets the content of the file with the UTF-8 character set, and returns the content of the file as a plain string.

Provides the absolute path to the file or a path relative to the location of the Java system property `user.dir`.

Parameters

string

Name of the file to read.

Returns

string

Content of the file or `null` on error.

readProperties

readProperties(string)

Takes a Java Properties filename as a `string`, and returns the content of the file as a key/value map of properties or `null` on error (due to the file not being found, for example).

Java properties files are expected to be encoded with ISO-8859-1. Characters that cannot be directly represented in ISO-8859-1 can be written using Unicode escapes, as defined in [Unicode Escapes](#), in *The Java™ Language Specification*.

Parameters

string

The absolute path to the Java properties file or a path relative to the location of the Java system property `user.dir`.

For example, to return the value of the `key` property in the Java properties file `/path/to/my.properties`, provide `${readProperties('/path/to/my.properties')['key']}`.

Returns

object

Key/value map of properties or `null` on error.

readWithCharset

`readWithCharset(string, string)`

Takes a file name as a string, interprets the content of the file with the specified Java character set, and returns the content of the file as a plain string.

Parameters

filename

Name of the file to read.

Provides the absolute path to the file or a path relative to the location of the Java system property `user.dir`.

charsetName

Name of a Java character set with which to interpret the file, as described in [Class Charset](#).

Returns

string

Content of the file or `null` on error.

split

`split(string, pattern)`

Splits the specified string into an array of substrings around matches for the specified [regular expression pattern](#).

Parameters

string

String to be split.

pattern

Regular expression to split substrings around.

Returns

array

Resulting array of split substrings.

toJson

toJson(JSON string)

Converts a JSON string to a JSON structure.

Parameters

JSON string

JSON string representing a JavaScript object.

For example, the string value contained in `contexts.amSession.properties.userDetails` contains the JSON object `{"email": "test@example.com"}`.

Returns

JSON structure

JSON structure or `null` on error.

In the expression `"${toJson(contexts.amSession.properties.userDetails).email}"`, the string value is treated as JSON, and the expression evaluates to `test@example.com`.

toLowerCase

toLowerCase(string)

Converts all the characters in a string to lowercase.

Parameters

string

String whose characters are to be converted.

Returns

string

String with characters converted to lowercase.

toString

toString(object)

Returns the string value of an arbitrary object.

Parameters

object

Object whose string value is to be returned.

Returns

string

String value of the object.

toUpperCase

```
toUpperCase(string)
```

Converts all of the characters in a string to upper case.

Parameters

string

String whose characters are to be converted.

Returns

string

String with characters converted to upper case.

trim

```
trim(string)
```

Returns a copy of a string with leading and trailing whitespace omitted.

Parameters

string

String whose white space is to be omitted.

Returns

string

String with leading and trailing white space omitted.

urlDecode

```
urlDecode(string)
```

Returns the URL decoding of the provided string.

This is equivalent to [formDecodeParameterNameOrValue](#).

Parameters

string

String to be URL decoded, which may be `null`.

Returns

string

URL decoding of the provided string, or `null` if string was `null`.

urlEncode

```
urlEncode(string)
```

Returns the URL encoding of the provided string.

This is equivalent to [formEncodeParameterNameOrValue](#).

Parameters

string

String to be URL encoded, which can be `null`.

Returns

string

URL encoding of the provided string or `null` if string was `null`.

urlDecodeFragment

```
urlDecodeFragment(string)
```

Returns the string that results from decoding the provided URL encoded fragment as per RFC 3986, which can be `null` if the input is `null`.

Parameters

string

URL encoded fragment.

Returns

string

String resulting from decoding the provided URL encoded fragment as per RFC 3986.

urlDecodePathElement

```
urlDecodePathElement(string)
```

Returns the string that results from decoding the provided URL encoded path element as per RFC 3986, which can be `null` if the input is `null`.

Parameters

string

The path element.

Returns

string

String resulting from decoding the provided URL encoded path element as per RFC 3986.

urlDecodeQueryParameterNameOrValue

`urlDecodeQueryParameterNameOrValue(string)`

Returns the string that results from decoding the provided URL encoded query parameter name or value as per RFC 3986, which can be `null` if the input is `null`.

Parameters

string

Parameter name or value.

Returns

string

String resulting from decoding the provided URL encoded query parameter name or value as per RFC 3986.

urlDecodeUserInfo

`urlDecodeUserInfo(string)`

Returns the string that results from decoding the provided URL encoded userInfo as per RFC 3986, which can be `null` if the input is `null`.

Parameters

string

URL encoded userInfo.

Returns

string

String resulting from decoding the provided URL encoded userInfo as per RFC 3986.

urlEncodeFragment

`urlEncodeFragment(string)`

Returns the string that results from URL encoding the provided fragment as per RFC 3986, which can be `null` if the input is `null`.

Parameters

string

Fragment.

Returns

string

The string resulting from URL encoding the provided fragment as per RFC 3986.

urlEncodePathElement

```
urlEncodePathElement(string)
```

Returns the string that results from URL encoding the provided path element as per RFC 3986, which can be `null` if the input is `null`.

Parameters

string

Path element.

Returns

string

String resulting from URL encoding the provided path element as per RFC 3986.

urlEncodeQueryParameterNameOrValue

```
urlEncodeQueryParameterNameOrValue(string)
```

Returns the string that results from URL encoding the provided query parameter name or value as per RFC 3986, which can be `null` if the input is `null`.

Parameters

string

Parameter name or value.

Returns

string

String resulting from URL encoding the provided query parameter name or value as per RFC 3986.

urlEncodeUserInfo

```
urlEncodeUserInfo(string)
```

Returns the string that results from URL encoding the provided userInfo as per RFC 3986, which can be `null` if the input is `null`.

Parameters

string

userInfo.

Returns

string

String resulting from URL encoding the provided userInfo as per RFC 3986.

More information

Some functions are provided by [org.forgerock.openig.el.Functions](#).

Other functions are provided by [org.forgerock.http.util.Uris](#).

Patterns and PingGateway

Patterns in configuration parameters and expressions use the standard Java regular expression [Pattern](#) class. For more information on regular expressions, refer to Oracle's [tutorial on Regular Expressions](#).

Pattern templates

A regular expression pattern template expresses a transformation to apply for a matching regular expression pattern. It may contain references to [capturing groups](#) within the match result. Each occurrence of `$g`, where `g` is an integer value, is substituted by the indexed capturing group in a match result. Capturing group zero `"$0"` denotes the entire pattern match. A dollar sign or numeral literal immediately following a capture group reference can be included as a literal in the template by preceding it with a backslash (`\`). Backslash itself must be also escaped in this manner.

More information

Java [Pattern](#) class

[Regular Expressions tutorial](#)

PingGateway scripts

PingGateway uses Groovy for scripting. Learn more in the [Groovy Language Documentation](#).

Groovy scripts used in the PingGateway configuration are restricted to the UTF-8 character set.

Use Groovy scripts with the following object types:

- [ScriptableFilter](#) to customize the flow of requests and responses.
- [ScriptableHandler](#) to customize response creation.
- [ScriptableThrottlingPolicy](#) to customize throttling rates.
- [ScriptableAccessTokenResolver](#) to customize resolution and validation of OAuth 2.0 access tokens.

- `ScriptableResourceAccess` in [OAuth2ResourceServerFilter](#) to customize the list of OAuth 2.0 scopes required in an OAuth 2.0 access token.
- [ScriptableIdentityAssertionPlugin](#) with an [IdentityAssertionHandler](#) for local processing.

When PingGateway accesses a script, it compiles and then caches the script. PingGateway uses the cached version until the script is changed.

After you update a script used in a route, wait at least one second before processing a request. The Groovy interpreter needs time to detect and take the update into account.

Important

When writing scripts or Java extensions that use the Promise API, avoid the blocking methods `get()`, `getOrThrow()`, and `getOrThrowUninterruptibly()`. A promise represents the result of an asynchronous operation; therefore, using a blocking method to wait for the result can cause deadlocks and/or race issues. Instead, consider using `then()` methods, such as `thenOnResult()`, `thenAsync()`, or `thenCatch()`, which allow execution blocks to be executed when the response is available.

Blocking code example

```
def response = next.handle(ctx, req).get() // Blocking method 'get' used
response.headers['new']="new header value"
return response
```

Non-blocking code example

```
return next.handle(ctx, req)
    .thenOnResult { response ->
        response.headers['new']="new header value"
    }
```

Usage

```
{
  "name": string,
  "type": scriptable object type,
  "config": {
    "type": string,
    "file": configuration expression<string>, // Use either "file"
    "source": [ string, ... ], // or "source", but not both.
    "args": map or configuration expression<map>,
    "clientHandler": Handler reference
  }
}
```

Properties

"type": *string, required*

The Internet media type (formerly MIME type) of the script, "application/x-groovy" for Groovy

"file": *configuration expression<string>, required if source isn't used*

Path to the file containing the script; mutually exclusive with `source`. Specify `file` as follows:

For Groovy files from default packages

- Place Groovy files in the base script directory, `$HOME/.openig/scripts/groovy` (on Windows, `%appdata%\OpenIG\scripts\groovy`). For example, place `myScript.groovy` from the default package in `$HOME/.openig/scripts/groovy`.
- Specify `file` with the filename of the Groovy file. For the previous example, specify:

```
"config": {
  "type": "application/x-groovy",
  "file": "myScript.groovy"
}
```

For Groovy files from non-default packages

- Place Groovy files in a subdirectory of the base script directory that corresponds to the package name. For example, place `myScript.groovy` from the package `com.example.groovy` in `$HOME/.openig/scripts/groovy/com/example/groovy`.
- Specify `file` with the relative path from the base script directory **and** the filename. For the previous example, specify:

```
"config": {
  "type": "application/x-groovy",
  "file": "com/example/groovy/myScript.groovy"
}
```



Important

PingGateway runs scripts from an absolute path, or from a path relative to the base script directory. Routes that refer to scripts otherwise, such as through a URL, fail to deploy.

Do one of the following to prevent errors:

- Move scripts to the base script directory or the correct subdirectory of the base script directory.
- Refer to scripts through an absolute path.

"source": *array of <strings>, required if file is not used*

The script as one or more strings; mutually exclusive with `file`.

The following example shows the source of a script as an array of strings:

```
"source": [
  "Response response = new Response(Status.OK)",
  "response.entity = 'foo'",
  "return response"
]
```

"args": *map or configuration expression<map>, optional*

A map of one or more data pairs with the format `Map<String, String>`, where:

- The key is the name of a configuration parameter in a script
- The value is a string to use in the script, or a configuration expression that evaluates to the string

The following formats are allowed:

```
{
  "args": {
    "string": "configuration expression<string>",
    ...
  }
}
```

```
{
  "args": "configuration expression<map>"
}
```

In the following example, the property is a map whose values are scalars, arrays, and objects:

```
{
  "args": {
    "title": "Coffee time",
    "status": 418,
    "reason": [
      "Not Acceptable",
      "I'm a teapot",
      "Acceptable"
    ],
    "names": {
      "1": "koffie",
      "2": "kafe",
      "3": "cafe",
      "4": "kafo"
    }
  }
}
```

- A script can access the `args` parameters in the same way as other global objects. The following example sets the response status to `I'm a teapot`:

```
response.status = Status.valueOf(418, reason[1])
```

For information about the 418 status code refer to [RFC 7168: 418 I'm a Teapot](#).

- The following example configures arguments as strings and numbers for a ScriptableThrottlingPolicy:

```
"args": {
  "status": "gold",
  "rate": 6,
  "duration": "10 seconds"
}
```

The following lines set the throttling rate to 6 requests each 10 seconds when the response status is `gold`:

```
if (attributes.rate.status == status) {
  return new ThrottlingRate(rate, duration)
}
```

- The following example configures arguments that reference a SampleFilter defined in the heap:

```
{
  "heap": [
    {
      "name": "SampleFilter",
      "type": "SampleFilter",
      "config": {
        "name": "X-Greeting",
        "value": "Hello world"
      }
    }
  ]
}
```

In the following example, the property is a map whose value is an expression to pass SampleFilter to the script:

```
{
  "args": {
    "filter": "${heap['SampleFilter']}"
  }
}
```

The script can then reference SampleFilter as `filter`.

"clientHandler": *ClientHandler* [reference](#), optional

A [Handler](#) for making outbound HTTP requests to third-party services. In a script, `clientHandler` is wrapped within the global object `http`.

Default: The default ClientHandler.

Available objects

The following global objects are available to scripts:

Any parameters passed as args

You can use the configuration to pass parameters to the script by specifying an args object.

The args object is a map whose values can be scalars, arrays, and objects. The args object can reference objects defined in the heap by using expressions, for example, "`${heap['ObjectName']}`".

The values for script arguments can be defined as configuration expressions, and evaluated at configuration time.

Script arguments cannot refer to `context` and `request`, but `context` and `request` variables can be accessed directly within scripts.

Take care when naming keys in the args object. If you reuse the name of another global object, cause the script to fail and PingGateway to return a response with HTTP status code 500 Internal Server Error.

All heap objects

The heap object configuration, described in [Heap objects](#).

openig

An implicit object that provides access to the environment when expressions are evaluated.

attributes

The [attributes](#) object provides access to a context map of arbitrary attributes, which is a mechanism for transferring transient state between components when processing a single request.

Use `session` for maintaining state between successive requests from the same logical client.

builder

For ScriptableJwtValidatorCustomizer only.

Used by the ScriptableJwtValidatorCustomizer and [JwtValidationFilter](#) to create constraints to test JWT claims and sub-claims. The purpose of the ScriptableJwtValidatorCustomizer is to enrich the `builder` object.

For information about methods to enrich the `builder` instance, refer to [JwtValidator.Builder](#).

constraints

The [constraints](#) object, all its static methods, `constant(String)`, and `claim(String)`.

Use this object for JWT validation with the `customizer` property of [JwtValidationFilter](#).

`claim(String)` must be followed by one of the following methods: `asString()`, `asInteger()`, `asLong()`, `asDouble()`, `asBoolean()`, `as(yourCustomJsonValueTransformer)`

context

The processing [context](#).

This context is the leaf of a chain of contexts. It provides access to other Context types, such as SessionContext, AttributesContext, and ClientContext, through the `context.asContext(ContextClass.class)` method.

contexts

a map<string, context> object. For information, refer to [PingGateway context reference](#).

request

The HTTP [request](#).



Important

The `request.form` method, used in scripts to read or set query and form parameters, is deprecated. Use the following replacement settings:

- `Request.getQueryParams()` to read query parameters
- `Entity.getForm()` to read form parameters
- `Entity.setForm()` to set form parameters

For more information, refer to the [Deprecated](#) section of the *Release Notes*.

globals

This object is a [Map](#) that holds variables that persist across successive invocations.

http

An embedded client for making outbound HTTP requests, which is an [org.forgerock.http.Client](#).

If a `"clientHandler"` is set in the configuration, then that Handler is used. Otherwise, the default ClientHandler configuration is used.

For information, refer to [PingGateway handlers](#).

logger

The [logger](#) object provides access to a unique SLF4J logger instance for scripts, where the logger instance is named with the script name.

For information about logging for scripts, refer to [Logging in scripts](#).

next

The object named [next](#) refers to the next element in the chain, which can be the following filter or the terminal handler. If the next object in the chain is a filter, PingGateway wraps it in a handler.

session

The [session](#) object provides access to the session context, which is a mechanism for maintaining state when processing a successive requests from the same logical client or end user.

Use `attributes` for transferring transient state between components when processing a single request.

Imported classes

The following classes are imported automatically for Groovy scripts:

- [org.forgerock.http.Client](#)
- [org.forgerock.http.Filter](#)
- [org.forgerock.http.Handler](#)
- [org.forgerock.http.protocol.Header](#)
- [org.forgerock.openig.filter.throttling.ThrottlingRate](#)
- [org.forgerock.http.util.Uris](#)
- [org.forgerock.util.AsyncFunction](#)
- [org.forgerock.util.Function](#)
- [org.forgerock.util.promise.NeverThrowsException](#)
- [org.forgerock.util.promise.Promise](#)
- [org.forgerock.util.promise.Promises](#)
- [org.forgerock.services.context.Context](#)
- `org.forgerock.http.protocol.*`
- [org.forgerock.http.oauth2.AccessTokenInfo](#)
- [org.forgerock.json.JsonValue](#), and all its static methods, including `json(Object)`, `array(Object...)`, `object(fields...)`, and `field(String, Object)`
- [org.forgerock.openig.util.JsonValues](#) and all its static methods.
- [org.forgerock.openig.tools.jwt.validation.Constraints](#) and all its static methods.

Examples

This documentation includes script examples in context, such as the following:

- [Discovery and dynamic registration with PingAM](#)
- [Extend PingGateway](#)
- [HttpBasicAuthenticationClientFilter](#)
- [Scripting required scopes with PingAM](#)

Accessing secrets

The following example shows a script reading a password from a `SecretsProvider` :

```

{
  "name": "SecretsApiExample",
  "condition": "${find(request.uri.path, '/secrets')}",
  "heap": [
    {
      "type": "SecretsProvider",
      "name": "LocalSecretsProvider",
      "config": {
        "stores": [
          {
            "name": "SecretsPasswords",
            "type": "Base64EncodedSecretStore",
            "_comment": "Base64-encoded 'password'",
            "config": {
              "secrets": {
                "secret.password": "cGFzc3dvcmQ="
              }
            }
          }
        ]
      }
    }
  ],
  "handler": {
    "name": "AccessPasswordAsGenericSecret",
    "type": "ScriptableHandler",
    "config": {
      "type": "application/x-groovy",
      "args": {
        "mySecretsProvider": "${heap['LocalSecretsProvider']}"
      },
      "source": [
        "import org.forgerock.secrets.GenericSecret",
        "import org.forgerock.secrets.Purpose",
        "Purpose<GenericSecret> purpose = Purpose.purpose('secret.password', GenericSecret.class)",
        "mySecretsProvider",
        "    .getActiveSecret(purpose)",
        "    .then(password -> password.revealAsUtf8(String::new))",
        "    .then(password -> new Response(Status.OK).setEntity('Secret password: ' + password))"
      ]
    }
  }
}

```

Source: [secrets.json](#)

When you browse to this route, PingGateway displays `Secret password: password`.

Learn more about the secrets API in the [Javadoc](#).

More information

- [ScriptableFilter](#), [org.forgerock.openig.filter.ScriptableFilter](#), and [org.forgerock.http.Filter](#)
- [ScriptableHandler](#), [org.forgerock.openig.handler.ScriptableHandler](#), and [org.forgerock.http.Handler](#)

- `ScriptableThrottlingPolicy`, `org.forgerock.openig.filter.throttling.ScriptableThrottlingPolicy.Heaplet`[↗](#), and `org.forgerock.openig.filter.throttling.ThrottlingPolicy`[↗](#)
- `ScriptableResourceAccess` in `OAuth2ResourceServerFilter`, `org.forgerock.openig.filter.oauth2.ScriptableResourceAccess`[↗](#), and `org.forgerock.http.oauth2.ResourceAccess`[↗](#)
- `ScriptableAccessTokenResolver` in `OAuth2ResourceServerFilter`, `org.forgerock.openig.filter.oauth2.ScriptableAccessTokenResolver`[↗](#), and `org.forgerock.http.oauth2.AccessTokenResolver`[↗](#)
- `ScriptableJwtValidatorCustomizer` in `JwtValidationFilter` and `org.forgerock.openig.filter.jwt.ScriptableJwtValidatorCustomizer`[↗](#)

PingGateway route properties

Configuration parameters, such as host names, port numbers, and directories, can be declared as property variables in the PingGateway configuration or in an external JSON file. The variables can then be used in expressions in routes and in `config.json` to set the value of configuration parameters.

Properties can be inherited across the router, so a property defined in `config.json` can be used in any of the routes in the configuration. Storing the configuration centrally and using variables for parameters that can be different for each installation makes it easier to deploy PingGateway in different environments without changing a single line in your route configuration.

Usage

Simple property configured inline

```
{
  "properties": {
    "<variable name>": "valid JSON value"
  }
}
```

Group property configured inline

```
{
  "properties": {
    "<group name>": {
      "<variable name>": "valid JSON value", ...
    }
  }
}
```

Properties configured in one or more external files

```
{
  "properties": {
    "$location": expression
  }
}
```

In this example, `description1` and `description2` prefix the variable names contained in the external file.

```
{
  "properties": {
    "description1": {
      "$location": expression
    },
    "description2": {
      "$location": expression
    }
  }
}
```

Properties

"<variable name>": *configuration expression*<string>

The name of a variable to use in the PingGateway configuration. The variable can be used in expressions in routes or in `config.json` to assign the value of a configuration parameter.

The value assigned to the variable can be any valid JSON value: string, number, boolean, array, object, or null.

- In the following example from `config.json`, the URL of an application is declared as a property variable named `appLocation`. The variable is then used by the `baseURI` parameter of the handler, and can be used again in other routes in the configuration.

```
{
  "properties": {
    "appLocation": "https://app.example.com:8444"
  },
  "handler": {
    "type": "Router",
    "baseURI": "${appLocation}",
    "capture": "all"
  }
}
```

- In the following example, the property variable `ports` is added to define an array of port numbers used by the configuration. The `ports` variable is referenced in the `appLocation` variable, and is resolved at runtime with the value in the ports array:

```
{
  "properties": {
    "ports": [8444, 8445, 8446],
    "appLocation": "https://app.example.com:${ports[1]}"
  },
  "handler": {
    "type": "Router",
    "baseURI": "${appLocation}",
    "capture": "all"
  }
}
```

- In the following example route, the request path is declared as the property variable `uriPath`, with the value `hello`, and the variable is used by the route condition:

```
{
  "properties": {
    "uriPath": "hello"
  },
  "handler": {
    "type": "StaticResponseHandler",
    "config": {
      "status": 200,
      "headers": {
        "Content-Type": [ "text/plain; charset=UTF-8" ]
      },
      "entity": "Hello world!"
    }
  },
  "condition": "${matchesWithRegex(request.uri.path, '^/welcome') or matchesWithRegex(request.uri.path, '&{uriPath}')}"
}
```

When PingGateway is set up as described in the [Getting started with PingGateway](#), requests to `ig.example.com:8080/hello` or `ig.example.com:8080/welcome` can access the route.

"<group name>": <object>, required

The name of a group of variables to use in the PingGateway configuration. The group name and variable name are combined using dot notation in an expression.

In the following example from `config.json`, the property group `directories` contains two variables that define the location of files:

```
{
  "properties": {
    "directories": {
      "config": "${openig.configDirectory.path}",
      "auditlog": "/tmp/logs"
    }
  }
}
```

The group name and variable name are combined using dot notation in the following example to define the directory where the audit log is stored:

```
{
  "type": "AuditService",
  "config": {
    "eventHandlers": [
      {
        "class": "org.forgerock.audit.handlers.csv.CsvAuditEventHandler",
        "config": {
          "name": "csv",
          "logDirectory": "${directories.auditlog}",
          . . .
        }
      }
    ]
  }
}
```

"\$location": configuration expression<string>, required

The location and name of one or more JSON files where property variables are configured.

Files must be `.json` files, and contain property variables with a key/value format, where the key cannot contain the period (`.`) separator.

For example, this file is correct:

```
{
  "openamLocation": "https://am.example.com:8888/am/",
  "portNumber": 8444
}
```

This file would cause an error:

```
{
  "openam.location": "https://am.example.com:8888/am/",
  "port.number": 8444
}
```

Examples

Property variables configured in one file

In the following example, the location of the file that contains the property variables is defined as an expression:

```
{
  "properties": {
    "$location": "${fileToUrl(openig.configDirectory)}/myProperties.json"
  }
}
```

In the following example, the location of the file that contains the property variables is defined as a string:

```
{
  "properties": {
    "$location": "file:///Users/user-id/.openig/config/myProperties.json"
  }
}
```

The file location can be defined as any real URL.

The file `myProperties.json` contains the base URL of an AM service and the port number of an application.

```
{
  "openamLocation": "https://am.example.com:8888/am/",
  "appPortNumber": 8444
}
```

Property variables configured in multiple files

In the following example, the property variables are contained in two files, defined as a set of strings:

```
{
  "properties": {
    "urls": {
      "$location": "file://path-to-file/myUrlProperties.json"
    },
    "ports": {
      "$location": "file://path-to-file/myPortProperties.json"
    }
  }
}
```

The file `myUrlProperties.json` contains the base URL of the sample application:

```
{
  "appUrl": "https://app.example.com"
}
```

The file `myPortProperties.json` contains the port number of an application:

```
{
  "appPort": 8444
}
```

The base config file, `config.json`, can use the properties as follows:

```
{
  "properties": {
    "urls": {
      "$location": "file:///Users/user-id/.openig/config/myUrlProperties.json"
    },
    "ports": {
      "$location": "file:///Users/user-id/.openig/config/myPortProperties.json"
    }
  },
  "handler": {
    "type": "Router",
    "name": "_router",
    "baseURI": "${urls.appUrl}:${ports.appPort}",
    . . .
  }
}
```

PingGateway context reference

The root object for request context information.

Contexts is a map of available contexts that implement the [Context](#) interface. The `contexts` map is populated dynamically when creating bindings to evaluate expressions and scripts.

If a context type appears multiple times in the chain of contexts, only the last value of the context is exposed in the `contexts` map. For example, if a route contains two `JwtBuilderFilters` each providing data in the `JwtBuilderContext`, only data from the last processed `JwtBuilderFilter` is contained in `${contexts.jwtBuilder}`. Data from the first processed `JwtBuilderFilter` can be accessed by scripts and extensions through the `Context` API. The following example script accesses data from the first processed `JwtBuilderFilter`:

```
Context second = context.get("jwtBuilder")
    .map(Context::getParent)
    .flatMap(ctx -> ctx.get("jwtBuilder"))
    .orElse(null);
```

The map keys are strings and the values are context objects. All context objects use their version of the following properties:

"context-Name": *string*

Context name.

"context-ID": *string*

Read-only string uniquely identifying the context object.

"context-rootContext": *boolean*

True if the context object is a `RootContext` (has no parent).

"context-Parent": *Context object*

Parent of this context object.

Contexts provide contextual information to downstream filters and handlers about a handled request. The context can include information about the client making the request, the session, the authentication or authorization identity of the user, and any other state information associated with the request.

Contexts provide a way to access state information throughout the duration of the HTTP session between the client and protected application. Interaction with additional services can also be captured in the context.

Filters can enrich existing contexts (store objects in sessions or attributes) or provide new contexts tailored for a purpose. The list of available contexts is dynamic and depends on which filters have been executed when a context is queried. For example, a context can be queried by a script, at startup, or at runtime.

Unlike session information, which spans multiple request/response exchanges, contexts last only for the duration of the request/response exchange and are then lost.

Summary of contexts

Type	Accessible at	Populated by	Contains
AttributesContext	<code>contexts.attributes.attributes</code> and <code>attributes</code>	PingGateway core, when a request enters PingGateway	Map of request attributes for use by filters at different positions in the chain
AuthRedirectContext	<code>\$ {contexts.AuthRedirectContext}</code>	FragmentFilter and DataPreservationFilter	Indication to the FragmentFilter and DataPreservationFilter that a login redirect is pending
CapturedUserPasswordContext	<code>\$ {contexts.capturedPassword}</code>	CapturedUserPasswordFilter	Decrypted AM password of the current user
CdSsoContext	<code>\$ {contexts.cdssso}</code>	CrossDomainSingleSignOnFilter	CDSSO token properties, session user ID, full claims set
CdSsoFailureContext	<code>\$ {contexts.cdsssoFailure}</code>	CrossDomainSingleSignOnFilter	Information about errors occurring during CDSSO authentication
ClientContext	<code>\$ {contexts.client}</code>	PingGateway core, when a request enters PingGateway	Information about the client sending the request and the client certificate when using mTLS
FileAttributesContext	<code>\$ {contexts.fileAttributes}</code>	FileAttributesFilter	Map of keys and values extracted with a FileAttributesFilter

Type	Accessible at	Populated by	Contains
IdentityRequestJwtContext	\$ {contexts.IdentityRequestJwtContext}	IdentityAssertionHandler	Information and claims for an identity request JWT issued by PingOne Advanced Identity Cloud to PingGateway
IdpSelectionLoginContext	\$ {contexts.idpSelectionLogin}	AuthorizationCodeOAuth2ClientFilter when <code>loginHandler</code> is specified.	The original target URI for a request received by PingGateway
JwtBuilderContext	\$ {contexts.jwtBuilder}	JwtBuilderFilter	Built JWT as string, <code>JsonValue</code> , or map
JwtValidationContext	\$ {contexts.jwtValidation}	JwtValidationFilter and IdTokenValidationFilter	Properties of a JWT after validation
JwtValidationErrorContext	\$ {contexts.jwtValidationError}	JwtValidationFilter and IdTokenValidationFilter	Properties of a JWT after validation fails
OAuth2Context	\$ {contexts.oauth2}	OAuth2ResourceServerFilter	Properties of an OAuth 2.0 access token after validation
OAuth2FailureContext	\$ {contexts.oauth2Failure}	AuthorizationCodeOAuth2ClientFilter and OAuth2TokenExchangeFilter	OAuth 2.0 authorization operation error and error description
OAuth2TokenExchangeContext	\$ {contexts.oauth2TokenExchange}	OAuth2TokenExchangeFilter	Issued token and its scopes
PingOneProtectDeviceProfileContext	\$ {contexts.pingOneProtectProfile}	PingOneProtectEvaluationFilter	Internal-use-only device profile data to support PingOne Protect risk evaluation
PingOneProtectEvaluationContext	\$ {contexts.pingOneProtect}	PingOneProtectEvaluationFilter	A PingOne Protect risk evaluation result for an incoming request

Type	Accessible at	Populated by	Contains
PolicyDecisionContext	\$ {contexts.policyDecision}	PolicyEnforcementFilter	Attributes and advices returned by AM policy decisions
SessionContext	\$ {contexts.session}	PingGateway core, when a request enters PingGateway	Information about stateful and stateless sessions
SessionInfoContext	\$ {contexts.amSession}	SessionInfoFilter	AM session information and properties
SqlAttributesContext	\$ {contexts.sqlAttributes}	SqlAttributesFilter	Map of keys and values extracted with an SqlAttributesFilter
SsoTokenContext	\$ {contexts.ssoToken}	SingleSignOnFilter and CrossDomainSingleSignOnFilter	SSO tokens and their validation information
StsContext	\$ {contexts.sts}	TokenTransformationFilter	Result of a token transformation
TransactionIdContext	\$ {contexts.transactionId}	PingGateway core, when a request enters PingGateway	ForgeRock transaction ID of a request
UriRouterContext	\$ {contexts.router}	PingGateway core, when a request traverses a route	Routing information associated with a request
UserProfileContext	\$ {contexts.userProfile}	UserProfileFilter	User profile information

PingGateway uses these contexts:

- [AttributesContext](#)
- [AuthRedirectContext](#)
- [CapturedUserPasswordContext](#)
- [CdSsoContext](#)
- [CdSsoFailureContext](#)
- [ClientContext](#)
- [FileAttributesContext](#)

- [IdentityRequestJwtContext](#)
- [IdpSelectionLoginContext](#)
- [JwtBuilderContext](#)
- [JwtValidationContext](#)
- [JwtValidationErrorContext](#)
- [OAuth2Context](#)
- [OAuth2FailureContext](#)
- [OAuth2TokenExchangeContext](#)
- [PingOneProtectEvaluationContext](#)
- [PolicyDecisionContext](#)
- [SessionContext](#)
- [SessionInfoContext](#)
- [SqlAttributesContext](#)
- [SsoTokenContext](#)
- [StsContext](#)
- [TransactionIdContext](#)
- [UriRouterContext](#)
- [UserProfileContext](#)

AttributesContext

Provides a map for request attributes. When PingGateway processes a single request, it injects transient state information about the request into this context. Attributes stored when processing one request aren't accessible when processing a subsequent request.

PingGateway automatically provides access to the `attributes` field through the `attributes` bindings in expressions. For example, to access a username with an expression, use `${attributes.credentials.username}` instead of `${contexts.attributes.attributes.credentials.username}`

Use [SessionContext](#) to maintain state between successive requests from the same logical client.

Properties

The context is named `attributes`, and is accessible at `${attributes}`. The context has the following property:

"attributes": *map*

Map with the format `Map<String, Object>`, where:

- Key: Attribute name
- Value: Attribute value

Cannot be null.

More information

[org.forgerock.services.context.AttributesContext](#)

AuthRedirectContext

Used by the following filters to indicate that a login redirect is pending:

- [FragmentFilter](#)
- [DataPreservationFilter](#)

This context isn't intended for use in scripts or extensions.

For a single request there must be at most one instance of `AuthRedirectContext` in the context hierarchy. Confirm for the presence of an `AuthRedirectContext` before adding a new instance or adding query parameters to an existing instance.

The context is named `AuthRedirectAwareContext`, and is accessible at `${contexts.AuthRedirectContext}`.

Properties**"impendingIgRedirectNotified": *boolean***

Returns `true` if a PingGateway redirect attempt is pending. Otherwise, returns `false`.

"notifyImpendingIgRedirectAndUpdateUri": *URI*

Notifies that a PingGateway redirection has been attempted, and returns an updated URI as follows:

- If no query parameters are added to the context, return the original URI.
- If query parameters are added to the context, apply them to the URI and return an updated URI.
- If the added query parameters have the same name as existing query parameters, replace the existing parameters and return an updated URI.

For example, a request to `example.com/profile` triggers a login redirect to `example.com/login`. After authentication, the request is expected to be redirected to the original URI, `example.com/profile`.

"addQueryParameter": *java.lang.String*

Adds a query parameter to the context, for use by `notifyImpendingIgRedirectAndUpdateUri`.

More information

[org.forgerock.openig.filter.AuthRedirectContext](#)

CapturedUserPasswordContext

Provides the decrypted AM password of the current user. When the [CapturedUserPasswordFilter](#) processes a request, it injects the decrypted password from AM into this context.

Properties

The context is named `capturedPassword`, and is accessible at `${contexts.capturedPassword}`. The context has the following properties:

"raw": *byte*

The decrypted password as bytes.

"value": *java.lang.String*

The decrypted password as a UTF-8 string.

More information

[org.forgerock.openig.openam.CapturedUserPasswordContext](#)

CdSsoContext

Provides the cross-domain SSO properties for the CDSSO token, the user ID of the session, and the full claims set. When the [CrossDomainSingleSignOnFilter](#) processes a request, it injects the information in this context.

Properties

The context is named `cdsso`, and is accessible at `${contexts.cdsso}`. The context has the following properties:

"claimsSet": *org.forgerock.json.jose.jwt.JwtClaimsSet*

Full `JwtClaimsSet` for the identity of the authenticated user. Cannot be null.

Access claims as follows:

- Claims with a getter by using the property name. For example, access `getSubject` with `contexts.cdsso.claimsSet.subject`.
- All other claims by using the `getClaim` method. For example, access `subname` with `contexts.cdsso.claimsSet.getClaim('subname')`.

"cookieInfo": *org.forgerock.openig.http.protocol.CookieBuilder*

Configuration data for the CDSSO authentication cookie, with the following attributes:

- `name`: Cookie name (string)

- **domain** : (Optional) Cookie domain (string)
- **path** : Cookie path (string)

No attribute can be null.

"redirectEndpoint": [java.lang.String](#)

Redirect endpoint URI configured for communication with AM. Cannot be null.

"sessionId": [java.lang.String](#)

Universal session ID. Cannot be null.

"token": [java.lang.String](#)

Value of the CDSSO token. Cannot be null.

More information

[org.forgerock.openig.openam.CdSsoContext](#)

CdSsoFailureContext

Contains the error details for any error that occurred during cross-domain SSO authentication. When the [CrossDomainSingleSignOnFilter](#) processes a request, should an error occur that prevents authentication, the error details are captured in this context.

Properties

The context is named `cdssoFailure`, and is accessible at `${contexts.cdssoFailure}`. The context has the following properties:

"error": [java.lang.String](#)

The error that occurred during authentication. Cannot be null.

"description": [java.lang.String](#)

A description of the error that occurred during authentication. Cannot be null.

"throwable": [java.lang.Throwable](#)

Any `Throwable` associated with the error that occurred during authentication. Can be null.

More information

[org.forgerock.openig.openam.CdSsoFailureContext](#)

ClientContext

Information about the client sending a request. When PingGateway receives a request, it injects information about the client sending the request into this context.

Properties

The context is named `client`, and is accessible at `${contexts.client}`. The context has the following properties:

"certificates": [java.util.List](#) <[java.security.cert.Certificate](#)>

List of X.509 certificates presented by the client. If the client doesn't present any certificates, PingGateway returns an empty list. Never `null`.

The following example uses the certificate associated with the incoming HTTP connection:

```
{
  "name": "CertificateThumbprintFilter-1",
  "type": "CertificateThumbprintFilter",
  "config": {
    "certificate": "${contexts.client.certificates[0]}"
  }
}
```

"isExternal": *boolean*

True if the client connection is external.

"isSecure": *boolean*

True if the client connection is secure.

"localAddress": [java.lang.String](#)

The IP address of the interface that received the request.

"localPort": *integer*

The port of the interface that received the request.

"remoteAddress": [java.lang.String](#)

The IP address of the client (or the last proxy) that sent the request.

"remotePort": *integer*

The source port of the client (or the last proxy) that sent the request.

"remoteUser": [java.lang.String](#)

The login of the user making the request, or `null` if unknown. This is likely to be `null` unless you have deployed PingGateway with a non-default deployment descriptor that secures the PingGateway web application.

"userAgent": [java.lang.String](#)

The value of the User-Agent HTTP header in the request if any, otherwise `null`.

More information

[org.forgerock.services.context.ClientContext](#)

FileAttributesContext

Map of keys and value strings extracted with a [FileAttributesFilter](#).

The content corresponds to the key-value pairs for a single record.

Properties

The context is named `fileAttributes` and is accessible at `${contexts.fileAttributes}`.

The property keys are the `fields` of the `FileAttributesFilter`. For example, if the fields are `username` and `password`, access the username as `${contexts.fileAttributes.record.username}` and the password as `${contexts.fileAttributes.record.password}`.

More information

org.forgerock.openig.filter.FileAttributesContext

IdentityRequestJwtContext

Provides the properties of an identity request JWT issued by PingOne Advanced Identity Cloud to PingGateway as part of a PingOne Advanced Identity Cloud authentication journey with an `IdentityGatewayAssertionNode` node.

The context is created by the [IdentityAssertionHandler](#).

Properties

The context is named `identityRequestJwt`, and is accessible at `${contexts.identityRequestJwt}`. The context has the following properties:

"dataClaims": [java.util.Map](#)

Map of claims that can be required by a plugin, in the format `Map<String, Object>`, where:

- Key: Claim name
- Value: Claim value

Claims are documented on a per-plugin basis.

If no claim is provided, this is an empty map.

"nonce": [java.lang.String](#)

Unique ID generated by the `IdentityGatewayAssertionNode` and returned in the identity assertion JWT.

Can't be null

"redirect": [java.net.URI](#)

The URL on which to send the identity assertion JWT.

Can't be null

"version": [java.lang.String](#)

The JWT version; only the value `v1` is supported.

Can't be null

IdpSelectionLoginContext

Provides the original target URI for the request received by PingGateway. Use this context with `loginHandler` in [AuthorizationCodeOAuth2ClientFilter](#).

Properties

The context is named `idpSelectionLogin` and is accessible at `${contexts.idpSelectionLogin}`. The context has the following property:

"originalUri": [URI](#)

The original target URI for the request received by PingGateway. The value of this field is read-only.

JwtBuilderContext

When the [JwtBuilderFilter](#) processes a request, it stores provided data in this context. This context returns the JWT as string, `JsonValue`, or map for downstream use.

Properties

The context is named `jwtBuilder`, and is accessible at `${contexts.jwtBuilder}`, with the following properties:

"value": [java.lang.String](#)

The base64url encoded UTF-8 parts of the JWT, containing name-value pairs of data. Cannot be null.

"claims": [java.util.Map](#)

Map with the format `Map<String, Object>`, where:

- Key: Claim name
- Value: Claim value

"claimsAsJsonValue": [org.forgerock.json.JsonValue](#)

Claims as a JSon value.

More information

[org.forgerock.openig.filter.JwtBuilderFilter](#)

[org.forgerock.openig.filter.JwtBuilderContext](#)

JwtValidationContext

Provides the properties of a JWT after validation. When the [JwtValidationFilter](#) validates a JWT, or the [IdTokenValidationFilter](#) validates an id_token, it injects a copy of the JWT and its claims into this context.

Properties

The context is named `jwtValidation`, and is accessible at `${contexts.jwtValidation}`. The context has the following properties:

"value": [java.lang.String](#)

The value of the JWT. Cannot be null.

"claims": [org.forgerock.json.jose.jwt.JwtClaimsSet](#)

A copy of the claims as a `JwtClaimsSet`.

"info": [java.util.Map](#)

A map in the format `Map<String, Object>`, where:

- Key: Claim name
- Value: Claim value

"jwt": [org.forgerock.json.jose.jwt.Jwt](#)

A copy of the JWT.

More information

[org.forgerock.openig.filter.jwt.JwtValidationFilter](#)

[org.forgerock.openig.filter.oauth2.client.IdTokenValidationFilterHeaplet](#)

[org.forgerock.openig.filter.jwt.JwtValidationContext](#)

[org.forgerock.openig.filter.jwt.JwtValidationErrorContext](#)

JwtValidationErrorContext

Provides the properties of a JWT after validation fails. When the [JwtValidationFilter](#) fails to validate a JWT, or the [IdTokenValidationFilter](#) fails to validate an id_token, it injects the JWT and a list of violations into this context.

Properties

The context is named `jwtValidationError`, and is accessible at `${contexts.jwtValidationError}`. The context has the following properties:

"jwt": [java.lang.String](#)

The value of the JWT. Cannot be null.

"violations": [java.util.List](#)<[Violation](#)>

A list of violations.

More information

[org.forgerock.openig.filter.jwt.JwtValidationFilter](#)

[org.forgerock.openig.filter.oauth2.client.IdTokenValidationFilterHeaplet](#)

[org.forgerock.openig.filter.jwt.JwtValidationContext](#)

[org.forgerock.openig.filter.jwt.JwtValidationErrorContext](#)

OAuth2Context

Provides OAuth 2.0 access tokens. When the [OAuth2ResourceServerFilter](#) processes a request, it injects the access token into this context.

Properties

The context name is `oauth2`, and is accessible at `${contexts.oauth2}`. The context has the following properties:

"accessToken": [org.forgerock.http.oauth2.AccessTokenInfo](#)

The AccessTokenInfo is built from the following properties:

"info": [java.util.Map](#)

A map with the format [Map](#)<[String](#), [Object](#)>, where

- Key: Claim name
- Value: Claim value in raw JSON

"token": [java.lang.String](#)

Access token identifier issued from the Authorization Server.

"scopes": [java.util.Set](#)

A set scopes associated to this token, with the format [Set](#)<[String](#)>.

"expiresAt": [java.lang.Long](#)

Timestamp of when the token expires, in milliseconds since epoch.

More information

[org.forgerock.http.oauth2.OAuth2Context](#)

[org.forgerock.http.oauth2.AccessTokenInfo](#)

OAuth2FailureContext

When an OAuth 2.0 authorization operation fails, the error and error description provided by the authorization service are injected into this context for use downstream.

The amount and type of information in the context depends on when a failure occurs.

This context is created by [AuthorizationCodeOAuth2ClientFilter](#) and [OAuth2TokenExchangeFilter](#).

This context supports OAuth 2.0 error messages in the format given by [RFC 6749](#).

Properties

The context is named `OAuth2Failure`, and is accessible at `${contexts.oauth2Failure}`. The context has the following properties:

"error": [java.lang.String](#)

The error field name.

"description": [java.lang.String](#)

Error description field name.

"exception": [org.forgerock.openig.filter.oauth2.client.OAuth2ErrorException](#)

The OAuth 2.0 exception associated with the token exchange error.

Examples

For examples that use `${contexts.oauth2Failure.error}` and `${contexts.oauth2Failure.description}`, refer to the routes in [OAuth 2.0 token exchange with PingAM](#) and [Discovery and dynamic registration with PingAM](#).

More information

[org.forgerock.openig.filter.oauth2.OAuth2FailureContext](#)

[OAuth2TokenExchangeContext](#)

[OAuth2TokenExchangeFilter](#)

[RFC 6749: Error Response](#)

OAuth2TokenExchangeContext

When the [OAuth2TokenExchangeFilter](#) successfully issues a token, it injects the issued token and its scopes into this context.

Properties

The context name is `OAuth2TokenExchangeContext`, and is accessible at `${contexts.oauth2TokenExchange}`.

The context has the following properties:

"issuedToken": [java.lang.String](#)

The token issued by the Authorization Server.

"issuedTokenType": [java.lang.String](#)

The token type URN.

"scopes": [java.util.Set](#)<[java.lang.String](#)>

One or more scopes associated with the issued token, for example, "scope1", "scope2", "scope3".

"rawInfo": [org.forgerock.json.JsonValue](#)

The raw token info as issued by the Authorization Server.

More information

[org.forgerock.openig.filter.oauth2.OAuth2TokenExchangeContext](#)

[OAuth2FailureContext](#)

[OAuth2TokenExchangeFilter](#)

[RFC 6749: Error Response](#)

PingOneProtectDeviceProfileContext

Internal-use only context that holds device profile data obtained from the user-agent to support PingOne Protect risk evaluation.

A [PingOneProtectEvaluationFilter](#) gathers the device profile data and records it in this context.

Properties

This internal-use-only context is named `pingOneProtectProfile`. PingGateway stores it at `$ {contexts.pingOneProtectProfile}`. It has the following properties:

"deviceProfile": [java.lang.String](#)

The encoded device profile data. This is empty when no device profile data has been collected.

"requestEvaluationState": [java.lang.Object](#)

Metadata about the request to prepare for risk evaluation.

"state": [java.util Enumeration](#)

The state of the profile data in this context; one or more of:

- `PROFILE_ABSENT` : no profile data, needs to be collected
- `PROFILE_ABSENT_MAY_PROCEED` : no profile data, but the filter configuration allows risk evaluation without it
- `PROFILE_PRESENT` : found profile data in the context

- `PROFILE_REQUESTED` : ready to collect profile data from the user-agent

PingOneProtectEvaluationContext

Holds a PingOne Protect risk evaluation result for the incoming request.

You use a [PingOneProtectEvaluationFilter](#) to make a risk evaluation request to PingOne Protect. The filter records the evaluation result in the PingOneProtectEvaluationContext object.

Configure a [PingOneProtectThreatLevelRoutingHandler](#) to act on the risk level set in the context. As an alternative, use a [DispatchHandler](#) to act on the risk score.

Properties

The context is named `pingOneProtect`. It is accessible at `${contexts.pingOneProtect}` and has the following properties:

"clientIdAddress": [java.lang.String](#) 

The client IP address for the PingOne Protect evaluation result.

"clientUserAgent": [java.lang.String](#) 

The string user-agent identifier for the PingOne Protect evaluation result.

"evaluationId": [java.lang.String](#) 

The string identifier for the PingOne Protect evaluation result.

"isReadyToComplete": *boolean*

Whether PingGateway is ready to report the status to PingOne Protect following post-evaluation actions.

"level": [java.lang.String](#) 

The level from the PingOne Protect evaluation result; one of:

- `LOW`
- `MEDIUM`
- `HIGH`

"score": *integer*

The score from the PingOne Protect evaluation result.

"status": [java.lang.String](#) 

The completion status following post-evaluation actions, if complete; one of:

- `FAILED`
- `SUCCESS`

PolicyDecisionContext

Provides attributes and advices returned by AM policy decisions. When the [PolicyEnforcementFilter](#) processes a request, it injects the attributes and advices into this context.

Properties

The context is named `policyDecision`, and is accessible at `${contexts.policyDecision}`. The context has the following properties:

"attributes": [java.util.Map](#)

A map with the format `Map<String, List<String>>`, where:

- Key: Attribute name.
- Value: A One or more attribute values provided in the policy decision. Can be empty, but not null.

"jsonAttributes": [java.util.Map](#)

A map with the format `Map<String, List<String>>`, where:

- Key: Attribute name.
- Value: One or more attribute values provided in the policy decision. Can be empty, but not null.

"advices": [java.util.Map](#)

A map with the format `Map<String, List<String>>`, where:

- Key: Advice name.
- Value: One or more advice values provided in the policy decision. Can be empty, but not null.

"jsonAdvices": [java.util.Map](#)

A map with the format `Map<String, List<String>>`, where:

- Key: Advice name
- Value: One or more advice values provided in the policy decision. Can be empty, but not null.

"actions": [java.util.Map](#)

A map with the format `Map<String, Boolean>` where:

- Key: Action name.
- Value: `true` when an action is allowed for the specified resource, `false` otherwise. Cannot be null.

"jsonActions": [json.JsonValue](#)

A map with the format `Map<String, Boolean>`, where:

- Key: Action name.

- Value: `true` when an action is allowed for the specified resource, `false` otherwise. Cannot be null.

"resource": [java.lang.String](#)

The resource value used in the policy request. Can be empty, but not null.

More information

[org.forgerock.openig.openam.PolicyDecisionContext.html](#)

SessionContext

Provides access to information about stateful and stateless sessions.

To process a single request, consider using [AttributesContext](#) to transfer transient state between components and prevent PingGateway from creating additional sessions.

PingGateway automatically provides access to the `session` field through the `session` bindings in expressions. For example, to access a username with an expression, use `${session.username}` instead of `${contexts.session.session.username}`

Properties

The context is named `session`, and is accessible at `${contexts.session}`. The context has the following properties:

"session": [java.util.Map](#)

A map with the format [Map](#)[<String](#), [Object](#)[>](#), where:

- Key: Session property name
- Value: Session property value

Any object type can be stored in the session.

More information

[org.forgerock.http.session.SessionContext](#)

SessionInfoContext

Provides AM session information and properties. When the [SessionInfoFilter](#) processes a request, it injects info and properties from the AM session into this context.

Properties

The context is named `amSession`, and is accessible at `${contexts.amSession}`. The context has the following properties:

"asJsonValue()": [json.JsonValue](#)

Raw JSON.

"latestAccessTime": [java.time.Instant](#)

The timestamp of when the session was last used. Can be null if the DN isn't resident on the SSO token, or if the time cannot be obtained from the session.

"maxIdleExpirationTime": [java.time.Instant](#)

The timestamp of when the session would time out for inactivity. Can be null if the DN isn't resident on the SSO token, or if the time cannot be obtained from the session.

"maxSessionExpirationTime": [java.time.Instant](#)

The timestamp of when the session would time out regardless of activity. Can be null if the DN isn't resident on the SSO token, or if the time cannot be obtained from the session.

"properties": [java.util.Map](#)

A read-only map with the format [Map](#)<[String](#), [String](#)>, where

- Key: Name of a property bound to the session
- Value: Value of the property

The following properties are retrieved:

- When `sessionProperties` in AmService is configured, listed session properties with a value.
- When `sessionProperties` in AmService isn't configured, all session properties with a value.
- Properties with a value that are required by PingGateway but not specified by `sessionProperties` in AmService. For example, when the session cache is enabled, session properties related to the cache are automatically retrieved.

Properties with a value are returned, properties with a null value aren't returned

Can be empty, but not null.

"realm": [java.lang.String](#)

The realm as specified by AM, in a user-friendly slash (/) separated format. Can be null if the DN isn't resident on the SSO token.

"sessionHandle": [java.lang.String](#)

The handle to use for logging out of the session. Can be null if the handle is not available for the session.

"universalId": [java.lang.String](#)

The DN that AM uses to uniquely identify the user. Can be null if it cannot be obtained from the SSO token.

"username": [java.lang.String](#)

A user-friendly version of the username. Can be null if the DN isn't resident on the SSO token, or empty if it cannot be obtained from the DN.

More information

[org.forgerock.openig.openam.SessionInfoContext](#)

SqlAttributesContext

Map of keys and value strings extracted with a [SqlAttributesFilter](#).

The content corresponds to the key-value pairs for a single row.

Properties

The context is named `sqlAttributes` and is accessible at `${contexts.sqlAttributes}`.

The property keys are the names of the columns in the row. For example, if the columns are `username` and `password`, access the username as `${contexts.sqlAttributes.row.username}` and the password as `${contexts.sqlAttributes.row.password}`.

More information

[org.forgerock.openig.sql.SqlAttributesContext](#)

SsoTokenContext

Provides SSO tokens and their validation information. When the [SingleSignOnFilter](#) or [CrossDomainSingleSignOnFilter](#) processes a request, it injects the value of the SSO token and additional information in this context.

Properties

The context is named `ssoToken`, and is accessible at `${contexts.ssoToken}`. The context has the following properties:

"info": [java.util.Map](#)

A map with the format `Map<String, Object>`, where

- Key: Property bound to the SSO token, such as `realm` or `uid`
- Value: Value of the property

Information associated with the SSO token, such as `realm` or `uid`. Cannot be null.

"loginEndpoint": [java.lang.String](#)

A string representing the URL of the login endpoint, evaluated from the configuration of `SingleSignOnFilter`.

"value": [java.lang.String](#)

The value of the SSO token. Cannot be null.

More information

[org.forgerock.openig.openam.SsoTokenContext](#)

StsContext

Provides the result of a token transformation. When the [TokenTransformationFilter](#) processes a request, it injects the result into this context.

Properties

The context is named `sts`, and is accessible at `${contexts.sts}`. The context has the following properties:

"issuedToken": [java.lang.String](#)

The result of the token transformation.

More information

[org.forgerock.openig.openam.StsContext](#)

TransactionIdContext

The transaction ID of a request. When PingGateway receives a request, it injects the transaction ID into this context.

Properties

The context is named `transactionId`, and is accessible at `${contexts.transactionId}`. The context has the following properties:

"transactionId": [org.forgerock.services.TransactionId](#)

The ID of the transaction.

More information

[org.forgerock.services.TransactionIdContext](#)

[org.forgerock.services.context.TransactionIdContext](#)

UriRouterContext

Provides routing information associated with a request. When PingGateway routes a request, it injects information about the routing into this context.

Properties

The context is named `router`, and is accessible at `${contexts.router}`. The context has the following properties:

"baseUri": [java.lang.String](#)

The portion of the request URI which has been routed so far.

"matchedUri": [java.lang.String](#)

The portion of the request URI that matched the URI template.

"originalUri": [URI](#)

The original target URI for the request, as received by PingGateway. The value of this field is read-only.

"remainingUri": [java.lang.String](#)

The portion of the request URI that is remaining to be matched.

"uriTemplateVariables": [java.util.Map](#)

A map with the format `Map<String, String>`, where:

- Key: Name of a URI template variable
- Value: Value of a URI template variable

More information

[org.forgerock.http.routing.UriRouterContext](#)

UserProfileContext

When the [UserProfileFilter](#) processes a request, it injects the user profile information into this context. This context provides raw JSON representation, and convenience accessors that map commonly used LDAP field names to a context names.

Properties

The context is named `userProfile`, and is accessible at `${contexts.userProfile}`. The context has the following properties:

"username": [java.lang.String](#)

User-friendly version of the username. This field is always fetched. If the underlying data store doesn't include `username`, this field is null.

Example of use: `${contexts.userProfile.username}`

"realm": [java.lang.String](#)

Realm as specified by AM, in a user-friendly slash (/) separated format. Can be null.

Example of use: `${contexts.userProfile.realm}`

"distinguishedName": [java.lang.String](#)

Distinguished name of the user. Can be null.

Example of use: `${contexts.userProfile.distinguishedName}`

"commonName": [java.lang.String](#)

Common name of the user. Can be null.

Example of use: `${contexts.userProfile.commonName}`

"rawInfo": [java.util.Map](#)

An unmodifiable map in the format `Map<String, Object>`, where:

- Key: Name of a field in an AM user profile
- Value: Value of a field in an AM user profile

This context contains the object structure of the AM user profile. Any individual field can be retrieved from the map. Depending on the requested fields, the context can be empty or values can be null.

Examples of use: `${contexts.userProfile.rawInfo}`, `${contexts.userProfile.rawInfo.username}`, `${contexts.userProfile.rawInfo.employeeNumber[0]}`.

"asJsonValue()": [json.JsonValue](#)

User profile information structured as JSON.

Example of use: `${contexts.userProfile.asJsonValue()}`

More information

[org.forgerock.openig.openam.UserProfileContext](#)

[UserProfileFilter](#)

PingGateway requests and responses

PingGateway provides the following objects for working with HTTP:

- [Request](#)
- [Response](#)
- [Status](#)
- [URI](#)

Request

An HTTP request message. Access the content of the request by using [expressions](#).

Properties

"method": [java.lang.String](#)

The HTTP method; for example, `GET`.

"uri": [java.net.URI](#)

The fully-qualified URI of the resource being accessed; for example, `https://www.example.com/resource.txt`.

"version": [java.lang.String](#)

The protocol version used for the request; for example, `HTTP/2`.

"headers": [org.forgerock.http.protocol.Headers](#)

One or more headers in the request, with the format `header_name: [ header_value, ... ]`. The following example accesses the first value of the request header `UserId`:

```
${request.headers['UserId'][0]}
```

"cookies": [org.forgerock.http.protocol.RequestCookies](#)

Incoming request cookies, with the format `cookie_name: [ cookie_value, ... ]`. The following example accesses the first value of the request cookie `my-jwt`:

```
${request.cookies['my-jwt'][0].value}
```

"entity": [Entity](#)

The message body. The following example accesses the subject token from the request entity:

```
#{request.entity.form['subject_token'][0]}
```

"queryParams": [Form](#)

Returns a copy of the query parameters decoded as a form. Modifications to the returned form aren't reflected in the request.

More information

[org.forgerock.http.protocol.Request](#)

Response

An HTTP response message. Access the content of the response by using [expressions](#).

Properties

"cause": [java.lang.Exception](#)

The cause of an error if the status code is in the range 4xx-5xx. Possibly null.

"status": [Status](#)

The response status.

"version": [java.lang.String](#)

The protocol version used the response; for example, HTTP/2 .

"headers": [org.forgerock.http.protocol.Headers](#)

One or more headers in the response. The following example accesses the first value of the response header `Content-Type` :

```
${response.headers['Content-Type'] [0]}
```

"trailers": [org.forgerock.http.protocol.Headers](#)

One or more trailers in the response. The following example accesses the first value of the response trailer `Content-Length` :

```
${response.trailers['Content-Length'] [0]}
```

"entity": [Entity](#)

The message entity body. The following example accesses the user ID from the response:

```
#{toString(response.entity.json['userId'])}
```

More information

[org.forgerock.http.protocol.Response](#)

Status

An HTTP response status.

Properties

"code": *integer*

Three-digit integer reflecting the HTTP status code.

"family": *enumeration*

Family Enum value representing the class of response that corresponds to the code:

Family.INFORMATIONAL

Status code reflects a provisional, informational response: 1xx.

Family.SUCCESSFUL

The server received, understood, accepted and processed the request successfully. Status code: 2xx.

Family.REDIRECTION

Status code indicates that the client must take additional action to complete the request: 3xx.

Family.CLIENT_ERROR

Status code reflects a client error: 4xx.

Family.SERVER_ERROR

Status code indicates a server-side error: 5xx.

Family.UNKNOWN

Status code doesn't belong to one of the known families: 600+.

"reasonPhrase": *string*

The human-readable reason-phrase corresponding to the status code.

"isClientError": *boolean*

True if Family.CLIENT_ERROR.

"isInformational": *boolean*

True if Family.INFORMATIONAL.

"isRedirection": *boolean*

True if Family.REDIRECTION.

"isServerError": *boolean*

True if Family.SERVER_ERROR.

"isSuccessful": *boolean*

True if Family.SUCCESSFUL.

More information

[Response Status Codes](#).

org.forgerock.http.protocol.Status

URI

Represents a Uniform Resource Identifier (URI) reference.

Properties

"scheme": *string*

The scheme component of the URI, or `null` if the scheme is undefined.

"authority": *string*

The decoded authority component of the URI, or `null` if the authority is undefined.

Use "rawAuthority" to access the raw (encoded) component.

"userInfo": *string*

The decoded user-information component of the URI, or `null` if the user information is undefined.

Use "rawUserInfo" to access the raw (encoded) component.

"host": *string*

The host component of the URI, or `null` if the host is undefined.

"port": *number*

The port component of the URI, or `null` if the port is undefined.

"path": *string*

The decoded path component of the URI, or `null` if the path is undefined.

Use "rawPath" to access the raw (encoded) component.

"query": *string*

The decoded query component of the URI, or `null` if the query is undefined.

Note

The query key and value is decoded. However, because a query value can be encoded more than once in a redirect chain, even though it is decoded it can contain unsafe ASCII characters.

Use "rawQuery" to access the raw (encoded) component.

"fragment": *string*

The decoded fragment component of the URI, or `null` if the fragment is undefined.

Use "rawFragment" to access the raw (encoded) component.

More information

[org.forgerock.http.MutableUri](#)

PingGateway access token resolvers

The following objects are available to resolve OAuth 2.0 access tokens:

- [CacheAccessTokenResolver](#)
- [ConfirmationKeyVerifierAccessTokenResolver](#)
- [ScriptableAccessTokenResolver](#)
- [StatelessAccessTokenResolver](#)
- [TokenIntrospectionAccessTokenResolver](#)

CacheAccessTokenResolver

Enable and configure caching of OAuth 2.0 access tokens, based on *Caffeine*. For more information, refer to the GitHub entry, [Caffeine](#).

This resolver configures caching of OAuth 2.0 access tokens, and delegates their resolution to another `AccessTokenResolver`. Use this resolver with AM or any OAuth 2.0 access token provider.

For an alternative way to cache OAuth 2.0 access tokens, configure the `cache` property of `OAuth2ResourceServerFilter`.

Usage

```
{
  "name": string,
  "type": "CacheAccessTokenResolver",
  "config": {
    "delegate": AccessTokenResolver reference,
    "enabled": configuration expression<boolean>,
    "defaultTimeout": configuration expression<duration>,
    "executor": Executor reference,
    "maximumSize": configuration expression<number>,
    "maximumTimeToCache": configuration expression<duration>,
    "amService": AmService reference,
    "onNotificationDisconnection": configuration expression<enumeration>
  }
}
```

Properties

"delegate": *AccessTokenResolver* [reference](#), *required*

Delegate access token resolution to one of the access token resolvers in [PingGateway access token resolvers](#).

To use AM WebSocket notification to evict revoked access tokens from the cache, the delegate must be able to provide the token metadata required to update the cache.

- The `notification` property of `AmService` is enabled.
- The delegate `AccessTokenResolver` provides the token metadata required to update the cache.

enabled: configuration expression<[boolean](#)>, optional

Enable caching.

When an access token is cached, PingGateway can reuse the token information without repeatedly asking the Authorization Server to verify the access token. When caching is disabled, PingGateway must ask the Authorization Server to validate the access token for each request.

Default: `true`

defaultTimeout: configuration expression<[duration](#)>, optional

The duration for which to cache an OAuth 2.0 access token when it doesn't provide a valid expiry value or `maximumTimeToCache`.

If the `defaultTimeout` is longer than the `maximumTimeToCache`, then the `maximumTimeToCache` takes precedence.

Default: `1 minute`

"executor": Executor [reference](#), optional

An executor service to schedule the execution of tasks, such as the eviction of entries from the cache.

Default: `ForkJoinPool.commonPool()`

"maximumSize": configuration expression<[number](#)>, optional

The maximum number of entries the cache can contain.

Default: Unlimited/unbound

"maximumTimeToCache": configuration expression<[duration](#)>, optional

The maximum duration for which to cache access tokens.

Cached access tokens are expired according to their expiry time and `maximumTimeToCache`, as follows:

- If the expiry time is *before* the current time plus the `maximumTimeToCache`, the cached token is expired when the expiry time is reached.
- If the expiry time is *after* the current time plus the `maximumTimeToCache`, the cached token is expired when the `maximumTimeToCache` is reached

The duration cannot be `zero` or `unlimited`.

Default: The token expiry time or `defaultTimeout`

"amService": AmService [reference](#), optional

An AmService to use for the WebSocket notification service.

When an access token is revoked on AM, the CacheAccessTokenResolver can delete the token from the cache when both of the following conditions are true:

- The `notification` property of AmService is enabled.
- The delegate AccessTokenResolver provides the token metadata required to update the cache.

When a `refresh_token` is revoked on AM, all associated access tokens are automatically and immediately revoked.

See also [AmService](#).

onNotificationDisconnection: *configuration expression*<enumeration>, optional

An `amService` must be configured for this property to have effect.

The strategy to manage the cache when the WebSocket notification service is disconnected, and PingGateway receives no notifications for AM events. If the cache is not cleared it can become outdated, and PingGateway can allow requests on revoked sessions or tokens.

Cached entries that expire naturally while the notification service is disconnected are removed from the cache.

Use one of the following values:

- `NEVER_CLEAR`
 - When the notification service is disconnected:
 - Continue to use the existing cache.
 - Deny access for requests that aren't cached, but don't update the cache with these requests.
 - When the notification service is reconnected:
 - Continue to use the existing cache.
 - Query AM for incoming requests that aren't found in the cache, and update the cache with these requests.
- `CLEAR_ON_DISCONNECT`
 - When the notification service is disconnected:
 - Clear the cache.
 - Deny access to all requests, but don't update the cache with these requests.
 - When the notification service is reconnected:
 - Query AM for all requests that aren't found in the cache. (Because the cache was cleared, the cache is empty after reconnection.)
 - Update the cache with these requests.
- `CLEAR_ON_RECONNECT`
 - When the notification service is disconnected:
 - Continue to use the existing cache.
 - Deny access for requests that aren't cached, but don't update the cache with these requests.
 - When the notification service is reconnected:
 - Query AM for all requests that aren't found in the cache. (Because the cache was cleared, the cache is empty after reconnection.)

- Update the cache with these requests.

Default: `CLEAR_ON_DISCONNECT`

Example

For an example that uses the `CacheAccessTokenResolver`, refer to [Caching PingAM access tokens](#).

ConfirmationKeyVerifierAccessTokenResolver

In `OAuth2ResourceServerFilter`, use the `ConfirmationKeyVerifierAccessTokenResolver` to verify that certificate-bound OAuth 2.0 bearer tokens presented by clients use the same mTLS-authenticated HTTP connection.

When a client obtains an access token from AM by using mTLS, AM can optionally use a confirmation key to bind the access token to a certificate. When the client connects to PingGateway using that certificate, the `ConfirmationKeyVerifierAccessTokenResolver` verifies that the confirmation key corresponds to the certificate.

This proof-of-possession interaction ensures that only the client in possession of the key corresponding to the certificate can use the access token to access protected resources.

To use the `ConfirmationKeyVerifierAccessTokenResolver`, the following configuration is required in AM:

- OAuth 2.0 clients must be registered using an X.509 certificate, that is self-signed or signed in public key infrastructure (PKI)
- The AM client authentication method must be `self_signed_client_auth` or `tls_client_auth`.
- AM must be configured to bind a confirmation key to each client certificate.

The `ConfirmationKeyVerifierAccessTokenResolver` delegates the token resolution to a specified `AccessTokenResolver`, which retrieves the token information. The `ConfirmationKeyVerifierAccessTokenResolver` verifies the confirmation keys bound to the access token, and then acts as follows:

- If there is no confirmation key, pass the request down the chain.
- If the confirmation key matches the client certificate, pass the request down the chain.
- If the confirmation key doesn't match the client certificate, throw an error.
- If the confirmation key method is not supported by PingGateway, throw an error.

For an example that uses the `ConfirmationKeyVerifierAccessTokenResolver`, refer to [Mutual TLS with PingAM](#).

For information about issuing certificate-bound OAuth 2.0 access tokens, refer to [Certificate-bound proof-of-possession](#) in AM's *OAuth 2.0 guide*. For information about authenticating an OAuth 2.0 client using mTLS certificates, refer to [Mutual TLS](#) in AM's *OAuth 2.0 guide*.

Usage

Use this resolver with the `accessTokenResolver` property of `OAuth2ResourceServerFilter`.

```
"accessTokenResolver": {
  "type": "ConfirmationKeyVerifierAccessTokenResolver",
  "config": {
    "delegate": AccessTokenResolver reference
  }
}
```

Properties

"delegate": *AccessTokenResolver* [reference](#), required

The access token resolver to use for resolving access tokens. Use any access token resolver described in [PingGateway access token resolvers](#).

Examples

For an example that uses the ConfirmationKeyVerifierAccessTokenResolver with the following route, refer to [Mutual TLS with PingAM](#).

More information

[org.forgerock.openig.filter.oauth2.cnf.ConfirmationKeyVerifierAccessTokenResolver](#) 

[OAuth 2.0 Mutual TLS Client Authentication and Certificate Bound Access Tokens](#) 

[OAuth2ResourceServerFilter](#)

ScriptableAccessTokenResolver

In OAuth2ResourceServerFilter, use a Groovy script to resolve access tokens against an Authorization Server.

Receive a string representing an access token and use a Groovy script to create an instance or promise of `org.forgerock.http.oauth2.AccessTokenInfo`.

Usage

Use this resolver with the `accessTokenResolver` property of OAuth2ResourceServerFilter.

```
"accessTokenResolver": {
  "type": "ScriptableAccessTokenResolver",
  "config": {
    "type": configuration expression<string>,
    "file": configuration expression<string>, // Use either "file"
    "source": [ string, ... ],                // or "source", but not both.
    "args": map,
    "clientHandler": Handler reference
  }
}
```

Properties

For information about properties for ScriptableAccessTokenResolver, refer to [PingGateway scripts](#).

More information

[org.forgerock.openig.filter.oauth2.ScriptableAccessTokenResolver](#)

[OAuth2ResourceServerFilter](#)

StatelessAccessTokenResolver

Locally resolve and validate stateless access tokens issued by AM, without referring to AM.

AM can be configured to secure access tokens by signing or encrypting. The `StatelessAccessTokenResolver` must be configured for signature or encryption according to the AM configuration.

Usage

Use this resolver with the `accessTokenResolver` property of `OAuth2ResourceServerFilter`.

```
"accessTokenResolver": {
  "type": "StatelessAccessTokenResolver",
  "config": {
    "issuer": configuration expression<string>,
    "secretsProvider": SecretsProvider reference,
    "verificationSecretId": configuration expression<secret-id>, // Use "verificationSecretId" or
    "decryptionSecretId": configuration expression<secret-id>, // "decryptionSecretId", but not both
    "skewAllowance": configuration expression<duration>
  }
}
```

Properties

"issuer": configuration expression<string>, required

URI of the AM instance responsible for issuing access tokens.

"secretsProvider": SecretsProvider reference, required

The [SecretsProvider](#) to query for passwords and cryptographic keys.

"verificationSecretId": configuration expression<secret-id>, required if AM secures access tokens with a signature

The secret ID for the secret used to verify the signature of signed access tokens.

This secret ID must point to a [CryptoKey](#).

Depending on the type of secret store that is used to verify signatures, use the following values:

- For `JwkSetSecretStore`, use any non-empty string that conforms to the field convention for [secret-id](#). The value of the string isn't used.
- For other types of secret stores:
 - `null` : No signature verification is required.

- A `kid` as a string: Signature verification is required with the provided `kid`. The `StatelessAccessTokenResolver` searches for the matching `kid` in the `SecretsProvider`.

You can find more information about how signatures are validated in [Validate the signature of signed tokens](#). You can find more information about how each type of secret store resolves named secrets in [Secrets](#).

Use either `verificationSecretId` or `decryptionSecretId`, according to the configuration of the token provider in AM. If AM is configured to sign **and** encrypt tokens, encryption takes precedence over signing.

"decryptionSecretId": configuration expression<secret-id>, required if AM secures access tokens with encryption

The secret ID for the secret used to decrypt the JWT, for confidentiality.

This secret ID must point to a [CryptoKey](#).

Use either `verificationSecretId` or `decryptionSecretId`, according to the configuration of the token provider in AM. If AM is configured to sign **and** encrypt the token, encryption takes precedence over signing.

"skewAllowance": configuration expression<duration>, optional

The duration to add to the validity period of a JWT to allow for clock skew between different servers.

A `skewAllowance` of 2 minutes affects the validity period as follows:

- A JWT with an `iat` of 12:00 is valid from 11:58 on the PingGateway clock.
- A JWT with an `exp` 13:00 is expired after 13:02 on the PingGateway clock.

Default: To support a zero-trust policy, the skew allowance is by default `zero`.

Example

For examples of how to set up and use `StatelessAccessTokenResolver` to resolve signed and encrypted access tokens, refer to [Validating PingAM stateless access tokens](#).

More information

[org.forgerock.openig.filter.oauth2.StatelessAccessTokenResolver](#) 

[OAuth2ResourceServerFilter](#)

TokenIntrospectionAccessTokenResolver

In `OAuth2ResourceServerFilter`, use the token introspection endpoint, `/oauth2/introspect`, to resolve access tokens and retrieve metadata about the token. The endpoint typically returns the time until the token expires, the OAuth 2.0 *scopes* associated with the token, and potentially other information.

The introspection endpoint is defined as a standard method for resolving access tokens, in RFC-7662, [OAuth 2.0 Token Introspection](#) .

Usage

Use this resolver with the `accessTokenResolver` property of `OAuth2ResourceServerFilter`.

```

"accessTokenResolver": {
  "type": "TokenIntrospectionAccessTokenResolver",
  "config": {
    "amService": AmService reference,           // Use either "amService"
    "endpoint": configuration expression<url>, // or "endpoint", but not both.
    "providerHandler": Handler reference
  }
}

```

Properties

"amService": *AmService* [reference](#), required if endpoint isn't configured

The AmService heap object to use for the token introspection endpoint. The endpoint is extrapolated from the `url` property of the AmService.

When the Authorization Server is AM, use this property to define the token introspection endpoint.

If `amService` is configured, it takes precedence over `endpoint`.

See also [AmService](#).

"endpoint": *configuration expression<url>*, required if amService isn't configured

The URI for the token introspection endpoint. Use `/oauth2/introspect`.

When the Authorization Server is not AM, use this property to define the token introspection endpoint.

If `amService` is configured, it takes precedence over `endpoint`.

"providerHandler": *Handler* [reference](#), optional

Invoke this HTTP client handler to send token info requests.

Provide either the name of a Handler object defined in the heap or an inline Handler configuration object.

Default: `ForgeRockClientHandler`

If you use the AM token introspection endpoint, this handler can be a `Chain` containing a `HeaderFilter` to add the authorization to the request header, as in the following example:


```

"providerHandler": {
  "type": "Chain",
  "config": {
    "filters": [
      {
        "type": "HeaderFilter",
        "config": {
          "messageType": "request",
          "add": {
            "Authorization": [ "Basic ${encodeBase64('<client_id>:<client_secret>')}" ]
          }
        }
      }
    ],
    "handler": "ForgeRockClientHandler"
  }
}

```

Example

You can find an example route that uses the token introspection endpoint in [Validating PingAM access tokens with introspection](#).

More information

[org.forgerock.openig.filter.oauth2.TokenIntrospectionAccessTokenResolverHeaplet](#) 

[OAuth2ResourceServerFilter](#)

PingGateway caches

Learn about Cache metrics in [Metrics at the Prometheus Scrape Endpoint](#).

Session cache

When a user authenticates with AM, this cache stores information about the session. PingGateway can reuse the information without asking AM to verify the session token (SSO token or CDSO token) for each request.

If WebSocket notifications are enabled, the cache evicts entries based on session notifications from AM, making the cached content more accurate and reliable.

By default, session information isn't cached. To increase performance, consider enabling and configuring the cache. Find out more from `sessionCache` in [AmService](#).

Policy cache

When the PolicyEnforcementFilter requests and receives a policy decision from AM, it stores the decision in the policy cache.

When a request matches a cached policy decision, PingGateway can reuse the decision without asking AM for a new decision. When caching is disabled, PingGateway must ask AM to make a decision for each request.

 Tip

Maximize the cache hit ratio by using [RequestResourceUriProvider](#) or [ScriptableResourceUriProvider](#) in conjunction with AM policies. The PolicyEnforcementFilter identifies cached policy decisions by the resource URL returned by these URI providers.

Find more information from the [resourceUriProvider](#) property of PolicyEnforcementFilter.

If WebSocket notifications are enabled, the cache evicts entries based on policy notifications from AM, making the cached content more accurate and reliable.

By default, policy decisions aren't cached.

User profile cache

When the [UserProfileFilter](#) retrieves user information, it caches it. PingGateway can reuse the cached data without repeatedly querying AM to retrieve it.

By default, profile attributes aren't cached.

Access token cache

When a user presents an access token to the OAuth2ResourceServerFilter, the access token cache stores the token. PingGateway can reuse the token information without asking the Authorization Server to verify the access token for each request.

By default, access tokens aren't cached. To increase performance by caching access tokens, consider configuring a cache in one of the following ways:

- Configure a [CacheAccessTokenResolver](#) for a cache based on Caffeine.
- Configure the `cache` property of [OAuth2ResourceServerFilter](#).

Open ID Connect user information cache

When a downstream filter or handler needs user information from an OpenID Connect provider, PingGateway fetches it lazily. By default, PingGateway caches the information for 10 minutes to prevent repeated calls over a short time.

Find out more from `cacheExpiration` in [AuthorizationCodeOAuth2ClientFilter](#).

PingGateway secrets

PingGateway uses the Commons Secrets API to manage secrets, such as passwords and cryptographic keys.

For more information about how PingGateway manages secrets, refer to [About secrets](#).

- [Base64EncodedSecretStore](#)
- [FileSystemSecretStore](#)
- [HsmSecretStore](#)
- [JwkPropertyFormat](#)

- [JwkSetSecretStore](#)
- [KeyStoreSecretStore](#)
- [PemPropertyFormat](#)
- [SecretsKeyManager](#)
- [SecretKeyPropertyFormat](#)
- [SecretsProvider](#)
- [SecretsTrustManager](#)
- [SystemAndEnvSecretStore](#)
- [TrustManager \(deprecated\)](#)

Base64EncodedSecretStore

Manage a repository of generic secrets, such as passwords or simple shared secrets, whose values are base64-encoded, and hard-coded in the route.

This Secret store can only manage the [GenericSecret](#) type.

The secrets provider queries the Base64EncodedSecretStore for a named secret, identified by the `secret-id` in the `"secret-id": "string"` pair. The Base64EncodedSecretStore returns the matching secret.

The secrets provider builds the secret, checking that the secret's constraints are met, and returns a unique secret. If the secret's constraints aren't met, the secrets provider cannot build the secret and the secret query fails.

Secrets from Base64EncodedSecretStore never expire.



Important

Use Base64EncodedSecretStore for testing or evaluation only, to store passwords locally. In production, use an alternative secret store.

Learn how PingGateway manages secrets in [About secrets](#).

Usage

```
{
  "name": string,
  "type": "Base64EncodedSecretStore",
  "config": {
    "secrets": map or configuration expression<map>
  }
}
```

Properties

"secrets": *map or configuration expression<map>, required*

Map of one or more data pairs with the format `Map<String, String>`, where:

- The key is the ID of a secret used in a route
- The value is the base64-encoded value of a secret, or a configuration expression that evaluates to the base64-encoded value of a secret

The following formats are allowed:

```
{
  "secrets": {
    "secret-id": "configuration expression<string>",
    ...
  }
}
```

```
{
  "secrets": "configuration expression<map>"
}
```

In the following example, the property is a map whose values are provided by strings:

```
{
  "type": "Base64EncodedSecretStore",
  "config": {
    "secrets": {
      "agent.password": "d2VsY29tZQ==",
      "crypto.header.key": "Y2hhbmdlaXQ="
    }
  }
}
```

In the following example, the property is a map whose values are provided by a configuration token and a configuration expression. The values are substituted when the route is loaded:

```
{
  "type": "Base64EncodedSecretStore",
  "config": {
    "secrets": {
      "agent.password": "&{secret.value|aGVsbG8=}",
      "crypto.header.key": "${readProperties('file.property')['b64.key.value']}"
    }
  }
}
```

Log level

To facilitate debugging secrets for the Base64EncodedSecretStore, in `logback.xml` add a logger defined by the fully qualified package name of the Base64EncodedSecretStore. The following line in `logback.xml` sets the log level to `ALL` :

```
<logger name="org.forgerock.openig.secrets.Base64EncodedSecretStore" level="ALL" />
```

Example

For an example that uses Base64EncodedSecretStore, refer to `client-credentials.json` in [Client credentials grant with PingAM](#).

More information

Secrets

[org.forgerock.openig.secrets.Base64EncodedSecretStore](#) 

FileSystemSecretStore

Manage a store of secrets held in files, specified as follows:

- Each file must contain only one secret.
- The file must be in the directory specified by the property `directory` .
- The filename must match the `mappings` property `secretId` .
- The file content must match the `mappings` property `format` . For example, if the mapping specifies `BASE64` , the file content must be base64-encoded.

This Secret store can manage secrets of both [GenericSecret](#) and [CryptoKey](#) types when used with dedicated formats.

Secrets are read lazily from the filesystem.

The secrets provider queries the FileSystemSecretStore for a named secret, identified by the name of a file in the specified directory, without the prefix/suffix defined in the store configuration. The FileSystemSecretStore returns the secret that exactly matches the name.

The secrets provider builds the secret, checking that the secret's constraints are met, and returns a unique secret. If the secret's constraints aren't met, the secrets provider cannot build the secret and the secret query fails.

Learn how PingGateway manages secrets in [About secrets](#).

Usage

```
{
  "name": string,
  "type": "FileSystemSecretStore",
  "config": {
    "directory": configuration expression<string>,
    "format": SecretPropertyFormat reference,
    "versionSuffix": configuration expression<string>,
    "suffix": configuration expression<string>,
    "mappings": [ object, ... ],
    "leaseExpiry": configuration expression<duration>,
    "autoRefresh": object
  }
}
```

Properties

"directory": *configuration expression<string>, required*

File path to a directory containing secret files. This object checks the specified directory, but not its subdirectories.

format: *SecretPropertyFormat reference, optional*

Format in which the secret is stored. Use one of the following values or formats:

- **BASE64** : Base64-encoded.

The original secret prior to base64-encoding must use UTF-8 encoding.

- **PLAIN** : Plain text.

The file must use UTF-8 encoding.

- A **JwkPropertyFormat**.

- A **PemPropertyFormat**.

- A **SecretKeyPropertyFormat**.

Default: **BASE64**

"versionSuffix": *configuration expression<string>, optional*

A version suffix, such as `.v`, not including any version numbers.

For details, refer to [the examples that follow](#).

Default: None

"suffix": *configuration expression<string>, optional*

A file suffix or extension, such as `.secret`.

For details, refer to [the examples that follow](#).

Default: None

"mappings": *array of [objects](#), optional*

One or more mappings to define a secret:

secretId: *configuration expression*<[secret-id](#)>, required

The ID of the secret used in your configuration.

format: *SecretPropertyFormat [reference](#), required*

The format and algorithm of the secret. Use [SecretKeyPropertyFormat](#) or [PemPropertyFormat](#).

"leaseExpiry": *configuration expression*<[duration](#)>, optional

The amount of time that secrets produced by this store can be cached before they must be refreshed.

If the duration is `zero` or `unlimited`, PingGateway issues a warning, and uses the default value.

Default: 5 minutes

"autoRefresh": *[object](#), optional*

Automatically reload the FileSystemSecretStore when a file is edited or deleted in the directory given by `directory`.

When `autoRefresh` is triggered, secrets and keys are refreshed even if the `leaseExpiry` has not expired. When `autoRefresh` is triggered, the `leaseExpiry` is reset.

```
{
  "enabled": configuration expression<boolean>,
  "executor": ScheduledExecutorService reference
}
```

enabled: *configuration expression*<[boolean](#)>, optional

Flag to enable or disable automatic reload:

- `true`: Enable
- `false`: Disable

Default: `true`

"executor": *ScheduledExecutorService [reference](#), optional*

A [ScheduledExecutorService](#) to monitor the filesystem.

Default: The default ScheduledExecutorService in the heap

Log level

To facilitate debugging secrets for the FileSystemSecretStore, in `logback.xml` add a logger defined by the fully qualified package name of the property resolver. The following line in `logback.xml` sets the log level to `ALL`:

```
<logger name="org.forgerock.secrets.propertyresolver" level="ALL" />
```

Examples

The following example `FileSystemSecretStore` matches `example.pem`, `example.v1.pem`, and `example.v2.pem`. The active secret file is the one with the largest version number, `mySecret.v2.pem`:

```
{
  "name": "FileSystemSecretStore-1",
  "type": "FileSystemSecretStore",
  "config": {
    "directory": "&{secretsDir}",
    "format": "PLAIN",
    "versionSuffix": ".v",
    "suffix": ".pem",
    "mappings": [
      {
        "secretId": "example",
        "format": "pemPropertyFormat"
      }
    ]
  }
}
```

Also refer to [Pass runtime data in a JWT signed with a PEM](#).

More information

Secrets

org.forgerock.openig.secrets.FileSystemSecretStoreHeaplet 

HsmSecretStore

Manage a store of secrets with a hardware security module (HSM) device or a software emulation of an HSM device, such as SoftHSM.

This Secret store can only manage secrets of the [CryptoKey](#) type.

The secrets provider queries the `HsmSecretStore` for a named secret, identified by a secret ID and a stable ID, corresponding to the `secret-id / aliases` mapping. The `HsmSecretStore` returns a list of matching secrets.

The secrets provider builds the secret, checking that the secret's constraints are met, and returns a unique secret. If the secret's constraints aren't met, the secrets provider cannot build the secret and the secret query fails.

Learn how PingGateway manages secrets in [About secrets](#).

Usage

```
{
  "name": string,
  "type": "HsmSecretStore",
  "config": {
    "providerName": configuration expression<string>,
    "storePasswordSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference,
    "mappings": [ object, ... ],
    "leaseExpiry": configuration expression<duration>,
    "storePassword": configuration expression<secret-id> //deprecated
  }
}
```

Properties

"providerName": *configuration expression<string>, required*

The name of the pre-installed Java Security Provider supporting an HSM. Use a physical HSM device, or a software emulation of an HSM device, such as SoftHSM.

For the SunPKCS11 provider, concatenate "providerName" with the prefix `SunPKCS11-`. For example, declare the following for the name `FooAccelerator`:

```
"providerName": "SunPKCS11-FooAccelerator"
```

"storePasswordSecretId": *configuration expression<secret-id>, optional*

The secret ID of the password to access the HsmSecretStore.

This secret ID must point to a [GenericSecret](#).

For information about how PingGateway manages secrets, refer to [About secrets](#).

"secretsProvider": *SecretsProvider reference, required*

The [SecretsProvider](#) to query for the `storePassword`.

"mappings": *array of objects, required*

One or more mappings of one secret ID to one or more aliases.

```
"mappings" : {
  "secretId": configuration expression<secret-id>,
  "aliases": array of configuration expression<string>, //use aliases or
  "aliasesMatching": [ string, ... ] //aliasesMatching but not both
}
```

"secretId": *configuration expression<secret-id>, required*

The secret ID of the key.

"aliases": array of configuration expression<strings>, required if aliasesMatching is not used

One or more key aliases. Named aliases are mapped to the secret ID.

Use `aliases` or `aliasesMatching` but not both.

"aliasesMatching": array of <strings>, required if aliases is not used

One or more regular expressions to match key aliases. Aliases that match the expressions are mapped to the secret ID.

Use `aliases` or `aliasesMatching` but not both.

Some KeyStores, such as a global Java TrustStore, can contain hundreds of valid certificates. Use this property to map multiple aliases to a secret ID without listing them all in the mapping.

The secret store uses the mappings as follows:

- When the secret is used to create signatures or encrypt values, the secret store uses the *active secret*, the first alias in the list.
- When the secret is used to verify signatures or decrypt data, the secret store tries all of the mapped aliases in the list, starting with the first, and stopping when it finds a secret that can successfully verify signature or decrypt the data.

The following example maps the named aliases to the named secret IDs:

```
"mappings": [
  {
    "secretId": "id.key.for.signing.jwt",
    "aliases": [ "signingkeyalias", "anothersigningkeyalias" ]
  },
  {
    "secretId": "id.key.for.encrypting.jwt",
    "aliases": [ "encryptionkeyalias" ]
  }
]
```

The following example maps aliases that match the regular expression `.*` to the named secret ID:

```
"mappings": [
  {
    "secretId": "id.key.for.signing.jwt",
    "aliasesMatching": [ ".*" ]
  }
]
```

secretId: configuration expression<secret-id>, required

The ID of the secret used in your configuration.

aliases: array of configuration expression<strings>, required

One or more aliases for the secret ID. :leveloffset: +2

"leaseExpiry": configuration expression<duration>, optional

The amount of time that secrets produced by this store can be cached before they must be refreshed.

If the duration is `zero` or `unlimited`, PingGateway issues a warning, and uses the default value.

Default: 5 minutes

"storePassword": configuration expression<secret-id>, required if storePasswordSecretId not set**Important**

The use of this property is deprecated. If the KeyStore is password-protected, use `storePasswordSecretId`. For more information, refer to the [Deprecated](#) section of the *Release Notes*.

The secret ID of the password to access the `HsmSecretStore`.

+ For information about how PingGateway manages secrets, refer to [About secrets](#).

Log level

To facilitate debugging secrets for the `HsmSecretStore`, in `logback.xml` add a logger defined by the fully qualified package name of the `HsmSecretStore`. The following line in `logback.xml` sets the log level to `ALL`:

```
<logger name="org.forgerock.secrets.keystore" level="ALL" />
```

Example

To set up this example:

1. Set up and test the example in [JwtBuilderFilter](#), and then replace the `KeyStoreSecretStore` in that example with an `HsmSecretStore`.
2. Set an environment variable for the `HsmSecretStore` password, `storePassword`, and then restart PingGateway.

For example, if the `HsmSecretStore` password is `password`, set the following environment variable:

```
export HSM_PIN='cGFzc3dvcmQ='
```

The password is retrieved by the `SystemAndEnvSecretStore`, and must be base64-encoded.

3. Create a provider config file, as specified in the [PKCS#11 Reference guide](#).
4. Depending on your version of Java, create a `java.security.ext` file for the PingGateway instance, with the following content:

```
security.provider.<number>=<provider-name> <path-to-provider-cfg-file>
```

or

```
security.provider.<number>=<class-name> <path-to-provider-cfg-file>
```

5. Start the PingGateway JVM with the following system property that points to the provider config file:

```
-Djava.security.properties=file://path-to-security-extension-file
```

The following example route is based on the examples in [JwtBuilderFilter](#), replacing the KeyStoreSecretStore with an HsmSecretStore:

```

{
  "name": "hsm-jwt-signature",
  "condition": "${find(request.uri.path, '/hsm-jwt-signature$')}",
  "baseURI": "http://app.example.com:8081",
  "heap": [
    {
      "name": "SystemAndEnvSecretStore-1",
      "type": "SystemAndEnvSecretStore"
    },
    {
      "name": "AmService-1",
      "type": "AmService",
      "config": {
        "agent": {
          "username": "ig_agent",
          "passwordSecretId": "agent.secret.id"
        },
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "url": "http://am.example.com:8088/openam"
      }
    },
    {
      "name": "HsmSecretStore-1",
      "type": "HsmSecretStore",
      "config": {
        "providerName": "SunPKCS11-SoftHSM",
        "storePasswordSecretId": "hsm.pin",
        "secretsProvider": "SystemAndEnvSecretStore-1",
        "mappings": [{
          "secretId": "id.key.for.signing.jwt",
          "aliases": [ "signature-key" ]
        }]
      }
    }
  ],
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [{
        "name": "SingleSignOnFilter-1",
        "type": "SingleSignOnFilter",
        "config": {
          "amService": "AmService-1"
        }
      }, {
        "name": "UserProfileFilter-1",
        "type": "UserProfileFilter",
        "config": {
          "username": "${contexts.ssoToken.info.uid}",
          "userService": {
            "type": "UserProfileService",
            "config": {
              "amService": "AmService-1"
            }
          }
        }
      }, {
        "name": "JwtBuilderFilter-1",
        "type": "JwtBuilderFilter",
        "config": {

```

```
    "template": {
      "name": "${contexts.userProfile.commonName}",
      "email": "${contexts.userProfile.rawInfo.mail[0]}"
    },
    "secretsProvider": "HsmSecretStore-1",
    "signature": {
      "secretId": "id.key.for.signing.jwt"
    }
  }, {
    "name": "HeaderFilter-1",
    "type": "HeaderFilter",
    "config": {
      "messageType": "REQUEST",
      "add": {
        "x-openig-user": ["${contexts.jwtBuilder.value}"]
      }
    }
  }],
  "handler": "ReverseProxyHandler"
}
```

Source: [hsm-jwt-signature.json](#)

More information

Secrets

[org.forgerock.openig.secrets.HsmSecretStoreHeaplet](#)

JwkPropertyFormat

The format of a secret used with [FileSystemSecretStore](#) to decode JSON Web Key (JWK) formatted keys into secrets.

Usage

```
{
  "name": string,
  "type": "JwkPropertyFormat"
}
```

Example

```
{
  "heap" : [
    {
      "name": "jwkPropertyFormat",
      "type": "JwkPropertyFormat"
    },
    {
      "name": "MySecretStore",
      "type": "FileSystemSecretStore",
      "config": {
        "format": "jwkPropertyFormat",
        "directory": "&{secretsDir}/idcloud",
        "mappings": [ {
          "secretId": "my.privateKey.jwk",
          "format": "jwkPropertyFormat"
        }
      ]
    }
  ]
}
```

More information

[org.forgerock.openig.secrets.JwkPropertyFormatHeaplet](https://forgerock.org/openig/secrets/JwkPropertyFormatHeaplet)

JwkSetSecretStore

A secret store of JSON Web Keys (JWK) from a local or remote JWK Set.

This Secret store can only manage secrets of the [CryptoKey](#) type.

The secrets provider builds the secret, checking that the secret's constraints are met, and returns a unique secret. If the secret's constraints aren't met, the secrets provider cannot build the secret and the secret query fails.

You can find a description of how secrets are managed in [About secrets](#).

You can find more information about JWKs and JWK Sets in [JSON Web Key \(JWK\)](#).

Usage

```
{
  "name": string,
  "type": "JwkSetSecretStore",
  "config": {
    "jwkUrl": configuration expression<url>,
    "handler": Handler reference,
    "cacheTimeout": configuration expression<duration>,
    "cacheMissCacheTime": configuration expression<duration>,
    "leaseExpiry": configuration expression<duration>
  }
}
```

Properties

"jwkUrl": *configuration expression*<url>, *required*

A URL that contains the client's public keys in JWK format.

"handler": *Handler reference*, *optional*

An HTTP client handler to communicate with the `jwkUrl`.

Usually set this property to the name of a ClientHandler configured in the heap, or a chain that ends in a ClientHandler.

Default: ClientHandler

"cacheTimeout": *configuration expression*<duration>, *optional*

Delay before the cache is reloaded. The cache contains the `jwkUrl`.

The cache cannot be deactivated. If a value lower than 10 seconds is configured, a warning is logged and the default value is used instead.

Default: 2 minutes

"cacheMissCacheTime": *configuration expression*<duration>, *optional*

If the `jwkUrl` is looked up in the cache and isn't found, this is the delay before the cache is reloaded.

Default: 2 minutes

"leaseExpiry": *configuration expression*<duration>, *optional*

The amount of time that secrets produced by this store can be cached before they must be refreshed.

If the duration is `zero` or `unlimited`, PingGateway issues a warning, and uses the default value.

Default: 5 minutes

Log level

To facilitate debugging secrets for the JwkSetSecretStore, in `logback.xml` add a logger defined by the fully qualified package name of the JwkSetSecretStore. The following line in `logback.xml` sets the log level to `ALL`:

```
<logger name="org.forgerock.secrets.jwkset" level="ALL" />
```

Example

You can find an example of how to set up and use JwkSetSecretStore to validate signed access tokens in [With JwkSetSecretStore and PingAM](#).

In the following example, a StatelessAccessTokenResolver validates a signed access token by using a JwkSetSecretStore:


```

"accessTokenResolver": {
  "type": "StatelessAccessTokenResolver",
  "config": {
    "secretsProvider": {
      "type": "JwkSetSecretStore",
      "config": {
        "jwkUrl": "https://am.example.com:8888/am/oauth2/connect/jwk_uri"
      },
      "issuer": "https://am.example.com:8888/am/oauth2",
      "verificationSecretId": "verification.secret.id"
    }
  }
}

```

The JWT signature is validated as follows:

- If the JWT contains a `kid` with a matching secret in the JWK set:
 - The secrets provider queries the `JwkSetSecretStore` for a named secret.
 - The `JwkSetSecretStore` returns the matching secret, identified by a stable ID.
 - The `StatelessAccessTokenResolver` tries to validate the signature with that named secret. If it fails, the token is considered as invalid.

In the route, note that the property `verificationSecretId` must be configured but isn't used in named secret resolution.

- If the JWT contains a `kid` without a matching secret in the JWK set:
 - The secrets provider queries the `JwkSetSecretStore` for a named secret.
 - Because the referenced JWK set doesn't contain a matching secret, named secret resolution fails. PingGateway tries valid secret resolution in the same way as when the JWT doesn't contain a `kid`.
- If the JWT doesn't contain a `kid`:
 - The secrets provider queries the `JwkSetSecretStore` for list of valid secrets, whose secret ID is `verification.secret.id`.
 - The `JwkSetSecretStore` returns all secrets in the JWK set whose purpose is signature verification. For example, signature verification keys can have the following JWK parameters:

```

{
  "use": "sig"
}

```

```

{
  "key_opts": [ "verify" ]
}

```

Secrets are returned in the order that they are listed in the JWK set.

- The `StatelessAccessTokenResolver` tries to validate the signature with each secret sequentially, starting with the first, and stopping when it succeeds.
- If none of the valid secrets can verify the signature, the token is considered as invalid.

More information

org.forgerock.openig.secrets.JwkSetSecretStoreHeaplet 

[JSON Web Key \(JWK\)](#) 

KeyStoreSecretStore

Manages a secret store for cryptographic keys and certificates, based on a standard Java keystore.



Warning

Legacy keystore types such as JKS and JCEKS are supported but aren't secure. Consider using the PKCS#12 keystore type.

The secrets provider queries the `KeyStoreSecretStore` for a named secret, identified by a secret ID and a stable ID, corresponding to the `secret-id / aliases` mapping. The `KeyStoreSecretStore` returns a secret that exactly matches the name, and whose purpose matches the secret ID and any purpose constraints.

The secrets provider builds the secret, checking that the secret's constraints are met, and returns a unique secret. If the secret's constraints aren't met, the secrets provider cannot build the secret and the secret query fails.

Learn how PingGateway manages secrets in [About secrets](#).

Usage

```
{
  "name": string,
  "type": "KeyStoreSecretStore",
  "config": {
    "file": configuration expression<string>,
    "storeType": configuration expression<string>,
    "storePasswordSecretId": configuration expression<string>,
    "entryPasswordSecretId": configuration expression<string>,
    "secretsProvider": SecretsProvider reference,
    "mappings": [ {
      "secretId": configuration expression<secret-id>,
      // Use aliases or aliasesMatching, not both:
      "aliases": array of configuration expression<string>,
      "aliasesMatching": [ string, ... ]
    }, ... ],
    "leaseExpiry": configuration expression<duration>,
    "securityProvider": configuration expression<string>,
    "autoRefresh": {
      "enabled": configuration expression<boolean>,
      "executor": ScheduledExecutorService reference
    },
    "storePassword": configuration expression<string>, //deprecated
    "keyEntryPassword": configuration expression<string> //deprecated
  }
}
```

Properties

file

"file" : configuration expression<[string](#)>, required

The path to the keystore file.

storeType

"storeType" : configuration expression<[string](#)>, optional

The keystore type.

Default: PKCS12

storePasswordSecretId

"storePasswordSecretId" : configuration expression<[secret-id](#)>, optional

The secret ID of the password to access the keystore.

This secret ID must point to a [GenericSecret](#).

PingGateway searches for the value of the password until it finds it, first locally, then in parent routes, then in `config.json`.

To create a store password, add a file containing the password. The filename must correspond to the secret ID. The file content must contain only the password with no trailing spaces or carriage returns.

Default: None; the keystore isn't password-protected

entryPasswordSecretId

"entryPasswordSecretId" : *configuration expression*<secret-id>, optional

The secret ID of the password to access entries in the keystore.

This secret ID must point to a [GenericSecret](#).

To create an entry password, add a file containing the password. The filename must correspond to the secret ID. The file content must contain only the password with no trailing spaces or carriage returns.

When this property is used, the password must be the same for all entries in the keystore. If the keystore uses different passwords for entries, **entryPasswordSecretId** doesn't work.

Default: The value of [storePasswordSecretId](#)

secretsProvider

"secretsProvider" : *SecretsProvider* [reference](#), required

The [SecretsProvider](#) to query for the keystore password and key entry password.

mappings

"mappings" : *array of* [objects](#), required

One or more mappings of one secret ID to one or more aliases.

Some keystores, such as a global Java truststore, can contain hundreds of valid certificates. Use this property to map multiple aliases to a secret ID without listing them all in the mapping.

The secret store uses the mappings as follows:

- When the secret is used to create signatures or encrypt values, the secret store uses the *active secret*, the first alias in the list.
- When the secret is used to verify signatures or decrypt data, the secret store tries all the mapped aliases in the list, starting with the first. It stops when it finds a secret that can successfully verify the signature or decrypt the data.

"secretId" : *configuration expression*<secret-id>, required

The secret ID of the key.

"aliases" : *array of configuration expression*<strings>, required if **aliasesMatching** isn't used

One or more key aliases. Named aliases are mapped to the secret ID.

Use **aliases** or **aliasesMatching** but not both.

The following example maps aliases that match the regular expression `.*` to the named secret ID:

```
"mappings": [
  {
    "secretId": "id.key.for.signing.jwt",
    "aliasesMatching": [".*"]
  }
]
```

"aliasesMatching": array of <strings>, required if aliases isn't used

One or more regular expressions to match key aliases. Aliases that match the expressions are mapped to the secret ID.

Use `aliases` or `aliasesMatching` but not both.

The following example maps the named aliases to the named secret IDs:

```
"mappings": [
  {
    "secretId": "id.key.for.signing.jwt",
    "aliases": [ "signingkeyalias", "anothersigningkeyalias" ]
  },
  {
    "secretId": "id.key.for.encrypting.jwt",
    "aliases": [ "encryptionkeyalias" ]
  }
]
```

leaseExpiry

"leaseExpiry" : *configuration expression<duration>, optional*

The amount of time that secrets produced by this store can be cached before they must be refreshed.

If the duration is `zero` or `unlimited`, PingGateway issues a warning and uses the default value.

Default: 5 minutes

securityProvider

"securityProvider" : *configuration expression<string>, optional*

Java security provider to use when loading the keystore.

For example, the name of a security provider in the `java.security` configuration file for the JVM.

Default: use the default security provider for the JVM

autoRefresh

"autoRefresh" : *object, optional*

Automatically reload the KeyStoreSecretStore when the keystore is edited or deleted.

enabled: *configuration expression*<[boolean](#)>, optional

Flag to enable or disable automatic reload:

- `true` : Enable
- `false` : Disable

Default: `true`

"executor": *ScheduledExecutorService* [reference](#), optional

A [ScheduledExecutorService](#) to monitor the keystore.

Default: The default ScheduledExecutorService in the heap

storePassword (deprecated)

"storePassword" : *configuration expression*<[secret-id](#)>, required

**Important**

This property is deprecated. Use [storePasswordSecretId](#) instead. Learn more in the [Deprecated](#) [section of the Release Notes](#).

The secret ID of the password to access the KeyStore.

This secret ID must point to a [GenericSecret](#).

PingGateway searches for the value of the password until it finds it, first locally, then in parent routes, then in `config.json`.

To create a store password, add a file containing the password. The filename must correspond to the secret ID. The file content must contain only the password with no trailing spaces or carriage returns.

keyEntryPassword (deprecated)

"keyEntryPassword" : *configuration expression*<[secret-id](#)>, optional

**Important**

This property is deprecated. Use [entryPasswordSecretId](#) instead. Learn more in the [Deprecated](#) [section of the Release Notes](#).

The secret ID of the password to access entries in the KeyStore.

This secret ID must point to a [GenericSecret](#).

To create an entry password, add a file containing the password. The filename must correspond to the secret ID. The file content must contain only the password with no trailing spaces or carriage returns.

When this property is used, the password must be the same for all entries in the keystore. If the keystore uses different passwords for entries, `keyEntryPassword` doesn't work.

Default: The value of [storePassword \(deprecated\)](#)

Log level

To facilitate debugging secrets for the KeyStoreSecretStore, in `logback.xml` add a logger defined by the fully qualified package name of the KeyStoreSecretStore. The following line in `logback.xml` sets the log level to `ALL` :

```
<logger name="org.forgerock.secrets.keystore" level="ALL" />
```

Examples

Passwords, passphrases, and API keys

You can store passwords, passphrases, and API keys in JCEKS and PKCS12 keystores using the Java `keytool` command. This feature is limited to Java software.

The following example uses the Java `keytool -importpass` command to store an API key:

```
$ keytool \  
-importpass \  
-alias my-client-password \  
-keystore /path/to/secrets/keystore \  
-storepass:file /path/to/secrets/keystore.pin \  
Enter the password to be stored:  
Re-enter password:
```

Use a KeyStoreSecretStore to set the secret ID for the password, passphrase, or API key. The following example gets the password to authenticate to a third-party service from the keystore:

```

{
  "heap": [
    {
      "name": "ClientPasswordSecretStore",
      "type": "KeyStoreSecretStore",
      "config": {
        "file": "/path/to/secrets/keystore",
        "storePasswordSecretId": "keystore.pin",
        "secretsProvider": {
          "type": "FileSystemSecretStore",
          "config": {
            "directory": "/path/to/secrets/",
            "format": "PLAIN"
          }
        }
      },
    },
    "mappings": [
      {
        "secretId": "client.password.secret.id",
        "aliases": [
          "my-client-password"
        ]
      }
    ]
  },
  {
    "name": "Client of third-party service",
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "HttpBasicAuthenticationClientFilter",
          "config": {
            "username": "my-client",
            "passwordSecretId": "client.password.secret.id",
            "secretsProvider": "ClientPasswordSecretStore"
          }
        }
      ],
      "handler": "ClientHandler"
    }
  }
]
}

```

Verification keys

This example gets the keys to validate a signed access token from a keystore:


```

"accessTokenResolver": {
  "type": "StatelessAccessTokenResolver",
  "config": {
    "secretsProvider": {
      "type": "KeyStoreSecretStore",
      "config": {
        "file": "IG_keystore.p12",
        "storeType": "PKCS12",
        "storePasswordSecretId": "keystore.secret.id",
        "entryPasswordSecretId": "keystore.secret.id",
        "mappings": [{
          "secretId": "verification.secret.id",
          "aliases": [ "verification.key.1", "verification.key.2" ]
        }]
      },
      "issuer": "https://am.example.com:8888/am/oauth2",
      "verificationSecretId": "verification.secret.id"
    }
  }
}

```

The JWT signature is validated as follows:

- If the JWT contains a `kid` with a mapped value, for example `verification.key.1` :
 - The secrets provider queries the KeyStoreSecretStore for a named secret with the secret ID `verification.secret.id` and the stable ID `verification.key.1` .
 - Because the KeyStoreSecretStore contains that mapping, the KeyStoreSecretStore returns a named secret.
 - The StatelessAccessTokenResolver tries to validate the JWT signature with the named secret. If it fails, the token is considered as invalid.
- If the JWT contains a `kid` with an unmapped value, for example, `verification.key.3` :
 - The secrets provider queries the KeyStoreSecretStore for a named secret with the secret ID `verification.secret.id` and the stable ID `verification.key.3` .
 - Because the KeyStoreSecretStore doesn't contain that mapping, named secret resolution fails. PingGateway tries valid secret resolution in the same way as when the JWT doesn't contain a `kid` .
- If the JWT doesn't contain a `kid` :
 - The secrets provider queries the KeyStoreSecretStore for all valid secrets, whose alias is mapped to the secret ID `verification.secret.id` . There are two valid secrets, with aliases `verification.key.1` and `verification.key.2` .
 - The StatelessAccessTokenResolver first tries to verify the signature with `verification.key.1` . If that fails, it tries `verification.key.2` .
 - If neither of the valid secrets can verify the signature, the token is considered as invalid.

More information

[org.forgerock.secrets.keystore.KeyStoreSecretStore](#) 

org.forgerock.openig.secrets.KeyStoreSecretStoreHeaplet

PemPropertyFormat

The format of a secret used with a mappings configuration in FileSystemSecretStore and SystemAndEnvSecretStore. Privacy-Enhanced Mail (PEM) is a file format for storing and sending cryptographic keys, certificates, and other data, based on standards in [Textual Encodings of PKIX, PKCS, and CMS Structures](#). By default, OpenSSL generates keys using the PEM format.

Encryption methods and ciphers used for PEM encryption must be supported by the Java Cryptography Extension.

PEM keys have the following format, where the PEM label is associated to the type of stored cryptographic material:

```
-----BEGIN {PEM label}-----
Base64-encoded cryptographic material
-----END {PEM label}-----
```

PEM Label	Stored Cryptographic Material
CERTIFICATE	X.509 Certificate
PUBLIC KEY	X.509 SubjectPublicKeyInfo
PRIVATE KEY	PKCS#8 Private Key
ENCRYPTED PRIVATE KEY	Encrypted PKCS#8 Private Key
EC PRIVATE KEY	EC Private Key
RSA PRIVATE KEY	PKCS#1 RSA Private Key
RSA PUBLIC KEY	PKCS#1 RSA Public Keys
DSA PRIVATE KEY	PKCS#1-style DSA Private Key
HMAC SECRET KEY	HMAC Secret Keys
AES SECRET KEY	AES Secret Keys
GENERIC SECRET	Generic Secrets (passwords, API keys, etc)

Note the following points about the key formats:

- PKCS#1 is the standard that defines RSA. Learn more in [RFC 8017: RSA Public Key Syntax](#).
- PKCS#1-style DSA and EC keys aren't defined in any standard, but are adapted from the RSA format.
- `HMAC SECRET KEY` , `AES SECRET KEY` , and `GENERIC SECRET` are a ForgeRock extension, and not currently supported by any other tools.

The following example is non-standard PEM encoding of an HMAC symmetric secret key. The payload is base64-encoded random bytes that are the key material, with no extra encoding.

```
-----BEGIN HMAC SECRET KEY-----
Pj/Ve1...thB0U=
-----END HMAC SECRET KEY-----
```

Run the following example command to create the key:

```
cat <<EOF
-----BEGIN HMAC SECRET KEY-----
$(head -c32 /dev/urandom | base64)
-----END HMAC SECRET KEY-----
EOF
```

Usage

```
{
  "name": string,
  "type": "PemPropertyFormat",
  "config": {
    "decryptionSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference
  }
}
```

Properties

"decryptionSecretId": *configuration expression*<[secret-id](#)>, optional

The secret ID for the secret to decrypt a PKCS#8 private key.

This secret ID must point to a [GenericSecret](#).

"secretsProvider": *SecretsProvider* [reference](#), required when decryptionSecretId is used

The [SecretsProvider](#) to query for the decryption secret.

Example

You can find examples of use in [Pass runtime data in a JWT signed with a PEM](#) and [Pass runtime data in a JWT signed and encrypted with a PEM](#).

More information

org.forgerock.openig.secrets.PemPropertyFormatHeaplet [↗](#)

SecretsKeyManager

Uses the Commons Secrets API to manage keys that authenticate a TLS connection to a peer. The configuration references the keystore that holds the keys.

Usage

```
{
  "name": string,
  "type": "SecretsKeyManager",
  "config": {
    "signingSecretId": [ configuration expression<secret-id>, ... ] || configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference
  }
}
```

Properties

"signingSecretId": array of configuration expressions<secret-id>, required

One or more secret IDs used to retrieve private signing keys.

PingGateway accepts a scalar instead of an array when there's only one secret ID.

A secret ID must point to a [CryptoKey](#).

"secretsProvider": SecretsProvider reference, required

The [SecretsProvider](#) to query for secrets to resolve the private signing key.

Example

The following example uses a private key found from a keystore for TLS handshake.

```
{
  "type": "SecretsKeyManager",
  "config": {
    "signingSecretId": "key.manager.secret.id",
    "secretsProvider": {
      "type": "KeyStoreSecretStore",
      "config": {
        "file": "path/to/certs/ig.example.com.p12",
        "storePasswordSecretId": "keystore.pass",
        "secretsProvider": "SecretsPasswords",
        "mappings": [{
          "secretId": "key.manager.secret.id",
          "aliases": [ "ig.example.com" ]
        }]
      }
    }
  }
}
```

More information

Secrets

[org.forgerock.openig.secrets.SecretsKeyManagerHeaplet](#)

SecretKeyPropertyFormat

The format of a secret used with a secret store.

Usage

```
{
  "name": string,
  "type": "SecretKeyPropertyFormat",
  "config": {
    "format": SecretPropertyFormat reference,
    "algorithm": configuration expression<string>
  }
}
```

Properties

format: *SecretPropertyFormat* [reference](#), *optional*

Format in which the secret is stored. Use one of the following values or define a format:

- **BASE64** : Base64-encoded

The original secret prior to base64-encoding must use UTF-8 encoding.

- **PLAIN** : Plain text

The text must use UTF-8 encoding.

Default: **BASE64**

"algorithm": *configuration expression*<[string](#)>, *required*

The algorithm name used for encryption and decryption. Use algorithm names given in [Java Security Standard Algorithm Names](#).

Example

```
{
  "type": "SecretKeyPropertyFormat",
  "config": {
    "format": "PLAIN",
    "algorithm": "AES"
  }
}
```

More information

Secrets

org.forgerock.openig.secrets.SecretKeyPropertyFormatHeaplet

SecretsProvider

Uses the specified secret stores to resolve queried secrets, such as passwords and cryptographic keys. Attempts to resolve the secret with the secret stores in the order that they are declared in the array.

Usage

```
{
  "name": string,
  "type": "SecretsProvider",
  "config": {
    "stores": [ SecretStore reference, ... ]
  }
}
```

This object can alternatively be configured in a compact format, without the SecretsProvider declaration, as follows:

- With an inline secret store:

```
"secretsProvider": {
  "type": "secret store type1",
  "config": {...}
}
```

- With multiple inline secret stores:

```
"secretsProvider": [
  {
    "type": "secret store type1",
    "config": {...}
  },
  {
    "type": "secret store type2",
    "config": {...}
  }
]
```

- With a referenced secret store:

```
"secretsProvider": "mySecretStore1"
```

- With multiple referenced secret stores:

```
"secretsProvider": [
  "mySecretStore1", "mySecretStore2"
]
```

Refer to [Example](#) for more example configurations.

Properties

"stores": *array of SecretStore references, required*

One or more secret stores to provide access to stored secrets. Configure secret stores described in [Secrets](#).

Example

The following SecretsProvider is used in [Discovery and dynamic registration with PingAM](#).

```
"secretsProvider": {
  "type": "SecretsProvider",
  "config": {
    "stores": [
      {
        "type": "KeyStoreSecretStore",
        "config": {
          "file": "/path/to/keystore.p12",
          "mappings": [
            {
              "aliases": [ "myprivatekeyalias" ],
              "secretId": "private.key.jwt.signing.key"
            }
          ]
        },
        "storePasswordSecretId": "keystore.secret.id",
        "storeType": "PKCS12",
        "secretsProvider": "SystemAndEnvSecretStore-1"
      }
    ]
  }
}
```

The following example shows the equivalent SecretsProvider configuration with an inline compact format:

```

"secretsProvider": {
  "name": "KeyStoreSecretStore-1",
  "type": "KeyStoreSecretStore",
  "config": {
    "file": "/path/to/keystore.p12",
    "mappings": [
      {
        "aliases": [ "myprivatekeyalias" ],
        "secretId": "private.key.jwt.signing.key"
      }
    ],
    "storePasswordSecretId": "keystore.secret.id",
    "storeType": "PKCS12",
    "secretsProvider": "SystemAndEnvSecretStore-1"
  }
}

```

The following example shows the equivalent SecretsProvider configuration with a compact format, referencing a KeyStoreSecretStore object in the heap:

```

"secretsProvider": "KeyStoreSecretStore-1"

```

More information

[StatelessAccessTokenResolver](#)

[Secrets](#)

[org.forgerock.secrets.SecretsProvider](https://forgerock.org/docs/forgerock-secrets/SecretsProvider) 

SecretsTrustManager

Uses the Commons Secrets API to manage trust material that verifies the credentials presented by a peer. Trust material is usually public key certificates. The configuration references the secrets store that holds the trust material.

Usage

```

{
  "name": string,
  "type": "SecretsTrustManager",
  "config": {
    "verificationSecretId": configuration expression<secret-id>,
    "certificateVerificationSecretId": configuration expression<secret-id>,
    "secretsProvider": SecretsProvider reference,
    "checkRevocation": configuration expression<boolean>
  }
}

```


Properties

"verificationSecretId": configuration expression<[secret-id](#)>, required if certificateVerificationSecretId isn't used

Either `verificationSecretId` or `certificateVerificationSecretId` is required.

The secret ID to retrieve trusted certificates. This secret ID must point to a [CryptoKey](#).

Consider the following requirements for using certificates with `verificationSecretId`:

- Certificates loaded from keystores can be used with the following constraint:
 - The KeyUsage extension `digitalSignature` must be set **or** no KeyUsage extension must be set
- Certificates loaded from JWKs or JWK sets can be used with the following constraints:
 - The `use` parameter must be set to `sig` **or** the `use` parameter must not be set
 - The `key_ops` parameter must contain `verify` **or** the `key_ops` parameter must not be set
- Certificates loaded from PEM can be used without constraint.

"certificateVerificationSecretId": configuration expression<[secret-id](#)>, required if verificationSecretId isn't used

Either `verificationSecretId` or `certificateVerificationSecretId` is required.

The secret ID to retrieve certificates for trusted certificate authorities (CA). Use this property when you trust client certificates **only because** they are signed by a trusted CA.

Consider the following requirements:

- Certificates loaded from keystores can be used with the following constraint:
 - The KeyUsage extension `keyCertSign` must be set **or** no KeyUsage extension must be set
- Certificates loaded from JWKs or JWK sets can be used with the following constraints:
 - The `use` parameter must not be set
 - The `key_ops` parameter must not be set
- Certificates loaded from PEM can be used without constraint.

"secretsProvider": [SecretsProvider](#) [reference](#), required

The [SecretsProvider](#) to query for secrets to resolve trusted certificates.

"checkRevocation": configuration expression<[boolean](#)>, optional

Specifies whether to check for certificate revocation.

Default: `true`

Example

The following example trusts a list of certificates found in a given keystore:

```
{
  "name": "SecretsTrustManager-1",
  "type": "SecretsTrustManager",
  "config": {
    "verificationSecretId": "trust.manager.secret.id",
    "secretsProvider": {
      "type": "KeyStoreSecretStore",
      "config": {
        "file": "path/to/certs/truststore.p12",
        "storePasswordSecretId": "keystore.pass",
        "secretsProvider": "SecretsPasswords",
        "mappings": [{
          "secretId": "trust.manager.secret.id",
          "aliases": [ "alias-of-trusted-cert-1", "alias-of-trusted-cert-2" ]
        }]
      }
    }
  }
}
```

The following example trusts a list of CA-signed certificates found in a given keystore:

```
{
  "type": "SecretsTrustManager",
  "config": {
    "certificateVerificationSecretId": "ca.secret.id",
    "secretsProvider": {
      "type": "KeyStoreSecretStore",
      "config": {
        "file": "${ig.instance.dir}/certs/truststore.p12",
        "storePassword": "keystore.pass",
        "secretsProvider": "SecretsPasswords",
        "mappings": [{
          "secretId": "ca.secret.id",
          "aliases": [ "alias-of-trusted-cacert-1", "alias-of-trusted-cacert-2" ]
        }]
      }
    }
  }
}
```

More information

Secrets

org.forgerock.openig.secrets.SecretsTrustManagerHeaplet 

SystemAndEnvSecretStore

Manage a store of secrets from system properties and environment variables.

This secret store can manage GenericSecret and CryptoKey [secret types](#) when used with dedicated formats.

A secret ID must conform to the convention described in [secret-id](#). The reference is then transformed to match the environment variable name, as follows:

- Periods (.) are converted to underscores.
- Characters are transformed to uppercase.

For example, `my.secret.id` is transformed to `MY_SECRET_ID`.

The secrets provider queries the SystemAndEnvSecretStore for a named secret, identified by the name of a system property or environment variable. The SystemAndEnvSecretStore returns a secret that exactly matches the name.

The secrets provider builds the secret, checking that the secret's constraints are met, and returns a unique secret. If the secret's constraints aren't met, the secrets provider cannot build the secret and the secret query fails.

Learn how PingGateway manages secrets in [About secrets](#).

Usage

```
{
  "name": string,
  "type": "SystemAndEnvSecretStore",
  "config": {
    "format": SecretPropertyFormat reference,
    "mappings": [ object, ... ],
    "leaseExpiry": configuration expression<duration>
  }
}
```

Properties

format: *SecretPropertyFormat [reference](#), optional*

Format in which the secret is stored. Use one of the following values or define a format:

- **BASE64** : Base64-encoded

The original secret prior to base64-encoding must use UTF-8 encoding.

- **PLAIN** : Plain text

The text must use UTF-8 encoding.

Default: **BASE64**

"mappings": *array of [objects](#), optional*

One or more mappings to define a secret:

secretId: *configuration expression<[secret-id](#)>, required*

The ID of the secret used in your configuration.

format: *SecretPropertyFormat* [reference](#), *required*

The format and algorithm of the secret. Use [SecretKeyPropertyFormat](#) or [PemPropertyFormat](#).

"leaseExpiry": *configuration expression*[<duration>](#), *optional*

The amount of time that secrets produced by this store can be cached before they must be refreshed.

If the duration is `zero` or `unlimited`, PingGateway issues a warning, and uses the default value.

Default: 5 minutes

Log level

To facilitate debugging secrets for the SystemAndEnvSecretStore, in `logback.xml` add a logger defined by the fully qualified package name of the property resolver. The following line in `logback.xml` sets the log level to `ALL`:

```
<logger name="org.forgerock.secrets.propertyresolver" level="ALL" />
```

Example

For an example of how to use a SystemAndEnvSecretStore to manage a password, refer to [Using the default PingAM journey](#).

More information

Secrets

[org.forgerock.openig.secrets.SystemAndEnvSecretStoreHeaplet](#) [↗](#)

TrustManager (deprecated)



Important

This object is deprecated. Use [SecretsTrustManager](#) instead.

The configuration of a Java Secure Socket Extension [TrustManager](#) [↗](#) to manage trust material (typically X.509 public key certificates) for PingGateway. The configuration references the keystore that holds the trust material.

When PingGateway acts as a client, it uses a trust manager to verify that the server is trusted. When PingGateway acts as a server, it uses a trust manager to verify that the client is trusted.

Usage

```
{
  "name": string,
  "type": "TrustManager",
  "config": {
    "keystore": KeyStore reference,
    "alg": configuration expression<string>
  }
}
```

Properties

"keystore": *KeyStore reference, required*

The [KeyStore \(deprecated\)](#) object that references the store for key certificates. When `keystore` is used in a KeyManager, it queries for private keys; when `keystore` is used in a TrustManager, it queries for certificates.

Provide either the name of the keystore object defined in the heap or an inline keystore configuration object.

"alg": *configuration expression<string>, optional*

The certificate algorithm to use.

Default: the default for the platform, such as `SunX509`.

Example

The following example configures a trust manager that depends on a KeyStore configuration. This configuration uses the default certificate algorithm:

```
{
  "name": "MyTrustManager",
  "type": "TrustManager",
  "config": {
    "keystore": {
      "type": "KeyStore",
      "config": {
        "url": "file://${env['HOME']}/keystore.p12",
        "passwordSecretId": "${system['keypass']}",
        "secretsProvider": "SystemAndEnvSecretStore"
      }
    }
  }
}
```

More information

[org.forgerock.openig.security.TrustManagerHeaplet](https://forgerock.org/openig/security/TrustManagerHeaplet)

[JSSE reference guide](#), [KeyManager](#), [MiscellaneousConfigurationObjects.adoc#KeyStore.adoc](#)

PingGateway supported standards

PingGateway implements the following RFCs, Internet-Drafts, and standards:

[OAuth 2.0](#)

[RFC 6749: The OAuth 2.0 Authorization Framework](#)

[RFC 6750: The OAuth 2.0 Authorization Framework: Bearer Token Usage](#)

[RFC 7515: JSON Web Signature \(JWS\)](#)

[RFC 7516: JSON Web Encryption \(JWE\)](#)

[RFC 7517: JSON Web Key \(JWK\)](#)

[RFC 7518: JSON Web Algorithms \(JWA\)](#)

[RFC 7519: JSON Web Token \(JWT\)](#)

[RFC 7523: JSON Web Token \(JWT\) Profile for OAuth 2.0 Client Authentication and Authorization Grants](#)

[RFC 7591: OAuth 2.0 Dynamic Client Registration Protocol](#)

[RFC 7636: Proof Key for Code Exchange by OAuth Public Clients](#) (PKCE)

[RFC 7662: OAuth 2.0 Token Introspection](#)

[RFC 7800: Proof-of-Possession Key Semantics for JSON Web Tokens \(JWTs\)](#)

[RFC 8705: OAuth 2.0 Mutual-TLS Client Authentication and Certificate-Bound Access Tokens](#)

[OpenID Connect 1.0](#)

PingGateway can be configured to play the role of OpenID Connect relying party. The OpenID Connect specifications depend on OAuth 2.0, JSON Web Token, Simple Web Discovery and related specifications. The following specifications make up OpenID Connect 1.0.

- [OpenID Connect Core 1.0](#) defines core OpenID Connect 1.0 features.

Note

In section 5.6 of the specification, PingGateway supports *Normal Claims*. The optional *Aggregated Claims* and *Distributed Claims* representations aren't supported by PingGateway.

- [OpenID Connect Discovery 1.0](#) defines how clients can dynamically discover information about OpenID Connect providers.
- [OpenID Connect Dynamic Client Registration 1.0](#) defines how clients can dynamically register with OpenID Connect providers.
- [OAuth 2.0 Multiple Response Type Encoding Practices](#) defines additional OAuth 2.0 response types used in OpenID Connect.

FAPI

[Financial-grade API Security Profile 1.0 - Part 1: Baseline](#)

[Financial-grade API Security Profile 1.0 - Part 2: Advanced](#)

User-Managed Access (UMA) 2.0

[User-Managed Access \(UMA\) 2.0 Grant for OAuth 2.0 Authorization](#)

[Federated Authorization for User-Managed Access \(UMA\) 2.0](#)

Representational State Transfer (REST)

Style of software architecture for web-based, distributed systems. PingGateway's APIs are RESTful APIs.

Security Assertion Markup Language (SAML)

Standard, XML-based framework for implementing a SAML service provider. PingGateway supports multiple versions of SAML including 2.0, 1.1, and 1.0.

Specifications are available from the [OASIS standards page](#).

Other Standards

[RFC 4627: The application/json Media Type for JavaScript Object Notation \(JSON\)](#), JSON text is encoded with Unicode; PingGateway reads and stores JSON as Unicode.

[RFC 2616: Hypertext Transfer Protocol — HTTP/1.1](#).

[RFC 2617: HTTP Authentication: Basic and Digest Access Authentication](#), supported as an authentication module.

[RFC 5280: Internet X.509 Public Key Infrastructure Certificate](#), supported for certificate-based authentication.

[RFC 5785: Defining Well-Known Uniform Resource Identifiers \(URIs\)](#).

[RFC 6265: HTTP State Management Mechanism](#) regarding HTTP Cookies and `Set-Cookie` header fields.

Internationalization and PingGateway

PingGateway supports internationalization (i18n) to facilitate localization for target audiences that vary in culture, region, or language.

Information type	Character set/encoding
HTTP header names and values	US-ASCII
HTTP trailer names and values	US-ASCII

Information type	Character set/encoding
Response entities for StaticResponseHandler	The Content-Type header must be set. For text content, the character set must also be specified; for example: • Content-Type: <code>text/html; charset=utf-8</code> • Content-Type: <code>text/plain; charset=utf-8</code> The entity must conform to the content type.
Text in request and response entities for CaptureDecorator	If the Content-Type header is set for the request or response, the decorator uses it to decode the text in request or response messages, and then writes them to the logs. If the Content-Type header is not set, the decorator doesn't write the request or response messages to the logs.
Logs	The system default character set where PingGateway is running. To use a different character set, configure <code>logback.xml</code> as described in Change the character set and format of log messages.
PingGateway configuration files	UTF-8
Hostnames	US-ASCII Non US-ASCII characters must be escaped with Punycode encoding.
URIs	US-ASCII Non US-ASCII and reserved characters must be escaped with percent-encoding.

About Common REST

Common REST is a common REST API framework. It provides Ping Identity Platform software common ways to access web resources and collections of resources. Adapt the examples in this section to your resources and deployment.

Note

This page describes the full Common REST framework. Some platform component products do not implement all Common REST behaviors exactly as described. For details, refer to the product-specific examples and reference information.

Common REST resources

Servers generally return JSON-format resources, though resource formats can depend on the implementation.

Resources in collections can be found by their unique identifiers (IDs). IDs are exposed in the resource URIs. For example, if a server has a user collection under `/users`, then you can access a user at `/users/user-id`. The ID is also the value of the `_id` field of the resource.

Resources are versioned using revision numbers. A revision is specified in the resource's `_rev` field. Revisions make it possible to figure out whether to apply changes without resource locking and without distributed transactions.

Common REST verbs

The Common REST APIs use the following verbs, sometimes referred to collectively as **CRUDPAQ**. For details and HTTP-based examples of each, follow the links to the sections for each verb.

Create

Add a new resource.

This verb maps to HTTP PUT or HTTP POST.

For details, see [Create](#).

Read

Retrieve a single resource.

This verb maps to HTTP GET.

For details, see [Read](#).

Update

Replace an existing resource.

This verb maps to HTTP PUT.

For details, see [Update](#).

Delete

Remove an existing resource.

This verb maps to HTTP DELETE.

For details, see [Delete](#).

Patch

Modify part of an existing resource.

This verb maps to HTTP PATCH.

For details, see [Patch](#).

Action

Perform a predefined action.

This verb maps to HTTP POST.

For details, see [Action](#).

Query

Search a collection of resources.

This verb maps to HTTP GET.

For details, see [Query](#).

Common REST parameters

Common REST reserved query string parameter names start with an underscore, `_`. Reserved query string parameters include, but are not limited to, the following names:

- `_action`
- `_api`
- `_crestapi`
- `_fields`
- `_mimeType`
- `_pageSize`
- `_pagedResultsCookie`
- `_pagedResultsOffset`
- `_prettyPrint`
- `_queryExpression`
- `_queryFilter`
- `_queryId`
- `_sortKeys`
- `_totalPagedResultsPolicy`

Note

Some parameter values are not safe for URLs, so URL-encode parameter values as necessary.

Continue reading for details about how to use each parameter.

Common REST extension points

The *action* verb is the main vehicle for extensions. For example, to create a new user with HTTP POST rather than HTTP PUT, you might use `/users?_action=create`. A server can define additional actions. For example, `/tasks/1?_action=cancel`.

A server can define *stored queries* to call by ID. For example, `/groups?_queryId=hasDeletedMembers`. Stored queries can call for additional parameters. The parameters are also passed in the query string. Which parameters are valid depends on the stored query.

Common REST headers

Accept-API-Version

Common REST APIs use the `Accept-API-Version` header to specify protocol and resource versions:

`Accept-API-Version: protocol=version,resource=version`

protocol

The version reflects changes in the Common REST protocol, such as common method parameters and headers specified by the protocol itself, or the input or response conventions it prescribes.

For example, protocol version 2.2 introduced the `_countOnly` parameter.

resource

The version reflects changes in the resource implementation, including JSON representation of resources, input parameters required, and incompatible behavior changes.

For example, the version changes when `errorMessage` changes to `message` in a JSON response.

Whether this header is required depends on the product and API you make the request to.

X-ForgeRock-TransactionId

Common REST APIs use the `X-ForgeRock-TransactionId` header to track related requests through Ping Identity Platform.

`X-ForgeRock-TransactionId: transactionID`

The *transactionID* consists of a unique identifier for the transaction optionally followed by a sequence number for the individual request.

This header is optional. In self-managed deployments, you configure products to trust transaction IDs and let them propagate for audit purposes.

Common REST API documentation

Common REST APIs often depend at least in part on runtime configuration. Many Common REST endpoints therefore serve *API descriptors* at runtime. An API descriptor documents the actual API as it is configured.

Use the following query string parameters to retrieve API descriptors:

_api

Serves an API descriptor that complies with the [OpenAPI specification](#).

This API descriptor represents the API accessible over HTTP. It is suitable for use with popular tools such as [Swagger UI](#).

_crestapi

Serves a native Common REST API descriptor.

This API descriptor provides a compact representation that is not dependent on the transport protocol. It requires a client that understands Common REST, as it omits many Common REST defaults.

 Note

Consider limiting access to API descriptors in production environments in order to avoid unnecessary traffic. To provide documentation in production environments, see [To publish OpenAPI documentation](#) instead.

To publish OpenAPI documentation

In production systems, developers expect stable, well-documented APIs. Rather than retrieving API descriptors at runtime through Common REST, prepare final versions, and publish them alongside the software in production.

Use the OpenAPI-compliant descriptors to provide API reference documentation for your developers:

1. Configure the software to produce production-ready APIs.

In other words, configure the software as for production so that the APIs match exactly.

2. Retrieve the OpenAPI-compliant descriptor.

The following command saves the descriptor to a file. :

```
$ curl -o <filename>.json <endpoint>?_api
```

 Note

The *endpoint* must be a valid endpoint. For example:

```
$ curl -o myapi.json https://am.example.com:8443/am/json/realms/root/authenticate?_api
```

3. If necessary, edit the descriptor.

For example, add security definitions to describe the API protection.

4. Publish the descriptor using a tool such as [Swagger UI](#).

Create

There are two ways to create a resource, HTTP POST or HTTP PUT.

To create a resource using POST, perform an HTTP POST with the query string parameter `_action=create`, and the JSON resource as a payload. Accept a JSON response. The server creates the identifier if not specified:

```
POST /users?_action=create HTTP/1.1
Host: example.com
Accept: application/json
Content-Length: ...
Content-Type: application/json
{ JSON resource }
```

To create a resource using PUT, perform an HTTP PUT including the case-sensitive identifier for the resource in the URL path, and the JSON resource as a payload. Use the `If-None-Match: *` header. Accept a JSON response:

```
PUT /users/some-id HTTP/1.1
Host: example.com
Accept: application/json
Content-Length: ...
Content-Type: application/json
If-None-Match: *
{ JSON resource }
```

The `_id` and content of the resource depend on the server implementation. The server is not required to use the `_id` that the client provides. The server response to the request indicates the resource location as the value of the `Location` header.

If you include the `If-None-Match` header, you must use `If-None-Match: *`. In this case, the request creates the object if it does not exist, and fails if the object does exist. If you include any value other `If-None-Match: *`, the server returns an HTTP 400 Bad Request error. For example, creating an object with `If-None-Match: revision` returns a bad request error.

If you do not include `If-None-Match: *`, the request creates the object if it does not exist, and *updates* the object if it does exist.

Parameters

`_fields=field[,field...]`

Return only the specified fields in the body of the response.

The `field` values are JSON pointers. For example if the resource is `{"parent":{"child":"value"}}`, `parent/child` refers to the `"child":"value"`.

If the `field` is left blank, the server returns all default values.

`_prettyPrint=true`

Format the body of the response.

Read

To retrieve a single resource, perform an HTTP GET on the resource by its case-sensitive identifier (`_id`), and accept a JSON response:

```
GET /users/some-id HTTP/1.1
Host: example.com
Accept: application/json
```

Parameters

`_fields=field[,field...]`

Return only the specified fields in the body of the response.

The `field` values are JSON pointers. For example if the resource is `{"parent":{"child":"value"}}`, `parent/child` refers to the `"child":"value"`.

If the `field` is left blank, the server returns all default values.

_mimeType=mime-type

Some resources have fields whose values are multi-media resources, such as a profile photo.

If the feature is enabled for the endpoint, you can read a single field that is a multi-media resource by specifying the *field* and *mime-type*.

In this case, the content type of the field value returned matches the *mime-type* that you specify, and the body of the response is the multi-media resource.

Do not use the `Accept` header in this case. For example, `Accept: image/png` does not work. Use the `_mimeType` query string parameter instead.

_prettyPrint=true

Format the body of the response.

Update

To update a resource, perform an HTTP PUT including the case-sensitive identifier (`_id`) as the final element of the path to the resource, and the JSON resource as the payload. Use the `If-Match: _rev` header to check that you are actually updating the version you modified. Use `If-Match: *` if the version does not matter. Accept a JSON response:

```
PUT /users/some-id HTTP/1.1
Host: example.com
Accept: application/json
Content-Length: ...
Content-Type: application/json
If-Match: _rev
{ JSON resource }
```

When updating a resource, include all the attributes to retain. Omitting an attribute in the resource amounts to deleting the attribute unless it is not under the control of your application. Attributes not under the control of your application include private and read-only attributes. In addition, virtual attributes and relationship references might not be under the control of your application.

Note

Product-specific implementations may differ. Not all products use the payload to replace the state of the resource in its entirety. For example, attributes that are omitted from the request payload to AM will not be deleted. Instead, you need to specify the attribute and set the value to an empty array to delete the attribute from the resource. For more information, see the product-specific examples and reference information.

Parameters

_fields=field[,field...]

Return only the specified fields in the body of the response.

The `field` values are JSON pointers. For example if the resource is `{"parent":{"child":"value"}}`, `parent/child` refers to the `"child":"value"`.

If the `field` is left blank, the server returns all default values.

_prettyPrint=true

Format the body of the response.

Delete

To delete a single resource, perform an HTTP DELETE by its case-sensitive identifier (`\_id`) and accept a JSON response:

```
DELETE /users/some-id HTTP/1.1
Host: example.com
Accept: application/json
```

Parameters

_fields=field[,field...]

Return only the specified fields in the body of the response.

The `field` values are JSON pointers. For example if the resource is `{"parent":{"child":"value"}}`, `parent/child` refers to the `"child":"value"`.

If the `field` is left blank, the server returns all default values.

_prettyPrint=true

Format the body of the response.

Patch

To patch a resource, send an HTTP PATCH request with the following parameters:

- `operation`
- `field`
- `value`
- `from` (optional with copy and move operations)

You can include these parameters in the payload for a PATCH request, or in a JSON PATCH file. If successful, you'll see a JSON response similar to the following:

```
PATCH /users/some-id HTTP/1.1
Host: example.com
Accept: application/json
Content-Length: ...
Content-Type: application/json
If-Match: _rev
{ JSON array of patch operations }
```

PATCH operations apply to three types of targets:

- **single-valued**, such as an object, string, boolean, or number.
- **list semantics array**, where the elements are ordered, and duplicates are allowed.
- **set semantics array**, where the elements are not ordered, and duplicates are not allowed.

Common REST PATCH supports multiple **operations** :

Patch operation: add

The **add** operation ensures that the target field contains the value provided, creating parent fields as necessary.

If the target field is single-valued, then the value you include in the PATCH replaces the value of the target. A single-valued field is an **object**, **string**, **boolean**, or **number**.

An **add** operation has different results on two standard types of arrays:

- **List semantic arrays**: you can run any of these **add** operations on that type of array:
 - If you **add** an array of values, the PATCH operation appends it to the existing list of values.
 - If you **add** a single value, specify an ordinal element in the target array, or use the **{-}** special index to add that value to the end of the list.
- **Set semantic arrays**: The value included in the patch is merged with the existing set of values. Any duplicates within the array are removed.

As an example, start with the following list semantic array resource:

```
{
  "fruits" : [ "orange", "apple" ]
}
```

The following add operation includes the pineapple to the end of the list of fruits, as indicated by the **-** at the end of the **fruits** array.

```
{
  "operation" : "add",
  "field" : "/fruits/-",
  "value" : "pineapple"
}
```

The following is the resulting resource:

```
{
  "fruits" : [ "orange", "apple", "pineapple" ]
}
```


You can add only one array element one at a time, as per the corresponding [JSON Patch specification](#). If you add an array of elements, for example:

```
{
  "operation" : "add",
  "field" : "/fruits/-",
  "value" : ["pineapple", "mango"]
}
```

The resulting resource would have the following invalid JSON structure:

```
{
  "fruits" : [ "orange", "apple", ["pineapple", "mango"]]
}
```

Patch operation: copy

The copy operation takes one or more existing values from the source field. It then adds those same values on the target field. Once the values are known, it is equivalent to performing an **add** operation on the target field.

The following **copy** operation takes the value from a field named **mail**, and then runs a **replace** operation on the target field, **another_mail**.

```
[
  {
    "operation": "copy",
    "from": "mail",
    "field": "another_mail"
  }
]
```

If the source and target field values are arrays, the result depends on whether the array has list semantics or set semantics, as described in [Patch operation: add](#).

Patch operation: increment

The **increment** operation changes the value or values of the target field by the amount you specify. The value that you include must be one number, and may be positive or negative. The value of the target field must accept numbers. The following **increment** operation adds **1000** to the target value of **/user/payment**.

```
[
  {
    "operation" : "increment",
    "field" : "/user/payment",
    "value" : "1000"
  }
]
```

Since the **value** of the **increment** is a single number, arrays do not apply.

Patch operation: move

The move operation removes existing values on the source field. It then adds those same values on the target field. This is equivalent to a **remove** operation on the source, followed by an **add** operation with the same values, on the target.

The following **move** operation is equivalent to a **remove** operation on the source field, **surname**, followed by a **replace** operation on the target field value, **lastName**. If the target field does not exist, it is created:

```
[
  {
    "operation": "move",
    "from": "surname",
    "field": "lastName"
  }
]
```

To apply a **move** operation on an array, you need a compatible single-value, list semantic array, or set semantic array on both the source and the target. For details, see the criteria described in [Patch operation: add](#).

Patch operation: remove

The **remove** operation ensures that the target field no longer contains the value provided. If the remove operation does not include a value, the operation removes the field. The following **remove** deletes the value of the **phoneNumber**, along with the field.

```
[
  {
    "operation" : "remove",
    "field" : "phoneNumber"
  }
]
```

If the object has more than one **phoneNumber**, those values are stored as an array.

A **remove** operation has different results on two standard types of arrays:

- **List semantic arrays:** A **remove** operation deletes the specified element in the array. For example, the following operation removes the first phone number, based on its array index (zero-based):

```
[
  {
    "operation" : "remove",
    "field" : "/phoneNumber/0"
  }
]
```

- **Set semantic arrays:** The list of values included in a patch are removed from the existing array.

Patch operation: replace

The **replace** operation removes any existing value(s) of the targeted field, and replaces them with the provided value(s). It is essentially equivalent to a **remove** followed by a **add** operation. If the arrays are used, the criteria is based on [Patch operation: add](#). However, indexed updates are not allowed, even when the target is an array.

The following **replace** operation removes the existing **telephoneNumber** value for the user, and then adds the new value of **+1 408 555 9999**.

```
[
  {
    "operation" : "replace",
    "field" : "/telephoneNumber",
    "value" : "+1 408 555 9999"
  }
]
```

A PATCH replace operation on a list semantic array works as a PATCH remove operation. The following example demonstrates how the effect of both operations. Start with the following resource:

```
{
  "fruits" : [ "apple", "orange", "kiwi", "lime" ],
}
```

Apply the following operations on that resource:

```
[
  {
    "operation" : "remove",
    "field" : "/fruits/0",
    "value" : ""
  },
  {
    "operation" : "replace",
    "field" : "/fruits/1",
    "value" : "pineapple"
  }
]
```

The PATCH operations are applied sequentially. The **remove** operation removes the first member of that resource, based on its array index, (**fruits/0**), with the following result:

```
[
  {
    "fruits" : [ "orange", "kiwi", "lime" ],
  }
]
```

The second PATCH operation, a `replace`, is applied on the second member (`fruits/1`) of the intermediate resource, with the following result:

```
[
  {
    "fruits" : [ "orange", "pineapple", "lime" ],
  }
]
```

Patch operation: transform

The `transform` operation changes the value of a field based on a script, or some other data transformation command. The following `transform` operation takes the value from the field named `/objects`, and applies the `something.js` script as shown:

```
[
  {
    "operation" : "transform",
    "field" : "/objects",
    "value" : {
      "script" : {
        "type" : "text/javascript",
        "file" : "something.js"
      }
    }
  }
]
```

Patch operation limitations

Some HTTP client libraries do not support the HTTP PATCH operation. Make sure that the library you use supports HTTP PATCH before using this REST operation.

For example, the Java Development Kit HTTP client does not support PATCH as a valid HTTP method. Instead, the method `URLConnection.setRequestMethod("PATCH")` throws `ProtocolException`.

Parameters

`_fields=field[,field...]`

Return only the specified fields in the body of the response.

The `field` values are JSON pointers. For example if the resource is `{"parent":{"child":"value"}}`, `parent/child` refers to the `"child":"value"`.

If the `field` is left blank, the server returns all default values.

`_prettyPrint=true`

Format the body of the response.

Action

Actions are a means of extending Common REST APIs and are defined by the resource provider, so the actions you can use depend on the implementation.

The standard action indicated by `_action=create` is described in [Create](#).

Parameters

In addition to these parameters, specific action implementations have their own parameters:

`_fields=field[,field...]`

Return only the specified fields in the body of the response.

The `field` values are JSON pointers. For example if the resource is `{"parent":{"child":"value"}}`, `parent/child` refers to the `"child":"value"`.

If the `field` is left blank, the server returns all default values.

`_prettyPrint=true`

Format the body of the response.

Query

To query a resource collection (or resource container), perform an HTTP GET, and accept a JSON response, including either a `_queryExpression`, `_queryFilter`, or `_queryId` parameter. The parameters cannot be used together:

```
GET /users?_queryFilter=true HTTP/1.1
Host: example.com
Accept: application/json
```

The server returns the result as a JSON object including a `"results"` array, and other fields that depend on the parameters.

Parameters

`_countOnly=true`

Return a count of query results without returning the resources.

This parameter requires protocol version 2.2 or later.

`_fields=field[,field...]`

Return only the specified fields in the body of the response.

The `field` values are JSON pointers. For example if the resource is `{"parent":{"child":"value"}}`, `parent/child` refers to the `"child":"value"`.

If the `field` is left blank, the server returns all default values.

_queryFilter=filter-expression

Query filters request that the server return entries that match the filter expression. You must URL-escape the filter expression.

The string representation is summarized as follows. Continue reading for additional explanation:

```
Expr          = OrExpr
OrExpr        = AndExpr ( 'or' AndExpr ) *
AndExpr       = NotExpr ( 'and' NotExpr ) *
NotExpr       = '!' PrimaryExpr | PrimaryExpr
PrimaryExpr   = '(' Expr ')' | ComparisonExpr | PresenceExpr | LiteralExpr
ComparisonExpr = Pointer OpName JsonValue
PresenceExpr  = Pointer 'pr'
LiteralExpr   = 'true' | 'false'
Pointer       = JSON pointer
OpName        = 'eq' | # equal to
               'co' | # contains
               'sw' | # starts with
               'lt' | # less than
               'le' | # less than or equal to
               'gt' | # greater than
               'ge' | # greater than or equal to
               STRING # extended operator
JsonValue     = NUMBER | BOOLEAN | ''' UTF8STRING '''
STRING        = ASCII string not containing white-space
UTF8STRING    = UTF-8 string possibly containing white-space
```

JsonValue components of filter expressions follow [RFC 7159: The JavaScript Object Notation \(JSON\) Data Interchange Format](#). In particular, as described in section 7 of the RFC, the escape character in strings is the backslash character. For example, to match the identifier `test\`, use `_id eq 'test\\'`. In the JSON resource, the `\` is escaped the same way: `"_id":"test\\"`.

When using a query filter in a URL, the filter expression is part of a query string parameter. A query string parameter must be URL encoded, as described in [RFC 3986: Uniform Resource Identifier \(URI\): Generic Syntax](#). For example, white space, double quotes (`"`), parentheses, and exclamation characters must be URL encoded in HTTP query strings. The following rules apply to URL query components:

```
query         = *( pchar / "/" / "?" )
pchar         = unreserved / pct-encoded / sub-delims / ":" / "@"
unreserved    = ALPHA / DIGIT / "-" / "." / "_" / "~"
pct-encoded   = "%" HEXDIG HEXDIG
sub-delims    = "!" / "$" / "&" / "'" / "(" / ")"
               / "*" / "+" / "," / ";" / "="
```

`ALPHA`, `DIGIT`, and `HEXDIG` are core rules of [RFC 5234: Augmented BNF for Syntax Specifications](#):

```
ALPHA         = %x41-5A / %x61-7A ; A-Z / a-z
DIGIT         = %x30-39 ; 0-9
HEXDIG        = DIGIT / "A" / "B" / "C" / "D" / "E" / "F"
```

As a result, a backslash escape character in a *JsonValue* component is percent-encoded in the URL query string parameter as `%5C`. To encode the query filter expression `_id eq 'test\\'`, use `_id+eq+'test%5C%5C'`, for example.

A simple filter expression can represent a comparison, presence, or a literal value.

For comparison expressions, use `json-pointer comparator json-value`, where the *comparator* is one of the following:

```
eq (equals)
co (contains)
sw (starts with)
lt (less than)
le (less than or equal to)
gt (greater than)
ge (greater than or equal to)
```

For presence, use `json-pointer pr` to match resources where the JSON pointer is present, and the value it points to is not `null`.

Literal values include `true` (match anything) and `false` (match nothing).

Complex expressions employ `and`, `or`, and `!` (not), with parentheses, `(expression)`, to group expressions.

`_queryId=identifier`

Specify a query by its identifier.

Specific queries can take their own query string parameter arguments, which depend on the implementation.

`_pagedResultsCookie=string`

The string is an opaque cookie used by the server to keep track of the position in the search results. The server returns the cookie in the JSON response as the value of `pagedResultsCookie`.

In the request `_pageSize` must also be set and non-zero. You receive the cookie value from the provider on the first request, and then supply the cookie value in subsequent requests until the server returns a `null` cookie, meaning the final page of results has been returned.

The `_pagedResultsCookie` parameter is supported when used with the `_queryFilter` parameter. The `_pagedResultsCookie` parameter is not guaranteed to work with the `_queryExpression` or `_queryId` parameters.

The `_pagedResultsCookie` and `_pagedResultsOffset` parameters are mutually exclusive, and not to be used together.

`_pagedResultsOffset=integer`

When `_pageSize` is non-zero, use this as an index in the result set indicating the first page to return.

The `_pagedResultsCookie` and `_pagedResultsOffset` parameters are mutually exclusive, and not to be used together.

`_pageSize=integer`

Return query results in pages of this size. After the initial request, use `_pagedResultsCookie` or `_pageResultsOffset` to page through the results.

`_prettyPrint=true`

Format the body of the response.

`_totalPagedResultsPolicy=string`

When a `_pageSize` is specified, and non-zero, the server calculates the `"totalPagedResults"`, in accordance with the `totalPagedResultsPolicy`, and provides the value as part of the response.

The `"totalPagedResults"` is either an estimate of the total number of paged results (`_totalPagedResultsPolicy=ESTIMATE`), or the exact total result count (`_totalPagedResultsPolicy=EXACT`). If no count policy is specified in the query, or if `_totalPagedResultsPolicy=NONE`, result counting is disabled, and the server returns value of -1 for `"totalPagedResults"`.

`_sortKeys=(|-)__field__[, (|-)field...]`

Sort the resources returned based on the specified field(s), either in `+` (ascending, default) order, or in `-` (descending) order.

Because ascending order is the default, including the ``` character in the query is unnecessary. If you do include the ``` character, it must be URL-encoded as `%2B`, for example:

```
http://localhost:8080/api/users?_queryFilter=true&_sortKeys=%2Bname/givenName
```

The `_sortKeys` parameter is not supported for predefined queries (`_queryId`).

HTTP status codes

When working with a Common REST API over HTTP, client applications should expect at least these HTTP status codes. Not all servers necessarily return all status codes identified here:

200 OK

The request was successful and a resource returned, depending on the request.

201 Created

The request succeeded and the resource was created.

204 No Content

The action request succeeded, and there was no content to return.

304 Not Modified

The read request included an `If-None-Match` header, and the value of the header matched the revision value of the resource.

400 Bad Request

The request was malformed.

401 Unauthorized

The request requires user authentication.

403 Forbidden

Access was forbidden during an operation on a resource.

404 Not Found

The specified resource could not be found, perhaps because it does not exist.

405 Method Not Allowed

The HTTP method is not allowed for the requested resource.

406 Not Acceptable

The request contains parameters that are not acceptable, such as a resource or protocol version that is not available.

409 Conflict

The request would have resulted in a conflict with the current state of the resource.

410 Gone

The requested resource is no longer available, and will not become available again. This can happen when resources expire for example.

412 Precondition Failed

The resource's current version does not match the version provided.

415 Unsupported Media Type

The request is in a format not supported by the requested resource for the requested method.

428 Precondition Required

The resource requires a version, but no version was supplied in the request.

500 Internal Server Error

The server encountered an unexpected condition that prevented it from fulfilling the request.

501 Not Implemented

The resource does not support the functionality required to fulfill the request.

503 Service Unavailable

The requested resource was temporarily unavailable. The service may have been disabled, for example.